TP 77-7

Evaluation of the Computation of Wave Direction with Three-Gage Arrays

by
Dinorah C. Esteva

TECHNICAL PAPER NO. 77-7
JULY 1977

Approved for public release;
distribution unlimited

U.S. ARMY, CORPS OF ENGINEERS
COASTAL ENGINEERING
RESEARCH CENTER

Kingman Building
Fort Belvoir, Va. 22060

GB
450
T4
no. 77-7

Reprint or republication of any of this material shall give appropriate credit to the U.S. Army Coastal Engineering Research Center.

Limited free distribution within the United States of single copies of this publication has been made by this Center. Additional copies are available from:

*National Technical Information Service
ATTN: Operations Division
5285 Port Royal Road
Springfield, Virginia 22151*

Contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM						
1. REPORT NUMBER TP 77-7	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER						
4. TITLE (and Subtitle) EVALUATION OF THE COMPUTATION OF WAVE DIRECTION WITH THREE-GAGE ARRAYS		5. TYPE OF REPORT & PERIOD COVERED Technical Paper						
		6. PERFORMING ORG. REPORT NUMBER						
7. AUTHOR(s) Dinorah C. Esteva		8. CONTRACT OR GRANT NUMBER(s)						
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of the Army Coastal Engineering Research Center (CERRE-CO) Kingman Building, Fort Belvoir, Virginia 22060		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS A31462						
11. CONTROLLING OFFICE NAME AND ADDRESS Department of the Army Coastal Engineering Research Center Kingman Building, Fort Belvoir, Virginia 22060		12. REPORT DATE July 1977						
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 123						
		15. SECURITY CLASS. (of this report) UNCLASSIFIED						
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE						
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release, distribution unlimited.								
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)								
18. SUPPLEMENTARY NOTES								
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)								
<table border="0"> <tr> <td>Pt. Mugu, California</td> <td>Wave measurement</td> </tr> <tr> <td>Three-gage arrays</td> <td>Wave train</td> </tr> <tr> <td>Wave direction</td> <td>Waves</td> </tr> </table>			Pt. Mugu, California	Wave measurement	Three-gage arrays	Wave train	Wave direction	Waves
Pt. Mugu, California	Wave measurement							
Three-gage arrays	Wave train							
Wave direction	Waves							
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagation. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is shown by calculations based on simulated narrow-banded wave trains. Directional results from the field study indicate (continued)								

the maximum accuracy of wave direction determinations with a three-gage array is on the order of $\pm 20^\circ$. This level of accuracy may be expected only for narrow-banded wave trains with periods longer than a lower limit determined at each location by array dimensions and water depth. The field study also indicates narrow-banded wave trains are frequent at this coastal location.

PREFACE

This report is published to provide guidance to coastal engineers in planning wave data collection in coastal waters for climatology purposes, including wave direction. The popularity of three-gage arrays for proposed wave direction measuring systems makes it necessary to evaluate the capabilities and the limitations of these arrays. The availability of the CERC five-gage array at Pt. Mugu, California, provided a unique opportunity for evaluating the performance of wave recording systems and the directional capabilities of three-gage arrays. The work was carried out under the wave measurement and analyses program of the U.S. Army Coastal Engineering Research Center (CERC).

This report was prepared by Dr. Dinorah C. Esteva under the supervision of Dr. D. Lee Harris, Chief, Coastal Oceanography Branch, Research Division. The author acknowledges the valuable insight and comments provided by Dr. D. Lee Harris and Mr. R. P. Savage, Chief, Research Division, CERC.

Comments on this publication are invited.

Approved for publication in accordance with Public Law 166, 79th Congress, approved 31 July 1945, as supplemented by Public Law 172, 88th Congress, approved 7 November 1963.

JOHN H. COUSINS
Colonel, Corps of Engineers
Commander and Director

CONTENTS

	Page
CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI)	6
I INTRODUCTION.	7
1. The System	10
2. Data Collection.	14
II FIELD DATA ANALYSIS	14
1. Computation of Wave Direction.	18
2. Simulated Data Analysis.	20
3. Identification of Wave Trains from the High-Resolution Spectrum	28
4. Spectra and Direction of Wave Propagation for Field Data.	28
5. Conclusions.	31
LITERATURE CITED.	32
APPENDIX	
A DERIVATION OF THE EXPRESSION FOR WAVE DIRECTION	35
B COMPUTER OUTPUT FOR CROSS-SPECTRA COMPUTATIONS.	36
C FOURIER COEFFICIENTS FOR A MIXTURE OF THREE SINUSOIDS	48
D SPECTRA PLOTS AND COMPUTER OUTPUT FOR SIMULATED OBSERVATIONS.	54
E HIGH-RESOLUTION SPECTRA FOR FIELD WAVE DATA	79
TABLES	
1 Percent of observations where the largest departure of the standard deviations from the mean in the observations was as indicated (871 observations in 1970).	16
2 Directional results with 0.01 hertz resolution for two observations	21
3 Characteristics of simulated wave trains.	24
4 Computational results at closest spectral frequencies for simulated wave trains.	26
5 Directional results of high-resolution spectral computations for 8-second wave.	27
6 Average spread in computed directions for 280 wave trains identified in the high-resolution spectra of 44 field wave observations	30

CONTENTS--Continued

FIGURES

	Page
1 Aerial photo of wave field at Pt. Saint George, California. . .	8
2 Radar scan of wave field at Nauset, Massachusetts	9
3 Five-gage array dimensions and geometry	11
4 Location of the five-gage array	12
5 Schematics of transducer assembly	13
6 Tripod mounting for pressure sensors.	15
7 Summarized pressure and surface spectra	17
8 Long-crested wave propagating in direction α_m	19

CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI)
UNITS OF MEASUREMENT

U.S. customary units of measurement used in this report can be converted to metric (SI) units as follows:

Multiply	by	To obtain
inches	25.4	millimeters
	2.54	centimeters
square inches	6.452	square centimeters
cubic inches	16.39	cubic centimeters
feet	30.39	centimeters
	0.3048	meters
square feet	0.0929	square meters
cubic feet	0.0283	cubic meters
yards	0.9144	meters
square yards	0.836	square meters
cubic yards	0.7646	cubic meters
miles	1.6093	kilometers
square miles	259.0	hectares
knots	1.8532	kilometers per hour
acres	0.4047	hectares
foot-pounds	1.3558	newton meters
millibars	1.0197×10^{-3}	kilograms per square centimeter
ounces	28.35	grams
pounds	453.6	grams
	0.4536	kilograms
ton, long	1.0160	metric tons
ton, short	0.9072	metric tons
degrees (angle)	0.1745	radians
Fahrenheit degrees	5/9	Celsius degrees or Kelvins ¹

¹To obtain Celsius (C) temperature readings from Fahrenheit (F) readings, use formula: $C = (5/9) (F - 32)$.

To obtain Kelvin (K) readings, use formula: $K = (5/9) (F - 32) + 273.15$.

EVALUATION OF THE COMPUTATION OF WAVE DIRECTION WITH THREE-GAGE ARRAYS

by
Dinorah C. Esteve

I. INTRODUCTION

Wave direction is an important parameter in the solution of many coastal engineering problems. A knowledge of wave direction is essential for (a) estimating the direction and magnitude of sediment transport by waves, (b) using refraction calculations to infer wave conditions at one site from measurements made elsewhere, and (c) verifying theories of wave generation.

Visual observations of wave directions have been collected by ship-board observers for over a century. About 20 years ago the Beach Erosion Board (BEB), predecessor to the Coastal Engineering Research Center (CERC), engaged the assistance of U.S. Coast Guard installations in the collection of visual observations of breaker direction from shore. However, objective determinations of wave direction are desirable without being restricted to location, time of day, or visibility condition. The capability to do so involves the use of wave measuring instruments. Panicker (1971, 1974) presents extensive reviews of reports dealing with the determination of wave direction from instrument records with particular emphasis on those involving sea-surface elevation or pressure records.

In March 1970, CERC installed an array of wave gages at Pt. Mugu, California. Records from the array were to be used to compare redundant values of wave direction and to estimate the level of accuracy of the computations. The available procedures for determining wave direction from an array involved assumptions that had not been thoroughly established. Thus, the records from the array would also be used in a systematic examination of these assumptions, and of the reliability of wave gages.

This study discusses the array performance and the information gained about wave direction. Redundant values of directions were obtained from the 10 three-gage arrays possible with five gages. The mathematical model used assumes that the sea surface is the result of the superposition of a small number of narrow-banded wave trains consisting of long-crested waves traveling in well-defined directions. It was also assumed that only one wave train is present with a particular period. The first assumption is supported by the energy spectra computed at CERC (Thompson, 1974), by aerial photos of the sea surface (Fig. 1), and by radar images of the wave field (Fig. 2). Many published reports include photos similar to that in Figure 1; e.g., McClenan and Harris (1975). Fujinawa (1974, 1975) conjectured that narrow directional spread might be responsible for the incomplete recovery of the true directional spectrum from field records in his computations using high directional resolution.

Average values of wave direction for bands of constant frequency width were computed from cross-spectra between gage pairs. Direction

Figure 1. Aerial photo of wave field at Pt. Saint George, California.

Figure 2. Radar scan of wave field at Nauset, Massachusetts.

estimates for all bands 0.01 hertz wide between approximately 30 and 3 seconds were obtained for the 10 arrays. The results displayed discrepancies of the order of 20° for those bands with central periods above 10 seconds and of 180° for those with shorter central periods. It had been expected that the array would yield direction to better than 20° and for periods between 25 and 7 seconds.

To isolate problems associated with the calculations, the propagation of narrow-banded wave trains across the array was simulated in a computer. The computational model was applied to the simulated observations using the maximum frequency resolution available from spectral computations based on 20-minute records. It was found that the directional results obtained with this model are highly dependent on the spectral width, both in frequency and direction, of the wave train involved and on the relationship between wavelength at the site and gage separations. The assigned directions were recovered within 1° for 16-second waves when the frequencies of the spectral components in the wave train differed by 0.003 hertz or more, and the directions were spread within a 5° arc. This frequency separation results in a minimum difference in periods of 0.7 second for waves with periods near 16 seconds.

Application of the same analyses to field wave pressure records with standard deviations above 0.61 meter (2 feet) resulted in an average discrepancy of 20° among computed directions for narrow-banded wave trains with periods longer than 10 seconds. Larger discrepancies resulted for shorter periods. Thus, accuracies no better than 20° can be expected for wave directions resulting from three-gage arrays.

1. The System.

A minimum of three gages is required for a unique determination of wave direction by most proposed models. Since these models make a few assumptions about the nature of ocean waves which have not been established, some redundancy was thought to be necessary which would require a minimum of four gages. However, it was agreed that a five-gage array would increase the probability of redundancy in the ocean environment. An array was designed at CERC by Leon E. Borgman, statistician-engineer, while on sabbatical leave from the University of California, Berkeley, when the experiment was being planned. He investigated the directional resolving power of several array geometries and concluded that the pattern shown in Figure 3 would be the most suitable for the conditions to be expected at Pt. Mugu (Borgman and Panicker, 1970).

The array was installed off Pt. Mugu, approximately 80.47 kilometers (50 miles) northwest of Los Angeles (Fig. 4), in about 9.14 meters (30 feet) of water, 0.76 meter (2.5 feet) from the bottom. The gages in the array are pressure transducers developed mostly at CERC (Williams, 1969). The heart of the system is a Fairchild pressure transducer which is potted inside a 2-inch Plexiglas tube (Fig. 5) (Peacock, 1974). A plastic tube filled with silicone oil transmits the pressure from the seawater to the pressure transducer. The silicone oil is separated from seawater by

Figure 3. Five-gage array dimensions and geometry.

Figure 4. Location of the five-gage array (from Panicker, 1971).

Figure 5. Schematics of transducer assembly (Peacock, 1974).

rubber diaphragms. A Teflon scouring pad dipped in antifouling paint separates the rubber diaphragm from the end of the package which admits the seawater pressure. The instrument is mounted vertically on a tripod (Fig. 6). The signals from the pressure transducers are brought by cables to a recording and transmitting station onshore.

2. Data Collection.

The array went into operation on 27 March 1970. The water pressure at the five gages was registered continuously at a rate of four times a second on digital magnetic tape. Difficulties experienced during the first year with individual sensors were mostly of short duration and were presumed to be due to biological activity. However, major difficulties were experienced with the recording system, and on 16 March 1971 the recorder was disconnected at Pt. Mugu and transferred to the CERC laboratory, then located in Washington, D.C. Recording from all five gages was reinitiated at CERC on 9 April 1971. Records were obtained continuously until 3 January 1972 when the recorder failed. During this period much of the data were useless because of an unacceptable level of high-frequency noise. The source of the noise was difficult to locate and was not eliminated from the signal until shortly before the failure of the recorder in January. Since 2 February 1972, records from three of the five gages at Pt. Mugu have been included in the time-shared recording of waves from east and gulf coast wave stations (Peacock, 1974). In 1972, data were recorded for 20 minutes out of each hour; since February 1973, data have been recorded for 20 minutes out of each 2-hour interval.

II. FIELD DATA ANALYSIS

The five gages in the array provided uninterrupted data for most of the first year of operation. Eight daily observations, each consisting of simultaneous 20-minute records from the five gages, were processed from these data. The observations had starting times within 1.5 hours of the weather synoptic times (0100, 0400, 0700, 1000, 1300, 1600, and 1900 hours P.s.t.). The potential energy in the wave field is proportional to the variance of the time history of sea-surface elevation at a fixed location (Kinsman, 1965). For most conditions, the standard deviation of the surface displacement is one-fourth of the significant wave height. The standard deviation of the pressure at a fixed depth is roughly proportional to the wave height and may also serve as a measure of the wave height.

The standard deviation of the recorded pressure was computed from the records of each of the five gages for eight records each day. The standard deviation of the record from each gage was compared with the average of the five gages. If the standard deviation from any gage differed from the average by more than 20 percent, the record from that gage was deleted and the average recomputed from the remaining gages. A comparison of the individual standard deviations from the mean for that time period is shown in Table 1.

Figure 6. Tripod mounting for pressure sensors.

Table 1. Percent of observations where the largest departure of the standard deviations from the mean in the observations was as indicated (871 observations in 1970).

Deviation from mean (pct)	Percent of Observations
≤ 2	41
3 to 10	52
11 to 20	1
≥ 20	6

This comparison indicates the system operated consistently. The field wave records used for wave direction computation (discussed later) were chosen from the observations in Table 1, for which the standard deviations from all gages differed by 3 percent or less from their mean and for which the average significant wave height (uncompensated for attenuation with depth) was above 0.61 meter.

Fourier analysis provides a reliable procedure for obtaining the periods of the most important waves. A Fourier analysis of sea-surface elevation (or pressure) with time results in the distribution of energy with frequency, usually referred to as the *energy spectrum*. The energy spectrum for the record from gage 5 in each of the eight daily observations was computed using the Fast Fourier Transform algorithm developed by Cooley and Tukey (1967). The first 1,024 seconds of the 20-minute record was used in this computation. Gage 5 was chosen because of a good history of performance.

Fast Fourier Transform computations yield the contribution to the variance at each of a set of frequencies which are harmonics of a fundamental given by the inverse of the record duration, T . In this study, the frequencies of these harmonics are referred to as *spectral frequencies*, and the corresponding periods, given by their inverse, as *spectral periods*. The energy content between 32 seconds and 3 seconds was used to normalize the spectrum. The lower limit on period was estimated from the thickness of the water column above the pressure sensors. A summarized spectrum (Fig. 7) was formed by combining the energy content in 11 adjacent spectral periods. The band width in the summarized spectrum was slightly larger than 10^{-2} hertz (0.0107 hertz). The energy appearing at each spectral period in the pressure spectrum was compensated for attenuation with depth by using the classical hydrodynamic pressure correction:

$$F(k,h) = \frac{\cosh kh}{\cosh k\Delta z}, \quad (1)$$

here k is the wave number, h the water depth, and Δz the vertical distance of sensor from bottom. This resulted in a surface or compensated

Figure 7. Summarized pressure and surface spectra.

spectrum. Surface root-mean-square (rms) values were obtained from the compensated energy at each spectral period.

Since 1972, four simultaneous 20-minute records from each of the three gages included in the time-shared recording sequence are processed daily. More records are processed during special studies. The records processed from gages 1, 2, and 3 of the Pt. Mugu array start about 0100, 0700, 1300, and 1900 hours (P.s.t.). The significant wave height, the distribution function, the first five moments of the distribution, and the pressure spectra are computed for these records in a study of wave record variability. These records are not analyzed for wave direction.

1. Computation of Wave Direction.

For a long-crested sinusoidal wave with frequency σ_m , propagating in direction α_m (Fig. 8), the phase difference between locations 1 and 2 with coordinates (x_1, y_1) and (x_2, y_2) respectively, is given by:

$$\phi_{12} = k_m [(x_1 - x_2) \cos \alpha_m + (y_1 - y_2) \sin \alpha_m] , \quad (2)$$

where $k_m = 2\pi/L_m$ is the wave number associated with frequency σ_m , and L_m is the wavelength. The subscript is used to indicate the possible presence of different wave trains with different frequencies and directions.

The addition of the wave profile, η_3 , at a third noncolinear location allows solving for the sine and cosine of α_m . Thus, a unique solution for the wave direction is obtained from the following equation when the signs of numerator and denominator are considered. (see App. A.):

$$\alpha_m = \tan^{-1} \left[\frac{[(x_1 - x_3) \phi_{12} - (x_1 - x_2) \phi_{13}]/D}{[(y_1 - y_2) \phi_{13} - (y_1 - y_3) \phi_{12}]/D} \right] , \quad (3)$$

where ϕ_{13} is the phase difference between the third and first locations, and D is a function of gage separation.

Phase differences between locations for each different wave period are the only unknowns in the right-hand side of equation (3). Estimates of a representative phase difference between gage pairs for bands of constant frequency width are easily computed from cross-spectra of the wave (pressure) records. These spectra give, for each band, average values of the covariance of the wave records along two perpendicular directions.

Substitution of these representative values of phase difference into equation (3) affords an expedient and economic means of obtaining estimates of a "representative" wave direction for each of the spectral bands, provided the results are of engineering use. The agreement among

Figure 8. Long-crested wave propagating in direction $\alpha_{\hat{m}}$.

redundant computations of direction from the 10 three-gage arrays is an indication of the degree of confidence that can be placed on the resulting directions.

Directions were computed for a few observations (using the equation below) for the representative phase difference in each spectral band, where again, the sign of numerator and denominator must be considered.

$$\phi_{12\Delta} = \tan^{-1} \left[\frac{\text{Quad}_{\Delta}}{\text{Co}_{\Delta}} \right]. \quad (4)$$

The subscript Δ in equation (4) indicates the value is for a given spectral band. The cospectrum, Co , and quadrature spectrum, Quad , are defined as:

$$\begin{aligned} \text{Co}_{\Delta} &= \sum_{\Delta} x_1 x_2 \cos \phi_{12} \\ \text{Quad}_{\Delta} &= \sum_{\Delta} x_1 x_2 \sin \phi_{12}, \end{aligned} \quad (5)$$

where x_1 and x_2 are the spectral amplitudes from wave records 1 and 2, and $\sum_{\Delta}$ indicates summation over the adjacent spectral periods combined to make up a band. Jenkins and Watts (1968) showed that the definitions in equation (5) are equivalent to the more standard definitions based on correlation functions.

A computer output for runs using this approach is presented in Appendix B. Summaries of the results of the observations at 0700 hours, 25 June, and 2010 hours, 28 June, are given in Table 2. The first column in the table gives the period at the center of the band; the second column gives the average percent energy in each band for the five gages. The last 10 columns give the computed "representative" direction of each band for the three-gage array. Directions are measured from the seaward normal with positive values counterclockwise and negative values clockwise. The table shows that in these two observations disagreements in direction of the order of 20° are obtained for the longer period peaks and of 160° for the shorter period peaks. Examination of the computer output in Appendix B indicates the results are typical.

The array had been expected to yield directions to better than 20° for periods between 25 and 7 seconds. Understanding of the problems involved was sought by simulating the propagation through the array of narrow-banded wave trains traveling in a specified direction (discussed in next subsection).

2. Simulated Data Analysis.

In simulating the wave records for use, special consideration was given to wave period and to the difficulties arising in spectral analysis.

Table 2. Directional results with 0.01 hertz resolution for two observations.

Period at center of band (s)	Avg. pct energy	Three-gage arrays									
		1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
25 June 1970 at 0700 hr											
5.99	2.32	173	44	156	-50	-42	-46	-145	-131	-147	-39
6.40	0.46	173	32	157	-44	-44	-44	-147	-135	-153	-30
6.87	0.56	-64	-23	-45	-33	-43	-39	-149	-136	-166	-18
7.42	1.08	167	56	150	-35	-50	-42	-150	-24	46	-20
8.06	0.75	133	33	162	3	155	-49	8	5	-5	0
8.83	1.51	-20	-12	-9	-19	-18	0	5	2	-1	0
9.75	2.01	2	3	2	5	1	13	10	12	16	18
10.89	4.04	5	4	4	4	-2	16	-1	2	8	11
12.34	9.13	21	19	16	16	7	27	14	14	20	21
14.22	27.19	33	30	26	29	16	40	31	28	32	34
16.79	42.92	29	25	22	21	10	33	26	25	27	28
20.48	1.23	-1	-1	0	0	-8	31	26	25	27	28
26.26	0.24	74	119	121	117	131	120	178	144	109	135
28 June 1970 at 2010 hr											
5.99	7.44	169	52	136	-38	-31	-28	-148	-136	-155	-23
6.40	10.85	-47	-38	-33	-40	-34	-33	-148	-138	-157	-25
6.87	16.56	-40	-34	-29	-36	-30	-27	-151	-22	46	-21
7.42	9.75	-40	-33	-29	-35	-30	-27	-152	-20	48	-20
8.06	19.61	-40	-33	-29	-36	-30	-27	-152	-22	49	-21
8.83	7.65	-37	-29	-24	-32	-27	-20	-18	-15	-14	-14
9.75	0.96	-16	-15	-12	-16	-16	-2	-3	-3	-4	0
10.89	1.10	0	0	0	1	-7	25	-3	8	21	24
12.34	2.34	23	13	11	5	-4	26	14	14	14	14
14.22	4.46	12	12	10	12	4	24	8	10	16	18
16.79	1.61	19	14	12	9	0	28	15	15	21	21
20.48	1.00	108	46	40	25	2	52	40	49	43	34
26.26	0.70	-91	-89	-75	-89	-67	-95	-92	-66	-56	-72

Assume a sinusoid with frequency given as:

$$\sigma = \frac{2\pi(\hat{m} + \delta)}{N\Delta t}, \quad (6)$$

where Δt is the interval of time between samples, $|\delta|$ is less than or equal to $1/2$, and $N\Delta t = T$, the record duration.

Equation (6) provides for assigning frequencies which differ from the spectral frequencies. The contribution to the variance at the spectral frequencies of the sampled record is given by S_m^2 as:

$$S_m^2 = a_m^2 + b_m^2, \quad (7)$$

where a_m and b_m are the Fourier coefficients.

Harris (1974) showed that for values of m near $\hat{m}$ (i.e., for spectral frequencies near the frequency of the sinusoid), and for $\hat{m}$ far removed from one and $N/2$, the approximations below are good estimates to the coefficients.

$$\begin{aligned} a_m &\doteq \frac{A \sin \pi \delta \cos(\phi - \pi \delta)}{\pi(\hat{m} - m + \delta)}, \\ b_m &\doteq \frac{A \sin \pi \delta \sin(\phi - \pi \delta)}{\pi(\hat{m} - m + \delta)}. \end{aligned} \quad (8)$$

Slow convergence of the energy toward the spectral period closest to the assigned period is clearly indicated. Thus, the energy is spread over adjacent spectral periods. This spreading, due to the finiteness of the record, is usually referred to as *spillover*.

The technique routinely used at CERC to decrease spillover is to apply the cosine bell data window as defined by:

$$\hat{y}_i = \frac{1}{2} \left[1 - \cos \frac{2\pi t_i}{T} \right] y_i, \quad i = 1, \dots, N, \quad (9)$$

where y_i are the values in the original record. The Fourier coefficient for the resulting function $\hat{y}_i$, is given by:

$$\begin{aligned} \tilde{a}_m &\doteq \frac{A \sin \pi \delta \cos(\phi - \pi \delta)}{2\pi(\hat{m} - m + \delta) [(\hat{m} - m + \delta)^2 - 1]}, \\ \tilde{b}_m &\doteq \frac{A \sin \pi \delta \sin(\phi - \pi \delta)}{2\pi(\hat{m} - m + \delta) [(\hat{m} - m + \delta)^2 - 1]}. \end{aligned}$$

Thus, convergence is greatly increased and spillover is effectively reduced to three adjacent spectral periods.

The cosine bell data window was applied to the simulated records; therefore, it was sufficient to consider wave trains consisting of three sinusoids with nearby periods spread over at most six adjacent spectral periods. In general, the periods of waves in the ocean will differ from the spectral periods. Thus, the sinusoids in each simulated observation were specifically assigned periods differing slightly from the spectral periods by use of equation (6). Central periods of about 8 and 16 seconds were chosen to simulate 8- and 16-second swells. Swells with periods in this range are observed on the west coast.

Each simulated wave record consisted of values of the wave profile at the five gage locations computed at 0.25-second intervals for 17.07 minutes (1,024 seconds), to simulate the sampling rate and record duration customarily used at CERC for field data.

The three sinusoids were assigned specific directions and zero initial phase at the origin of coordinates, and were propagated across the array assuming a constant depth of 9.14 meters. Appendix C shows that the Finite Fourier Transform gives the correct phases for three sinusoids thus combined, provided the sinusoids are assigned the same direction, nearly the same amplitudes, and the frequency difference of each component to the nearest spectral frequency is the same. A frequency difference of $0.134/1,024 \div 0.000120$ hertz was chosen.

Characteristics of the first eight simulated observations are given in Table 3. Rough considerations of refraction using linear theory (McClenan, 1975) yield 22° from the normal to the coastline as the maximum possible direction that waves with a 16-second period may have at the depth of the array. Directions within 21° N. and 21° S. from the normal were chosen for the first four simulated wave trains. Since waves with an 8-second period may approach the coastline at the array site from a much wider arc, directions up to 60° N. and 60° S. were used for the directions of the fifth to eighth simulated trains.

The computed spectra for these eight simulated observations are shown in Appendix D (Figs. D-1 to D-8). In these figures the variance of the record, proportional to the energy, at each spectral period is plotted versus a linear frequency scale. No grouping of the variance at adjacent spectral periods has been made. These ungrouped spectra are referred to as *high-resolution spectra*. For spectra computed from 1,024-second records, this high resolution is approximately 0.001 hertz.

The program used to compute these spectra is the same program used at CERC for the analysis of field data. Many spectra of field data computed with this program and summarized by grouping 11 adjacent spectral periods are given by Thompson (1974).

The effect of spillover in the spectrum is shown in the figures of Appendix D. Each spectrum resulted from combining only three sinusoids; however, energy contributions appear at from five to nine adjacent spectral periods.

Table 3. Characteristics of simulated wave trains.

Wave train	Period ¹ (s)	Amplitude (cm)	Direction (°)
1	16.75	11.43	21 S.
	15.97	15.24	21 S.
	15.25	11.43	21 S.
2	16.75	11.43	21 S.
	15.97	15.24	15 S.
	15.25	11.43	21 N.
3	16.48	11.43	21 S.
	15.97	15.24	21 S.
	15.72	11.43	21 S.
4	16.48	11.43	21 S.
	15.97	15.24	15 S.
	15.72	11.43	21 N.
5	8.18	11.43	60 N.
	7.99	15.24	60 N.
	7.80	11.43	60 N.
6	8.18	11.43	60 N.
	7.99	15.24	40 N.
	7.80	11.43	60 S.
7	8.11	11.43	60 N.
	7.99	15.24	60 N.
	7.93	11.43	60 N.
8	8.11	11.43	60 N.
	7.99	15.24	40 N.
	7.93	11.43	60 S.

¹ Approximate value.

The periods assigned to the sinusoids giving rise to simulated observations 1, 2, 5, and 6, differed by exactly three spectral periods (see Table 3). The spectra for these four observations (Figs. D-1, D-2, D-5, and D-6) exhibit three maxima separated by two minima. The energy at these two minima may be interpreted as due to spillover since no sinusoids were combined with the corresponding periods.

The high-resolution spectra from field wave observations are discussed later; however, the use of the minima in these spectra to estimate spillover and noise is discussed here. The average energy at the minima between 25 and 7 seconds in the high-resolution spectra of the field observations was used as a measure of spillover and noise. Only spectral periods displaying an energy content at least twice this "background" energy were interpreted as possibly arising from physical wave components in the wave field.

The average directions resulting from the 10 three-gage arrays are given in Table 4 (last column). Only results of computations at the spectral periods closest to the assigned periods are shown. The table shows that for wave trains 1, 2, and 3 the computed directions for the 10 arrays agree with the input directions to within 1° .

The directional results for wave train 4 are correct only for spectral period 62. The main difference between this train and wave train 2 is the narrower spectral width. Wave train 2 gave the correct directions for all spectral periods; wave train 4 did not.

For simulated wave trains 5 to 8, the average directions seem meaningless. To determine whether these poor results were due to a programming deficiency, another eight sets of simulated records were generated, interchanging periods and directions. The computer output for the simulated observations is in Appendix D. This appendix and Table 5 should be referenced in the following discussion of additional simulated wave trains.

The directional results for the sinusoids with periods clustered around 16 seconds were of the same quality regardless of the assigned direction. However, the directional results for the 8-second sinusoids indicate that the capability to sense the correct direction for these shorter waves depends on the orientation of the three-gage array relative to the direction of propagation of the incoming wave. The resulting directions, which differed by less than 87° from the assigned directions, are given in Table 5. The top of each column in the table shows the shape and orientation of the array. These results are not surprising since the effective gage separation for the different gage pairs varies with orientation relative to direction of wave propagation. Table 5 also shows that the more nearly equilateral arrays have wider direction discernability. The design considerations for the array indicated an effectiveness for wave periods between 25 and 7 seconds (Borgman and Panicker, 1970).

Table 4. Computational results at closest spectral frequencies for simulated wave trains.

Wave train	Closest spectral frequency (1/1024 hz)	Spectral period (s)	Amplitude (cm)	Direction (°)
1	61	16.79	5.62	20 S.
	64	16.00	7.55	20 S.
	67	15.28	5.70	20 S.
2	61	16.79	5.62	21 S.
	64	16.00	7.55	15 S.
	67	15.28	5.70	20 N.
3	62	16.52	5.52	20 S.
	64	16.00	5.35	20 S.
	65	15.75	1.19	20 S.
4	62	16.52	5.52	21 S.
	64	16.00	5.35	25 S.
	65	15.75	1.19	36 N.
5	125	8.19	5.62	142 N.
	128	8.00	7.55	142 N.
	131	7.82	5.70	142 N.
6	125	8.19	5.62	142 N.
	128	8.00	7.55	78 N.
	131	7.82	5.70	162 S.
7	126	8.13	5.52	142 N.
	128	8.00	5.35	142 N.
	129	7.94	1.19	142 N.
8	126	8.13	5.52	142 N.
	128	8.00	7.14	76 N.
	129	7.94	5.83	172 S.

Table 5. Directional results of high-resolution spectral computations for 8-second wave.

Assigned direction ¹ (°)	Three-gage arrays									
	1-2-3 ▽	1-2-4 ▽	1-2-5 ▽	1-3-4 ▽	1-3-5 ▽	1-4-5 ▽	2-3-4 ▽	2-3-5 ▽	2-4-5 ▽	3-4-5 △
60 N.				59 N.	60 N.	59 N.		60 N.		60 N.
40 N.	40 N.	40 N.	40 N.	40 N.	40 N.	40 N.		40 N.		39 N.
21 N.	21 N.	20 N.	21 N.	21 N.	20 N.	20 N.		21 N.		20 N.
15 N.	14 N.	14 N.	14 N.	14 N.	14 N.	14 N.		14 N.		15 N.
15 S.	14 S.	14 S.		14 S.			14 S.	14 S.	14 S.	15 S.
21 S.	21 S.	20 S.		20 S.			20 S.	20 S.	20 S.	20 S.
40 S.	40 S.	39 S.		39 S.			39 S.	40 S.	39 S.	39 S.
60 S.				60 S.			60 S.	59 S.	59 S.	60 S.

¹Results differing by 87° or more from the assigned directions have been omitted.

The consistent and exact recovery of assigned directions achieved for the simulated 16-record wave trains is in part due to the use of the high computational resolution available in a large computer. Use of less exact data as available from recording instruments is expected to result in a less consistent and accurate recovery of the true direction. Simulated observations 1 to 4 were rerun truncating the computed profile values to three digits as is commonly available from recording systems. The effect of this truncation is estimated to have introduced an error of the order of ± 0.127 centimeter (0.05 inch) in the instantaneous values of the profiles. No appreciable differences in computed directions resulted by this truncation.

3. Identification of Wave Trains from the High-Resolution Spectrum.

A wave train in the real ocean is conceivably made up of several wave components with nearby periods propagating in approximately the same direction. Simplistic idealizations of such wave trains are exemplified by simulated observations 1, 3, 5, and 7. For wave trains 1 and 3, the long-crested wave model gave the correct direction of wave propagation for all 10 combinations (within 5°), not only at those spectral periods closest to the periods of the sinusoids combined, but at several adjacent ones on either side of these periods (see App.D, Figs. D-1 and D-3). At some of these adjacent spectral periods, the contribution to the energy was several times the background level and nearly the same at the five gage locations. Thus, it can be assumed that a wave train in the ocean will give rise to a number of adjacent spectral periods in the high-resolution energy spectrum with energy content several times the background level. This background level can be estimated by inspection of the minima in the energy spectrum, as discussed previously. A criterion for what energy level will be considered "high-energy content" can be set, and groups of adjacent spectral periods in the spectrum with high-energy content identified. These groups may each be assumed to arise from the presence of a wave train in the field with a mean wave period within the range of spectral periods in the group (a wave packet). The number of adjacent spectral periods in each group will be used as a measure of the width of the energy peak in the spectrum and indicates the spread in periods of the wave train. The spread in computed directions at adjacent spectral periods in a group is an indication of the degree of directional organization in the wave train. Large spread in directional results may indicate the possibility that crossing wave trains with nearly the same period are present. As results for simulated wave train 4 indicate, the long-crested model based on the assumption of a single wave train at each frequency is not suitable for a determination of wave direction in such cases. Multiple wave trains at a single frequency may result from refraction around a shoal or island or from reflection by a vertical wall.

4. Spectra and Direction of Wave Propagation for Field Data.

The energy and direction of wave propagation at each spectral period were computed for 44 field observations where the average uncompensated

significant wave height was over 2 feet and the discrepancy of individual standard deviations from their mean was 3 percent or less. Plots of the high-resolution spectra for these observations are in Appendix E. The vertical lines represent the energy contribution at each spectral period. The background level for each observation was estimated from the minima between 25 and 7 seconds in the spectra. Spectral periods in this range with energy content above twice the estimated background energy were identified. Contributions to the energy satisfying this criterion at adjacent spectral periods were considered as arising from the same wave train. The number of adjacent periods in each train was used as a measure of the *spectral width* of the train. The energy had to be above the chosen level at all five gages for the spectral period to be included in the group. The spectral period among these showing maximum energy was taken as the "period" of the wave train.

Directions were computed at all the spectral periods in each train for the 10 arrays. The total spread among these directions was found, and an average total spread was computed for the trains having the same spectral width. The same was done for the computed directional spread at the period of the train.

Twenty-five percent of the identified wave trains had total directional (computed) spreads above 100° and were not considered further. For 89 percent of the discarded trains, the period of the train was under 9.4 seconds. Thus, all trains with periods under 9.4 seconds were discarded.

Results for the different spectral widths for the trains retained (280) are shown in Table 6. The second column in the table gives the average total directional spread for the corresponding spectral width; the third column gives the average directional spread at the period of the wave train. The last column gives the number of wave trains having the spectral width in the first column.

These results indicate that the total directional spread increased with frequency width. Narrow peaks consisting of from one to three spectral periods are most frequent, and the spread in the direction at the period of the train remains relatively constant. Since the average spread for narrow-banded trains (width ≤ 0.003 hertz) is 21.8° , it is expected that three-gage arrays cannot yield directional results to any better accuracy. The mathematical exercise in Appendix C shows that array dimension is a limiting factor as to the shortest period for which some directional discrimination may be expected. An important factor in the validity of the directional result is the spectral structure of the wave train involved. Only in very special circumstances will the quantities involved in equation C-10 (App. C) combine to give better results.

There are various possible explanations for the large spreads observed in the directional results from field records. For the long-crested wave model to be strictly applicable, it is important that:

Table 6. Average spread in computed directions for 280 wave trains identified in the high-resolution spectra of 44 field wave observations.

Spectral width (hz)	Avg. total spread in direction for all periods (°)	Avg. spread in direction for period of train (°)	Cases (No.)
0.001	21.8	21.8	96
0.002	30.9	22.9	58
0.003	33.6	20.2	41
0.004	41.5	20.4	22
0.005	38.7	19.8	21
0.006	43.8	19.8	16
0.007	48.2	17.0	5
0.008	84.5	17.6	8
0.009	53.0	15.3	6
0.010	49.3	13.7	3
0.011	38.0	18.0	1
0.012	81.0	15.0	1
0.013	48.5	15.2	2

(a) The phase differences be known accurately or that the probable error in their computed values be known.

(b) The wave crests over the array site be long and straight; thus, the waves must not have undergone appreciable refraction.

(c) The sea surface be stationary in time for the duration of the record and in space over the span of the array.

The mathematical exercise in Appendix D indicates that the analysis yields accurate phase differences only for strictly monochromatic conditions. When this is not the case, no accurate estimate of the error involved in the computation of direction can be given. This inability is inherent to the computational procedure and cannot be resolved.

Waves with periods over 8 seconds have been and are undergoing refraction at the site of the array. Therefore, the wave crests are not exactly straight. For the longer waves, with wavelengths at the array site several times the gage separations, the curvature will not

introduce much error. This will not be the case for the shorter waves and orientation of the array becomes important.

Because of refraction, the curvature of a wave train changes, perhaps only slightly, while propagating over the array. This change will introduce differences in the direction at each gage and differences in the direction sensed by different gage pairs, causing undetermined additional errors in the computation of direction. To determine the magnitude of these errors, two additional sets of simulated wave records were generated. The periods of the sinusoids combined were those for simulated observation 3; the directions assigned were spread within a 10° arc for the first set and 20° for the second. The last two computer outputs in Appendix D show that spreads of the order of 16° and 32° , respectively, resulted in computed directions.

A stationary condition in time is usually assumed when developing wave directional models. Indications are that this is not strictly applicable at all times.

The three factors discussed above are sufficient to account for the inaccuracies encountered in the computations.

5. Conclusions.

The results of directional computations, for both simulated and field wave data records, indicate three-gage arrays have some capabilities to determine wave direction under certain conditions. These capabilities depend on:

(a) The dimension of the array and the water depth at the site which place a lower limit on the wave period for which possibly accurate directions may be computed.

(b) The orientation of the array for the shorter periods.

(c) The nature of the wave field; directional results for wave trains with a narrow frequency distribution or where the computed directions differ little at the adjacent spectral periods might be meaningful.

For wave trains with narrow frequency and directional width, and period above 10 seconds, the three-gage arrays at Pt. Mugu yield directions to an estimated accuracy of 20° .

At the Pt. Mugu site, 16-second waves may approach the coastline at angles of 22° or less from the normal. The directional information provided by the array adds little to this and seems hardly cost effective.

LITERATURE CITED

- BORGMAN, L.E., and PANICKER, N.N., "Design Study for A Suggested Wave Gage Array off Point Mugu, California," Technical Report HEL 1-14, University of California, Hydraulic Engineering Laboratory, Berkeley, Calif., Jan. 1970.
- COOLEY, J.W., and TUKEY, J.W., "The Fast Fourier Transform," *Institute of Electrical and Electronic Engineers Spectrum*, Vol. 4, No. 1, Jan. 1967, pp. 63-70.
- FUJINAWA, J., "Measurement of Directional Spectrum of Wind Waves Using an Array of Wave Detectors," *Journal of the Oceanographical Society of Japan*, Vol. 30, No. 1, Feb. 1974, pp. 10-22.
- FUJINAWA, Y., "Measurement of Directional Spectrum of Wind Waves Using an Array of Wave Detectors, Part II--Field Observations," *Journal of the Oceanographical Society of Japan*, Vol. 31, No. 1, Feb. 1975, pp. 25-42.
- HARRIS, D.L., "Finite Spectrum Analyses of Wave Records," *Proceedings of the International Symposium on Ocean Wave Measurement and Analysis*, Sept. 1974, pp. 107-124.
- JENKINS, G.M., and WATTS, D.G., *Spectral Analysis and Its Applications*, Holden-Day, San Francisco, Calif., 1968.
- KINSMAN, B., *Wind Waves*, Prentice-Hall, Englewood Cliffs, N.J., 1965.
- McCLENAN, C.M., and HARRIS, D.L., "The Use of Aerial Photography in the Study of Wave Characteristics in the Coastal Zone," TM-48, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Jan. 1975.
- McCLENAN, C.M., "Simplified Method of Estimating Refraction and Shoaling Effects on Ocean Waves," TM-59, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Nov. 1975.
- PANICKER, N.N., "Determination of Directional Spectra of Ocean Waves from Gage Arrays," Technical Report HEL 1-18, University of California, Hydraulic Engineering Laboratory, Berkeley, Calif., Aug. 1971.
- PANIKER, N.N., "Review of Techniques for Wave Spectra," *Proceedings of the International Symposium on Ocean Wave Measurement and Analysis*, Sept. 1974, pp. 669-688.

PEACOCK, H.G., "CERC Field Wave Gaging Program." *Proceedings of the International Symposium on Ocean Wave Measurement and Analysis*, Sept. 1974, pp. 170-185.

THOMPSON, E.F., "Results from the CERC Wave Measurement Program," *Proceedings of the International Symposium on Ocean Wave Measurement and Analysis*, Sept. 1974, pp. 836-855.

WILLIAMS, L.C., "CERC Wave Gages," TM-30, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Washington, D.C., Dec. 1969.

APPENDIX A

DERIVATION OF THE EXPRESSION FOR WAVE DIRECTION

Let the coordinates of nearby gage sites be (x_i, y_i) , $i = 1, N$; with N = number of gages. The water surface displacement at each site due to the passage of a sinusoidal wave of frequency σ , and amplitude A , traveling in direction α (α_m in Fig. 8), is given by:

$$\eta_i = A \cos\{k[x_i \cos \alpha + y_i \sin \alpha] - 2\pi\sigma t - \phi\}, \quad (\text{A-1})$$

where $k = 2\pi/L$ is the wave number, L the wavelength, and ϕ the initial phase at the origin.

The phase difference, ϕ_{ij} , between locations i and j for the sinusoid considered is:

$$\phi_{ij} = k[(x_i - x_j) \cos \alpha + (y_i - y_j) \sin \alpha]. \quad (\text{A-2})$$

Thus, for three noncolinear locations,

$$\phi_{12} = k[(x_1 - x_2) \cos \alpha + (y_1 - y_2) \sin \alpha],$$

$$\phi_{13} = k[(x_1 - x_3) \cos \alpha + (y_1 - y_3) \sin \alpha], \quad (\text{A-3})$$

suffice for a unique solution of the direction α . Eliminating first the $\sin \alpha$ terms and then the $\cos \alpha$ terms, to obtain:

$$\begin{aligned} \sin \alpha &= \frac{(x_1 - x_3) \phi_{12} - (x_1 - x_2) \phi_{13}}{k[(x_1 - x_3)(y_1 - y_2) - (x_1 - x_2)(y_1 - y_3)]}, \\ \cos \alpha &= \frac{(y_1 - y_2) \phi_{13} - (y_1 - y_3) \phi_{12}}{k[(x_1 - x_3)(y_1 - y_2) - (x_1 - x_2)(y_1 - y_3)]}. \end{aligned} \quad (\text{A-4})$$

Since k is always positive, consideration need only be given to the other terms. Letting D stand for the quantity in square brackets, the direction, α , for $D \neq 0$ is given by:

$$\alpha = \tan^{-1} \left\{ \frac{[(x_1 - x_3) \phi_{12} - (x_1 - x_2) \phi_{13}]/D}{[(y_1 - y_2) \phi_{13} - (y_1 - y_3) \phi_{12}]/D} \right\}. \quad (\text{A-5})$$

A unique value for direction can be obtained by considering the signs of both numerator and denominator. The quantity D differs from zero for all nonlinear arrays as shown below.

Let $x_1 = y_1 = 0$, D will equal zero for $y_2/x_2 = y_3/x_3$; thus, x_2, y_2 and x_3, y_3 will be on a straight line with slope given by this ratio.

APPENDIX B

COMPUTER OUTPUT FOR CROSS-SPECTRA COMPUTATIONS

Table. Guide to computer output.

Line (from top)	Column (from left)	Explanation
1		Title, plus date and time of the observation (day, month, year, hour, and minutes).
2 to 4		Headings for columns. The numbers separated by dashes in the fourth line give the numbers of the gages in the array (see Fig. 3).
	1	Sequential number of bands 0.0107 hertz wide.
	2	Period at center of band (seconds).
	3 to 7	Percent of energy in each band for gages 1 to 5. Normalized to the energy content from approximately 30 to 3 seconds.
	8 to 17	Resulting "representative" direction of wave propagation for the 10 arrays for the corresponding band (degrees).

PT MUGU FIRE 245E ARMY 24 6 1970 906

PRESSURE SPECTRA

DIRECTION CUES FROM SEWARD NORMAL

BAND	PERIOD	AT	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-4-5	3-4-5
1	170.97	1.61	1.55	10	19	14	34	31	35	-27	3
2	50.24	.52	.57	45	47	49	74	56	70	159	40
3	36.57	.31	.20	172	40	35	28	8	48	50	48
4	26.26	.11	.16	133	92	88	63	27	92	42	72
5	20.56	2.23	2.42	16	20	17	28	16	28	18	23
6	18.79	3.51	3.63	28	23	20	21	11	31	24	23
7	14.22	24.00	25.70	12	11	9	9	3	21	13	14
8	12.32	20.44	24.65	13	12	10	11	3	22	12	13
9	10.83	1.86	4.67	2	2	2	2	2	15	6	8
10	9.45	5.36	2.92	7	6	6	6	6	4	5	6
11	8.63	1.13	1.37	3	2	2	2	2	9	7	7
12	7.99	1.19	1.74	127	46	157	18	152	47	1	1
13	7.22	1.33	1.11	155	26	124	26	124	20	152	14
14	6.57	.30	.91	132	29	101	0	154	47	150	47
15	5.96	.27	.50	133	26	155	1	151	42	146	102
16	5.31	.23	.23	135	1	154	3	142	34	141	148
17	5.01	.16	.19	173	22	125	5	136	152	143	167
18	4.51	.10	.10	175	1	126	13	138	132	132	136
19	4.02	.08	.11	177	15	136	18	140	130	137	137
20	3.75	.05	.08	179	1	178	10	140	110	110	105
21	3.53	.23	.25	179	1	178	10	140	110	110	101
22	3.24	.33	.35	178	5	177	48	139	126	126	126
23	3.22	.44	.47	178	4	177	48	139	126	126	126
24	3.13	.15	.16	178	4	177	48	139	126	126	126
25	3.05	.13	.15	178	4	177	48	139	126	126	126
26	3.00	.09	.10	178	4	177	48	139	126	126	126
27	3.00	.09	.10	178	4	177	48	139	126	126	126
28	3.00	.09	.10	178	4	177	48	139	126	126	126
29	3.00	.09	.10	178	4	177	48	139	126	126	126
30	3.00	.09	.10	178	4	177	48	139	126	126	126
31	3.00	.09	.10	178	4	177	48	139	126	126	126
32	3.00	.09	.10	178	4	177	48	139	126	126	126
33	3.00	.09	.10	178	4	177	48	139	126	126	126
34	3.00	.09	.10	178	4	177	48	139	126	126	126

PT MUGU FIVE GAGE ARRAY 24 6 1970-1206

BAND PERIOD AT CENTER	PRESSURE SPECTRA										DIRECTION (DEGREES FROM SEWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5		
1 170.47	2.62	3.90	3.38	2.42	2.58	1.54	1.14	98	122	-6	112	64	85	89	75					
2 506.51	1.40	3.74	3.06	2.51	2.08	1.17	80	63	71	-17	86	61	62	92	71					
3 584.74	1.49	3.54	2.86	2.29	1.79	-22	-60	-50	-43	-175	-57	-79	-74	-71	-62					
4 500.68	1.08	1.54	1.35	1.29	1.20	26	116	148	114	143	134	171	121	121	137					
5 164.79	51.20	48.30	51.40	54.75	50.25	21	11	12	12	4	20	15	15	18	13					
6 144.24	20.15	21.69	20.12	17.55	17.55	11	11	19	19	0	24	15	15	17	20					
7 124.34	9.13	8.33	7.36	7.36	7.36	34	24	23	16	0	28	24	23	25	22					
8 104.95	2.47	1.51	1.58	2.10	1.96	-1	0	0	-2	-8	11	11	9	9	39					
9 84.33	5.42	5.44	6.05	5.05	5.05	58	48	163	35	154	-54	73	29	44	22					
10 64.03	3.61	1.21	1.58	2.62	1.96	142	51	162	12	155	-53	64	4	15	14					
11 44.66	8.1	7.4	1.75	1.76	1.35	0	1	1	15	15	14	-4	4	20	11					
12 24.93	1.17	1.60	1.34	.69	.53	117	39	162	14	154	-50	-23	24	137	152					
13 6.97	.54	1.17	.68	.47	1.02	166	42	146	-26	-42	-38	-37	-37	-37	-37					
14 6.00	.22	.24	.66	.23	.41	172	42	148	-45	-38	-39	-35	-35	-35	-35					
15 5.09	.54	1.01	.56	.41	.70	173	41	150	-49	-49	-40	-45	-45	-47	101					
16 5.03	.18	.22	.22	.21	.04	172	37	151	-45	-45	-41	35	116	142	113					
17 5.03	.18	.13	.20	.21	.14	165	15	162	-21	168	-43	32	159	134	71					
18 5.02	.22	.44	.34	.31	.36	179	1	2	-40	-28	-33	32	92	128	89					
19 4.96	.18	.16	.19	.13	.17	175	20	117	-47	-33	-29	127	119	121	152					
20 4.96	.32	.41	.31	.25	.24	-166	-22	-15	-46	-29	5	24	63	117	87					
21 4.96	.53	.52	.35	.16	.42	-171	-23	-15	-51	-30	126	62	64	64	145					
22 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
23 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
24 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
25 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
26 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
27 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
28 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
29 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
30 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
31 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
32 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
33 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					
34 4.96	.37	.54	.39	.44	.44	174	146	67	-78	-30	126	62	64	64	145					

PT MUGU FIVE GAGE ARRAY 24 6 1970 1506

BAND PERIOD PRESSURE SPECTRA

DIRECTION (DEGREES FROM SEA-LEVEL NORMAL)

POSITIVE VALUES ARE COUNTERCLOCKWISE

CENTER	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
1 170.67	1.09	1.79	1.62	1.99	1.99	1.56	1.33	1.31	1.34	1.32
2 60.24	1.06	1.23	1.09	1.02	1.02	1.26	1.26	1.26	1.26	1.26
3 36.57	1.33	1.41	1.35	1.40	1.40	1.42	1.42	1.42	1.42	1.42
4 26.26	1.12	1.80	1.93	1.80	1.80	1.75	1.75	1.75	1.75	1.75
5 20.38	2.50	2.43	3.07	3.31	3.31	3.49	3.49	3.49	3.49	3.49
6 16.79	4.11	35.17	35.57	33.74	33.74	31.54	31.54	31.54	31.54	31.54
7 11.22	3.61	42.90	41.35	41.32	41.32	40.66	40.66	40.66	40.66	40.66
8 12.34	4.18	6.04	4.89	6.12	6.12	7.93	7.93	7.93	7.93	7.93
9 10.89	1.55	2.41	2.00	1.52	1.52	2.38	2.38	2.38	2.38	2.38
10 9.75	2.97	1.28	1.39	1.00	1.00	2.07	2.07	2.07	2.07	2.07
11 8.63	2.04	1.25	1.67	1.00	1.00	1.96	1.96	1.96	1.96	1.96
12 7.06	1.46	1.40	1.64	1.00	1.00	1.14	1.14	1.14	1.14	1.14
13 6.42	1.31	1.35	1.02	1.00	1.00	1.36	1.36	1.36	1.36	1.36
14 5.67	1.00	1.13	1.12	1.00	1.00	1.37	1.37	1.37	1.37	1.37
15 5.00	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
16 5.00	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
17 5.00	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
18 5.31	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
19 5.02	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
20 4.78	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
21 4.53	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
22 4.32	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
23 4.13	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
24 3.95	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
25 3.79	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
26 3.64	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
27 3.51	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
28 3.36	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
29 3.26	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
30 3.15	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
31 3.05	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
32 2.95	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
33 2.86	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36
34 2.78	1.00	1.13	1.14	1.00	1.00	1.36	1.36	1.36	1.36	1.36

PT HUGU FIVE GAGE ARRAY 24 6 1970 1807

BAND PERIOD PRESSURE SPECTRA

AT CENTER

DIRECTION (DEGREES FROM SEAWARD NORMAL)

POSITIVE VALUES ARE COUNTERCLOCKWISE

	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5						
1	170.67	1.44	2.03	1.94	1.62	1.15	-175	-170	-81	-148	-39	148	134	143	148	150
2	60.24	1.22	1.17	1.04	1.22	1.36	14	20	24	30	66	11	14	14	15	16
3	36.57	.29	.00	.29	.25	.26	49	58	44	42	37	71	49	30	40	57
4	26.26	.32	.03	.29	.25	.20	1	2	1	26	3	52	-43	0	18	37
5	20.48	1.50	1.02	1.37	1.24	1.12	45	26	18	15	-2	47	22	23	20	23
6	16.79	25.61	34.03	28.25	24.68	27.16	24	21	18	16	6	29	22	21	21	22
7	14.22	28.06	23.70	25.52	24.86	27.09	20	18	16	15	6	27	19	17	18	19
8	12.34	10.03	12.21	11.74	10.58	12.25	19	15	13	11	1	20	16	17	27	28
9	10.69	4.87	3.43	3.47	4.25	3.37	39	27	24	19	8	32	27	26	27	28
10	9.75	3.10	1.25	2.72	4.37	1.77	6	6	5	5	-1	20	11	11	9	14
11	8.83	1.62	1.02	1.47	1.67	1.25	33	19	17	9	9	-2	35	21	21	21
12	8.06	.93	.77	1.21	1.09	1.11	-16	-24	-17	-15	-16	-3	12	6	-13	-1
13	7.42	.63	1.25	2.75	1.50	2.00	-5	3	2	-10	-3	-3	15	0	0	0
14	6.87	.40	.62	.36	.44	.34	167	54	149	-33	-32	-37	-39	-47	-54	-18
15	6.40	.50	.30	1.1	.75	.80	170	56	150	-50	-39	-42	-46	-37	-58	-27
16	5.84	1.72	2.04	1.51	1.73	2.09	173	35	159	-44	-44	-47	-44	-33	-51	-44
17	5.37	4.72	5.17	3.24	3.52	3.68	174	29	152	-45	-45	-40	-42	-31	-40	103
18	5.02	4.72	5.17	3.24	3.52	3.68	176	20	152	-45	-44	-42	-42	-31	-35	199
19	4.40	3.89	3.29	3.50	3.43	3.43	178	9	170	-49	-44	-42	-40	-36	-31	105
20	4.72	3.89	3.29	3.72	3.67	3.62	178	9	170	-49	-44	-42	-40	-36	-31	105
21	4.53	1.17	1.45	1.64	1.37	2.58	178	-5	168	-51	-42	-40	-30	-29	91	127
22	4.32	.24	.55	.79	.79	.68	164	-46	-18	-60	-50	-30	70	27	94	127
23	4.13	.41	.59	.51	.41	.49	167	-13	-10	-46	-49	-29	2	94	73	82
24	3.95	.36	.28	.21	.15	.35	167	-25	-66	-49	-49	-47	77	59	61	73
25	3.79	.22	.11	.20	.12	.09	-6	-25	-35	-44	143	-35	57	42	47	-124
26	3.64	.05	.18	.17	.16	.09	-179	-177	-1	-19	155	-29	127	43	44	-119
27	3.51	.05	.09	.07	.05	.15	14	16	171	136	110	-53	23	21	29	32
28	3.38	.04	.04	.05	.04	.04	150	150	65	136	110	-53	23	21	29	32
29	3.26	.03	.02	.02	.02	.01	-166	-130	-150	-102	-66	-107	122	174	-129	-62
30	3.15	.01	.01	.01	.01	.01	174	47	92	-52	-31	127	154	-120	-62	-54
31	3.05	.01	.02	.01	.01	.00	12	143	40	125	134	127	127	-62	55	-73
32	2.95	.00	.01	.00	.00	.00	0	178	1	127	134	127	127	-62	55	-73
33	2.86	.01	.00	.00	.00	.00	-176	-3	-175	-33	-167	-50	-50	-56	74	149
34	2.76	.00	.00	.00	.00	.00	0	178	1	127	134	127	127	-62	55	-73

PT HUGU FIVE GAGE ARRAY 25 6 1970 7

BAND PERIOD PRESSURE SPECTRA

[illegible]

PT MUGU FIVE GAGE ARRAY 25 6 1970 307

BAND PERIOD AT PRESSURE SPECTRA

	1-0-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-5	2-4-5	3-4-5
1 170.67	1.03	.76	.92	1.25	1.48	1.74	1.60	1.55	1.38
2 60.24	1.10	.74	.97	1.25	1.48	1.74	1.60	1.55	1.38
3 36.57	.22	.21	.21	.26	.29	1.0	1.0	1.0	1.0
4 20.26	.26	.26	.23	.26	.29	1.0	1.0	1.0	1.0
5 20.46	.84	.69	.87	1.04	1.10	1.13	1.0	1.0	1.0
6 16.79	40.90	36.52	36.02	36.34	36.07	36.23	36.20	36.17	36.17
7 14.22	34.15	31.76	31.65	31.08	30.74	30.51	30.40	30.35	30.35
8 12.34	8.31	8.00	8.64	8.66	8.54	8.31	8.25	8.21	8.21
9 10.79	2.74	2.30	2.60	2.21	2.22	2.1	2.1	2.1	2.1
10 10.75	1.20	2.06	1.85	1.24	2.4	1.1	1.1	1.1	1.1
11 8.63	1.56	1.2	1.55	1.16	1.5	1.1	1.1	1.1	1.1
12 8.35	.60	.60	.65	.65	.65	.65	.65	.65	.65
13 7.95	.60	.60	.65	.65	.65	.65	.65	.65	.65
14 6.87	.60	.60	.65	.65	.65	.65	.65	.65	.65
15 6.40	.17	.17	.17	.17	.17	.17	.17	.17	.17
16 5.99	.49	.49	.49	.49	.49	.49	.49	.49	.49
17 5.63	1.61	1.20	1.22	1.33	1.33	1.33	1.33	1.33	1.33
18 5.31	1.61	1.06	1.26	1.15	1.33	1.33	1.33	1.33	1.33
19 5.02	2.37	1.64	1.65	1.73	1.33	1.33	1.33	1.33	1.33
20 4.76	.74	.65	.65	.65	.65	.65	.65	.65	.65
21 4.53	.47	.47	.47	.47	.47	.47	.47	.47	.47
22 4.32	.43	.43	.43	.43	.43	.43	.43	.43	.43
23 4.13	.27	.11	.11	.15	.17	.17	.17	.17	.17
24 3.95	.13	.06	.06	.06	.06	.06	.06	.06	.06
25 3.79	.04	.04	.04	.04	.04	.04	.04	.04	.04
26 3.59	.05	.05	.05	.05	.05	.05	.05	.05	.05
27 3.51	.02	.02	.02	.02	.02	.02	.02	.02	.02
28 3.36	.01	.01	.01	.01	.01	.01	.01	.01	.01
29 3.26	.01	.00	.00	.00	.00	.00	.00	.00	.00
30 3.15	.00	.00	.00	.00	.00	.00	.00	.00	.00
31 3.05	.00	.00	.00	.00	.00	.00	.00	.00	.00
32 2.95	.00	.00	.00	.00	.00	.00	.00	.00	.00
33 2.78	.00	.00	.00	.00	.00	.00	.00	.00	.00

DIRECTION (DEGREES FROM SEWARD NORMAL)

POSITIVE VALUES ARE COUNTERCLOCKWISE

	1-2-5	1-3-4	1-3-5	1-4-5	2-3-5	2-4-5	3-4-5
1 170.67	169	169	169	169	169	169	169
2 60.24	125	125	125	125	125	125	125
3 36.57	10	10	10	10	10	10	10
4 20.26	39	39	39	39	39	39	39
5 20.46	4	4	4	4	4	4	4
6 16.79	17	17	17	17	17	17	17
7 14.22	15	15	15	15	15	15	15
8 12.34	21	21	21	21	21	21	21
9 10.79	24	24	24	24	24	24	24
10 10.75	12	12	12	12	12	12	12
11 8.63	19	19	19	19	19	19	19
12 8.35	21	21	21	21	21	21	21
13 7.95	18	18	18	18	18	18	18
14 6.87	137	137	137	137	137	137	137
15 6.40	137	137	137	137	137	137	137
16 5.99	137	137	137	137	137	137	137
17 5.63	137	137	137	137	137	137	137
18 5.31	137	137	137	137	137	137	137
19 5.02	137	137	137	137	137	137	137
20 4.76	137	137	137	137	137	137	137
21 4.53	137	137	137	137	137	137	137
22 4.32	137	137	137	137	137	137	137
23 4.13	137	137	137	137	137	137	137
24 3.95	137	137	137	137	137	137	137
25 3.79	137	137	137	137	137	137	137
26 3.59	137	137	137	137	137	137	137
27 3.51	137	137	137	137	137	137	137
28 3.36	137	137	137	137	137	137	137
29 3.26	137	137	137	137	137	137	137
30 3.15	137	137	137	137	137	137	137
31 3.05	137	137	137	137	137	137	137
32 2.95	137	137	137	137	137	137	137
33 2.78	137	137	137	137	137	137	137

PT MUGU FIVE GAGE ARMY 25 6 1970 1608

BAND PERIOD AT CENTER PRESSURE SPECTRA

BAND PERIOD AT CENTER	DIRECTION (DEGREES FROM SEASAND NORMAL)									
	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
1 170.87	1.73	.93	1.26	-176	-5	-19	-40	-33	-22	161
2 170.84	1.88	1.07	1.16	49	39	40	34	-20	18	32
3 169.57	1.82	1.01	1.01	-171	161	160	-139	-89	153	171
4 169.56	.86	.45	.29	138	102	117	91	99	-164	153
5 169.56	.82	.45	.29	37	19	11	8	-8	53	129
6 169.59	30.08	29.42	24.84	26	24	21	22	13	30	26
7 169.52	13.58	12.75	15.62	33	31	28	29	21	35	29
8 169.52	14.74	14.66	10.51	31	26	21	22	8	37	26
9 169.49	14.74	14.66	10.51	31	26	21	22	8	37	26
10 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
11 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
12 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
13 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
14 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
15 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
16 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
17 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
18 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
19 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
20 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
21 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
22 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
23 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
24 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
25 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
26 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
27 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
28 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
29 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
30 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
31 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
32 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
33 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32
34 169.55	1.88	1.07	1.16	49	39	40	34	-20	18	32

PT MUGU FIVE GAGE APRAY 25 6 1970 2108

BAND PERIOD
CENTER PRESSURE SPECTRADIRECTION COEFFS FROM SEABED NORMAL
POSITIVE VALUES ARE COUNT/CLOCKWISE

BAND CENTER	PERIOD	PRESSURE	SPECTRA	DIRECTION COEFFS FROM SEABED NORMAL									
				1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
1	170.87	.77	1.04	.97	1.15	.99	174	171	172	176	-173	179	172
2	169.24	.87	.66	.66	1.72	1.65	146	-171	-171	-173	179	172	171
3	168.59	.90	.54	.54	1.72	1.65	146	-171	-171	-173	179	172	171
4	167.87	.93	.40	.40	1.74	1.67	147	-172	-172	-174	180	174	174
 

PT MUGU FIVE GAGE ARRAY 26 6 1970 1758

BAND PERIOD CENTER	PRESSURE SPECTRA										DIRECTION (WEATHER FROM SEARAD NORMAL)																		
	POSITION										POSITION																		
	1-2-3	1-2-4	1-2-5	1-3-6	1-3-7	1-3-8	1-4-9	1-4-10	1-4-11	1-4-12	1-5-13	1-5-14	1-5-15	1-6-16	1-6-17	1-6-18	1-7-19	1-7-20	1-7-21	1-7-22	1-7-23	1-7-24	1-7-25	1-7-26	1-7-27	1-7-28	1-7-29	1-7-30	
1 170.67	.66	2.10	1.93	1.65	.95	.95	.167	.155	.14	.136	.20	129	161	20	30	174													
2 170.24	.51	.76	.74	.61	.95	.95	.176	.175	.175	.167	.170	137	164	179	142	142													
3 169.57	.46	.46	.47	.38	.28	.28	.2	.2	.0	.15	.17	.58	17	18	.15	16													
4 169.26	.49	.23	.41	.54	.56	.56	.152	.152	.164	.151	.179	.116	12	18	.24	.61													
5 169.36	.37	1.00	.97	.79	.76	.76	.4	.4	.4	.2	.8	.34	30	10	10	13													
6 169.79	3.70	3.04	3.05	2.67	3.23	3.23	.41	.21	.15	.4	.9	.4	39	25	25	15													
7 169.22	11.51	12.20	13.58	13.06	1.06	1.06	.26	.13	.21	.21	.17	20	23	23	22	22													
8 169.34	6.67	4.49	3.40	3.49	3.98	3.98	.17	.13	.11	.11	.7	0	19	18	18	16													
9 169.77	6.67	5.27	4.25	6.06	4.25	4.25	.29	.19	.16	.11	.0	30	23	23	23	22													
10 169.65	1.26	1.94	2.43	1.55	1.45	1.45	.29	.20	.14	.7	.21	20	20	20	22	20													
11 169.01	1.14	1.14	1.14	1.08	1.21	1.21	.16	.20	.13	.19	.18	.20	9	.2	.14	.12													
12 169.03	3.14	1.99	1.71	1.50	1.21	1.21	.16	.20	.13	.19	.18	.20	9	.2	.14	.12													
13 169.47	7.73	7.73	7.73	7.73	7.73	7.73	.47	.47	.47	.47	.47	.47	.47	.47	.47	.47													
14 169.60	2.53	2.86	2.49	2.61	2.71	2.71	.170	.158	.147	.145	.141	.139	.130	.146	.160	.132													
15 169.67	1.90	1.97	1.87	1.87	1.87	1.87	.170	.170	.170	.170	.170	.170	.170	.170	.170	.170													
16 169.59	4.38	9.12	6.29	6.67	12.07	12.07	.172	.172	.172	.172	.172	.172	.172	.172	.172	.172													
17 169.53	4.38	3.24	4.38	4.38	3.08	3.08	.173	.173	.173	.173	.173	.173	.173	.173	.173	.173													
18 169.31	5.95	1.42	1.00	1.19	2.32	2.32	.174	.174	.174	.174	.174	.174	.174	.174	.174	.174													
19 169.02	1.32	2.36	1.44	1.17	3.37	3.37	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179													
20 169.76	1.62	.69	.69	.38	.49	.49	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177													
21 169.53	1.62	.69	.69	.38	.49	.49	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177													
22 169.32	1.68	.67	.67	.58	.58	.58	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177													
23 169.35	.69	.69	.69	.77	.73	.73	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177													
24 169.35	.69	.69	.69	.7	.7	.7	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177													
25 169.40	.20	.23	.23	.20	.28	.28	.159	.158	.162	.155	.122	.135	137	135	137	110													
26 169.51	.20	.23	.23	.20	.28	.28	.179	.178	.177	.168	.161	.157	149	146	149	118													
27 169.51	.03	.10	.03	.07	.11	.11	.1	.1	.1	.0	.0	.175	15	15	15	18													
28 169.38	.03	.03	.03	.03	.02	.02	.161	.161	.161	.161	.161	.161	.161	.161	.161	.161													
29 169.29	.03	.03	.03	.03	.02	.02	.171	.137	.107	.109	.127	.127	.127	.127	.127	.127													
30 169.315	.02	.01	.01	.01	.00	.00	.171	.137	.107	.109	.127	.127	.127	.127	.127	.127													
31 169.32	.00	.01	.01	.01	.00	.00	.171	.137	.107	.109	.127	.127	.127	.127	.127	.127													
32 169.35	.00	.00	.00	.00	.00	.00	.154	.154	.154	.154	.154	.154	.154	.154	.154	.154													
33 169.36	.00	.00	.00	.00	.00	.00	.162	.162	.162	.162	.162	.162	.162	.162	.162	.162													
34 169.78	.00	.00	.00	.00	.00	.00	.156	.153	.156	.157	.158	.160	.160	.160	.160	.160													

PT HUGU FIVE GAGE ARRAY 2B 6 1970 2010

BAND PERIOD AT CENTER PRESSURE SPECTRA

BAND PERIOD AT CENTER	DIRECTION (DEGREES FROM SEASWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
	1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	2-3-4	2-3-5	2-4-5	3-4-5	3-4-6
1 170.87	.97	.98	.86	.81	.90	.142	.36	.59	.14	.13
2 60.24	.86	.54	.86	.81	.85	.111	.104	.125	.16	.12
3 36.57	.86	.112	.85	.86	.86	.79	.74	.77	.16	.11
4 20.46	.86	.81	.86	.86	.86	.84	.79	.84	.16	.11
5 10.89	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
6 1.72	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
7 1.72	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
8 1.72	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
9 1.72	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
10 1.72	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
11 6.15	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
12 6.15	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
13 7.42	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
14 6.40	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
15 5.99	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
16 5.63	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
17 5.31	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
18 5.02	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
19 4.76	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
20 4.53	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
21 4.32	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
22 4.12	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
23 3.95	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
24 3.79	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
25 3.64	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
26 3.50	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
27 3.36	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
28 3.23	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
29 3.10	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
30 2.98	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
31 2.86	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
32 2.76	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
33 2.66	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11
34 2.56	.86	.86	.86	.86	.86	.84	.79	.84	.16	.11

PT MUGU FIVE GAGE ARRAY 26 6 1970 2050

PRESSURE SPECTRA

DIRECTION (DEGREES FROM SEWARD NORMAL)

BAND PERIOD AT CENTER	POSITIVE VALUES ARE COUNTERCLOCKWISE										SEWARD NORMAL												
	1-2	3	12-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5	1-2	3	12-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5	
1 170.67	.20	.39	.27	.36	.37	.12	.42	.56	.73	.17	.46	.163	.154	.141	.141	.154	.154	.154	.154	.154	.154	.154	.154
2 60.24	.42	.53	.40	.62	.64	.13	.15	.15	.12	.12	.15	.15	.15	.15	.15	.15	.15	.15	.15	.15	.15	.15	
3 36.57	.22	.37	.30	.25	.20	.33	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	.44	
4 26.26	.16	.11	.15	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	
5 20.48	.34	.46	.37	.40	.33	.40	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	.12	
6 14.79	1.91	1.60	1.60	1.60	1.52	1.60	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	.24	
7 14.22	12.24	13.00	12.24	13.00	12.24	13.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
8 12.54	5.25	6.76	7.54	7.42	6.00	7.42	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
9 10.79	2.11	3.10	2.67	2.75	2.10	2.75	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
10 8.63	2.00	1.87	1.87	1.58	2.22	1.58	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
11 7.52	1.99	1.84	1.84	1.54	1.84	1.54	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
12 8.03	1.71	1.71	1.71	1.54	1.71	1.54	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
13 7.92	1.71	1.71	1.71	1.54	1.71	1.54	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
14 6.87	19.44	19.44	22.94	22.94	22.94	22.94	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
15 5.99	15.68	15.68	15.68	15.68	15.68	15.68	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
16 5.09	10.68	10.68	9.56	9.56	9.56	9.56	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
17 5.63	6.56	6.56	9.15	9.15	9.15	9.15	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
18 5.31	2.04	1.88	1.93	2.15	2.15	2.15	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
19 5.02	.93	1.60	1.23	2.07	2.07	2.07	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
20 4.76	.93	1.60	1.23	2.07	2.07	2.07	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
21 4.53	.26	.41	.56	.47	.47	.47	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
22 4.32	.18	.22	.22	.22	.22	.22	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
23 4.13	.13	.16	.16	.16	.16	.16	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
24 3.95	.14	.18	.12	.11	.11	.11	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
25 3.79	.37	.12	.11	.10	.10	.10	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
26 3.64	.34	.07	.04	.04	.04	.04	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
27 3.51	.03	.02	.03	.03	.03	.03	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
28 3.46	.01	.01	.01	.01	.01	.01	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
29 3.38	.01	.01	.01	.01	.01	.01	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
30 3.32	.01	.00	.01	.00	.00	.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
31 3.25	.00	.00	.00	.00	.00	.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
32 3.19	.00	.00	.00	.00	.00	.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
33 3.13	.00	.00	.00	.00	.00	.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	
34 3.07	.00	.00	.00	.00	.00	.00	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	.14	

APPENDIX C

FOURIER COEFFICIENTS FOR A MIXTURE OF THREE SINUSOIDS

The Fourier Transform of the function:

$$f(t) = A \cos(\sigma t - \phi) \quad (C-1)$$

with

$$\sigma = \frac{2\pi(\hat{m} + \delta)}{N\Delta t}, \quad |\delta| \leq \frac{1}{2}, \quad (C-2)$$

where $1 \ll \hat{m} \ll N$, computed from N values of $f(t)$ evaluated at equal increments of t ; Δt is given by the set of coefficients (Harris, 1974):

$$\begin{aligned} a_m &= \frac{2A \sin \pi \delta \cos(\pi \delta - \phi)}{N} \left[\frac{1}{\tan[\pi(\hat{m} - m + \delta)/N]} + \frac{1}{\tan[\pi(\hat{m} + m + \delta)/N]} \right], \\ b_m &= \frac{2A \sin \pi \delta \sin(\pi \delta - \phi)}{N} \left[\frac{1}{\tan[\pi(\hat{m} - m + \delta)/N]} - \frac{1}{\tan[\pi(\hat{m} + m + \delta)/N]} \right], \\ m &= 1, 2, \dots, \frac{N}{2}. \end{aligned} \quad (C-3)$$

Harris shows that for values of m near $\hat{m}$, and for $\hat{m}$ far removed from 1 and $N/2$,

$$\begin{aligned} a_m &\doteq \frac{A \sin \pi \delta \cos(\phi - \pi \delta)}{\pi(\hat{m} - m + \delta)}, \\ b_m &\doteq \frac{A \sin \pi \delta \sin(\phi - \pi \delta)}{\pi(\hat{m} - m + \delta)}, \quad m = 1, 2, \dots, \frac{N}{2} \end{aligned} \quad (C-4)$$

are good approximations to the coefficients in equation (C-3). Equation (C-4) shows that convergence is slow.

For the special case $\delta = 0$, substitution into equations (C-3) or (C-4) gives:

$$a_m = b_m = 0, \quad m \neq \hat{m},$$

and

$$a_m = b_m = \text{indeterminate for } m = \hat{m}.$$

Use of L' Hospital Rule in equation (C-3) when $\delta \rightarrow 0$, shows that:

$$a_m = A \cos \phi, \quad b_m = A \sin \phi, \quad m = \hat{m}. \quad (C-5)$$

Application of the cosine bell data window,

$$\tilde{f}(n\Delta t) = \frac{1}{2} \left\{ \left[1 - \cos \frac{2\pi n}{N} \right] \right\} f(n\Delta t), \quad n = 1, \dots, N, \quad (C-6)$$

is equivalent to replacing the original sinusoid $f(n\Delta t)$ with the sum of three sinusoids (Harris, 1974), where

$$\begin{aligned} \tilde{f}(n\Delta t) = \frac{A}{2} & \left[2 \cos \left[\frac{2\pi(\hat{m} + \delta)n}{N} - \phi \right] \right. \\ & \left. - \cos \left[\frac{2\pi(\hat{m} - 1 + \delta)n}{N} - \phi \right] - \cos \left[\frac{2\pi(\hat{m} + 1 + \delta)n}{N} - \phi \right] \right]. \quad (C-7) \end{aligned}$$

For $\delta = 0$, and in view of equation (C-5), the Fourier Transform of this modified function will be given by:

$$a_{\hat{m}-1} = a_{\hat{m}+1} = -\frac{A}{4} \cos \phi, \quad b_{\hat{m}-1} = b_{\hat{m}+1} = -\frac{A}{4} \sin \phi$$

and

$$a_{\hat{m}} = \frac{A}{2} \cos \phi, \quad b_{\hat{m}} = \frac{A}{2} \sin \phi$$

with $a_m = b_m = 0$ for all other values of m . Thus, energy appears at three adjacent m values.

Harris (1974) shows that after application of the cosine bell data window, the approximate values of the coefficients are given by:

$$\begin{aligned} a_m & \doteq \frac{A \sin \pi \delta \cos(\phi - \pi \delta)}{2\pi(\hat{m} - m + \delta) [(\hat{m} - m + \delta)^2 - 1]}, \\ b_m & \doteq \frac{A \sin \pi \delta \sin(\phi - \pi \delta)}{2\pi(\hat{m} - m + \delta) [(\hat{m} - m + \delta)^2 - 1]}, \quad m = 1, \dots, \frac{N}{2}. \quad (C-8) \end{aligned}$$

Thus, convergence increases rapidly, and values of the coefficients for $(\hat{m} - m) \geq 3$ may be disregarded.

Equations (C-3), (C-4), and (C-8) imply that

$$\tan(\phi - \pi \delta) = \frac{a_m}{b_m} \quad (C-9)$$

Since δ may be as large as $1/2$, phase values computed from the Finite Fourier Transform may be in error by as much as 90° .

For a simplistic simulation of a wave train, it is sufficient to combine three sinusoids with nearby periods propagating in the same direction. Letting A_i equal the amplitudes and k_i , $i = 1, 2, 3$, the wave numbers, the Fourier Transform of the combination is given by:

$$\begin{aligned} a_m &= \sum_{i=1}^3 \frac{A_i \sin \pi \delta_i \cos(\Phi_i - \pi \delta_i)}{2\pi(\hat{m}_i - m + \delta_i) [(\hat{m}_i - m + \delta_i)^2 - 1]}, \\ b_m &= \sum_{i=1}^3 \frac{A_i \sin \pi \delta_i \sin(\Phi_i - \pi \delta_i)}{2\pi(\hat{m}_i - m + \delta_i) [(\hat{m}_i - m + \delta_i)^2 - 1]}. \end{aligned} \quad (C-10)$$

Nearby periods are attained by setting

$$\Delta_i = (\hat{m}_i - m) \leq 3. \quad (C-11)$$

Let the coordinates of three nearby locations be (x_j, y_j) ; $j = 1, 2, 3$. The only difference among the Fourier Transforms (eq. C-10) arising from wave records at each location is the values of the Φ_i 's. At each location j , the Φ_i values are:

$$\Phi_{ij} = k_i(x_j \cos \alpha + y_j \sin \alpha) - \phi_i, \quad i = 1, 2, 3, \quad (C-12)$$

or

$$\Phi_{ij} = k_i \Omega_j - \phi_i,$$

where

$$\Omega_j = x_j \cos \alpha + y_j \sin \alpha, \quad j = 1, 2, 3. \quad (C-13)$$

Since the three sinusoids are assumed to have nearby periods, let

$$k_1 \doteq k_2 \doteq k_3 = k.$$

Thus,

$$\Phi_{ij} = k \Omega_j - \phi_i.$$

Then, for the wave record at location j :

$$\begin{aligned} a_{mj} &\doteq \sum_{i=1}^3 \frac{A_i \sin \pi \delta_i \cos(k \Omega_j - \pi \delta_i - \phi_i)}{2\pi(\Delta_i + \delta_i) [(\Delta_i + \delta_i)^2 - 1]}, \\ b_{mj} &\doteq \sum_{i=1}^3 \frac{A_i \sin \pi \delta_i \sin(k \Omega_j - \pi \delta_i - \phi_i)}{2\pi(\Delta_i + \delta_i) [(\Delta_i + \delta_i)^2 - 1]}. \end{aligned} \quad (C-14)$$

Let:

$$[i] = 2\pi(\Delta_{\mathcal{L}} + \delta_{\mathcal{L}}) [(\Delta_{\mathcal{L}} + \delta_{\mathcal{L}})^2 - 1] , \quad i = 1, 2, 3 . \quad (C-15)$$

The expanded expression for a_{mj} , after collecting terms in $\cos k\Omega_j$ and $\sin k\Omega_j$, is:

$$\begin{aligned} a_{mj} \doteq & \cos k\Omega_j \left\{ \frac{A_1 \sin \pi\delta_1 \cos(\phi_1 + \pi\delta_1)}{[1]} \right. \\ & + \frac{A_2 \sin \pi\delta_2 \cos(\phi_2 + \pi\delta_2)}{[2]} \\ & \left. + \frac{A_3 \sin \pi\delta_3 \cos(\phi_3 + \pi\delta_3)}{[3]} \right\} \\ & + \sin k\Omega_j \left\{ \frac{A_1 \sin \pi\delta_1 \sin(\phi_1 + \pi\delta_1)}{[1]} \right. \\ & + \frac{A_2 \sin \pi\delta_2 \sin(\phi_2 + \pi\delta_2)}{[2]} \\ & \left. + \frac{A_3 \sin \pi\delta_3 \sin(\phi_3 + \pi\delta_3)}{[3]} \right\} ; \end{aligned}$$

and similarly for b_{mj} :

$$\begin{aligned} b_{mj} \doteq & \sin k\Omega_j \left\{ \frac{A_1 \sin \pi\delta_1 \cos(\phi_1 + \pi\delta_1)}{[1]} \right. \\ & + \frac{A_2 \sin \pi\delta_2 \cos(\phi_2 + \pi\delta_2)}{[2]} \\ & \left. + \frac{A_3 \sin \pi\delta_3 \cos(\phi_3 + \pi\delta_3)}{[3]} \right\} \\ & - \cos k\Omega_j \left\{ \frac{A_1 \sin \pi\delta_1 \sin(\phi_1 + \pi\delta_1)}{[1]} \right. \\ & + \frac{A_2 \sin \pi\delta_2 \sin(\phi_2 + \pi\delta_2)}{[2]} \\ & \left. + \frac{A_3 \sin \pi\delta_3 \sin(\phi_3 + \pi\delta_3)}{[3]} \right\} . \end{aligned}$$

For every narrow-banded wave train, $|\Delta_{\mathcal{L}}| < 3$ in equation (C-15), unpredictable terms are introduced in the expressions for the coefficients

which make the ratio b_m/a_m a poor estimator of the value of the phase of the sinusoid.

The numerators of the terms inside the braces in the above equations for a_{mj} and b_{mj} are at most of order A_i , $i = 1, 2, 3$.

Randomness in the values of δ_i , $i = 1, 2, 3$ and in the phase relationships of the three sinusoids at the origin of coordinates might produce partial cancellations among the terms inside the braces to reduce the resulting error.

Assume for example: $\phi_i = 0$, $i = 1, 2, 3$. The coefficients reduce to:

$$a_{mj} \doteq \frac{1}{2} \cos k\Omega_j \left\{ \frac{A_1 \sin 2\pi\delta_1}{[1]} + \frac{A_2 \sin 2\pi\delta_2}{[2]} + \frac{A_3 \sin 2\pi\delta_3}{[3]} \right\} \\ + \sin k\Omega_j \left\{ \frac{A_1 \sin^2 \pi\delta_1}{[1]} + \frac{A_2 \sin^2 \pi\delta_2}{[2]} + \frac{A_3 \sin^2 \pi\delta_3}{[3]} \right\};$$

similarly, for b_{mj} :

$$b_{mj} \doteq \frac{1}{2} \sin k\Omega_j \left\{ \frac{A_1 \sin 2\pi\delta_1}{[1]} + \frac{A_2 \sin 2\pi\delta_2}{[2]} + \frac{A_3 \sin 2\pi\delta_3}{[3]} \right\} \\ - \cos k\Omega_j \left\{ \frac{A_1 \sin^2 \pi\delta_1}{[1]} + \frac{A_2 \sin^2 \pi\delta_2}{[2]} + \frac{A_3 \sin^2 \pi\delta_3}{[3]} \right\}. \quad (C-16)$$

Letting:

$$L_1 = A_1 \sin 2\pi\delta_1, \quad L_2 = A_1 \sin^2 \pi\delta_1, \\ M_1 = A_2 \sin 2\pi\delta_2, \quad M_2 = A_2 \sin^2 \pi\delta_2, \\ N_1 = A_3 \sin 2\pi\delta_3, \quad N_2 = A_3 \sin^2 \pi\delta_3; \quad (C-17)$$

then:

$$a_{mj} \doteq \frac{1}{2} \cos k\Omega_j \left[\frac{L_1}{[1]} + \frac{M_1}{[2]} + \frac{N_1}{[3]} \right] + \sin k\Omega_j \left[\frac{L_2}{[1]} + \frac{M_2}{[2]} + \frac{N_2}{[3]} \right],$$

and

$$b_{mj} \doteq \frac{1}{2} \sin k\Omega_j \left[\frac{L_1}{[1]} + \frac{M_1}{[2]} + \frac{N_1}{[3]} \right] - \cos k\Omega_j \left[\frac{L_2}{[1]} + \frac{M_2}{[2]} + \frac{N_2}{[3]} \right]. \quad (C-18)$$

Assume further: $A_1 \sim A_2 \sim A_3$ and $|\hat{m}_i - m| = 0$ for $i = 2$ and equal for $i = 1$ and 3 . Since $|\delta| < 1$, the terms $[1]$ and $[3]$ are of

approximately the same magnitude but of opposite signs. Thus, terms involving the products [1] [2] and [2] [3] tend to cancel. Letting $\delta_1 = \delta_2 = \delta_3 = \delta$:

$$\frac{b_{mj}}{a_{mj}} = \frac{\sin k\Omega_j \cdot \sin 2\pi\delta - 2 \cos k\Omega_j \cdot \sin^2 \pi\delta}{\cos k\Omega_j \sin 2\pi\delta + 2 \sin k\Omega_j \sin^2 \pi\delta} .$$

Using the trigonometric identities for the double arc, this expression reduces to:

$$\frac{b_{mj}}{a_{mj}} = \tan (k\Omega_j - \pi\delta) . \quad (C-19)$$

Phase differences between locations will be approximately correct.

APPENDIX D

SPECTRA PLOTS AND COMPUTER OUTPUT FOR SIMULATED OBSERVATIONS

Figures D-1 to D-8 show high-resolution spectra pressure gages 1 to 5 at Pt. Mugu, California.

Figure D-1.

Figure D-2.

Figure D-3.

Figure D-4.

Figure D-5.

Figure D-6.

Figure D-7.

Figure D-8.

3IMULATED MIXED SEA PERIODS(SEC) DIRECTIONS(DEGREES) AMPLITUDES(CM)
 16.75 21. 11.43
 21. 15.24
 21. 15.26
 21. 11.43

LINE PERIOD (SEC)	PRESSURE SPECTRA (50 CM)	DIRECTION (DEGREES FROM SEWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
		1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
41	24.98	00	00	00	00	00	178	183	182	179	179
42	24.58	00	00	00	00	00	177	183	182	179	179
43	23.51	00	00	00	00	00	177	183	183	179	179
44	23.57	00	00	00	00	00	177	184	183	179	179
45	23.26	00	00	00	00	00	176	183	183	179	179
46	22.76	00	00	00	00	00	175	182	183	179	179
47	21.79	00	00	00	00	00	174	182	183	179	179
48	21.33	00	00	00	00	00	173	181	182	179	179
49	20.60	00	00	00	00	00	172	180	181	179	179
50	20.48	00	00	00	00	00	171	179	180	179	179
51	20.08	00	00	00	00	00	169	177	178	178	178
52	19.69	00	00	00	00	00	167	174	173	178	178
53	19.32	00	00	00	00	00	164	169	170	178	178
54	18.96	00	00	00	00	00	161	165	173	177	176
55	18.62	00	00	00	00	00	158	160	167	176	176
56	18.29	00	00	00	00	00	156	158	167	175	176
57	17.96	00	00	00	00	00	152	159	167	173	175
58	17.66	00	00	00	00	00	150	157	166	172	175
59	17.36	00	00	00	00	00	149	156	166	172	175
60	17.06	00	00	00	00	00	147	154	164	171	175
61	16.79	00	00	00	00	00	145	152	162	169	175
62	16.52	00	00	00	00	00	143	150	160	167	175
63	16.25	00	00	00	00	00	141	148	158	164	175
64	16.00	00	00	00	00	00	139	146	156	162	175
65	15.75	00	00	00	00	00	137	144	154	160	175
66	15.52	00	00	00	00	00	135	142	152	158	175
67	15.28	00	00	00	00	00	133	140	150	156	175
68	15.06	00	00	00	00	00	131	138	148	154	175
69	14.84	00	00	00	00	00	129	136	146	152	175
70	14.63	00	00	00	00	00	127	134	144	150	175
71	14.42	00	00	00	00	00	125	132	142	148	175
72	14.22	00	00	00	00	00	123	130	140	146	175
73	14.03	00	00	00	00	00	121	128	138	144	175
74	13.84	00	00	00	00	00	119	126	136	142	175
75	13.65	00	00	00	00	00	117	124	134	140	175
76	13.47	00	00	00	00	00	115	122	132	138	175
77	13.31	00	00	00	00	00	113	120	130	136	175
78	13.13	00	00	00	00	00	111	118	128	134	175
79	12.96	00	00	00	00	00	109	116	126	132	175
80	12.80	00	00	00	00	00	107	114	124	130	175
81	12.64	00	00	00	00	00	105	112	122	128	175
82	12.49	00	00	00	00	00	103	110	120	126	175
83	12.34	00	00	00	00	00	101	108	118	124	175
84	12.19	00	00	00	00	00	99	106	116	122	175
85	12.05	00	00	00	00	00	97	104	114	120	175
86	11.91	00	00	00	00	00	95	102	112	118	175
87	11.77	00	00	00	00	00	93	100	110	116	175
88	11.64	00	00	00	00	00	91	98	108	114	175
89	11.51	00	00	00	00	00	89	96	106	112	175

LINE	PERIOD (SEC)	SIMULATED MIXED SEA	PERIODS(SEC)		DIRECTIONS(DEGREES)		AMPLITUDES(CM)		DIRECTION (DEGREES FROM SEARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
			PRESSURE SPECTRA (30 CM)															
			16.75	21	11.43	12.4	12.5	12.6	12.7	12.8	12.9	13.0	13.1	13.2	13.3	13.4	13.5	13.6
			15.26	15	15.24													
			15.26	-21	11.43													
41	24.98	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
42	24.58	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
43	24.51	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
44	24.27	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
45	22.76	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
46	22.56	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
47	21.53	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
48	21.13	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
49	20.93	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
50	20.48	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
51	20.08	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
52	19.69	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
53	19.32	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
54	18.96	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
55	18.62	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
56	18.29	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
57	17.96	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
58	17.66	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
59	17.36	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
60	17.07	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
61	16.79	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
62	16.52	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
63	16.25	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
64	15.98	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
65	15.75	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
66	15.52	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
67	15.28	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
68	15.06	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
69	14.84	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
70	14.63	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
71	14.42	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
72	14.22	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
73	14.03	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
74	13.84	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
75	13.65	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
76	13.47	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
77	13.30	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
78	13.13	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
79	12.96	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
80	12.80	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
81	12.64	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
82	12.49	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
83	12.34	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
84	12.19	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
85	12.05	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
86	11.91	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
87	11.77	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
88	11.64	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
89	11.51	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

LINE PERIOD (SEC)	SIMULATED MIXED SEA	PERIODS(SEC)			DIRECTIONS(DEGREES)	AMPLITUDES(CM)			DIRECTION (DEGREES FROM SEAWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE																		
		PRESSURE SPECTRA (50 CM)				1-2-3			1-2-4			1-2-5			1-3-4			1-3-5			1-4-5			2-4-5	2-4-5	2-4-5	3-4-5
		15.46 21.4 15.72	18.46 21.4 15.24	11.43 21.4 11.43		1-2-3	1-2-4	1-2-5	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5												
41	28.98	.00	.00	.00	.00	.81	.178	.178	.163	.162	.179	.161	.160	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
42	28.38	.00	.00	.00	.00	.81	.177	.177	.163	.163	.179	.161	.160	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
43	28.11	.00	.00	.00	.00	.80	.177	.177	.163	.163	.179	.160	.159	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
44	28.27	.00	.00	.00	.00	.76	.176	.176	.164	.163	.179	.160	.159	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
45	28.06	.00	.00	.00	.00	.79	.175	.175	.164	.163	.179	.160	.158	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
46	28.26	.00	.00	.00	.00	.80	.174	.174	.163	.163	.179	.160	.158	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
47	28.19	.00	.00	.00	.00	.82	.172	.171	.166	.164	.179	.159	.157	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
48	28.33	.00	.00	.00	.00	.87	.171	.169	.169	.167	.179	.157	.157	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	.179	
49	28.90	.00	.00	.00	.00	.97	.168	.165	.172	.169	.178	.156	.151	.178	.178	.178	.178	.178	.178	.178	.178	.178	.178	.178	.178	.178	
50	28.48	.00	.00	.00	.00	.110	.166	.162	.175	.173	.178	.155	.150	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177	.177	
51	28.08	.00	.00	.00	.00	.133	.163	.157	.177	.178	.177	.155	.149	.176	.176	.176	.176	.176	.176	.176	.176	.176	.176	.176	.176	.176	
52	18.59	.00	.00	.00	.00	.144	.160	.153	.171	.164	.177	.155	.149	.174	.174	.174	.174	.174	.174	.174	.174	.174	.174	.174	.174	.174	
53	18.46	.00	.00	.00	.00	.158	.157	.147	.160	.132	.175	.156	.151	.171	.171	.171	.171	.171	.171	.171	.171	.171	.171	.171	.171	.171	
54	18.22	.00	.00	.00	.00	.158	.155	.143	.152	.105	.174	.156	.154	.168	.168	.168	.168	.168	.168	.168	.168	.168	.168	.168	.168	.168	
55	18.42	.00	.00	.00	.00	.160	.151	.137	.142	.80	.173	.157	.156	.162	.162	.162	.162	.162	.162	.162	.162	.162	.162	.162	.162	.162	
56	18.76	.00	.00	.00	.00	.20	.24	.27	.29	.49	.18	.21	.20	.22	.22	.22	.22	.22	.22	.22	.22	.22	.22	.22	.22	.22	
57	18.66	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
58	18.94	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
59	18.70	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
60	18.52	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
61	18.37	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
62	18.52	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
63	18.25	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
64	18.00	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
65	18.75	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
66	18.52	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
67	18.28	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
68	18.06	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
69	18.44	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
70	18.53	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
71	18.22	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
72	18.22	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
73	18.53	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
74	18.27	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
75	18.65	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
76	18.37	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
77	18.30	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
78	18.13	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
79	18.96	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
80	18.64	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
81	18.24	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
82	18.49	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
83	18.34	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
84	18.19	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
85	18.05	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
86	18.91	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
87	18.77	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
88	18.44	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	
89	18.51	.00	.00	.00	.00	.20	.22	.23	.23	.27	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	.20	.21	

LINE	PERIOD (SEC)	SIMULATED MIXED SEA PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)	DIRECTION (DEGREES FROM REWARD NORMAL)										
					POSITIVE VALUES ARE COUNTERCLOCKWISE										
					1=0	1=1	1=2	1=3	1=4	1=5	1=6	1=7	1=8	1=9	
PRESSURE SPECTRA (100 CM)					1=0	1=1	1=2	1=3	1=4	1=5	1=6	1=7	1=8	1=9	
94	10.89	00	00	00	00	00	00	00	00	00	00	00	00	00	00
95	10.76	00	00	00	00	00	00	00	00	00	00	00	00	00	00
96	10.67	00	00	00	00	00	00	00	00	00	00	00	00	00	00
97	10.54	00	00	00	00	00	00	00	00	00	00	00	00	00	00
98	10.46	00	00	00	00	00	00	00	00	00	00	00	00	00	00
99	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
100	10.24	00	00	00	00	00	00	00	00	00	00	00	00	00	00
101	10.18	00	00	00	00	00	00	00	00	00	00	00	00	00	00
102	10.14	00	00	00	00	00	00	00	00	00	00	00	00	00	00
103	10.09	00	00	00	00	00	00	00	00	00	00	00	00	00	00
104	9.95	00	00	00	00	00	00	00	00	00	00	00	00	00	00
105	9.75	00	00	00	00	00	00	00	00	00	00	00	00	00	00
106	9.66	00	00	00	00	00	00	00	00	00	00	00	00	00	00
107	9.47	00	00	00	00	00	00	00	00	00	00	00	00	00	00
108	9.39	00	00	00	00	00	00	00	00	00	00	00	00	00	00
109	9.30	00	00	00	00	00	00	00	00	00	00	00	00	00	00
110	9.10	00	00	00	00	00	00	00	00	00	00	00	00	00	00
111	9.14	00	00	00	00	00	00	00	00	00	00	00	00	00	00
112	9.14	00	00	00	00	00	00	00	00	00	00	00	00	00	00
113	9.06	00	00	00	00	00	00	00	00	00	00	00	00	00	00
114	8.98	00	00	00	00	00	00	00	00	00	00	00	00	00	00
115	8.98	00	00	00	00	00	00	00	00	00	00	00	00	00	00
116	8.83	00	00	00	00	00	00	00	00	00	00	00	00	00	00
117	8.75	00	00	00	00	00	00	00	00	00	00	00	00	00	00
118	8.68	00	00	00	00	00	00	00	00	00	00	00	00	00	00
119	8.51	00	00	00	00	00	00	00	00	00	00	00	00	00	00
120	8.51	00	00	00	00	00	00	00	00	00	00	00	00	00	00
121	8.46	00	00	00	00	00	00	00	00	00	00	00	00	00	00
122	8.39	00	00	00	00	00	00	00	00	00	00	00	00	00	00
123	8.25	00	00	00	00	00	00	00	00	00	00	00	00	00	00
124	8.25	00	00	00	00	00	00	00	00	00	00	00	00	00	00
125	8.19	31.73	31.65	31.62	31.61	31.60	31.59	31.58	31.57	31.56	31.55	31.54	31.53	31.52	31.51
126	8.13	12.13	12.23	12.25	12.25	12.25	12.25	12.25	12.25	12.25	12.25	12.25	12.25	12.25	12.25
127	8.06	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76
128	8.06	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76	9.76
129	7.94	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49
130	7.88	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49
131	7.72	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49
132	7.72	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49	20.49
133	7.70	11.63	11.63	11.62	11.62	11.62	11.62	11.62	11.62	11.62	11.62	11.62	11.62	11.62	11.62
134	7.64	00	00	00	00	00	00	00	00	00	00	00	00	00	00
135	7.59	00	00	00	00	00	00	00	00	00	00	00	00	00	00
136	7.47	00	00	00	00	00	00	00	00	00	00	00	00	00	00
137	7.47	00	00	00	00	00	00	00	00	00	00	00	00	00	00
138	7.42	00	00	00	00	00	00	00	00	00	00	00	00	00	00
139	7.37	00	00	00	00	00	00	00	00	00	00	00	00	00	00
140	7.37	00	00	00	00	00	00	00	00	00	00	00	00	00	00
141	7.26	00	00	00	00	00	00	00	00	00	00	00	00	00	00
142	7.21	00	00	00	00	00	00	00	00	00	00	00	00	00	00
143	7.16	00	00	00	00	00	00	00	00	00	00	00	00	00	00
144	7.16	00	00	00	00	00	00	00	00	00	00	00	00	00	00
145	7.04	00	00	00	00	00	00	00	00	00	00	00	00	00	00
146	7.04	00	00	00	00	00	00	00	00	00	00	00	00	00	00
147	6.97	00	00	00	00	00	00	00	00	00	00	00	00	00	00

LINE POSITION (SEC)	SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)	DIRECTION (DEGREES FROM STANDARD NORMAL)									
					POSITIVE VALUES ARE COUNTERCLOCKWISE									
					1-2-3									
					1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3
LINE POSITION (SEC)	SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)	DIRECTION (DEGREES FROM STANDARD NORMAL)									
					POSITIVE VALUES ARE COUNTERCLOCKWISE									
					1-2-3									
					1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3	1-2-3
95	10.79	9.00	00	00	00	00	00	00	00	00	00	00	00	00
96	10.79	9.00	00	00	00	00	00	00	00	00	00	00	00	00
97	10.67	9.00	00	00	00	00	00	00	00	00	00	00	00	00
98	10.56	9.00	00	00	00	00	00	00	00	00	00	00	00	00
99	10.56	9.00	00	00	00	00	00	00	00	00	00	00	00	00
100	10.24	9.00	00	00	00	00	00	00	00	00	00	00	00	00
101	10.14	9.00	00	00	00	00	00	00	00	00	00	00	00	00
102	9.99	9.00	00	00	00	00	00	00	00	00	00	00	00	00
103	9.89	9.00	00	00	00	00	00	00	00	00	00	00	00	00
104	9.85	9.00	00	00	00	00	00	00	00	00	00	00	00	00
105	9.75	9.00	00	00	00	00	00	00	00	00	00	00	00	00
106	9.69	9.00	00	00	00	00	00	00	00	00	00	00	00	00
107	9.64	9.00	00	00	00	00	00	00	00	00	00	00	00	00
108	9.49	9.00	00	00	00	00	00	00	00	00	00	00	00	00
109	9.19	9.00	00	00	00	00	00	00	00	00	00	00	00	00
110	9.21	9.00	00	00	00	00	00	00	00	00	00	00	00	00
111	9.14	9.00	00	00	00	00	00	00	00	00	00	00	00	00
112	9.14	9.00	00	00	00	00	00	00	00	00	00	00	00	00
113	9.06	9.00	00	00	00	00	00	00	00	00	00	00	00	00
114	8.96	9.00	00	00	00	00	00	00	00	00	00	00	00	00
115	8.90	9.00	00	00	00	00	00	00	00	00	00	00	00	00
116	8.83	9.00	00	00	00	00	00	00	00	00	00	00	00	00
117	8.74	9.00	00	00	00	00	00	00	00	00	00	00	00	00
118	8.64	9.00	00	00	00	00	00	00	00	00	00	00	00	00
119	8.61	9.00	00	00	00	00	00	00	00	00	00	00	00	00
120	8.51	9.00	00	00	00	00	00	00	00	00	00	00	00	00
121	8.46	9.00	00	00	00	00	00	00	00	00	00	00	00	00
122	8.36	9.00	00	00	00	00	00	00	00	00	00	00	00	00
123	8.31	9.00	00	00	00	00	00	00	00	00	00	00	00	00
124	8.26	9.00	00	00	00	00	00	00	00	00	00	00	00	00
125	8.19	9.00	00	00	00	00	00	00	00	00	00	00	00	00
126	8.14	9.00	00	00	00	00	00	00	00	00	00	00	00	00
127	8.03	9.00	00	00	00	00	00	00	00	00	00	00	00	00
128	8.00	9.00	00	00	00	00	00	00	00	00	00	00	00	00
129	7.94	9.00	00	00	00	00	00	00	00	00	00	00	00	00
130	7.89	9.00	00	00	00	00	00	00	00	00	00	00	00	00
131	7.83	9.00	00	00	00	00	00	00	00	00	00	00	00	00
132	7.76	9.00	00	00	00	00	00	00	00	00	00	00	00	00
133	7.70	9.00	00	00	00	00	00	00	00	00	00	00	00	00
134	7.64	9.00	00	00	00	00	00	00	00	00	00	00	00	00
135	7.53	9.00	00	00	00	00	00	00	00	00	00	00	00	00
136	7.47	9.00	00	00	00	00	00	00	00	00	00	00	00	00
137	7.42	9.00	00	00	00	00	00	00	00	00	00	00	00	00
138	7.31	9.00	00	00	00	00	00	00	00	00	00	00	00	00
139	7.26	9.00	00	00	00	00	00	00	00	00	00	00	00	00
140	7.21	9.00	00	00	00	00	00	00	00	00	00	00	00	00
141	7.16	9.00	00	00	00	00	00	00	00	00	00	00	00	00
142	7.06	9.00	00	00	00	00	00	00	00	00	00	00	00	00
143	7.04	9.00	00	00	00	00	00	00	00	00	00	00	00	00
144	7.01	9.00	00	00	00	00	00	00	00	00	00	00	00	00
145	6.97	9.00	00	00	00	00	00	00	00	00	00	00	00	00
146	6.91	9.00	00	00	00	00	00	00	00	00	00	00	00	00
147	6.87	9.00	00	00	00	00	00	00	00	00	00	00	00	00

69

LINE	PERIOD (SEC)	SIMULATED MIXED SEA	PERIODS(SEC) 7.5-86 7.5-93 7.5-93	DIRECTIONS(DEGREES) 000 000 000	AMPLITUDES(CM) 15.22 15.22 11.03	DIRECTION (DEGREES FROM REARWARD NOMINAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
						PRESSURE SPECTRA (SD CM)									
						1-2-3	1-2-4	1-2-5	1-3-4	1-4-5	2-3-4	2-4-5	3-4-5	2-4-5	3-4-5
98	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
99	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
100	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
101	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
102	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
103	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
104	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
105	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
106	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
107	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
108	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
109	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
110	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
111	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
112	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
113	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
114	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
115	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
116	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
117	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
118	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
119	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
120	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
121	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
122	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
123	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
124	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
125	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
126	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
127	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
128	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
129	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
130	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
131	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
132	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
133	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
134	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
135	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
136	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
137	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
138	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
139	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
140	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
141	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
142	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
143	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
144	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
145	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
146	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00
147	10.34	00	00	00	00	00	00	00	00	00	00	00	00	00	00

SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)			DIRECTION (DEGREES FROM SEAWARD NORMAL)									
			0.16	21.	11.43	1-2.3	1-2.4	1-2.5	1-3.4	1-3.5	1-4.5	2-3.4	2-3.5	2-4.5	3-4.5
	0.16	21.	0.16	21.	11.43										
	7.49	21.	7.49	21.	11.43										
	7.81	21.	7.81	21.	11.43										
PRESSURE SPECTRA															
(30 CH)															
LINE PERIOD															
(SEC)															
117	0.15	0.00	0.00	0.00	0.00	-1.81	-1.83	-1.9	-1.29	-3.0	131	-157	-160	-148	-138
118	0.08	0.00	0.00	0.00	0.00	-1.61	-1.46	-1.9	-1.30	-3.0	132	-157	-160	-148	-138
119	0.01	0.00	0.00	0.00	0.00	-1.61	-1.47	-2.0	-1.33	-3.0	133	-157	-160	-148	-138
120	0.31	0.00	0.00	0.00	0.00	-1.61	-1.50	-1.9	-1.39	-3.0	133	-158	-160	-149	-139
121	0.36	0.00	0.00	0.00	0.00	-1.61	-1.61	-1.8	-1.63	-2.4	126	-160	-161	-150	-142
122	4.36	0.00	0.00	0.00	0.00	-2.0	-1.2	1.72	4	155	-51	19	19	20	20
123	6.33	0.01	0.01	0.01	0.01	-2.0	-1.2	1.72	16	153	-49	20	20	20	20
124	8.26	5.53	5.57	5.50	5.57	-2.1	-2.0	1.66	16	152	-49	20	20	20	20
125	0.16	31.73	31.64	31.78	31.62	-2.1	-2.1	1.66	21	152	-49	21	21	21	21
126	0.13	1.16	1.25	1.14	1.24	-2.1	-2.0	1.66	20	152	-49	20	20	20	20
127	0.06	0.87	0.83	0.85	0.85	-2.1	-2.0	1.66	20	152	-48	20	20	20	20
128	0.00	5.16	5.03	5.23	5.00	-2.1	-2.0	1.66	21	152	-48	21	21	21	21
129	7.84	20.66	20.36	20.85	20.44	-2.1	-2.0	1.66	20	152	-48	20	20	20	20
130	7.84	3.55	3.45	3.54	3.45	-2.1	-2.0	1.62	21	152	-48	21	21	21	21
131	7.82	3.65	3.55	3.70	3.45	-2.1	-2.0	1.62	21	152	-48	21	21	21	21
132	7.76	11.23	11.24	11.13	11.22	-2.0	-2.0	1.63	23	151	-48	21	21	21	21
133	7.70	0.03	0.03	0.03	0.02	-2.0	-2.0	1.63	23	151	-48	21	21	21	21
134	7.64	0.00	0.00	0.00	0.00	-1.9	-1.9	1.62	23	150	-47	22	22	22	22
135	7.59	0.00	0.00	0.00	0.00	-1.9	-1.9	1.61	43	150	-48	22	22	22	22
136	7.43	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	46	150	-48	23	23	23	23
137	7.43	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	46	150	-48	23	23	23	23
138	7.33	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	50	150	-48	23	23	23	23
139	7.33	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	51	150	-48	23	23	23	23
140	7.31	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	51	150	-48	23	23	23	23
141	7.26	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	52	150	-49	22	22	22	22
142	7.26	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	52	150	-49	22	22	22	22
143	7.11	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	53	150	-49	22	22	22	22
144	7.11	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	53	150	-49	22	22	22	22
145	7.06	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	53	150	-49	22	22	22	22
146	7.01	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	53	150	-49	22	22	22	22
147	6.97	0.00	0.00	0.00	0.00	-1.8	-1.8	1.61	53	150	-49	22	22	22	22

LINE PERIOD (SEC)	SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)	DIRECTION (DEGREES FROM SEAWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE									
					1-2-3 1-2-4 1-2-5 1-3-4 1-3-5 1-4-5 2-3-4 2-3-5 2-4-5 3-4-5									
					PRESSURE SPECTRA (80 CM)									
117	0.75	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
118	0.68	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
119	0.61	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
120	0.53	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
121	0.46	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
122	0.39	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
123	0.33	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
124	0.26	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
125	0.19	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
126	0.11	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
127	0.08	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
128	0.04	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
129	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
130	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
131	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
132	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
133	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
134	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
135	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
136	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
137	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
138	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
139	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
140	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
141	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
142	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
143	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
144	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
145	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
146	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
147	0.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CH)	DIRECTION (DEGREES FROM SEWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																				
				1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
	6.12	21.	11.43																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					

SIMULATED MIXED SEA			PERIODS(SEC)			DIRECTIONS(DEGREES)			AMPLITUDES(CM)		
			8.12		21.				11.43		
			7.99		15.				15.24		
			7.93		21.				11.43		
LINE PERIOD (SEC)			PRESSURE SPECTRA (80 CM)			1-2-3 1-2-4 1-2-5 1-3-4 1-3-5 1-4-5 2-3-4 2-3-5 2-4-5 3-4-5			DIRECTION (DEGREES FROM SEAWARD NORMAL) POSITIVE VALUES ARE COUNTERCLOCKWISE		
117	8.75	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
118	8.68	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
119	8.61	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
120	8.53	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
121	8.46	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
122	8.39	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
123	8.33	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
124	8.26	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
125	8.19	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
126	8.13	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
127	8.06	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
128	8.00	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
129	7.94	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
130	7.88	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
131	7.82	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
132	7.76	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
133	7.70	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
134	7.60	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
135	7.59	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
136	7.51	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
137	7.47	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
138	7.42	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
139	7.37	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
140	7.31	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
141	7.26	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
142	7.21	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
143	7.16	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
144	7.11	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
145	7.06	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
146	7.01	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
147	6.97	.00	.00	.00	.00	.00	.00	.00	.00	.00	.00

SIMULATED MIXED SEA			PERIODS(SEC)		DIRECTIONS(DEGREES)		AMPLITUDES(CM)		DIRECTION (DEGREES FROM SEAWARD NORMAL)									
			PRESSURE SPECTRA						POSITIVE VALUES ARE COUNTERCLOCKWISE									
LINE PERIOD									1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
53	19.32	.00	.00	.00	.00	.00	.00	.00	.130	.162	.156	.177	.177	.177	.154	.148	.176	.177
54	18.96	.00	.00	.00	.00	.00	.00	.00	.133	.159	.151	.170	.161	.177	.154	.148	.176	.177
55	18.62	.00	.00	.00	.00	.00	.00	.00	.133	.156	.155	.159	.126	.175	.154	.148	.176	.177
56	18.29	.00	.00	.00	.00	.00	.00	.00	.137	.153	.140	.150	.109	.174	.155	.149	.171	.174
57	17.96	.00	.00	.00	.00	.00	.00	.00	.139	.149	.132	.139	.126	.172	.151	.149	.166	.170
58	17.66	.00	.00	.00	.00	.00	.00	.00	.139	.144	.135	.149	.109	.174	.151	.149	.159	.162
59	17.36	.00	.00	.00	.00	.00	.00	.00	.139	.144	.135	.149	.109	.174	.151	.149	.159	.162
60	17.07	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
61	16.79	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
62	16.52	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
63	16.25	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
64	16.00	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
65	15.75	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
66	15.52	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
67	15.28	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
68	15.06	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
69	14.84	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
70	14.63	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
71	14.42	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
72	14.22	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
73	14.03	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
74	13.84	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
75	13.65	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
76	13.47	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
77	13.29	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
78	13.13	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
79	12.96	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
80	12.80	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
81	12.64	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162
82	12.49	.00	.00	.00	.00	.00	.00	.00	.135	.144	.135	.149	.109	.174	.151	.149	.159	.162

LINE PERIOD	SIMULATED MIXED SEA	PERIODS(SEC)	DIRECTIONS(DEGREES)	AMPLITUDES(CM)	DIRECTION (DEGREES FROM SEAWARD NORMAL)									
					POSITIVE VALUES ARE COUNTERCLOCKWISE									
					1-2-3	1-2-4	1-2-5	1-3-4	1-3-5	1-4-5	2-3-4	2-3-5	2-4-5	3-4-5
53	19.12	.00	.00	.00	.125	.142	.155	.178	.178	.177	.154	.147	.176	.177
54	18.66	.00	.00	.00	.140	.159	.150	.170	.162	.177	.154	.146	.174	.174
55	18.42	.00	.00	.00	.151	.155	.143	.158	.125	.175	.154	.147	.170	.174
56	18.29	.00	.00	.00	.155	.152	.138	.149	.96	.174	.154	.148	.165	.170
57	17.96	.00	.00	.00	.157	.147	.127	.138	.74	.172	.150	.145	.155	.160
58	17.66	.00	.00	.00	.109	.97	.69	.95	.56	.119	.87	.58	.44	.59
59	17.36	.00	.00	.00	.11	.13	.15	.16	.34	.8	.8	.8	.10	.10
60	17.07	.01	.01	.01	.12	.12	.13	.14	.17	.11	.11	.11	.12	.12
61	16.79	.573	5.77	5.78	.11	.11	.11	.11	.11	.11	.11	.11	.11	.11
62	16.52	31.72	31.64	31.60	.10	.10	.10	.10	.10	.10	.10	.10	.10	.10
63	16.25	32.42	31.41	32.27	.15	.15	.15	.15	.15	.15	.15	.15	.15	.15
64	16.00	9.79	11.23	10.53	.14	.13	.13	.13	.13	.13	.14	.14	.13	.13
65	15.75	6.09	8.04	6.03	.39	.41	.40	.42	.42	.41	.41	.40	.41	.42
66	15.52	10.11	10.25	10.17	.31	.31	.31	.31	.31	.31	.31	.31	.31	.31
67	15.24	.04	.03	.03	.24	.27	.27	.27	.26	.27	.28	.28	.27	.27
68	15.06	.00	.00	.00	.27	.24	.24	.24	.21	.18	.24	.25	.24	.23
69	14.79	.00	.00	.00	.38	.36	.36	.36	.35	.34	.34	.35	.34	.33
70	14.53	.00	.00	.00	.34	.34	.34	.34	.34	.34	.34	.34	.34	.34
71	14.22	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
72	13.93	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
73	13.64	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
74	13.35	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
75	13.05	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
76	12.77	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
77	12.50	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
78	12.23	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
79	11.96	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
80	11.69	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
81	11.42	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40
82	11.14	.00	.00	.00	.40	.40	.40	.40	.40	.40	.40	.40	.40	.40

APPENDIX E

HIGH-RESOLUTION SPECTRA FOR FIELD WAVE DATA

Figures E-1 to E-44 show high-resolution spectra for pressure gages 1 to 5 at Pt. Mugu, California. Date and significant wave height are indicated for each figure.

Figure E-1. Significant wave height 93.6 centimeters (3.1 feet), 10 April 1970, 2206 hours.

Figure E-2. Significant wave height 84.3 centimeters (2.8 feet), 20 April 1970, 0928 hours.

Figure E-3. Significant wave height 81.0 centimeters (2.7 feet), 20 April 1970, 1228 hours.

Figure E-4. Significant wave height 105.3 centimeters (3.5 feet), 21 April 1970, 0028 hours.

Figure E-5. Significant wave height 95.2 centimeters (3.1 feet), 21 April 1970, 0229 hours.

Figure E-6. Significant wave height 100.7 centimeters (3.4 feet), 21 April 1970, 0929 hours.

Figure E-7. Significant wave height 94.7 centimeters (3.1 feet), 21 April 1970, 1229 hours.

Figure E-8. Significant wave height 113.8 centimeters (3.7 feet), 21 April 1970, 1829 hours.

Figure E-9. Significant wave height 85.1 centimeters (2.8 feet), 21 April 1970, 2129 hours.

Figure E-10. Significant wave height 109.3 centimeters (3.6 feet),
10 June 1970, 1421 hours.

Figure E-11. Significant wave height 117.9 centimeters (3.9 feet), 10 June 1970, 1731 hours.

Figure E-12. Significant wave height 113.1 centimeters (3.7 feet), 10 June 1970, 2041 hours.

Figure E-13. Significant wave height 87.5 centimeters (2.9 feet),
10 June 1970, 2351 hours.

Figure E-14. Significant wave height 93.3 centimeters (3.1 feet), 11 June 1970, 0301 hours.

Figure E-15. Significant wave height 81.0 centimeters (2.7 feet), 11 June 1970, 0631 hours.

Figure E-16. Significant wave height 88.6 centimeters (2.9 feet), 11 June 1970, 0942 hours.

Figure E-17. Significant wave height 71.0 centimeters (2.3 feet), 24 June 1970, 0906 hours.

Figure E-18. Significant wave height 69.3 centimeters (2.3 feet),
24 June 1970, 1206 hours.

Figure E-19. Significant wave height 79.5 centimeters (2.6 feet), 24 June 1970, 1506 hours.

Figure E-20. Significant wave height 72.5 centimeters (2.4 feet),
24 June 1970, 1807 hours.

Figure E-21. Significant wave height 70.1 centimeters (2.3 feet),
25 June 1970, 0007 hours.

Figure E-22. Significant wave height 76.9 centimeters (2.5 feet),
25 June 1970, 0307 hours.

Figure E-23. Significant wave height 66.7 centimeters (2.2 feet), 25 June 1970, 1808 hours.

Figure E-24. Significant wave height 70.3 centimeters (2.3 feet), 25 June 1970, 2108 hours.

Figure E-25. Significant wave height 61.2 centimeters (2.0 feet), 26 June 1970, 1758 hours.

Figure E-26. Significant wave height 79.7 centimeters (2.6 feet), 26 June 1970, 2358 hours.

gure E-27. Significant wave height 92.3 centimeters (3.0 feet),
28 June 1970, 2010 hours.

Figure E-28. Significant wave height 83.2 centimeters (2.7 feet), 28 June 1970, 2310 hours.

Figure E-29. Significant wave height 78.7 centimeters (2.6 feet), 29 June 1970, 0510 hours.

Figure E-30. Significant wave height 64.0 centimeters (2.1 feet), 16 November 1970, 1607 hours.

Figure E-31. Significant wave height 80.9 centimeters (2.7 feet), 16 November 1970, 1907 hours.

Figure E-32. Significant wave height 63.0 centimeters (2.1 feet), 17 November 1970, 0407 hours.

Figure E-33. Significant wave height 74.6 centimeters (2.4 feet), 16 December 1970, 1700 hours.

Figure E-34. Significant wave height 95.3 centimeters (3.1 feet), 16 December 1970, 2000 hours.

Figure E-35. Significant wave height 85.3 centimeters (2.8 feet), 16 December 1970, 2300 hours.

Figure E-36. Significant wave height 90.9 centimeters (3.0 feet), 17 December 1970, 0200 hours.

Figure E-37. Significant wave height 103.5 centimeters (3.4 feet), 17 December 1970, 0500 hours.

Figure E-38. Significant wave height 120.7 centimeters (4.0 feet), 17 December 1970, 0800 hours.

Figure E-39. Significant wave height 97.4 centimeters (3.2 feet),
17 December 1970, 1044 hours.

Figure E-40. Significant wave height 93.4 centimeters (3.1 feet), 17 December 1970, 1344 hours.

Figure E-41. Significant wave height 91.2 centimeters (3.0 feet), 17 December 1970, 1644 hours.

Figure E-42. Significant wave height 108.1 centimeters (3.5 feet), 17 December 1970, 1944 hours.

Figure E-43. Significant wave height 71.5 centimeters (2.3 feet), 18 December 1970, 0445 hours.

Figure E-44. Significant wave height 66.9 centimeters (2.2 feet),
18 December 1970, 0745 hours.

<p>Esteve, Dinorah C. Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977. 123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7) Bibliography: p. 32. A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains. 1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.</p> <p>TC203 .U581tp no. 77-7 627</p>	<p>Esteve, Dinorah C. Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977. 123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7) Bibliography: p. 32. A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains. 1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.</p> <p>TC203 .U581tp no. 77-7 627</p>
<p>Esteve, Dinorah C. Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977. 123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7) Bibliography: p. 32. A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains. 1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.</p> <p>TC203 .U581tp no. 77-7 627</p>	<p>Esteve, Dinorah C. Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977. 123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7) Bibliography: p. 32. A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains. 1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.</p> <p>TC203 .U581tp no. 77-7 627</p>

Esteve, Dinorah C.

Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977.
123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7)

Bibliography: p. 32.

A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains.

1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.

TC203

.U581tp

no. 77-7

627

Esteve, Dinorah C.

Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977.
123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7)

Bibliography: p. 32.

A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains.

1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.

TC203

.U581tp

no. 77-7

627

Esteve, Dinorah C.

Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977.
123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7)

Bibliography: p. 32.

A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains.

1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.

TC203

.U581tp

no. 77-7

627

Esteve, Dinorah C.

Evaluation of the computation of wave direction with three-gage arrays / by Dinorah C. Esteve. - Fort Belvoir, Va. : U.S. Coastal Engineering Research Center, 1977.
123 p. : ill. (Technical paper - U.S. Coastal Engineering Research Center ; no. 77-7)

Bibliography: p. 32.

A description of the collection and analyses of data obtained with an array of five pressure sensors near Pt. Mugu, California, is presented. The 10 three-gage arrays possible with five gages are used to compare redundant values of the direction of wave propagations. The dependence of directional determination on array orientation relative to incident wave direction and wavelength at the array site is revealed by calculations based on simulated narrow-banded wave trains.

1. Waves. 2. Wave propagation. 3. Wave direction. 4. Pt. Mugu, Calif. I. Title. II. Series: U.S. Coastal Engineering Research Center. Technical paper no. 77-7.

TC203

.U581tp

no. 77-7

627