DEPARTMENT OF THE NAVY

HYDROMECHANICS

○

EVALUATION OF STRESSES IN WEB-STIFFENED
CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM
EXTERNAL PRESSURE

AERODYNAMICS

by

James A. Nott and Gerald D. Ward

STRUCTURAL
MECHANICS

○

Distribution of this Document is Unlimited

APPLIED
MATHEMATICS

○

STRUCTURAL MECHANICS LABORATORY
RESEARCH AND DEVELOPMENT REPORT

LOGISTICS AND
OPERATION

September 1965

Report 2092

6C
1
103
10-2092

DENCO

MBL/WHOI

0 0301 0037633 1

EVALUATION OF STRESSES IN WEB-STIFFENED
CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM
EXTERNAL PRESSURE

by

James A. Nott and Gerald D. Ward

Distribution of this Document is Unlimited

September 1965

Report 2092
S-F013 03 02
Task 1956

TABLE OF CONTENTS

	Page
ABSTRACT	1
ADMINISTRATIVE INFORMATION	1
INTRODUCTION	1
DESCRIPTION OF MODELS	2
INSTRUMENTATION AND TEST PROCEDURE	3
TEST RESULTS	3
DISCUSSION	3
CONCLUSION	4
REFERENCES	13

LIST OF FIGURES

	Page
Figure 1 - Model Dimensions	5
Figure 2 - SER Models after Instrumentation	5
Figure 3 - Circumferential Strains on Outer Surface of Outside Shell	6
Figure 4 - Circumferential Strains on Inner Surface of Outside Shell	7
Figure 5 - Circumferential Strains on Outer Surface of Inside Shell	8
Figure 6 - Circumferential Strains on Inner Surface of Inside Shell	8
Figure 7 - Longitudinal Strains on Outer Surface of Outside Shell	9
Figure 8 - Longitudinal Strains on Inner Surface of Outside Shell	10
Figure 9 - Longitudinal Strains on Outer Surface of Inside Shell	11
Figure 10 - Longitudinal Strains on Inner Surface of Inside Shell	12

ABSTRACT

Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.

ADMINISTRATIVE INFORMATION

This investigation was conducted under the sponsorship of the Bureau of Ships, Code 442, Project No. S-F013 03 02, Task 1956.

INTRODUCTION

In recent years, the Navy has shown great interest in the exploration of the depths of the ocean by means of deep-diving manned submarines. Since the pressure hulls of these submarines are weight critical and often involve the use of thick plates, new types of structures are being investigated to reduce fabrication difficulties and to produce hulls with improved strength-to-weight ratio characteristics. One of these structures is a cylindrical sandwich shell consisting of two concentric cylinders connected by annular webs; this type is illustrated in Figure 1.

To evaluate the structural strength of a cylindrical sandwich shell, the locations and magnitudes of maximum stresses must be determined. Analyses for stress distribution in sandwich shells loaded under external hydrostatic pressure were carried out in References 1 and 2.* The maximum stresses occur in the shells at locations next to the webs and midway between adjacent webs. The stresses in these locations are of interest for the purposes of structural design. A graphical analysis for determining

* References are listed on page 13.

these stresses is also shown in Reference 2. From the stresses obtained by use of this analysis,² theoretical strains can be computed and compared directly with observed data.

To evaluate the theoretical analysis, four sandwich-type models were fabricated from epoxy resin and tested under external hydrostatic pressure. Strains were recorded at locations next to the webs and midway between the two webs on both outside and inside shells. A longitudinal strain distribution along a web spacing was also measured in one model. This report presents the experimental strains and a comparison of observed and theoretical values.

DESCRIPTION OF MODELS

Four models, designated SER-1, SER-2, SER-3, and SER-4, were fabricated from epoxy resin. The composition of the epoxy resin was 50 percent Versamid 125 and 50 percent Epon 828. A sandwich-type configuration for the models was constructed by joining a series of channel-shaped rings together. These rings were individually formed by pouring liquid resin into a mold, allowing the resin to harden at room temperature for 24 hr, and then post curing the rings in an oven for 8 hr at a temperature of 130 F. Each ring was then machined to the final required dimensions. The dimensions of these rings are shown in Figure 1.

Specimens were made to determine the material properties of the epoxy resin. A Young's modulus of 328,000 psi and a Poisson's ratio of 0.4 were determined from separate tests using a compressometer, deflectometer, and a Tuckerman optical strain gage. These values were used for determining the theoretical strains presented in this report.

The design of the four models was oriented to study the effects of shell lengths on stress distributions in the sandwich shells. The basic design of the shell thicknesses and the radii was fashioned after a geometry for a proposed deep-diving oceanographic hull structure.³ On each of the four models, the outside radius was 5.40 in., the inside radius was 4.11 in., the outside and inside shell thicknesses were 0.163 in., and the web thickness was 0.138 in. Only the web spacing in the four models varied. The spacings (dimension L_f shown in Figure 1) were 0.75 in. for Model SER-1, 1.00 in. for Model SER-2, 1.25 in. for Model SER-3, and 1.50 in. for Model SER-4.

INSTRUMENTATION AND TEST PROCEDURE

Each model was instrumented with foil-type strain gages 0.063 in. in length. These gages were located on the two shells of each model in areas of critical stress. The middle ring (Ring 5) on each model was instrumented at locations next to the web and midway between adjacent webs on the 0- and 180-deg orientation. Check points were instrumented at locations midway between the webs on an adjacent ring (Ring 6). Additional gages were also placed on the outside surfaces of the models next to the webs at the 45-, 90-, and 135-deg orientations on Ring 5. Model SER-2 was instrumented with additional longitudinal gages covering the area between midbay and the web juncture. After the models were instrumented, the rings were bonded together with the same type of epoxy resin used in the models.

Figure 2 shows the four models before testing. The models were tested hydrostatically in a pressure tank to obtain elastic strain data. Two pressure runs were made on each model to a pressure of 100 psi, and strains were read at each 10-psi increment.

TEST RESULTS

The strain recordings obtained during the second run of each test were used to compute strain sensitivities. These strains were plotted as a function of x/ℓ (where x is the distance from the web to the center of the strain gage and ℓ is the unsupported length of the bay) and are shown in Figures 3 through 10. The solid line represents theoretical strains computed by utilizing Reference 2. The dotted vertical lines in these figures represent the fillet at the intersection of the web and shell.

DISCUSSION

The primary purpose of this investigation was to establish experimental verification for the analysis of deformations in web-stiffened sandwich cylinders.

In general, excellent agreement was obtained as shown in Figures 3 through 10. Data on the longitudinal strain gradient between webs provided by the additional longitudinal gages on SER-2 agreed well with the theoretical values.

The largest discrepancies occurred at the intersection of the shell and web where the fillet was located. This fillet (Figure 1) was incorporated to reduce the effects of shear and possible stress concentrations due to undercutting or voids that could have developed during fabrication. Observation of the experimental strains suggested that a portion of the fillet acted as a stiffener. This effect is less noticeable or negligible on the two models with longer bay lengths.

CONCLUSION

Theoretical analysis as given in Reference 2 will adequately predict the elastic axisymmetric behavior in web-stiffened cylindrical sandwich shells subjected to hydrostatic pressure.

MODEL	LENGTH
MODEL	L_f (IN)
SER-1	0.75
SER-2	1.00
SER-3	1.25
SER-4	1.50

Figure 1 - Model Dimensions

Figure 2 - SER Models after Instrumentation

Figure 3 - Circumferential Strains on Outer Surface of Outside Shell

Figure 4 - Circumferential Strains on Inner Surface of Outside Shell

Figure 5 - Circumferential Strains on Outer Surface of Inside Shell

Figure 6 - Circumferential Strains on Inner Surface of Inside Shell

Figure 7 - Longitudinal Strains on Outer Surface of Outside Shell

Figure 8 - Longitudinal Strains on Inner Surface of Outside Shell

Figure 9 - Longitudinal Strains on Outer Surface of Inside Shell

Figure 10 - Longitudinal Strains on Inner Surface of Inside Shell

REFERENCES

1. Pulos, John G., "Axisymmetric Elastic Deformation and Stresses in a Web-Stiffened Sandwich Cylinder under External Hydrostatic Pressure," David Taylor Model Basin Report 1543 (Nov 1961).
2. Nott, James A., "Graphical Analysis for Maximum Stresses in Sandwich Cylinders under External Uniform Pressure," David Taylor Model Basin Report 1817 (May 1964).
3. Hom, Kenneth and Blumenberg, William F., "Hydrostatic Tests of Structural Models for Preliminary Design of a Web-Stiffened Sandwich Pressure Hull," David Taylor Model Basin Report 1763 (Sep 1963).

INITIAL DISTRIBUTION

Copies

14

CHBUSHIPS

- 2 Sci & Res Sec (Code 442)
- 1 Lab Mgt (Code 320)
- 3 Tech Lib (Code 210L)
- 1 Ships Res Br (Code 341)
- 1 Appli Sci Br (Code 342)
- 1 Prelim Des Br (Code 420)
- 1 Prelim Des Sec (Code 421)
- 1 Ship Protec (Code 423)
- 1 Hull Des Br (Code 440)
- 1 Hull Struc Sec (Code 443)
- 1 Sub Br (Code 525)

1 CHONR, Head Struc Mech (Code 439)

1 CNO (Op 07TB)

1 CDR, USNOL

1 CDR, USNRL (2027)

1 CDR, USNOTS, China Lake

1 CO, USNUOS

1 CO, USNUSL

1 CHBUWEPS, SP-001

20 CDR, DDC

2 NAVSHIPYD PTSMH

1 NAVSHIPYD MARE

1 NAVSHIPYD CHSN

1 NAVSHIPYD NY

1 USNASL

1 SUPSHIP, Groton

1 Elec Boat Div, Genl Dyn Corp

1 SUPSHIP, Newport News

1 NNSB & DD Co

1 SUPSHIP, Pascagoula

1 DIR DEF R & E
Attn: Tech Lib

1 CO, USNROTC & NAVADMINU, MIT

1 O in C, PGSCOL, Webb

1 DIR, APL, Univ of Wash, Seattle

Copies

1

NAS, Attn: Comm on
Undersea Warfare

1

DIR, WHOI

1

Dr. R. DeHart, SWRI

2

Prof. J. Kempner,
Brooklyn Polytechnic Inst

1

Mr. J. L. Mershon, AEC

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)		2a. REPORT SECURITY CLASSIFICATION	
David Taylor Model Basin		Unclassified	
		2b. GROUP	
3. REPORT TITLE			
Evaluation of Stresses in Web-Stiffened Cylindrical Sandwich Shells Subjected to Uniform External Pressure			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)			
5. AUTHOR(S) (Last name, first name, initial)			
Nott, James A. Ward, Gerald D.			
6. REPORT DATE		7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
September 1965		15	3
8a. CONTRACT OR GRANT NO.		9a. ORIGINATOR'S REPORT NUMBER(S)	
b. PROJECT NO. S-F013 03 02		2092	
c. Task 1956		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.			
10. AVAILABILITY/LIMITATION NOTICES			
No Limitation			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY	
		Bureau of Ships Department of Navy	
13. ABSTRACT			
<p>Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.</p>			

14.	KEY WORDS	LINK A		LINK B		LINK C	
		ROLE	WT	ROLE	WT	ROLE	WT
	Sandwich Construction Web-Stiffened Sandwich External Hydrostatic Pressure Stresses in Sandwich Cylinders Concentric Cylinders						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

<p>David Taylor Model Basin. Report 2092.</p> <p>EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.</p> <p>UNCLASSIFIED</p> <p>Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.</p>	<p>1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses</p> <p>2. Cylindrical shells (Stiffened)--Sandwich construction--Annular web stiffeners</p> <p>3. Cylindrical shells (Stiffened)--Stresses--Evaluation</p> <p>4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation</p>
<p>David Taylor Model Basin. Report 2092.</p> <p>EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.</p> <p>UNCLASSIFIED</p> <p>Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.</p>	<p>1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses</p> <p>2. Cylindrical shells (Stiffened)--Sandwich construction--Annular web stiffeners</p> <p>3. Cylindrical shells (Stiffened)--Stresses--Evaluation</p> <p>4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation</p>
<p>David Taylor Model Basin. Report 2092.</p> <p>EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.</p> <p>UNCLASSIFIED</p> <p>Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.</p>	<p>1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses</p> <p>2. Cylindrical shells (Stiffened)--Sandwich construction--Annular web stiffeners</p> <p>3. Cylindrical shells (Stiffened)--Stresses--Evaluation</p> <p>4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation</p>

- I. Nott, James A.
 - II. Ward, Gerald D.
 - III. S-F013 03 02
-

- I. Nott, James A.
 - II. Ward, Gerald D.
 - III. S-F013 03 02
-

- I. Nott, James A.
 - II. Ward, Gerald D.
 - III. S-F013 03 02
-

- I. Nott, James A.
 - II. Ward, Gerald D.
 - III. S-F013 03 02
-

David Taylor Model Basin. Report 2092.

EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.

UNCLASSIFIED

Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.

1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses

2. Cylindrical shells (Stiffened)--Sandwich construction--

Annular web stiffeners

3. Cylindrical shells (Stiffened)--

Stresses--Evaluation

4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation

David Taylor Model Basin. Report 2092.

EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.

UNCLASSIFIED

Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.

1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses

2. Cylindrical shells (Stiffened)--Sandwich construction--

Annular web stiffeners

3. Cylindrical shells (Stiffened)--

Stresses--Evaluation

4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation

David Taylor Model Basin. Report 2092.

EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.

UNCLASSIFIED

Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.

1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses

2. Cylindrical shells (Stiffened)--Sandwich construction--

Annular web stiffeners

3. Cylindrical shells (Stiffened)--

Stresses--Evaluation

4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation

David Taylor Model Basin. Report 2092.

EVALUATION OF STRESSES IN WEB-STIFFENED, CYLINDRICAL SANDWICH SHELLS SUBJECTED TO UNIFORM EXTERNAL PRESSURE, by James A. Nott and Gerald D. Ward. Sep 1965. ii, 15p., illus., graphs, refs.

UNCLASSIFIED

Four cylindrical web-stiffened sandwich models were tested under external hydrostatic pressure. Experimental strains were recorded on both outside and inside shells and compared with theoretical strains computed from existing formula developed at the David Taylor Model Basin. The differences between experimental and theoretical results were within the range of experimental error.

1. Cylindrical shells (Stiffened)--Sandwich construction--Stresses

2. Cylindrical shells (Stiffened)--Sandwich construction--

Annular web stiffeners

3. Cylindrical shells (Stiffened)--

Stresses--Evaluation

4. Cylindrical shells (Stiffened)--Hydrostatic pressure--Evaluation

I. Nott, James A.
II. Ward, Gerald D.
III. S-F013 03 02

I. Nott, James A.
II. Ward, Gerald D.
III. S-F013 03 02

I. Nott, James A.
II. Ward, Gerald D.
III. S-F013 03 02

I. Nott, James A.
II. Ward, Gerald D.
III. S-F013 03 02