DEPTH REGULATION OF LOWERED OCEANOGRAPHIC EQUIPMENT

Describes an experimental sensor and winch control equipment that eliminates most of the unwanted vertical motion of the suspending cable

C. J. Shipek and E. C. Evans • Development Report 1215 • 27 March 1964
U. S. NAVY ELECTRONICS LABORATORY, SAN DIEGO, CALIFORNIA 92152 • A BUREAU OF SHIPS LABORATORY

TK
7855
105
no. 1215

STOCK AVAILABLE AT OFFICE OF TECHNICAL SERVICES
DEPARTMENT OF COMMERCE
WASHINGTON 25, D. C.

THE PROBLEM

Investigate Navy problems in sea floor oceanography through suitably devised means, methods, and equipment. Specifically, develop a method for controlling the depth of deep-sea cameras and other oceanographic equipment lowered from floating platforms.

RESULTS

1. An experimental, low-cost, depth regulation equipment has been developed. It consists of a bellows-type depth sensor together with phase and power amplifiers, servo units, and hoist-train equipment previously installed on USS MARYSVILLE (EPCER 857).

2. Dockside tests of the equipment with a small portable electric winch were successful. They indicated that up to 85 per cent of unwanted vertical wire motion can be eliminated when lowering oceanographic devices from floating platforms.

3. Sea tests were not attempted because the sensor and the phase and power amplifiers had not been constructed for normal shipboard use.

RECOMMENDATIONS

1. Investigate the possibility of adapting standard U. S. Navy hoist-train servo systems to depth regulation equipment, in particular on oceanographic winches.

MBL/WHOI

0 0301 0040546 0

2. Investigate the application of depth regulation and dynamic stress control equipment to various types of military operations requiring the lowering and deep towing of underwater devices.

3. Redesign and package the experimental equipment to provide a portable prototype depth regulator capable of being installed on any standard hydrographic winch for ship-board use. Perform tests under rough sea conditions to substantiate the value of depth regulation.

4. If use of the depth regulator proves successful at sea, install a depth regulator on the dredging winch of the AGOR 5 (USNS DAVIS). This would facilitate the safe handling of heavy transducers and of the NEL Type VII Deep Sea Camera and Survey System, and also make it possible through accurate lens-to-target control to obtain a continuous stereophotographic record of the sediment-water interface.

ADMINISTRATIVE INFORMATION

Work was performed under SR 004 03 01, Task 0539 (NEL L4-1) during the period September 1961 to May 1963. The report was approved for publication 27 March 1964.

The equipment described is covered by U. S. Patent No. 3,088,710 dated 7 May 1963, issued to the authors (see Patent Gazette, Vol. 790, No. 1, General and Mechanical, pages 187-188).

The authors wish to thank E. C. Buffington, E. L. Hamilton, E. C. LaFond, and G. H. Curl for reviewing the manuscript.

CONTENTS

THE PROBLEM OF DEPTH CONTROL... *page* 5

THE NEL DEPTH REGULATION EQUIPMENT... 8

 Description... 8

 Operational Factors... 11

EVALUATION... 12

DISCUSSION AND CONCLUSIONS... 13

ILLUSTRATIONS

1 Ship motion... *page* 5

2 Oceanographic winch with depth regulation equipment... 9

3 Schematic of depth regulation equipment... 9

4 Depth sensor mechanical details... 10

5 Depth sensor location and development of error signal... 10

6 General depth control relationships... 12

THE PROBLEM OF DEPTH CONTROL

The collection of oceanographic data often requires that underwater equipment be maintained at a constant height above the sea floor or towed at a constant depth below the sea surface level. Measurements of temperature and light intensity, collection of water samples, acoustic ranging and listening with lowered transducers, recordings of wave movement, and underwater photography are some of the operations that require depth regulation.

Varying sea surface conditions, however, impose great difficulty in maintaining depth control. The wind-stirred surface of the ocean causes ships to roll, pitch, yaw, surge, sway, and heave. Figure 1 (adapted from a sketch by R. Marra¹) shows how wave action moves a vessel.

Figure 1. Ship motion.

1. Pearlman, M. D., "Waves, Ships and Seaworthiness," Sea Frontiers, v. 9, p. 310-316, Christmas 1963

Many attempts have been made in the past to dampen such ship motion for purposes of personal comfort, military operations, and scientific research. Bilge keels, gyro stabilizers, hydraulic systems, flow tanks, and mechanical devices have been used to lessen the effects of roll and pitch. But heave of the vessel itself, caused by the periodic passing of wave troughs and crests, has never been appreciably reduced.

In a different approach, efforts have been made, and some with moderate success, to remove or reduce excessive pull or tension changes in wire lowering rope. Spring accumulators and hydraulic pistons mounted on fair leads and head sheaves, air systems, and accelerometers have been employed by oceanographers and engineers to provide constant wire tension in many marine operations. None of these attempts has been 100 per cent successful. Accumulators and hydraulic pistons have only dampened the resultant overload strains and movements to some degree. Differential systems employing compressed air springs and sheaves have been defeated by friction, phasing, and timing, and other systems by cost, weight, and size.

A particularly urgent need exists for a simple, effective, and almost frictionless device to provide depth control of deep-sea cameras. These cameras are self-contained units that are lowered to specific distances above the sea floor which they photograph at preset time intervals while being towed by drifting platforms (vessels). Camera lenses and electronic light sources are limited to short distances when used underwater because of the strong absorption and scattering of light by water and suspended particles.² To obtain good color rendition and sharp focus, it is necessary to shoot close-ups at carefully controlled

2. Schenck, H., Jr. and Kendall, H., Underwater Photography, Cornell Maritime Press, 1954

target distances. To add to the optical problems caused by the water itself, the heave of the vessel lowering the camera to a position near the sea floor promotes erratic and sometimes violent depth changes. Up-and-down movements of the lowered cameras in excess of 12 feet are not uncommon, and surges up to 20 feet and more are possible during heavy sea surface action. The roll, pitch, yaw, and heave imposed on a surface vessel by wave motion often combine to produce a movement greater than the depth of focus of even the best wide-angle lenses and greater than the target distances desired.

To recapitulate, depth control is needed for increased safety and efficiency in sea floor photography and in other operations, in all but the calmest seas. For these reasons the Navy Electronics Laboratory undertook the development of the depth regulation equipment described in this report. The equipment provides automatic and high speed winch control regardless of the intensity, timing, and shape of the waves. The effects of heave are almost eliminated, and the camera tends to remain at a constant depth despite the changing depth of the lowering platform, the extent of surface wave penetration, the relative location of the depth sensor with respect to the lowered object, the weight and length of wire rope payed out from the winch drum, and the weight and shape of the lowered object.

The depth regulation equipment not only minimizes the effect of ship motion, but reduces the chance of damage to the wire and oceanographic equipment and makes possible the collection of scientific data unobtainable with older deep-sea winches. Lowering wires are kept under constant tension well below the region of overload, and should therefore last longer.

THE NEL DEPTH REGULATION EQUIPMENT

Description

The NEL depth regulation equipment (figs. 2 and 3) is based on a principle previously neglected in attempts to stabilize vertical wire cable movements. Since many of the earlier efforts had been defeated by the effects of friction and weight, it was decided to utilize the increase of water pressure with depth as a means of preventing the unwanted vertical wire motion.³

An experimental depth sensor (fig. 4) is used to convert the vertical ship motion into pressure changes. It is submerged at a depth equal to one-half of the wavelength of the surface waves (fig. 5). At this depth the orbital action of the surface waves particles is negligible,³ and the changing wave motion has no effect on the sensor.

The depth sensor consists of a pressure bellows mechanically linked to a synchro motor. The shaft of the latter rotates in proportion to the vertical depth changes of the sensor which are synchronized with the vertical motions of the platform from which the sensor is suspended. When the platform moves downward, the sensor also moves down, experiences an increase in pressure, and causes a directional synchro movement. When the platform moves upward, the directional synchro movement is in the opposite direction. Thus, an increase in pressure on the sensor tends to raise the submerged equipment and a decrease in pressure tends to lower it.

3. Sverdrup, H. U., Johnson, M. W. and Fleming, R. H., The Oceans, Their Physics, Chemistry, and General Biology, Prentice-Hall, 1942

Figure 2. Oceanographic winch with depth regulation equipment.

Figure 3. Schematic of depth regulation equipment.

Figure 4. Depth sensor mechanical details.

Figure 5. Depth sensor location and development of error signal.

The sensor actually develops an error signal which is amplified, reversed in phase, and presented to the winch motor through a phase amplifier and power control unit (fig. 5). A synchro motor similar to the one mounted in the sensor is mechanically geared to the winch drum in such a way that the error signal is balanced out as the winch motor automatically corrects for ship motion (fig. 4). It is, however, important to place the sensor over the side at a location close to where the oceanographic device or other equipment is lowered to enable the sensor to feel the same relative motion (fig. 5). Stretch in the lowering cable and sway and surge of the vessel tend to offset the degree of correction afforded by the generated signal, but the use of the depth regulation equipment removes violent tension overloads, thereby maintaining wire tension and stretch at stable values.

Operational Factors

Factors to consider in the employment of the depth regulation equipment are:

(1) Under calm sea surface conditions, with the floating platform on an even, steady keel, the depth sensor feels no appreciable ship motion other than that caused by normal flotation and develops only a negligible error signal, with little correction needed.

(2) When objects are lowered over the stern of a platform, the roll effect is minimized, and the pitch and resultant heave require the greatest correction.

(3) When objects are lowered from a position amidships on either side of a floating platform, the pitch is minimized and roll requires the major correction.

(4) Heave of a vessel caused by passing wave action has to be corrected for, regardless of the location on the floating platform from which the equipment is lowered.

EVALUATION

Two dockside field tests were conducted with the oceanographic winch and experimental depth regulation equipment shown in figure 2. The depth sensor equipped with bellows and synchro motor was first lowered into 20 feet of water alongside a Navy Electronics Laboratory pier. Up-and-down manually controlled movements gave positive and linear signals from 0.1 to 2 volts per inch of depth change.

In another dockside demonstration, the experimental depth regulation equipment was attached to the oceanographic winch temporarily installed on USS MARYSVILLE (EPCER 857). Voltage signals comparable to those obtained in the sensor test were induced into the phase amplifier circuit to simulate pressure changes that would be encountered by a vessel under the influence of surface wave action. All synchro signals responded to the induced pressure changes, with 85 per cent or greater efficiency of signal range and reaction. Figure 6 illustrates in a general way how depth regulation reduces unwanted vertical motion.

Shipboard tests at sea have not been made because the equipment is an experimental one. Such tests await the construction of an equipment engineered for shipboard use.

Figure 6. General depth control relationships.

DISCUSSION AND CONCLUSIONS

Adverse weather and sea surface conditions affect the motions of all floating platforms, particularly the smaller vessels. Oceanographic ships are usually designed to be just large enough to meet general needs, the shape, length, and tonnage all being adjusted to keep down the operating costs. Many such vessels, particularly of United States registry, are less than 200 feet long. Moderate to rough seas are therefore unkind to the people that operate them and to the scientific equipment lowered over their sides.

Although weather and sea state are given considerable attention in the planning of oceanographic studies, storms can never be completely avoided on long cruises. Man has therefore had to learn to live with and tolerate adverse conditions at sea in order to gather the data he needs.

The depth regulation equipment described in this report makes possible many oceanographic operations without any attempt to control erratic ship motions; instead the latter are sensed and corrected for in the winch operation only. Some examples of applications of the equipment follows.

Deep-sea cameras can be programmed, before they are lowered and positioned by sonar, for definite periods of hovering time at preselected target distances. Depth can be automatically controlled to 1 or 2 feet, regardless of sea surface state (fig. 6), permitting better bottom photo coverage with fewer blank frames. Film can thus be utilized more efficiently in the production of continuously recorded data.

Precise depth control is not limited in its use to underwater cameras. Water bottles, large and small, can be held to constant depth until tripped or activated. Other oceanographic equipments that require depth control are thermistor beads for temperature recording, salinity units,

depth units, and current velocity meters. In the field of acoustics, heavy transducers can now be lowered safely to various depths and held there without fear of loss or damage. Constant tension can be maintained in mooring cables securing oil-drilling barges and other anchored platforms.

In some situations, the depth regulation equipment would permit deep-sea vehicles and sonar units to be towed at constant tension and depth. When sediment corers, grab samplers, heat probes, and dredges are being lowered to the sea floor, the use of depth regulation equipment would prevent premature contacts, unwanted touchdowns, disrupted coring sequences, and mistimed grab samples.

Depth regulation equipment can and should be incorporated into all new winches during manufacture. The resultant benefits in oceanographic work would be far-reaching. Rough, wind-stirred oceans would cease to be a controlling factor in the planning and accomplishment of underwater activities.

<p>Navy Electronics Laboratory Report 1215 DEPTH REGULATION OF LOWERED OCEANOGRAPHIC EQUIPMENT, by C. J. Shipek and E. C. Evans. 14 p., 27 March 1964.</p> <p>UNCLASSIFIED</p> <p>Experimental depth regulation equipment has been developed for the vertical stabilization of oceanographic instruments lowered by wire from free-floating platforms. Surface wave action imparts to such instruments a vertical motion that is sensed with a submerged bellows detector. A synchro motor attached to the bellows develops an error signal which is amplified, reversed in phase, and fed into a power control unit on a winch. The latter automatically pays out and takes in wire as demanded by the pressure sensor. The equipment can be utilized to hold deep sea cameras at specific heights above the sea floor or to hold other devices such as transducers, water bottles, and current meters at constant depths. Dockside tests with the experimental sensor and winch control equipment have been successful.</p>	<p>1. Oceanography - Instrumentation 2. Hoists - Control systems</p> <p>I. Shipek, C. J. II. Evans, E. C.</p> <p>SR 004 03 01, Task 0539 (NEL L4-1)</p> <p>This card is UNCLASSIFIED</p>
<p>Navy Electronics Laboratory Report 1215 DEPTH REGULATION OF LOWERED OCEANOGRAPHIC EQUIPMENT, by C. J. Shipek and E. C. Evans. 14 p., 27 March 1964.</p> <p>UNCLASSIFIED</p> <p>Experimental depth regulation equipment has been developed for the vertical stabilization of oceanographic instruments lowered by wire from free-floating platforms. Surface wave action imparts to such instruments a vertical motion that is sensed with a submerged bellows detector. A synchro motor attached to the bellows develops an error signal which is amplified, reversed in phase, and fed into a power control unit on a winch. The latter automatically pays out and takes in wire as demanded by the pressure sensor. The equipment can be utilized to hold deep sea cameras at specific heights above the sea floor or to hold other devices such as transducers, water bottles, and current meters at constant depths. Dockside tests with the experimental sensor and winch control equipment have been successful.</p>	<p>1. Oceanography - Instrumentation 2. Hoists - Control systems</p> <p>I. Shipek, C. J. II. Evans, E. C.</p> <p>SR 004 03 01, Task 0539 (NEL L4-1)</p> <p>This card is UNCLASSIFIED</p>
<p>Navy Electronics Laboratory Report 1215 DEPTH REGULATION OF LOWERED OCEANOGRAPHIC EQUIPMENT, by C. J. Shipek and E. C. Evans. 14 p., 27 March 1964.</p> <p>UNCLASSIFIED</p> <p>Experimental depth regulation equipment has been developed for the vertical stabilization of oceanographic instruments lowered by wire from free-floating platforms. Surface wave action imparts to such instruments a vertical motion that is sensed with a submerged bellows detector. A synchro motor attached to the bellows develops an error signal which is amplified, reversed in phase, and fed into a power control unit on a winch. The latter automatically pays out and takes in wire as demanded by the pressure sensor. The equipment can be utilized to hold deep sea cameras at specific heights above the sea floor or to hold other devices such as transducers, water bottles, and current meters at constant depths. Dockside tests with the experimental sensor and winch control equipment have been successful.</p>	<p>1. Oceanography - Instrumentation 2. Hoists - Control systems</p> <p>I. Shipek, C. J. II. Evans, E. C.</p> <p>SR 004 03 01, Task 0539 (NEL L4-1)</p> <p>This card is UNCLASSIFIED</p>
<p>Navy Electronics Laboratory Report 1215 DEPTH REGULATION OF LOWERED OCEANOGRAPHIC EQUIPMENT, by C. J. Shipek and E. C. Evans. 14 p., 27 March 1964.</p> <p>UNCLASSIFIED</p> <p>Experimental depth regulation equipment has been developed for the vertical stabilization of oceanographic instruments lowered by wire from free-floating platforms. Surface wave action imparts to such instruments a vertical motion that is sensed with a submerged bellows detector. A synchro motor attached to the bellows develops an error signal which is amplified, reversed in phase, and fed into a power control unit on a winch. The latter automatically pays out and takes in wire as demanded by the pressure sensor. The equipment can be utilized to hold deep sea cameras at specific heights above the sea floor or to hold other devices such as transducers, water bottles, and current meters at constant depths. Dockside tests with the experimental sensor and winch control equipment have been successful.</p>	<p>1. Oceanography - Instrumentation 2. Hoists - Control systems</p> <p>I. Shipek, C. J. II. Evans, E. C.</p> <p>SR 004 03 01, Task 0539 (NEL L4-1)</p> <p>This card is UNCLASSIFIED</p>

INITIAL DISTRIBUTION LIST

CHIEF, BUREAU OF SHIPS
 CODE 210L (3)
 CODE 240C (2)
 CODE 320
 CODE 360
 CODE 370

CHIEF, BUREAU OF NAVAL WEAPONS
 DL1-3
 DL1-31
 FASS
 RU-222
 RUOC-2
 RUOC-11
 RUOC-11

CHIEF, BUREAU OF YARDS AND DOCKS
 CHIEF OF NAVAL PERSONNEL
 PERS 11B

CHIEF OF NAVAL OPERATIONS
 OP-077
 OP-71
 OP-76C
 OP-03EG
 OP-09B5

CHIEF OF NAVAL RESEARCH
 CODE 416
 CODE 466
 CODE 468

COMMANDER IN CHIEF US PACIFIC FLEET
 COMMANDER IN CHIEF US ATLANTIC FLEET
 COMMANDER OPERATIONAL TEST AND
 EVALUATION FORCE
 DEPUTY COMMANDER OPERATIONAL TEST -
 EVALUATION FORCE, PACIFIC
 COMMANDER CRUISER-DESTROYER FORCE,
 US ATLANTIC FLEET
 US PACIFIC FLEET
 COMMANDER TRAINING COMMAND
 US PACIFIC FLEET
 COMMANDER SUBMARINE DEVELOPMENT
 GROUP TWO
 US NAVAL AIR DEVELOPMENT CENTER
 NADC LIBRARY
 US NAVAL MISSILE CENTER
 TECH. LIBRARY, CODE NO 3022
 PACIFIC MISSILE RANGE /CODE 3250/
 US NAVAL ORDNANCE LABORATORY
 LIBRARY
 US NAVAL ORDNANCE TEST STATION
 PASADENA ANNEX LIBRARY
 CHINA LAKE
 PUGET SOUND NAVAL SHIPYARD
 USN RADIOLOGICAL DEFENSE LABORATORY
 DAVID TAYLOR MODEL BASIN
 APPLIED MATHEMATICS LABORATORY
 /LIBRARY/
 US NAVY MINE DEFENSE LABORATORY
 US NAVAL TRAINING DEVICE CENTER
 CODE 365H, ASW DIVISION
 USN UNDERWATER SOUND LABORATORY (3)
 LIBRARY
 ATLANTIC FLEET ASW TACTICAL SCHOOL
 USN MARINE ENGINEERING LABORATORY
 US NAVAL CIVIL ENGINEERING LAB.
 L54
 US NAVAL RESEARCH LABORATORY
 CODE 2027
 US NAVAL ORDNANCE LABORATORY
 CORONA
 USN UNDERWATER SOUND REFERENCE LAB.
 BEACH JUMPER UNIT TWO
 US FLEET ASW SCHOOL
 US FLEET SONAR SCHOOL
 USN UNDERWATER ORDNANCE STATION
 OFFICE OF NAVAL RESEARCH
 PASADENA
 USN WEATHER RESEARCH FACILITY
 US NAVY OCEANOGRAPHIC OFFICE (2)
 US NAVAL POSTGRADUATE SCHOOL
 LIBRARY (2)
 DEPT. OF ENVIRONMENTAL SCIENCES
 OFFICE OF NAVAL RESEARCH
 LONDON
 BOSTON
 CHICAGO
 SAN FRANCISCO

FLEET NUMERICAL WEATHER FACILITY
 US NAVAL ACADEMY
 ASSISTANT SECRETARY OF THE NAVY R-D
 ONR SCIENTIFIC LIAISON OFFICER
 WOODS HOLE OCEANOGRAPHIC INSTITUTION
 INSTITUTE OF NAVAL STUDIES
 LIBRARY
 AIR DEVELOPMENT SQUADRON ONE /VX-1/
 DEFENSE DOCUMENTATION CENTER (20)
 DOD RESEARCH AND ENGINEERING
 TECHNICAL LIBRARY
 NASA (5)
 LANGLEY RESEARCH CENTER
 COMMITTEE ON UNDERSEA WARFARE
 US COAST GUARD
 OCEANOGRAPHY - METEOROLOGY BRANCH
 ARCTIC RESEARCH LABORATORY
 WOODS HOLE OCEANOGRAPHIC INSTITUTION
 US COAST AND GEODETIC SURVEY
 MARINE DATA DIVISION /ATTN-22/ (3)
 US WEATHER BUREAU
 US GEOLOGICAL SURVEY LIBRARY
 DENVER SECTION
 US BUREAU OF COMMERCIAL FISHERIES
 LA JOLLA DR. AHLSTROM
 WASHINGTON 25, D. C.
 POINT LOMA STATION
 WOODS HOLE, MASSACHUSETTS
 HONOLULU-JOHN C. MARR
 LA JOLLA, CALIFORNIA
 HONOLULU, HAWAII
 STANFORD, CALIFORNIA
 POINT LOMA STA-J. H. JOHNSON
 ABERDEEN PROVING GROUND, MARYLAND
 REDSTONE SCIENTIFIC INFORMATION
 CENTER
 BEACH EROSION BOARD
 CORPS OF ENGINEERS, US ARMY
 DEPUTY CHIEF OF STAFF, US AIR FORCE
 AFRST-SC
 STRATEGIC AIR COMMAND
 HQ AIR WEATHER SERVICE
 UNIVERSITY OF MIAMI (3)
 THE MARINE LAB. LIBRARY
 COLUMBIA UNIVERSITY
 HUDSON LABORATORIES
 LAMONT GEOLOGICAL OBSERVATORY
 DARTMOUTH COLLEGE
 THAYER SCHOOL OF ENGINEERING
 RUTGERS UNIVERSITY
 CORNELL UNIVERSITY
 OREGON STATE UNIVERSITY
 DEPARTMENT OF OCEANOGRAPHY
 UNIVERSITY OF SOUTHERN CALIFORNIA
 ALLAN HANCOCK FOUNDATION
 UNIVERSITY OF WASHINGTON
 DEPARTMENT OF OCEANOGRAPHY
 FISHERIES-OCEANOGRAPHY LIBRARY
 NEW YORK UNIVERSITY
 DEPT OF METEOROLOGY - OCEANOGRAPHY
 UNIVERSITY OF MICHIGAN (2)
 DR. JOHN C. AYERS
 UNIVERSITY OF ALASKA
 GEOPHYSICAL INSTITUTE
 UNIVERSITY OF RHODE ISLAND
 NARRAGANSETT MARINE LABORATORY
 YALE UNIVERSITY
 BINGHAM OCEANOGRAPHIC LABORATORY
 FLORIDA STATE UNIVERSITY
 OCEANOGRAPHIC INSTITUTE
 UNIVERSITY OF HAWAII
 A-M COLLEGE OF TEXAS
 DEPARTMENT OF OCEANOGRAPHY
 THE UNIVERSITY OF TEXAS
 DEFENSE RESEARCH LABORATORY
 HARVARD UNIVERSITY
 SCRIPPS INSTITUTION OF OCEANOGRAPHY (2)
 UNIVERSITY OF CALIFORNIA
 ENGINEERING DEPARTMENT
 THE JOHNS HOPKINS UNIVERSITY
 APPLIED PHYSICS LABORATORY
 INSTITUTE FOR DEFENSE ANALYSIS