100 02 223
distributing
Coast. Eng. Res. Ctr.
MR 79-4
(AD - A074 393)

Sediment Distribution, Sand Resources, and Geologic Character of the Inner Continental Shelf Off Galveston County, Texas

by

**S. Jeffress Williams , Dennis A. Prins,
and Edward P. Meisburger**

**MISCELLANEOUS REPORT NO. 79-4
JULY 1979**

Approved for public release;
distribution unlimited.

**U.S. ARMY, CORPS OF ENGINEERS
COASTAL ENGINEERING
RESEARCH CENTER**

**Kingman Building
Fort Belvoir, Va. 22060**

TC
203
10581
MR 79-4

Reprint or republication of any of this material shall give appropriate credit to the U.S. Army Coastal Engineering Research Center.

Limited free distribution within the United States of single copies of this publication has been made by this Center. Additional copies are available from:

*National Technical Information Service
ATTN: Operations Division
5285 Port Royal Road
Springfield, Virginia 22161*

Contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MR 79-4	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SEDIMENT DISTRIBUTION, SAND RESOURCES, AND GEOLOGIC CHARACTER OF THE INNER CONTINENTAL SHELF OFF GALVESTON COUNTY, TEXAS		5. TYPE OF REPORT & PERIOD COVERED Miscellaneous Report
7. AUTHOR(s) S. Jeffress Williams Dennis A. Prins Edward P. Meisburger		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Department of the Army Coastal Engineering Research Center (CEREN-GE) Kingman Building, Fort Belvoir, Virginia 22060		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Department of the Army Coastal Engineering Research Center Kingman Building, Fort Belvoir, Virginia 22060		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS D31466
14. MONITORING AGENCY NAME & ADDRESS (If different from Controlling Office)		12. REPORT DATE July 1979
		13. NUMBER OF PAGES 159 158
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Artificial beach nourishment Sediments Galveston County, Texas Seismic reflection Geomorphology		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) About 850 square kilometers (330 square miles) of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles taken along several hundred kilometers of trackline and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects.		

(continued)

Pleistocene and older sedimentary deposits underlie the study area at shallow depths, and several prominent erosion surfaces and deeply incised, and subsequently filled, stream channels are evident on the seismic records. The thickness of Holocene sediments is generally less than 3 meters (10 feet), except in channels, and the contact between the Holocene and Pleistocene units is obvious in most cores and shows good correlation with a regional reflector on the seismic profiles. Mud and muddy fine sands predominate in the area; however, very fine to fine sand is present on the shoreface and in several delta shoals. Five sites are identified which contain sand suitable for beach nourishment; two of the sites, a shoal adjacent to Galveston south jetty and an area off San Luis Pass, offer the highest potential. Volumetric estimates indicate that 63 million cubic meters (82 million cubic yards) of sand exists in the five sites.

PREFACE

This report provides data and information on the geomorphology, geologic character, and sediment distribution on a part of the Inner Continental Shelf of the Gulf of Mexico, with specific emphasis on locating, describing, and delineating marine sand deposits having potential for use as fill material for beach nourishment projects. Seismic reflection data and sediment cores comprise the data base for the study which is part of the Galveston County Shore Erosion Study. The work was carried out under the coastal processes program of the U.S. Army Coastal Engineering Research Center (CERC).

The report was prepared principally by S. Jeffress Williams, a CERC geologist, with assistance in all phases of the study from Dennis A. Prins and Edward P. Meisburger. General supervision and review of this report was provided by C.H. Everts, Chief, Geotechnical Engineering Branch.

The authors acknowledge S. Tanner and C. McClenan, principal investigators at the U.S. Army Engineer District, Galveston; M. Kieslich, the former project engineer; G.R. Powledge and E.W. Schuldt, Foundations and Materials Branch; and R. McCullough, captain of the survey vessel *Vollert*. The U.S. Geological Survey (USGS), Corpus Christi, provided copies of existing seismic profiles as well as logistical help and facilities for sampling the cores; H.L. Berryhill and G.L. Shideler of USGS were especially helpful in providing their time and geologic knowledge of the Texas shelf. The authors also acknowledge J.H. McGowen and R. Morton, University of Texas, Bureau of Economic Geology, for their permission to use unpublished data on surficial sediment distributions derived from their studies.

The original copies of the seismic data, as well as sample splits of representative sediment from the cores, are stored at CERC. The cores are stored at the USGS in Corpus Christi. Request for information relative to all of the above should be directed to S.J. Williams, Coastal Engineering Research Center, Kingman Building, Fort Belvoir, Virginia 22060.

Comments on this publication are invited.

Approved for publication in accordance with Public Law 166, 79th Congress, approved 31 July 1945, as supplemented by Public Law 172, 88th Congress, approved 7 November 1963.

TED E. BISHOP
Colonel, Corps of Engineers
Commander and Director

CONTENTS

	Page
CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI)	6
I INTRODUCTION	7
Scope	10
II BACKGROUND	10
1. Equipment and Field and Laboratory Procedures	10
2. Geographic Setting.	23
3. Geologic Setting and Regional Stratigraphy.	24
III RESULTS.	28
1. Continental Shelf Morphology.	28
2. Shallow Subbottom Structure and Stratigraphy.	28
3. Primary Sediment Classes.	31
4. Suitability of Sandfill for Beach Nourishment	36
5. Dredging Effects on the Shore	36
6. Potential Offshore Sand Borrow Sites.	38
IV SUMMARY AND RECOMMENDATIONS.	49
LITERATURE CITED	50
APPENDIX	
A CORE SEDIMENT DESCRIPTIONS	53
B GRANULOMETRIC DATA AND CUMULATIVE CURVE PLOTS.	71

TABLES

1 Grain-size scales (soil classification)	34
2 Characteristics of possible borrow sites.	41

FIGURES

1 Sections of the Texas gulf coast from High Island to Freeport which are experiencing severe beach erosion.	8
2 Photo showing the effects of beach erosion at Surfside Beach. . .	9
3 Bathymetric map of the Texas inner shelf between High Island and Freeport	11
4 Schematic of a seismic reflection instrument being towed along a profile line	13
5 The Galveston District survey boat, <i>Vollert</i> , used to collect the seismic reflection data and to locate core sites for phase II	14

CONTENTS

FIGURES--Continued

	Page
6 A vibratory core rig, used to obtain 34 cores with a maximum length of 6.1 meters.	15
7 The jack-up barge, <i>Lim Bowman</i> , used as the platform for coring during phase II of data collection	16
8 Location of seismic reflection ship tracklines and vibratory cores taken between High Island and Freeport.	19
9 Generalized geologic map of Quaternary-age sediments in the Galveston-Brazoria County region of the Texas gulf Coastal Plain	25
10 Sea level changes on the Texas coast during the past 100,000 years correlated with geologic events	26
11 Modern environments and facies on the Galveston barrier island .	29
12 Geologic cross sections at Galveston showing the Pleistocene unconformity, Holocene stratigraphy, and the configuration of the ancestral Trinity Channel.	30
13 The four primary sediment types on the inner shelf surface, determined from the CERC cores and seismic records and from TBEG grab samples	33
14 Mean grain-size diameter for native beach sands along the Texas coast from the Sabine River to Surfside Beach	37
15 Map of five sites selected as possible locations for obtaining sand for beach nourishment.	39
16 Possible borrow area A, which is confined to a relict buried stream channel cut into the Pleistocene erosion surface	42
17 Map of possible borrow site B, and site C which has a high potential inshore area.	43
18 Borrow area D, which consists of the San Luis ebb tidal shoal and adjacent shoreface.	45
19 The sedimentary facies and different environments associated with San Luis Pass, which result from complex ebb and flood tidal processes	46
20 Quaternary stratigraphy at San Luis Pass based on interpretations of descriptive logs of 16 borings	47
21 Borrow area E off Surfside Beach at the west end of the survey area	48

CONVERSION FACTORS, U.S. CUSTOMARY TO METRIC (SI)
UNITS OF MEASUREMENT

U.S. customary units of measurement used in this report can be converted to metric (SI) units as follows:

Multiply	by	To obtain
inches	25.4	millimeters
	2.54	centimeters
square inches	6.452	square centimeters
cubic inches	16.39	cubic centimeters
feet	30.48	centimeters
	0.3048	meters
square feet	0.0929	square meters
cubic feet	0.0283	cubic meters
yards	0.9144	meters
square yards	0.836	square meters
cubic yards	0.7646	cubic meters
miles	1.6093	kilometers
square miles	259.0	hectares
knots	1.852	kilometers per hour
acres	0.4047	hectares
foot-pounds	1.3558	newton meters
millibars	1.0197×10^{-3}	kilograms per square centimeter
ounces	28.35	grams
pounds	453.6	grams
	0.4536	kilograms
ton, long	1.0160	metric tons
ton, short	0.9072	metric tons
degrees (angle)	0.01745	radians
Fahrenheit degrees	5/9	Celsius degrees or Kelvins ¹

¹To obtain Celsius (C) temperature readings from Fahrenheit (F) readings, use formula: $C = (5/9) (F - 32)$.

To obtain Kelvin (K) readings, use formula: $K = (5/9) (F - 32) + 273.15$.

SEDIMENT DISTRIBUTION, SAND RESOURCES, AND GEOLOGIC CHARACTER OF THE INNER CONTINENTAL SHELF OFF GALVESTON COUNTY, TEXAS

by
S. Jeffress Williams, Dennis A. Prins,
and Edward P. Meisburger

I. INTRODUCTION

The Galveston region of the Texas coast is an important resort area that is threatened by severe erosion. The National Shoreline Study (U.S. Army, Corps of Engineers, 1971), which included an assessment of beaches in the Galveston area, reported severe erosion along a 6.4-kilometer (4 miles) section of beach immediately west of the end of the Galveston seawall, as well as along a 20.8-kilometer (13 miles) stretch on Bolivar Peninsula west of High Island (Fig. 1). More recent surveys (U.S. Army Engineer District, Galveston, 1976) show that the threat of severe erosion is great along most of the upper Texas coast, and in particular the western end of Galveston Island at San Luis Pass and at Surfside Beach, a 3.2-kilometer (2 miles) stretch of beach near Freeport (Fig. 1). Beach recession at Surfside averaged 2.4 meters (8 feet) per year from 1968 to 1975, and several houses were undermined and destroyed by the waves (Fig. 2).

In 1976, the Galveston District initiated a study to evaluate causes of erosion and possible control measures for eroding gulf and bay shorelines in Galveston County, as well as the Surfside Beach area in adjacent Brazoria County (U.S. Army Engineer District, Galveston, 1976). The overall objectives of the study were to: (a) determine the needs and concerns of local people relating to shoreline erosion within the study area, (b) identify eroding shoreline areas and determine the cause and rates of erosion, (c) delineate those shoreline areas where potential Federal interest exists and develop and evaluate alternatives, and (d) make recommendations for solving the erosion problems.

Beach nourishment has proven to be one solution for many severely eroded coastal areas because it is usually environmentally and esthetically acceptable. In addition, it is often an important and effective means of counteracting coastal erosion, of providing relief from hurricane flooding, and of enhancing recreational facilities (U.S. Army, Corps of Engineers, Coastal Engineering Research Center, 1977). However, nourishment of a beach does require large volumes of suitable sand as fill, and in recent years it has often been impractical to obtain needed material from back-barrier island lagoons and bays or from inland sources because of economic or environmental factors, or land-use restrictions. Also, material from bays and lagoons is often too fine grained to meet beach-fill design criteria.

The Coastal Engineering Research Center (CERC) has a continuing research program with the objective to locate and accurately describe offshore marine sand resources suitable for dredging and transport to

Figure 1. Sections of the Texas gulf coast from High Island to Freeport which are experiencing severe beach erosion as identified by the National Shoreline Study (U.S. Army, Corps of Engineers, 1971) and the U.S. Army Engineer District, Galveston (1976) surveys.

(Photo by S.J. Williams)

Figure 2. Photo showing the effects of beach erosion at Surfside Beach, June 1977.

adjacent project shorelines. This study was conducted to provide a detailed survey (using seismic reflection data and long cores) of the shelf off Galveston County and Surfside Beach to determine the location, character, and volume of sand having potential value as fill for nourishment of eroding beaches.

Scope.

The study area (Fig. 3) covers about 850 square kilometers (330 square miles) of the Gulf of Mexico from High Island (94°20'W., 29°30'N.) west about 85 kilometers (55 miles) to Freeport (95°20'W., 28°55'N.), and centered about Galveston, Texas. It includes parts of the Texas Inner Continental Shelf off Bolivar Peninsula, Galveston Island, Follets Island, and Surfside Beach. The area of data collection extends seaward a maximum of about 8 kilometers (5 miles) from the shoreface (water depths from about 3 to 15.5 meters or 10 to 50 feet). Data collected consist of about 435 kilometers (270 miles) of seismic reflection profiles and 34 cores ranging in length from 2.2 to 6.1 meters (7.3 to 20 feet). The mean core length is 4.9 meters (16 feet). These data were supplemented by logs of engineering borings taken along the Freeport and Galveston jetties and across San Luis Inlet. Additional information on the subbottom geology was also derived from several hundred trackline kilometers of seismic records taken along shore-normal transects as part of a joint U.S. Geological Survey (USGS) and the University of Texas, Bureau of Economic Geology (TBEG) program. Also, a TBEG map showing surficial sediment distributions based on several hundred grab samples was used. Pertinent scientific and technical literature and hydrographic maps were also used. Especially informative were the TBEG environmental atlases by Fisher, et al. (1972, 1973) and McGowen, et al. (1976).

II. BACKGROUND

1. Equipment and Field and Laboratory Procedures.

a. Geographic Positioning System. An electronic positioning system, the Motorola Mini-Ranger III, was used to accurately determine position of the research survey vessels during both phase I of seismic surveying and phase II of taking cores. The system determines the position of the survey vessel with respect to two known reference points on shore and is restricted to line-of-sight operation. The stated accuracy is ± 3 meters. The basic system consists of a master mobile unit mounted on board the vessel and two shore-based transponders. The master unit interrogates each transponder separately and the elapsed time between the transmitted pulse and the transponder reply pulse is converted to a measurement of distance. Each distance (range) from the two transponders at the known shore stations is displayed, in turn, on the range console. This range information, together with the known locations of the shore stations, is then trilaterated and plotted on hydrographic charts to obtain the position (fix) of the survey vessel. Navigational fixes during the seismic survey were obtained about every 2 to 4 minutes and each fix was keyed to the seismic records by an event mark on the records.

Figure 3. Bathymetric map of the Texas inner shelf between High Island and Freeport.

b. Seismic Reflection Profiling. Seismic reflection profiling is a technique widely used for delineating geologic features such as bedding surfaces, faults, rock outcrops, channels, and structures beneath the sea floor. Continuous reflections are obtained by generating repetitive, high-energy, sound pulses near the water surface and at the same time recording "echoes" from the sea floor-water interface and from subbottom interfaces between acoustically dissimilar materials. This is done while the survey vessel is moving. In general, the compositional and physical properties (e.g., porosity, water content, relative density) which commonly differentiate sediments and rocks also serve to produce acoustic contrasts which show as dark lines on the seismic paper records. Thus, a seismic profile is roughly comparable to a geologic cross section (Fig. 4).

The seismic reflection data were obtained by towing sound-generating and -receiving instruments behind the Galveston survey boat *Vollert* which followed predetermined survey tracklines (Fig. 5). In phase I of this study, two seismic subbottom profiling systems were used simultaneously. An Ocean Research Equipment, Inc. (ORE) 3.5-kilohertz pinger system was employed to gain very high resolution of the upper 15 meters of sea floor; an E.G.G., Inc. UNIBOOM system was used to decipher geologic conditions to depths of 40 meters (131 feet) below the sea floor with little sacrifice in resolution. Data from each system complement each other and are needed to achieve maximum understanding of the subbottom geologic character. A vertical scale on the profiles was determined using a sound velocity of 1,463 meters (4,800 feet) per second in water and 1,645 meters (5,400 feet) per second for typical marine sediments. Additional information on various seismic profiling techniques is discussed in Ewing (1963), Moore and Palmer (1967), Barnes, et al. (1972), and Ling (1972).

c. Coring Equipment. A pneumatic vibratory coring device specifically designed to obtain sediment cores a maximum of 6.1 meters long (Fig. 6) was used in the phase II survey operation. The apparatus is equally effective in penetrating and recovering granular and cohesive sediments. The core rig consists of a standard 10.1-centimeter (4 inches) steel core barrel, clear plastic inner liner, shoe and core catcher, and pneumatic driving head attached to the upper end of the barrel. These elements are enclosed in a tripodlike frame with four articulated legs which rest on the sea floor. The aluminum H-beam and frame serve as a support structure and guide for the vibrator head and core pipe as the core barrel penetrates the sea floor. Detachment of the core device from the surface vessel allows limited motion of the vessel during the actual coring process. Power is supplied to the pneumatic vibrator head by a flexible hose line connected to a large-capacity (250 cubic feet per minute) air compressor. After coring is completed, the assembly is hoisted on board the vessel, the liner containing the core removed, samples from the top and bottom of the core removed, the ends sealed, and the core is carefully marked for orientation and identification. The historical development of vibratory coring equipment is discussed by Tirey (1972).

The self-propelled jack-up barge, *Lim Bowman* (Fig. 7), was used as the platform for phase II coring. It is 18.3 meters (60 feet) long and

Figure 4. Schematic of a seismic reflection instrument being towed along a profile line. Acoustic energy penetrates the subbottom strata and is reflected back to surface hydrophones. The sea floor and primary acoustic horizons (reflectors) are recorded on continuous chart paper.

(Photo by S.J. Williams)

Figure 5. The Galveston District survey boat, *Volleert*, used to collect the seismic reflection data and to locate core sites for phase II.

(Photo by S.J. Williams)

Figure 6. A vibratory core rig, used to obtain 34 cores with a maximum length of 6.1 meters. In many instances sedimentary layers in the cores were correlated with acoustic reflectors on the seismic profiles.

(Photo by S.J. Williams)

Figure 7. The jack-up barge *Lám Bowman*, used as the platform for coring during phase II of data collection.

requires a boat crew of two and a four-man coring crew to navigate the vessel and operate the 5-ton crane used to lower and raise the core apparatus between the deck and sea floor. The three legs on the barge, which are hydraulically operated from the pilot house, enable the barge to be raised above the sea and swell to provide a stable coring platform.

d. Data Collection Planning. Before the field data collection effort, tentative offshore seismic survey tracklines were established and plotted on navigation charts of the survey area. Position, spacing, and length of the tracklines were determined by several factors. A primary concern was spacing the lines to achieve maximum coverage of the study area. The inshore boundary was approximately the 5-meter depth contour which is about the minimum depth for obtaining good quality seismic profiles; the seaward boundary was about 8 kilometers offshore which was judged to be the economic limit for sand transport to project beaches.

A second factor was to lay out the seismic lines so that buried stream channels, relict barrier islands, tidal shoals, river deltas, and other geologic features with a high potential for containing sand would be crossed and show on the seismic profiles. Preliminary core sites were selected on the basis of bathymetric information; however, final core sites were chosen after all the seismic data were collected and subjected to preliminary interpretation. After the survey tracklines were selected, the locations of the shore stations for the navigation system were determined. Of high priority were stations at elevated positions (for adequate line-of-sight) which also offered good triangular position in relation to the survey ship and adjacent shore stations. (Optimum geometry is achieved when the angle of range intercept of the vessel is greater than 30° and less than 150° ; optimum range angle intercept is 90° .) After shore stations were determined and plotted on map sheets, their positions were accurately surveyed. A total of eight shore navigation stations were used along 85 kilometers of coast. Occasionally, positions and spacing of the predetermined tracklines were altered to gather additional information on geologic features such as buried stream channels, sediment contacts, and sea floor outcrops of possible sandy material.

After approximately 435 kilometers of seismic profile records was collected, preliminary analysis and interpretations were made to select coring sites with the greatest potential, based on past experience, for retrieving sandy material. Use of seismic data to decipher geologic conditions before selecting final core sites enables their selection to be based on the best information available. Thus, this procedure maximizes the usefulness of both sources of data and provides the most efficient use of funds.

During phase II the *Vollert*, with the positioning system on board, was used to relocate fix positions selected as coring sites. This was done by duplicating the range values from the shore stations. The *Vollert* first maneuvered until one of the ranges was duplicated and then

an arc was run on that range until the other range was intersected, at which time an anchored float was used to mark the core location. The jack-up barge was then positioned adjacent to the float for coring. Core sites were located and marked in this manner because of the limited maneuverability of the barge. Without the *Vollert* much additional time would have been required to get the barge to the precisely determined core locations. The *Vollert* located a core position in minutes and dropped a float marker; the barge then immediately moved in on the marker, jacked-up within a few minutes, and the core rig was lifted from the deck and set on the sea floor next to the float. Meanwhile, the *Vollert* retrieved the float and proceeded to the next core site. Once on the bottom the coring device was energized, the core barrel was driven into the sea floor, and within about 15 minutes the apparatus was lifted back onto the barge. The core liner containing the sediment was removed from the barrel and small reference samples were obtained from the top and the bottom of each core. The liner was then capped and sealed, labeled, and visually inspected. The jack-up barge was lowered and moved to the next coring location. While underway, the coring device was reassembled and loaded with a new liner for the next core.

At the end of each working day the jack-up barge was raised above the sea surface. The barge remained at sea for the duration of the survey.

e. Processing of Data. After completion of both phases of data collection, all the navigational fix marks, ship trackline positions, core sites, and shore stations were plotted to show the coverage within the survey area (Fig. 8). The seismic records were visually examined and marked to establish the primary geologic features such as regional sedimentary reflectors, erosional unconformities, faults, and buried stream channels. Selected acoustic reflectors were then mapped to provide areal continuity of horizons considered significant because of their extent and relationship to the general structure and geology of the study area. Where possible, the topmost reflectors were correlated with cored sediment to provide a measure of continuity between cores.

The cores were visually inspected and described in general terms aboard the barge; a more detailed study of the cores was made later. All cores were split longitudinally to show changes in sediment composition, texture, and physical character. Selected intervals of cores were color-photographed to provide an archive record of the sediment character and color before oxidation and drying from exposure to air. The sediments were identified, logged, and described according to textural properties, gross lithology, color, strength, thickness, presence of marine organisms, and depth from the sea floor (top of the core) (see App. A). Representative sediment samples from each core were examined with a plane light binocular microscope. Samples of sandy material potentially usable for beach fill were prepared; a total of 84 individual samples were processed and the test of every fifth sample was duplicated as a quality control check. Granulometric parameters (e.g., mean grain size, sorting, cumulative-size distribution) were evaluated by using the CERC Rapid Sediment Analyzer (RSA) as described on page 4-26 of the Shore

Figure 8. Location of seismic reflection ship tracklines and vibratory cores taken between High Island and Freeport.--Continued

Figure 8. Location of seismic reflection ship tracklines and vibratory cores taken between High Island and Freeport.--Continued

Figure 8. Location of seismic reflection ship tracklines and vibratory cores taken between High Island and Freeport.--Continued

Protection Manual (SPM) (U.S. Army, Corps of Engineers, Coastal Engineering Research Center, 1977). These RSA data, as well as sieve data from one sample too coarse to process by RSA, are presented in Appendix B. Cumulative distribution curves are also presented.

All of the sand sample sizes are described in both millimeters and phi (ϕ) units where $\phi = -\log_2 D$. D is the grain-size diameter in millimeters. In the RSA analysis the sand sample falls through a tube of water and a pressure transducer is used to determine the fall velocity of the sand grains. The SEDANL computer program is then used to compute moments to convert fall velocity to hydraulic grain-size diameter. The RSA method is fast and reliable, but it is limited to analyzing very fine to medium sands. Any fine-grained material present with the sand often remains in suspension in the tube when the measurements are stopped. Thus, the silt and clay fraction in a muddy sand sample is often omitted from the size analysis results, making the sample appear better sorted than it actually is. Most researchers agree that RSA values are consistent and slightly coarser than sieve values for identical samples. Ramsey and Galvin (1977) suggest adding 0.33 phi to the RSA mean to obtain the equivalent sieve mean; another formula, with a similar constant, is shown in Appendix B.

2. Geographic Setting.

The study area is part of the Texas coast of the Gulf of Mexico, a large geosynclinal basin of active deposition that receives sediment from nine major rivers draining from most of Texas and part of New Mexico. The entire Texas coast from the Sabine River at the Louisiana border, south to the Rio Grande River marking the border with Mexico, is composed of long and narrow sandy barrier islands broken by tidal inlets which lead to lagoons and estuaries between the barrier islands and the mainland. The islands are generally of low relief, except for vegetated sand dunes, and most remain in their natural state, relatively undisturbed by human activity. All the barrier island peninsulas are attached to mainland areas on their northeastern ends with the unattached ends extending southwest (Bullard, 1942). Also, the northeast ends of the islands exhibit maximum width and the islands taper toward the southwest. In the study area, these conditions are best exemplified by Bolivar Peninsula (Fig. 3).

The back-barrier lagoons and barrier islands of the Texas coast are geologically very recent features which have formed during the past 5,000 years in response to complex coastal processes as well as the gradual worldwide rise in sea level. The barrier islands in the study area, and for much of the Texas coast, are constructional landforms built up over thousands of years by sand transported to the coast by rivers and then westward along the coast by wave-generated longshore currents.

Galveston Bay is a shallow estuary extending about 32 kilometers (20 miles) inland from the gulf and consists of East Bay behind Bolivar Peninsula and Trinity Bay to the north. Galveston Bay occupies the ancestral

flood plains and drowned channels of the San Jacinto and Trinity Rivers which were inundated as sea level rose during the past 20,000 years. Galveston Island extends about 48 kilometers (30 miles) from the inlet at Bolivar Roads to San Luis Pass. West of San Luis Pass, Follets Island continues for 20 kilometers (12 miles) to the Brazos River Inlet channel and includes the Surfside Beach community near Freeport. About 48 kilometers of coast in the Surfside-Freeport area and west to Matagorda Bay is a headland region which protrudes into the gulf and represents an ancestral delta complex formed by the Brazos and Colorado Rivers. This is one of the few areas along the entire 592 kilometers (370 miles) of Texas coast which is not fronted by barrier islands.

3. Geologic Setting and Regional Stratigraphy.

Galveston County lies within the Coastal Plain Province of the Gulf of Mexico geosyncline. Of greatest importance to this study are the Pleistocene- and Holocene-age sedimentary deposits which make up the youngest of the Coastal Plain deposits (Fig. 9). These materials are composed primarily of alluvial, deltaic, estuarine, and marine deposits. Lankford and Rehkemper (1969) suggest that two of the primary factors controlling the distribution, geometry, and composition of these deposits are (a) tectonic uplift of inland areas and subsidence of offshore gulf areas, separated by a hinge line; and (b) fluctuating elevations of sea level during the past million years or more in response to periods of worldwide glaciation and deglaciation. These sea level fluctuations had a major influence on forming the geologic character and present physiography of the Texas mainland coast and inner gulf shelf. Periods of depressed sea level initiated episodes of mass erosion on land as rivers eroded deep into the valleys and tended to meander more across broad flood plains. In contrast, as sea level rose base levels of the streams were also raised and deposition of sediment predominated. Evidence of different episodes of geologic conditions are sometimes obvious on land in the form of deeply buried ancestral stream channels, broad thick fluvial flood plain deposits, extensive deltaic deposits associated with many of the major streams, and relict barrier spits, islands, dunes, and strand plains resulting from past sea level elevations higher than the present one.

a. Montgomery Formation. The earliest formation of direct importance to this study is the Montgomery Formation (Upper Lissie) (Fig. 10) which is the name for materials deposited during the Sangamon interglacial period directly preceding Wisconsin Glaciation. The Montgomery Formation is composed of various sedimentary facies that reflect fluvial, deltaic, lagoonal and open marine environments of deposition and range in composition from gravels and sands to sandy clays and clays (Anderson and Clark, 1977). During Wisconsin-age (the last glacial episode) the Montgomery Formation was subaerially exposed and subjected to erosion and weathering processes which altered some original sediments to ferruginous sands and stiff oxidized clays with ferruginous concretions.

b. Beaumont Formation. The Beaumont Formation (Fig. 10), which is younger than the Montgomery and unconformably overlies it, is the most

Figure 9. Generalized geologic map of Quaternary-age sediments in the Galveston-Brazoria County region of the Texas gulf Coastal Plain (from Garner, 1967).

Figure 10. Sea level changes on the Texas coast during the past 100,000 years (Late Quaternary) correlated with geologic events. Data show that sea level has been both 53 meters (175 feet) higher and 134 meters (440 feet) lower than present levels (from Graf, 1966).

widespread and prevalent in both subaerial and submarine exposure in the study area and therefore the most germane to this report. It was deposited during the Wisconsin Glaciation when sea level fluctuated in elevation. Barton (1930) and Pettit and Winslow (1957) describe the Beaumont as consisting of abruptly changing facies of fluvial and deltaic sediments mixed with lagoonal shallow marine deposits and sandy barrier island deposits. The ancient barrier beaches, termed *Ingleside*, consist of three distinct topographic ridges, inland but roughly parallel to the present coast; these have been correlated with similar features from southern Texas to parts of Louisiana. These old barrier islands generally have relief of about 3 meters and are about 1.6 kilometers (1 mile) wide. Submerged relict Beaumont (*Ingleside*) barrier beaches present on the gulf shelf have been speculated on in the literature, but no evidence of their presence was found in this study.

The Beaumont Formation consists of yellow, reddish-brown, grayish-green, and black clays, silty sands, and fine brown sand. Calcareous (caliche) nodules and shell fragments are also sometimes present. The surface of the Beaumont was deeply weathered and eroded during exposure in late Wisconsin-age; consequently, its surface sediment is usually stiff, dehydrated, and multicolored. These characteristics make it relatively easy to identify in outcrop, as well as in the cores taken during this study, except in the vicinity of inlets where deep erosion and subsequent filling by recent sediments has occurred. Because of the sediment's dense character and uneven eroded surface, it generally creates a strong and distinctive acoustic reflector that is traceable on seismic profiles over nearly the entire study area.

c. Deweyville Formation. Deweyville sediments are late Wisconsin-age and overlie the Beaumont. Bernard (1950) describes them as clayey silts and silty fine sands with minor occurrences of sand. They are younger than 30,000 years and grade into Holocene-age sediments. Their exposure on land is apparently limited and their presence on the shelf is unknown.

d. Holocene-Modern Sediments. Several authors working in different geographic areas have placed the Pleistocene-Holocene boundary at 12,000 to 20,000 years ago. This is the time when the world climate moderated and ice sheets from the latest glaciation (Wisconsin) began to melt and release water to the ocean basins with a consequent elevation of sea level to the present level.

This rise in sea level is shown in Figure 10, which depicts a steady rise until about 4,500 years ago at which time the curve changed to a more gradual slope. The time from about 4,500 years ago to the present is termed modern. Presently, sea level in relation to land at Galveston is rising about 40 centimeters (1.4 feet) per century (Hicks, 1972). This figure is based on measurements taken from 1940 to 1970, and is complicated by documented subsidence in the Galveston region due to both natural and man-induced causes. The Holocene and modern sedimentary deposits along the Texas coast consist of fluvial flood plain and deltaic

sediments as well as fine-grained materials in the lagoons and on parts of the open shelf. Very fine and fine grained sand comprises the beaches and dunes.

In the study area, marine nearshore processes have been dominant in forming the barrier islands and in modifying the physiography of the region. Galveston Island is probably the best known example of a barrier island that has prograded seaward from about 3,500 to at least 800 years ago, based on research by LeBlanc and Bernard (1954), Bernard, LeBlanc, and Major (1962), Lankford and Rehkemper (1969), and Bernard, et al. (1970). Both Galveston Island and Bolivar Peninsula are characterized by elongate, abandoned beach ridges separated by low swales which parallel the present shoreline. The ridges indicate the islands have accreted seaward. The source of this sand is thought to be the Sabine River and other rivers to the east (Bernard, Major, and Parrott, 1959). Figure 11, which shows a cross section of Galveston Island based on borings, indicates the maximum thickness of Holocene sands occurs in the center of the island. The Pleistocene erosion surface underlies the island at about -12 meters (40 feet) and has a gentle seaward slope. Figure 12 shows that the Pleistocene surface remains at about the same elevation under the eastern part of Galveston Island, but at Bolivar Roads there is a deeply incised river channel with a thalweg depth of -31 meters (-120 feet) filled with Holocene sands and muds. Rehkemper's (1969) interpretations of a number of borings show that this channel is the ancestral Trinity River which was deeply incised during Pleistocene low stands of sea level.

III. RESULTS

1. Continental Shelf Morphology.

The Continental Shelf width varies from a maximum of 232 kilometers (145 miles) off the Texas-Louisiana boundary to about 112 kilometers (70 miles) off Matagorda Bay. As shown by the 18.3-meter contour in Figure 3, considerable change in sea floor slope occurs in the study area between High Island and Freeport. The inner shelf off High Island is extremely flat and featureless with a slope of 0.2 meter per kilometer (1.7 feet per mile); off Freeport, the 18.3-meter contour is 12.6 kilometers (7 miles) offshore and the shelf is considerably steeper with a slope of 1.5 meters per kilometer (9.2 feet per mile).

2. Shallow Subbottom Structure and Stratigraphy.

The morphology and geologic character of the sea floor and Coastal Plain in the study area are directly related to past and present geologic conditions such as erosional and depositional processes, uplift and subsidence, sources and quantities of sediment supply, and the worldwide rises and falls of sea level due to fluctuations in the climate.

a. Planar Reflectors and Channels. The CERC seismic profiles contain several very prominent reflectors which are traceable over much of

MAP VIEW

CROSS SECTION

Figure 11. Modern environments and facies on the Galveston barrier island. Radiocarbon-age dates and beach ridge patterns show that the island has historically prograded seaward. Map is from Fisher, et al. (1972), and cross section is from Bernard, et al. (1970).

the study area. Most can be related to past transgressions and regressions of the sea across the shelf, and many deeply incised stream channels are evident. These channels record the positions of ancient rivers which once flowed across the shelf during low stands of sea level. All of the channels were subsequently filled with sediment and several show evidence of postfill erosion. (It is usually impossible to trace a channel from one seismic profile to an adjacent profile because line spacing is too great.) Ancestral shelf surfaces had low relief and the rivers meandered across broad flood plains, much as they do today. Most of the channels appear to be oriented perpendicular to the modern shore and several show alignment with subaerial channels onshore. The combined Trinity-San Jacinto River channel which underlies Galveston Inlet is several kilometers wide and the largest in the area. Its size indicates that the Trinity and San Jacinto Rivers are at least 100,000 years old and have occupied only one channel on the shelf. Other sizeable channels which cut into the Pleistocene surface are located just west of High Island, immediately east and offshore of Crystal Beach on Bolivar Peninsula, and just west of Freeport Inlet (the ancestral Brazos channel). These channels are generally filled with Holocene fine-grained cohesive sediments. A prominent reflector in the area marks the contact between the Pleistocene erosion surface (top Beaumont Formation) and overlying Holocene sediments. This reflector is a good mappable horizon in all parts of the area except in the vicinity of Galveston Inlet, San Luis Pass, and Freeport Inlet where distinctions between Holocene and Pleistocene sediments are difficult because of deep fluvial erosion and subsequent filling. The depth of the reflector on the records correlates well in many cores with the contact between greenish-gray and reddish-brown indurated clay and softer grayish-brown overlying modern sediments. This reflector also correlates well with the top of reported Pleistocene elevations and with stratigraphy contained in boring logs from Galveston Inlet, San Luis Pass, and Freeport Inlet.

b. Faults. Faults are evident on many seismic profiles in the eastern part of the area but none were observed west of Galveston Inlet. Most of the fault surfaces are vertical and maximum displacement is about 2 to 3 meters (6 to 10 feet). Tracing a fault between adjacent seismic lines, even though the lines are only several kilometers apart, is difficult which suggests the faults are minor flexures possibly related to the salt-dome tectonics of High Island. All faults seem restricted to Pleistocene sediments and many extend to the sea floor where Holocene cover is absent. No evidence of displaced Holocene sediments or fault relief on the sea floor was observed to suggest that movements along these faults occur at present or have occurred in the recent past.

3. Primary Sediment Classes.

a. General. Data from the 34 cores collected during this study, along with information on the TBEG map showing surficial sediment distributions based on several hundred grab samples, provide the ground-truth information on surficial and shallow subbottom sediments within the study area. The seismic profiles were used to extrapolate the sediment

information from the core and grab sample sites to adjacent sea floor areas. The TBEG map actually contains 38 sediment descriptors; however, such detail was not appropriate for this study so the sediments were grouped into the four primary classes (Fig. 13). Detailed descriptions of each core are contained in Appendix A, and textural analyses of the sand fractions are included in Appendix B.

The Wentworth scale for soil classification was used for describing sediment textures and size classifications in this report. Table 1 shows that classification and the Unified Soil Classification (USC), as well as the relationship between grain-size diameters in millimeters (mm) and phi (ϕ) units.

b. Mud. The most common sediment type found in the study area is a mixture of silt and clay termed *mud* in this report. (Mud constitutes all materials with grain diameters smaller than 0.063 millimeter or > 4 phi.) The mud occurs over much of the study area seaward of the shoreface (Fig. 13). When wet, the mud is generally greenish-gray to dark gray in color, soft, and fairly cohesive; however, the mud becomes denser and harder when dried. In most places, the mud occurs as a horizontally stratified veneer and secondarily as fill material in several of the buried ancestral stream channels which transect the shelf. Evidence of a high degree of bioturbation, a low shear strength and high moisture content, and a relationship of the mud to deeper deposits on the seismic records and in the cores suggests deposition by modern hydraulic shelf processes.

c. Sand. Sand recovered in the cores does not exhibit much diversity in compositional and textural character. It is predominantly quartz, generally of very fine to fine grained size (0.063 to 0.25 millimeter, 4 to 2 phi), and is poorly to well sorted. Most clean sand (free of fines) appears moderate to well sorted, and is found only in the shoal area adjacent to the Galveston south jetty, the ebb tidal shoal at San Luis Pass, and parts of the shoreface region of Bolivar Peninsula and of Galveston Island west to within about 2.4 kilometers (1.5 miles) of Surfside Beach (Fig. 13). Its presence in this area is based on information in Fisher, et al. (1972, 1973). The width of the shoreface sand body (distance from shore to the sand-mud boundary) varies from about 0.4 kilometer (0.25 mile) off central Galveston Island to about 2.5 kilometers (1.6 miles) off San Luis Pass and the eastern end of Galveston Island. The sand width in other areas averages about 1.6 to 2.4 kilometers (1 to 1.5 miles). East of Galveston Inlet to High Island, clean sand is noticeably absent from any of the CERC cores or the TBEG grab samples.

d. Stiff Clay. Greenish-gray to reddish-brown and yellow stiff clay was found in 22 of the 34 cores and in several grab samples. The clay generally appears leached and oxidized and locally contains ferruginous and calcareous nodules. Its physical character, relationship to overlying modern sediments, and position and configuration on the seismic records suggest that the top of the clay is an erosion surface that was exposed to subaerial processes before sea level rose to present levels. As shown in

Figure 13. The four primary sediment types on the inner shelf surface, determined from the CERC cores and seismic records and from TBEG grab samples.

Figure 13, the clay actually crops out at the sea floor in several areas (e.g., cores 4 and 7); in other areas it is covered by a relatively thin mantle of Holocene muds and muddy sands.

e. Sediment Age. Sediment properties and faunal content indicate that some sediments recovered in the cores are part of the modern shelf and nearshore sediment blanket, and other sediments are from various relict deposits. Distinctions between the modern sediments and underlying relict sediments are relatively clear in most cases; however, more subtle gradations occur in places, such as adjacent to the inlets and in the Galveston Bay dredged-material disposal area.

Modern sediments are usually characterized in bulk by their gray to grayish-brown color and low shear strength. Microscopic examination shows that the principal sand-size components are subangular quartz particles with various amounts of fragmented mollusk shells, echinoid tests, ostracod carapaces, and foraminiferal tests. The most common inorganic accessory minerals are opaques dominated by pale-olive to dark-green glauconite grains. The foraminiferal fauna is a typical low diversity marginal marine assemblage dominated by *Ammonia beccarii* (Linne) and several species of *Elphidium*.

Most of the relict sediments appear to belong to two widespread deposits underlying the surficial modern sediment blanket. The largest of these is a stiff clay, with interbedded sand layers, which is nearly ubiquitous in cores 19 through 32 (Fig. 13). Typically, the clay is a yellow to reddish-brown color, massive, and very stiff. Residues from washing the clay through a U.S. Standard 230 sieve (0.063 millimeter or 4 phi) generally consist of a small amount of quartz grains.

The sand, which appears to be interbedded with the stiff clay, is usually reddish-brown in color, well sorted, and consists predominantly of quartz particles. In contrast to the surficial modern sediments, samples of this deposit contain little or no faunal remains or glauconite grains. Seismic data as well as lithology indicate that the stiff clay and associated sand are part of the Pleistocene Beaumont Formation.

The other extensive relict deposit occurs in the eastern part of the study area (cores 1, 2, 4, 5, 6, and 7; Fig. 13). This deposit consists of muddy sand with abundant shells and shell fragments of the marsh clam (*Rangia* sp.). The sand fraction contains little or no glauconite and the sparse, marginal marine foraminiferal fauna is usually dominated by *Ammonia beccarii* (Linne). The presence of *Rangia* sp. indicates these sediments were deposited in a back-barrier lagoon or estuary and not in the existing open marine environment. This deposit may be either Pleistocene-age or have been deposited during the Holocene transgression.

A third group of deposits consisting of gray to grayish-brown sand and mud is very similar in character to the modern sediment layer but contains small percentages of glauconite and a foraminiferal fauna characterized by a greater diversity as well as a larger number of *Quinqueloculina* sp. than

the clearly modern deposits. Whether this is a relict, possibly hypersaline lagoon, deposit or a facies of the modern sediment is unclear.

In summary, it appears that modern and relict deposits in the study area can be differentiated in most cases by bulk properties (i.e., shear strength, water content, density), glauconite content, the presence or absence of fauna, and in some cases by the nature of the faunal assemblage. More precise sediment age determinations will be available when the results from seven radiocarbon-14 analyses are made on shells and wood fragments in cores 1, 2, 4, 7, 14, and 28.

4. Suitability of Sandfill for Beach Nourishment.

The suitability of sand as fill material in the restoration and maintenance of beaches depends on such factors as mineralogic composition, transport distance from the project site, percentage of fine-grained sediments, means of dredging, methods of transport and placement, grain size, and total grain-size distribution (degree of sorting). The relation of these factors to the total design of beach fills is discussed in Krumbein and James (1965), James (1974, 1975), Dean (1974), Hobson (1977), and in pages 5-9 to 5-18 of the SPM (U.S. Army, Corps of Engineers, Coastal Engineering Research Center, 1977).

Borrow material should be at least the same size or, preferably, slightly coarser than native material on the beach to be nourished. Borrow material that is significantly finer in grain size than native sand will probably be less stable than the natural material and hence more easily eroded. The net effect would be an accelerated retreat of the beach in an attempt to readjust nearshore profiles which would require considerably larger volumes of initial fill as well as more frequent nourishment. If the borrow sand does not have the same grain-size characteristics as the native beach sand, the grain-size population of the borrow sand should have a greater variation in grain size than the native beach sand. However, the borrow sand should not contain large amounts of fine-grained silts and clays (< 0.063 millimeter or > 4 phi) which, if placed on the beach, would soon be introduced to the nearshore zone. Turbidity caused by the solids could have a detrimental impact on native marine fauna and also be esthetically displeasing. Borrow material should also be composed of hard, chemically and physically resistant minerals (e.g., quartz) which will not readily degrade in the high-energy nearshore beach-dune environment.

The grain size of native beach sand decreases from High Island west to Surfside (Fig. 14), but all the beach sand is in the very fine to fine grain-size range (0.063 to 0.25 millimeter, 4 to 2 phi). Most beach sand is moderately sorted (0.71 to 1.0 millimeter) to very well sorted (< 0.35 millimeter). Borrow material should ideally meet or exceed these size and sorting criteria.

5. Dredging Effects on the Shore.

Another factor to be carefully evaluated when considering offshore sand as a source of fill in beach nourishment is the possible effects of

Figure 14. Mean grain-size diameter (in millimeters) for native beach sands along the Texas coast from the Sabine River to Surfside Beach (modified from Hsu, 1960).

dredging on the stability of the adjacent coast. Some important variables are the distance of the potential fill from the adjacent shore, the water depths over the borrow site, and the side slopes of the dredge area. Most shores composed of loose granular sediments maintain a profile across the beach and shoreface which is in dynamic equilibrium with the waves and tides which affect it. The profile segment landward of some "close-out" depth generally shows changes in sea floor elevation over relatively short time periods which suggest that sediments are routinely being transported to and from the beach over the entire profile. Seaward of the close-out depth the profile elevation remains almost unchanged, suggesting that sediments are little affected by normal waves and tides and that removal of offshore sediments would not significantly affect sediments on the beach. However, if sufficient quantities of sand are dredged and removed from sea floor areas inshore of the close-out depth, a sand sink may be formed which could promote erosion on the adjacent shore until the depression is filled and a profile of equilibrium is again attained. Such a practice would be self-defeating to beach nourishment and should be avoided.

The position of the close-out limit as defined by water depth varies considerably, depending on the composition of the shore and the wave climate; its distance from shore depends on the slope of the sea floor. The subject of defining the seaward limit of sand transport due to surface waves, and its relation to the effects of nearshore dredging on the shore are of vital importance to the practice of beach nourishment and are areas of active research at the Coastal Engineering Research Center.

For the Galveston coast, the close-out depth on an offshore profile has been calculated to be approximately 4.4 meters (14.5 feet), using an extreme wave height of 1.9 meters (6.2 feet) with a period of 9.4 seconds. A discussion of the methods used to arrive at this seaward-limit value is in Hallermeier (1977). The wave gage data used are from Thompson (1977). Because of the acknowledged lack of precision in making these close-out determinations and because wave heights may be larger elsewhere in the study area, the estimated close-out has been increased by 25 percent. Therefore, it is recommended that no sand be removed shoreward of the 5.5-meter (18 feet) depth contour, with the exception of outer bars and shoals of inlets. This exception applies to the ebb tidal shoal complex at San Luis Pass, and possibly to the shoal south of Galveston Inlet, and is discussed in greater detail later in this section.

6. Potential Offshore Sand Borrow Sites.

Interpretations of the cores and seismic records obtained during this study, along with other geologic information from the TBEG grab samples and the deep engineering borings taken in the vicinity of Galveston, San Luis Pass, and Freeport Inlet, reveal that sand with textural properties suitable for beach fill is apparently available in five areas. As shown in Figure 15, the sites are divided into two types: "possible borrow areas" A, B, part of C, and E (areas where the data show that sand is available but may be low quality due to the presence of silt and clay

Figure 15. Map of five sites (A to E) selected as possible locations for obtaining sand for beach nourishment.

size sediments, or seismic records show the sand deposits vary considerably in thickness and areal extent); "high priority borrow areas," part of C and D (areas located on the shoal south of Galveston Inlet and in the vicinity of the ebb tidal shoal near San Luis Pass). The most pertinent information on the five borrow areas is contained in Table 2. Of the 34 cores obtained (see App. A), 84 samples from 20 cores (3, 5, 11, 12, 14 to 19, 21 to 28, 33, and 34) had enough sand for textural analysis (see App. B). Appropriate textural data are summarized for each borrow area in Table 2.

a. High Island to Crystal Beach. Of the cores taken in this region, only cores 3 and 5 contain sand in quantity. Core 5, taken about 4 kilometers (2.5 miles) off Gilcrest, contains only about 30 centimeters (1 foot) of fine sand at the bottom of the core; the thick overburden of soft mud and stiff clay eliminates this as a possible borrow site. Core 3 in area A (Fig. 16) was taken in a filled stream channel about 5.5 kilometers (3.3 miles) offshore. This channel extends close to shore (Fig. 16) but is not visible on the seismic profile closest to shore. The sand in core 3 is very fine and present as thin lenses interbedded with silts and clays which make the material of marginal quality for beach fill. However, it is the best prospect in the Gilcrest-High Island offshore region. The volume estimate of 6.8 million cubic meters (8.9 million cubic yards) for this deposit (Table 2) includes the fine-grained constituents as well as the sand. The net volume of sand is probably 50 to 70 percent of the estimate. The remaining cores in this region contain stiff gray-green clay or cohesive mud. Seismic records show numerous other buried channels but they are either too small to be significant sand repositories or they are filled with cohesive modern muds as shown in cores 8 and 9 (App. A). The seismic records also show a thinly buried pipeline crossing area A in a shore-parallel orientation just inshore of the 9.1-meter (30 feet) depth contour. This is a 50.8-centimeter (20 inches) gasline which would preclude dredging in the immediate vicinity.

b. Galveston Inlet. Borrow area B is adjacent to the north jetty of Galveston Inlet and contains cores 11 and 12 (Fig. 17). Core 11 was taken on the flank of a buried channel about 4 kilometers off Bolivar Beach; core 12, taken in 7 meters (23 feet) of water, penetrated the fill of the ancestral Trinity River. Both cores contain sand but the entire area appears to be overlain by about 1 meter (3 feet) of very soft mud (Table 2). To remove the sand in area B the mud overburden would have to be removed and disposed of in an environmentally acceptable manner. It is possible that the overburden becomes thinner toward shore, but removal of material in water shallower than 5.5 meters could aggravate erosion on the adjacent shore and is not recommended without evaluating the impact.

Borrow area C to the south of Galveston Inlet is triangular in plan view and comprises the lower shoreface and shoal area off Galveston Beach (Fig. 17). It actually consists of two areas. The area of highest potential includes cores 15, 17, and 18 which contain relatively clean, fine-grained sand interbedded with thin mud and muddy sand layers. Seismic records show that the horizontal stratification in the cores extends

Table 2. Characteristics of possible borrow sites.

Designation	Core (No.)	Water depths (m)	Thickness (m)	Mean grain diameter (mm)	Standard deviation (phi units)	Mud overburden (m)	Area ($10^6 m^3$)	Est. volume ($10^6 m^3$)	Remarks
A	3	6 to 10	>2.3 ≤8.2	0.11 to 0.16	0.5 to 1.00	None	2.9	6.8 ¹	Sand is interbedded with mud as channel fill. Buried 20-inch gasoline crosses site and may be a hazard to dredging.
8	11 12	5.5 to 8.5	1.7 1	0.16 to 0.23 0.16 to 0.23	0.42 to 1.04 0.50 to 1.39	1.3 1	9.9	9.9 ²	Sand in C-11 occurs as basal channel fill and Pleistocene erosion surface. Sand in C-12 occurs in two layers separated by 0.9 meter of mud and sandy mud.
C	14 15 17 18	5.5 to 9.8	2 0.3 ≥0.5 ≤5.4 ≤9.1 4	0.12 to 0.19 0.12 to 0.19 0.13 to 0.17 0.10 to 0.16	0.51 to 1.06 0.53 to 1.02 0.40 to 0.81 0.43 to 0.78	None 0.4 0.7 None	27.6	20.6 ³	Sand in C-14 is interbedded with muddy sand in dredge disposal area. Sand in C-15 occurs in two layers separated by 1.6 meters of mud and sandy mud. Sand in 17 and 18 is interbedded with muddy sand.
D	25 27	1.5 to 9.1	>1.5 ≤9.1	0.13 to 0.24 0.15 to 0.17	0.37 to 0.60 0.57 to 1.24	None None	12.6	23.2 ⁴	
E	34	5.5 to 7	2.5	0.10 to 0.12	0.61 to 0.88	0.1	0.8	2.1 ⁵	Muddy sand in C-34 possibly part of the relict Brazos River delta.

¹Based on thickness of 2.3 meters.²Based on thickness of 1 meter.³Based on thickness of 1 meter in high potential area and 0.5 meter in possible area.⁴Based on thickness of 2 meters.⁵Based on thickness of 2.5 meters.

Figure 16. Possible borrow area A, which is confined to a relict buried stream channel cut into the Pleistocene erosion surface.

Figure 17. Map of possible borrow site B, and site C which has a high potential inshore area.

throughout the borrow area but the sediments probably become progressively finer seaward from core 15. Core 14 at the seaward boundary of the area contains 2 meters of sand but it is just within the authorized dredged-material disposal area and it is probably a unique occurrence, since most of the dredged material dumped there is fine grained in nature. The estimated volume of sandy sediment in area C is 20.6 million cubic meters (27 million cubic yards) using a thickness of 1 meter in the high priority area and 0.5 meter (1.6 feet) in the offshore region (Table 2).

Several cores on the Galveston shelf between area C and San Luis Pass contain sandy material worthy of textural analysis (App. A), but the sand layers are generally thin and the seismic data suggest that lateral continuity of the sand is lacking.

c. San Luis Pass. Borrow area D is a high potential area (Fig. 18); it contains the best quality sand as well as the largest estimated available volume for the entire study area. The area comprises the modern ebb tidal shoal (Fig. 19) of San Luis Pass and adjacent parts of the lower shoreface. Cores 26 and 27 contain fine to medium sand with small amounts of finer sediments. There is a possibility that the deposit in core 25 is correlative with that in core 23, 5 kilometers (3 miles) to the east. If this is correct, borrow area D would be considerably larger than shown. Additional cores are necessary to fully evaluate this possibility. An analysis of 16 borings taken at locations across San Luis Inlet as shown in Figure 20, as well as the offshore seismic profiles, shows that the stratigraphy in the region consists of generally sandy Holocene sediments overlying the Pleistocene unconformity at about -10 meters (-33 feet) which is considered the depth limit for dredging. Figure 20 also shows sandy sediments about 9 meters thick (borings 4 to 8) on the shoal east of the inlet channel and inshore of area D. The estimated volume of sand in area D using a 2-meter thickness, is 23.2 million cubic meters (30.3 million cubic yards) (Table 2). It could be considerably larger if more shoal area were included for the entire 10-meter thickness. As shown in Figure 18, the recommended area extends from water depths of only 1.5 to 9.1 meters (5 to 30 feet). This is an exception to the usual recommendation that no sand be dredged in water shallower than 5.5 meters. Walton and Dean (1976) suggest that inlet shoals, such as the one at San Luis Pass, may be excellent sources of fill sand, and that removal of the sand may not be detrimental to adjacent coastal areas. They show that such shoals refract incident waves, making adjacent shores more vulnerable to erosion than if the inlet and offshore shoals were not present. Walton and Dean suggest that removal of fill sand from the shoals may indirectly reduce erosion on adjacent coasts by making the wave refraction patterns more uniform along the coast. In 1975, sand in water depths of 2 meters, dredged from the ebb tidal shoal at Fripp Inlet, was successfully used for beach fill at Hunting Island, South Carolina. No negative effects on the adjacent coast have been reported (Hobson, in preparation, 1979).

d. San Luis Pass to Freeport Inlet. Of the seven cores taken in this area, only core 34 (Fig. 21) contains enough sand to warrant designating the site (off Surfside Beach) a possible borrow area (area E). The sand

Figure 18. Borrow area D, which consists of the San Luis ebb tidal shoal and adjacent shoreface. Area D is the most promising site as a source of sandfill for beach nourishment.

Figure 19. The sedimentary facies and different environments associated with San Luis Pass, which result from complex ebb and flood tidal processes. The high-energy shoal and delta areas offer the highest potential for sandfill of any locality in the study area (from Fisher et al., 1972).

San Luis Inlet Stratigraphy

LEGEND

Figure 20. Quaternary stratigraphy at San Luis Pass based on interpretations of descriptive logs of 16 (boring 9 not taken) borings. The Pleistocene surface in this profile correlates well with offshore data and is used to define the lower boundary for Borrow Area D.

Figure 21. Borrow area E off Surfside Beach at the west end of the survey area, defined by core 34 which contains muddy sand. This is the smallest and least promising of the five designated borrow sites.

is very fine grained and mixed with varying percentages of silt and clay (Table 2; App. B). The area is also overlain by about 12 centimeters (5 inches) of mud which could be a detriment to dredging. Seismic records in the area show several buried stream channels close to core 34; it is likely that the sand in core 34 is part of one of these small channels or alternately is part of the ancestral delta of the Brazos River which entered the gulf near this location in the past. The estimated sand volume in area E is 2.1 million cubic meters (2.7 million square yards), based on a thickness of 2.5 meters (8.1 feet); however, deep dredging close to the shore could aggravate the already serious erosion problems at Surfside Beach.

IV. SUMMARY AND RECOMMENDATIONS

The primary objective of this study was to determine the geologic character of the Texas inner shelf in order to evaluate the potential of sandy sediments suitable for nourishment of eroding beaches. Several hundred kilometers of high-resolution seismic reflection profiles were taken to identify the primary stratigraphic subbottom reflectors, buried stream channels, bars, and delta shoals in the area. Long cores were taken in 34 of the most promising sites and the seismic records were used to extrapolate the core stratigraphy to adjacent areas of the shelf. The major findings and recommendations are listed below.

a. The Pleistocene erosion surface is generally ≤ 3 meters below the sea floor, except for buried ancestral river channels, and because it is primarily composed of indurated clay, is considered the lower boundary for dredging of sand for beach nourishment.

b. None of the ancestral stream channels cut into Pleistocene sediments and filled with Holocene sediments contain high quality sand. However, a buried channel west of High Island contains muddy sand and is considered of marginal quality as a borrow site.

c. Five sites were selected as containing possible borrow material but only two, one at Galveston and one at San Luis Pass, were judged to be of high potential. The Galveston site consists of lower shoreface sand and a relict ebb tidal deltal complex; the San Luis Pass site comprises the modern outer bar and ebb tidal shoal complex. None of the sites contain any artifacts or structures of known archeological significance, and none contain obstructions that would interfere with dredging, except the gasline in area A.

d. Prior to project dredging, it is recommended that cores be taken in a dense grid matrix to provide more detailed information on the three-dimensional framework of the borrow site, as well as give additional textural data for proper design of the beach fill.

LITERATURE CITED

- ANDERSON, J.B., and CLARK, H.C., "Geologic Results of the Galveston Company Shore Erosion Study," U.S. Army Engineer District, Galveston, Galveston, Tex., unpublished, Apr. 1977.
- BARNES, B., et al., "Geologic Prediction: Developing Tools and Techniques for the Geophysical Identification and Classification of Sea Floor Sediments," TR ERL 224-MMTC-2, National Oceanic and Atmospheric Administration, Rockville, Md., 1972.
- BARTON, D.C., "Surface Geology of Coastal Southeast Texas," *American Association of Petroleum Geologists Bulletin*, Vol. 14, 1930, pp. 1301-1320.
- BERNARD, H.A., "Quaternary Geology of Southeast Texas," unpublished Ph.D. Dissertation, Louisiana State University, Baton Rouge, La., 1950.
- BERNARD, H.A., MAJOR, C.F., and PARROTT, B.S., "The Galveston Barrier Island and Environs: A Model for Predicting Reservoir Occurrence and Trend," *Gulf Coast Association of Geological Society Transactions*, Vol. IX, 1959, pp. 221-224.
- BERNARD, H.A., LEBLANC, R.J., and MAJOR, C.F., "Recent and Pleistocene Geology of Southeast Texas," *Geology of the Gulf Coast and Central Texas*, E.H. Rainwater and R.P. Zingula, eds., 1962, pp. 175-224.
- BERNARD, H.A., et al., "Recent Sediments of Southeast Texas: A Field Guide to the Brazos Alluvial and Deltaic Plains and the Galveston Barrier Island Complex," Guidebook 11, Bureau of Economic Geology, University of Texas, Austin, Tex., 1970.
- BULLARD, F.M., "Source of Beach and River Sands on Gulf Coasts of Texas," *Bulletin of the American Geological Society*, Vol. 53, July 1942, pp. 1021-1044.
- DEAN, R.J., "Compatibility of Borrow Materials for Beachfills," *Proceedings of the 14th Coastal Engineering Conference*, American Society of Civil Engineers, 1974.
- EWING, J.I., "Elementary Theory of Seismic Refraction and Reflection Measurements," *The Earth Beneath the Sea*, Vol. 3, 1963, pp. 3-19.
- FISHER, W.L., et al., "Environmental Geologic Atlas of the Texas Coastal Zone-Galveston-Houston Area," Texas Bureau of Economic Geology, Austin, Tex., 1972.
- FISHER, W.L., et al., "Environmental Geologic Atlas of the Texas Coastal Zone-Beaumont-Port Arthur Area, Texas Bureau of Economic Geology, Austin, Tex., 1973.

- GARNER, L.E., "Sand Resources of Texas Gulf Coast," Report of Investigation No. 60, Texas Bureau of Economic Geology, Mar. 1967.
- GRAF, C., "The Late Pleistocene Ingleside Barrier Trend, Texas and Louisiana," unpublished M.S. Thesis, Rice University, Houston, Tex., 1966.
- HALLERMEIER, R.J., "Calculating a Yearly Limit Depth to the Active Beach Profile," TP 77-9, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Sept. 1977.
- HICKS, S.D., "On the Classification and Trends of Long Period Sea Level Series," *Shore and Beach*, Vol. 40, Apr. 1972, pp. 20-23.
- HOBSON, R.D., "Review of Design Elements for Beach-Fill Evaluation," TP 77-6, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., June 1977.
- HOBSON, R.D., "Typical U.S. Beach Nourishment Requirements Using Off-shore Sand Deposits," U.S. Army Engineer Waterways Experiment Station, Vicksburg, Miss. (in preparation, 1979).
- HSU, K.J., "Texture and Mineralogy of the Recent Sands of the Gulf Coast," *Journal of Sedimentary Petrology*, Vol. 30, No. 3, 1960, pp. 380-403.
- JAMES, W.R., "Beach Fill Stability and Borrow Material Texture," *Proceedings of the 14th International Coastal Engineering Conference*, American Association of Civil Engineers, 1974, pp. 1334-1347.
- JAMES, W.R., "Techniques in Evaluating Suitability of Borrow Material for Beach Nourishment," TM-60, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Dec. 1975.
- KRUMBEIN, W.C., and JAMES, W.R., "A Lognormal Size Distribution Model for Estimating Stability of Beach Fill Material," TM-16, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Washington, D.C., Nov. 1965.
- LANKFORD, R.R., and REHKEMPER, L.J., "The Galveston Bay Complex: A Summary of Characteristics," *Holocene Geology of the Galveston Bay Areas*, L.J. Lankford and J.W. Rogers, eds., Houston Geology Society, Delta Study Group, Houston, Tex., 1969, pp. 1-11.
- LEBLANC, R.J., and BERNARD, H.A., "Resume of Late Recent Geological History of the Gulf Coast," *Geologie en Mijnbouw*, Vol. 16, 1954, pp. 185-194.
- LEBLANC, R.J., and HODGSON, W.D., "Origin and Development of the Texas Shoreline," *Gulf Coast Association of Geological Society Transactions*, Vol. IX, 1959, pp. 197-220.

- LING, S.C., "State-of-the-Art of Marine Soil Mechanics and Foundation Engineering," TR S-72-11, U.S. Army Engineer Waterways Experiment Station, Vicksburg, Miss., 1972.
- McGOWEN, J.H., et al., "Environmental Geologic Atlas of the Texas Coastal Zone - Bay City - Freeport Area," Texas Bureau of Economic Geology, Austin Tex., 1976.
- MOORE, D.G., and PALMER, H.P., "Offshore Seismic Reflection Surveys," *Proceedings of the Conference on Civil Engineering in the Oceans*, American Society of Civil Engineers, 1967, pp. 789-806.
- PETTIT, B.M., Jr., and WINSLOW, A.G., "Geology and Ground Water Resources of Galveston County, Texas," Water Supply Paper 1416, U.S. Geological Survey, Washington, D.C., 1957.
- RAMSEY, M.D., and GALVIN, C.J., Jr., "Size Analysis of Sand Samples from Southern New Jersey Beaches," MR 77-3, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Mar. 1977.
- REHKEMPER, L.J., "Sedimentology of Holocene Estuarine Deposits, Galveston Bay," *Galveston Bay Geology*, R.R. Lankford and J.W. Rogers, eds., Houston Geology Society, Houston, Tex., 1969.
- THOMPSON, E.F., "Wave Climate at Selected Locations Along U.S. Coasts," TR 77-1, U.S. Army, Corps of Engineers, Coastal Engineering Research Center, Fort Belvoir, Va., Jan. 1977.
- TIREY, G.B., "Recent Trends in Underwater Soil Sampling Methods," Special Technical Publication 501, American Society for Testing and Materials, Philadelphia, Pa., 1972.
- U.S. ARMY, CORPS OF ENGINEERS, "Report on National Shoreline Study," Washington, D.C., Aug. 1971.
- U.S. ARMY, CORPS OF ENGINEERS, COASTAL ENGINEERING RESEARCH CENTER, *Shore Protection Manual*, 3d ed., Vols. I, II, and III, Stock No. 008-022-00113-1, U.S. Government Printing Office, Washington, D.C., 1977, 1,262 pp.
- U.S. ARMY ENGINEER DISTRICT, GALVESTON, "Galveston County Shore Erosion Study," Galveston, Tex., Oct. 1976.
- WALTON, T.L., Jr., and DEAN, R.G., "Use of Outer Bars of Inlets as Sources of Beach Nourishment Material," *Shore and Beach*, Vol. 44, No. 2, July 1976, pp. 13-19.

APPENDIX A

CORE SEDIMENT DESCRIPTIONS

This appendix contains core sediment descriptions, based on both megascopic and microscopic examination, from sampling locations shown in Figure 8. Sediment color is based on damp samples.

Sediment names are based on the following Wentworth size scale:

Sediment	Size (mm)	Phi
Gravel	>2	<-1
Very coarse sand	1.0 to 2.0	0 to -1
Coarse sand	0.5 to 1.0	1 to 0-
Medium sand	0.25 to 0.5	2 to 1-
Fine sand	0.125 to 0.25	3 to 2-
Very fine sand	0.0625 to 0.125	4 to 3-
Silt and mud	<0.0625	>4

Sorting terms	
Very well sorted	0.35
Well sorted	0.50
Moderately well sorted	0.80
Moderately sorted	1.40
Poorly sorted	2.00
Very poorly sorted	2.60
Extremely poorly sorted

1. Sediment textural analysis (App. B)
2. Gray, soft, interbedded, moderately sorted, fine sands and muds, rhythmic bedding evident
3. Gray, compact, moderately sorted, very fine to fine sand with thin gray mud lenses toward bottom

CORE # 3-717.5
WATER
DEPTH 10.1m (33 ft)
RECOVERY 2.3m (7.7 ft)

1. Pleistocene surface
2. Grayish-green, stiff mud with tan oxidation streaks
3. Radiocarbon-14 age date
4. Tan, firm, muddy, very fine sand with many whole mercenaria shells
5. Tan, firm, muddy, very fine sand with many broken and immature shells
6. Gray, firm, sandy mud with many shell fragments

CORE # 4-750
WATER
DEPTH 8.8m (29 ft)
RECOVERY 6.1m (20 ft)

1. Dark-gray to brown, soft, cohesive mud with thin sand lenses; mud becomes firmer with depth

CORE # 9-674

WATER
DEPTH 9.1m (30 ft)

RECOVERY 5.3m(17.5 ft.)

1. Dark-grayish brown, very soft mud
2. Pleistocene surface
3. Greenish-gray, firm clay
4. Light-gray, firm, muddy, very fine sand
5. Tannish-gray, stiff clay, some thin sandy lenses and some scattered large shells at 260 cm

CORE # 10-660

WATER
DEPTH 9.4m (31 ft)

RECOVERY 5.3m(17.3 ft.)

1. Brown, very soft mud
2. Sediment textural analysis (App. B)
3. Brown, soft, muddy, fine sand
4. Grayish-brown, soft mud
5. Dark-gray sandy mud with 1- to 2-cm layers of muddy sand
6. Gray, very fine to fine sand

CORE # 15-871

WATER
DEPTH 7.6m (25 ft)

RECOVERY 2.6m (8.6 ft)

1. Brown, very soft mud with thin muddy sand layers; gray, moderately sorted, fine sand (52 to 57 cm)
2. Sediment textural analysis (App. B)
3. Brown, soft mud with thin, muddy sand layers
4. Dark-gray, muddy, fine sand with abundant shell fragments at 153 to 159 cm
5. Dark-gray, sandy mud with thin layers of muddy sand
6. Dark-gray, soft, cohesive clay

CORE # 16-614

WATER
DEPTH 8m (32 ft)

RECOVERY 4.3m (14.1 ft)

1. Dark grayish-brown, very soft mud
2. Gray, muddy, coarse sand and yellowish-gray, firm, sandy mud
3. Tannish-gray gravel
4. Pleistocene surface
5. Yellowish-gray and tan (oxidized), stiff clay
6. Calcareous nodule

CORE # 31-526

WATER
DEPTH 11.6m (38 ft)

RECOVERY 5.5m (18 ft)

1. Reddish-brown, soft, silty, very fine sand
2. Pleistocene surface
3. Reddish-brown and yellowish-gray, firm to stiff clay
4. Greenish-gray, firm to stiff clay
5. Reddish-brown, stiff clay becomes sandy for bottom 10 cm

CORE # 32-379

WATER
DEPTH 6.7m (22 ft)

RECOVERY 4.3m (14.1 ft)

APPENDIX B

GRANULOMETRIC DATA AND CUMULATIVE CURVE PLOTS

This appendix contains the results of Rapid Sand Analyzer (RSA) size analyses of selected sediment samples from 15 cores in the study area shown in Figure 8. Also included are sieve data from one sample too coarse to process by RSA. Analyses are based on sand-size fractions only.

The samples are identified by core number and sample interval below the top of the core. Specific locations of the samples from each core are shown in Appendix A.

Data include the frequency percent at 0.5-phi intervals along with the cumulative percent which indicates the percentages of sand grains coarser than the size shown. Also included are the median, mean, standard deviation (sorting), skewness, and kurtosis for each sample.

Experience has shown that grain-size values from RSA analyses are consistent and slightly coarser than results of dry sieve analyses of identical samples. To relate these RSA data to other sieve data, empirical relations for converting RSA means and standard deviation to sieve analyses equivalents have been determined. The relationships, developed from RSA and sieve analyses at a 0.25-phi interval, are:

$$\text{mean: } \bar{x}_{\phi \text{ sieve}} = 1.0735 \bar{x}_{\phi \text{ RSA}} + 0.1876$$

RSA standard deviation values may be converted to sieve sorting equivalents by the formula:

$$\text{standard deviation: } \sigma_{\phi \text{ sieve}} = 1.4535 \sigma_{\phi \text{ RSA}} - 0.146$$

In addition, cumulative curves of RSA data from the samples, plotted by computer, are included. Sample plots are not necessarily in consecutive order.

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

C#, 0003-0017

REFERENCE QUOTED 151 CONSECUTIVE NUMBER 3 MARSDEN SQUARE 82 LOG SQUARE 24 DEPTH ZONE 0 CORE TOP BOTTOM(CM) 0 ANALYSIS CODE 0 SAMPLE ID CORE 3 LATITUDE 29 29.10N LONGITUDE 096 23.67W

GALVESTON/CORE 03/000C(TOP)

07-09-77

PHI	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
0.50	1.014	0.00	0.00	0.00	10.22
0.60	1.000	4.75	4.75	0.06	11.52
0.70	0.707	2.11	6.86	0.06	8.03
1.00	0.500	1.28	8.14	0.09	5.41
1.50	0.354	1.65	9.79	0.09	3.49
2.00	0.250	2.15	11.94	0.04	2.12
2.50	0.177	17.31	29.25	0.07	1.22
3.00	0.125	24.52	53.77	0.07	0.85
3.50	0.08	45.38	99.15	0.05	0.45
4.00	0.03	16.75	100.00	0.05	0.00
4.50	0.02	0.00	100.00	0.00	0.00

16 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS

PHI MM.
2.68
2.70
0.95
-1.39
5.36

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

LONGITUDE
096 23.67W

LATITUDE
29 29.10N

SAMPLE ID
CORE 3

16 PCT.
50 PCT.
84 PCT.

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42
2.84

ANALYSIS CODE 0
CORE TOP BOTTOM(CM) 0

LATITUDE
29 29.10N

LONGITUDE
096 23.67W

07-09-77

0.06
1.42

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CM, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	I DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CODE	LATITUDE	LONGITUDE
151	3	82	29	A	200	200	0	CODE 3	29 29.10N	090 23.70W

GALVESTON/CORE 01/200CM(=0.0 FT)

07-09-77

PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
.50	.707	0.00	0.00	
1.00	.500	.17	.17	8.03
1.50	.354	2.23	2.40	5.91
2.00	.250	2.77	5.16	3.49
2.50	.177	14.23	19.39	2.12
3.00	.125	31.89	51.28	1.22
3.50	.088	40.14	91.43	.67
4.00	.063	8.57	100.00	.55
.LT.	.400	.062	100.00	

STATISTICAL PARAMETERS

PHI
MM.
2.9A
2.90
1.134
1.024
1.02
4.30

MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

16 PCT.
50 PCT.
84 PCT.

76
1.20
2.27

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	I DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CODE	LATITUDE	LONGITUDE
151	3	82	29	A	235	235	0	CODE 3	29 29.10N	090 23.70W

GALVESTON/CORE 01/235CM(=7.7 FT HTM)

07-09-77

PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
0.00	1.000	0.00	0.00	
.50	.707	2.83	2.83	11.52
1.00	.500	4.16	6.99	8.03
1.50	.354	7.43	14.42	5.41
2.00	.250	2.86	10.29	3.49
2.50	.177	6.98	17.25	2.12
3.00	.125	17.67	34.92	1.22
3.50	.088	35.51	70.44	.67
4.00	.063	29.56	100.00	.43
.LT.	.400	.062	100.00	

STATISTICAL PARAMETERS

PHI
MM.
3.25
3.00
1.125
1.024
1.02
5.71

MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

16 PCT.
50 PCT.
84 PCT.

54
1.91
2.25

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	5	42	29	A	340	340	0	CONF 5	29 28.30N	094 29.00W

GALVESTON/CORE 05/340CM(=11.2 FT)

07-09-77

PHI MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00		22.72	PHI
-0.50	1.414	.19	.19		16.22	MM
0.00	1.000	16.66	11.05		11.52	3.01
.50	.707	4.94	15.09		8.03	.174
1.00	.500	1.98	17.07		5.41	.172
1.50	.354	1.01	18.06		3.49	2.412
2.00	.250	1.64	19.73		2.12	1.27
2.50	.177	.66	26.37		1.22	-1.36
3.00	.125	21.16	49.53		.67	3.46
3.50	.088	33.90	83.43		.43	
4.00	.063	18.57	100.00			
4.50	.042	0.00	100.00			

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	5	82	29	A	340	340	0	CONF 5	29 28.30N	094 29.00W

GALVESTON/CORE 05/340CM(=11.2 FT)

07-09-77

PHI MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00		16.22	PHI
-0.50	1.414	4.43	4.43		11.52	MM
0.00	1.000	4.97	9.79		8.03	2.97
.50	.707	3.23	13.02		5.41	.127
1.00	.500	.91	13.93		3.49	.161
1.50	.354	2.62	16.75		2.12	2.049
2.00	.250	10.32	27.07		1.22	1.04
2.50	.177	24.62	51.69		.67	-1.52
3.00	.125	36.00	87.69		.50	4.25
3.50	.088	0.00	100.00			
4.00	.063	0.00	100.00			
4.50	.042	0.00	100.00			

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	5	82	29	A	340	340	0	CONF 5	29 28.30N	094 29.00W

GALVESTON/CORE 05/340CM(=11.2 FT)

07-09-77

PHI MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00		16.22	PHI
-0.50	1.414	4.43	4.43		11.52	MM
0.00	1.000	4.97	9.79		8.03	2.97
.50	.707	3.23	13.02		5.41	.127
1.00	.500	.91	13.93		3.49	.161
1.50	.354	2.62	16.75		2.12	2.049
2.00	.250	10.32	27.07		1.22	1.04
2.50	.177	24.62	51.69		.67	-1.52
3.00	.125	36.00	87.69		.50	4.25
3.50	.088	0.00	100.00			
4.00	.063	0.00	100.00			
4.50	.042	0.00	100.00			

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	5	82	29	A	340	340	0	CONF 5	29 28.30N	094 29.00W

GALVESTON/CORE 05/340CM(=11.2 FT)

07-09-77

PHI MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00		16.22	PHI
-0.50	1.414	4.43	4.43		11.52	MM
0.00	1.000	4.97	9.79		8.03	2.97
.50	.707	3.23	13.02		5.41	.127
1.00	.500	.91	13.93		3.49	.161
1.50	.354	2.62	16.75		2.12	2.049
2.00	.250	10.32	27.07		1.22	1.04
2.50	.177	24.62	51.69		.67	-1.52
3.00	.125	36.00	87.69		.50	4.25
3.50	.088	0.00	100.00			
4.00	.063	0.00	100.00			
4.50	.042	0.00	100.00			

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARGIN SQUARE	I DG. SQUARE	DEPTH ZONE	CORE TOP	ROTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	11	82	29	A	140	140	0	CONF11	29 23.40N	099 39.40E

GALVESTON/CONF 11/140CM(=4.5 FT)

07=10-77

PHI	MM*	FREQUENCY	CUMULATIVE	FALL
SIZE	PERCENT	PERCENT	VELOCITY	VELOCITY
-1.00	2.000	0.00	0.00	22.72
.50	1.314	.55	.55	16.22
0.00	1.000	.14	.69	11.52
.50	.707	.11	1.01	8.03
1.00	.500	.07	1.08	5.41
1.50	.354	.31	1.39	3.49
2.00	.250	1.20	2.59	2.12
2.50	.177	36.69	39.28	1.22
3.00	.125	38.10	77.38	.90
3.50	.068	88.74	100.00	
4.00	.063	11.26	100.00	
.LT.	.400	.062	100.00	

STATISTICAL PARAMETERS

PHI	MM*
2.61	.163
2.69	.155
.59	1.503
-1.02	
9.99	

16 PCT.
50 PCT.
84 PCT.

.89
1.87
2.72

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARGIN SQUARE	I DG. SQUARE	DEPTH ZONE	CORE TOP	ROTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	11	82	29	A	200	200	0	CONF11	29 23.40N	099 39.40E

GALVESTON/CONF 11/200CM(=6.5 FT)

07=10-77

PHI	MM*	FREQUENCY	CUMULATIVE	FALL
SIZE	PERCENT	PERCENT	VELOCITY	VELOCITY
0.00	1.000	0.00	0.00	11.52
.50	.707	.50	.50	8.03
1.00	.500	1.73	2.23	5.41
1.50	.354	4.02	4.02	3.49
2.00	.250	10.15	14.16	2.12
2.50	.177	48.10	62.27	1.26
3.00	.125	37.73	100.00	
3.50	.068	100.00	100.00	
.LT.	.400	.062	100.00	

STATISTICAL PARAMETERS

PHI	MM*
2.37	.193
2.33	.199
.42	1.340
-1.57	
7.30	

16 PCT.
50 PCT.
84 PCT.

1.70
2.37
3.43

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	11	82	29	A	240	240	0	CORE11	29 23.40N	094 39.40W

GALVESTON(CORE 11/240CM(=7.8 FT))

07=10=77

PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
10 PCT.	4.50	1.414	0.00	16.22
50 PCT.	0.00	1.000	4.68	11.52
60 PCT.	1.50	0.707	3.46	8.03
	1.00	0.500	11.81	5.41
	1.50	0.354	20.06	3.15
	2.00	0.250	31.15	2.12
	2.50	0.177	45.83	1.22
	3.00	0.125	64.15	0.67
	3.50	0.086	84.39	0.43
	4.00	0.063	100.00	
LT.	4.00	0.062	100.00	

STATISTICAL PARAMETERS

PHI	MM.
2.59	.166
2.36	.105
1.04	2.042
-.77	
2.67	

MEDIAN	MEAN
STANDARD DEVIATION	MEAN
SKEWNESS	2.042
KURTOSIS	2.67

10 PCT.
50 PCT.
60 PCT.

79
95
5.80

REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	11	82	29	A	250	250	0	CORE11	29 23.40N	094 39.40W

GALVESTON(CORE 11/250CM(=8.2 FT))

07=10=77

PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
10 PCT.	4.50	1.414	0.00	16.22
50 PCT.	0.00	1.000	4.27	11.52
60 PCT.	1.50	0.707	3.18	8.03
	1.00	0.500	11.81	5.41
	1.50	0.354	20.06	3.15
	2.00	0.250	31.15	2.12
	2.50	0.177	45.83	1.22
	3.00	0.125	64.15	0.67
	3.50	0.086	84.39	0.43
	4.00	0.063	100.00	
LT.	4.00	0.062	100.00	

STATISTICAL PARAMETERS

PHI	MM.
2.19	.219
2.20	.218
-.59	1.507
-.56	
3.61	

MEDIAN	MEAN
STANDARD DEVIATION	MEAN
SKEWNESS	1.507
KURTOSIS	3.61

10 PCT.
50 PCT.
60 PCT.

1.46
2.92
4.86

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 1 OF 2					CN. 0005-0017				
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	DEPTH TOP	DEPTH BOTTOM	ANALYSIS CODE	SAMPLE TO CONF	LONGITUDE
151	11	82	29	A	270	270	0	CONF11	094 39.00W
GALVESTON/COBE 11/270CM(-6.8 FT) 07-10-77									
PHI	M4.2	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
SIZE	SIZE				PHI	MM.			
1.00	2.000	0.00	0.00	5.41	2.11	.231			
1.50	1.500	0.33	1.33	3.49	2.15	.225			
2.00	1.000	36.18	37.50	2.12	2.17	1.022			
2.50	0.750	41.41	41.11	1.24	2.27				
3.00	0.500	18.49	100.00		2.44				
3.50	0.250	0.00	100.00						
4.00	0.000		100.00						
LT. 4.00	0.002								
16 PCT.				1.99					
50 PCT.				3.11					
84 PCT.				4.26					
GALVESTON/COBE 11/270CM(-6.8 FT) 07-10-77									
PHI	M4.2	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
SIZE	SIZE				PHI	MM.			
1.00	2.000	0.00	0.00	22.72	2.07	.239			
1.50	1.500	.43	1.43	16.22	2.13	.229			
2.00	1.000	.23	1.66	11.92	2.17	1.477			
2.50	0.750	.46	1.19	8.43					
3.00	0.500	.64	1.83	5.41					
3.50	0.250	1.09	3.35	3.49					
4.00	0.000	42.19	45.74	2.12					
4.50	0.125	30.97	76.72	1.22					
5.00	0.063	16.10	92.62	.86					
5.50	0.031	7.18	100.00						
6.00	0.016	0.00	100.00						
LT. 4.00	0.002								
16 PCT.				1.71					
50 PCT.				3.14					
84 PCT.				4.49					

GALVESTON, TEXAS - JEFF WILLIAMS PART 1 OF 2 CN. 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP BOTTH(CM)	CORE	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	12	82	29	7	115	115	0	CORE12	29 22.80N	094 41.50W

GALVESTON/CORE 12/115CM(-3.7 FT) 07-10-77

PHI	MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00	0.00	22.72	PHI MM
-1.50	1.014	1.38	1.38	1.38	16.22	2.65
0.00	1.000	6.44	7.82	7.82	11.52	2.15
1.50	0.707	15.64	23.45	23.45	8.03	1.39
1.00	0.500	5.70	29.15	29.15	5.41	2.628
1.50	0.354	3.68	32.83	32.83	3.49	1.78
2.00	0.250	5.57	38.41	38.41	2.12	
2.50	0.177	7.61	46.01	46.01	1.82	
3.00	0.125	16.69	62.71	62.71	1.67	
3.50	0.088	18.60	81.31	81.31	1.40	
4.00	0.063	18.69	100.00	100.00		
4.50	0.046	0.00	100.00	100.00		
4.75	0.033	0.00	100.00	100.00		
5.00	0.025	0.00	100.00	100.00		
5.25	0.019	0.00	100.00	100.00		
5.50	0.014	0.00	100.00	100.00		
5.75	0.010	0.00	100.00	100.00		
6.00	0.008	0.00	100.00	100.00		
6.25	0.006	0.00	100.00	100.00		
6.50	0.004	0.00	100.00	100.00		
6.75	0.003	0.00	100.00	100.00		
7.00	0.002	0.00	100.00	100.00		
7.25	0.001	0.00	100.00	100.00		
7.50	0.001	0.00	100.00	100.00		
7.75	0.000	0.00	100.00	100.00		
8.00	0.000	0.00	100.00	100.00		
8.25	0.000	0.00	100.00	100.00		
8.50	0.000	0.00	100.00	100.00		
8.75	0.000	0.00	100.00	100.00		
9.00	0.000	0.00	100.00	100.00		
9.25	0.000	0.00	100.00	100.00		
9.50	0.000	0.00	100.00	100.00		
9.75	0.000	0.00	100.00	100.00		
10.00	0.000	0.00	100.00	100.00		
10.25	0.000	0.00	100.00	100.00		
10.50	0.000	0.00	100.00	100.00		
10.75	0.000	0.00	100.00	100.00		
 				

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN NUMBER	1 DG, SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CONFID	LATITUDE 29 22.60N	LONGITUDE 094 41.50W
151	12	82	29	7	240	240	0			

GALVESTON/CORE 12/240CM(-7.8 FT)

07=10=77

PHI MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS
1.00	2.000	0.00	0.00	22.72	PHI MM.
.50	1.014	.04	.04	16.22	2.50
0.00	1.000	.22	.27	11.52	2.34
.50	.707	.91	.91	6.03	.192
1.00	.500	1.89	3.06	5.41	1.416
1.50	.354	3.20	6.26	3.49	.50
2.00	.250	5.01	11.27	2.12	-2.02
2.50	.177	38.67	49.94	1.26	8.50
3.00	.125	50.06	100.00		
3.50	.088	0.00	100.00		
4.00	.062	0.00	100.00		

16 PCT.
50 PCT.
84 PCT.

1.53
2.12
3.17

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN NUMBER	1 DG, SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CONFID	LATITUDE 29 22.60N	LONGITUDE 094 41.50W
151	12	82	29	7	440	440	0			

GALVESTON/CORE 12/440CM(-14.4 FT)

07=10=77

PHI MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS
1.00	2.000	0.00	0.00	16.22	PHI MM.
.50	1.014	.99	.99	11.52	2.77
0.00	1.000	1.71	2.70	6.03	.147
1.00	.500	1.03	3.73	5.41	.165
1.50	.354	2.53	6.26	3.49	1.557
2.00	.250	4.35	10.60	2.12	.50
2.50	.177	20.02	30.52	1.26	-2.24
3.00	.125	34.17	44.74	.84	8.99
3.50	.088	24.21	100.00		
4.00	.062	0.00	100.00		

16 PCT.
50 PCT.
84 PCT.

1.08
1.98
2.55

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	ROTATION(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	14	82	29	A	0	0	0	CONF14	29 17.40N	094 41.20W

GALVESTON/CORE 14/000CM(TOP)

07=11=77

PHI	MM.	FREQUENCY	CUMULATIVE	FALL
SIZE	SIZE	PERCENT	PERCENT	VELOCITY
.50	1.414	0.00	0.00	
0.00	1.000	.24	.24	16.22
.50	.707	3.34	3.58	11.52
1.00	.500	1.41	4.99	8.03
1.50	.354	2.73	7.72	5.91
2.00	.250	11.52	19.24	3.49
2.50	.177	27.57	46.81	2.12
3.00	.125	44.80	91.61	1.22
3.50	.088	8.19	100.00	1.04
4.00	.063	0.00	100.00	
.LT.	4.00	.062	100.00	

14 PCT.
50 PCT.
84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	ROTATION(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	14	82	29	A	0	0	0	CONF14	29 17.40N	094 41.20W

GALVESTON/CORE 14/000CM(TOP)

07=11=77

PHI	MM.	FREQUENCY	CUMULATIVE	FALL
SIZE	SIZE	PERCENT	PERCENT	VELOCITY
.50	.707	0.00	0.00	
1.00	.500	3.47	3.47	8.03
1.50	.354	2.90	6.37	5.91
2.00	.250	4.96	11.33	3.49
2.50	.177	29.22	40.55	2.12
3.00	.125	51.11	91.67	1.22
3.50	.088	8.33	100.00	1.04
4.00	.063	0.00	100.00	
.LT.	4.00	.062	100.00	

14 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS
PHI MM.
2.54 .172
2.34 .192
1.541
MEAN
STANDARD DEVIATION .63
SKEWNESS -1.68
KURTOSIS 6.27

STATISTICAL PARAMETERS
PHI MM.
2.59 .166
2.47 .180
1.436
MEAN
STANDARD DEVIATION .52
SKEWNESS -1.59
KURTOSIS 5.84

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 1 OF 2									
CN, 0003-0017									
REFERENCE NUMBER	CONSECUTIVE NUMBER	HARDEN SQUARE	LOG, SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE
151	14	82	29	A	62	62	0	CONF14	29 17.40N
GALVESTON/CORE 14/062CM(=2.0 FT)									
07-11-77									
PMT SIZE	MM, SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
0.00	1.000	0.00	0.00	11.52	PHI	MM,			
1.50	.707	1.10	1.10	11.52	2.53	.173			
1.00	.500	2.95	4.05	A.03	MEAN				
1.50	.354	2.53	6.58	5.41	STANDARD DEVIATION				
2.00	.250	5.46	12.04	3.49	SKEWNESS				
2.50	.177	34.76	46.80	2.12	KURTOSIS				
3.00	.125	53.20	100.00	1.26					
3.50	.088	0.00	100.00	1.26					
4.00	.062	0.00	100.00	1.26					
ALT, 0.00									
16 PCT, 50 PCT, 84 PCT,									
REFERENCE NUMBER	CONSECUTIVE NUMBER	HARDEN SQUARE	LOG, SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE
151	14	82	29	B	94	94	0	CONF14	29 17.40N
GALVESTON/CORE 14/094CM(=3.0 FT)									
07-11-77									
PMT SIZE	MM, SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
1.50	.707	0.00	0.00		PHI	MM,			
1.00	.500	1.06	1.06	A.03	MEAN				
1.50	.354	1.18	2.25	5.41	STANDARD DEVIATION				
2.00	.250	2.97	4.91	3.49	SKEWNESS				
2.50	.177	4.19	11.11	2.12	KURTOSIS				
3.00	.125	31.17	44.26	1.22					
3.50	.088	30.58	80.86	.67					
4.00	.062	19.14	100.00	.43					
ALT, 0.00									
16 PCT, 50 PCT, 84 PCT,									

GALVESTON, TEXAS - JEFF - ILLIAMS

PART 1 OF 2

CH. 0001-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CUBE TOP	CUBE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	1	10	29	A	124	124	0	CONF14	29 17.40N	094 41.20W

GALVESTON/CUBE 14/124CM(-0.0 FT)

07-11-77

PHI SIZE	M.M. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
0.50	1.014	0.00	0.00	16.22
0.50	1.000	0.20	0.20	11.52
1.00	1.000	1.17	1.37	6.03
1.50	1.000	1.15	2.51	3.49
2.00	1.000	1.05	3.56	2.42
2.50	1.000	1.05	4.61	1.52
3.00	1.000	1.05	5.66	0.77
3.50	1.000	1.05	6.71	
4.00	1.000	1.05	7.76	
4.50	1.000	1.05	8.81	
5.00	1.000	1.05	9.86	
5.50	1.000	1.05	10.91	
6.00	1.000	1.05	11.96	
6.50	1.000	1.05	13.01	
7.00	1.000	1.05	14.06	
7.50	1.000	1.05	15.11	
8.00	1.000	1.05	16.16	
8.50	1.000	1.05	17.21	
9.00	1.000	1.05	18.26	
9.50	1.000	1.05	19.31	
10.00	1.000	1.05	20.36	
10.50	1.000	1.05	21.41	
11.00	1.000	1.05	22.46	
11.50	1.000	1.05	23.51	
12.00	1.000	1.05	24.56	
12.50	1.000	1.05	25.61	
13.00	1.000	1.05	26.66	
13.50	1.000	1.05	27.71	
14.00	1.000	1.05	28.76	
14.50	1.000	1.05	29.81	
15.00	1.000	1.05	30.86	
15.50	1.000	1.05	31.91	
16.00	1.000	1.05	32.96	
16.50	1.000	1.05	34.01	
17.00	1.000	1.05	35.06	
17.50	1.000	1.05	36.11	
18.00	1.000	1.05	37.16	
18.50	1.000	1.05	38.21	
19.00	1.000	1.05	39.26	
19.50	1.000	1.05	40.31	
20.00	1.000	1.05	41.36	
20.50	1.000	1.05	42.41	
21.00	1.000	1.05	43.46	
21.50	1.000	1.05	44.51	
22.00	1.000	1.05	45.56	
22.50	1.000	1.05	46.61	
23.00	1.000	1.05	47.66	
 				

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CM, 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	15	82	29	7	40	40	0	CONF15	29 17.40N	099 43.80W

GALVESTON/CORE 15/0400CM(=1.3 FT)

07-11-77

PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
SIZE	707	0.00	0.00			PHI MM.
1.50	500	74	74		8.03	2.99
1.50	154	43	117		5.41	2.99
2.00	250	2.21	3.18		3.49	0.05
2.50	177	6.23	11.62		2.12	-1.23
3.00	125	39.14	50.75		1.22	6.29
3.50	684	41.53	92.29		1.67	
4.00	663	7.71	100.00		.55	
4.50	662	0.00	100.00			

16 PCT.
50 PCT.
80 PCT.

1.23
1.95

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	15	82	29	7	40	40	0	CONF15	29 17.40N	099 43.80W

GALVESTON/CORE 15/0400CM(=1.3 FT)

07-11-77

PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
SIZE	1.014	0.00	0.00			PHI MM.
0.50	1.000	15	15		16.22	3.01
1.50	707	73	88		11.52	2.91
1.00	500	45	1.32		8.03	0.61
1.50	154	2.83	4.15		5.41	-1.57
2.00	250	3.16	7.32		3.49	7.05
2.50	177	10.29	17.61		2.12	
3.00	125	48.95	58.56		1.22	
3.50	688	31.34	89.91		1.67	
4.00	663	37.06	100.00		.46	
4.50	662	0.00	100.00			

16 PCT.
50 PCT.
80 PCT.

1.21
2.23

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN. 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	15	82	29	7	213	213	0	CORE15	29 17.00N	090 43.80W

GALVESTON/CORE 15/213CM(=6.9 FT)

07=11-77

PHI SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00	22.72	PHI MM.
-0.50	1.014	.32	.32	16.22	3.31
0.00	1.000	.60	.60	1.52	.101
1.50	.707	1.05	1.96	0.03	.117
1.00	.500	1.06	3.04	5.41	1.705
1.50	.334	1.51	6.35	3.49	
2.00	.250	1.85	15.65	2.12	STANDARD DEVIATION
2.50	.177	7.26	31.13	1.22	SKEWNESS
3.00	.125	15.98	63.23	.67	KURTOSIS
3.50	.086	32.10	100.00	.43	
4.00	.063	36.77	100.00		
4.50	.042	100.00			

16 PCT.
50 PCT.
84 PCT.

.51
.83
2.04

REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	15	82	29	7	230	230	0	CORE15	29 17.00N	090 43.80W

GALVESTON/CORE 15/230CM(=7.5 FT)

07=11-77

PHI SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00	22.72	PHI MM.
0.00	1.014	.32	.32	16.22	2.83
0.50	1.000	.60	.60	1.52	.161
1.00	.707	1.05	7.35	0.03	.185
1.50	.500	1.06	10.21	5.41	2.029
2.00	.334	1.51	16.91	3.49	
2.50	.250	1.85	19.61	2.12	STANDARD DEVIATION
3.00	.177	7.26	26.94	1.22	SKEWNESS
3.50	.125	15.98	66.01	.67	KURTOSIS
4.00	.086	32.10	100.00	.43	
4.50	.063	100.00			
5.00	.042	100.00			

16 PCT.
50 PCT.
84 PCT.

1.03
1.45
4.57

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN. 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARKSDEN SQUARE #2	1 DG. SQUARE #2	DEPTH ZONE	CUR. TOP	CUR. BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	15		29	7	202	262	0	CORE 15	29 17.60N	090 03.80W

GALVESTON/CORE 15/262CM(=8.0 FT RTM.) 07-11-77

PHI	MM.	FREQUENCY	CUMULATIVE	FALL
SIZE	SIZE	PERCENT	PERCENT	VELOCITY
-5.0	1.400	0.00	0.00	
0.0	1.200	1.21	1.21	16.22
1.0	1.200	1.90	1.60	11.52
2.0	1.200	1.23	2.33	8.03
3.0	1.200	1.27	3.20	5.41
4.0	1.200	1.25	4.45	3.40
5.0	1.200	1.27	5.69	2.12
6.0	1.200	1.25	6.93	1.22
7.0	1.200	1.25	8.18	0.77
8.0	1.200	1.25	9.43	
9.0	1.200	1.25	10.68	
10.0	1.200	1.25	11.93	
11.0	1.200	1.25	13.18	
12.0	1.200	1.25	14.43	
13.0	1.200	1.25	15.68	
14.0	1.200	1.25	16.93	
15.0	1.200	1.25	18.18	
16.0	1.200	1.25	19.43	
17.0	1.200	1.25	20.68	
18.0	1.200	1.25	21.93	
19.0	1.200	1.25	23.18	
20.0	1.200	1.25	24.43	
21.0	1.200	1.25	25.68	
22.0	1.200	1.25	26.93	
23.0	1.200	1.25	28.18	
24.0	1.200	1.25	29.43	
25.0	1.200	1.25	30.68	
26.0	1.200	1.25	31.93	
27.0	1.200	1.25	33.18	
28.0	1.200	1.25	34.43	
29.0	1.200	1.25	35.68	
30.0	1.200	1.25	36.93	
31.0	1.200	1.25	38.18	
32.0	1.200	1.25	39.43	
33.0	1.200	1.25	40.68	
34.0	1.200	1.25	41.93	
35.0	1.200	1.25	43.18	
36.0	1.200	1.25	44.43	
37.0	1.200	1.25	45.68	
38.0	1.200	1.25	46.93	
39.0	1.200	1.25	48.18	
40.0	1.200	1.25	49.43	
41.0	1.200	1.25	50.68	
42.0	1.200	1.25	51.93	
43.0	1.200	1.25	53.18	
44.0	1.200	1.25	54.43	
45.0	1.200	1.25	55.68	
46.0	1.200	1.25	56.93	
47.0	1.200	1.25	58.18	
48.0	1.200	1.25	59.43	
49.0	1.200	1.25	60.68	
50.0	1.200	1.25	61.93	
51.0	1.200	1.25	63.18	
52.0	1.200	1.25	64.43	
53.0	1.200	1.25	65.68	
 	

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CURE TOP	ROTATION(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	16	82	29	R	155	155	0	CONF16	29 15.20N	090 00.50W

GALVESTON/CORE IN/ISSCM(=5.0 FT)

07-11-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
-1.00	2.000	0.00	0.00	0.00	22.72	
-1.50	1.414	0.23	0.23	0.23	16.22	
0.00	1.000	3.75	3.98	3.98	11.52	
1.00	0.707	3.19	7.17	11.15	8.03	
1.50	0.500	2.82	9.99	13.98	5.41	
2.00	0.354	2.19	12.18	16.17	3.49	
2.50	0.250	3.11	15.29	19.46	2.12	
3.00	0.177	6.52	21.82	26.00	1.22	
3.50	0.125	16.65	38.67	42.67	0.67	
4.00	0.083	25.47	64.14	68.00	0.40	
4.50	0.062	35.86	100.00	100.00	0.00	

STATISTICAL PARAMETERS

PHI

MM.

3.426

1.04

2.409

0.135

2.125

1.09

-1.57

0.69

STANDARD DEVIATION

SKEWNESS

KURTOSIS

16 PCT.
50 PCT.
84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CURE TOP	ROTATION(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	16	82	29	R	155	155	0	CONF16	29 15.20N	090 00.50W

GALVESTON/CORE IN/ISSCM(=5.0 FT)

07-11-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
-1.00	2.000	0.00	0.00	0.00	22.72	
-1.50	1.414	3.02	3.02	3.02	16.22	
0.00	1.000	5.21	8.23	8.23	11.52	
1.00	0.707	9.03	17.26	17.26	8.03	
1.50	0.500	2.02	19.28	19.28	5.41	
2.00	0.354	1.68	20.96	20.96	3.49	
2.50	0.250	4.27	25.23	25.23	2.12	
3.00	0.177	16.65	41.88	41.88	1.22	
3.50	0.125	21.83	53.71	53.71	0.67	
4.00	0.083	27.10	80.81	80.81	0.40	
4.50	0.062	0.00	100.00	100.00	0.00	

STATISTICAL PARAMETERS

PHI

MM.

2.96

0.129

2.63

0.161

2.297

1.20

-1.52

4.06

STANDARD DEVIATION

SKEWNESS

KURTOSIS

16 PCT.
50 PCT.
84 PCT.

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 1 OF 2									
CN, 0003-0017									
REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	LOG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LONGITUDE
151	17	82	29	7	70	70	0	CONF17	09 46.00N
GALVESTON/CORE 17/070CM(=2.2 FT) 07-11-77									
PMT SIZE	MM.2	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
1.00	2.009	0.00	0.00	22.72	PMT	MM.			
1.50	1.614	0.14	0.14	19.22	2.92	0.192			
2.00	1.000	0.00	0.14	11.52	2.83	0.190			
2.50	0.707	0.35	0.49	0.03	0.56	1.673			
3.00	0.500	1.97	1.06	5.41	STANDARD DEVIATION				
3.50	0.350	1.59	2.71	3.49	SKEWNESS				
4.00	0.250	2.46	5.17	2.12	KURTOSIS				
4.50	0.177	14.21	20.43	1.22					
5.00	0.125	38.95	59.36	0.67					
5.50	0.088	38.95	95.62	0.61					
6.00	0.063	4.36	100.00	0.61					
6.50	0.062	0.00	100.00	0.61					
LT.	4.00	0.062	0.00	0.61					
16 PCT.				0.83					
50 PCT.				1.33					
84 PCT.				2.51					
GALVESTON/CORE 17/086CM(=2.8 FT) 07-11-77									
PMT SIZE	MM.2	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
1.00	1.614	0.00	0.00	16.22	PMT	MM.			
1.50	1.707	0.02	0.02	11.52	3.01	0.129			
2.00	1.500	0.11	0.11	5.03	2.90	0.134			
2.50	1.250	2.30	2.41	0.01	1.69	1.511			
3.00	0.875	2.53	7.04	3.49	STANDARD DEVIATION				
3.50	0.727	6.63	16.90	1.22	SKEWNESS				
4.00	0.425	31.95	48.86	1.22	KURTOSIS				
4.50	0.388	40.16	89.24	0.67					
5.00	0.063	10.76	100.00	0.55					
5.50	0.062	0.00	100.00	0.55					
LT.	4.00	0.062	0.00	0.55					
16 PCT.				0.74					
50 PCT.				1.20					
84 PCT.				2.17					

GALVESTON, TEXAS - JEFF WILLIAMS PART 1 OF 2 CN, 0003-0017										
REFERENCE NUMBER 151	CONSECUTIVE NUMBER 17	MARSDEN SQUARE 82	1 DG, SQUARE 29	DEPTH ZONE 7	CORE TOP 100	CORE BOTTOM(CM) 100	ANALYSIS COORD 0	SAMPLE ID CONF17	LATITUDE 29 16.90N	LONGITUDE 99 46.40W
GALVESTON/CORE 17/100CM(=3.2 FT) 07-11-77										
PW	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS					
0.00	1.000	0.00	0.00	0.00	MEAN					
0.50	2.000	2.50	2.50	11.52	MEAN					
1.00	3.000	7.50	7.50	11.52	MEAN					
1.50	4.000	1.00	1.00	11.52	MEAN					
2.00	5.000	1.00	1.00	11.52	MEAN					
2.50	6.000	1.00	1.00	11.52	MEAN					
3.00	7.000	1.00	1.00	11.52	MEAN					
3.50	8.000	1.00	1.00	11.52	MEAN					
4.00	9.000	1.00	1.00	11.52	MEAN					
4.50	10.000	1.00	1.00	11.52	MEAN					
5.00	11.000	1.00	1.00	11.52	MEAN					
5.50	12.000	1.00	1.00	11.52	MEAN					
6.00	13.000	1.00	1.00	11.52	MEAN					
6.50	14.000	1.00	1.00	11.52	MEAN					
7.00	15.000	1.00	1.00	11.52	MEAN					
7.50	16.000	1.00	1.00	11.52	MEAN					
8.00	17.000	1.00	1.00	11.52	MEAN					
8.50	18.000	1.00	1.00	11.52	MEAN					
9.00	19.000	1.00	1.00	11.52	MEAN					
9.50	20.000	1.00	1.00	11.52	MEAN					
10.00	21.000	1.00	1.00	11.52	MEAN					
10.50	22.000	1.00	1.00	11.52	MEAN					
11.00	23.000	1.00	1.00	11.52	MEAN					
11.50	24.000	1.00	1.00	11.52	MEAN					
12.00	25.000	1.00	1.00	11.52	MEAN					
12.50	26.000	1.00	1.00	11.52	MEAN					
13.00	27.000	1.00	1.00	11.52	MEAN					
13.50	28.000	1.00	1.00	11.52	MEAN					
14.00	29.000	1.00	1.00	11.52	MEAN					
14.50	30.000	1.00	1.00	11.52	MEAN					
15.00	31.000	1.00	1.00	11.52	MEAN					
15.50	32.000	1.00	1.00	11.52	MEAN					
16.00	33.000	1.00	1.00	11.52	MEAN					
16.50	34.000	1.00	1.00	11.52	MEAN					
17.00	35.000	1.00	1.00	11.52	MEAN					
17.50	36.000	1.00	1.00	11.52	MEAN					
18.00	37.000	1.00	1.00	11.52	MEAN					
18.50	38.000	1.00	1.00	11.52	MEAN					
19.00	39.000	1.00	1.00	11.52	MEAN					
19.50	40.000	1.00	1.00	11.52	MEAN					
20.00	41.000	1.00	1.00	11.52	MEAN					
20.50	42.000	1.00	1.00	11.52	MEAN					
21.00	43.000	1.00	1.00	11.52	MEAN					
21.50	44.000	1.00	1.00	11.52	MEAN					
22.00	45.000	1.00	1.00	11.52	MEAN					
 								

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 1 OF 2									
CN. 0003-0017									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN NUMBER	LOG SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE
151	17	82	29	7	200	200	0	CONF17	29 16.90N
GALVESTON/CORE 17/200CM(=6.5 FT) 07-11-77									
PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS MM. PHI 2.83 1.40 2.66 1.18 1.569 -2.51 10.44				
-1.00	2.000	0.00	0.00	22.72					
-0.50	1.414	0.34	0.34	16.22					
0.00	1.000	1.01	1.35	11.52					
1.00	1.000	1.16	2.54	8.03					
1.50	1.500	1.88	3.42	5.41	STATISTICAL PARAMETERS MM. PHI 3.00 1.25 2.49 1.127 1.359 -1.70 4.76				
2.00	2.000	2.34	5.76	3.49					
2.50	2.500	2.56	8.32	2.12					
3.00	3.000	2.77	11.09	1.22					
3.50	3.500	2.93	13.82	0.86					
4.00	4.000	3.00	16.82	0.00	STATISTICAL PARAMETERS MM. PHI 3.00 1.25 2.49 1.127 1.359 -1.70 4.76				
4.50	4.500	3.00	19.82	0.00					
5.00	5.000	3.00	22.82	0.00					
5.50	5.500	3.00	25.82	0.00					
6.00	6.000	3.00	28.82	0.00					
6.50	6.500	3.00	31.82	0.00	STATISTICAL PARAMETERS MM. PHI 3.00 1.25 2.49 1.127 1.359 -1.70 4.76				
7.00	7.000	3.00	34.82	0.00					
7.50	7.500	3.00	37.82	0.00					
8.00	8.000	3.00	40.82	0.00					
8.50	8.500	3.00	43.82	0.00					
9.00	9.000	3.00	46.82	0.00	STATISTICAL PARAMETERS MM. PHI 3.00 1.25 2.49 1.127 1.359 -1.70 4.76				
9.50	9.500	3.00	49.82	0.00					
10.00	10.000	3.00	52.82	0.00					
 					

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 1 OF 2									
CN. 0003-0017									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE
151	17	82	29	7	235	235	0	CONF17	29 10.90N
GALVESTON/CORE 17/235CM(=7.7 FT)									
07-11-77									
PHI	MM.	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS				
SIZE	SIZE	PERCENT	PERCENT	VELOCITY	PHI	MM.	MEAN	STANDARD DEVIATION	SKENNESS
-1.00	2.000	0.00	0.00	22.72	3.113	0.116	MEAN	-1.25%	5.73
-5.0	1.414	18	18	14.22	2.97	0.128	MEAN		
0.00	1.000	79	97	11.52	2.81	1.756	STANDARD DEVIATION		
1.50	1.707	34	135	8.03			SKENNESS		
1.00	1.500	3.73	5.04	5.41			KURTOSIS		
1.50	1.154	2.16	7.24	3.49					
2.00	1.250	3.34	10.57	2.12					
2.50	1.177	6.31	16.88	1.22					
3.00	1.125	23.66	42.54	0.67					
3.50	0.888	28.43	70.97	0.40					
4.00	0.663	29.03	100.00						
4.50	0.662	0.00	100.00						
-LT. 4.00 0.662									
16 PCT.									
50 PCT.									
84 PCT.									
GALVESTON/CORE 17/270CM(=8.8 FT)									
07-11-77									
PHI	MM.	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS				
SIZE	SIZE	PERCENT	PERCENT	VELOCITY	PHI	MM.	MEAN	STANDARD DEVIATION	SKENNESS
0.00	1.000	0.00	0.00	11.52	2.75	0.109	MEAN	-1.72	6.31
5.0	1.707	61	61	8.03	2.60	0.165	MEAN		
1.00	1.500	1.17	1.78	5.41			STANDARD DEVIATION		
1.50	1.354	3.43	5.41	3.49			SKENNESS		
2.00	1.250	6.55	11.96	2.12			KURTOSIS		
2.50	1.177	16.34	30.30	1.22					
3.00	1.125	40.92	60.21	0.67					
3.50	0.888	19.79	100.00	1.04					
4.00	0.663	0.00	100.00						
4.50	0.662	0.00	100.00						
-LT. 4.00 0.662									
16 PCT.									
50 PCT.									
84 PCT.									
GALVESTON/CORE 17/270CM(=8.8 FT)									
07-11-77									
PHI	MM.	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS				
SIZE	SIZE	PERCENT	PERCENT	VELOCITY	PHI	MM.	MEAN	STANDARD DEVIATION	SKENNESS
0.00	1.000	0.00	0.00	11.52	2.75	0.109	MEAN	-1.72	6.31
5.0	1.707	61	61	8.03	2.60	0.165	MEAN		
1.00	1.500	1.17	1.78	5.41			STANDARD DEVIATION		
1.50	1.354	3.43	5.41	3.49			SKENNESS		
2.00	1.250	6.55	11.96	2.12			KURTOSIS		
2.50	1.177	16.34	30.30	1.22					
3.00	1.125	40.92	60.21	0.67					
3.50	0.888	19.79	100.00	1.04					
4.00	0.663	0.00	100.00						
4.50	0.662	0.00	100.00						
-LT. 4.00 0.662									
16 PCT.									
50 PCT.									
84 PCT.									

GALVESTON, TEXAS - JEFF WILLIAMS

PART 1 OF 2

CN. 0003-0017

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 LG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	17	82	29	7	323	323	0	CORE17	29 16.90N	094 06.40W

GALVESTON/CORE 17/323CM(=10.5 FT) 07-11-77

PHT	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
SIZE	MM.					
2.50	1.014	0.00	0.00			PHT MM.
0.00	1.000	.57	.57	14.22		2.91 .133
1.50	.707	.21	.79	11.52		2.80 .140
1.00	.500	.07	1.06	8.03		1.405
1.50	.354	1.05	3.61	5.41		SKENNESS
2.00	.250	3.06	7.07	3.49		11.59
2.50	.177	6.39	16.39	2.12		
3.00	.125	43.60	60.18	1.22		
3.50	.084	39.42	100.00	.77		
4.00	.063	0.00	100.00			
4.50	.062	0.00	100.00			
ALT.	4.00					

16 PCT.
50 PCT.
84 PCT.

GALVESTON/CORE 17/354CM(=11.6 FT) 07-11-77

PHT	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
SIZE	MM.					
2.50	1.414	.19	.19	22.72		PHT MM.
0.00	1.000	.51	.70	16.22		2.90 .134
1.50	.707	1.71	2.48	11.52		2.74 .150
1.00	.500	1.50	4.01	8.03		1.574
1.50	.354	2.68	6.69	5.41		SKENNESS
2.00	.250	3.70	8.95	3.49		2.24
2.50	.177	13.19	22.34	2.12		KURTOSIS
3.00	.125	17.47	60.21	1.22		
3.50	.084	39.79	100.00	.68		
4.00	.063	0.00	100.00			
4.50	.062	0.00	100.00			
ALT.	4.00					

14 PCT.
50 PCT.
84 PCT.

GALVESTON, TEXAS - JEFF WILLIAMS PART 1 OF 2 C.N. 0003-0017										
REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	LOG SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CONF17	LATITUDE 29 16.90N	LONGITUDE 099 46.40W
151	17	62	29	7	458	458	0			
GALVESTON/CORE 17/458CM(=15.0 FT) 07-11-77										
PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS					
0.00	1.000	0.00	0.00	11.52	PHI	MM.	MEAN	3.00		
.50	.707	.06	.06	8.03			MEAN	2.90	.116	
1.00	.500	1.03	1.08	5.49			STANDARD DEVIATION	1.493	.129	
1.50	.354	3.41	4.59	3.49			SKENNESS	0.58	1.493	
2.00	.250	2.23	6.82	2.12			KURTOSIS	0.13		
2.50	.177	8.00	14.82	1.22						
3.00	.125	26.81	41.63	.67						
3.50	.089	44.82	86.45	.55						
4.00	.063	11.57	100.00							
.LT.	4.00	.062	100.00							
16 PCT.				.72						
50 PCT.				1.09						
84 PCT.				2.00						
REFERENCE NUMBER	CONSECUTIVE NUMBER	HARSDEN SQUARE	LOG SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CONF17	LATITUDE 29 16.90N	LONGITUDE 099 46.40W
151	17	62	29	7	500	500	0			
GALVESTON/CORE 17/500CM(=16.4 FT) 07-11-77										
PHI	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS					
0.00	1.000	0.00	0.00	8.03	PHI	MM.	MEAN	3.02	.123	
.50	.707	.06	.06	5.41			MEAN	2.90	.134	
1.00	.500	1.08	1.08	3.49			STANDARD DEVIATION	1.492		
1.50	.354	.85	1.93	2.12			SKENNESS	.48	1.492	
2.00	.250	4.16	6.09	1.22			KURTOSIS	7.42		
2.50	.177	8.48	14.57	.68						
3.00	.125	32.59	47.16							
3.50	.089	52.69	100.00							
4.00	.063	0.00	100.00							
.LT.	4.00	.062	100.00							
16 PCT.				.86						
50 PCT.				1.19						
84 PCT.				2.07						

GALVESTON, TEXAS - JEFF WILLIAMS PART 1 OF 2 CN, 0003-0017 DEPTH ZONE CORE TOP BOTTOM(CM) ANALYSIS CODE SAMPLE ID LATITUDE LONGITUDE

151 17 82 29 7 570 570 0 COR-17 29 16.90N 094 06.30W

GALVESTON/CORE 17/570CM(=16.7 FT) 07-11-77

REFERENCE NUMBER	CONSECUTIVE NUMBER	HANSEN SQUARE	100% SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	17	82	29	7	570	570	0	COR-17	29 16.90N	094 06.30W

STATISTICAL PARAMETERS

PHI	MM _s	SIZE	PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	MEAN	STANDARD DEVIATION	SKEWNESS	KURTOSIS
0.50	1.414	0.00	0.00	0.00	16.22	2.86	0.116	0.65	7.93
0.50	1.000	0.70	1.91	1.91	11.52	2.86	0.157	0.65	7.93
1.00	0.707	1.82	2.97	4.89	8.03	2.86	0.157	0.65	7.93
1.50	0.500	2.97	7.11	11.58	5.31	2.86	0.157	0.65	7.93
2.00	0.354	2.23	11.58	18.99	3.49	2.86	0.157	0.65	7.93
2.50	0.250	4.41	18.99	63.34	2.12	2.86	0.157	0.65	7.93
3.00	0.177	8.41	63.34	100.00	1.84	2.86	0.157	0.65	7.93
3.50	0.125	13.16	100.00	100.00	1.84	2.86	0.157	0.65	7.93
4.00	0.084	16.66	100.00	100.00	1.84	2.86	0.157	0.65	7.93
4.50	0.062	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
5.00	0.047	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
5.50	0.036	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
6.00	0.028	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
6.50	0.022	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
7.00	0.018	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
7.50	0.014	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
8.00	0.011	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
8.50	0.009	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
9.00	0.007	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
9.50	0.006	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
10.00	0.005	0.00	100.00	100.00	1.84	2.86	0.157	0.65	7.93
 	

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 OF 2					CN. 0018-0033				
REFERENCE NUMBER	CONSTITUTIVE NUMBER	MARSDEN SQUARE	LOG. SQUARE	DEPTH (CM)	CORE TOP	CORE BOTTOM (CM)	ANALYSIS CODE	SAMPLE ID	LONGITUDE
151	1A	82	29	7	0	0	0	CONT1A	09 47.20N
GALVESTON/CORE 1R/000CM(TOP)									
07-11-77									
PRI	MM*	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS				
SIZE	SIZE	PERCENT	PERCENT	VELOCITY	PHI				
0.00	1.000	0.00	0.00		MM.				
.50	.767	1.15	1.15	11.52	2.65				
1.00	.500	1.06	2.21	6.03	.139				
1.50	.354	2.42	4.63	5.41	2.73				
2.00	.250	3.77	8.40	3.49	.151				
2.50	.177	4.91	21.51	21.51	.57				
3.00	.125	39.01	61.12	1.22	1.480				
3.50	.088	36.68	100.00	.77	1.86				
4.00	.063	0.00	100.00		7.27				
4.50	.042	0.00	100.00		STANDARD DEVIATION				
5.00					SKENNESS				
5.50					KURTOSIS				
6.00					PHI				
6.50					MM.				
7.00					2.88				
7.50					.136				
8.00					2.68				
8.50					.156				
9.00					.75				
9.50					1.678				
10.00					-2.35				
10.50					9.32				
11.00					STANDARD DEVIATION				
11.50					SKENNESS				
12.00					KURTOSIS				
12.50					PHI				
13.00					MM.				
13.50					2.88				
14.00					.136				
14.50					2.68				
15.00					.156				
15.50					.75				
16.00					1.678				
16.50					-2.35				
17.00					9.32				
17.50					STANDARD DEVIATION				
18.00					SKENNESS				
18.50					KURTOSIS				
19.00					PHI				
19.50					MM.				
20.00					2.88				
20.50					.136				
21.00					2.68				
21.50					.156				
22.00					.75				
22.50					1.678				
23.00					-2.35				
23.50					9.32				
24.00					STANDARD DEVIATION				
24.50					SKENNESS				
25.00					KURTOSIS				
25.50					PHI				
26.00					MM.				
26.50					2.88				
27.00					.136				
27.50					2.68				
28.00					.156				
28.50					.75				
29.00					1.678				
29.50					-2.35				
30.00					9.32				
30.50					STANDARD DEVIATION				
31.00					SKENNESS				
31.50					KURTOSIS				
32.00					PHI				
32.50					MM.				
33.00					2.88				
33.50					.136				
34.00					2.68				
34.50					.156				
35.00					.75				
35.50					1.678				
36.00					-2.35				
36.50					9.32				
37.00					STANDARD DEVIATION				
37.50					SKENNESS				
38.00					KURTOSIS				
38.50					PHI				
39.00					MM.				
39.50					2.88				
40.00					.136				
40.50					2.68				
41.00					.156				
41.50					.75				
42.00					1.678				
42.50					-2.35				
43.00					9.32				
43.50					STANDARD DEVIATION				
44.00					SKENNESS				
44.50					KURTOSIS				
45.00					PHI				
45.50					MM.				
46.00					2.88				
46.50					.136				
47.00					2.68				
47.50					.156				
48.00					.75				
48.50					1.678				
49.00					-2.35				
49.50					9.32				
50.00					STANDARD DEVIATION				
50.50					SKENNESS				
51.00					KURTOSIS				
51.50					PHI				
52.00					MM.				
52.50					2.88				
53.00					.136				
53.50					2.68				
54.00					.156				
54.50					.75				
55.00					1.678				
55.50					-2.35				
56.00					9.32				
56.50					STANDARD DEVIATION				
57.00					SKENNESS				
57.50					KURTOSIS				
58.00					PHI				
58.50					MM.				
59.00					2.88				
59.50					.136				
60.00					2.68				
60.50					.156				
61.00					.75				
61.50					1.678				
62.00					-2.35				
62.50					9.32				
63.00					STANDARD DEVIATION				
63.50					SKENNESS				
64.00					KURTOSIS				
64.50					PHI				
65.00					MM.				
65.50					2.88				
66.00					.136				
66.50					2.68				
67.00					.156				
67.50					.75				
68.00					1.678				
68.50					-2.35				

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 OF 2									
CN, 0018-0030									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	LOG SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE
151	1A	82	29	7	220	220	0	CORE18	29 16.50N
LONGITUDE 090 47.20W									
GALVESTON/CORE 1A/220CM(=7.2 FT) 07-11-77									
PHI	MM, SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS			
1.00	4500	0.00	0.00		5.41	MEAN			
1.50	3534	1.49	1.29		3.40	DEVIATION			
2.00	250	7.07	8.36		2.12	STANDARD			
2.50	177	14.97	23.32		1.22	KURTOSIS			
3.00	125	40.28	63.61		.88				
3.50	108	36.39	100.00						
4.00	103	0.00	100.00						
4.50	103	0.00	100.00						
ALT, 4.00 0.62									
1A PCT, 1.03									
50 PCT, 1.39									
80 PCT, 2.42									
GALVESTON/CORE 1A/310CM(=10.1 FT) 07-11-77									
PHI	MM, SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS			
0.00	1.000	0.00	0.00		11.42	MEAN			
0.50	707	.33	.33		4.03	DEVIATION			
1.00	500	.69	1.62		5.91	STANDARD			
1.50	354	3.55	4.57		3.40	KURTOSIS			
2.00	250	3.34	7.94		2.12				
2.50	177	9.62	17.57		1.22				
3.00	125	24.24	45.85		.87				
3.50	108	40.31	95.15		.61				
4.00	103	4.45	100.00						
4.50	103	0.00	100.00						
ALT, 4.00 0.62									
1B PCT, 1.40									
50 PCT, 1.17									
80 PCT, 2.18									
GALVESTON/CORE 1A/310CM(=10.1 FT) 07-11-77									
PHI	MM, SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS			
0.00	1.000	0.00	0.00		11.42	MEAN			
0.50	707	.33	.33		4.03	DEVIATION			
1.00	500	.69	1.62		5.91	STANDARD			
1.50	354	3.55	4.57		3.40	KURTOSIS			
2.00	250	3.34	7.94		2.12				
2.50	177	9.62	17.57		1.22				
3.00	125	24.24	45.85		.87				
3.50	108	40.31	95.15		.61				
4.00	103	4.45	100.00						
4.50	103	0.00	100.00						
ALT, 4.00 0.62									
1B PCT, 1.40									
50 PCT, 1.17									
80 PCT, 2.18									

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 (IF 2)									
CH. 0018-0034									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DEG. SQUARE	DEPTH ZONE	CUR. TOP 396	ANALYSIS COEF	SAMPLE ID	LATITUDE	LONGITUDE
151	14	82	29	7	396	0	CONF 8	29 16.50N	094 47.20W
GALVESTON/CURE (14/306CM=12.9 FT)									
07-11-77									
PHI SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS					
1.50	2.000	0.00	22.72	PHI	MM.				
2.00	1.414	0.00	19.22	3.05	1.121				
3.00	1.000	3.02	11.52	2.92	1.142				
4.00	0.707	5.57	5.03	1.690	1.690				
5.00	0.500	8.94	3.49	STANDARD DEVIATION	2.064				
6.00	0.354	12.97	2.12	SKENNESS	2.064				
7.00	0.250	16.41	1.22	KURTOSIS	10.92				
8.00	0.177	19.57	0.66						
9.00	0.125	22.28							
10.00	0.088	25.14							
11.00	0.063	27.00							
12.00	0.042	28.86							
13.00	0.030	30.00							
14.00	0.020	31.00							
15.00	0.014	32.00							
16.00	0.010	33.00							
17.00	0.007	34.00							
18.00	0.005	35.00							
19.00	0.003	36.00							
20.00	0.002	37.00							
21.00	0.001	38.00							
22.00	0.001	39.00							
23.00	0.001	40.00							
24.00	0.001	41.00							
25.00	0.001	42.00							
26.00	0.001	43.00							
27.00	0.001	44.00							
28.00	0.001	45.00							
29.00	0.001	46.00							
30.00	0.001	47.00							
31.00	0.001	48.00							
32.00	0.001	49.00							
33.00	0.001	50.00							
34.00	0.001	51.00							
35.00	0.001	52.00							
36.00	0.001	53.00							
37.00	0.001	54.00							
38.00	0.001	55.00							
39.00	0.001	56.00							
40.00	0.001	57.00							
41.00	0.001	58.00							
42.00	0.001	59.00							
43.00	0.001	60.00							
44.00	0.001	61.00							
45.00	0.001	62.00							
46.00	0.001	63.00							
47.00	0.001	64.00							
48.00	0.001	65.00							
49.00	0.001	66.00							
50.00	0.001	67.00							
51.00	0.001	68.00							
52.00	0.001	69.00							
53.00	0.001	70.00							
 				

REFERENCE CONSECUTIVE HANSEN I OG.
 NUMBER NUMBER SQUARE SQUARE
 151 21 82 29

DEPTH ZONE
 7 0

ANALYSIS CODE
 0

SAMPLE ID
 COMF21

LATITUDE
 29 10.90N

LONGITUDE
 094 56.80W

GALVESTON/CURE 21/000CM(TOP) 07=12=77

PHI	MM*	FREQUENCY	CUMULATIVE	FALL
SIZE	PERCENT	PERCENT	VELOCITY	
-1.00	2.000	0.00	0.00	22.72
-0.50	1.000	.17	.17	16.22
0.00	1.000	.79	.96	11.52
.50	.707	.71	1.67	6.03
1.00	.500	2.16	3.83	5.01
1.50	.354	3.23	7.06	3.00
2.00	.250	4.78	11.84	2.12
2.50	.177	8.54	20.38	1.22
3.00	.125	34.16	54.56	.77
3.50	.088	45.04	100.00	
4.00	.053	0.00	100.00	
.LT.	.4.00	.062	100.00	

16 PCT.
 50 PCT.
 84 PCT.

REFERENCE CONSECUTIVE HANSEN I OG.
 NUMBER NUMBER SQUARE SQUARE
 151 21 82 29

DEPTH ZONE
 7 0

ANALYSIS CODE
 0

SAMPLE ID
 COMF21

LATITUDE
 29 10.90N

LONGITUDE
 094 56.80W

GALVESTON/CURE 21/000CM(=1.6 FT) 07=12=77

PHI	MM*	FREQUENCY	CUMULATIVE	FALL
SIZE	PERCENT	PERCENT	VELOCITY	
-1.00	2.000	0.00	0.00	22.72
-0.50	1.000	.17	.17	16.22
0.00	1.000	2.61	2.78	11.52
.50	.707	2.07	4.85	5.01
1.00	.500	5.70	10.55	3.00
1.50	.354	4.94	15.49	2.12
2.00	.250	9.38	24.87	1.22
2.50	.177	17.66	42.53	.77
3.00	.125	43.29	85.82	.61
3.50	.088	93.57	100.00	
4.00	.053	100.00	100.00	
.LT.	.4.00	.062	100.00	

16 PCT.
 50 PCT.
 84 PCT.

ANALYSIS CODE
 0

SAMPLE ID
 COMF21

LATITUDE
 29 10.90N

LONGITUDE
 094 56.80W

GALVESTON, TEXAS - JEFF WILLIAMS PART 2 OF 2 CN, 0018-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP CORE	BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	21	82	29	7	80	80	0	CMF21	29 10.90N	094 56.60W

GALVESTON/CMF21/80CM(=246 FT) 07-12-77

PHI	MM*	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
0.50	1.000	0.00	0.00	0.00		11.52	PHI MM, MEDIAN
0.50	0.707	0.00	0.00	0.00		5.03	3.10 .110
1.00	0.500	0.19	0.55	1.43		5.41	3.10 .117
1.50	0.354	0.68	1.43	5.55		3.49	.58 1.409
2.00	0.250	4.12	5.55	12.61		2.12	-1.21
2.50	0.177	7.06	12.61	35.76		1.22	5.20
3.00	0.125	23.16	35.76	73.86		.67	
3.50	0.086	34.10	73.86	100.00		.40	
4.00	0.063	24.14	100.00				
4.50	0.046	0.00	100.00				
4.75	0.030	0.00					
5.00	0.022	0.00					
5.25	0.016	0.00					
5.50	0.011	0.00					
5.75	0.008	0.00					
6.00	0.006	0.00					
6.25	0.004	0.00					
6.50	0.003	0.00					
6.75	0.002	0.00					
7.00	0.001	0.00					
7.25	0.001	0.00					
7.50	0.001	0.00					
7.75	0.001	0.00					
8.00	0.001	0.00					
8.25	0.001	0.00					
8.50	0.001	0.00					
8.75	0.001	0.00					
9.00	0.001	0.00					
9.25	0.001	0.00					
9.50	0.001	0.00					
9.75	0.001	0.00					
10.00	0.001	0.00					
10.25	0.001	0.00					
10.50	0.001	0.00					
10.75	0.001	0.00					
11.00	0.001	0.00					
11.25	0.001	0.00					
11.50	0.001	0.00					
11.75	0.001	0.00					
12.00	0.001	0.00					
12.25	0.001	0.00					
12.50	0.001	0.00					
12.75	0.001	0.00					
13.00	0.001	0.00					
13.25	0.001	0.00					
13.50	0.001	0.00					
13.75	0.001	0.00					
14.00	0.001	0.00					
14.25	0.001	0.00					
14.50	0.001	0.00					
14.75	0.001	0.00					
15.00	0.001	0.00					
15.25	0.001	0.00					
15.50	0.001	0.00					
15.75	0.001	0.00					
16.00	0.001	0.00					
16.25	0.001	0.00					
16.50	0.001	0.00					
16.75	0.001	0.00					
17.00	0.001	0.00					
17.25	0.001	0.00					
17.50	0.001	0.00					
17.75	0.001	0.00					
18.00	0.001	0.00					
18.25	0.001	0.00					
18.50	0.001	0.00					
18.75	0.001	0.00					
19.00	0.001	0.00					
19.25	0.001	0.00					
19.50	0.001	0.00					
19.75	0.001	0.00					
20.00	0.001	0.00					
20.25	0.001	0.00					
20.50	0.001	0.00					
20.75	0.001	0.00					
21.00	0.001	0.00					
21.25	0.001	0.00					
21.50	0.001	0.00					
21.75	0.001	0.00					
22.00	0.001	0.00					
22.25	0.001	0.00					
22.50	0.001	0.00					
22.75	0.001	0.00					
23.00	0.001	0.00					
23.25	0.001	0.00					
23.50	0.001	0.00					
23.75	0.001	0.00					
24.00	0.001	0.00					
24.25	0.001	0.00					
24.50	0.001	0.00					
24.75	0.001	0.00					
25.00	0.001	0.00					
25.25	0.001	0.00					
25.50	0.001	0.00					
25.75	0.001	0.00					
26.00	0.001	0.00					
26.25	0.001	0.00					
26.50	0.001	0.00					
26.75	0.001	0.00					
27.00	0.001	0.00					
27.25	0.001	0.00					
27.50	0.001	0.00					
27.75	0.001	0.00					
28.00	0.001	0.00					
28.25	0.001	0.00					
28.50	0.001	0.00					
28.75	0.001	0.00					
29.00	0.001	0.00					
29.25	0.001	0.00					
29.50	0.001	0.00					
29.75	0.001	0.00					
30.00	0.001	0.00					
30.25	0.001	0.00					
30.50	0.001	0.00					
30.75	0.001	0.00					
31.00	0.001	0.00					
31.25	0.001	0.00					
31.50	0.001	0.00					
31.75	0.001	0.00					
32.00	0.001	0.00					
32.25	0.001	0.00					
32.50	0.001	0.00					
32.75	0.001	0.00					
33.00	0.001	0.00					
33.25	0.001	0.00					
33.50	0.001	0.00					
33.75	0.001	0.00					
34.00	0.001	0.00					
34.25	0.001	0.00					
34.50	0.001	0.00					
34.75	0.001	0.00					
35.00	0.001	0.00					
35.25	0.001	0.00					
35.50	0.001	0.00					
35.75	0.001	0.00					
36.00	0.001	0.00					
36.25	0.001	0.00					
36.50	0.001	0.00					
36.75	0.001	0.00					
37.00	0.001	0.00					
37.25	0.001	0.00					
37.50	0.001	0.00					
37.75	0.001	0.00					
38.00	0.001	0.00					
38.25	0.001	0.00					
38.50	0.001	0.00					
38.75	0.001	0.00					
39.00	0.001	0.00					
39.25	0.001	0.00					
39.50	0.001	0.00					
39.75	0.001	0.00					
40.00	0.001	0.00					
40.25	0.001	0.00					
40.50	0.001	0.00					
40.75	0.001	0.00					
41.00	0.001	0.00					
41.25	0.001	0.00					
41.50	0.001	0.00					
41.75	0.001	0.00					
42.00	0.001	0.00					
42.25	0.001	0.00					
42.50	0.001	0.00					
42.75	0.001	0.00					
43.00	0.001	0.00					
43.25	0.001	0.00					
43.50	0.001	0.00					
43.75	0.001	0.00					
44.00	0.001	0.00					
44.25	0.001	0.00					
44.50	0.001	0.00					
44.75	0.001	0.00					
45.00	0.001	0.00					
45.25	0.001	0.00					
45.50	0.001	0.00					
45.75	0.001	0.00					
46.00	0.001	0.00					
46.25	0.001	0.00					
46.50	0.001	0.00					
46.75	0.001	0.00					
47.00	0.001	0.00					
47.25	0.001	0.00					
47.50	0.001	0.00					
47.75	0.001	0.00					
48.00	0.001	0.00					
48.25	0.0						

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 OF 2									
CN. 0018-0034									
REFERENCE NUM-151	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID CONF21	LONGITUDE 09W 56.60N
GALVESTON/CORE 21/125CM(=4.1 FT)									
07-12-77									
PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS			
1.00	7500	0.00	0.00			PHI	MM.		
1.50	3354	.49	.49		5.41	2.80	.115		
2.00	2250	4.08	4.57		3.49	2.82	.142		
2.50	1777	14.93	19.54		2.12	.42	1.341		
3.00	1257	34.59	54.13		1.22	M-93			
3.50	988	41.51	100.00		.77	3.73			
4.00	663	0.00	100.00						
4.50	462	0.00	100.00						
.LT. 4.00									
16 PCT.					.95				
50 PCT.					1.36				
84 PCT.					2.23				
GALVESTON/CORE 21/200CM(=6.5 FT)									
07-12-77									
PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS			
1.00	7400	0.00	0.00			PHI	MM.		
1.50	3414	2.17	2.17		27.72	3.06	.120		
2.00	1400	3.19	5.36		11.22	2.74	.144		
2.50	1077	3.19	8.55		5.03	1.09	2.133		
3.00	750	2.06	10.61		5.03	M-93			
3.50	500	2.12	12.73		3.49	5.68			
4.00	334	2.06	14.79		2.12				
4.50	225	25.91	40.70		1.67				
5.00	125	33.13	73.83		.93				
5.50	668	21.24	100.00						
6.00	462	0.00	100.00						
.LT. 4.00									
16 PCT.					.59				
50 PCT.					1.11				
84 PCT.					3.03				

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

C.N. 0018-0034

REFERENCE	CONSECUTIVE	HARDEN	I DG.	DEPTH	CORE	ANALYSIS	SAMPLE ID	LATITUDE	LONGITUDE
NUMBER	NUMBER	SQUARE	SQUARE	ZONE	TOP	BOTTOM(FT)	CODE	29 10.90N	090 56.60W
151	21	82	29	7	350	350	0	CORF 21	

GALVESTON/CORE 21/350CM(=11.0 FT) 07-12-77

STATISTICAL PARAMETERS	
PWt	MM ₀
2.94	.130
2.85	.139
.59	1.507
2.60	
3.17	

16
50
44

SAMPLE ID	LATITUDE	LONGITUDE
CONF22	29 09.00N	094 59.90W

ANALYSIS
CODE
0

CURE
BOTTOM (CM)
140

DEPT. OF
ZONING

1 DG.
SQUARE
29

TIVE
HEH
22

३३५

GALVESTON/CUNE 20/140CM(04.5 FT) 07-12-77

PHI	MM.
2.67	0.137
2.70	0.154
2.60	1.520
2.09	
7.52	

•

12248

100.00
65.06
18.96

7.94
46.10
34.94

17	50
12	00
08	50

16 PCT.
50 PCT.
80 PCT.

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN. 0010-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP BOTTOM (CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	22	82	29	7	180 180	0	CORE22	29 09.00N	094 59.90W

GALVESTON/CORE 22/180CM (=3.9 FT)

07-12-77

PMI SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
0.50	0.00	0.00	0.30
1.00	0.57	0.57	16.22
1.50	1.95	2.52	11.52
2.00	1.35	3.87	8.03
2.50	4.45	8.32	5.41
3.00	7.07	15.39	3.99
3.50	15.18	30.57	2.13
4.00	33.09	63.66	1.22
4.50	38.98	102.64	0.77
5.00	11.95	114.59	0.55
5.50	0.00	114.59	0.55

A.T. 4.00

16 PCT.

50 PCT.

84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE
151	23	82	29	8

GALVESTON/CORE 23/094CM (=3.2 FT)

07-12-77

PMI SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
0.50	0.00	0.00	0.30
1.00	0.57	0.57	16.22
1.50	1.95	2.52	11.52
2.00	1.35	3.87	8.03
2.50	4.45	8.32	5.41
3.00	7.07	15.39	3.99
3.50	15.18	30.57	2.13
4.00	33.09	63.66	1.22
4.50	38.98	102.64	0.77
5.00	11.95	114.59	0.55
5.50	0.00	114.59	0.55

A.T. 4.00

16 PCT.

50 PCT.

84 PCT.

STATISTICAL PARAMETERS			
PMI	MM		
3.01	1.24		
2.80	1.15		
1.95	1.366		
1.97			
0.31			

STATISTICAL PARAMETERS			
MEDIAN	MEAN	STANDARD DEVIATION	SKEWNESS
1.24	1.15	1.366	1.97
0.31			

STATISTICAL PARAMETERS			
PMI	MM		
3.24	1.08		
3.02	1.23		
2.03	1.626		
2.03			
7.77			

STATISTICAL PARAMETERS			
MEDIAN	MEAN	STANDARD DEVIATION	SKEWNESS
1.08	1.23	1.626	2.03
2.03			
7.77			

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN. 0018-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP CORE	BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	23	62	29	A	98	98	0	CONF23	29 09,90N	095 01.70W

GALVESTON/CORE 23/098CM(-3.2 FT)

07-12-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS
0.00	1.000	0.00	0.00	0.00	11.52	PHI MM.
1.50	.707	.03	.03	.03	5.41	3.91
1.00	.500	.59	.62	.62	5.41	3.12
1.50	.354	.56	.19	.81	5.41	1.00
2.00	.250	1.40	2.09	1.00	5.41	1.407
2.50	.177	2.06	5.91	1.00	5.41	1.407
3.00	.125	12.51	18.12	1.00	5.41	1.407
3.50	.068	01.36	59.48	1.00	5.41	1.407
4.00	.063	40.52	100.00	1.00	5.41	1.407
4.50	.062	0.00	100.00	1.00	5.41	1.407

16 PCT.
50 PCT.
84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP CORE	BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	23	62	29	A	300	300	0	CONF23	29 09,90N	095 01.70W

GALVESTON/CORE 23/300CM(-9.8 FT)

07-12-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS
0.00	1.000	0.00	0.00	0.00	11.52	PHI MM.
1.50	.707	.03	.03	.03	5.41	3.91
1.00	.500	.75	.78	.78	5.41	3.12
1.50	.354	1.07	1.82	1.82	5.41	1.00
2.00	.250	2.47	4.29	2.00	5.41	1.407
2.50	.177	15.45	20.14	2.00	5.41	1.407
3.00	.125	35.90	56.05	2.00	5.41	1.407
3.50	.068	39.21	95.26	2.00	5.41	1.407
4.00	.063	4.74	100.00	2.00	5.41	1.407
4.50	.062	0.00	100.00	2.00	5.41	1.407

16 PCT.
50 PCT.
84 PCT.

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN. 0018-0013

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	COPE	ROTDM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	23	82	29	8	360	360	380	0	CONF23	29 09.90N	095 01.70W

GALVESTON/COPE 23/380CM(-12.0 FT)

07-12-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00	0.00	22.72	22.72	PHI
-0.50	1.014	0.40	0.40	0.40	16.22	16.22	MM.
0.00	1.000	1.67	1.67	2.07	11.52	11.52	3.00
0.50	1.077	0.51	2.59	2.59	5.03	5.03	1.653
1.00	0.900	0.49	3.09	3.09	3.41	3.41	MEAN
1.50	0.354	0.32	3.49	3.49	3.49	3.49	STANDARD DEVIATION
2.00	0.270	0.37	3.85	3.85	2.12	2.12	SKEWNESS
2.50	0.177	0.35	4.20	4.20	1.67	1.67	KURTOSIS
3.00	0.125	0.51	4.71	4.71	1.00	1.00	
3.50	0.068	0.47	5.18	5.18	1.00	1.00	
4.00	0.063	0.22	5.40	5.40	1.00	1.00	
4.50	0.062	0.00	5.40	5.40	1.00	1.00	

16 PCT.
50 PCT.
84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	COPE	ROTDM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	23	82	29	8	469	469	469	0	CONF23	29 09.90N	095 01.70W

GALVESTON/COPE 23/469CM(-15.0 FT BTM) 07-12-77

PHI	MM.	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL	STATISTICAL PARAMETERS
-1.00	2.000	0.00	0.00	0.00	22.72	22.72	PHI
-0.50	1.014	0.20	0.20	0.20	16.22	16.22	MM.
0.00	1.000	1.53	1.73	1.73	11.52	11.52	3.00
0.50	0.707	0.46	2.19	2.19	6.03	6.03	1.653
1.00	0.500	0.32	2.51	2.51	5.41	5.41	MEAN
1.50	0.354	0.49	2.99	2.99	3.49	3.49	STANDARD DEVIATION
2.00	0.250	0.35	3.35	3.35	2.12	2.12	SKEWNESS
2.50	0.177	0.57	3.92	3.92	1.22	1.22	KURTOSIS
3.00	0.125	0.43	4.35	4.35	1.00	1.00	
3.50	0.088	0.65	5.00	5.00	1.00	1.00	
4.00	0.063	0.00	5.00	5.00	1.00	1.00	
4.50	0.062	0.00	5.00	5.00	1.00	1.00	

16 PCT.
50 PCT.
84 PCT.

GALVESTON, TEXAS • JEFF WILLIAMS

PART 2 OF 2

CN. 0014-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM (CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	24	62	29	7	0	0	0	CONF24	29 07.50N	095 02.40W

GALVESTON/COMF 24/000CM(TUP) 07-12-77

STATISTICAL PARAMETERS	
PHI	MM.
3.09	.117
2.95	.129
.72	1.652
1.80	
7.18	

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

CUMULATIVE PERCENT	VELOCITY	FALL
0.00	.47	16.25
2.51	.51	11.52
3.42	.55	8.03
5.55	.60	5.41
7.86	.65	3.49
18.14	.70	2.12
41.86	.75	1.22
61.48	.80	.67
100.00	.85	.40
100.00	.90	.20

PHI	SIZE	W ₁ †	FREQUENCY PERCENT
0.50	1.614	1.00	0.00
0.00	1.000	1.00	0.47
1.50	1.07	1.60	1.60
1.00	1.50	1.11	1.11
1.50	1.50	2.10	2.10
2.00	2.50	2.33	2.33
2.50	1.77	10.26	10.26
3.00	1.25	39.62	39.62
3.50	0.68	14.52	14.52
4.00	0.63	0.09	0.09
4.00	0.62		

16 OCT. 1951

2.30
1.08
1.02

SAMPLE ID LATITUDE LONGITUDE
CONE24 29 07.50N 095 02.40W

EDTOM(CH)
45
ANALYSIS
CODE
0

DEN
12
1 DG.
SQUARE
29
DEPT
ZONE
7

REFERENCE NUMBER	CONSECUTIVE NUMBER	DATE	NAME	STATUS
151	24			

GALVESTON/COME 24/045CH(01.4 17)

STATISTICAL PARAMETERS	
PHI	MM ²
2.84	.140
2.57	.149
.96	1.940
1.68	
4.99	

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

CUMULATIVE PERFIT	FALL VELOCITY
0.00	16.22
4.53	11.52
8.92	8.03
11.31	5.01
12.92	

PHI	SIZE	MM. Ø	FREQUENCY	PERCENT
0.50	1.00	1.00	0.00	0.00
0.00	1.00	1.00	0.53	0.53
0.50	1.00	1.00	0.39	0.39
1.00	1.00	1.00	2.39	2.39
1.00	1.00	1.00	1.40	1.40

2000

27.16	2.12
62.61	1.22
93.60	.67
	.5

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN, 0018-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CUME BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	24	R2	29	7	45	45	0	CONE24	29 07.50N	095 02.40W

GALVESTON/CUME 24/045CM(=1.4 FT) 07-12-77

PRI	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
-1.00	2.000	0.00	0.00	22.72
-0.50	1.414	0.09	0.09	16.22
0.00	1.000	1.35	1.43	11.52
0.50	0.707	2.40	4.24	8.03
1.00	0.500	3.29	7.53	5.41
1.50	0.354	2.78	10.31	3.49
2.00	0.250	4.37	14.68	2.12
2.50	0.177	16.48	31.16	1.22
3.00	0.125	42.92	74.08	0.88
3.50	0.068	25.92	100.00	
4.00	0.063	0.00	100.00	
4.50	0.062	0.00	100.00	

16 PCT.
50 PCT.
84 PCT.

1.09
1.62
3.34

STATISTICAL PARAMETERS
PRI MM.
2.75
2.51
1.691
-1.485
6.12

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CUME BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	24	R2	29	7	102	102	0	CONE24	29 07.50N	095 02.40W

GALVESTON/CUME 24/102CM(=3.3 FT) 07-12-77

PRI	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
-1.00	2.000	0.00	0.00	22.72
-0.50	1.414	3.07	3.07	16.22
0.00	1.000	11.44	14.51	11.52
0.50	0.707	6.32	20.63	8.03
1.00	0.500	1.17	20.99	5.41
1.50	0.354	1.67	22.66	3.49
2.00	0.250	1.96	24.62	2.12
2.50	0.177	10.67	35.29	1.22
3.00	0.125	24.04	59.33	0.88
3.50	0.064	29.65	88.97	0.67
4.00	0.063	11.03	100.00	0.46
4.50	0.062	0.00	100.00	

16 PCT.
50 PCT.
84 PCT.

1.76
1.42
15.89

STATISTICAL PARAMETERS
PRI MM.
2.46
2.10
2.555
-1.408
2.664

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CH. 001B-0034

REFERENCE NUMBER
151

CONSECUTIVE NUMBER
25

MARSDEN SQUARE
62

DEPTH ZONE
A

TOP BOTTOM(CM)
0 0

ANALYSIS CODE
0

SAMPLE ID
C04F25

LATITUDE
29 05.10N

LONGITUDE
095 04.60W

GALVESTON//CORE 25//000CM(TOP)

07-13-77

PHI	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
1.50	.707	0.00	0.00	8.03
1.00	.500	.70	2.70	5.41
1.50	.354	1.66	2.36	3.49
2.00	.250	2.30	4.78	2.12
2.50	.177	9.10	14.06	1.22
3.00	.125	26.57	42.60	1.22
3.50	.084	57.54	100.00	1.68
4.00	.063	0.00	100.00	0.00
4.00	.062	0.00	100.00	0.00

STATISTICAL PARAMETERS

PHI MM.
3.06
MEAN
2.82
STANDARD DEVIATION
1.79
SKEWNESS
0.92
KURTOSIS

16 PCT.
50 PCT.
63 PCT.

.61
1.13
2.03

REFERENCE NUMBER
151

CONSECUTIVE NUMBER
25

MARSDEN SQUARE
62

DEPTH ZONE
B

CORE BOTTOM(CM)
120

ANALYSIS CODE
0

SAMPLE ID
C04F25

LATITUDE
29 05.10N

LONGITUDE
095 04.60W

GALVESTON//CORE 25//120CM(=3.9 FT)

07-13-77

PHI	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
1.00	2.000	0.00	0.00	22.72
.50	1.414	.15	.15	16.22
0.00	1.000	.16	.31	11.52
.50	.707	.09	.40	8.43
1.00	.500	.83	1.23	5.43
1.50	.354	1.69	2.92	3.43
2.00	.250	24.49	27.41	2.12
2.50	.177	20.67	48.08	1.22
3.00	.125	52.52	100.00	1.22
3.50	.084	0.00	100.00	1.68
4.00	.063	5.96	100.00	0.00
4.00	.062	0.00	100.00	0.00

STATISTICAL PARAMETERS

PHI MM.
3.04
MEAN
2.94
STANDARD DEVIATION
2.51
SKEWNESS
-2.21
KURTOSIS
11.90

16 PCT.
50 PCT.
63 PCT.

.76
1.10
1.96

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN. 0018-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	25	82	29	A	148	148	0	COMF25	29 05.10N	095 04.60W

GALVESTON/CURE 25/148CM(=4.8 FT)

07-13-77

PHI	SIZE	FREQ	PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
1.50	1.414	0.00	0.00	0.00	10.22	
0.00	1.000	0.10	0.10	0.10	11.52	
0.50	0.707	0.18	0.28	0.28	8.03	
1.00	0.500	0.55	0.83	0.83	5.41	
1.50	0.354	1.22	0.95	0.95	3.49	
2.00	0.250	17.97	22.87	22.87	2.12	
2.50	0.177	24.07	46.95	46.95	1.22	
3.00	0.125	34.07	81.02	81.02	0.67	
3.50	0.088	34.14	100.00	100.00	0.46	
4.00	0.063	18.92	100.00	100.00	0.46	
4.50	0.045	0.00	100.00	100.00		
5.00	0.032	0.00	100.00	100.00		

16 PCT.	1.16	0.03
50 PCT.	2.38	
84 PCT.		

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	25	82	29	B	200	200	0	COMF25	29 05.10N	095 04.60W

GALVESTON/CURE 25/200CM(=6.5 FT)

07-13-77

PHI	SIZE	FREQ	PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
1.00	1.000	0.00	0.00	0.00	5.41	
1.50	0.707	0.12	0.12	0.12	3.49	
2.00	0.500	5.52	6.64	6.64	2.12	
2.50	0.354	17.97	24.61	24.61	1.22	
3.00	0.250	40.86	65.47	65.47	0.77	
3.50	0.177	32.04	97.51	97.51		
4.00	0.125	0.00	100.00	100.00		
4.50	0.088	0.00	100.00	100.00		
5.00	0.063	0.00	100.00	100.00		

16 PCT.	1.51	0.99
50 PCT.	2.76	
84 PCT.		

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 OF 2									
CN, 0018-0034									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	200	200	0		29 05.10N
GALVESTON/CORE 25/200CH(=6.5 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
1.50	.750	0.00	0.00						
2.00	.375	0.00	0.00						
2.50	.177	10.45	11.51	3.49					
3.00	.125	31.59	43.10	2.12					
3.50	.068	33.59	81.69	1.22					
4.00	.033	14.94	100.00	.67					
.LT.	.400	.002	100.00	.40					
STATISTICAL PARAMETERS									
PHI	MM.								
3.03	.122								
3.04	.121								
.46	1.375								
.01									
2.43									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					
1.50	.354	2.17	3.65	5.41					
2.00	.250	2.41	6.06	3.49					
2.50	.177	45.42	51.48	2.12					
3.00	.125	42.09	91.57	1.22					
3.50	.068	6.43	100.00	1.04					
.LT.	.400	.062	100.00						
STATISTICAL PARAMETERS									
PHI	MM.								
2.48	.179								
2.48	.179								
.42	1.361								
-1.19									
6.13									
MEOTAN									
STANDARD DEVIATION									
SKEWNESS									
KURTOSIS									
REFERENCE NUMBER	CONSECUTIVE NUMBER	MAKSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CH)	ANALYSIS CODE	SAMPLE ID CORE25	LATITUDE
151	25	82	29	A	250	250	0		29 05.10N
GALVESTON/CORE 25/250CH(=6.2 FT) 07-13-77									
PHI	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY					
0.00	1.000	0.00	0.00						
.50	.707	.04	.04	11.52					
1.00	.500	1.44	1.48	8.03					

GALVESTON, TEXAS - JEFF WILLIAMS PART 2 OF 2 CN, 0018-0034

REFERENCE NUMBER 151 CONSECUTIVE NUMBER 25 MARSDEN SQUARE 82 1 DG. SQUARE 24 DEPTH ZONE 8 CURE TOP BOTTOM(CM) 350 350 ANALYSIS CODE 0

SAMPLE ID
CORE25

LATITUDE
29 05.10N

LONGITUDE
095 04.60W

GALVESTON/CORE 25/350CM(=11.4 FT)

07-13-77

PI	MM.	SIZE	FREQUENCY	CUMULATIVE	PERCENT	VELOCITY	FALL
1.00	.500	1.00	0.00	0.00	0.00	5.41	
1.50	.250	1.11	10.00	10.00	10.00	3.49	
2.00	.125	1.22	21.95	31.95	31.95	2.12	
3.00	.063	13.76	100.00	100.00	100.00	.67	
4.00	.032	0.00	0.00	0.00	0.00	.63	
5.00	.016	0.00	0.00	0.00	0.00	.72	
6.00	.008	0.00	0.00	0.00	0.00	1.95	
7.00	.004	0.00	0.00	0.00	0.00	3.45	

16 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS
MM.
PI
2.50
2.68
.91
1.526
1.94

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

16 PCT.
50 PCT.
84 PCT.

SAMPLE ID
CORE25

LATITUDE
29 05.10N

LONGITUDE
095 04.60W

GALVESTON/CORE 25/400CM(=13.1 FT)

07-13-77

PI	MM.	SIZE	FREQUENCY	CUMULATIVE	PERCENT	VELOCITY	FALL
1.00	.500	1.00	0.00	0.00	0.00	3.49	
1.50	.250	1.11	10.00	10.00	10.00	2.12	
2.00	.125	13.76	100.00	100.00	100.00	.67	
3.00	.063	0.00	0.00	0.00	0.00	.61	
4.00	.032	0.00	0.00	0.00	0.00	.61	
5.00	.016	0.00	0.00	0.00	0.00	1.19	
6.00	.008	0.00	0.00	0.00	0.00	2.44	
7.00	.004	0.00	0.00	0.00	0.00	3.73	

16 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS
MM.
PI
2.31
2.44
.62
1.413
2.42

MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

GALVESTON, TEXAS - JEFF WILLIAMS									
PART 2 OF 2					CN. 0018-0034				
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	25	82	8	405	405	0	CONE25	29 05.10N	095 04.60W
GALVESTON/CONE 25/UNSCM(-13.3 FT BTH) 07-13-77									
PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
0.50	1.014	0.00	0.00	16.22	PHI MM.				
1.00	1.000	0.06	0.06	11.52	2.06	0.98			
1.50	0.707	0.37	0.43	8.03	2.06	0.29			
1.00	0.500	1.86	1.29	5.41	0.37	1.269			
1.50	0.354	2.11	4.40	3.49	-1.00				
2.00	0.250	40.44	43.85	2.12	0.53				
2.50	0.177	45.02	100.00	1.61					
3.00	0.125	11.13	100.00						
3.50	0.088	0.00	100.00						
4.00	0.062	0.00	100.00						
LT.	4.00	0.00							
16 PCT.				2.24					
50 PCT.				3.27					
84 PCT.				4.34					
REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	DEPTH ZONE	TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	26	82	8	80	80	0	CONE26	29 02.50N	095 04.20W
GALVESTON/CONE 26/080CM(-2.0 FT) 07-13-77									
PHI SIZE	MM. SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY	STATISTICAL PARAMETERS				
0.50	0.707	0.00	0.00	8.03	PHI MM.				
1.00	0.500	0.51	0.51	5.41	3.34	0.98			
1.50	0.354	1.65	1.15	3.49	3.24	0.10			
2.00	0.250	1.42	2.77	2.12	0.52	1.418			
2.50	0.177	4.54	7.31	1.62	-1.33				
3.00	0.125	20.59	27.90	1.22	0.53				
3.50	0.088	36.50	64.40	0.67					
4.00	0.063	35.60	100.00	0.38					
LT.	4.00	0.00	100.00						
16 PCT.				0.50					
50 PCT.				0.81					
84 PCT.				1.65					

GALVESTON, TEXAS - JEFF WILLIAMS PART 2 OF 2 CN, 0016-0034

REFERENCE NUMBER	CONSECUTIVE NUMBER	HANSEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CURE TOP	CURE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	26	62	29	8	RO	RO	0	COFE26	29 02.450N	095 04.620W

GALVESTON/CURE 26/000C(-2.6 FT) 07-13-77

SIZE	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL
1.00	2.000	0.00	0.00		
1.50	1.414	7.0	7.0	22.72	
2.00	1.000	52	1.22	10.42	
2.50	0.707	26	1.59	11.52	
3.00	0.500	0.00	0.00	5.03	
3.50	0.354	1.01	5.00	5.41	
4.00	0.250	2.00	10.00	2.49	
4.50	0.177	10.72	16.17	2.32	
5.00	0.125	18.10	24.97	1.52	
5.50	0.088	44.10	79.07	0.67	
6.00	0.063	21.19	100.00	0.50	
6.50	0.045	0.00	100.00		
7.00	0.032	0.00			

STATISTICAL PARAMETERS
PHI MM. 1.19
MEAN 0.104
STANDARD DEVIATION 0.123
SKEWNESS -0.67
KURTOSIS 11.73

16 PCT. 1.6
50 PCT. 4.5
84 PCT. 6.5

REFERENCE NUMBER 151

SIZE	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	DEPTH ZONE
1.00	1.414	0.00	0.00		
1.50	1.000	42	42	16.22	
2.00	0.707	58	1.00	11.52	
2.50	0.500	1.79	2.40	8.03	
3.00	0.354	1.03	4.73	5.41	
3.50	0.250	1.95	6.67	3.49	
4.00	0.177	16.46	23.13	2.12	
4.50	0.125	64.59	87.72	1.22	
5.00	0.088	35.41	100.00	0.77	
5.50	0.063	0.00	100.00		
6.00	0.045	0.00			
6.50	0.032	0.00			

STATISTICAL PARAMETERS
PHI MM. 2.86
MEAN 0.138
STANDARD DEVIATION 0.151
SKEWNESS 0.59
KURTOSIS 9.22

16 PCT. 1.6
50 PCT. 4.5
84 PCT. 6.5

REFERENCE NUMBER 151

SIZE	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	DEPTH ZONE
1.00	1.414	0.00	0.00		
1.50	1.000	42	42	16.22	
2.00	0.707	58	1.00	11.52	
2.50	0.500	1.79	2.40	8.03	
3.00	0.354	1.03	4.73	5.41	
3.50	0.250	1.95	6.67	3.49	
4.00	0.177	16.46	23.13	2.12	
4.50	0.125	64.59	87.72	1.22	
5.00	0.088	35.41	100.00	0.77	
5.50	0.063	0.00	100.00		
6.00	0.045	0.00			
6.50	0.032	0.00			

STATISTICAL PARAMETERS
PHI MM. 2.86
MEAN 0.138
STANDARD DEVIATION 0.151
SKEWNESS 0.59
KURTOSIS 9.22

16 PCT. 1.6
50 PCT. 4.5
84 PCT. 6.5

REFERENCE NUMBER 151

GALVESTON/CURE 27/000C(TUP) 07-13-77

SIZE	MM.	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	DEPTH ZONE
1.00	1.414	0.00	0.00		
1.50	1.000	42	42	16.22	
2.00	0.707	58	1.00	11.52	
2.50	0.500	1.79	2.40	8.03	
3.00	0.354	1.03	4.73	5.41	
3.50	0.250	1.95	6.67	3.49	
4.00	0.177	16.46	23.13	2.12	
4.50	0.125	64.59	87.72	1.22	
5.00	0.088	35.41	100.00	0.77	
5.50	0.063	0.00	100.00		
6.00	0.045	0.00			
6.50	0.032	0.00			

STATISTICAL PARAMETERS
PHI MM. 2.86
MEAN 0.138
STANDARD DEVIATION 0.151
SKEWNESS 0.59
KURTOSIS 9.22

16 PCT. 1.6
50 PCT. 4.5
84 PCT. 6.5

REFERENCE NUMBER 151

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CM, 0018-0030

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 OG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	27	82	29	7	150	150	0	CONF27	29 03.40N	095 07.50W

GALVESTON/COPE 24/0008CM(TOP)

07-13-77

PHI	MM*	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL VELOCITY	STATISTICAL PARAMETERS
1.00	2.000	0.00	0.00		22.72	PHI
0.50	1.414	0.00	0.00		16.22	MM*
0.00	1.000	8.16	8.21		11.52	MEAN
0.50	0.707	4.35	12.56		8.03	MEAN
1.00	0.500	4.52	17.08		5.41	STANDARD DEVIATION
1.50	0.354	3.32	20.40		3.49	SKWENESS
2.00	0.250	2.22	22.63		2.12	KURTOSIS
2.50	0.177	1.34	30.97		1.22	
3.00	0.125	0.93	50.49		0.67	
3.50	0.088	0.68	76.17		0.37	
4.00	0.063	0.33	100.00			
4.50	0.042	0.00	100.00			

16 PCT.
50 PCT.
80 PCT.

0.55
1.23
2.38

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 OG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	28	82	29	7	0	0	0	CONF28	29 02.70N	095 08.10W

GALVESTON/COPE 24/0008CM(TOP)

07-13-77

PHI	MM*	FREQUENCY PERCENT	CUMULATIVE PERCENT	VELOCITY	FALL VELOCITY	STATISTICAL PARAMETERS
1.00	2.000	0.00	0.00		22.72	PHI
0.50	1.414	1.20	1.20		18.52	MM*
0.00	1.000	1.99	3.19		14.72	MEAN
0.50	0.707	1.71	4.90		10.23	MEAN
1.00	0.500	2.57	7.47		5.41	STANDARD DEVIATION
1.50	0.354	2.63	10.10		3.49	SKWENESS
2.00	0.250	3.00	13.10		2.12	KURTOSIS
2.50	0.177	3.71	20.36		1.22	
3.00	0.125	2.21	48.56		0.67	
3.50	0.088	4.50	90.07		0.37	
4.00	0.063	0.93	100.00		0.55	
4.50	0.042	0.00	100.00			

16 PCT.
50 PCT.
80 PCT.

0.75
1.19
2.83

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

CN. 0018-0030

DEPTH	1 OG.	CORE	ANALYSIS	SAMPLE ID	LATITUDE	LONGITUDE
151	28	0	0	CORP28	29 02.70N	095 09.10W
151	28	0	0			

GALVESTON/CONE 28/000CM(TOP)

07-13-77

PHI	MM.	SIZE	FREQUENCY	CUMULATIVE	FALL
PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	VELOCITY
0.00	1.000	0.00	0.00	0.00	11.52
1.50	.707	1.24	1.24	1.24	8.03
1.00	.500	2.06	3.29	3.29	5.41
1.50	.354	2.41	5.70	5.70	3.49
2.00	.250	2.97	8.67	8.67	2.12
2.50	.177	5.74	14.41	14.41	1.22
3.00	.125	30.88	45.29	45.29	.68
3.50	.086	54.71	100.00	100.00	
4.00	.063	0.00	100.00	100.00	
4.50	.062	0.00	100.00	100.00	

STATISTICAL PARAMETERS
PHI MM.
3.04 .122
2.85 .139
2.62 1.541
-2.18 SKEWNESS
8.13 KURTOSIS

STANDARD DEVIATION
MEAN
MEAN
SKEWNESS
KURTOSIS

16 PCT.
50 PCT.
84 PCT.

.84
1.16
1.97

REFERENCE
NUMBER
151

1 OG.
SQUARE
29

CORE
TOP
180

LATITUDE
29 02.70N

LONGITUDE
095 09.10W

GALVESTON/CONE 28/180CM(=5.9 FT)

07-13-77

PHI	MM.	SIZE	FREQUENCY	CUMULATIVE	FALL
PERCENT	PERCENT	PERCENT	PERCENT	PERCENT	VELOCITY
0.00	1.000	0.00	0.00	0.00	8.03
1.50	.707	.12	1.12	1.12	5.41
1.00	.500	1.47	1.59	1.59	3.49
1.50	.354	2.64	4.24	4.24	2.12
2.00	.250	11.50	16.04	16.04	1.22
2.50	.177	34.24	50.28	50.28	.68
3.00	.125	45.72	100.00	100.00	
3.50	.086	0.00	100.00	100.00	
4.00	.063	0.00	100.00	100.00	
4.50	.062	0.00	100.00	100.00	

STATISTICAL PARAMETERS
PHI MM.
2.86 .129
2.68 .156
-1.35 SKEWNESS
5.14 KURTOSIS

STANDARD DEVIATION
MEAN
MEAN
SKEWNESS
KURTOSIS

16 PCT.
50 PCT.
84 PCT.

.87
1.29
2.12

GALVESTON, TEXAS - JEFF - ILLIAMS

PART 2 OF 2

CNA, 0018-0036

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	28	82	29	7	353	353	0	COM28	29 02.70N	095 09.10W

GALVESTON/CORE 28/353CM(=11.5 FT)

07=15=77

PHI	MM.	FREQUENCY	CUMULATIVE PERCENT	VELOCITY	FALL
SIZE	SIZE	PERCENT			
-1.00	2.000	0.00	0.00	0.00	22.72
.50	1.414	3.49	4.02	4.02	16.22
0.00	1.000	3.49	5.36	5.36	11.52
1.50	.707	1.35	5.63	5.63	6.03
1.00	.500	1.35	6.97	6.97	5.41
1.50	.354	1.14	9.94	9.94	3.40
2.00	.250	12.97	24.23	24.23	2.12
2.50	.177	12.29	57.18	57.18	1.22
3.00	.125	32.95	94.16	94.16	1.07
3.50	.089	36.88	100.00	100.00	.61
4.00	.062	34.94	100.00	100.00	
LT.	4.00	.062	0.00		

STATISTICAL PARAMETERS	
PHI	MM.
2.91	.133
2.70	.154
.84	1.780
-2.26	
6.65	

14 PCT.
50 PCT.
84 PCT.

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SQUARE	1 DG. SQUARE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	28	82	29	7	403	403	0	COM28	29 02.70N	095 09.10W

GALVESTON/CORE 28/403CM(=13.2 FT)

07=15=77

PHI	MM.	FREQUENCY	CUMULATIVE PERCENT	VELOCITY	FALL
SIZE	SIZE	PERCENT			
-1.00	2.000	0.00	0.00	0.00	22.72
.50	1.414	.31	4.31	4.31	16.22
0.00	1.000	4.00	5.67	5.67	11.52
.50	.707	1.36	9.41	9.41	8.03
1.00	.500	3.74	11.25	11.25	5.41
1.50	.354	1.64	14.23	14.23	3.49
2.00	.250	2.99	20.66	20.66	2.12
2.50	.177	6.42	34.31	34.31	1.22
3.00	.125	17.66	73.30	73.30	.67
3.50	.089	34.99	100.00	100.00	.40
4.00	.062	26.70	100.00	100.00	
LT.	4.00	.062	0.00		

STATISTICAL PARAMETERS	
PHI	MM.
3.17	.111
2.87	.137
1.03	2.036
-1.78	
5.48	

16 PCT.
50 PCT.
84 PCT.

GALVESTON, TEXAS - JEFF WILLIAMS PART 2 OF 2 CN, 0018-003u

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SOURCE	1 DG SOURCE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	34	82	29	7	20	20	0	CONF34	28 56+60N	095 16+50W

GALVESTON~CORE 34/020CM(+0.4 FT)

07-11-77

PHI	MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
-450	1.014	0.00	0.00	0.00	16.22
0.00	1.000	1.51	1.51	1.51	11.52
450	0.707	1.59	3.10	3.10	8.03
1.00	0.500	1.05	4.15	4.15	5.41
1.50	0.354	1.42	5.57	5.57	3.49
2.00	0.250	1.69	7.26	7.26	2.12
2.50	0.177	1.89	9.15	9.15	1.22
3.00	0.125	15.33	24.48	24.48	0.67
3.50	0.088	34.49	58.97	58.97	0.45
4.00	0.063	33.73	92.70	92.70	
4.50	0.042	0.00	100.00	100.00	

LT, 4.00

16 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS
PHI MM
3.30
3.03
3.03
1.063
2.04
6.96

STATISTICAL PARAMETERS
MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

REFERENCE NUMBER	CONSECUTIVE NUMBER	MARSDEN SOURCE	1 DG SOURCE	DEPTH ZONE	CORE TOP	CORE BOTTOM(CM)	ANALYSIS CODE	SAMPLE ID	LATITUDE	LONGITUDE
151	34	82	29	7	100	100	0	CONF34	28 56+60N	095 16+50W

GALVESTON~CORE 34/100CM(+3.2 FT)

07-11-77

PHI	MM	SIZE	FREQUENCY PERCENT	CUMULATIVE PERCENT	FALL VELOCITY
0.00	1.000	0.00	0.00	0.00	11.52
450	0.707	0.42	0.42	0.42	8.03
1.00	0.500	1.02	1.44	1.44	5.41
1.50	0.354	1.36	2.80	2.80	3.49
2.00	0.250	1.56	4.37	4.37	2.12
2.50	0.177	4.63	9.00	9.00	1.22
3.00	0.125	14.11	23.10	23.10	0.67
3.50	0.088	34.53	57.63	57.63	0.40
4.00	0.063	42.37	100.00	100.00	
4.50	0.042	0.00	100.00	100.00	

LT, 4.00

16 PCT.
50 PCT.
84 PCT.

STATISTICAL PARAMETERS
PHI MM
3.41
3.24
3.24
1.523
2.01
8.31

STATISTICAL PARAMETERS
MEDIAN
MEAN
STANDARD DEVIATION
SKEWNESS
KURTOSIS

GALVESTON, TEXAS - JEFF WILLIAMS

PART 2 OF 2

C# 0018-0030

REFLECTANCE	CONSECUTIVE	MARSDEN	1 DG.	DEPTH	CURE	ANALYSIS	SAMPLE ID	LATITUDE	LONGITUDE
NUMBER	NUMBER	SQUARE	SQUARE	ZONE	TOP	CODE	CORE30	28 56.60N	095 16.50W
151	30	M2	29	7	200	0			

GALVESTON/CORE 30/270CM (=0.5 FT)

07-11-77

SIZE	TYPE	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS
MM	SIZE	PERCENT	PERCENT	VELOCITY	PHI MM.
0.50	1.000	0.00	0.00		3.33
0.60	1.000	1.55	1.55	16.22	0.09
0.70	1.000	2.14	3.69	11.52	3.11
0.80	1.000	1.29	4.97	8.01	0.16
1.00	1.50	1.53	6.50	5.41	1.760
1.25	1.50	1.55	8.05	3.49	
1.50	2.50	3.23	11.28	2.12	STANDARD DEVIATION
1.75	1.77	14.95	26.23	1.22	0.82
2.00	1.25	18.95	45.18	0.67	SKEWNESS
3.50	0.68	35.05	80.23	0.13	-2.59
4.00	0.81	100.00	100.00		0.89
4.50	0.62	100.00	100.00		KURTOSIS
4.75	0.62	100.00	100.00		0.89

10 PCT.
50 PCT.
90 PCT.

0.52
0.83
1.64

REFLECTANCE CONSECUTIVE MARSDEN

1 DG.

CURE

ANALYSIS

SAMPLE ID

LATITUDE

LONGITUDE

095 16.50W

GALVESTON/CORE 30/270CM (=0.6 FT)

07-11-77

SIZE	TYPE	FREQUENCY	CUMULATIVE	FALL	STATISTICAL PARAMETERS
MM	SIZE	PERCENT	PERCENT	VELOCITY	PHI MM.
0.60	1.000	0.00	0.00		3.31
0.70	1.10	1.10	1.10	11.52	0.10
0.80	1.50	0.45	1.55	8.03	0.13
1.00	1.26	2.81	4.36	5.41	1.542
1.25	1.57	3.44	6.80	3.49	
1.50	2.50	7.45	14.25	2.12	STANDARD DEVIATION
1.75	1.77	14.57	28.82	1.22	0.66
2.00	1.25	30.57	59.39	0.67	SKEWNESS
3.50	0.68	100.00	100.00	0.40	-1.63
4.00	0.81	100.00	100.00		0.36
4.50	0.62	100.00	100.00		KURTOSIS
4.75	0.62	100.00	100.00		0.36

10 PCT.
50 PCT.
90 PCT.

0.51
0.85
1.42

CERC SEDIMENT ANALYSIS

CERC CN 27 Collected by S.J. Williams Date 7-13-77
 Project Galveston, Texas - Core 27
 Location/Sample No. -127 cm (-4.1 ft)
 Remarks _____

SIEVE ANALYSIS OF SAND
 Weight of Sample 69.39 gr. Analyzed by M.L. Koenig Date 1-24-77

φ	Screen Opening mm	U.S. Mesh Number	Retained on Sieves			Cumulative Per Cent Passing
			Grams	Per Cent	Cumulative Per Cent	
-4.00	16.000	5/8				
-3.68	13.550	1/2				
-3.50	11.100	7/16	1.94	2.805	17.826	82.175
-3.25	9.520	3/8	3.60	5.205	23.031	76.970
-3.00	7.930	5/16	5.18	7.489	30.520	69.481
-2.65	6.350	1/4	6.79	9.816	40.336	59.665
-2.50	5.613	3 1/2	1.59	2.299	42.635	57.366
-2.25	4.760	4	3.72	5.378	48.013	51.988
-2.00	3.962	5	3.29	4.756	52.769	47.232
-1.75	3.350	6				
-1.50	2.794	7	7.10	10.265	63.034	36.967
-1.25	2.362	8	2.60	3.759	66.793	33.208
-1.00	2.000	10	.74	1.070	67.863	32.138
-0.75	1.700	12	1.38	1.995	69.858	30.143
-0.50	1.400	14	2.00	2.891	72.749	27.252
-0.25	1.180	16	1.49	2.154	74.903	25.098
0.00	1.000	18	1.22	1.764	76.667	23.334
+0.25	.850	20	1.52	2.197	78.864	21.137
+0.50	.710	25	1.25	1.807	80.671	19.330
+0.75	.600	30	.92	1.330	82.001	18.000
+1.00	.500	35	.71	1.026	83.027	16.974
+1.25	.425	40	.58	.839	83.866	16.135
+1.50	.355	45	.50	.723	84.589	15.412
+1.75	.300	50	.39	.564	85.153	14.848
+2.00	.250	60	.38	.549	85.702	14.299
+2.25	.212	70	.49	.708	86.410	13.591
+2.50	.180	80	.38	.549	86.959	13.042
+2.75	.150	100	2.40	3.470	90.429	9.572
+3.00	.125	120	1.88	2.718	93.147	6.854
+3.25	.106	140	1.62	2.631	95.778	4.223
+3.50	.090	170	1.72	2.487	98.265	1.736
+3.75	.075	200	.78	1.128	99.393	.608
+4.00	.063	230	.10	.145	99.538	.463
	0.000	Pan	.32	.463	100.001	.000
Totals			69.17	100.001		
Gain or loss			-.22			

Mean diameter: 4.16 mm (-2.06 phi)
 Phi standard deviation: 2.35

GALVESTON/CORE 03/000CM(TOP)
 GALVESTON/CORE 03/000CM(TOP)
 GALVESTON/CORE 03/030CH(-1.1 FT)

□
 △
 X

GALVESTON/CORE 03/090CM(-3.0 FT)

□

GALVESTON/CORE 03/200CM(-6.6 FT)

△

GALVESTON/CORE 03/235CM(-7.7 FT BTH)

×

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 05/340CM(-11.2 FT) □

GALVESTON/CORE 05/340CM(-11.2 FT) Δ

GALVESTON/CORE 11/140CM(-4.5 FT) X

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 11/200CM(-6.5 FT)

□

GALVESTON/CORE 11/240CM(-7.8 FT)

△

GALVESTON/CORE 11/250CM(-8.2 FT)

×

GALVESTON/CORE 11/270CM(-8.8 FT)
 GALVESTON/CORE 11/270CM(-8.8 FT)

□
 △

GALVESTON/CORE 12/115CM(-3.7 FT)

□

GALVESTON/CORE 12/140CM(-4.5 FT)
 GALVESTON/CORE 12/240CM(-7.8 FT)
 GALVESTON/CORE 12/440CM(-14.4 FT)

□
 △
 ×

PARTICLE SIZE DISTRIBUTION MILLIMETERS

GALVESTON/CORE 14/000CM(TOP)
 GALVESTON/CORE 14/000CM(TOP)
 GALVESTON/CORE 14/062CM(-2.0 FT)

□
 △
 ×

GALVESTON/CORE 14/094CM(-3.0 FT) □

GALVESTON/CORE 14/124CM(-4.0 FT) Δ

GALVESTON/CORE 14/190CM(-6.2 FT) X

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

NONUNIFORM SCALE

GALVESTON/CORE 15/040CH(-1.3 FT)

□

GALVESTON/CORE 15/040CH(-1.3 FT)

△

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

NORTH SCALE

GALVESTON/CORE 15/213CM(-6.9 FT)
 GALVESTON/CORE 15/230CM(-7.5 FT)
 GALVESTON/CORE 15/262CM(-8.6 FT BTH)

□

△

×

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 16/056CM(-1.8 FT)

□

GALVESTON/CORE 16/155CM(-5.0 FT)

△

GALVESTON/CORE 16/155CH(-5.0 FT)

×

GALVESTON/CORE 17/070CM(-2.2 FT)

GALVESTON/CORE 17/086CM(-2.8 FT)

GALVESTON/CORE 17/106CM(-3.2 FT)

□

△

×

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
MONTGOMERY SCALE					

GALVESTON/CORE 17/150CM(-4.9 FT) □

GALVESTON/CORE 17/200CM(-6.5 FT) Δ

GALVESTON/CORE 17/200CM(-6.5 FT) X

GALVESTON/CORE 17/235CM(-7.7 FT)
 GALVESTON/CORE 17/270CM(-8.8 FT)
 GALVESTON/CORE 17/323CM(-10.5 FT)

□
 △
 X

GALVESTON/CORE 17/354CM(-11.6 FT)

□

GALVESTON/CORE 17/390CM(-12.7 FT)

△

GALVESTON/CORE 17/390CM(-12.7 FT)

×

GALVESTON/CORE 17/458CM(-15.0 FT)

GALVESTON/CORE 17/500CM(-16.4 FT)

GALVESTON/CORE 17/570CM(-18.7 FT)

□

Δ

X

PARTICLE SIZE DISTRIBUTION MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 18/000CM(TCP)
 GALVESTON/CORE 18/070CM(-2.2 FT)
 GALVESTON/CORE 18/070CM(-2.2 FT)

□
 △
 ×

GALVESTON/CORE 18/120CM(-3.9 FT)
 GALVESTON/CORE 18/220CM(-7.2 FT)
 GALVESTON/CORE 18/310CM(-10.1 FT)

□
 △
 ×

GALVESTON/CORE 18/365CM (-11.9 FT)
 GALVESTON/CORE 18/396CM (-12.9 FT)
 GALVESTON/CORE 18/336CM (-12.9 FT)

□
 △
 X

SPRINKLE	TEST COURSE	CORRUS RING	MEDIUM RING	PIKE RING	VERY PIKE RING
----------	-------------	-------------	-------------	-----------	----------------

NORTHWEST CORNER

GALVESTON/CORE 21/125CM (~4.1 FT)

GALVESTON/CORE 21/125CM (~4.1 FT)

GALVESTON/CORE 21/200CM (~6.5 FT)

PARTICLE SIZE DISTRIBUTION
 MILLIMETERS

GALVESTON/CORE 19/210CM(-0.8 FT)

□

GALVESTON/CORE 23/098CM(-3.2 FT)

△

GALVESTON/CORE 23/098CM(-3.2 FT)

×

GALVESTON/CORE 21/000CM (TOP)

GALVESTON/CORE 21/050CM (-1.6 FT)

GALVESTON/CORE 21/080CM (-2.6 FT)

GALVESTON/CORE 23/300CM(-9.8 FT)
 GALVESTON/CORE 23/380CM(-12.4 FT)

□
 △

GALVESTON/CORE 21/350CM(-11.4 FT)

□

GALVESTON/CORE 22/140CM(-4.5 FT)

△

GALVESTON/CORE 22/180CM(-5.9 FT)

×

GALVESTON/CORE 24/000CH(TOP)
 GALVESTON/CORE 24/045CH(-1.4 FT)
 GALVESTON/CORE 24/045CH(-1.4 FT)

□
 △
 ×

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 23/469CM(-15.4 FT BTM)

GALVESTON/CORE 25/120CM(-3.9 FT)

GALVESTON/CORE 25/148CM(-4.8 FT)

□

△

×

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

NONORTH SCALE

GALVESTON/CORE 25/200CM(-6.5 FT)

□

GALVESTON/CORE 25/200CM(-6.5 FT)

△

GALVESTON/CORE 25/250CM(-8.2 FT)

×

GALVESTON/CORE 25/350CM(-11.4 FT) □
 GALVESTON/CORE 25/400CM(-13.1 FT) △
 GALVESTON/CORE 25/405CM(-13.3 FT BTM) ×

GALVESTON/CORE 25/000CM(TOP)
 GALVESTON/CORE 26/080CM(-2.6 FT)
 GALVESTON/CORE 26/080CM(-2.6 FT)

□
 △
 ×

GALVESTON/CORE 24/102CM(-3.3 FT)
GALVESTON/CORE 27/000CM(TOP)

□
△

PARTICLE SIZE DISTRIBUTION
 MILLIMETERS

GRAVEL	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
--------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 27/050CM(-1.6 FT)

GALVESTON/CORE 27/100CM(-3.2 FT)

GALVESTON/CORE 27/150CM(-4.8 FT)

□

△

×

GALVESTON/CGRE 28/000CM(TOP)
 GALVESTON/CGRE 28/000CM(TOP)
 GALVESTON/CGRE 28/180CM(-5.9 FT)

□
 △
 ×

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GRABBLE	VERY COARSE	COARSE SAND	MEDIUM SAND	FINE SAND	VERY FINE SAND
---------	-------------	-------------	-------------	-----------	----------------

GALVESTON/CORE 28/353CM (~11.5 FT)

□

GALVESTON/CORE 28/403CM (~13.2 FT)

△

GALVESTON/CORE 34/020CM (~0.6 FT)

×

GALVESTON/CORE 33/200CM (-6.5 FT)

□

PARTICLE SIZE DISTRIBUTION
MILLIMETERS

GALVESTON/CORE 34/100CM(-3.2 FT)

GALVESTON/CORE 34/200CM(-6.6 FT)

GALVESTON/CORE 34/270CM(-8.8 FT)

□

△

X

<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581nr no. 79-4 627</p>	<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581nr no. 79-4 627</p>
<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581nr no. 79-4 627</p>	<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581nr no. 79-4 627</p>

<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581mr no. 79-4 627</p>	<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581mr no. 79-4 627</p>
<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581mr no. 79-4 627</p>	<p>Williams, S. Jeffress Sediment distribution, sand resources, and geologic character of the inner continental shelf off Galveston County, Texas / by S. Jeffress Williams, Dennis A. Prins. . . [et al.]. - Ft. Belvoir, Va. : U.S. Coastal Engineering Research Center ; Springfield, Va. : available from National Technical Information Service, 1979. 159 p. : ill. (Miscellaneous report - U.S. Coastal Engineering Research Center ; no. 79-4) Bibliography : p. 50. About 850 square kilometers of the Texas inner shelf from High Island to Freeport was surveyed and studied, using high-resolution continuous seismic reflection profiles and 34 long cores, to determine the general geologic character and surface and subbottom sediment distribution. The objective was to assess the resource potential of sand deposits suitable as fill for beach nourishment projects. 1. Geomorphology. 2. Continental shelf. 3. Marine sediments. 4. Beach nourishment. I. Title. II. Prins, Dennis A., joint author. III. Series: U.S. Coastal Engineering Research Center. Miscellaneous report no. 79-4. TC203 .U581mr no. 79-4 627</p>

100-100