Historic, archived document

Do not assume content reflects current scientific knowledge, policies, or practices.

UNITED STATES DEPARTMENT OF AGRICULTURE

BULLETIN No. 750

Joint Contribution from the Bureau of Chemistry
CARL L. ALSBERG, Chief
and the Insecticide and Fungicide Board
J. K. HAYWOOD, Chairman

Washington, D. C.

Professional Paper

October 5, 1918.

A METHOD FOR PREPARING A COMMERCIAL
GRADE OF CALCIUM ARSENATE.

By J. K. HAYWOOD, *Chief, Miscellaneous Division, and Chairman, Insecticide and Fungicide Board*, and C. M. SMITH, *Assistant Chemist*.

CONTENTS.

	Page.		Page.
Calcium arsenate as a substitute for lead arsenate.....	1	Effect of dilution and temperature upon the compound.....	7
Preparation of calcium arsenate.....	2	Experiments with limestone.....	9
Slaking the lime.....	4	Summary.....	9
Proper proportion of arsenic oxid and lime.....	4	Labeling the product.....	10

CALCIUM ARSENATE AS A SUBSTITUTE FOR LEAD ARSENATE.

Recently attention has been directed to the use of calcium arsenate as a substitute for lead arsenate, principally because of the cheapness of lime as compared with lead oxid. While no one recommends the use of calcium arsenate alone on tender foliage, experiments by the United States Department of Agriculture¹, the Canadian Department of Agriculture², and others have shown that it gives excellent results on some of the more resistant plants, as well as very promising results when combined with other sprays, especially sulphids, which cause to a greater or less extent the breaking up of lead arsenate.

¹ U. S. Dept. Agr. Bul. 278, Farmers' Bul. 908.

² Crop Protection Leaflet 10.

PREPARATION OF CALCIUM ARSENATE.

The Bureau of Entomology of this Department has carried out experiments with "homemade" calcium arsenate prepared by slaking burned lime with a solution of sodium arsenate. Others¹ have recommended calcium arsenate prepared by the action of soluble lime salts on sodium arsenate. In all such cases soluble by-products are formed. Since these may influence the action of the spray if not removed, they should be washed and filtered out if a good grade of commercial calcium arsenate is desired.

From the chemical standpoint, the simplest means of producing calcium arsenate is the direct union of calcium hydroxid and arsenic acid. As the only by-product of this reaction is water, filtration of the material is the only treatment that should be required, thus eliminating the washing necessary with most products. The following experiments were made with the idea of determining the proportions and procedure necessary to obtain a product having the properties desired for spraying purposes². The arsenic acid used was commercial 75 per cent acid. Its density was found to be 1.88, corresponding to 61 per cent As_2O_5 , or 75 per cent arsenic acid, H_3AsO_4 . The lime was a good grade of commercial lime of the following composition:

	Per cent.
Loss on ignition.....	5.07
Calcium oxid, CaO	93.36
Magnesium oxid, MgO	.69
Silicon dioxid, SiO_2	.54
Oxids of iron and aluminum, R_2O_3	.68
	<hr/> 100.34

In the absence of other drawbacks, the most desirable method of uniting lime and arsenic acid is to have both ingredients in solution before they are mixed. This necessitates the use of lime water which contains only about 1 gram of CaO per liter, and of a quantity of water so large that it probably would be prohibitive in commercial practice. Nevertheless, a few experiments were made to discover the nature of the product so formed.

¹ Oregon Agr. Exp. Sta. Bul. 131.

² The desirable features of a good arsenical spray material may be enumerated here. It should not contain an excessive amount of soluble arsenic, which would cause injury to foliage; it should be very finely divided in order that it may be distributed well over the foliage; it should be light when in the dry form, to permit of ready application by dusting; it should suspend well in water, to permit of even distribution when applied in the form of a spray; and when sprayed and subsequently dried it should stick well to the foliage.

If arsenic acid of any strength is added slowly to lime water containing phenolphthalein until the latter is just about to decolorize, a gelatinous, slow-settling precipitate is formed. After the lapse of an hour or so, this crystallizes and settles to about one-eighth of the volume of the liquid used. The precipitate filters very readily, leaving a cake which on the steam bath dries fairly rapidly to very light lumps easily powdered between the fingers. Its extreme lightness is very noticeable, and it does not require grinding, simply a disintegration of the lumps. One preparation, dried at about 70°C. on the steam bath, had the following composition:

	Per cent.
Calcium oxid, CaO.....	32.00
Arsenic oxid, As ₂ O ₅	42.96
Water (by difference) (slight amount of CO ₂).....	25.04
	<hr/> 100.00

The molecular ratio of CaO to As₂O₅ is here 3.05, showing the compound to be tricalcium arsenate. It approximates most closely to the formula Ca₃(AsO₄)₂·8H₂O. In an investigation on the chemistry of the calcium arsenates, the results of which will be published later, it has been shown that such a compound exists. Drying at 110°C. results in the loss of about seven of the eight molecules of water of crystallization. The lightness of this material may be judged from the fact that 2 ounces of it filled a graduated cylinder to the 500 cubic centimeter mark, which is equivalent to 240 cubic inches per pound, this, of course, without any attempt at packing. If jarred for a sufficient time the space occupied will be reduced to about 60 per cent of this figure.

The compound thus formed yields appreciable amounts of soluble arsenic when treated with water. In one experiment 1.8 grams were treated with 1 liter of water (equivalent in arsenic content to 1 pound of dilead arsenate in 50 gallons) for 24 hours, and 55 milligrams, or 3.04 per cent, of As₂O₅ were rendered soluble. R. H. Robinson¹ found 79 milligrams of As₂O₅ per liter for somewhat similar material. This, of course, is an excessive amount, and would render the material unfit for use alone on any but the hardiest foliage, such as will stand applications of paris green.

If the manufacture of calcium arsenate by this process were attempted commercially, the liquid left from the settling of one batch of arsenate could be used again for the preparation of more lime water, and thus the consumption of water might be greatly reduced. However, methods requiring the handling of as little material as

¹ Oregon Agr. Exp. Sta. Bul. 131, p. 7.

possible probably would be preferable. On first thought, such a process would be the direct slaking of the stone lime with the requisite strength arsenic acid solution. But such a procedure is not practicable. Owing to the slow surface action, the As_2O_5 is locally always in excess, resulting in the formation of dicalcium or even monocalcium arsenate (if the H_3AsO_4 is strong enough), which, while it may be changed later by the excess of lime, renders the product lumpy or granular. Even the use of strong arsenic acid with a concentrated lime paste suffers from the same drawbacks—the addition of the acid causes a further thickening of the paste, and thorough and rapid mixing becomes impossible.

SLAKING THE LIME.

Only more or less dilute lime paste, made by the slaking of quicklime, was used in the experiments here reported. It is self-evident that the ease with which such a paste will combine with acid is directly dependent on the smoothness of the paste. Consequently experiments to determine the best procedure to follow in slaking so that the paste would be smooth and free from lumps were made first. It was soon found that the use of 3 to $3\frac{1}{2}$ times as much water (by weight) as lime gave a paste which was entirely satisfactory, if the lime employed was sufficiently pure. This produces a paste rather thick, but not thick enough to interfere with good mixing when working with small quantities. Best results were obtained by using boiling water for slaking, although in bulk the natural heat of reaction would be sufficient.

PROPER PROPORTION OF ARSENIC OXID AND LIME.

As previously noted, it is essential that a compound for spraying purposes shall be free, or nearly so, from arsenic in water-soluble forms. As seen by reference to the description of practically pure crystalline tricalcium arsenate, that material is appreciably acted upon by water. Other work done in the Bureau of Chemistry on this subject has shown that all of the calcium arsenates more acid than this are likewise somewhat soluble (or decomposable), the action increasing until the monoarsenate, which is very readily soluble in water, is reached. Evidently, then, it is necessary to look toward the basic side. It has long been known that the addition of an excess of lime to a spraying compound renders the arsenic insoluble. The object here was to find the right proportions to produce a material combining high arsenic oxid content with sufficiently low water-soluble As_2O_5 to prevent burning or reduce it to the lowest possible limit. Two series of experiments were made

along this line. Each series included 8 experiments, the molecular ratio, $\text{CaO}/\text{As}_2\text{O}_5$ being varied from 3 to 5 by appropriate steps. The amount of As_2O_5 used was kept constant, being 25 cubic centimeters of a solution containing 0.4 gram As_2O_5 per cubic centimeter (in other words, a total of 10 grams As_2O_5). The weighed amounts of lime were slaked in beakers with 3 times their weight of boiling water, and the cold arsenic solution added rather slowly, from a pipette, with constant stirring. In one series (A) the acid was added to the lime while still hot from slaking; in the other series (B) the lime paste was permitted to cool to room temperature before mixing. Each mixture was then divided into two portions, one of which was permitted to stand over night, then decanted, the other being filtered and sucked as dry as possible on a Büchner funnel for the purpose of determining the amount of water each process left in the paste. Water was determined in portions of each paste by drying in the oven at 105°C . The dried portions were used for chemical analysis. The water-soluble arsenic was determined on the dry material, using 1.2 grams in 500 cubic centimeters (equivalent to 1 pound in 50 gallons). The results of these experiments are summarized in Table 1.

TABLE 1.—*Analysis of experimental spraying compounds.*

Exp. No.	Designation.		Lime used, Grams.	As ₂ O ₃ used, Grams.	Water in—		Analysis of material dried at 105°C.		Molecular ratio, CaO/As ₂ O ₃ , Per cent.	Soluble arsenic, As ₂ O ₃ , Per cent.	Dried material per pound, Cubic inches.
	Series No.				Settled material, Per cent.	Filtered material, Per cent.	CaO, Per cent.	As ₂ O ₃ , Per cent.			
1	{ A.....		7.30	10	52.5	36.2	35.52	52.71	2.76	11.51	69
	{ B.....		7.30	10	66.1	58.8	37.30	51.76	2.95	8.26	82
2	{ A.....		7.79	10	59.2	47.7	38.75	51.84	3.07	5.06	66
	{ B.....		7.79	10	67.5	59.2	38.70	51.53	3.08	4.52	77
3	{ A.....		8.28	10	61.7	51.2	39.70	50.77	3.20	2.51	68
	{ B.....		8.28	10	67.8	53.8	40.59	50.17	3.17	1.52	76
4	{ A.....		8.77	10	64.6	51.1	41.15	49.46	3.41	1.83	68
	{ B.....		8.77	10	66.8	53.9	41.49	48.00	3.51	1.14	80
5	{ A.....		9.25	10	59.8	56.4	40.45	46.38	3.58	.48	69
	{ B.....		9.25	10	67.7	54.3	42.32	46.22	3.75	.42	76
6	{ A.....		9.74	10	59.2	52.4	42.02	46.17	3.73	.50	62
	{ B.....		9.74	10	66.9	51.5	42.90	43.22	4.07	.19	72
7	{ A.....		10.96	10	60.7	48.5	43.67	41.42	4.32	.25	70
	{ B.....		10.96	10	66.7	49.6	44.80	43.36	4.24	.06	80
8	{ A.....		12.17	10	67.7	54.2	45.76	39.26	4.78	.27	74
	{ B.....		12.17	10	66.1	58.0	47.66	40.32	4.79	(¹)	83

¹ Lost.

It will be noted that in every case series B gave lower soluble arsenic figures than series A, and also that only when the ratio equals 4 or more does the soluble arsenic decrease to about 0.2 per cent. Consequently, all commercial calcium arsenates should be at least as basic as $4\text{CaO}.\text{As}_2\text{O}_5$, upon which ratio all later experiments were based. The content of water of constitution, and probably crystallization (about 14 per cent), might be reduced by heating to a sufficiently high temperature if this were found to be desirable from a commercial standpoint. Probably next in importance to the question of soluble arsenic comes the question of lightness of material, that quality which governs the suspension in water. This is controlled by two things, actual density and size of particles. All the calcium arsenates have densities around 3, approximately half that of the corresponding lead compounds. This is a characteristic property of each compound, practically independent of conditions. The size of particles, however, is influenced by the manner of mixing, the temperature, the concentration, etc. In the experiments reported in Table 1, the arsenic acid was added quite slowly to the lime, in the belief that it was best to prevent even the slightest local excess of acid. It was found later, however, that rapid mixing gave a product which was much more easily powdered. Table 1 also shows that temperature has a marked effect, a more bulky product being formed when the solutions are mixed in the cold.

EFFECT OF DILUTION AND TEMPERATURE UPON THE COMPOUND.

A group of 16 experiments was designed to show the effect of dilution and temperature upon this quality of lightness. In all the experiments the quantity of lime and acid used was the same—11 grams of lime (93 per cent CaO) and 10 grams of As_2O_5 . In every case the lime was slaked with 35 cubic centimeters of boiling water. Four temperature combinations were used: Both hot; lime hot, acid cold; acid hot, lime cold; both cold. Four dilutions were used. In every case the acid was dumped as fast as possible into the lime. In the more concentrated mixtures, especially when warm, reaction took place rapidly, phenolphthalein being reddened immediately. But as dilution increased and the temperature fell, action was delayed, the solution remaining acid for perhaps 10 minutes. This is no doubt due to the fact that the acid does not penetrate instantaneously into the small particles of lime in suspension. When both solutions are hot the reaction is violent, causing rapid boiling, while when both solutions are cold, only a mod-

erate rise in temperature occurs. For instance, in 4 A the temperature rose from 32°C. to 65°C., and in 4 D from 32°C. to 40°C.

After mixing and standing for 15 to 20 minutes the precipitates were filtered off, and dried over night on the steam bath. Portions were then sieved through a No. 100 mesh sieve, and their bulkiness compared by measuring the volume occupied by 2.77 grams in a 10 cubic centimeter graduated cylinder. Ten times the figure read on the cylinder equals the number of cubic inches per pound. The measurements were taken just as the material was poured into the cylinders, no attempt being made to pack it. Entomologists have stated that a good calcium arsenate for dusting purposes should occupy from 70 to 90 cubic inches per pound. Such determinations, however, are comparable only when conducted in the same way.

The results of these experiments are summarized in Table 2.

TABLE 2.—*Effect of dilution and temperature on lightness of spraying compounds.*

Experiment No.	Temperature.	Series number, degree of dilution, and lightness of compound.			
		A.	B.	C.	D.
		11 gm. lime— 35 cc H ₂ O 10 gm. As ₂ O ₅ — 25 cc H ₂ O.	11 gm. lime— 70 cc H ₂ O 10 gm. As ₂ O ₅ — 50 cc H ₂ O.	11 gm. lime— 105 cc H ₂ O 10 gm. As ₂ O ₅ — 75 cc H ₂ O.	11 gm. lime— 140 cc H ₂ O 10 gm. As ₂ O ₅ — 100 cc H ₂ O.
		Cu. in. per lb.	Cu. in. per lb.	Cu. in. per lb.	Cu. in. per lb.
1	Lime hot, acid cold.....	69	96	104	128
2	Acid hot, lime cold.....	69	104	126	112
3	Both hot.....	69	78	92	98
4	Both cold.....	86	104	90	80

These results show that the general tendency is the production of the lighter material in the lower concentrations. But here a new feature, the hardness of the lumps and the effort necessary to reduce them to powder, makes its appearance. Amorphousness is usually associated with the production of hard, lumpy residues on drying, as, for example, in the case of aluminum hydroxid. So here we have 1 D, 2 C, and 2 D, the lightest of the powders, producing hard lumps, 2 D being the hardest of the lot. It was difficult to break them in the fingers, and for commercial use they would almost certainly have to be ground. On the other hand, 4 A and 4 D were crumbly, and could be readily reduced to powder by simply shaking them. Probably, then, a compromise between a method of preparation which produces the lightest powder and a method which produces the most easily pulverized powder would be necessary.

The results show equal bulkiness for 2 B, 4 B, and 1 C, and all of these, especially 1 C, were easily powdered. *Based on this work, the authors are of the opinion that the most advantageous method to produce a reasonably light material, which at the same time is easily pulverized, is to slake the lime, add two more volumes of hot water, and then add the cold arsenic acid solution as rapidly as possible (method 1 C).* Methods 4 B, 2 B, and 4 A also, however, give a product which is reasonably light and easily pulverized.

None of these products, except the tricalcium arsenate mentioned in the beginning of this article, is quite as bulky as some of the commercial dilead arsenates, some of which run as high as 140 cubic inches per pound when measured in the manner prescribed here. However, this calcium arsenate, as aforesaid, yields an excessive amount of water-soluble arsenic, and is prepared by a method that is hardly practicable under manufacturing conditions.

EXPERIMENTS WITH LIMESTONE.

It was at first thought that calcium arsenate might be made directly from limestone, instead of from lime, thus saving the expense of burning. A few experiments along this line showed that calcium carbonate reacts quite readily with arsenic acid at room temperature, and continues to do so until the solution is about neutral to methyl orange. At this point, the solution contains CaO and As_2O_5 in the proportions to form calcium monoarsenate, $\text{CaH}_4(\text{AsO}_4)_2$. If this solution is heated by itself, it deposits crystals of dicalcium arsenate, $\text{CaHAsO}_4 \cdot \text{H}_2\text{O}$, which on continued boiling change to CaHAsO_4 . In the presence of excess CaCO_3 , reaction continues until practically all the As_2O_5 has been precipitated as CaHAsO_4 . This, however, takes place readily only if the carbonate is in a fine state of division, and hardly at all if it is in pea-sized lumps. Calcium carbonate is not alkaline enough to carry the conversion to the tricalcium arsenate stage. This dicalcium arsenate is fairly crystalline and granular, and, owing to its solubility and other physical properties, is not well suited for use as a spray. It could, of course, be mixed with excess lime, but, owing to its granular nature, reaction would be slow and when sprayed the lime might be completely carbonated before some of the crystals were changed, thus giving a chance for injury by the soluble arsenic. All things considered, it appears that there is no advantage in attempting to substitute limestone for lime.

SUMMARY.

The most desirable procedure for making calcium arsenate from lime and arsenic acid may be summarized as follows:

1. Use a good grade of lime, containing a high percentage of CaO .
2. Slake the lime to as smooth a paste as possible, for upon this depends the smoothness of the final product, as well as the readiness with which the lime and acid react. Use from 3 to $3\frac{1}{2}$ times as much water, by weight, as lime, and have it, preferably, warm. Let stand for a while, then thoroughly mix, after which add twice as much hot water as used for slaking, and mix again.
3. The lime and arsenic should be in such proportion that the weight of actual CaO used will equal that of the As_2O_5 used. This gives a product with a molecular ratio slightly over 4, which is necessary if the soluble As_2O_5 is to be kept down to desirable limits.
4. Add the acid at room temperature to the lime as quickly as possible, and stir well until the liquid becomes alkaline to phenolphthalein.
5. Filter to as dry a state as possible, do not wash, and if a dry product is desired dry directly in any suitable manner.
6. Crush in a suitable disintegrator, or grind if necessary.

To produce 100 pounds of a commercial grade of calcium arsenate by this process will require 45 pounds of CaO (approximately 50 pounds of a high-grade lime) to be slaked with 18 gallons of water, the addition of 36 gallons more of water, and then 45 gallons of a solution containing 1 pound of As_2O_5 per gallon. Slight departure from the figures given for water will probably have little effect.

LABELING THE PRODUCT.

A product prepared in accordance with the procedure outlined is, of course, not pure calcium arsenate, but consists of tricalcium arsenate, probably with some water of crystallization, together with excess of other calcium compounds, such as calcium hydroxid and calcium carbonate. The product, therefore, should not be designated simply "Calcium Arsenate," but by some such designation as, "Calcium Arsenate Containing other Calcium Compounds." In labeling such a product, the following is suggested by the Insecticide and Fungicide Board of this Department as the simplest form of statement which will fulfill the requirements of section 8 of the Insecticide Act of 1910, relative to the statement of active and inert ingredients and total and water-soluble arsenic.

Active ingredient:		
Tricalcium arsenate	—	%
Inert ingredients	—	%
Total arsenic (as metallic)	—	%
Arsonic in water-soluble forms (as metallic)	—	%