UNIVERSITY OF ALBERTA

0 0003 13870 79

EX LIBRIS
UNIVERSITATIS
ALBERTAENSIS

Digitized by the Internet Archive
in 2018 with funding from
University of Alberta Libraries

McGRAW-HILL PUBLICATIONS IN THE
AGRICULTURAL AND BOTANICAL SCIENCES
EDMUND W. SINNOTT, CONSULTING EDITOR

MILK AND MILK PRODUCTS

SELECTED TITLES FROM
**McGRAW-HILL PUBLICATIONS IN THE
 AGRICULTURAL AND BOTANICAL SCIENCES**

EDMUND W. SINNOTT, *Consulting Editor*

-
<i>Adams</i> —Farm Management	<i>Hayes and Garber</i> —Crop Plants
<i>Babcock and Clausen</i> —Genetics	<i>Heald</i> —Manual of Plant Diseases
<i>Belling</i> —The Use of the Microscope	<i>Hill, Overholts and Popp</i> —Botany
<i>Boyle</i> —Marketing of Agricultural Products	<i>Hutcheson, Wolfe and Kipps</i> —Field Crops
<i>Boysen Jensen</i> —Growth Hormones in Plants	<i>Lutman</i> —Microbiology
<i>Braun-Blanquet and Fuller and Conrad</i> —Plant Sociology	<i>Maximov</i> —Plant Physiology
<i>Brown</i> —Cotton	<i>Miller</i> —Plant Physiology
<i>Cruess</i> —Commercial Fruit and Vegetable Products	<i>Pool</i> —Flowers and Plants
<i>Curtis</i> —The Translocation of Solutes in Plants	<i>Rice</i> —Breeding Farm Animals
<i>Eames</i> —Morphology of Vascular Plants	<i>Seifriz</i> —Protoplasm
<i>Eames and MacDaniels</i> —Plant Anatomy	<i>Sharp</i> —Cytology
<i>Eckles, Combs and Macy</i> —Milk and Milk Products	<i>Sinnott</i> —Botany
<i>Fawcett</i> —Citrus Diseases	<i>Sinnott and Dunn</i> —Genetics
<i>Fitzpatrick</i> —The Lower Fungi	<i>Smith</i> —Fresh-water Algae
<i>Gardner, Bradford and Hooker</i> —Orcharding	<i>Swingle</i> —Systematic Botany
Fruit Production	<i>Thompson</i> —Vegetable Crops
<i>Gäumann and Dodge</i> —Comparative Morphology of Fungi	<i>Waite</i> —Poultry Science
	<i>Weaver</i> —Root Development of Field Crops
	<i>Weaver and Bruner</i> —Root Development of Vegetable Crops
	<i>Weaver and Clements</i> —Plant Ecology
	<i>Wodehouse</i> —Pollen Grains

MILK AND MILK PRODUCTS

PREPARED FOR THE USE OF
AGRICULTURAL COLLEGE STUDENTS

BY

CLARENCE HENRY ECKLES, D. Sc.

Late Chief, Division of Dairy Husbandry, University of Minnesota

WILLES BARNES COMBS, M. A.

Professor of Dairy Husbandry, University of Minnesota

HAROLD MACY, PH. D.

Professor of Dairy Bacteriology, University of Minnesota

SECOND EDITION

McGRAW-HILL BOOK COMPANY, INC.

NEW YORK AND LONDON

1936

COPYRIGHT, 1929, 1936, BY THE
MCGRAW-HILL BOOK COMPANY, INC.

PRINTED IN THE UNITED STATES OF AMERICA

*All rights reserved. This book, or
parts thereof, may not be reproduced
in any form without permission of
the publishers.*

THE MAPLE PRESS COMPANY, YORK, PA.

PREFACE TO THE SECOND EDITION

The senior author, Doctor C. H. Eckles, passed away on February 13, 1933. The dairy industry and particularly dairy research and education suffered an irreparable loss in his untimely death. We, his intimate associates, have missed his wise counsel and valued friendship. It is our aim to carry on the fine traditions and standards of a splendid character.

Since the appearance of the first edition of this text, there have been certain changes and developments in the dairy industry and advances in our knowledge of the fundamental facts concerning milk and its products. We have attempted to include the more significant items in this revision. The suggestions made by many colleagues, especially Professors C. L. Roadhouse, A. C. Ragsdale, C. A. Iverson, E. V. Ellington, L. M. Thurston, and E. O. Anderson, are gratefully acknowledged. We wish also to thank those publishers, manufacturers, and dairy-plant operators who have so graciously permitted us to use certain portions of their publications and many of their photographs illustrating modern improvements in dairy science and practice.

W. B. COMBS.

H. MACY.

ST. PAUL, MINNESOTA
September, 1936.

PREFACE TO THE FIRST EDITION

In most colleges of agriculture an introductory course in dairying is given to students during the first or second year. One of the difficulties experienced in planning the subject matter for a beginning course of this kind is the fact that few of the students in agriculture have planned their line of specialization at the time they are enrolled in it. The instructor realizes that within the group are some that will later become dairy specialists, while for many it is the only course dealing with the dairy industry that they will take. The selection of subject matter would be much easier if these groups were segregated. As it is, the course usually offered is something of a compromise between presenting the fundamentals of the subject and giving a general course conceived to be of the greatest value to students expected to engage in farming operations.

Considerable variation exists in different colleges as to the subject matter selected. Some undertake to cover the entire field of dairying in the form of a survey course including milk production, the nature of milk, and the manufacture of dairy products. The larger number, including ourselves, find the results more satisfactory when a portion of the field is covered more thoroughly.

The material included in "Milk and Milk Products" is the result of considerable experience by the authors with a course of this kind. In the past we have presented the subject matter by a combination of lectures, textbook assignments, and library references.

The need has been felt for a text of college grade in which some knowledge of chemistry on the part of the students is assumed. Most of the students enrolled in an introductory course in dairying have had some elementary chemistry either in high school or college, but the majority have not had elementary bacteriology. For this reason a brief account is given of the nature and activities of bacteria and other microörganisms important in dairying.

We have found it advisable to dwell rather intensively on the composition and properties of milk and the factors which influence

these characteristics. In this connection a discussion of the microbiology of milk is presented because of the important relationship of microorganisms to changes in the composition and properties of milk and its products. When these fundamental facts have been presented, it is possible to point out the bearing which they have upon the various milk products and the processes which are involved in their manufacture. Such an understanding of the fundamental nature of milk, and the forces which are active in its alteration or processing for the preparation of milk products, is essential if one is to gain an insight into the true nature of the phenomena involved in the modern methods of dairying.

Students, as well as those engaged in dairying in a commercial way, seem to experience special difficulties in solving certain practical problems with which they are confronted which involve the application of simple mathematics. Experience has taught the practical importance of using material of the type presented in the chapter entitled "Dairy Arithmetic." Each problem introduced represents a type confronted in practical dairy operations.

In view of the fact that many students take but one course in dairying, emphasis is also placed upon the sanitary production of milk and the value of dairy products in the human diet.

In the preparation of the manuscript the authors naturally contributed those portions which come within the field of their specialization. The whole has been combined and revised by them until no differentiation of authorship is made concerning any particular portion.

The authors wish to acknowledge their indebtedness to Dr. Lloyd M. Thurston, a former colleague, who assisted in the preparation of portions of the material, especially Chapters VII and VIII.

THE AUTHORS.

ST. PAUL, MINNESOTA
September, 1929.

CONTENTS

	PAGE
PREFACE TO THE SECOND EDITION	V
PREFACE TO THE FIRST EDITION	vii

CHAPTER I

INTRODUCTION	1
Early use of dairy products—Dairy products in the diet—Permanency of the dairy industry—Dairy conditions previous to 1850—Changes since 1850—Present extent of the dairy industry—Market milk—Butter manufacture—By-products from butter making—Cheese making—Ice cream—Condensed and dry milk—Other uses—Losses in handling	

CHAPTER II

THE CONSTITUENTS OF MILK	14
General characteristics of milk—Chemical composition—Water in milk—Fat in milk—Structure and nature of fat in milk—Size of fat globules, importance—Composition of milk fat—Volatile and non-volatile groups—Properties of butterfat—Factors influencing the composition of fat—Proteins of milk—Casein—Albumin—Lactalbumin—Other proteins—Lactose—Action of bacteria on lactose—Lactose in dairy manufactures—Ash or mineral matter—Uses of mineral matter—Minor constituents of milk—Phospholipids—Cholesterol—Enzymes of milk—Vitamins—Gases—Non-protein nitrogenous substances	

CHAPTER III

FACTORS INFLUENCING THE COMPOSITION OF MILK	38
Importance of variations—Nature of variations—Species of animal—Breed—Stage of lactation—Individual variations—Seasonal variations—Variations, milking to milking—Interval between milkings—First and last milk—Fatness of cow—Feed of cow—Effect of feed upon milk—Miscellaneous	

CHAPTER IV

PROPERTIES OF MILK	57
Physical state of milk—Chemical reaction—Specific gravity—Taste and odor—Color of milk—Freezing point—Effect of freezing on milk—Specific heat—Boiling point—Effect of heat on milk—Viscosity of milk—Adhesiveness—Effects of enzymes on milk—Effect of acids on milk	

CHAPTER V

MILK AND DAIRY PRODUCTS AS FOOD 69

Food requirements—Water—Carbohydrates and fats—Proteins—Minerals or ash—Food accessories, vitamins—Requirements of a suitable food—Economy of milk as a food—Milk as a source of protein—Milk as a source of energy—Relation of richness of milk to food value—Milk for the child and adult—Food value of other dairy products—Butter—Cheese—Ice cream—Concentrated milks—Skim milk and buttermilk—Fermented milk

CHAPTER VI

MICROÖRGANISMS 84

Bacteria—Yeasts—Molds—Naming of microörganisms—The growth of microörganisms—Food supply—Moisture—Atmosphere—Chemical and physical environment—Preservatives—Light and electricity—Thunder storms and the souring of milk—Concentration of medium—Temperature—Products of growth—Enzymes—Decomposition products—Pigments, toxins—Methods of counting microörganisms—Sources of the microörganisms in milk, udder, exterior of cow's body, air and utensils, milker or handler—Fermentations of milk—The "germicide" period—Period of souring—Neutralization period—General decomposition—Specific fermentations of milk—Souring—Souring and gassiness—Aroma and flavor—Proteolysis—Alkali production—Ropiness—Sweet curdling—Butyric acid fermentation—Bitter flavor—Alcoholic color—Miscellaneous fermentations—Transmission of disease through milk—Determining the wholesomeness of milk

CHAPTER VII

THE BABCOCK TEST FOR DETERMINING FAT IN MILK AND CREAM. . . 113

Historical—General procedure—Principles of the test—Testing whole milk, measuring the sample, adding the acid, centrifuging, reading the test—Defective tests—Testing cream—Variations from milk procedure, why cream samples are weighed, elimination of meniscus, size of samples taken, procedure—Approximate method for cream testing—Details of test bottles and balances, the milk bottle, the cream bottle, the cream balance—Testing skim milk, buttermilk, and whey—Centrifuges

CHAPTER VIII

COMMON DAIRY PROCESSES 132

Cream Separation—Historical—Basic principle of separation—Gravity creaming—Shallow-pan, deep setting, water-dilution method—Centrifugal creaming—Early developments—Introduction into United States—Principle of centrifugal separation—Construction of a centrifugal separator—Control of richness of cream—Factors governing fat percentage, speed, temperature, richness of milk, rate of inflow, flushing—Slime—Extent of vari-

ations under practical conditions—Efficiency of the separator—Factory separator—Effect of separation upon microorganisms—Straining, filtration, and clarification of milk—Pasteurization of milk—Relation to microorganisms—Methods of pasteurization, the holding system, the flash system—Construction of holding pasteurizers—Construction of flash pasteurizers—Cooling milk or cream—In-the-bottle pasteurization—Electrical pasteurization—Homogenization of milk—Construction of the homogenizer—Use of the homogenizer—Emulsification

CHAPTER IX

MARKET MILK.	180
Stages of development—Complexity of the problem—Necessity for public supervision—Production of market milk, clean, healthy cows, proper construction of barns, small topped pail, clean, healthy people, clean, sterilized utensils, the milking machine and separator, prompt cooling, prompt delivery—Certified milk—Transportation of milk—Delivery of milk—Purchase of milk—The milk plant—Problems of the distributor—Health control of milk supplies—Control measures, supervision in the small town, supervision in the large city—Pasteurization as a health-control measure—Grades of milk	

CHAPTER X

THE MANUFACTURE OF DAIRY PRODUCTS—BUTTER.	201
Historical—Effect of the cream separator—Status of farm butter—Composition of butter—Processes involved—Separation of milk—Cream for butter making—Off-flavors in cream—Cream grades and grading—Neutralization of cream—Pasteurization of cream for butter making—Starters—Cream ripening—Butter color—Churning—Nature of churning—The churn—The combined churn and worker—Churning procedure—Factors influencing churning, temperature, composition of fat, influence of size of fat globules, acidity, viscosity of cream, richness of cream, fullness of churn, speed of churn—Fat losses in buttermilk—Difficult churning—Salting butter—Overrun in butter making—Working butter—Marketing butter—Market terms—Market grades—Butter defects—Farm butter making	

CHAPTER XI

THE MANUFACTURE OF DAIRY PRODUCTS—CHEESE.	238
Historical—Nature of cheese—Classification of cheese—Composition of cheese—Milk for cheese making—Manufacture of hard cheese—American Cheddar cheese, equipment required, process of manufacture, curing, forms, market grades, defects—Emmental or Swiss cheese—Roquefort cheese—Brick cheese—Soft cheeses, Limburger cheese, Camembert cheese, Cottage cheese, Cream cheese—Process cheese—Cheese spreads	

CHAPTER XII

THE MANUFACTURE OF DAIRY PRODUCTS—ICE CREAM.	261
Historical—Definition and classification—Ingredients used—	
Quality of dairy products—Sweeteners—Stabilizers—Flavoring	
materials—Preparation of the ice-cream mix—Calculation of the	
mix—A problem in calculating the mix—Pasteurization of the	
mix—Homogenizing the mix—Aging the mix—Freezing the ice	
cream—Bulk ice cream—Brick ice cream—Preparation of indi-	
vidual forms—Quality of ice cream—Ice-cream defects—Distribu-	
tion of ice cream—Ice-cream making in the home—Microbiology	
of ice cream	

CHAPTER XIII

THE MANUFACTURE OF DAIRY PRODUCTS—CONDENSED MILK, DRY	
MILK, MILK BY-PRODUCTS	281
History of condensed milk—Classification of condensed milk—	
Composition of condensed milk—Properties of condensed milk—	
Method of condensing milk—The vacuum pan—Standardization of	
condensed milk—Use of condensed milks—Defects in condensed	
milks—Dry milk, historical—Types of dry milk—Composition of	
dry milk—Properties of dry milk—Methods of manufacture, the	
spray process, the drum process, atmospheric-drum process,	
vacuum drum process—Use of dry milk—Malted milk—Defects	
in dry milk—Marketing of dried milk—Microbiology of condensed	
and dry milk—Milk by-products—Skim milk as a by-product, for	
animal feed, for human food, other uses—Buttermilk—Whey—	
Manufacture of casein—Milk sugar—Fermented milk beverages	

CHAPTER XIV

DAIRY ARITHMETIC	312
Calculations of interest to the producer, determining pounds of fat	
in milk, finding the true average fat percentage, setting the price	
of milk, determining the value of cream sold by the gallon, farm	
separation problems, determining the most profitable market—	
Selling milk or cream—Standardizing milk and cream—Calcula-	
tions pertaining to butter—Calculating the composition of the ice-	
cream mix	

CHAPTER XV

MISCELLANEOUS TESTS	328
Sampling milk and cream, how to take a sample, sampling frozen	
milk or cream, sampling churned milk or cream, sampling sour	
milk or cream, preserving the sample—The composite sample,	
equipment required, the sample container, taking the sample,	
preservatives for composite samples, composite cream samples,	
care of the composite sample—Modified Babcock tests, testing	
butter, cheese, testing ice cream, testing condensed milk, testing	
dry milk—The calibration of Babcock testing glassware—Roese-	
Gottlieb fat analysis—The determination of specific gravity—	

CONTENTS

xiii

PAGE

The lactometer—Calculation of total solids—The determination of acidity, use in dairy manufacturing, details of test—The sediment test—Analyses of butter at factory, sampling, moisture and salt determinations, Kohman method—Detection of added water by freezing point determination—Total solids determination—Marschall rennet test—Methylene blue test for milk quality—Alcohol test—Fermentation test—Tests for heated milk—Storch test—Arnold or Guaiac test—Test to distinguish oleomargarine from butter.

APPENDIX 361

Outline of methods for bacteriological analysis of milk—Roesse-Gottlieb method for fat determination (Official A.O.A.C.)—Babcock method for fat determination (Official A.O.A.C.)—Score card for sanitary inspection of dairy farms—Specific gravity and weight per gallon of milk and cream—Conversion table of standard weights and measures—Table for calculating total solids in milk from specific gravity and fat percentage—Conversion table Fahrenheit to Centigrade—Molecular weights of acids, bases, and salts and quantities necessary for tenth-normal solutions

INDEX. 373

MILK AND MILK PRODUCTS

CHAPTER I

INTRODUCTION

The oldest written records of the human race are in Sanskrit and are preserved in India. At the time these records began, about 6,000 years ago, milk had already become an important article of food. In fact, so important was the cow to these early peoples of Central Asia that wealth was measured in numbers of cattle, and the cow was in time made a sacred animal and is still so considered by a part of the population of India.

Still earlier men, who are known only by such remains as are found, must have hunted cattle as wild animals. According to the best authorities, the domestication of cattle occurred somewhere between 6,000 and 10,000 years ago, where and by whom is uncertain. The cow was worshipped in Babylonia, and in Egypt about 2,000 B. C. Hathor, the goddess who watched over the fertility of the land, was depicted as a cow. Over fifty references to cows and milk are found in the Old Testament and the promised land was described as "a land flowing with milk and honey."

Early Use of Dairy Products.—From these early days to the present, the cow has continued to be the constant companion of man and her importance as a source of food has not been diminished by the thousands of years which have passed. The soldiers of Jenghiz Khan, the Mongol emperor who conquered Asia and a large part of Europe in the thirteenth century, carried dried milk as a part of their ration. Cheese was an important part of the food carried by the Vikings in their voyages which carried them to the shores of all northern Europe and even across the Atlantic.

The first settlers in the new world made the mistake of not taking cattle with them. For example, the *Mayflower* did not bring cattle and as a result of the lack of suitable food, especially

FIG. 1.—A dairy scene about 3500 B.C. A pane found at Al 'Ubaid (a small town near Ur of the Chaldees) by the joint expedition of the British Museum and the Museum of the University of Pennsylvania. Note the milk containers, the strainers, and the method of milking. (Courtesy of the Museum of the University of Pennsylvania.)

milk, the death rate, particularly of children, was very high. In fact, nearly one-half of those who came in the *Mayflower* died the first winter, including every child under two years of age. Their mistake was recognized and, later, the governor ordered that one cow and two goats should be brought over for each six people. Later pioneers remembered the lesson. As they pushed the frontier towards the West, the immigrant wagon was always followed by two or three cows. For the past century, there has been in the United States approximately one cow to each family.

Dairy Products in the Diet.—Milk has long been an important part of the human diet and there is evidence that the proportion

FIG. 2.—Increase in per capita milk consumption in the United States. An increase in milk consumption of 33 per cent from 1917 to 1930 is significant both from the standpoint of the milk producers and public health. (Chart based on statistics of the United States Department of Agriculture previous to 1930.)

of the diet coming from milk and dairy products is increasing in America. At the present time about 20 per cent of the total food is estimated to come from this source. Figure 2 shows the per capita increase in milk consumption in recent years.

The per capita consumption of fluid milk at the present time is approximately 40 gallons per year. The use of butter per person reached a maximum of 19.9 pounds in 1899, decreased greatly during the world war to 14 pounds but has since been increasing again, although it is still below the level of 1899. Cheese consumption has fluctuated from 2.1 pounds per capita in 1889 to 4.7 pounds in 1930. The use of cheese in the United States is far below that of European countries where the consumption ranges from 8 to more than 20 pounds per capita. Cheese and meat are largely interchangeable in the diet. When the economic conditions are such that meat can be used freely, the cheese consumption is usually limited. This has been the

condition in the United States where meat consumption has been high compared with that of Europe. If future economic conditions in the United States are such as to decrease the use of meat, it is safe to predict that cheese consumption will increase decidedly.

In recent years there has been a greater use of condensed milk, dry milk, and ice cream, which has materially added to the milk actually used in the human diet.

Permanency of the Dairy Industry.—Although predicting the future is often a questionable procedure, it is important to consider the probabilities of the dairy industry remaining, as it is now one of the main contributors to the income of the farmer and one of the chief sources of food for mankind. A study of the question leads to but one conclusion—that every indication points towards the permanency of the industry. There are three reasons for this belief: (1) historical, (2) physiological, and (3) economic.

The fact that milk and dairy products have been important articles of food for over 6,000 years with the evident tendency for a larger per capita consumption year by year is a valid reason for believing that the use of these products will continue.

Scientific investigation in the field of nutrition has within the past two decades made clear the fundamental reasons why milk is an essential part of the diet under conditions of modern civilization. Without milk the human diet would be so lacking in certain essential factors, particularly vitamins, calcium, and proteins of the necessary quality, that civilization as now developed could not exist. Man's only recourse would be to return to the dietary habits of primitive mankind and depend upon the glands and organs of animals and large quantities of green vegetation to supply the deficiencies which would otherwise exist in his food.

The third reason for confidence that the dairy industry will continue to have a place in the future is the economic factor. The cow is a more efficient producer of human food than any other animal. In any system of farming, a large amount of forage and coarse feed of various kinds is available—often as by-products of grain growing or as the result of a necessary crop rotation. Man cannot use these substances as food, but the cow, by means of her digestive system, suited especially to handling feeds containing crude fiber, can, from these coarse

products, produce milk and meat, both suitable for the stomach of man.

Another of the economic reasons why the cow finds a permanent place in agriculture is her relation to soil fertility. One of the difficult, if not impossible, tasks of a system of agriculture which does not include livestock as part of the enterprise is that of maintaining the soil fertility. For example, exclusive grain growing has been found to result, sooner or later, in lowered yields due to the constant removal of the elements of fertility in the crop. Agricultural experience for generations has indicated that the maintenance of soil fertility is comparatively easy when livestock is a leading part of the system of farming.

Compared to other common types of farming, dairy farming also requires less acreage, which fact becomes decidedly important when the price of land becomes high. The production and sale of dairy products also offer a constant source of income to the farmer. For the reasons given, dairying has taken an important position in permanent systems of agriculture as developed in Europe and America and promises so to continue. It is clearly to the advantage of the consumer to have milk and dairy products available as part of the ration and of the farmer to produce them.

Dairy Conditions Previous to 1850.—For over 225 years, following the first settlements in America, very little change took place in the methods of producing milk or the manufacture of dairy products. Each family depended upon its own cows for the family milk supply. Cows were hardly expected to give milk in winter. Nearly all the cows freshened in the spring and early summer, and an abundance of milk was available as long as the pasture was good. The cows usually dried up in the fall due chiefly to lack of feed. Oftentimes cattle became so weak from lack of feed during the winter that they had to be helped to their feet and sometimes they actually starved to death. The death rate among children was very high, due to numerous causes, one of which was a shortage of milk during the winter season. During the summer, butter and cheese were made generally on those farms having several cows in milk. The market prices for these products during the summer seasons, if any market were available at all, were ridiculously low, while in winter fresh butter was not on the market at any price. The surplus butter made in summer was packed largely in firkins and covered with brine. It was stored in cellars or spring houses

and constituted the chief butter supply for winter use. People were accustomed to using butter with a more or less rancid and old flavor and the product sold for table use 75 years ago would be rejected entirely at present on the market except for industrial uses.

Cheese was far superior in quality to the butter as it is far easier to keep under the primitive conditions of storage. Much of the cheese, homemade though it was, really represented a grade equal to that now on the market. Between 1830 and 1850 certain farming sections in Vermont and New York began to develop as centers of production for surplus butter and cheese which was sold in the cities.

In the earlier days the only source of milk supply was the family cow; later, as the cities became centers of considerable population, the keeping of cows presented some difficulties. Farmers within easy driving distance began delivering milk over regular routes. Previous to 1850, however, most milk was necessarily produced within a few miles of where it was consumed on account of the lack of suitable means of transportation.

Changes in Dairy Conditions since 1850.—The middle of the nineteenth century is a convenient point to set as marking the beginning of modern dairying. More changes have been made during the 80 years that have passed since that date than in all the previous 60 to 100 centuries since cattle were domesticated.

The period since 1850 has witnessed an astonishing development in mechanical lines. The machine has, to a large extent, supplemented hand labor in all lines of industry. This movement is reflected in relation to the dairy industry by the invention of the cream separator, artificial refrigeration, the milking machine, the combined churn and worker, and the exceedingly complicated and efficient machinery of the modern dairy plant.

Another factor of tremendous significance in the development of civilization since 1850 is scientific investigation. The dairy industry has received its share of the contributions from this source. It is not too much to say that science, especially through the agency of the agricultural colleges and experiment stations, has revolutionized the dairy industry. Scientific study of feeding and breeding has made possible a tripling of the milk production per animal unit. Bacteriology has laid a foundation of knowledge upon which are built the methods to be followed

in producing and preparing milk for human food. Most fundamental of all has been the great amount of chemical study which has been made of milk and its products. Out of such studies, for example, have come the Babcock test and the important facts concerning the use of milk in the human diet.

Economic factors have also been involved. Prominent among these is the rapid growth of city population. The division of population between rural and urban in the census of 1850 was made on a basis different from that used in later years. For this reason the figures for 1880 are the earliest available comparable with those taken in the last census. In 1880, 71.4 per cent of the population was classed as rural and 28.6 as urban; by 1930 the percentage of rural had declined to 43.8, while the urban had increased to 56.2. In 1935, only 26 per cent of the population was actually on farms. On the average, in recent years, each farm supplies four families with dairy products.

The Factory System.—One of the outstanding developments since 1850 was the introduction of the factory system. In 1851, Williams, in New York, began the manufacture of cheese under the factory plan and within, relatively, few years the manufacture of cheese was transferred from a farm to a factory industry. The factory system was not applied to butter until 1871, and did not make such rapid progress in taking over the industry as in the case with cheese. Practically all the butter and cheese now on the general markets however, are of factory origin.

Milk Transportation.—In 1850, the regular shipment of milk by railroad was begun with the establishment of special milk trains. In recent years, further advances have been made in the way of the introduction of tank cars and trucks for milk transportation. By means of this equipment milk is shipped successfully for distances up to hundreds of miles.

Condensed and Dry Milk.—The early fifties saw an invention of great importance to dairying—that of a satisfactory process for condensing milk which was introduced by Gail Borden. At present, the product of about one and a third million cows is prepared in the form of condensed milk. In recent years the preparation of milk in a dry form is becoming of great economic importance.

The Cream Separator.—Among the many mechanical devices the invention of which profoundly affected dairying, the cream separator unquestionably stands first. It came into use about 1880. The use of this efficient machine today means a saving

each year in the United States alone of butter fat worth between \$150,000,000 and \$200,000,000.

The Babcock Test.—The Babcock method for the rapid determination of fat in milk and cream, first published in 1890, has been of almost inestimable value in factory operation and in making possible records of the production of individual cows.

Artificial Refrigeration.—Artificial refrigeration, which began to come into practical use between 1880 and 1890, has had a far-reaching effect upon markets and prices. Without the use of this system the modern dairy industry would be helpless, and could not long exist in anything like its present magnitude.

Scientific Discoveries in Bacteriology and Nutrition.—Scientific discoveries in the fields of bacteriology and nutrition have within recent years resulted in far-reaching developments, especially in connection with the use of milk for human food. Upon the findings of the science of bacteriology have been built the regulations for the supervision of milk supplies for cities as well as the modern methods of sanitary milk production. The remarkable increase in the use of milk as food is the result of having a safe supply available, and a dissemination of the facts concerning the value of milk in the human dietary.

Improved Livestock.—While a few improved cattle had been brought to the United States prior to 1850, the number was so

FIG. 3.—Dairy cows in the United States per 1,000 population. In 1840 there was one cow for 3.3 people, in 1929 one to five. An astounding increase in the use of milk has occurred while the number of cows in proportion to the population has decreased.

small and public interest in them so slight that no appreciable effect was noticeable upon the cattle population of the country. Between 1860 and 1885 the foundation stock was imported from which is descended most of our present dairy stock. As the result of better breeding and feeding, the average production of

the dairy cows in typical dairy herds of the United States is now more than double that of 1850.

Present Extent of the Dairy Industry.—The factors mentioned in outline are together chiefly responsible for the present magnitude of the dairy industry in the United States. Milk and dairy products rank as the largest single source of income to the American farmer. At present, about 23 per cent of the total agricultural income is from milk and an additional 3 per cent from dairy animals sold for meat, a total of 26 per cent of the total income to agriculture. Due to the combination of increased production and higher price, the total farm value of dairy products has increased enormously within 25 years and exceeded \$2,000,000,000 for 1935.

The total number of dairy cows in use in the United States is approximately 26,000,000. The number per 1,000 population is actually slightly lower than in 1850. At the same time, the consumption of milk has greatly increased—just how much can not be determined, although the statistics compiled by the U. S. Department of Agriculture show an increase of 33 per cent in milk consumption from 1917 to 1934. The greatly increased consumption of milk and the stationary ratio of cows to population show unmistakably that a considerable increase has taken place in the average production per cow. In fact, the average production per cow appears to be more than triple that of 1850. It is estimated that approximately 1,250,000 persons are employed in caring for these cows and in the various manufacturing and distributing activities which result.

The total amount of milk produced annually in the United States is about 100,000,000,000 pounds. No one can visualize this figure as a whole. If the milk produced in this country in a single year was placed in tank cars, each of which would hold 56,000 pounds of milk, it would require 35,714 trains of 50 cars each. A single day's production would require 98 such trains. The chief uses to which this enormous amount of milk is put are shown in Figs. 5 and 6.

FIG. 4.—Average yearly milk production per cow. The results of improved breeding and feeding practices are evident in an increase in the average milk production per cow since 1910.

Market Milk.—The largest fraction of the total milk produced is required to meet the demands for milk used in the household. For this purpose 40 to 45 per cent of the whole is needed. As already pointed out, the consumption of milk has shown a decided increase within recent years, in fact 33 per cent from 1917 to 1934. In a later chapter, further details are given regarding the means by which the great cities are now supplied

FIG. 5.—There are about 100,000,000,000 pounds of milk produced in the United States annually. This milk is sold in the form of market milk, cream, and several manufactured products.

with safe, wholesome milk, some of which may be shipped several hundred miles. The process of pasteurization and the use of mechanical refrigeration, together with the use of methods based upon an understanding of the sanitary and scientific questions involved have made this possible.

Butter Manufacture.—The second largest portion of the total milk produced is used for the manufacture of butter. Close to 35 per cent of the total milk production of 100,000,000,000 pounds is used in the butter industry. From this are produced between 1,500,000,000 and 2,000,000,000 pounds of factory-made or creamery butter. About 600,000,000 pounds of butter are made on farms. The production of high-quality butter made in the factory is constantly increasing. Practically

all of the surplus butter, that which appears on the general markets, is a factory product. The butter produced in the United States almost exactly equals the demand. Small imports are sometimes made and this is offset, as a rule, by approximately equal exports.

By-products from Butter Making.—From this enormous amount of butter, skim milk and buttermilk are available as by-products. The skim milk amounts to about 18 pounds for each pound of butter, a total of 50,000,000,000 pounds.

FIG. 6.—How milk is used. The total milk produced in the United States exceeds 100,000,000,000 pounds yearly. Nearly one-half is used in the household.

Of buttermilk, on the average, 1.7 pounds are available for each pound of butter made, resulting in an aggregate of over 4,000,000,000 pounds. The problem of using the by-products is a very important one. In the past, nearly all of these by-products have been fed to animals, but in recent years constantly increasing amounts are being used in the form of condensed and dried products. A discussion of these products appears in a later chapter.

Cheese Making.—The amount of milk used for cheese is small in comparison with that used for household purposes or for butter making. The percentage required for the cheese indus-

try is about 5.0 per cent of the whole. Until 1851, cheese was made exclusively on farms. In that year, the first cheese factory was established in New York. Following that date, the expansion of the cheese-factory system continued with a corresponding decrease in the amount of farm-made cheese until by 1880 it could be said that cheese making was no longer a farm industry. Many varieties of cheese are made in the United States, chiefly by following the processes of manufacture as originated in some locality in Europe. Among those made in the United States and placed on the market either under the European name or with the original name preceded by the word "American" are the Cheddar, Swiss, Limburger, Roquefort, Camembert, Primost, and others. The most common cheese found for sale in American stores is made by following, with more or less modification, the process as developed in England for making what is known as the Cheddar cheese. The practice of making process or pasteurized cheese sold under trade names has developed in the United States within recent years.

Ice Cream.—The ice-cream industry is of rather recent development. Although frozen products in which cream was the chief constituent have been made in the household for nearly 100 years, the extensive use of ice cream is a development of the past 35 years. In 1910, the average consumption per capita was 1.02 gallons. The use of ice cream steadily increased until 1929 when the per capita consumption reached 3 gallons. A decrease in consumption occurred during the years between 1930 and 1933, and consumption dropped slightly below 2 gallons per capita. Ice cream is now almost entirely a factory product and for efficiency in manufacture, expensive equipment and skilled operators are required. The total proportion of the milk supply used for ice cream is 2.6 per cent, or practically the same proportion used for calf feeding. This represents roughly the product of 750,000 cows.

Condensed Milk and Dry Milk.—The milk produced by about 1,000,000 cows, or 4.0 per cent of the total for the United States, is used for the preparation of concentrated milks. This amount is very nearly equal to that now used for cheese making. The condensing process was invented in 1856 by Gail Borden and became the basis of an important industry, as indicated by the figures given. More recently, the preparation of dry milk has become established as an important means of preserving

milk. Just how far it may supplant condensed milk is difficult to predict at the present time.

Use for Animal Feed.—A considerable amount of the total milk supply is used for calf feeding. According to Fig. 6 about 2.6 per cent is used for this purpose. In raising calves a certain amount of whole milk, averaging about 200 pounds per head, is necessary even when skim milk is later used or the calf is sold for veal.

Losses in Handling Milk.—The losses in handling milk are considerable, amounting on the average to about 3 per cent. These losses occur at every stage in handling from the dairy barn to the sales counter. Some milk adheres to the utensils used, some is accidentally spilled, or has to be discarded on account of some accident resulting in contamination.

CHAPTER II

THE CONSTITUENTS OF MILK

Milk as an article of food for mankind antedates the earliest recorded history. Its complex nature and unusual properties have baffled man since the time when he first became interested in the world about him. From the time when the Greeks theorized regarding the nature of milk and its origin to the present, it has been subjected to study by scientific minds of each generation. Most of the exact knowledge of the subject, however, is the product of the past 85 years. Undoubtedly, the future will show the present knowledge of the subject still to be very incomplete.

Milk may be defined as the normal secretion of the mammary glands of mammals. Nature designed milk as a food for the young. Mankind, thousands of years ago, learned the possibilities of milk and milk products as a food not only for the young but for adults. Accordingly, through selection and breeding, man has greatly increased the milk-producing functions of those animals best adapted as a source of milk for man, especially the cow and the goat. Other animals used as a source of milk for human food are the water buffalo, sheep, the camel, and, to a small extent, the mare and the llama. The milk of different species, although containing the same constituents in general, varies in composition and properties in minor ways. Although all the species mentioned are used as a source of milk by certain peoples, the cow supplies such a large proportion of the product used, especially in Europe and America, that little attention need be directed toward the product of other species. The term "milk" always will be understood as referring to the milk of the cow unless other species are mentioned specifically.

General Characteristics of Milk.—An intelligent observer, examining milk for the first time, would note the characteristics set forth below. Milk ranges in color from a bluish-white to an almost golden-yellow, depending upon the breed of cattle, the amount of fat and solids present, and, most of all, upon the nature

of the feed consumed by the cow. In large quantities, milk appears entirely opaque, while in thin layers it is somewhat transparent. Milk from which the fat has been removed or that is naturally very low in fat and other solids shows a bluish tint.

Milk has no pronounced taste but is slightly sweet to most persons. Any pronounced taste is abnormal. Freshly drawn milk has a characteristic, but not very pronounced, odor which is quite volatile and which practically disappears when the milk is exposed to the air. Other odors are abnormal and have their origin in sources discussed elsewhere.

If fresh milk is tested with litmus, the so-called "amphoteric reaction" will be found; that is, blue litmus turns red, and red litmus turns blue. When phenolphthalein is used as an indicator, normal fresh milk shows an acid reaction and if titrated with a standard alkali solution the acidity will be found to vary from 0.10 to 0.26 per cent calculated as lactic acid. Fresh milk has a hydrogen-ion concentration of approximately pH 6.5 which indicates that it is really somewhat on the acid side of neutrality.

Milk appears unchanged by heating until a point near the boiling point is reached, when a tough film forms on the surface. Prolonged boiling results in a brown shade of color and a change in the taste.

The addition of acids results in the formation of a precipitate which appears as a soft, white, jelly-like mass, known as "curd" with more or less separation of nearly clear fluid or "whey."

If examined under a compound microscope, immense numbers of glistening, spherical bodies of varying sizes will be seen in the milk. If tested in an appropriate manner, these would be found to be fat. When a portion of the fresh milk is allowed to stand undisturbed for a few hours, a layer forms on the surface—the well-known cream. It is due to the gathering of the fat globules in a portion of the milk. If the milk is allowed to remain at ordinary temperatures (60 to 70°F.) (15.6–21.1°C.) for 24 hours or longer, usually it will have a pronounced acid taste and, sooner or later, will coagulate as a soft, jelly-like mass.

Chemical Composition.—It is important that the student first become familiar with the chief components of milk, leaving until later a consideration of those which are present in small quantities, even though they may be of importance.

A chemist might describe milk as, essentially, an emulsion of fat in a watery solution of sugar and mineral salts, and with protein in a colloidal suspension. If asked to analyze an average sample of milk and determine the chief constituents, a chemist would report approximately as follows:

	Percentage
Water.....	87.25
Dry matter.....	12.75
Fat.....	3.80
Protein.....	3.50
Sugar.....	4.80
Ash.....	0.65
Total.....	100.00

There are certain terms used in connection with the above constituents when referring to them singly and in groups. "Milk fat" or "butter fat" refers to the fat of milk. The protein, sugar, and ash or salts of milk are termed "milk solids-not-fat" or "solids-not-fat." Those in dairy work often refer to this group of solids as the "serum solids" of milk. The dry matter is commonly designated as "total solids."

Water of Milk.—In average milk, about 87 in each 100 pounds is water. This water is not different from ordinary water and serves to hold in solution the soluble constituents of the milk. The percentage of water varies from 84.0 to 89.0 per cent although, occasionally, an individual sample of authentic milk may exceed these limits. Any variation in the amount of other constituents is also reflected upon the water percentage. The fluid nature and the high water percentages, as given above, often lead to an erroneous conception of the food value of milk. The facts are that many other articles of food, including radishes, carrots, and pumpkins, contain even more water than milk, while apples and potatoes rank but little above the richer milk samples in this respect. Among cattle feeds, fresh grass and root crops have less dry matter than milk, and some silages but little more.

FAT OF MILK

Milk fat, often called butter fat, is, commercially, the most valuable constituent of milk. It is also of great importance from the standpoint of the food value of the milk. The agreeable flavor of rich milk, and to a large extent of other dairy products, is largely due to the milk fat. If all the milk produced in the

United States could be brought together it would contain about 3.8 pounds of fat to the hundredweight. To give 3.8 as the average percentage, however, is misleading, so far as many localities are concerned, because of the preponderance of certain breeds of cattle in some localities. In the South, for example, where the Jersey is widely used, average milk would show a fat percentage of at least 4.5 and possibly even 5.0, while in those localities in the Northern states where Holsteins are generally used, the average percentage would be nearer 3.5. The fat percentage will seldom be less than 2.5 or more than 6.0, although occasionally milk from a single animal will exceed these limits.

The cream separator concentrates the milk fat into a small portion of the milk and the product is then known as "cream." Normally, cream for table use contains from 20 to 25 per cent of milk fat. Ordinary whipping cream contains from 30 to 40 per cent of fat. Cream containing from 65 to 80 per cent of milk fat has been termed "plastic cream." When cream is churned the milk fat is gathered in a concentrated mass, and after working, it is known as "butter." Butter is, therefore, a concentrated substance, containing from 80 to 85 per cent of milk fat. Practically all of the dairy products, with the exception of those made from skim milk, contain an appreciable amount of milk fat. Cheddar cheese contains from 30 to 40 per cent of this constituent and its rich, mellow flavor is very largely dependent upon the amount of milk fat present.

Ice cream varies in its milk fat content from 8 to 20 per cent. The quality of this product also is very closely associated with the milk fat it contains. Condensed milk and dry milk contain an average of about 8.0 and 27.0 per cent of milk fat, respectively. Butter oil, made by clarifying the pure fat from cream or butter, contains approximately 98 per cent of milk fat.

The Structure and Nature of the Fat of Milk.—Milk fat exists in milk in the form of minute globules in a true emulsion of the oil-in-water type, the fat globules being in the dispersed phase. The fat globules are invisible to the naked eye, but are seen readily under the low power of a microscope.

Early investigators advanced a theory that the fat globules of milk are surrounded by a membrane. No convincing evidence, however, was produced to support this view and, consequently, the membrane theory has been generally discarded. As a

result of the newer knowledge in the field of physical chemistry, the view in recent years has been that each globule of fat is surrounded by a very thin film of protein, or the serum of milk, condensed on the surface and held in place by surface attraction or adsorption. This concentration of the milk proteins around the fat globule is one factor assisting in maintaining the stability of the fat emulsion in milk. More recently, experimental evidence has been presented to indicate that the concentrated layer surrounding the fat globules is composed of certain protein- and fat-like substances, especially lecithin, a substance having many of the properties of fat, and found in milk in small quantities.

FIG. 7.—Fat globules in milk. Note the variation in size and the tendency to form clusters.

Size of the Fat Globules.—If a sample of milk is examined under a high-power microscope enormous numbers of fat globules will be seen. It will be observed that they vary widely in size, the largest having six or seven times as great a diameter as the smallest. Measurements will show that the average-sized globules have a diameter which would require about 10,000 placed side by side to extend 1 inch. It is estimated that a single drop of average milk will contain about 100,000,000 fat globules. It is impossible to conceive of the number of fat globules represented in 1 pound of butter. If a number of milk samples from different sources were examined, considerable difference would be found in the average size of the globules. Apparently there is some difference in this respect due to the

individuality of the animal producing the milk. The most consistent variations, however, are associated with the breed to which the cow belongs and to the stage of lactation.

Of these, the breed is the most important factor. It is possible, by a microscopic examination, to distinguish the milk from a Holstein or Ayrshire cow from that produced by a Guernsey or Jersey. Among the breeds commonly used in America for dairy purposes, the Jersey and Guernsey breeds produce the largest globules, the Holstein and Ayrshire stand at the other extreme, with other breeds intermediate.

During the first part of the lactation period, the fat globules are relatively large while as the lactation period progresses the globules become smaller. This fact has been offered as one explanation for difficult churning of cream which sometimes occurs under farm conditions, as it is known that milk possessing the smaller fat globules churns more slowly than milk containing large globules.

Practical Importance of the Size of the Fat Globule.—The size of the fat globule is of some practical importance in each of the following operations:

1. Separation of milk.
2. Churning of cream.
3. Shipping of milk or cream.
4. Cheese making.

Before the days of the centrifugal cream separator when gravity creaming of milk was practiced, the size of the fat globule was a matter of considerable importance because it was a factor in the loss of fat in the skim milk. Some difference can readily be observed in this respect by comparing the time required for the appearance of cream in the top of an ordinary milk bottle, using the product from different breeds. Since the introduction of the cream separator, the size of the fat globules has ceased to be a factor of importance in cream separation because the centrifugal force is so many times greater than the force of gravity that a difference in the size of the fat globules is of little importance, although careful tests usually will show a very small difference.

The size of the fat globules bears a definite, although not particularly important, relationship to the churning of cream. Cream with large fat globules churns with less agitation than that in which the smaller globules predominate. In this con-

nection it is well to recall the fact that the surface of spheres varies according to the square, and the volume according to the cube, of their diameters. A globule having twice the diameter of another has four times the surface and eight times the volume. The surface of the larger globule, as a result, is much less in proportion to the volume, and the surface tension which keeps the fat in the form of an emulsion is likewise easier to overcome by the agitation of churning.

The size of the fat globule is of some importance in connection with the handling and shipping of milk. Milk having large globules churns more readily, and after being transported some distance and passed through various apparatus may show some evidence of partial churning in the form of butter granules on the surface. The trouble is usually prevented by filling the can or other container completely to the lid, thus allowing no chance for agitation. In cheese making, the size of the fat globules is a matter worthy of consideration. When the milk contains large fat globules the cream comes to the surface of the milk in the cheese vat more quickly, and before the coagulation of the milk by the rennet has had time to check the movement of the fat and lock it within the coagulated casein. As a result, the loss of milk fat in the whey is somewhat larger. It has also been claimed that smaller fat globules are more readily digested than the larger, but little, if any, evidence is available to prove the correctness of such a statement.

Composition of Milk Fat.—Milk fat is not a single chemical compound but a variable mixture of several different glycerides. Each glyceride is the result of the union of glycerol and one or more organic acids. The organic acids contained in milk fat and fats from other sources other than milk fat are commonly termed "fatty acids." The common animal fats are relatively simple as compared with milk fat. Beef fat consists of the glycerides of palmitic, stearic, and oleic acids. Mutton tallow consists principally of the glyceride of stearic acid, while lard is primarily made up of the glyceride of oleic acid. Milk fat probably contains a larger number of the fatty acids than any other fat found in nature. It is, therefore, one of the most complex natural fats known to nature. It has been shown definitely that milk fat contains butyric, caproic, caprylic, capric, lauric, myristic, palmitic, stearic, and oleic acids. At least seven others have been reported by various workers, but

some doubt prevails as to whether all of these are actually present in normal milk fat.

The complexity of milk fat may be comprehended more readily when the chemical formulae for glycerol and the fatty acids are known. Glycerol is written $C_3H_5(OH)_3$ and butyric acid, for example, is written, C_3H_7COOH . When it is realized that glycerol combines with one or more of the fatty acids to form the glyceride of the fatty acid it may be seen that the chemical structure of milk fat is indeed exceedingly complex.

The composition of milk fat as reported by the workers of the Massachusetts Experiment Station, is indicated in the following statement:

FATTY ACIDS IN TWENTY-ONE SAMPLES OF BUTTER FAT FROM
MASSACHUSETTS COWS FED NORMAL RATIONS

Fatty acids	Chemical formula	Average, percentage	Range, percentage
Soluble acids:			
Butyric (a) ¹ (by difference)	C_3H_7COOH	2.932	2.41 to 4.230
Caproic (a) ¹	$C_6H_{11}COOH$	1.898	1.290 to 2.400
Caprylic (a) ¹	$C_7H_{15}COOH$	0.786	0.527 to 1.041
Capric (a) ¹	$C_9H_{19}COOH$	1.570	1.187 to 2.008
Total.....		7.186	6.470 to 8.601
Insoluble acids:			
Lauric.....	$C_{11}H_{23}COOH$	5.849	4.533 to 7.687
Myristic.....	$C_{13}H_{27}COOH$	19.784	15.554 to 22.618
Palmitic.....	$C_{15}H_{31}COOH$	15.167	5.782 to 22.863
Stearic.....	$C_{17}H_{35}COOH$	14.907	7.803 to 20.370
✓ Oleic.....	$C_{17}H_{33}COOH$	31.895	25.273 to 40.313
Total.....		87.602	86.145 to 88.471
Total fatty acids.....		94.788	94.746 to 94.980

¹ a = 20 samples analyzed.

The average analyses given by these workers conform in most instances with the reports of earlier investigators. The work of recent years has differed in that it has brought out the fact that milk fat can be expected to vary not only in the proportion of fatty acids but in those present.

The composition of milk fat as reported by Hilditch and Jones of the University of Liverpool will be of interest in this connection.

COMPOSITION OF NEW ZEALAND BUTTER, MARKET SAMPLES
As reported by Hilditch and Jones of the University of Liverpool

Fatty acid	Sample		
	A per cent	B per cent	C per cent
Butyric.....	3.4	3.1	3.2
Caproic.....	1.8	1.9	1.7
Caprylic.....	0.9	0.8	0.8
Capric.....	1.9	2.0	2.3
Lauric.....	3.1	3.9	4.3
Myristic.....	9.7	10.6	10.8
Palmitic.....	27.6	28.1	28.4
Stearic.....	12.2	8.5	9.4
Arachidic.....	0.7	1.0	0.5
Oleic.....	34.3	36.4	33.1
Linoleic.....	4.4	3.7	5.4

These workers report the presence of the nine fatty acids generally recognized in milk fat and, in addition, arachidic and linoleic acids.

Volatile and Non-volatile Groups.—It has been the common practice to divide the fatty acids of milk into two general groups, the volatile and the non-volatile. While these terms are not strictly accurate as applied to the fatty acids of milk fat, this grouping serves a useful purpose in indicating general properties. The volatile acids include butyric, caproic, caprylic, capric, lauric, and small quantities of others. Butyric, caprylic, and capric of this group are classed as soluble fatty acids. The non-volatile are myristic, palmitic, oleic, stearic, and small quantities of a few others. This group of fatty acids including lauric of the volatile group are classed as insoluble fatty acids.

The glycerides of the volatile group, butyrim, caprim, etc. make up about 17 per cent of the total in butter fat. It is this group of fats to which the characteristic flavors of butter and cream are generally attributed. Butyric acid is the most important acid found in this group. Butyric acid contributes to butter its characteristic taste and, on being liberated, is largely responsible for the rancid flavor which sometimes occurs in dairy products. Of the volatile fatty acids, butyric is the most variable. A slight decrease in the butyrim content of milk fat takes place as the lactation period progresses. Corn silage

is also known to produce an increase in the butyrin content of milk fat, while cottonseed meal has been shown to cause a decrease in the butyrin content.

The glycerides of the fatty acids found in the non-volatile group, myristin, palmitin, etc., constitute 82.7 per cent of milk fat. This group of fatty acids is particularly important because of their relation to the hardness or softness of milk fat and their ultimate relation to the texture of butter. The practical creamery man witnesses the influence of these fatty acids because of their effect on the temperature required for churning cream at various seasons of the year. In the spring months, there is a predominance of the fats possessing a low melting point which results in a soft butter and necessitates the churning of the cream at relatively lower temperature. During the winter months, when fewer of the fats of a low melting point are present, a higher churning temperature is therefore essential.

Oleic acid is the most variable of this group and, likewise, possesses the lowest melting point. It is, therefore, the chief acid influencing the hardness or softness of milk fat. It is known that the oleic acid content of milk fat increases when cows are permitted to graze on green grass, when fed linseed meal, cottonseed meal, and as the period of lactation progresses.

Though it is possible to classify the fatty acids into volatile and non-volatile groups and into soluble and non-soluble groups, neither of these classifications can be applied to the fats formed in the union of the fatty acids with glycerol. The fats are neither volatile nor soluble in water. When decomposed by bacteria or by chemical means, however, the fatty acids may be liberated, and their properties revealed. Rancidity of butter, for example, is said to be due to the breaking down of a triglyceride containing butyric acid and the liberation of butyric acid, which yields a rancid odor and taste.

Properties of Butter Fat.—Since butter fat is a mixture of fats, it cannot have a true melting point. By placing a disc of fat in alcohol and water and raising the temperature of the solution it will be observed that normal fat will melt and form a sphere at about 91.4°F. (33°C.). Variations can be expected from 84 to 96.8°F. (29 to 36°C.), depending upon the proportion of hard and soft fats present. Each fatty acid contained in butter fat possesses a different melting point, as will be noted in the following table, which presents, in addition to the melting

point, the boiling point and specific gravity of each of the fatty acids known to be contained in butter fat.

PROPERTIES OF THE FATTY ACIDS¹

Acid	Melting point		Boiling point		Specific gravity
	Degrees Fahrenheit	Degrees Centigrade	Degrees Fahrenheit	Degrees Centigrade	
Butyric.....	17.8	-7.9	326.3	163.5 at 760 millimeters	0.959 at 20/4°C.
Caproic.....	14.9	-9.5	395.6	202 at 760 millimeters	0.929 at 20/4°C.
Caprylic.....	60.8	16	459.5	237.5 at 760 millimeters	0.910 at 20/4°C.
Capric.....	87.8	31	515.1	268.4 at 760 millimeters	0.895 at 30°C.
Lauric.....	118.4	48	437.0	225 at 100 millimeters	0.883 at 20/4°C.
Myristic.....	136.4	58	482.9	250.5 at 100 millimeters	0.858 at 60/4°C.
Palmitic.....	147.2	64	419.0	215 at 15 millimeters	0.853 at 62/4°C.
Stearic.....	156.7	69.3	721.4	383 at 760 millimeters	0.847 at 69.3°C.
Oleic.....	57.2	14	546.8	286 at 100 millimeters	0.895 at 17.7/4°C.

¹ International Critical Tables, 1926.

Melting Point of Butter Fat.—The melting points of the fatty acids closely correlate with the melting points of the fats; however, butyric has a melting point of about -94°F. (-70°C.) and olein 41°F. (5°C.). The other fats of importance are as follows: myristin 129.2°F. (54°C.), palmitin 141.8°F. (61°C.), and stearin 149°F. (65°C.). Thus, it is seen that of the fats in butter fat the principal soft fats are butyric and olein, and the principal hard fats are myristin, palmitin, and stearin. The melting point of butter fat is influenced by its composition. An increase in the olein content of butter fat will result, therefore, in a lower melting point; likewise, will an increase in the butyric content. Should olein be decreased and palmitin or stearin be increased, the melting point would rise. Likewise, butter would vary in its firmness according to the proportion of the hard and soft fats present.

Closely associated with the melting point of butter fat is the solidifying point or the temperature at which it appears solid. The majority of the glycerides of the fatty acids of butter fat solidify at 50 to 53.6°F. (10-12°C.). The specific gravity of butter fat is generally considered to be about 0.9 at 140°F. (60°C.).

Other Properties of Butter Fat.—Butter fat is insoluble in water but it will absorb about 0.2 per cent of it. It is soluble in ether, carbon disulphide, nitro-benzene, and in acetone. It

is only slightly soluble in ethyl and amyl alcohol but a larger portion is soluble in hot amyl alcohol and hot glycerol.

In addition to the above properties, butter fat will absorb volatile odors very readily. Because of this property butter, milk, and cream should not be stored near the source of volatile odors which might contribute an off-flavor to these products. This fact is rather commonly known to practical men handling butter in creameries, warehouses, in transit, and in retail stores. The housewife who places butter in an ice box with fish or any food from which an odor is given off, may expect butter to absorb these odors very readily.

Factors Influencing the Composition of Butter Fat.—It has been stated that milk fat is a variable mixture of several different glycerides and that each glyceride is the result of the union of glycerol and one or more fatty acids. Attention has also been directed to the fact that the composition of milk fat varies. The principal fats which are known to vary are butyrim, olein, palmitin, and stearin. Variations in these fats are responsible for variations in the melting point of butter fat. The principal factors which have been demonstrated as being responsible for variations in the different fats of butter fat are breed of animal, stage of lactation, feed, and plane of nutrition.

Relation of Breed.—It has been demonstrated, experimentally, that the milk fat of the milk of Jerseys contains fat higher in the volatile acids than the milk fat of the milk of Holsteins, Ayrshires, or Shorthorns. The principal variation probably occurs in the butyrim content of the fat. The oleic acid content of fat produced by Holsteins and Shorthorns is noticeably higher than that from the Jersey, while in fat from the Ayrshire it is intermediate between these. The melting point of the fat produced by Holsteins and Ayrshires is, therefore, lower than that of Jerseys. Butter produced from the Jersey cream, under normal conditions, may be expected to be firmer than that produced from the cream from Holsteins or Ayrshires. In those localities in which Holsteins and Ayrshires predominate, the creameries use a relatively lower temperature in the churning of cream than in localities in which the Jersey predominates. There is every reason to believe that the fat produced by the Guernsey is very similar to that of the Jersey. Statements made in reference to one would doubtless apply to the other. The influence of the factors of feed and lactation, and feed in particular, however,

must be considered in certain localities as will be pointed out.

Not only is there a difference in the composition of the fat from animals of different breeds, but there is a noticeable difference between the individuals of the same breed even when receiving the same ration and when they are about in the same stage of lactation.

FIG. 8.—Relation of breed to relative size of fat globules in milk. It is possible to distinguish typical Jersey or Guernsey milk from Holstein or Ayrshire milk by microscopic examination.

Relation to Stage of Lactation.—The stage of the lactation period is probably one of the most important factors influencing the composition of milk fat. This statement is particularly true in reference to the influence of the stage of lactation on the volatile acids, principally butyric, of butter fat, which gradually decline from the beginning to the end of the lactation period. The oleic acid content is somewhat irregular at the beginning of the lactation period, but, after this period there is a slight but steady increase. The melting point remains almost constant after the first few weeks of the lactation period. Near the end of the lactation period it rises.

Relation to Feed.—One of the most interesting factors influencing the composition of milk fat is that of feed. Certainly its influence is more far-reaching than any of the factors mentioned. The influence of a few feeds as designated by various workers is indicated in the statement as shown on page 27.

As a general rule, feeds which cause an increase in the olein content of butter fat produce a soft fat of a low melting point. Cottonseed meal, however, is an exception. In the case of cottonseed meal, the increase in olein is counteracted by the decrease in butyrin which has a very much lower melting point than olein. It has been demonstrated that by feeding corn silage, which tends to increase the butyrin content of butter fat, the influence of cottonseed meal on the melting point of

Feed	Effect on butyrin	Effect on olein	Effect on melting point
Grass (pasture).....	No effect	Increase	Decrease
Corn silage.....	Increase	No effect	Decrease
Linseed meal.....	No effect	Increase	Decrease
Cottonseed meal.....	Decrease	Increase	Increase
Corn oil.....	Decrease	Increase	No effect
Velvet beans.....	Decrease	Increase	Increase
Malt sprouts.....		Decrease	
Buckwheat middlings.....	Increase	Decrease	
Wheat gluten.....	Increase	Decrease	
Oats.....		Decrease	
Molasses.....	Increase		Decrease
Beets.....	Increase	Decrease	

butter can be overcome. The feeds which result in a relatively higher olein content are those feeds rich in vegetable oils, such as linseed meal, soybean meal, and gluten feeds which are rich in fat. In addition, grass pasture brings about an increase in the olein content of butter fat. Feeds low in vegetable oils, and rich in carbohydrates, as a general rule, produce a butter fat of a relatively lower olein content and, consequently, a firmer fat. It must not be overlooked, however, that if a feed lowers the olein content and produces at the same time an increase in butyrin, the melting point of the butter fat may be affected in one or more ways. It is possible that it would be increased if the proportion of olein and butyrin was such as to permit this to occur. On the other hand, it may be decreased or there may be no influence whatsoever on the melting point of the butter fat or the firmness of the butter. In many instances it is not possible to state definitely the influence of a particular feed on the melting point of butter fat, because no work of this nature has been done on that particular feed.

Relation to Plane of Nutrition.—In addition to the influence of feeds on the composition of butter fat, Eckles and Palmer have demonstrated that the plane of nutrition may be a factor, particularly, in cases where animals are underfed. They point out that all types of underfeeding have marked effects on the physical and chemical constants of butter fat which are characterized by a decline in the volatile acids and an increase in the olein content of the butter fat produced. The melting point

of butter fat as a result of underfeeding may increase, remain stationary, or decrease, depending on the proportion of volatile acids, principally butyric, to the oleic acid content.

PROTEINS OF MILK

Proteins are among the most complex of organic substances. They contain carbon, hydrogen, oxygen, nitrogen, sulphur, and sometimes phosphorus. Protein is an indispensable part of the food of animals as it is the chief constituent of the protoplasm which forms the vital part of every living cell. Familiar examples of protein are the white of an egg and the curd of milk. Lean meat is chiefly protein with considerable water and some fat.

As would be expected from the purpose of milk in nature it contains considerable protein. In milk of average composition, that is, with a fat percentage of about 3.8, the protein content will be around 3 per cent. In milk containing as much as 5 per cent of fat the protein will be around 3.8. Nearly all samples of normal milk would come between 2.80 and 4.00 per cent. Greater extremes will be found only rarely. The protein of milk is not a single compound but includes three major proteins and small quantities of others. Of these, casein constitutes about 80 per cent of the total and lactalbumin 18 per cent.

The proteins of milk, principally casein, are among the chief constituents of the various types of cheese. Cheddar cheese contains approximately 33 per cent of casein. The average protein content of a few of the other more or less common cheeses is as follows: Domestic Swiss 26.0 to 30.0, Roquefort 21.0, Camembert 19.0, and Brick 21.0 per cent. The soft cheeses contain a greater percentage of moisture than the hard cheeses and contain from 12.0 to 20.0 per cent of protein, depending on the percentage of moisture and milk fat contained in the cheese.

In the manufacture of ice cream, the proteins constitute a large proportion of the milk solids-not-fat in the mixture and doubtless add to the relative smoothness of the texture of the finished product.

Casein of Milk.—There is no other protein in nature similar to casein. As it appears in commerce, casein is a yellowish-white granular substance. In its pure state it is snow-white, odorless, and tasteless. In milk, it is found in combination with calcium and is often spoken of as *calcium caseinate*. It is a

well-established fact that casein exists in milk in the form of small gelatinous particles in suspension. The chemist refers to this state of dispersion as "colloidal." Casein can be removed from milk by filtering through a porcelain filter, or through an animal membrane.

Casein may be precipitated from milk by dilute acids, rennin, and alcohol. Casein of fresh milk is not coagulated by heat until temperatures such as can be reached only under pressure are reached. On boiling fresh milk, a thin layer of finely precipitated casein, together with other milk constituents, forms a thin skin over the surface of the milk.

Commercial Uses of Casein.—Casein is prepared in a commercial way by precipitation from skim milk by the use of dilute acids or rennet. Sometimes the milk is allowed to stand until sufficient acid is produced naturally to curdle the milk. After precipitation the whey is partially expelled from the curd by heating and is drained from the curd which then is dried and ground.

Casein finds a wide use in industry. One interesting use is in the manufacture of plastics. Casein plastics are made in rolls, sheets, and tubes. They are very hard, resist the action of water, and take colors readily. They are odorless, non-inflammable, and can easily be cut into desired shapes and sizes. Casein plastic is used as a substitute for celluloid, horn, and tortoise shell. From it are made a wide variety of toilet articles such as combs, buttons, and rims for eyeglasses. It also is used extensively for fountain-pen barrels, billiard balls, and for electrical insulations.

One of the most important uses of casein in industry is in the sizing of high grade paper. Several millions of pounds of casein are used for this purpose annually. It is estimated by the authors that more than 80 per cent of the casein manufactured is used by the paper industry for one purpose or another.

Glue is another important product of this milk constituent. Casein glue is sold in a dry form and is ready to use upon the addition of water. Its strength and resistance to water make it of special value in industry where it finds a wide use. It is commonly used in the manufacture of furniture, door panels, refrigerators, airplanes, and automobile-body frames.

Casein is also an important constituent of cold-water paints, the use of which is increasing rapidly. Paints of this class are used

for both exterior and interior work. Casein also is used extensively in the textile industry and in the manufacture of leather of certain grades. Another use is as a spreader in connection with the application of sprays used in horticultural work. The addition of a certain amount of casein causes the spray to spread well over the foilage and to adhere better.

FIG. 9.—Articles made from casein plastic. This material is used in the manufacture of a multitude of articles, for example, toilet articles, rims for eyeglasses, fountain-pen barrels, and colored tiles. Casein glue, another product made from this milk constituent, finds a wide industrial use, as in the manufacture of furniture and the sizing of paper.

New uses for casein are constantly being found. It is used as a filler or a binder in certain foods. It may serve as the base material for a meat sauce, and as a binder in sausage; it may be the principal constituent of certain brands of baby foods.

Albumin.—The term “albumin” is used commonly to designate the protein of milk known chemically as “lactalbumin.” The albumin content of milk remains fairly uniform at about 0.5 per cent. It resembles but is not identical with blood albumin. When dried, lactalbumin is a tasteless powder. Like other proteins, albumin has an extremely complex chemical composi-

tion. It contains carbon, oxygen, hydrogen, nitrogen, and a small quantity of sulphur. Unlike casein, albumin is coagulated by heat, but not by rennet. There is some question as to whether albumin exists in milk in the colloidal state or in true solution. Albumin may be separated from milk by precipitating, first, the casein by the use of a weak acid, and heating the filtered whey to a temperature of 158°F. (70°C.), or above, for a short period. The turbid appearance of the heated filtrate shows the presence of coagulated albumin. By filtering the heated material the albumin may be recovered on the filter. This method, however, does not result in a complete precipitation of the albumin. Lactalbumin precipitated by the action of heat is insoluble.

Lactalbumin in Dairy Products.—The centrifugal separation of cream apparently does not affect the distribution of albumin in the serum. For that reason, the greater proportion of the total albumin of the milk goes into the skim milk when the milk is used for butter manufacture. The serum in the cream also contains the normal percentage, and most of this remains in the buttermilk at the time of churning. A small amount is found in the butter as an ingredient of the buttermilk which remains in the butter when the product is ready for the market.

In cheese making, as the albumin is not coagulated by the rennet, it goes chiefly into the whey. The food value of whey depends upon the albumin, milk sugar, milk ash, and a small amount of fat.

Commercial Uses.—Lactalbumin is not used to any extent commercially. Primost cheese, made by boiling off the water from whey, contains albumin as one of the important constituents, the others being lactose, fat, and milk ash.

Other Proteins.—In addition to casein and lactalbumin, milk is frequently credited with containing traces of other proteins; namely, lactoglobulin, fibrin, and alcohol-soluble proteins. Lactoglobulin was first isolated from milk by Sibelin and Emmerling who worked independently. The occurrence of globulin as an independent protein has been questioned by chemists though its properties are freely discussed. Milk does not contain more than 0.1 per cent of lactoglobulin. Only a trace of fibrin occurs in milk and under some conditions it is totally absent. Evidence indicates that milk contains an alcohol-soluble protein, the characteristics of which differ from the alcohol-soluble proteins of cereals in which these proteins usually occur.

LACTOSE

Milk sugar, known chemically as "lactose," is found only in milk. Mixed milk, including that from various breeds, contains on the average about 4.8 per cent of lactose. Nearly 90 per cent of all samples will show a variation not to exceed 0.2 from the average figure given. Some variation occurs with individuals within the breed while the breed itself is a small factor, in so far as some relationship is evident between the amount of other solids and the sugar content. Milk from the Jersey breed averages about 5 per cent of milk sugar compared to 4.6 per cent for that from the Holstein. Lactose is similar in composition to sucrose, ordinary cane sugar, and has the same chemical formula, $C_{12}H_{22}O_{11}$. It differs from sucrose, however, in molecular constitution and in relative sweetness. Sucrose is about six times as sweet as lactose. The lactose is in a true solution in the milk serum. Prolonged heating of aqueous solutions of lactose at temperatures from 212 to 266°F. (100 to 130°C.) results in a decomposition which is indicated by a light-brown color. This change is brought about by the sugar taking on oxygen and giving off carbon dioxide.

Action of Bacteria on Lactose.—Lactose has an important relation to the manufacture of the milk products, due to the fact that it is easily decomposed by bacteria. The lactic acid formed in milk, which gives to milk its characteristic sour taste, is the result of bacterial action on milk sugar.

The chemical reaction however, which takes place when lactic acid is produced from milk sugar by bacteria cannot be expressed quite as simply as above, nor is the amount produced necessarily equal to that indicated. Many other products may result from bacterial action, the nature and amount depending upon a variety of factors. It has been found that 1 gram of lactose may form on decomposition by bacteria 0.8 gram of lactic acid. In the ordinary souring of milk, the fermentation continues until an acid percentage of 0.8 to 1.0 is present at which point the acid itself inhibits further growth of the organisms which produced it. As a rule, not over 10 to 30 per cent of the sugar has been used in the normal souring of milk. If an alkali is added to sour milk to reduce some of the acidity, the acid-forming bacteria that are

present again will become active and develop acid to the maximum amount which the particular species can tolerate. As pointed out elsewhere, the acid fermentation is a factor of tremendous importance in both butter and cheese making. In fact, the present processes of manufacturing these products, based upon the experiences of generations, assume that the acid fermentation will occur. The typical butter flavor is undoubtedly due, in part, to products of fermentation in which the sugar takes a part. The same is true for, at least, the most widely used cheeses. One of the most important parts played by the acid formed by fermentation from the sugar is the checking of the growth of undesirable organisms. If it were not for this action, dairy products would rapidly undergo a decomposition that would render the product unfit for food.

Lactose in Dairy Manufactures.—When milk is used for butter making, the lactose goes chiefly into the skim milk. The serum of the cream contains the same proportion as the serum of the original milk. In the fermentation preceding churning, some of the lactose will be converted into acids although at least 80 per cent will still be in the buttermilk. A very small amount will be carried into the butter dissolved in the water of the butter. This small amount may be entirely converted into acid within a few days. When milk is used for cheese making, most of the lactose follows the whey. The portion which goes into the cheese is fermented largely in the course of a few days. The milk sugar of commerce is prepared from whey, a by-product of cheese manufacture.

ASH OR MINERAL MATTER (SALTS OF MILK)

If milk is dried first, then the residue burned, a white powder, which is the ash or mineral part of the original milk, remains. If careful weights are taken it will be found that the percentage of mineral is about 0.7. Further chemical study would reveal that this ash is a complicated mixture containing a number of metallic elements, in fact, the same ones found in the animal body.

The procedure followed in determining the ash content of milk makes it extremely difficult to determine the exact combinations that exist in the original product. Milk ash is known to contain potassium, sodium, calcium, magnesium, chlorine, phosphorus, and sulphur in relatively large amounts. There are present

small amounts of iron, copper, zinc, aluminum, manganese, and iodine, while traces of silicon, boron, titanium, vanadium, rubidium, lithium, and strontium have been reported as present.

Parts of the calcium and phosphorus are combined with the proteins. The remaining portions of these elements, together with the magnesium, are partly in suspension and partly in solution. The potassium, sodium, and chlorine are entirely in solution. The small quantity of sulphur enters into the composition of the casein and lactoglobulin.

Uses of Milk Ash.—The ash of milk is not used commercially. It is, from the standpoint of nutrition, however, one of the most important constituents of milk. A sufficient supply of minerals in the human diet is a matter of great importance. Diets based largely upon cereal-grain products are especially lacking in calcium. Milk shares with leafy vegetables the distinction of being the best source of supply for this important element. Milk is, however, low in iron, and for this reason would not supply all the needs of an adult. The newborn is supplied with a store of iron sufficient to tide it over until foods supplying more liberal quantities of iron are added to the diet.

The ash constituents of milk are extremely important in their relation to the heat stability of milk. This fact becomes of considerable practical importance when milk is subjected to such temperatures as are used in the sterilization of evaporated milk.

When milk is used for butter making, the ash necessarily goes with the skim milk and buttermilk, leaving small percentages of the original milk ash in the butter. In cheese making most of the ash goes with the whey, although the amount in the cheese is much greater than that which goes into butter. The well-known value of skim milk and buttermilk as supplementary feeds for swine and poultry depends in part upon the presence of the milk ash and its value in making up the deficiencies in mineral content of the grains which compose the chief part of the usual rations.

MINOR CONSTITUENTS OF MILK

In addition to the major constituents, water, protein, sugar, fat, and ash, milk contains a number of constituents which are of minor importance, particularly from the standpoint of the proportions in which they occur in milk. From the standpoint of the chemical and physical properties of milk, it is apparent

that some of these minor constituents are exceedingly important. For example, the yellow color of milk is due to a pigment known as "carotene." It is not possible to measure quantitatively the amount of carotene in milk but its presence in small or large quantities materially influences the yellow color of milk.

Phospholipids.—The principal phospholipid contained in milk is lecithin, a fat-like substance which contains nitrogen and phosphorus. Lecithin is closely associated with the fat, doubtless making a portion of the concentrated colloidal layer surrounding the fat. Upon the separation of milk, the lecithin becomes more concentrated in the cream, a trace being left in the skim milk. During the agitation of cream in churning, the lecithin is rubbed off the fat globule, and as the fat globules coalesce most of the lecithin remains in the buttermilk. A small portion only is retained in the butter which contains but a trace (0.03 to 0.05 per cent) of lecithin. Buttermilk, however, has been shown to contain, approximately, 0.2 per cent owing to the increased concentration which takes place.

Though butter contains but small amounts of lecithin, it is of great significance. Fishy flavor in butter, a rather common defect at times responsible for large losses on the market, has been shown to be due to the decomposition of lecithin. In the splitting of lecithin, trimethylamine is formed. This is the compound responsible for the fishy flavor. This same flavor is sometimes produced in other dairy products such as evaporated and dry milk.

Cholesterol.—Milk has been shown by Denis and Minot to contain cholesterol. These authors report cholesterol as occurring in milk in direct proportion to the amount of fat present. They report milk as containing from 105 to 176 parts per million of cholesterol.

Pigments.—Milk contains two pigments, one of which is fat soluble, and the other water soluble. The fat-soluble pigment of milk belongs to a group known as "carotinoids" and has been designated as "carotene." Carotene is responsible for the yellow color of milk fat. It does not occur in the milk of all species, as the milk of the goat, ewe, and camel, for example, are colorless.

Carotene is not synthesized by the cow, but by plants, and finds its way from the feed into the blood stream and, thus, into the milk. This pigment is deposited in the body fat of cattle, the amount varying with the breed as does the amount

in the milk fat. The body fat of the animals of the Jersey and Guernsey breeds is very highly colored; so much so as to cause objection by consumers when it is placed on the market. It appears that the yellow color of milk is very nearly in direct proportion to the amount of the pigment received by the cow in feed. Such feeds as green grass, green alfalfa hay, soiling crops, green-corn fodder, green silage, and carrots are rich in carotene. Hay which has lost its green color, dry-corn fodder, all kinds of straw, corn either yellow or white, wheat, oats, beet pulp, bran and oil meals are all feeds low in carotene. It should be explained that the color of yellow corn is due largely to xanthophylls which do not find their way into milk fat in sufficient quantities to influence the yellow color.

The water-soluble pigment of milk has been shown to be lactochrome and occurs in the serum, or whey, portion of milk, contributing a yellowish-green tint to this portion of milk. The amount of this pigment occurring in milk is very small, amounting to but 0.05 to 0.1 per cent. Lactochrome, not only occurs in the milk of the cow, but in the milk of most mammals. Its presence in milk cannot be connected directly with the feed the animal receives. There is some relationship, however, between the lactochrome content of milk and high protein feeds.

Enzymes of Milk.—Substances, known as “enzymes,” are apparently normal constituents of milk. Enzymes are chemical substances secreted by living plant and animal cells and which stimulate chemical reactions without becoming a part of the compounds formed. Common examples of enzymes are ptyalin of the saliva, which acts upon starch, forming maltose; and pepsin found in the stomach, which assists in the breaking down of proteins. One of the first enzymes demonstrated as occurring in milk is galactase, a proteolytic enzyme. Russell and Hastings were the first to contend that galactase was present as a normal constituent of milk. The enzyme is thought to play an important part in the ripening of cheese. Lipase, a fat-splitting enzyme, has been shown to be a normal constituent of the milk of cows that have been in milk for an abnormally long period. When this enzyme occurs in milk it may be the cause of a bitter flavor developing. Extreme cases of rancidity in butter, also, have been attributed to the action of lipase.

It has been established definitely that milk contains catalase, an oxidizing enzyme, and reductase, an enzyme which exhibits

its presence by its action on certain color compounds such as methylene blue. There is some evidence, too, that milk contains lactase, a sugar-fermenting enzyme; diastase, a starch-splitting enzyme; and peroxidase, an oxidizing enzyme. The presence of these last three mentioned enzymes, however, is often disputed.

Vitamins.—Milk contains all six of the recognized vitamins; namely, vitamin A (the antiophthalmic vitamin), vitamin B (the antineuritic or antiberiberi vitamin)—(vitamins A and B are both growth promoting)—vitamin C (the antiscorbutic vitamin), vitamin D (the antirachitic vitamin), vitamin E (the antisterility vitamin), and vitamin G (the antipellagra vitamin). The feed is known to be a factor influencing the amount of some vitamins in milk.

Gases.—Milk contains from 7 to 10 per cent by volume of gas. Carbon dioxide is present in milk as it comes from the udder, while nitrogen and oxygen are taken up by the milk during milking. On standing, the amount of gas becomes less.

In addition to the above gases, milk may absorb gaseous odors from the air and, although such conditions are abnormal, the fact remains that the market quality of milk may be seriously handicapped by absorbed gases.

Gases may also be formed in milk by certain bacteria. The detrimental effects of these gases, however, are not apparent for several hours after the milk is produced.

Non-protein Nitrogenous Substances.—Milk contains a group of nitrogenous substances in addition to the proteins. These substances do not occur in large quantities but they are known to be present. The non-protein nitrogenous substances of milk may be listed as follows: urea nitrogen, amino nitrogen, creatinine, creatine, uric acid, adenine, and guanine. These substances are measured in parts per million, ranging from 1.5 to 10 in milk.

CHAPTER III

FACTORS INFLUENCING THE COMPOSITION OF MILK

If a number of milk samples were gathered from different sources and subjected to careful chemical analysis, it is probable that not a single sample would have exactly the composition given as typical for average milk. If the samples were taken from mixed milk which included the product of numerous cows, especially if representing various breeds, the variation from the average figures might be small. The largest variation from the average figures would be found if the samples, which were analyzed, represented single milkings of individual cows of various breeds.

A study of the result from the analysis of a group of samples taken as suggested would show, first of all, that the samples in all cases contained the same constituents, and, further, that the range of variation is especially large with certain constituents. The nature and composition of milk has interested investigators and has been a subject of researches since the earliest days of science. Not much progress was made until the latter part of the nineteenth century when the development of chemical methods made possible rapid advances toward an understanding of milk and its properties. If one should ignore the present knowledge of the subject, and begin a study of the variations in the composition of milk with the purpose of covering the entire field, it would be found that years of work would be required to accumulate knowledge equal to that now available. Anyone who has conducted research work in this line realizes that even though the present knowledge of the subject is extensive, much remains for future discovery.

Importance of Variations in Composition.—The importance of knowledge concerning variations in the composition of milk is evident. Milk is used for food and as the material from which various dairy products are manufactured. If milk varies widely in composition, it is clear that the food value will also vary, and it becomes a matter of economic importance when the product

is placed on the market. Wide variations in the composition of milk would also be of significance in connection with the use of milk in the human diet, especially when it furnishes a large part of the food intake, as it does for infants. In the field of dairy manufacturing, milk, as the raw material from which the finished product is made, receives the same close scrutiny as would the materials for manufacture in any other line. For example, because of the wide variations in the fat percentage of milk in most parts of the world, tests for fat content are made when the milk passes from the producer to the manufacturer or dealer.

Nature of the Variations.—As pointed out, variations in the composition of milk are largely quantitative rather than qualitative. That is to say, milk from every source, regardless of breed or even of species, will contain the same classes of constituents. An ordinary chemical analysis of milk includes determinations of fat, protein, sugar, and ash. All of these will be found in any sample. If the chemical study is carried farther, however, for example, to a study of the nature of the proteins or the characteristics of the fat, decided differences will begin to appear.

The following figures give the average composition of cow's milk limited to the major constituents, and the normal range of composition:

AVERAGE COMPOSITION AND NORMAL RANGE

	Average percentage	Normal range, percentage
Water.....	87.25	89.50 to 84.00
Fat.....	3.80	2.60 to 6.00
Protein.....	3.50	2.80 to 4.00
Lactose.....	4.80	4.50 to 5.20
Ash.....	0.65	0.60 to 0.80

The widest variations occur with the fat, the next, with the protein, followed by those of the lactose and ash. It should be understood that variations that considerably exceed the figures given as the normal range occasionally are found. Such extreme variations are associated most often with the beginning or end of the lactation period or represent a single milking from an individual cow that, because of some unknown physiological or

pathological condition, temporarily secretes milk far from a normal composition. Mixed milk, representing a group of cows, nearly always will have a composition within the given normal range. If the milk is from cows which all represent the same breed, the range in composition will be decidedly less than when more than one breed is included. Much time and effort have been given to studying the factors responsible for the variations, especially in fat content, which are so commonly found. Certain well-established causes have been determined. These are presented in paragraphs which follow.

Species of Animal.—A comparison of cow's milk with that of other species is interesting and valuable at times. Table I,

TABLE I.—COMPOSITION OF MILK OF VARIOUS SPECIES

Species	Water, percent- age	Fat, percent- age	Protein, percent- age	Lactose, percent- age	Ash, percent- age
Human.....	88.30	3.11	1.19	7.18	0.21
Cow.....	87.25	3.80	3.50	4.80	0.65
Goat.....	87.88	3.82	3.21	4.54	0.55
Sheep.....	80.82	6.86	6.52	4.91	0.89
Mare.....	90.70	1.20	2.00	5.70	0.40
Water buffalo.....	76.89	12.46	6.03	3.74	0.89
Reindeer.....	67.20	17.09	9.89	2.82	1.49
Camel.....	87.61	5.38	2.98	3.26	0.70
Sow.....	84.09	4.55	7.23	3.13	1.05
Bitch.....	78.88	8.56	6.82	4.09	1.08
Cat.....	81.63	3.33	9.08	4.91	0.51

compiled from various sources, gives the composition of human milk and that from common domestic animals. It should be noted that human milk is decidedly low in protein as compared to cow's milk, somewhat lower in fat content, but decidedly higher in lactose. These marked differences are taken into account when cow's milk is modified for infant feeding. In general, the protein content is reduced by the addition of water. Cream is added to restore the fat percentage and the amount of sugar necessary to bring this constituent near to the normal for human milk.

The goat ranks next to the cow in importance as a producer of milk for human food. It is interesting to note that the com-

position of the milk, as given, closely approximates that of cow's milk. It should be stated that the milk from other species varies nearly as much as does cow's milk, and the figures given are merely average analyses obtained under one set of conditions. For example, the fat content of goat's milk as given in the literature ranges from 3 to 6 per cent. The question of breed evidently is an important factor in this case. The difficulties in getting fair samples of milk from the smaller animals greatly depreciates the value of the figures given for these species. The water buffalo is an important source of milk for human food in the Orient, and it is interesting to note the very high fat content in the milk of this species. The yield, however, is small compared to that from the cow as developed in Europe and America. Mare's milk is low in dry matter, especially fat and casein, in comparison with the milk of the cow. Mare's milk, however, is an important article of food for the tribes of Central Asia. A fermented drink, known as "koumiss," made from this milk is used widely. The milk of the sheep serves as human food in some localities. In these regions, breeds have been developed for this particular purpose. Roquefort, a well-known and highly esteemed cheese, is made in France chiefly from sheep's milk.

Influence of Breed.—It is a well-known fact that the breed is one of the most important factors influencing the composition of milk. So important is this influence that the value of any average figure given for the composition of milk has but a limited value. In the northern states, where Holstein-Friesian blood predominates among the dairy herds, the fat and protein content of the milk as it comes to market is distinctly below the average figures usually given, while in the south where milk from Jersey cows constitutes the larger proportion of the general supply, exactly the reverse is true.

Table II, a compilation based upon the work of several authors, gives the average composition of the milk from the breeds of cattle most common in America. It will be noted that the fat percentage varies widely, the protein considerably, but less than the fat, while the range of variation for the lactose and ash is relatively narrow. The composition of milk is a factor of great importance in the value of milk for manufacturing purposes, or for food. Those breeds producing milk with a high fat content produce less milk than those producing milk with the lower fat

percentages. There is also some tendency, although less marked, toward this same relationship within the breeds.

TABLE II.—BREED AS A FACTOR IN MILK COMPOSITION

Breed	Water, percent- age	Total solids, percent- age	Fat, percent- age	Protein, percent- age	Lactose, percent- age	Ash, percent- age
Holstein.....	88.07	11.93	3.45	3.15	4.65	0.68
Guernsey.....	85.45	14.55	4.98	3.84	4.98	0.75
Jersey.....	85.43	14.57	5.14	3.80	4.87	0.76
Ayrshire.....	87.28	12.72	3.85	3.32	4.90	0.65
Shorthorn.....	87.19	12.81	3.80	3.32	4.99	0.70

The relation of the several constituents to the total dry matter of the milk and to each other is of considerable importance. This relationship, so far as the chief constituents are concerned, is set forth in the tabular statement which follows:

THE COMPOSITION OF MILK FROM VARIOUS BREEDS IN TERMS OF TOTAL SOLIDS

Breed	Fat, per- centage	Protein, percentage	Sugar, percentage	Ash, per- centage
Holstein.....	28.9	26.4	39.0	5.7
Guernsey.....	34.2	26.4	34.2	5.1
Jersey.....	35.3	26.0	33.4	5.2
Ayrshire.....	30.2	26.1	38.5	5.1
Shorthorn.....	29.6	25.9	38.9	5.4

Calculations are based on Table II.

The figures show the differences between milk of several breeds; for example, in Jersey and Holstein milk it is not merely a question of water content. The solids also vary in composition. This is borne out by the fact that in average Jersey milk the fat constitutes 35 per cent of the total solids, while in Holstein milk the fat represents only 28 per cent of the total solids. In the case of Jersey milk the fat represents the greatest single portion of the total solids, while in the milk of the Holstein, Ayrshire, and Shorthorn the milk sugar or lactose constitutes the principal part of the total solids. The per cent of ash in the total solids of Holstein milk is greatest of all the above breeds.

Influence of Breed on Fat.—As pointed out in connection with the discussion of fat, breed is the most important factor influencing the size of fat globules. As illustrated in Fig. 8, the Jersey fat globule is the largest, while the Holstein, among common breeds, stands at the other extreme. The difference between these two breeds in this respect is sufficient to make possible the differentiation of typical Holstein from Jersey milk by the use of an ordinary compound microscope. The practical significance of the size of the fat globules is pointed out in other connections. Although some evidence may be found of breed influence upon the nature of the fat the variations are not marked, and other factors, especially feed and stage of lactation,

FIG. 10.—The relation of breed to milk composition. The ash is practically uniform and the variation in lactose not pronounced. The widest range is in fat and the second in protein. This graph is based upon Table II.

greatly overshadow the effects of breed. Furthermore, there is no evidence to indicate that such variations in fat composition as may be attributed to breed are of significance either from the standpoint of using milk directly for food or for manufacturing purposes. The chief breed effect upon the nature of the fat appears to be a slightly higher proportion of volatile acids in the fat from the Jersey and probably the Guernsey breeds.

Breed in Relation to Color.—Next to feed, the breed is the most important factor determining the amount of yellow color in milk. The Guernsey breed ranks first in this respect, followed by the Jersey. The Holstein and Ayrshire show the least color, with other breeds intermediate. As explained elsewhere, the cow does not make the yellow color as it is entirely a plant product. The cow passes more or less of it, when it is present, through the

body into the milk and body fat. The relatively smaller amount of yellow color in Holstein milk is to be attributed to a greater destruction or elimination of the pigment from the feed by this breed as a result of some physiological process. The pigment is decidedly important as a factor in marketing milk and cream. Because of the practice of maintaining a uniform color in butter and cheese by the addition, when necessary, of a harmless coloring matter, the breed variation in the amount of pigment secreted into the milk is of little economic importance where milk is used for manufacturing purposes.

Breed and the Quality of Dairy Products.—As was previously pointed out, there is no significant breed variation in the nature of the fat, with the exception of the yellow color. Although the proportion of other constituents also varies, no evidence is at hand to indicate any difference in the composition and qualities of these constituents. For these reasons, it would follow that the only special relation that the breed might have to the use of milk for food or for manufacturing purposes would depend upon the amount of the constituents present and possibly to their relation to each other. For cheese making, for example, the higher fat content in proportion to the proteins results in a cheese of better quality, but the yield in proportion to the fat is somewhat smaller. This raises some questions regarding the fairness of paying for milk to be used for cheese making upon the basis of the fat content.

In making condensed milk, the relation of the fat to the other solids is also a question of some importance. When the fat is higher in proportion to the solids-not-fat, in order to meet the legal requirements for solids other than fat, the fat content is unnecessarily high. For this reason, milk of a medium fat content generally is preferred to one having a very high fat percentage.

The Stage of Lactation.—The period from the time the calf is born until the cow ceases to give milk is called the “period of lactation.”

Colostrum.—The milk produced by an animal immediately after parturition and for the three to ten milkings following is termed “colostrum.” The composition of colostrum differs from normal milk in that it is lower in water, sugar, and fat, and higher in casein, albumin, globulin, and ash than normal milk. The most striking difference between normal milk and

colostrum is the globulin which often reaches 12 to 13 per cent in the colostrum. The average composition of colostrum is as follows: total solids, 28.31 per cent; fat, 3.37 per cent; casein, 4.83 per cent; albumin and globulin, 15.85 per cent; sugar, 2.48 per cent; and ash, 1.78 per cent.

Colostrum also differs considerably from normal milk in appearance and general properties. It has a reddish-yellow color, an abnormal odor, a bitter taste, is very slimy and viscous, and has a decidedly acid reaction. Because of its high total-solid content, colostrum also has a much higher specific gravity than normal milk, or approximately 1.079.

When examined under the microscope, colostrum shows a large number of colostrual cells which according to some writers is due to a sloughing of the epithelial cells of the udder. Others believe that these cells are leucocytes enlarged by absorption of fat globules. The fat globules appear as large, irregularly shaped masses of fat in colostrum as compared to the round,

TABLE III.—STAGE OF LACTATION IN RELATION TO MILK YIELD AND FAT PERCENTAGE¹

Month of lactation	Average daily milk yield, pounds	In terms of percentage	Fat content, percentage
1	32.9	99.6	4.07
2	33.0	100.0	3.94
3	30.3	92.0	4.06
4	28.4	86.0	4.00
5	27.0	82.0	4.10
6	24.7	75.0	4.10
7	23.4	71.0	4.17
8	22.7	69.0	4.20
9	21.1	64.0	4.20
10	17.1	52.0	4.50
11	11.3	34.0	4.59
12	3.8	11.5	4.70

¹ Data from a group of cows that calved again within a 12-month interval.

distinct fat globule of normal milk. Also, it has been found as the result of recent investigations that the colostrum contains antibodies which serve to protect the new-born calf against the invasion of bacteria, until the animal itself develops a resistance. It is this property that especially makes it important that the new-born calf secure the colostrum from its mother.

Stage of Lactation and the Fat.—It is well understood that certain changes in the fat accompany the advance in the lactation period. One such change concerns the size of the fat globules. A fresh cow secretes relatively large fat globules. There is considerable decrease in size until about the second month. From this point on, the decrease is less marked until near the close of the lactation period, when the decrease again becomes more rapid. The small fat globules in milk near the end of the lactation period are one cause of the difficult churning often experienced, especially under farm conditions.

The fat percentage also is affected in a rather characteristic manner by the stage of lactation. In the colostrum it is low, but within a few days it reaches the normal for the individual.

FIG. 11.—Relative size of fat globules as influenced by stage of lactation: (1) first month in milk, (2) fifth month, (3) ninth month, (4) twelfth month. The size of the fat globules is a factor in gravity separation of cream and in the time required for churning.

If the cow carries considerable body fat, the fat percentage may be higher at first and decline somewhat during the first month. From the time the normal fat level is reached until near the close of the lactation period, the change due to stage of lactation is not marked, but inclines somewhat upwards. A sharp rise occurs, normally, during the 6 weeks or 2 months immediately preceding the point at which the cow ceases to lactate.

The composition of the fat also undergoes some characteristic changes which are, primarily, a reduction of the volatile acids near the close of the lactation period. Sometimes the composition of the fat changes to such an extent that a sample of butter made exclusively from milk produced by a cow in this state of lactation might be pronounced adulterated if examined by a chemist.

The protein content of milk also follows the fat in showing a considerable increase near the end of the lactation period. The sugar remains quite constant. Occasionally, milk from cows near the end of the lactation period has an objectionable taste

and odor after standing 12 to 20 hours after milking. The cause of this abnormal change, usually described as bitter or rancid, has been found to be the result of the action upon the fat of an enzyme known as "lipase," which for some unknown reason may appear in the milk under these conditions.

Effect of Age.—The age of the cow is a factor of considerable importance in regard to the yield of milk, but of slight significance in connection with the composition. A tendency has been found for the fat percentage to increase slightly from the first to the second or third lactation period. It then remains practically the same until the effects of advancing age begin to affect the

FIG. 12.—Changes in milk yield and fat percentage during the lactation period. The maximum milk production is reached by the end of a month and from this point gradually declines. The fat percentage remains fairly constant until near the end of the lactation, then rises to the end.

animal. If a cow continues to reproduce until 12 years or more of age, some decline in fat percentage nearly always becomes apparent. This is especially the case with the breeds normally having a relatively high fat percentage in the milk. For example, the milk of four Jersey cows averaging 5.2 per cent of fat during their prime gradually decreased as they aged, until at the age of 15 years the fat percentage averaged 4.5. With the exception of this decline in fat percentage neither the composition of the milk nor the nature of the constituents shows any variations due to age.

Individual Variations.—Within the limits of the same breed and with uniform environmental conditions a considerable range of variation may occur, especially in the fat percentage although significant variations are also found in the other constituents. In Table IV is given the composition of the milk from six cows

where the ration was the same throughout the year, and all other conditions were maintained as nearly uniform as possible. Every milking was sampled and complete analyses were made of composite samples representing intervals of 7 days. It should be noted that variations occur in the percentage of each constituent reported. If a larger number of animals were included the range would probably be still greater.

TABLE IV.—INDIVIDUAL VARIATIONS IN MILK COMPOSITION, TRUE AVERAGE FOR A COMPLETE LACTATION PERIOD

	Total solids, percent-age	Fat, percent-age	Protein, percent-age	Sugar, percent-age
Holsteins:				
<i>a</i>	12.12	3.23	3.00	5.05
<i>b</i>	10.73	2.93	2.70	4.26
<i>c</i>	11.35	3.10	3.21	4.25
Shorthorns:				
<i>a</i>	13.08	3.89	3.40	5.04
<i>b</i>	13.01	4.13	3.49	4.91
<i>c</i>	12.17	3.37	3.28	4.98

The following tabulation shows the range in fat percentage found in the lifetime record of 25 cows of each breed. The first 25 cows having three or more lactation periods were selected alphabetically from the records of the University of Minnesota herd.

	Average fat percentage	Highest fat percentage	Lowest fat percentage
Holstein.....	3.27	3.70	2.60
Jersey.....	5.22	5.97	4.37
Guernsey.....	4.72	5.20	4.28

It is believed that the conditions under which these animals were kept were sufficiently uniform to justify the statement that these variations from the average were due to some individual characteristic which was a matter of inheritance. Had a larger number of animals been included, it is quite likely that still

greater ranges would have been found. Only in exceptional cases, however, would be found these wide variations from the normal. The data are not available for the milk constituents other than fat.

The question may arise as to the uniformity in the fat content from the same animal year by year. Daily variations occur and there is also some influence due to age as pointed out in another paragraph. When the true average fat percentages for the entire lactation periods are compared, these factors are largely eliminated and the variation which is found is not large. The figures which follow show the average fat percentage of the milk of four animals, one pair of Jerseys, the other Holsteins, for a term of years. These pairs were selected to include, in both cases, one cow with milk above and one below the average in fat percentage.

Jerseys (a) 4.6; 4.6; 4.4; 4.7; 4.3; 4.4; 4.5; 4.2.

(b) 5.6; 5.6; 5.5; 5.0; 5.1; 5.2; 5.0.

Holsteins (a) 2.4; 2.4; 2.7; 2.7; 2.6.

(b) 3.8; 4.0; 4.1; 3.6; 3.6; 3.5; 3.4.

Seasonal Variation.—When milk is sold according to the fat content it is noted, generally, that the fat test drops soon after the cows go out to pasture. Towards fall the test again rises. One often makes the mistake of attributing this decline in the test to the watery nature of the feed when the cows are eating grass, and the rise towards fall as the result of feeding grain or other dry feed. It has been proven experimentally that this assumption is not correct. Cows receiving exactly the same ration throughout a year show the same tendency toward a decline in the fat test during the summer and an increase again towards winter. The effect of the season is often obscured by the changes due to the stage of lactation. If the fat percentage is averaged for a large number of milk samples, including those from cows freshening at different periods of the year, it will be found that the high point is reached in December or January and the low point in June or July. The difference between the low and high points, however, will not be very significant, probably less than 0.5 per cent.

Seasonal Variations in Solids-not-fat.—It has been shown by White that the solids-not-fat follow the same general seasonal curve as does the fat. There are a number of important applications of these facts. For example, when cows are being pushed

for the maximum production, as is the case in advanced registry testing, the results during the hot weather are liable to be disappointing as far as the fat percentage is concerned. As a

FIG. 13.—Seasonal variations in fat percentage. The fat percentage tends to reach a high point in December or January and a low point in June or July. Note the effect of the seasonal factor upon the shape of the lactation curves.

result of the seasonal variation, the average test of a cow for a year will be a little higher if she freshens in the fall. A compilation of the records of 32 cows, some of which had lactation periods beginning in the fall and the others in the spring, showed an average fat percentage of 4.54 in the milk produced by the

cows with the lactation periods beginning in the spring as compared with 4.75 for those beginning in the fall. The results are brought about in the case of the fall freshening because the higher test and greater yield of milk come together. With those cows freshening in the spring the reverse condition exists.

The decline in the solids-not-fat content during the summer months often results in a serious condition in connection with milk standards. The legal requirement regarding solids-not-fat often is placed so high that at times during the summer a considerable portion of a particular milk supply may be below standard which may result in controversy and penalties for violation of the law when the source of the trouble is the normal seasonal variation in milk composition combined with a standard which is unreasonably high.

In a report by one of the authors attention was called to the seasonal variation in fat percentage, and the suggestion was made that temperature and relative humidity probably are the responsible factors. Later, carefully controlled experiments by Hays, Ragsdale, and Brody showed conclusively the importance of temperature. For each 10° decline in temperature from 72 to 27°F. (22.2 to 2.8°C.) the fat percentage increased approximately 0.2 per cent.

TABLE V.—TYPICAL VARIATIONS IN MILK COMPOSITION
Analyses of Morning's Milk for Five Successive Days

	Fat, percentage	Protein, percentage	Sugar, percentage
Ayrshire.....	4.09	3.25	5.41
	3.71	3.19	5.43
	4.08	3.19	5.30
	4.01	3.25	5.24
	3.94	3.19	5.08
	3.07	3.38	4.65
	2.71	3.19	5.05
Holstein.....	3.26	3.32	4.53
	3.49	3.25	4.53
	3.67	3.25	4.50
	5.54	3.51	5.11
	5.40	3.57	5.40
Jersey.....	5.11	3.64	4.66
	5.40	3.57	5.00
	5.45	3.57	5.03

Variations from Milking to Milking.—In addition to the factors discussed as responsible for variations in the composition of milk, certain changes occur from day to day because of conditions which are unknown. Table V shows typical variations of this character. All factors of feed and environment were kept as uniform as possible during the period covered by these samples. The variations, while not extreme, are noticeable and would be important in an attempt to secure a sample of milk which would be typical of the animal in question. If more animals and longer periods were included, greater ranges unquestionably would be found. These unavoidable variations suggest the importance of correct procedure in sampling, especially the desirability of having the milk samples used for testing prepared from mixed milk representing several milkings when the dairy value of a particular cow is to be judged.

Length of Interval between Milkings.—The fat content of milk secreted by a particular cow may show considerable variation from milking to milking, if the interval is varied between the milkings. The longer the interval the greater the quantity of milk and the lower the fat test. As a rule, when a cow is milked at 12-hour intervals little variation is found, although with some animals a tendency is found for a somewhat higher fat percentage in the morning milk. In practice, some dairy farmers, especially during the summer months, milk early in the morning and late at night. Under these conditions one interval may be 9 or 10 hours and the other 14 or 15, resulting in a variation in fat percentage of as much as 0.75 or 1.00 per cent. In taking samples for testing, this possibility of variation has to be taken into account. A sample from a single milking may be far from a true average. When milk is sold at retail, care also must be exercised so that mixed milk is used, otherwise dissatisfaction on the part of consumers will result. When cows are milked three or four times within the 24-hour period, the fat percentage is somewhat higher than would be the case with two milkings daily. With heavily producing cows, the added milkings also result in a considerable increase in quantity, but in case the milk production is small, no significant increase is obtained by the additional milkings. The variation due to the length of the interval between milkings appears to apply only to the fat content.

First and Last Milk.—The first milk drawn from a cow is low in fat while the last milk drawn, generally called the “strippings,” is very high. The range in fat percentage depends upon the milk yield of the particular cow; the higher the yield the greater the variation from foremilk to strippings. One of the authors found that cows producing approximately 40 pounds of milk daily yielded foremilk containing, on the average, 1.45 per cent of fat compared to 6.15 per cent in the strippings from the same cows. No difference was found in the nature of the fat or in the composition of the milk serum. The importance of a knowledge of the variation in question arises in sampling milk or in connection with methods of milking. If care is not taken to secure the strippings at the time of milking the fat percentage of the entire quantity may be appreciably lowered.

Fatness of Cow at Parturition.—It has been definitely proven that the condition of flesh of the animal at the time when lactation begins sometimes has a quite marked, though temporary, effect upon the fat content of the milk. The most noticeable results occur only when the cow is excessively fat at the time and is by nature a liberal producer of milk. A fat test covering a period as long as 7 days, if begun within a week after the birth of the calf may, under such conditions, be one-half higher or even twice the normal for the animal. Many examples could be taken from records of advanced registry showing a fat percentage varying from 5.0 to 6.0 per cent for 7 days when the average for the entire lactation period of the same animal was 3.4 to 3.6 per cent. When this abnormally high fat percentage results from high flesh of the cow, a gradual change towards the normal occurs. That point is reached in 15 to 30 days following the time of freshening. Unless these facts are understood samples for testing that give a wrong impression of the richness of the milk from a certain cow may be taken and buyers of breeding stock may be deluded regarding the merits of particular animals because of records of fat production made during this period of abnormal fat percentages.

Feed of the Cow.—It would seem entirely reasonable that the richness of the milk should depend upon the nature of the feed. Although the error of this supposition has been shown experimentally for nearly half a century, many practical cattle owners still assume it to be a fact. The fat percentage of the milk produced by any particular cow is a matter of heredity and not of

feed. As pointed out in another paragraph, variations due to climatic conditions, known as the seasonal variation, commonly, but erroneously, are attributed to the feed. It is possible by feeding a ration carrying a liberal amount of oils, for example, ground flax or ground soybeans, both of which contain large quantities of oil, to raise the fat percentage a trifle, perhaps 0.2 per cent, and with some individuals more. This is too small, however, to be of any practical significance. No experiment station investigator has found a definite means of increasing permanently the fat content to any significant extent by methods of feeding. The value of good feed and care is reflected in the yield of milk, not in the richness of the product. The proportion of other major constituents, likewise, is unaffected by the feed. The great importance of the mineral matter from the standpoint of human diet has often raised the question regarding the possible variations of these constituents from the normal. The available evidence indicates that even under extreme conditions of mineral intake with the ration the ash content of the milk produced remains normal. In the course of an investigation by one of the authors, analyses were made of milk produced by cows suffering extremely from a deficiency of phosphorus in the ration. The mineral content of the small amount of milk produced was entirely normal. Iodine added to the ration has been found to increase the amount of this element in the milk, but in this case it is not as a part of the normal mineral content. The reason for this stability in the composition of the milk is explained, in part, by the fact that it is produced from the blood and it is a well-known physiological fact that blood remains essentially the same in composition. If the ration of the cow is temporarily deficient in certain constituents, minerals, for example, the reserve of the body is used. In cases of long continued deficiency in supply, milk secretion slows up and finally ceases.

Some Effects of Feed upon Milk.—Feed does, however, have some important and well-known effects upon the milk. One concerns the yellow color. The amount of this pigment in the fat is dependent upon the amount in the feed, leaving out of consideration breed variations. Other products not normally found in milk may also come from the feed; for example, volatile oils from onions, turnips, or rape, and at times from other plants which may convey characteristic tastes to the milk or manufactured products. These substances however, are not

normal milk constituents and are dissolved only in the fat or serum.

Feed also may exert quite a pronounced effect upon the nature of the fat itself, as pointed out elsewhere. For example, fresh pasture grass results in softer milk fat and, consequently, butter that melts at a relatively low temperature. Cottonseed meal produces butter fat with a very high melting point and butter that will stand up at relatively high temperatures. Certain other feeds have more or less pronounced effects, although when fed as part of a ration it is only occasionally that special effects are noted.

Miscellaneous Causes for Variations.—A number of other less important factors sometimes are responsible for variations in milk composition. Among these are change of milkers, fright of the animal at milking time, sickness, oestrus, or the administration of drugs. The direction and extent of the variations from these causes are not constant and cannot be predicted. Sickness, for example, may result in either an abnormally low or high fat content. Frightening the animal at milking time usually lowers the fat percentage as a result of some of the richer strippings not being secured by the milker. A change of milkers often gives similar effects. At the oestrus or heat period, the composition of the milk is sometimes considerably abnormal, or it may remain constant throughout this interval. There are some reasons for suspecting that changes of a more fundamental character than variations in fat percentage may accompany oestrus, and even at times make the milk undesirable for infant food when all the milk used comes from one cow. Certain drugs may influence the fat percentage temporarily, but not without having also an unfavorable effect upon the milk yield. No means is known for increasing the fat yield by means of drugs.

General Discussion.—The difficulties encountered in securing a representative sample of milk may be appreciated when one considers the numerous factors known to result in variations in milk composition. When mixed milk is to be sampled, the variations from day to day should be much less than in the case of samples from a single animal, because a sudden variation due to some factor influencing a certain animal may be counteracted by a variation in the other direction by another factor or at least will be reduced by the larger proportion of milk not so affected. Certain factors necessarily affect an entire herd; for example,

the effect of the interval between milkings or the seasonal variations. If the majority of the herd freshens, within a short period the mixed milk, ordinarily, would show the typical changes due to stage of lactation. Where large quantities of milk are assembled from numerous herds, for example in a city milk distributing plant, the factors of breed and seasonal effect are about the only ones that can be observed in the composition of the milk which is handled. Sometimes, due to a uniformity of practice regarding time of freshening, this also may be a factor.

CHAPTER IV

PROPERTIES OF MILK

Physical State of Milk.—Milk is not only of a complex chemical nature, but, due to the various constituents, its physical nature also is very complicated. Water may be said to be a carrier or dispersion medium for the constituents of milk, and from the standpoint of the chemist, water serves as a continuous phase of liquid in which the constituents are dispersed. The chemist considers that matter exists in three general states of dispersion the limits of which have been set arbitrarily as follows: coarse dispersion, particles greater than 0.0001 millimeter; colloidal dispersion, particles from 0.0001 to 0.000001 millimeter; and molecular dispersion, where the particles are less than 0.000001 millimeter in diameter. All three of these states of dispersion are known to exist in milk.

Among the constituents of milk which are in molecular dispersion or true solution may be listed the lactose, a portion of the mineral salts, and possibly some of the lactalbumin. The proteins of milk, in general, are dispersed colloiddally through milk in finely divided particles, of which casein is the largest and albumin and globulin are the smallest. The calcium phosphate is associated with the proteins and also colloiddally dispersed. The fat of milk is the only constituent which occurs in the form of a coarse dispersion or an emulsion. In milk, water is the continuous phase and for this reason the emulsion is said to be of the fat-in-water type.

Chemical Reaction of Milk.—When milk is freshly drawn from the cow, it shows an amphoteric reaction, that is, it turns red litmus blue, and blue litmus, red. Normal fresh milk has a hydrogen-ion concentration of, approximately, pH 6.5 to 6.6, which indicates that the milk is slightly acid. When normal, fresh milk is titrated with an alkali solution using phenolphthalein as an indicator, it appears acid, showing from 0.10 to 0.26 per cent acid, if it is assumed that the acidity is due to lactic acid. It should be clearly understood that the acidity of freshly drawn milk is due to certain constituents of milk, some of which give

acid reactions (certain of the salts and casein) and some of which actually combine with the alkali. It should be clear to the student, therefore, that the true acidity of milk actually cannot be measured by titrating with a standard alkali solution. The method, however, is followed so commonly in the various branches of the dairy industry that attention is drawn to it at this point and it will be referred to again under the subject of "miscellaneous tests." The practice of titrating milk with an alkali is followed because it is known that after the acidity of milk reaches a point near 0.18 to 0.20 per cent, a large proportion of this acidity is due to the lactic acid formed by the action of bacteria on the lactose.

Specific Gravity.—Milk is a complex colloidal system in which the dispersion medium, water, contains salts and sugar in solution. It is therefore heavier than water. The specific gravity of milk from mixed herds averages 1.032. From herds it ranges from 1.027 to 1.035, and from individual cows a somewhat wider range will be found. The specific gravity of milk usually is taken at 60°F. (15.5°C.) or corrected to this point, as this is a convenient temperature at which to work in the laboratory. The specific gravity of milk is influenced by the relation of its constituents, each of which has a different specific gravity, approximately as follows: fat, 0.93; lactose, 1.666; proteins, 1.346; casein, 1.31; salts, 4.12.

The average specific gravity of the milk solids other than fat has been given by various authorities from 1.6007 to 1.638.

The specific gravity of a fluid varies with its temperature. Water reaches its maximum specific gravity at 39°F. (3.9°C.). Milk differs from water in this respect in that it does not reach its maximum specific gravity until a temperature of 31.01°F. (−0.55°C.), the freezing point of milk, is reached. As milk fat is the lightest constituent of milk, the more that is present, the lower the specific gravity will be; and in a like manner, the greater the percentage of solids-not-fat, the heavier the milk will be. The specific gravity of a fluid may be determined either by finding the weight of a known volume or by measuring the volume of a known weight. The lactometer makes use of the latter method.

The specific gravity of milk cannot be determined for at least an hour after it is drawn from the cow, owing to the air and carbon dioxide contained in fresh milk.

Taste and Odor of Milk.—Normal fresh milk tastes slightly sweet to most people and has a characteristic although not pronounced odor. The odor soon disappears when the milk is exposed to the air. A variety of tastes and odors may be found at times, but these must be classed as abnormal. Four sources of these abnormal tastes and odors may be recognized.

1. From the cow herself due to a disturbed physical condition. In this case, the substances giving the objectionable taste are secreted with the milk.

2. From the feed of the cow, in which case the odors or flavors are taken up by the blood and secreted in the milk.

3. From the absorption of pronounced odors to which milk is exposed.

4. From the decomposition of the milk constituents resulting from the growth of bacteria and other microorganisms.

Of these, the first is of the least importance as it seldom occurs. It is the exception and not the rule for the feed to affect the taste and odor. At times it becomes very important, however, even making milk unmarketable. In some localities, the cows eat wild onions or various weeds in the pastures to such an extent that it is a serious matter. Among feeds, otherwise desirable, turnips, fresh rye pasture, and, in fact, fresh pasture grass of any kind, at times produce some undesirable flavors and odors. The third source is also important at times as milk may be exposed to the air of a barn containing undesirable odors or the same condition may result when milk is stored in an ice box in close proximity to bananas or other aromatic food products. The fourth is the most common of all and the most important as flavors of this class develop in all milk sooner or later. More complete discussion of this subject is found in a later chapter.

The Color of Milk.—Milk ranges in color from a bluish-white to a golden yellow, depending upon the breed of animal, the kind of feed, and the amount of fat and solids present. In large quantities, milk appears entirely opaque while in thin layers it is slightly transparent. Milk from which the fat has been removed, or milk which is low in fat percentage, shows a bluish tint.

The white color of milk is due to the reflection of light by the dispersed fat globules, the calcium caseinate, and the colloidal phosphate. Any of these constituents when dispersed in the concentrations found in milk cause the liquid to appear "milky."

The Yellow Color—Carotene is the pigment responsible for the yellow color of milk. Carotene, closely associated with xanthophyll, is found in green plants. Carotene is yellow but its presence is overshadowed in plants by the green pigment, chlorophyll. When eaten by the animal, a portion of the carotene finds its way into the blood stream. The pigment is readily soluble in fat and a portion unites with the milk fat to give it the typical yellow color. The depth of color depends upon the amount of pigment present in the blood when the milk is secreted. The same pigment also colors the body fat of cattle to some extent. The pigment, as it occurs in the milk fat, so far as known, is identical, chemically, with that found in the plant. The proportion of the carotene, in the food, retained in the body varies to some extent with the individual animal and especially with the breed. The Guernsey and Jersey breeds produce fat with the deepest yellow and the Holsteins and Ayrshires the lightest. It is interesting to note that the animals that produce the yellowest milk fat also have the highest color in the body fat.

Some feeds are rich in carotene while others are not. For this reason certain feeds, such as green forage and carrots, tend to produce milk of a deeper yellow color than can be produced, for example, by timothy hay, white corn, or oats. This close relationship between the nature of the feed and the color of milk fat accounts for the well-known seasonal variation in the color of butter. In the spring and summer the cows generally have access to green grass, while during the winter dry feeds are fed. As a result, in the spring the butter is a deep golden yellow and in the winter, unless artificially colored, it is almost white in color in some localities.

The second pigment, lactochrome or lactoflavin occurs in solution in milk but is visible only in whey, to which it contributes a slightly greenish tint. In normal milk the lactoflavin (lactochrome) is masked by the milk constituents.

The Freezing Point of Milk.—Water freezes at 32°F. (0°C.), while milk freezes at temperatures slightly lower, the average being 31.01°F. (−0.55°C.). The range is between 31.1 and 30.9°F. (−0.50 to −0.61°C.). It is of interest to note the way in which milk freezes as compared with water. Should a bucket of water and one of milk be placed at a temperature below the freezing point of each, it will be found that the water will freeze

over the surface, while the milk will freeze on the walls of the pail, leaving a core of liquid milk in the center. It will require a very low temperature to freeze the milk completely, since about 75 per cent of it only will freeze at 14°F. ($-10^{\circ}\text{C}.$). As the milk freezes the solids become concentrated in the unfrozen portion, the water being the portion which freezes. A concentration of the solids of milk might be secured in this way.

The soluble constituents, lactose and ash, determine the freezing point of milk and are responsible for its being lower than that of water. The freezing point of water is affected by the material in solution. By the addition of salt to water, its freezing point can be reduced to exceedingly low temperatures. The fat and proteins have little or no effect on the freezing point of milk. Since the soluble constituents, lactose and ash, vary in milk so slightly, the freezing point remains almost constant. This fact makes it possible to determine whether or not milk has been watered. It has been shown that with the addition of 1 per cent (by volume) of water to milk, the freezing point rises approximately 0.0099°F. ($0.0055^{\circ}\text{C}.$). The freezing point determination is, therefore, of importance to those buying milk on the market. Care must be taken, however, that fresh milk is used in connection with the test. It so happens that an increase in acidity results in a lower freezing point. The same is true in case a preservative is added to the milk, as it would increase the materials held in solution.

Influence of Freezing on Milk.—It is interesting to note the effect of freezing, on the flavor of milk. After frozen milk has been melted to its original state, it has a diluted or watered taste. The cream line which such milk will form is much reduced as compared with the same milk not frozen. An examination of the fat globules of frozen milk, as reported by Reid, reveals the fact that they form in clumps or groups and become distorted and irregular in shape. There is a decided rupturing of the fat globules of milk when frozen, a liberation of some free fat and an apparent effect similar to that of churning. If milk is properly thawed after freezing, the effects of the freezing are less noticeable.

The manner in which cream freezes differs from that of milk, particularly when cream contains 30 per cent or more of milk fat. Cream, under these conditions, freezes more nearly as an homogeneous mass with very little if any migration of the fat or other solids toward the center.

Specific Heat.—To raise or lower the temperature of any substance a given number of degrees, a certain amount of heat must be added to or taken from the material. All substances vary in the amount of heat required, because they differ in their chemical nature and their physical state. The ratio between the amount of heat required to raise a given weight of substance to a given temperature and the amount of heat required to raise the same amount of water to the same temperature is termed specific heat. The unit of heat is known as the “calorie,” and is the amount of heat required to raise 1 gram of water from 59 to 60.8°F. (15–16°C.), that is 1°C. Since water remains the standard, however, the specific heat of a substance is the number of calories required to raise a definite amount of substance through 1° in temperature. It is commonly stated that the specific heat of a substance is the number of calories required to raise 1 gram or 1 pound of substance through 1°C. or F.

It is exceedingly important, however, to bear in mind that the amount of heat required to raise the temperature of a fluid is affected by the specific gravity, or density. Water has its greatest specific gravity at 39°F. (3.9°C.) and it is at this temperature, therefore, that the specific heat of water is taken as the standard with which other substances can be compared. It is important, however, to note the specific heat of a substance at various temperatures. Milk has a specific heat of 0.938 at

TABLE VI.—SPECIFIC HEAT OF MILK AND DAIRY PRODUCTS AT DIFFERENT TEMPERATURES

Product	Specific heat at various temperatures			
	At 32°F. (0°C.)	At 59°F. (15°C.)	At 104°F. (40°C.)	At 140°F. (60°C.)
Whey.....	0.978	0.976	0.974	0.972
Skim milk.....	0.940	0.943	0.952	0.963
Whole milk.....	0.920	0.938	0.930	0.918
15 per cent cream.....	0.750	0.923	0.899	0.900
20 per cent cream.....	0.723	0.940	0.880	0.886
30 per cent cream.....	0.673	0.983	0.852	0.860
45 per cent cream.....	0.606	1.016	0.787	0.793
60 per cent cream.....	0.560	1.053	0.721	0.739
Butter.....	0.512	0.527	0.556	0.580
Butter fat.....	0.445	0.467	0.500	0.530

59°F. (15°C.), of 0.920 at 32°F. (0°C.), of 0.930 at 104°F. (40°C.), and of 0.918 at 140°F. (60°C.). These figures are supplied by Hammer and Johnson, who report the specific heat of other milk products, as indicated in Table VI.

The differences in the specific heat of the various milk products doubtless are due to their chemical composition. At 59°F. (15°C.) the specific heat of whey is 0.976; of skim milk, 0.943; 15 per cent cream, 0.923; 20 per cent cream, 0.940; 30 per cent cream, 0.983; 45 per cent cream, 1.016; 60 per cent cream, 1.053; butter, 0.527; and butter fat, 0.467. In this case it is interesting to note that as the fat content of cream is increased the specific heat increases. With skim milk and whole milk, skim milk of a low fat content has a higher specific heat than whole milk. It is of further interest to observe that butter and butter fat containing a small amount of the other constituents of milk have a very low specific heat.

The specific heat of milk is of importance from a practical standpoint, as it is applied in measuring the cost of heating and cooling milk and milk products. Since milk and its products are perishable, it is essential that they be kept cool. The cost of cooling any product is related to its specific heat. Heat is generally expressed, commercially, in terms of the British thermal unit (B.t.u.) which is the amount of heat required to raise 1 pound of water 1°F. Thus, specific heat may be expressed in British thermal units. Since it is worked out fairly definitely as to how much fuel of different kinds is required to produce a given amount of heat, it is comparatively a simple matter for the milk engineer to calculate costs in the heating and cooling of milk and its products. The importance of these cost figures to the industry may be well understood.

Boiling Point of Milk.—Milk is slightly heavier than water, and, since the boiling point of a liquid is influenced by factors responsible for its specific gravity, milk boils at a temperature slightly above that of water. Water boils at 212°F. (100°C.) at sea level and average milk at 212.3°F. (100.17°C.). Variations in the boiling point of milk are so slight that they are of little practical importance. It is of interest only as one of the properties of milk, yet it has some bearing upon the condensing of milk in which process a portion of the water of milk is driven off in vapor. In calculating the heat required in reducing milk by boiling under vacuum, the boiling point becomes important.

The Effect of Heat on Milk.—Milk is influenced by heating in several different ways. When milk is brought to the boiling point in the air, a thin film forms over its surface. This film is due to the coagulation of a small amount of casein, with which are associated a small amount of calcium salts and, in the case of whole milk, butter fat. Should milk be slightly high in acid, it will curdle or coagulate when boiled. This property of milk is the cause of much disappointment on the part of the housewife, who, when attempting to boil milk, finds the utensil containing a cheesy mass in the place of the apparently sweet, fluid milk. In many recipes which include heating of milk to a boiling point, the housewife is instructed to add a pinch of soda to the milk before boiling. By this procedure, the acidity of the milk is reduced to a point where the milk might be boiled without danger of forming a cheesy mass. The temperature at which milk will coagulate, therefore, is closely associated with the acidity. Not only is this fact observed in the home, but it is of tremendous importance in market milk plants where milk is pasteurized by heating to 145°F. (62.7°C.) and held 30 minutes, after which it is cooled immediately. Milk must be fresh and of low acidity, or it will curdle during the process of pasteurization. In the condensary, milk not only is heated but concentrated by a partial removal of water. The result is a concentration of the milk constituents, including the acid of milk. Concentrated milk coagulates at a lower temperature, therefore, and must possess a low acidity in the fresh product.

Cause of Coagulation by Heat.—The coagulation of milk by heat is due to the presence in milk of proteins, principally casein and albumin. Casein is rather stable in milk and its coagulation is not accomplished easily in fresh milk of low acidity by the application of heat until a relatively high temperature (268 to 280°F., (131 to 137.8°C.), is reached. With increasing acidity, however, casein coagulates at lower temperatures. Albumin is coagulated more readily by heat than casein in fresh milk of low acidity; only small fractions, however, are coagulated at different temperatures under these conditions. Increase in acidity permits a more complete coagulation of albumin by the application of heat.

Mineral Balance as Affected by Heat.—Closely associated with the coagulation by heat is the mineral balance in milk. Some authors maintain that there must exist in milk a proper balance

between the calcium and magnesium, together with the citrates. Casein is most resistant to heat coagulation when it is in combination with a definite amount of calcium. Since calcium occurs in milk in combination with casein, citrates, and phosphates, a low calcium content results in an improper balance. Under such conditions, the casein of milk may be coagulated slightly by heat. Magnesium may function by replacing the calcium in the citrates and phosphates. Should there exist in milk an excess of calcium, there may not be sufficient citrate and phosphate to combine with the calcium, thus leaving an excess with the casein. The addition of citrates or phosphates to such milk results in a more stable casein by reducing the calcium content of the casein.

The above statements pertaining to the mineral balance of milk have to do with the relation of this balance to the coagulation of casein by heat. There are certain influences, however, on the salts themselves when heat is applied to milk. Closely associated with the coagulation of casein is the precipitation of the calcium salts in milk. In addition, the stability of the colloidal dicalcium phosphate is decreased, which probably causes a precipitation of phosphates.

Other Effects of Heat.—Other influences of heat on milk are its effect on the flavor and odor of the milk, the viscosity, and the fat. The most noticeable of these to the average consumer is the influence on the flavor and odor. When milk is heated to temperatures near the boiling point, it acquires a characteristic cooked taste and an odor with which everyone who is acquainted with the odors from the kitchen is familiar. This flavor and the accompanying odor probably are due to the influence of heat on the proteins and lactose of milk. A slight cooked taste and an odor often are noticeable in improperly pasteurized milk.

The influence of heating on the viscosity of milk may be one of an increase or a decrease, depending upon the temperature. The heating of milk to temperatures commonly used in pasteurization results in a decrease in viscosity, while heating nearly to the boiling point results in an increase in viscosity, where acidity may be a factor influencing to a certain extent this increase in viscosity.

The influence on the fat is physical. Fat globules tend to form in clusters. These clusters are broken up to a large extent when milk is heated. It is claimed by some workers that this breaking up of the fat clusters is responsible for the decrease in the viscosity of milk on heating. The creaming ability is notice-

ably affected when milk is heated to temperatures above 144°F. (62.2°C.), there being a decrease in the volume and a decided increase in the percentage of fat contained in the layer.

Viscosity of Milk.—Viscosity is a property of all fluids. It can be expressed only in relative terms, and, for convenience, the relative viscosity of any fluid is compared with water. Water flows with ease. Syrup pours much more slowly than water and possesses a greater viscosity. Milk is slightly more viscous than water, approximately 1.5 to 1.7 times more viscous, due to the presence of the solids in milk, some of which are in solution, others in suspension and in the form of an emulsion. All liquids appear more viscous at low than at high temperatures. Milk is no exception to this rule. Milk is quite different, however, from most fluids in that its original viscosity is destroyed, partially, under certain conditions, while under others it may be increased. The original viscosity of milk is reduced when milk is heated to temperatures commonly used in pasteurization. On the other hand, when milk is subjected to temperatures such as those reached under pressure, an increase in the viscosity of milk results. When milk is subjected to prolonged agitation the viscosity is reduced. Aging, souring, and the development of certain types of bacteria in milk are responsible for an increase in viscosity. It is conceded, generally, that the increase in viscosity is due to the changes taking place in the proteins of milk, primarily casein, which has hydrophylic properties similar to other proteins.

Practical Importance of Viscosity.—Fluctuations in the viscosity have very little relation to the marketing of milk, but viscosity is exceedingly important in the marketing of a few of the products of milk. Cream, for example, is often judged by the consumer by the way it pours. A viscous cream containing 20 per cent fat, appears to the consumer to be much richer than a thin cream of the same percentage of fat. It frequently happens that the consumer becomes suspicious that cream is low in fat content because of its low viscosity. Pasteurized cream, especially, appears thin unless it is aged for 12 to 48 hours at a low temperature. Cream aged in this manner whips with ease, while a freshly pasteurized cream may require more time before it will whip, and the whipped cream will appear watery.

Buttermilk churned from pasteurized cream is much less viscous than buttermilk churned from raw cream. It is not

uncommon to hear the complaint from the consumer that butter-milk has been watered when the viscosity simply has been reduced by pasteurization.

To secure a smooth, velvety texture in ice cream, the manufacturer develops a certain amount of viscosity in the ice-cream mixture, before freezing, simply by holding the mixture for 12 to 48 hours at a low temperature. The average consumer believes ice cream to be rich in fat if it has a smooth body, and prefers such an ice cream to one that is coarse and grainy which gives the impression that water was added.

In the manufacture of condensed and evaporated milks, it is important that they possess a certain degree of viscosity, at least, to give the impression to the consumer that large quantities of water were removed in their preparation. It should be clear, therefore, that although the viscosity of fluid milk is of little commercial importance, this property of milk is very decidedly useful in the handling of some of the other dairy products.

Measuring Viscosity.—The viscosity of fluids may be measured in several different ways, depending upon the accuracy desired. A relative viscosity may be observed simply by placing a drop of the fluids to be compared on a clean glass plate. The plate then is placed in a perpendicular position and the time required for the fluids to flow a given distance is observed. The Mac Michael viscosimeter which measures the resistance of the fluid to the movement of a solid body is far more accurate.

Adhesiveness of Milk.—Milk possesses adhesive properties which can be demonstrated easily by moistening a piece of paper with milk, and pasting it against a flat surface of wood, glass, or metal. The paper will stick very much the same as though it had been moistened with a small amount of glue. This property of milk doubtless is due to the casein of milk, which is used in rather large quantities in the manufacture of casein glue, one of the strongest glues made.

Effects of Enzymes on Milk.—Milk is subject to many changes. The complexity of its composition makes milk subject to the action of all types of enzymes which are present either in milk at the time of production, or produced by microorganisms which find milk an excellent medium in which they may grow. The extent to which milk may be acted upon by enzymes may be realized when it is stated that the proteins, fats, and sugars of milk may be decomposed completely by the action of enzymes

that act on these substances. So many by-products may be formed through the decomposition of these products that it would be difficult to attempt to name them. The protein of milk may be reduced to its simplest form; sugar may become the source of lactic acid, acetic acid, butyric acid, formic acid, alcohol, etc.; fats may be broken down into their fatty acids and glycerol, carbon dioxide and water.

One of the most interesting actions of enzymes, and one which is used commercially in the manufacture of cheese is the coagulation of the casein of milk by rennin. It has been estimated that 1 part of pure rennin will coagulate 3,000,000 parts of milk. It has been the practice for years to apply this principle in the home in making so-called "junket" with junket tablets which consist of powdered rennin.

Doubtless many off-flavors which occur in milk and milk products are linked with the formation of certain enzymes in milk. One very disagreeable defect is a bitter flavor accompanied by a rancid odor which is brought about in milk by lipase, a fat-splitting enzyme.

Effect of Acids on Milk.—The coagulation of milk is brought about readily by acidifying it. One of the first observations one might make in operating the Babcock test is the coagulation of the milk upon the addition of acid. This same change takes place normally in milk, due to the development of lactic acid. The proteins of milk, casein in particular and albumin to a minor extent, are coagulated from milk upon the addition of acid. Should the reaction be severe, however, there will result a complete digestion of the proteins by the acid. In extreme cases, the acid reaction may generate sufficient heat to result in the caramelization of some of the milk sugar.

The normal acidity of milk frequently is reduced with alkalies and it is of interest to observe under such conditions, that the coagulated casein returns to a state very similar to that in which it exists in normal milk.

CHAPTER V

MILK AND DAIRY PRODUCTS AS FOOD

For centuries, milk has been recognized as an almost indispensable food for mankind. Its value in the human diet and as a supplementary feed for animals was known for hundreds of years before it came under the scrutiny of the science of chemistry. Until within the past two decades, as the result of the early investigations in nutrition, all foods were looked upon merely as sources of proteins and of energy. In connection with nutritional studies of milk, attention was called to the fact that milk contains all the food constituents required in the human diet and in essentially the proper proportions.

In very recent years it has been clearly established that the value of milk is based upon more deeply seated fundamental facts than merely the amount of protein and energy it supplies to the body. First of all, milk supplies proteins of exceedingly high quality and of a nature to supplement, especially well, proteins in the human diet from other sources. Milk also supplies liberal amounts of calcium which is often otherwise deficient in the human diet, and third, milk is an excellent source of the vitamins necessary to health.

FOOD REQUIREMENTS

All living organisms require certain elements in order that the life processes may proceed. These elements are secured by the various forms of life in many different states, from those of the most simple to those of most complex nature. The mammal represents the highest form of life. The food requirements of the mammal include the following:

1. Water.
2. Carbohydrates and fat.
3. Protein.
4. Mineral matter.
5. Accessories to growth and health (vitamins).

Water.—The body of the mammal consists of about 60 per cent water. All tissues contain water in varying proportions.

Water serves as the carrier of food and waste to and from the cells of the body. It holds various constituents in solution and distributes the heat of the body. No animal can live without water. All foods consumed by man and animals contain water. Milk consists of a relatively high percentage of water, but such vegetables as radishes, pumpkins, tomatoes, spinach, and many of the fruits contain nearly as much or even more water than milk. The water content of a few common foods is as follows:

	Water, per cent		Water, per cent
Round steak.....	65	Peaches.....	89
Pork.....	34	Potatoes.....	78
Salmon.....	60	Turnips.....	90
Eggs.....	65	Tomatoes.....	94
Bread.....	35 to 60	Carrots.....	88
Cheese.....	37	Lettuce.....	94
Apples.....	84	Milk.....	86 to 88

Carbohydrates and Fat.—The body of the average man contains about 1 per cent of carbohydrates and nearly 15 per cent of fat. These constituents which contain carbon, hydrogen, and oxygen are essential for the animal body as a source of heat and energy. The animal body is entirely dependent on its food supply to furnish it with heat and the energy with which it may move about. Just as the steam engine requires coal or oil of a definite amount to produce a given amount of steam which is transformed into power, so the animal body requires fuel, which on oxidation results in the generation of heat and energy. Carbohydrates and fats are the principal sources of heat and energy in the body. Heat may be expressed in terms of the large calorie or the amount of heat required to raise 1,000 grams of water 1°C. (from 3.5 to 4.5°C.). The amount of heat which is supplied to the body from carbohydrates is 4.1 large calories per gram, from fats 9.3 calories per gram. In addition, proteins may supply the animal body with energy, 1 gram supplying 4.1 calories. The average man of the city requires from 2,500 to 3,000 calories per day. A man at rest may utilize but 1,700 calories a day, while a man at hard labor may require from 4,000 to 5,000 calories daily. The carbohydrates and fats may be used by the body as a source of heat and energy, or they may be stored in the body and

thus provide the body with stored heat and energy. Fat deposits serve to insulate the body and thus assist in conserving heat and energy in the body.

Source of Energy-producing Foods.—The principal sources of foods which furnish the body with a rich supply of energy include foods rich in sugars and starches. Such foods as cane sugar, potatoes, cornmeal, hominy and bread are rich in carbohydrates and supply large amounts of heat to the body. Foods rich in fat, such as nuts, chocolate, peanut butter, lard, fat pork, and sausage, may supply the body with large amounts of heat, or may be the source of fat stored in the body.

Milk contains a carbohydrate in the form of milk sugar and, in addition, contains fat and protein, thus furnishing to the body when consumed a supply of heat and energy.

Proteins.—Science has shown that animals may survive for a long period without carbohydrates or fat, but if proteins are not included in their diet, the animal will die shortly. Proteins differ from carbohydrates in their elementary composition in that they contain nitrogen in addition to carbon, hydrogen, and oxygen. Proteins may also contain sulphur and phosphorus, and some of the proteins are known to contain such elements as iron, iodine, copper, manganese, etc. Plants build their protein from the elements of the soil and air, while the proteins of the mammal are constructed from the proteins supplied from plants and other animals. Proteins are required in the body of mammals to build up the worn and new tissues of the body, to develop muscle, nerves, ligaments, skin, blood, lymph, and tendons. In addition, it is required in the bones, hair, nails, hoofs, and feathers of animals. The body of the average man contains about 15 per cent of protein. Man requires from 60 to 100 grams of protein daily along with carbohydrates and fat.

Source of Proteins.—Proteins are present in most foods, although the extent to which they occur varies materially, and few foods from plant sources supply them in liberal quantities. In general, the seed of the plant contains relatively higher amounts of protein than the leafy portions. Such foods as peas, beans, lima beans, wheat bread, and rolled oats are the principal sources from which man derives proteins of plant origin. Meats and eggs are especially valuable sources of protein for man. Milk contains several proteins and is exceedingly valuable as a food because of this fact. When milk constituents

are concentrated into such products as the various types of cheese, these products become the richest known sources of proteins for man.

Structure of Proteins.—The chemical structure of proteins has baffled the chemist for a number of years. The chemist has learned, however, that on hydrolysis proteins yield a mixture of amino acids. It is evident, therefore, that proteins are made up of various amino acids. Just how the amino acids are linked together in proteins is not clear. It has been shown however, that proteins of various sources contain widely varying amounts of the amino acids and that all of the amino acids are apparently not present in all proteins. Further, it has been demonstrated that certain of the amino acids are essential to the body growth. It has been suggested also, that certain amino acids may be essential for the building of proteins in the tissues and others for the manufacture of certain internal secretions in the body. It is known that the amino acids—lysine, tryptophane, cystine, tyrosine—are absolutely essential for normal development. To this group may also be added the amino acids, histidine and proline. It has been demonstrated by Osborn and Mendel that the protein of corn, which is known as “zein,” is deficient in the amino acids lysine and tryptophane and that animals fed corn as the only source of protein make an unsatisfactory growth. The addition of the two amino acids to the diet, however, results in growth and normal development. Thus, there is a difference in proteins according to their source. The proteins of milk are exceedingly valuable to man and animal, since they contain all the essential amino acids. In addition, it can be stated that the amounts of these amino acids in the milk proteins exceed the amounts in proteins from other sources, as eggs, the common meat cuts, and vegetables. These facts have led scientists to conclude that milk proteins are among the most valuable proteins for man.

Minerals or Ash.—Though the amount of mineral elements in the body of mammals is relatively small, it is essential that the body be supplied with these constituents. The bones of the skeleton are principally calcium and phosphorus with a small amount of magnesium; therefore, it is evident that a liberal supply of these elements must be furnished in the food for building and maintaining the skeleton. In addition to these, however, the mammal body requires small amounts of other elements,

including sodium, potassium, iron, chlorine, copper, and iodine. These elements are required for various purposes in the body, and not only must the food consumed by the mammal contain these elements, but evidence indicates that the ratio of these elements to one another is important.

Source of Minerals.—Minerals are found in most foods available to man and animals. Science has shown, however, that more attention is due the mineral constituents of the diet than has been given in years past. Foods high in protein may carry such mineral elements as sulphur, iron, phosphorus, copper, and magnesium, but these elements are not found associated with all proteins. Meat proteins supply minerals, although in relatively small amounts. Furthermore, much of the mineral content is in the inedible portions, for example, in the bones. The elements required by the body in largest amounts, as indicated in the previous paragraph, are calcium and phosphorus. These elements are best supplied to man through the leafy portions of vegetables, from fruits and milk. In addition, fruits and vegetables are an excellent source of iron, potassium, and iodine.

Milk and Milk Products as a Source of Minerals.—As indicated, milk is an excellent source of certain minerals required by the body. Attention may be directed to the ratio of calcium and potassium to magnesium and sodium in milk. This ratio as it occurs in milk resembles very closely the ratio of these same elements in the body of man. Milk contains all the essential mineral elements required by man, and milk with its products has been pronounced by nutritional experts as an excellent source particularly of calcium. Too much emphasis cannot be placed on this fact, since calcium is so essential in building the body skeleton and since it is not obtainable in a large variety of foods. Cheese has been shown to be a particularly important source of calcium in the diet of man. Fruits and vegetables eaten in liberal quantities supply to the body calcium, but the addition of milk to the diet insures the body an abundance of this mineral in quantities greater than will be found in any of the common foods.

The calcium content of milk is three times that of wheat, greatly exceeds that of corn, and is four times as great as that of human milk.

Milk is frequently criticized as being low in iron. It is true that milk is low in iron, too low, in fact, to meet the needs of the body if taken as the sole diet, but the iron of milk is readily

available to the body. The newborn is supplied with a store of iron sufficient to care for its needs until past the stage of depending upon an exclusive milk diet, hence the deficiency in this element is not considered serious. Iron is readily secured through other sources, such as the leafy vegetables and fruits. Eggs are also a very good source of iron.

Food Accessories.—In addition to the food constituents required by mammals, namely carbohydrates, fats, proteins, and minerals, certain constituents are also essential for the growth, general health, and reproduction of mammals. These essential substances for life, the chemical nature of which is not known, are termed “vitamins.” McCollum and Davis, and Osborne and Mendel, working independently with purified foods, found that butter fat or the ether extracts of butter fat or egg yolk, contained substances essential for growth. This substance became known as vitamin A or fat-soluble A. Since the work of these men, other vitamins have become recognized; namely, vitamin B, vitamin C, vitamin D, vitamin E, and vitamin G.

Vitamin A.—This vitamin is essential in the diet for the proper growth of the mammal. If the vitamin is lacking in the diet, the animal or man is susceptible to infection of the lungs, eyes, ears, sinus, and at the base of the tongue. Xerophthalmia, a disease of the eyes, is so commonly associated with a lack of vitamin A that vitamin is frequently referred to as the “antixerophthalmia” vitamin. Although the vitamin was first observed as present in milk fat and egg yolk, it is known to be present in even greater amounts in cod-liver oil. Such foods as the green leaves of plants are an excellent source of vitamin A for growing animals. The vitamin is secured in liberal quantities by man from such foods as milk, butter, cheese, and other dairy products, and from such vegetables as spinach, carrots, and tomatoes. It is secured to a moderate degree from many other vegetables, meats, and fruits. So far as known, vitamin A is a plant product and for this reason the amount in milk is dependent upon the supply received with the feed. Milk has the greatest vitamin A content when the animals are receiving fresh pasture grass or carefully cured legume hay.

Vitamin B.—The absence of this vitamin stunts the growth of the animal and results in such diseases as beriberi in man and polyneuritis in birds. The vitamin is frequently referred to as the “antineuritic vitamin.” Vitamin B is found more gener-

ously distributed in the common food materials than is vitamin A. It is found in milk and its products, the seeds of many plants, particularly in the embryo portion, in many fruits and vegetables. Its principal source for man is the cereals made of the whole seed, whole-wheat flour, egg yolks, and milk. The vitamin is also present in yeast. The vitamin B content of milk is at least partly dependent upon the amount supplied by the feed of the cow. There is evidence, however, that vitamin B is also synthesized by bacteria in the rumen of the cow, and from this source a portion of that found in the milk may be derived.

Vitamin C.—When vitamin C is lacking in the diet of an animal, such as the guinea pig, it will grow for about 2 weeks, then lose weight and die of scurvy. All animals are not affected in this manner, but are not immune. The vitamin is sometimes referred to as the “antiscorbutic vitamin.” It is available to man through fresh vegetables, fruits, and milk. The vitamin is destroyed by the application of heat to the extent commonly used in the pasteurization of milk, and for this reason when pasteurized milk or milk products are used in the diet, vitamin C should be supplied in the ration through other sources, such as oranges or fresh tomatoes. The vitamin C content of milk is apparently increased when cows are permitted to graze on good pasture; however, the evidence available to substantiate this statement is somewhat conflicting.

Vitamin D.—This vitamin is also closely associated with vitamin A and influences the growth of the animal in much the same way. Vitamin D, however, has the special property of preventing rickets and favoring the normal deposition of calcium and phosphorus salts in the growing bones. This vitamin is especially abundant in cod-liver oil but does not appear to be so widely distributed as the other vitamins. Although present in milk the amount is relatively small. It has been established that sunlight may take the place of vitamin D as an antirachitic factor.

In recent years, the vitamin D content of milk has been increased either by the feeding of irradiated yeast to the cow, direct exposure of milk to ultra-violet light, or the addition to milk of concentrates exceedingly rich in the antirachitic factor. This is a palatable and readily accepted source of this vitamin.

Vitamin E.—A vitamin designated as E is known to affect the fertility of animals, and thus becomes a factor influencing repro-

duction. Vitamin E is apparently present in fatty foods, including butter fat, the wheat germ, whole wheat, lettuce, meat, rolled oats, and dried alfalfa.

Vitamin G.—Growth, general health and well-being of people of all ages are influenced by vitamin G which also prevents pellagra, a serious disease due to faulty nutrition. Milk is an exceptionally rich source of this vitamin, whether it is whole, skimmed, evaporated, or dry milk. The heat treatment of milk does not appreciably affect this vitamin.

REQUIREMENTS OF A SUITABLE FOOD

The mere presence in a food of the food constituents discussed does not render a food entirely satisfactory to man. Certain other requirements which should be considered in the selection of food materials may be set forth as follows:

1. Man requires that a food be palatable.
2. Man requires a clean, wholesome food.
3. Man requires foods which are digestible.
4. Man requires economical foods.

Palatability of Foods.—One of the first requirements of a food is that it be palatable. A food should be relished and enjoyed by a given individual, if it is to be included on his menu. Milk is liked by most people. Its flavor is one which is enjoyed. In addition, milk is easily flavored with many flavoring materials and can be made palatable very readily for those who do not care for it in its natural state.

Cleanliness of Food.—Food must be clean if it is to appeal to the average person. A clean, wholesome food attracts the attention and creates a desire. Milk for direct consumption can be produced under very sanitary conditions and thus meets this requirement.

Digestibility of Foods.—Though it is essential that the various food constituents be present in a given food, it is also important that these constituents be present in such a form as to be readily utilized by the body. The proportion of each food constituent of a given food which is utilized by the body is frequently expressed in terms of percentage. An enormous amount of work has been conducted in determining the value of the various foods available for man and animals.

The percentage of the various food constituents of milk which are digestible is high. In fact, it is possible for certain individ-

uals to utilize as much as 98 per cent of the protein of milk, and 99 per cent of the carbohydrates and fat. The digestibility of proteins is given by various authorities as between 80 and 100 per cent. Some give the digestibility of animal proteins and milk as 90 to 100 per cent; proteins from cereals, fruits, or vegetables 80 to 90 per cent; and proteins from legumes as 80 per cent or lower. In addition to the digestibility of proteins, attention should be directed to the differences in the composition of proteins from various sources. All proteins do not contain the essential amino acids; however, milk proteins are extremely valuable from the standpoint of their amino-acid content.

Economy of Milk as Food.—The particular foods that make up the diet of a family depend upon a number of factors, the most important of which are food habits, availability, palatability, desirability from the standpoint of health, and economy in cost. Interesting and valuable information may be obtained concerning the economy of milk by comparing the relative cost of food constituents in milk and dairy products with other common foods. The difficulty that at once arises, however, is that food values can not be expressed in any one term. This is more particularly true of milk. Certain foods are purchased primarily for a certain class of constituents. Thus, bread is an excellent and cheap source of carbohydrates; lard, of fat, and certain meats, of protein. These foods do not furnish any considerable quantity of other constituents. In contrast, milk contains constituents of all classes needed by the body. It manifestly is not fair to compare milk with bread as a source of energy, with lard as a source of fat, or with lean meat as a source of protein.

Milk as a Source of Protein.—A serious difficulty that arises is the fact already explained that milk protein is far more valuable than that of vegetable origin; for example, that from cereal grains or legumes such as beans or peas. This difference is connected with the nature of the amino acids.

From analyses of foods it is easily possible to prepare a statement as given in Table VII taken from *Circular 235*, Illinois Experiment Station.

The figures given in this table merely show the amount of the food in question necessary to equal in protein and in total energy the value of a quart of milk containing 4 per cent of fat. In 6.3 ounces of sirloin steak, for example, is found protein equal in amount to that found in a quart of milk, but 11 ounces of

TABLE VII.—WEIGHTS OF FOODS NECESSARY TO YIELD AN AMOUNT OF PROTEIN AND ENERGY EQUIVALENT TO 1 QUART OF 4-PER CENT MILK

	Amount of protein, ounces	In total energy, ounces
Sirloin steak.....	6.3	11.0
Round steak.....	5.4	16.2
Pork chops.....	7.8	8.6
Ham, lean smoked.....	6.0	9.8
Fowl.....	7.6	14.0
Eggs.....	4.4	8.9
Halibut steak.....	6.8	23.0
Mackerel, salt.....	6.4	10.5
Salmon, dressed.....	7.6	18.2
Whitefish.....	9.9	33.6
Full cream cheese.....	3.1	5.4
Cottage cheese.....	5.0	21.2
Dry beans.....	4.7	6.7
Baked beans.....	15.2	18.0
Dry peas.....	4.2	6.5
Canned peas.....	29.0	42.0
Rolled oats.....	6.3	5.8
Peanut butter.....	3.6	4.2

the steak are required to supply an equal amount of energy. Comparisons are not given in terms of money value on account of the fluctuations in prices from one locality to another and from year to year. By using local prices, a fair comparison may be readily obtained. For example, if ham costs 40 cents per pound and milk 14 cents per quart, 6 ounces of ham costing 15 cents will supply the same amount of protein as 14 cents will buy in the form of milk. To obtain an equivalent amount of energy in ham, however, an expenditure of 34 cents will be required. Milk is usually a relatively cheap source of protein compared with other foods supplying proteins from animal sources such as eggs, meat, and fish.

Milk as a Source of Energy.—All of the solids of milk except the ash serve the body as sources of energy. The fat has a caloric value per unit about double that of protein or sugar and in average milk the aggregate is nearly equal to that of the sugar and protein together. A comparison can be readily made between the energy or caloric value of milk and other foods as

presented in a statement from *Extension Circular 63*, University of Minnesota.

ONE PINT OF MILK—337 CALORIES—AND ITS ENERGY EQUIVALENT IN
OTHER FOOD MATERIALS

Food Materials	Weight, Ounces	Food Materials	Weight, Ounces
Skimmed milk.....	32.4	Bananas.....	18.7
Cream.....	6.1	Prunes.....	4.6
Cabbage.....	45.0	Bread.....	4.6
Onions.....	27.0	Rolled oats.....	3.0
Sugar.....	3.0	Rice.....	3.4
Honey.....	3.6	Bacon.....	1.9
Potatoes.....	17.7	Round steak.....	6.2
Grapefruit.....	35.0	Eggs.....	9.0
Peanuts.....	2.9	Butter.....	1.6
Apples.....	25.3	Cheese.....	2.7

It appears from the above calculations that 1 pint of milk containing 337 calories is equivalent to 17.7 ounces of potatoes, 25.3 ounces of apples, 4.6 ounces of bread, 9 ounces of eggs, and 3 ounces of rolled oats.

A common method which has been used in comparing foods is to determine the number of calories that can be purchased for a given amount in a food at the prevailing market price. On this basis, milk is not found to be the cheapest source of energy. This position is usually held by the cereal products including oatmeal, corn meal, and bread. Milk, however, supplies calories more cheaply than many other foods, especially meats and eggs, fruits, and usually the vegetables.

Relation of Richness of Milk to Food Value.—On account of the variations in composition due to the breed of animals, milk as offered for sale may contain anywhere from 3.00 to 5.50 per cent of fat. As pointed out elsewhere, a variation in fat percentage also means a variation in the proportion of other constituents, although not in the same proportions. The question of the food value of milk as affected by the fat percentage often arises. A family may be offered milk at 12 cents a quart from one source and for 16 cents from another; the only apparent difference being in the fat percentage. Is the higher price justified?

A definite answer to such questions is difficult, but help in solving the problem may be had from the data given in Table VIII. Information should first be secured regarding the average

fat content of the milk from the two sources. Perhaps the milk offered at 12 cents would contain, approximately, 4.00 per cent fat and that offered at 16 cents, 5.00 per cent fat.

Milk containing 4 per cent fat, as shown in Table VIII, contains 29.7 grams of protein per quart while 5 per cent milk contains 35.4 grams. Solving this simple problem in proportion will show that the 5 per cent milk on a protein basis would be worth 14.3 cents per quart. As a source of energy, the proportion would be between 660.6 and 777.8 and would indicate a value of 14 cents for the 5 per cent milk in comparison with 12 cents for the 4 per cent product. If the richer milk sells for 16 cents, compared to 12 for the 4 per cent grade, the price must be partly justified in other ways than by food value; for example, by better sanitary conditions or better service. The tendency on the part of the public is to undervalue the richer milk. In the retail milk trade,

TABLE VIII.—RELATION OF RICHNESS OF MILK TO FOOD VALUE¹

Percentage	Food substance, per quart, grams	Calories, per quart	Total calories, per quart
3 per cent fat:			
Fat, 3.00.....	29.3	263.8	
Protein, 2.64.....	25.9	103.5	
Sugar, 4.60.....	44.9	179.6	546.9
4 per cent fat:			
Fat, 4.00.....	39.0	351.2	
Protein, 3.04.....	29.7	118.9	
Sugar, 4.88.....	47.6	190.5	660.6
5 per cent fat:			
Fat, 5.00.....	49.3	443.9	
Protein, 3.62.....	35.4	141.5	
Sugar, 4.92.....	48.1	192.4	777.8
6 per cent fat:			
Fat, 6.00.....	58.0	522.3	
Protein, 3.92.....	39.0	156.0	
Sugar, 4.88.....	47.7	190.6	868.9

¹ Adapted from *Circ.* 235, Ill. Exp. Sta.

it is difficult to obtain the 2 extra cents per quart for 5 per cent milk which is justified by the higher food value.

Milk for the Growing Child.—Milk is generally recognized as an excellent food for the growing child. Since milk contains

all of the food constituents, namely, carbohydrates, fat, proteins, and mineral matter in about the proportion which the growing child requires, it has been frequently referred to as a "perfect" food. In addition, milk is rich in mineral salts, particularly calcium, which is so vital in the development of the growing skeleton of the child. Doctors and dentists recommend milk in the diet of children and not infrequently nutrition experts recommend that the growing child should have included in its diet 1 quart of milk daily. In addition to the food constituents, milk is known to contain all of the vitamins essential for growth, health, and reproduction.

These are not the only reasons, however, for including milk in the diet of the child, particularly the infant. The constituents of milk are highly digestible, palatable, and require little preparation. The infant requires milk either from its mother or from other sources, but frequently in certain cases it is essential that milk be slightly modified for infant feeding.

The degree of softness of the curd resulting from coagulation is also important in infant feeding. It has been found that some cows produce milk which gives a softer curd than others, and that the softer curd is more easily digested than the firmer curd. Consequently, there has been a special selection of "soft curd" milk for the use of infants or invalids or the treatment of ordinary milk in such a way that a softer curd results.

Milk for the Adult.—Milk is an excellent food for the adult as well as for the growing child. It should be clear, however, that in the case of the adult it is not possible to secure as large a proportion of the total nutrients required as in the case of the infant or the growing child. Milk contains too much water to serve as the major portion of an adult's diet. It would require 8 to 11 pounds of milk daily to furnish the nutrients required by an adult. In addition, milk is too high in protein for the average adult, and the solid material is too concentrated. The digestive system requires some foods which are relatively high in fiber for proper development even in the growing child. A mixed diet is to be recommended. In the diet, however, milk should be included for both the growing child and the adult.

FOOD VALUE OF OTHER DAIRY PRODUCTS

In the foregoing discussion pertaining to the food value of milk, little has been stated in reference to the food value of milk prod-

ucts such as skim milk, cheese, butter, and concentrated milks, including condensed and dry milk.

Butter.—Butter differs from other dairy products in that it is a highly concentrated fat food and contains very little of the other milk constituents. Butter contains between 81 and 84 per cent of butter fat, a small amount of salt, and less than 1 per cent of protein. It is evident, therefore, that butter is chiefly a source of energy, supplying, when of average composition, 3,410 calories per pound. In addition, however, butter is an excellent source of vitamin A and is frequently mentioned by experts in nutrition as the chief source of this vitamin in the diet of the average American. A small amount of vitamins D and E are present in butter; however, it is lacking in vitamins B and C. Butter is not generally an especially cheap source of calories. Its palatability and vitamin A content, however, fully justify its wide use.

Cheese.—Most of the large varieties of cheese manufactured consist of a concentration of the milk solids of milk, chiefly casein, and butter fat. The food value of cheese depends on the proportion of water retained with these solids. Cheese may largely replace meat in the diet. It is the cheapest source of animal protein adapted for human food. In addition, cheese is an excellent source of calcium, phosphorus, and sulphur and is fairly high in iron.

Ice Cream.—The food value of ice cream varies with its composition; however, all the constituents of milk are present in a concentrated form. Where milk contains between 86 and 89 per cent of water, ice cream contains between 60 and 68 per cent of water. In addition, ice cream contains added sugar. To ice cream may be added such materials as eggs, gelatin, fruits, nuts, chocolate, and bakery products, all of which add to its food value. It is evident, therefore, that ice cream contains a rich supply of the food nutrients.

Concentrated Milks.—Dry milk and condensed milk contain all the food constituents of milk in a highly concentrated form. The food value of these products depends on the extent to which they are concentrated. If water equal to that removed be added to these products, the result is a milk with essentially the same constituents and food value as the original product.

Skim Milk.—Skim milk contains all the solids of milk excepting the butter fat. The water and milk solids-not-fat content of skim milk are present in very nearly the same proportion as they

occur in milk. Since skim milk contains but a fraction of a per cent of butter fat, the vitamin A content is low. Skim milk is known to be an excellent source of animal protein of high quality, however, and of the minerals, calcium and phosphorus. In addition, skim milk contains about the same proportion of lactose as is found in whole milk. As a feed for young growing animals, therefore, skim milk is excellent. Not infrequently skim milk is considered an inferior food for man, primarily because of its cheapness. So far as its food value is concerned, it is equally as valuable as whole milk from which it is derived, with the exception of its lack of butter fat. It is, therefore, an excellent and inexpensive source of milk protein and mineral elements for man. When included in the diet of growing children, care should be taken to insure the child an adequate supply of vitamin A from other sources, such as butter.

Buttermilk.—The composition and food value of buttermilk are comparable with skim milk with the exception that it may contain slightly more butter fat. Due to the decomposition of lactose by bacteria, buttermilk frequently contains from 0.2 to nearly 1 per cent of lactic acid. The presence of lactic acid in buttermilk is not harmful and may be beneficial.

Fermented Milks.—The food value of fermented milks is equivalent to that of the whole or skim milk from which they were prepared. These products depend upon the action of microorganisms for their desirable characteristics. The principal product formed in the fermentation is lactic acid. Most of the fermented milks are considered to be especially healthful. Some of them contribute desirable types of bacteria which establish themselves in the lower intestines. They compete with the undesirable putrefactive bacteria which ordinarily predominate along the intestinal tract and which produce toxic products. When lactose is available either from the milk or by direct addition in the diet, the desirable types of bacteria gain the ascendancy and dominate the fermentation, which becomes an acid, rather than a putrefactive, type of fermentation.

CHAPTER VI

MICROÖRGANISMS

THEIR NATURE AND GROWTH REQUIREMENTS

The dairy industry is vitally concerned with minute, living cells which are called "microorganisms." Nearly all of the changes which take place in the taste, odor, or appearance of milk, after it comes from the cow are the result of the activities of these organisms. Such common phenomena as the souring of milk or the formation of characteristic flavors in cheese are to be attributed to their action. The methods employed in the care or handling of milk or its products are directed largely towards the control of these microorganisms. An understanding of the changes which take place in milk or other dairy products is impossible without some knowledge of these organisms and the conditions which affect their growth.

The microorganisms which are most important in dairying are the bacteria, yeasts, and molds. All of these are members of the plant kingdom, and belong among the fungi; that is, they are plants without chlorophyll, the green coloring matter of higher plants.

Bacteria.—Bacteria are microscopic, unicellular fungi which occur principally in the form of spherical, cylindrical, or spiral cells, and which reproduce by transverse fission. In dairy products, the spherical and cylindrical forms are predominant.

Distribution.—Bacteria are found nearly everywhere in nature. They are prevalent wherever organic matter is available as a source of nourishment. They are found in tremendous numbers in the soil, sewage, decaying plant or animal substances, etc. Some are present in the air which one breathes, the water which one drinks and on the clothes which one wears.

Size.—Bacteria are so minute that they are visible only with the aid of a microscope. The unit of measurement is a micron, which is equal to 0.001 millimeter or 1/25,000 of an inch. The spherical type seldom has a diameter greater than 1 micron. There is greater variation in the size of the cylindrical types.

There are some which measure 0.2×0.5 micron while others may be 40 to 60 microns in length and 3 to 6 microns in width. The majority, however, are about 1×2 microns in dimension. It is estimated that 50 of these would be required to equal the thickness of ordinary writing paper.

It is not difficult to understand that large numbers of these cells may be present in a substance like milk without occupying an appreciable space. A milliliter (cubic centimeter) of milk may contain millions and even billions of bacteria. It has been estimated that approximately 16,000,000,000 average-sized

FIG. 14.—Photomicrograph showing rod forms of bacteria. Magnified 1,475 times.

bacteria would be required to balance a weight of 1 milligram (0.001 gram).

Cell Structure.—The bacteria are unicellular, which means that they are individual, single cells, each capable of pursuing its physiological processes independently. The cell consists of a rather well-defined mass of clear, colorless protoplasm without the demonstrable nucleus which is found commonly in most living cells. The individual cells may be united into pairs, chains, or clusters, but each cell retains its independent functions. Such groupings are to be attributed largely to physical forces. In certain forms, the surface of the cell becomes covered with a sticky, gum-like film which is called a “capsule.” It will be

explained later how such a condition may be responsible for a particular physical change in milk, known as "ropiness."

There are also some bacteria which, in the presence of inimical substances, in the absence of essential foods, or under unsuitable physical conditions, may concentrate their cell contents into a thick-walled structure designated as a "spore." This spore is very resistant to desiccation and heat. It makes possible the preservation of the bacterial life under circumstances which ordinarily would mean destruction. This phenomenon has some important practical significance, as will be seen in subsequent pages, particularly in relation to pasteurization.

FIG. 15.—Photomicrograph of the spherical type of bacteria. Magnified 1,475 times.

Motility.—When viewed under the microscope, all bacteria, when in liquids, show a vibratory motion which is known as the "Brownian movement." Some types, however, show a true motility, that is, the ability to move from place to place independently. They are able to swim about freely with the aid of hair-like projections or cilia which are termed "flagella." This arrangement allows for a change in position in the search for suitable food supplies or a favorable physical environment.

Reproduction.—There are apparently no sexes in bacteria. The cell reproduces itself merely by a division across the center, thus forming two cells from the original one. This multiplication, by division, accounts for the extremely rapid reproduction of which the bacteria are capable. Soon after the division occurs, each individual assumes approximately the size and shape of the

parent cell. Maturity is almost simultaneous with the separation. Thereafter, each cell may divide again, independently. Thus the next generation will consist of four cells. This process continues in the form of a geometrical, rather than an arithmetical, progression. Under favorable conditions, a new generation may be produced in a period of half an hour. Consequently, if the reproduction of a single cell were to continue at this rate for 24 hours, the progeny of this original mother cell number several millions. If nothing were done to check such development, in the course of a few days there would be formed a mass of bacteria

FIG. 16.—Photomicrograph of yeast cells. This shows their characteristic oval shape. Magnified, 1,475 times.

greater than the earth itself. Obviously, such a result is not possible, because of natural conditions which check this development before it reaches such proportions. Nevertheless, the rapidity with which bacteria may multiply in a favorable medium such as milk becomes a matter of concern of the greatest importance. This will be discussed more in detail in the following pages.

Yeasts.—Yeasts are also microscopic, unicellular, non-chlorophyll-bearing plants but usually are somewhat larger than bacteria and with the cell constituents more highly organized. A definite nucleus may be observed. The method of reproduction is entirely different, however. It may take place through the process of budding in which a portion of the protoplasm forms a slight protuberance on the mother cell and gradually develops into maturity whence it becomes an independent cell, or by the formation within the mother cell of reproductive spores each of

which may give rise to a new yeast cell. The yeasts are not so important as bacteria in dairying but do enter into some of the common fermentations and will be mentioned in later discussions.

Molds.—The term “mold” is used, popularly, to designate a considerable number of lower fungi, which are much more complex than bacteria and which more nearly resemble the higher plants. Molds are multicellular forms, the individual cells of which are not visible to the naked eye. At maturity, however, they may be observed readily as a mass of branching, radiating, or interwoven threads.

FIG. 17.—Photomicrograph of a mold (*Oospora lactis*) commonly found in milk. The conidia or spores of the mold are pinched off at the ends of the various branches. The photograph shows many of these oval or cylindrical conidia. Magnified 735 times.

The most common type of reproduction is by means of fruiting bodies which often are brightly colored, and which produce myriads of conidia, or spores, which are disseminated widely. Each of these spores is capable of establishing a new vegetative phase of the mold's life cycle under favorable conditions. Other asexual and sexual methods of reproduction also appear. The group is so complex that it is not practical to discuss it in detail in this text. The molds are of considerable importance in cheese-making and are responsible for some defects of butter and other products. These considerations will be introduced elsewhere.

The Naming of Microorganisms.—Anyone who reads the technical literature on dairying often will be confronted with the scientific names used to designate the particular species, genus, etc. to which a microorganism belongs. It is not possible to

discuss in detail the actual classifications of bacteria, yeast, and molds nor to mention many of the genera or species. The names are derived from many sources and languages, but according to custom and international agreement, are given a Latin termination. One ordinarily finds an organism designated in the literature by a combination of a genus and species name, for example, *Streptococcus lactis* (the common milk-souring type of bacteria), where the first part defines the genus, and the second the species. Each portion has a particular significance in the system of classification.

Some of the genus names of bacteria which may appear commonly in the literature are: *Streptococcus*, *Micrococcus*, *Sarcina*, *Bacillus*, *Bacterium*, *Pseudomonas*, *Lactobacillus*, *Escherichia*, *Aerobacter*, *Spirillum*, etc. Genera of yeasts may be encountered such as *Saccharomyces*, *Torula*, *Mycoderma*, etc. Among the more common genera of the molds will be noted *Penicillium*, *Oospora*, *Aspergillus*, *Mucor*, *Monilia*, *Alternaria*, *Fusarium*, and many others.

This merely indicates that there is an attempt to systematize the naming of microörganisms so that they may be catalogued in convenient, orderly classifications useful to all scientific workers of the world. Each microörganism is given a definite place in this scheme of classification depending upon its special characteristics which differentiate it from all others.

THE GROWTH OF MICROÖRGANISMS

The alterations, in the physical or chemical properties of milk or its products, which are to be attributed to microörganisms, do not occur because of the mere presence of the organisms but result from the activities of the individual cells during the period of their development and reproduction, or from substances produced during such activity. Wherever microörganisms have had an opportunity to grow in a nutrient material, a modification of that substrate, primarily of a chemical nature, must be expected. Simultaneously with the change in chemical constitution, a transformation in the physical properties of the environment may occur. Such changes take place in milk and dairy products as the result of the growth of microörganisms. The growth of microörganisms is influenced by the following factors: (1) food supply, (2) moisture, (3) atmosphere, (4) chemical and physical environment, and (5) temperature.

Food Supply.—Every living cell requires a source of energy to maintain its life processes and elements for the formation of its cell substance. The food requirements of a microscopic plant are extremely small, quantitatively, but, nevertheless, are exacting from the standpoint of quality. Carbon, oxygen, hydrogen, nitrogen, phosphorus, and sulphur are essential. They may be obtained from such compounds as proteins, fats, and carbohydrates or their constituent parts. These exist in milk or its products in abundance and in a variety of forms. Mineral elements, other than those mentioned, are also necessary in minute quantities for the development of the cell, especially potassium, calcium, sodium, magnesium, manganese, iron, and chlorine.

In general, it may be said, that there is to be found, in practically all dairy products, an adequate supply and variety of food elements, quite sufficient to meet the demands for nourishment made by most microorganisms. As far as the food supply is concerned, there is no reason why growth should not proceed without interruption in milk or dairy products.

Moisture.—The nutrition of the microorganism is accomplished by the acquisition of the food elements from an aqueous solution. Consequently, water is an absolute requirement. Microorganisms find the optimum condition for growth when the foodstuff and the atmosphere are saturated with moisture. When the concentration of water in the nutrient material falls below 30 per cent, there is usually a retarded growth of the cells. This condition is evident in several dairy products. Certain types of condensed milk are concentrated so much by the removal of water that only 25 to 26 per cent of moisture is left in the final product. Microorganisms do not grow very well under these conditions. Dry milk, which seldom contains more than 5 per cent of water, owes its well-known stability in storage to the lack of moisture which prevents the growth of microorganisms. In contrast with these conditions, fluid milk and cream contain abundant moisture, so that growth is not retarded in them because of a lack of water. The dehydration of many other food stuffs, such as fruits and vegetables, makes possible their preservation without refrigeration.

The molds, particularly, are susceptible to the humidity of the atmosphere. When the air is saturated with moisture, their growth is more active than it is at low humidities where it may be

checked. This fact is very important in a practical way, as will be pointed out later in connection with the molding of butter and cheese. The bacteria and yeasts are more dependent upon the moisture in the substrate than upon that in the atmosphere.

Atmosphere.—Certain types of bacteria can grow only where there is an unlimited supply of oxygen, while others cannot develop at all if traces of free oxygen are present. Between these two extremes, however, will be found a range of oxygen concentration which will satisfy the majority of bacteria. For example, the milk-souring bacteria are able to grow where there is either an abundance or a scarcity of oxygen. Yeasts are, for the most part, able to adjust themselves to modifications of either the absence or presence of free oxygen. Molds, on the contrary, grow best in an atmosphere rich in oxygen. For this reason, they are to be found most frequently on the surface of milk, butter, etc., or in fissures such as may be found in certain cheeses where air is available.

As far as milk and its products are concerned, either condition, *i.e.*, presence or absence of oxygen, may be found. There are plenty of organisms, ordinarily present in milk, that are able to thrive under one or the other of these conditions, or both, so that it is seldom a factor of very great importance in fluid milk and cream.

Chemical and Physical Environment.—Certain bacteria are decidedly sensitive to the presence of strong acids or bases. Most of them prefer a medium which is nearly neutral in reaction. If considerable acidity appears in the substratum, either by the action of microörganisms or through the addition of acids, most bacteria are impeded in their growth. As an example, it will be found that the ordinary milk-souring bacteria are inhibited after the acidity which they have produced has reached approximately 1 per cent. It has been observed that the presence of acid in certain cheeses checks the growth of undesirable types of organisms. Excessive quantities of basic substances in a substrate also retard development although this condition seldom occurs in food products.

Yeasts and molds usually grow best on acid media and often initiate their growth after the acidity has become concentrated sufficiently to check bacterial growth. It may be observed that a sour milk or cream will show a heavier growth of mold on its surface than will a sweet cream of the same age.

Preservatives.—Microorganisms are susceptible to the action of certain chemicals which either check growth or destroy the organisms outright. There are many substances of this sort, which are usually termed preservatives, antiseptics, disinfectants, germicides, etc. The preservation of composite milk or cream samples by the addition of bichloride of mercury (corrosive sublimate) is an example of this action. This substance kills the microorganisms. Consequently, no souring or decomposition takes place in the sample because there is no growth of the bacteria ordinarily responsible for spoilage. Formalin, boric acid, borax, benzoic acid, salicylic acid, hydrogen peroxide, and other chemicals have been used at one time or another for the purpose of prolonging the keeping quality of milk sold for human consumption. This practice is reprehensible as well as unlawful. The use of various chlorine preparations for the sterilization of dairy equipment, milk bottles, etc., is a legitimate application of the principle of chemical preservation or sterilization. In this case, there is no direct addition of the chemicals to milk. Furthermore, chlorine solutions will not destroy the microorganisms in milk unless they are present in such large quantities that the milk itself is changed so much in flavor or appearance that it would not be accepted as food.

Light.—The majority of microorganisms grow best in the dark. Light is more or less harmful. Bright light, natural or artificial, has a tendency to check or destroy them. Direct sunlight, unobstructed by ordinary glass, is rapidly destructive. The ultra-violet rays in this connection are the most lethal. They have been utilized for the sterilization of milk but the attempt has not been successful because some of the amino acids of milk apparently absorb the rays before they can exert a destructive effect upon the microorganisms. Dairy products are seldom kept in the bright light because it is known that light accelerates chemical changes, which are detrimental to the product. Consequently, light is not a very practical agent for checking the growth of microorganisms in milk.

Electricity.—A direct or alternating current of electricity in itself does not appear to have a destructive effect upon microorganisms. Methods for pasteurizing milk by electricity are in use at the present time but they depend principally upon the increase in temperature to exert the destructive effect. The resistance offered by milk to the passage of an electric current is

sufficient to raise the temperature to a point where bacteria are destroyed. The electricity may also cause the production of chemical compounds which, in turn, may exert a restraining or germicidal effect.

Thunder Storms and the Souring of Milk.—A familiar myth has been handed down from generation to generation that a thunder storm sours milk. Supposedly, the thunder and lightning exerted some mysterious power to bring about this change. Fortunately, there is no truth in the myth based upon the action of the thunder or the lightning themselves. Otherwise, many milk dealers in the large cities would be bankrupt. Generally at the time a thunder storm occurs, and some time before, the temperature is unusually high. If milk or cream happens to be stored under conditions that permit an increase in the temperature of the products, the growth of the milk-souring bacteria will be accelerated and the milk or cream may sour because of this more rapid growth and not because of the action of the thunder or lightning. Milk or cream absolutely free from microörganisms or kept at temperatures below those favorable for the growth of microörganisms will not sour during a thunder storm.

Concentration of Nutrient Solution.—Where there is a marked difference between the concentration of the solutions surrounding microörganisms and that of the cells themselves, the effect of osmotic pressure may bring about conditions which check growth or destroy the cells. An illustration of this phenomenon may be found in sweetened condensed milk. As mentioned previously, bacteria do not grow well in such a product, partly because of a lack of moisture. The main reason, however, lies in the fact that cane sugar is added to the condensed milk so that the product contains about 40 per cent by weight of this substance. This yields a thick syrup, especially with the concentration of the milk solids, much more concentrated than the cell substance. As a result, water is drawn from the cell to equalize the pressure. The cell substance shrinks and growth is checked. A strong brine may also affect the osmotic pressure and cause similar results. This is a partial explanation of the effect of salt in retarding the growth of microörganisms in butter and other products where certain organisms are checked by its action.

Temperature.—It has been pointed out that milk and dairy products provide an almost ideal food for the growth of most microörganisms. Adequate moisture is furnished in most cases,

notably in milk and cream. The atmospheric conditions are not, as a rule, unfavorable. The chemical or physical environment seldom is disturbing in the products intended for food. It follows that in the majority of dairy products conditions are exceptionally conducive to the growth of microorganisms, providing the principal factor, temperature, is satisfactory for cell development.

Different species of microorganisms vary in regard to their relation to temperature. For example, some common molds grow freely at a temperature so low that the bacteria which commonly sour milk will show scarcely any development. Each species has its optimum, maximum, and minimum temperature for growth. So sensitive are microorganisms to temperature that their growth, and, consequently, the changes which they bring about in the particular dairy product concerned may be checked or accelerated by the control of the temperature. The farmer cools his milk to retard bacterial fermentations, souring principally, in order that the milk may reach the consumer in a suitable condition. The factory operator may regulate carefully the temperature of the cream for butter making in order to favor the development of a desirable type of fermentation. As indicated, the activities of microorganisms in dairy products are largely controlled by means of temperature regulation. In fact, the handling of dairy products is largely concerned with the maintenance of proper temperatures for the discouragement or encouragement of the growth, or for the actual destruction of the microorganisms which may be present in the particular product.

The effect of temperature upon microorganisms may be considered under three arbitrary headings:

1. Low temperature: below 50°F. (10°C.).
2. Medium temperature: 50 to 110°F. (10 to 43°C.).
3. High temperature: above 110°F. (43°C.).

Low Temperature.—Most organisms survive exposure to low temperatures. In general, however, growth is retarded in proportion to the lowering of the temperature. On the other hand, there are some microorganisms which actually grow at the freezing point of water (32°F. or 0°C.) and slightly below that. Some bacteria actually are able to grow in milk, etc., until it is frozen solid. The presence of salt in butter results in the lowering of the freezing point of the water and buttermilk droplets therein

so that certain organisms may develop in butter at quite a low temperature. As a rule, however, growth is retarded below 50°F. (10°C.). For this reason, milk, cream, or other products should be refrigerated properly if there is a desire to check decomposition without modifying the product deleteriously. Fluid milk and cream should not be kept for more than a few days unless they are kept at a sufficiently low temperature to retard bacterial growth. Deterioration may occur in the course of time, however, even though its progress is hindered by the cold. The point to bear in mind is, that refrigeration below 50°F. (10°C.) tends to check the rapid growth of microorganisms.

Medium Temperature.—When the temperature of a product reaches a point above 50°F. (10°C.) growth is encouraged, especially between 60 and 100°F. (15.5 and 37.8°C.). Within this range will be found the optimum growth temperatures of the majority of organisms. At 60 to 70°F. (15.5–21.1°C.) the milk-souring bacteria grow most rapidly in comparison with the other types ordinarily present in milk. When these same organisms predominate, as they do in a starter culture, their most favorable growth temperature lies between 68 and 72°F. (20 and 22.2°C.), as will be explained later. When the temperature is raised above 80°F. (26.7°C.), there is a general acceleration of growth of the majority of types present in the product, until a point near 100°F. (37.8°C.) is reached. This range of temperatures (80 to 100°F., or 26.7 to 37.8°C.) encourages, especially, the types of bacteria which produce undesirable fermentations in milk and other products. It should be avoided whenever possible. At 100 to 110°F. (37.8 to 43.3°C.) there are a few organisms which grow actively. These hold a special interest as will be pointed out in subsequent pages.

High Temperature.—A few microorganisms are able to grow at temperatures above 110°F. (43.3°C.). These are rare, however. Most organisms are, on the contrary, destroyed at 140°F. (60°C.) or above. The higher the temperature becomes, the more completely are they eliminated, and in proportionately less time. A temperature of 145°F. (62.8°C.) maintained for 30 minutes (pasteurization) ordinarily will kill over 90 per cent of all the microorganisms present in milk or cream, and, fortunately, practically all of those which produce disease. At 170 to 180°F. (76.7 to 82.2°C.), an exposure for a few seconds will accomplish approximately the same results. The temperature of boiling

water (212°F. (100°C.) at sea level) will destroy most organisms in a few minutes. It requires a temperature of 235 to 245°F. (112.8 to 118.3°C.) for 15 to 30 minutes to destroy all microorganisms, including the resistant spore-forming types. Evaporated milk is treated in this way to destroy all the organisms present.

It may be seen that temperature is an all-important factor in the growth of microorganisms. If the dairyman wishes to control the quality of the product which he is handling, he must exercise keen judgment in the selection of the temperatures which will assist him to accomplish his purpose whether it be preservation, fermentation, or sterilization.

PRODUCTS OF THE GROWTH OF MICROÖRGANISMS

When microorganisms grow upon substances as complex as milk and its products, profound changes are to be expected. A great variety of end-products will be produced because of the utilization of the various constituents as sources of food.

Some of the products that are formed and changes produced by the growing organisms are:

1. Enzymes.
2. Decomposition products of fats, proteins, sugars, etc.
3. Pigments.
4. Toxins.
5. Miscellaneous physical changes.

Enzymes.—It has been pointed out previously, that in order to grow, bacteria must be furnished with a suitable food supply. Much of the food material is not in a form, physically or chemically, for immediate utilization. It must be altered in such a way that it can be taken up readily by the cell before it is finally utilized for its nutrition. This process is accomplished largely by means of enzymes, produced by the living microorganisms.

The nature of enzymes, in a chemical sense, is not clearly understood. They correspond most closely in their actions to the catalysts employed by the chemist. They are capable of accelerating a chemical reaction without being altered themselves. After the process takes place, they can be recovered in their original state of activity. Extremely minute quantities of them are able to bring about profound changes. Most of the physiological activities of microorganisms are due to them. Consequently, changes in the constituents of milk and dairy products

attributable to microörganisms are brought about by their enzymes.

Types of Enzymes.—There are many different types of enzymes, each with its specific action. Some cause hydrolysis, as the production of rancidity of fat, the decomposition of casein, and the splitting of lactose into simpler sugars. Some ferment sugars, changing them to alcohols, acids, carbon dioxide, etc. Others oxidize various compounds, as pointed out elsewhere in this text. Some bring about the reverse action, namely, reduction, as demonstrated by the reductase test used for determining the bacterial content of milk. Others are able to cause the coagulation of proteins. The casein of milk is acted upon in this way to cause the so-called “sweet-curdling” of milk. The enzymes are susceptible to heat, chemical reaction of the substrate, and many other factors. They do not possess the ability to reproduce themselves. They are tremendously important, as the chemical changes in dairy products are largely to be traced to the action of these enzymes produced at one time or another by living cells.

Decomposition Products.—Fats are broken down principally into their component parts, glycerol and the fatty acids. Defects in butter, such as rancidity, are often of this sort. Some of the characteristic flavor of Roquefort cheese is to be attributed to the action of certain molds upon the fat.

As there is a great variety of proteins, innumerable by-products may be formed when decomposition takes place. They may be broken down into amino acids, other organic acids, alcohols, aromatic compounds, gases and intermediate products too numerous to mention. The ripening of cheese is a good example of the action of microörganisms on protein.

Sugars are broken down principally into alcohols, acids, water, carbon dioxide, and hydrogen, or the intermediate products. The change of lactose into lactic acid by the action of the milk-souring bacteria is the most common change taking place in milk. Even the mineral compounds may be altered in one way or another.

Pigments.—Certain microörganisms secrete pigments of various sorts, such as blue, red, yellow, green, and black. Bacteria may cause remarkable changes of color in milk. Certain yeasts produce pink or red spots on butter or cheese. Molds may bring about marked discoloration of the surfaces of butter and cheese.

Toxins.—Various types of microorganisms produce poisonous compounds known as toxins. These may cause serious disturbances in the well-being of man or of animal. The bacteria which cause diphtheria, botulism, and tetanus act in this way.

Miscellaneous Changes.—There are bacteria which are able to cause the coagulation of milk without the production of acid, others may produce a ropy condition in milk or cream. As a result of chemical decomposition, an apparently solid dairy product may be transformed into a liquid by the action of microorganisms. Many of these changes will be mentioned later.

FIG. 18.—Colonies of bacteria and molds as they appear on an agar medium in a petri plate after several days' incubation. The bacterial colonies such as *B*, and the mold colonies such as *M* can be counted easily. This is the way in which the number of bacteria in milk, etc. is determined by the official petri-plate method. One-half natural size.

METHODS OF COUNTING MICROÖRGANISMS

Several methods are used for the determination of the number of microorganisms in a given dairy product. Consideration will be limited to the most common of these; namely, the plate method. The results of a quantitative analysis of a substance from a microbiological standpoint are recorded in terms of the number of microorganisms per milliliter (cubic centimeter) or gram of the material examined.

In the plate method, a definite quantity of material (milk, cream, etc.) is measured into a glass dish known as a "petri plate." A nutrient material is then added to this plate and mixed thoroughly with the sample. This mixture is allowed to solidify and then to stand several days during which time most

of the organisms grow. As these organisms reproduce, the progeny remain about the mother cell. In time, their number becomes so great that the mass becomes visible to the naked eye. This mass is called a "colony." After the necessary incubation period, a count is made of the number of colonies on the plate. This is then translated into the number of colonies in a milliliter or gram of the material seeded in that particular plate. For example, if 0.01 milliliter of milk were added to a plate and 240 colonies were observed to develop after incubation, the count per milliliter of the milk would be 240×100 or 24,000 per milliliter. This method is useful for either bacteria, yeasts, or molds. It is an estimation of the number of organisms in a given quantity of material, on the basis that each microorganism is able to reproduce itself to such an extent that a visible colony is formed. As a matter of fact, all organisms do not grow under these conditions, nor does the colony count actually represent the total number of individual cells in the given quantity of material analysed. It is a close approximation, however, and for many years has proved to be of inestimable value in the investigation and control of dairy products. References to the numbers of bacteria are usually given in terms of the count determined by the plate method as outlined. (See also the material in the Appendix and the chapter on Miscellaneous Tests.)

SOURCES OF MICROÖRGANISMS IN MILK

It is important to know the channels through which microorganisms gain access to milk or the products of milk. Since the organisms are widely distributed in nature, it is conceivable that they may be introduced into milk from a great variety of sources. These sources may be grouped conveniently from the standpoint of dairy practice under the following headings: (1) interior of the udder, (2) exterior of the cow's body, (3) atmosphere, (4) utensils, (5) various ingredients added to dairy products, and (6) milker or handler.

Each of these groups deserves special consideration because the number of microorganisms, as well as the types contributed from each source, may have a significant influence upon the quality of the commercial product.

Interior of the Udder.—For many years, it was believed that milk drawn directly from the udder of a healthy cow was a sterile

fluid, that is, that it contained no living microorganisms. It has been demonstrated, conclusively, in recent years, that freshly drawn milk usually contains bacteria. Ordinarily, however, as the milk is secreted it is free from bacteria. As the milk passes down through the ducts and through the reservoir of the udder, bacteria are picked up from the walls of these passage ways, especially along the teat canal. Apparently, certain bacteria exist normally in the udder, while others may be introduced through the opening of the teat from time to time, according to the environment of the animal. Most of these are unable to establish a permanent habitat in the udder. They are washed out, to a large extent, by the first few streams of milk withdrawn from the udder.

The numbers of bacteria which are present in freshly drawn milk vary with individual animals, various quarters of the udder, with the same animal or quarter at various times, with the environment of the animal (cleanliness of quarters, etc.), with the health of the animal, and various other factors. It is found that the first milk withdrawn from the udder (foremilk) usually has a higher bacterial content than that drawn later in the milking process, while the strippings may show a somewhat higher count than the latter. The total number of bacteria present in the milk as it leaves the udder of a normal cow is not very great. It varies considerably, but 500 to 1,000 per milliliter may be a fair estimate. In some cases, the number is consistently higher, in others lower.

Relation of Udder Bacteria to Human Disease.—The principal consideration in the case of bacteria from the udder lies in the possibility that a diseased animal may eliminate disease-producing types of bacteria through the milk which thus becomes a menace to the health of the man or animal consuming such milk. If there are lesions of tuberculosis in the udder, the organisms of tuberculosis may be discharged and be a serious source of infection. Inflammation of the udder, mastitis, commonly called "garget," may be caused by bacteria. If such condition exists bacteria may be present in tremendous numbers in the milk, and be a potential source of septic sore throat among consumers. The bacteria which cause contagious abortion in cattle may be eliminated in the milk and result in infection of animals drinking this milk. It is also possible that these bacteria may cause disease in man. Fortunately, the majority of the bacteria

ordinarily encountered in the udder are harmless and relatively unimportant from the standpoint of their action upon milk or its products.

Milk intended for human consumption should be obtained only from healthy animals. All cows should be tested regularly, especially for tuberculosis and contagious abortion, and all diseased animals should be removed from the herd if it supplies milk for human consumption. The cows should be stabled in clean stalls and pastured where there are no bogs, swamps, or stagnant water. Otherwise, undesirable bacteria may find their way into the teat canal from which they may be discharged later into the milk. Furthermore, the first few streams of milk should be discarded. This will tend to keep down the bacterial content and may be done without any particular financial loss, since the foremilk is comparatively low in fat. The improvement in the quality more than compensates for the small loss of milk.

Exterior of the Cow's Body.—The condition surrounding the stabling and pasturing of the cows, together with the character of the coat of the animal, is such that considerable contamination of the flanks, tail, and udder is to be expected. This is important because of the presence of large numbers and a great variety of microörganisms in soil, animal discharges, straw, dust, etc., which may accumulate on the body of the cow and be dislodged during the milking process, to fall into the milk pail.

It has been found that under ordinary farm conditions, the exterior of the cow's body may contribute as many as 10,000 bacteria to a milliliter of milk. This is a significant contamination and must be reduced when an attempt is being made to produce milk with a low bacterial count. The use of hygienic methods in the stable, the maintenance of clean stalls, the wiping of the flanks and udder with a clean damp cloth just before milking, and the employment of a small-topped pail, or properly sterilized milking machine, will remarkably reduce the contamination from this source. The types of organisms which may gain access to milk from this source often are among the most undesirable of all the organisms found in milk or its products. Many of the difficulties experienced in the attainment of high quality in dairy products may be attributed to the contamination of milk with microörganisms from the filth and dirt so frequently to be found on the rear quarters and udder of the cow.

Danger to Humans.—Disease-producing types may be present in the deposits on the body of the cow. For instance, a tubercular cow may eliminate the organisms causing the tuberculosis through the fecal or urinary discharges. The organisms may then find their way into the milk. These discharges constitute the principal source of the tubercle organisms in milk. In this way the disease may be transmitted to man or animal consuming such milk.

A serious intestinal disturbance, especially in children, often called "summer complaint" or "infantile diarrhoea" may be caused by infected milk. Organisms of this sort may come from the excreta of the cow and be present in large numbers when hygienic conditions in the dairy are neglected, and especially when temperatures are high enough to encourage the growth of these intestinal types. Hygiene and sanitation are the solutions of the problem of reducing or eliminating this source of microorganisms. The filth from the body of the cow must be reduced as much as possible. The wiping of the udder and flanks with a clean, damp cloth and the use of a small-topped pail are extremely important precautions that must be taken if one is to produce a clean, low-count milk.

Atmosphere.—At one time, the atmosphere of the stable or dairy was considered as an important source of microorganisms. In reality, it is a relatively minor consideration especially from the standpoint of numbers. Unless the stables or plants are excessively dusty, the contamination is very slight. The types of organisms that may be added from this source may be of some importance, however, particularly the molds. In a creamery or cheese factory, the mold spores may be spread through the air, consequently, butter and cheese must be protected from such contamination.

Ventilation and suitable barn construction are the best preventive measures. Cows should not be milked in a dusty stable. Dry feeds or forage should be fed after milking; otherwise, sufficient time should elapse between feeding and milking so that all dust has settled. In a dairy plant, dust may be avoided and all unnecessary exposure of the product must be prevented.

Utensils.—The term "utensils" is intended to include all containers or equipment in which, or by which, milk or its products are handled, processed, stored, transported, or merchandised. Utensils are usually the most prolific source of micro-

organisms as far as numbers are concerned. A milk can, improperly washed, inadequately sterilized, or insufficiently dried, may contribute millions of bacteria to every milliliter of milk placed in it. A neglected milking machine is a very fertile source of contamination. An unsterilized churn, butter tub, curd mill, or anything of the sort, may add large numbers of bacteria, molds, or yeasts to a product. The pipes and pumps so commonly employed in a modern dairy plant are often responsible for excessive contamination unless they are cleaned and sterilized thoroughly. Further instances of the contributions which utensils often make to the numbers of microorganisms in a dairy product will be cited under the discussions of the microbiology of the various products.

Utensils also may be the source of disease-producing types of bacteria. For example, the organisms causing typhoid fever may find their way into milk from utensils that have been rinsed in water that is contaminated with them. The same may be true of other pathogenic organisms. Contamination from utensils may be eliminated by thorough cleansing, followed by adequate sterilization. In the case of many utensils, such as pails, cans, pipes, pumps, etc., rapid drying and storage in a dry place is advisable. If a dairyman wishes to produce a milk with a low bacterial count he must pay particular attention to the care of the utensils.

Various Ingredients Added to Dairy Products.—Substances, such as salt, water, gelatin, etc., added to various dairy products, may be a source of microorganisms in large or small numbers, and of harmless or harmful types. These will be considered more fully under the products in which they are employed.

Milker or Handler.—The personal element in sanitation as applied to dairying is the key to the whole situation. When the milker, butter maker, cheese maker, or other dairyman is careful, he naturally is the agent who attends to the details of hygiene which lead to a reduction of the contamination from the various sources previously mentioned. When he is careless, uninformed, or wilfully negligent, he is responsible for much of the difficulty encountered in the manufacture of first-class dairy products.

A person must be exceedingly careless in his person or habits to contribute, directly, any significant number of bacteria or other organisms. Dirty hands and clothing may be the source of a few organisms—but relatively few. Man is a particularly dan-

gerous source of contamination from the standpoint of the types of bacteria which he may contribute. Several diseases caused by bacteria and spread through milk may be transmitted from the milker or handler to the product under his care. Typhoid fever, diphtheria, scarlet fever, and septic sore throat are sometimes transmitted from a diseased person or carrier through milk to susceptible individuals who consume the infected milk. Some of the most serious epidemics of these and other diseases may have their origin in infection from an individual who has handled the milk or utensils at one time or another.

Filthy habits, dirty apparel, wet-hand milking, and similar conditions or practices are to be condemned. No person suffering from an infectious or contagious disease, or a carrier of such, should be allowed to handle milk or its products or have a part in the cleansing or care of utensils used for them. Constant attention to the details of hygiene and sanitation is a responsibility which no one engaged in the dairy business can afford to neglect. Man may be a direct or indirect source of serious contamination of such a susceptible food product as milk. He must exercise every precaution to insure a product that is safe and wholesome.

THE FERMENTATION OF MILK

Inasmuch as milk consists of a variety of chemical compounds utilizable by microorganisms, it is to be expected that many changes are possible as a result of the growth of these organisms.

If one were to take an ordinary sample of milk immediately after milking, and place it in a shallow dish at room temperature (70°F. (21.1°C.)) a rather consistent series of changes usually will take place in this milk. These changes may be followed by bacteriological and chemical analyses and by ordinary observation. This sequence of events is sometimes called the "normal fermentation" of milk. It may be divided into four periods, as follows:

1. "Germicidal."
2. Souring.
3. Neutralization.
4. Putrefaction.

Each of these may be considered briefly.

"Germicidal" Period.—Immediately after milk is drawn from the cow, there appears to be a time during which there is

no growth of bacteria, and apparently a decrease in the numbers. This diminution is attributed to a "germicide" or destructive action, or to some unfavorable condition, the nature of which is not definitely known. This "germicide" period varies considerably in length, usually being shorter at higher temperatures but quite pronounced and more prolonged at lower temperatures. It varies in milk from different cows at different times, from various quarters of the udder, or fractions of milk from the same quarter. It is specific for certain organisms. The "germicide" activity is destroyed by heating milk to 140 to 176°F. (60 to 80°C.) for 30 minutes. It is of very slight practical significance and may not extend more than a few minutes or a few hours. Immediately, at the close of this period the bacteria begin to grow. This leads to the second period.

Period of Souring.—During this period there is rather active growth of many types of microorganisms but the milk-souring types dominate the field and bring about the change of lactose into lactic acid while other changes are taking place to a lesser degree. The souring may continue for several hours or several days, but will reach a maximum when so much acid has been produced that the bacteria which have been responsible for it are inhibited in their growth. This occurs at about 1 per cent acidity.

Neutralization Period.—In the presence of considerable quantities of acid most bacteria are checked. Molds and yeasts, however, usually will be present and flourish in the acid medium. The acid will be utilized by them, while other chemical changes producing alkaline by-products will accompany the reduction of acidity. A thick mat of mold often may be observed on the surface of the milk at this time. This process may involve several days or weeks.

Period of General Decomposition.—When the acid has disappeared due to the activity of the yeasts and molds, and the reaction of the milk changed from acid to neutral or slightly alkaline, certain bacteria which have remained dormant during the period when acidity was high, again enter into an active growth period. These are mostly putrefactive types which attack, principally, the casein. In cooperation with the yeasts and molds, these bacteria completely decompose the solid constituents of the milk with the result that a clear liquid,

bearing no resemblance to ordinary milk, is produced. This is the point of ultimate decomposition. Such a substance is no longer fit for food. In fact, it may be actually poisonous. Milk is seldom kept long enough in dairy practice to undergo such extensive fermentation but the part which microorganisms may play in the decomposition of the complex substances in milk is very clearly illustrated.

SPECIFIC FERMENTATIONS OF MILK

Souring.—Souring is the most common fermentation of milk. It is caused by the transformation of lactose (milk sugar) into lactic acid by the action of enzymes produced by microorganisms,

FIG. 19.—Photomicrograph of typical milk-souring bacteria. (*Streptococcus lactis*). This illustrates their appearance when a small quantity of sour milk is placed in a thin film upon a glass slide, stained, and examined under a microscope. Magnified 1,475 times.

principally the so-called “lactic-acid bacteria.” Certain yeasts and molds are able to produce lactic acid, but are not so important in this respect as the bacteria. Many bacteria produce lactic acid from lactose. The most important group is typified by *Streptococcus lactis*. This organism has been at various times called *Streptococcus lacticus*, *Bacterium lactis*, and *Bacterium lactis acidii*. It is present in practically all milk and, when conditions are favorable, it attacks the lactose to produce, principally, lactic acid which gives milk a sour taste and, in turn, causes the precipitation of the casein, a process known as “curdling.” The curd, which is formed, becomes a firm, smooth, coagulated mass without any visible signs of decomposition or rupture by gas. There are certain varieties of *Streptococcus*

lactis which produce malt-like, burnt, or caramel flavors, ropiness, or other characteristics, but their major activity is the production of lactic acid up to 1 per cent as determined by titration. They grow at temperatures between 50 and 100°F. (10 to 37.8°C.) but most favorably at 65 to 75°F. (18.3 to 23.9°C.).

Another group of the lactic-acid bacteria has as its type, *Lactobacillus bulgaricus* which also produces principally lactic acid from lactose but in larger quantities. The acidity often

FIG. 20.—Various fermentations of milk caused by bacteria. 1. Souring, and coagulation without gas formation or peptonization. 2. Souring and coagulation *with* gas formation. Note the slits and holes in the curd due to the gas. 3. Souring and coagulation, *with* gas formation and peptonization. Note that the curd is partly digested and rent with gas holes and that it has been forced to the top of the flask by the pressure of the gas. 4. Coagulation due to rennet-like enzyme of sweet-curdling bacteria, and digestion of the curd due to pepsin-like enzymes of the bacteria. The upper portion of the flask is practically all liquid.

reaches 2 to 4 per cent. This species will not grow at temperatures below 60°F. (15.5°C.) but will develop very well at 100 to 110°F. (37.8 to 43.3°C.). Other types in this group are *Lactobacillus casei* which is important in cheese ripening and which grows at a lower temperature than *L. bulgaricus* and *Lactobacillus acidophilus* which is widely used in milk cultures for therapeutic purposes in controlling intestinal fermentations.

Souring and Gassiness.—Lactic acid is also produced by certain bacteria commonly found in the manure and filth of the stable. Examples of these are *Escherichia coli*, which is a normal inhabitant of the intestines of man and animal and *Aero-*

bacter arogenes which is found in feces but comes largely from grain, soil, etc. These forms produce other acids besides lactic acid and in sufficient quantities to coagulate the milk. They also bring about the formation of gases which puncture the curd and cause difficulty in the manufacture of cheese. Besides, other products are formed which give to the milk a very undesirable flavor and aroma. Certain yeast-like organisms, and spore-bearing types of bacteria also are able to produce gassiness in milk and cream.

Desirable Aroma and Flavor Production.—Organisms are also found, frequently associated with *Streptococcus lactis*, which attack the citric acid of milk. *Streptococcus citrovorus* and *Streptococcus paracitrovorus* are prominent in this connection. As a result of their activity, volatile acids such as acetic acid are formed, as well as diacetyl and acetylmethylcarbinol, which contribute to the flavor and aroma. Lactic acid may also be broken down, by *Streptococcus paracitrovorus*, especially. These bacteria are important in producing the desirable flavor in starters used in butter making.

Proteolysis.—There are many organisms which show a tendency to break down the casein by a process known as “proteolysis” or “peptonization.” Such forms as *Bacillus subtilis*, *Streptococcus liquefaciens*, *Clostridium butyricum*, and *Serratia marcescens* are prominent in this connection. As a result of this decomposition, decided off-flavors and unpleasant odors appear, although in the case of certain cheeses the proteolysis takes place in such a way, by the action of desirable types of bacteria and molds, that a pleasing flavor and aroma develop.

Alkali Production.—There will be found present in milk a number of bacteria which attack the salts of citric acid and change them into alkaline carbonates so that the milk becomes decidedly alkaline in reaction. Some of the disease-producing bacteria fall within this category.

Ropiness.—There are a number of bacteria which are able to bring about a peculiar change in milk which is known as “ropiness.” Some sticky or gum-like substance is formed by these organisms. This causes the milk to become ropy so that when it is poured from a container long threads of milk will form. These may be several inches or even feet in length. It becomes a very troublesome situation for market milk distributors but is a characteristic of certain Scandinavian milk beverages.

Certain of the milk-souring types of bacteria may acquire this ability to produce ropiness. Most commonly, however, it is caused by bacteria similar to *Alkaligenes viscosus*, which grows best in sweet milk or cream and when in competition with the mixed flora of milk, at temperatures below those at which milk sours readily. These bacteria occur commonly in surface water and infect the milk directly by being added with water, or indirectly from contaminated utensils, cows, or stable refuse.

The typical ropiness is more of an annoying, than a dangerous, problem. Under certain circumstances, it is a fermentation eagerly sought. It must not be confused with the stringy or slimy condition of milk which sometimes occurs when a cow is suffering from a diseased udder. In this case, the abnormal condition is due to the presence of pus, with tissue cells and blood constituents which cause the sliminess. Such milk is unfit for food.

Sweet Curdling.—Occasionally, milk will become coagulated without the action of acid. This may be due to the formation of a rennet-like enzyme produced by bacteria, among which *Streptococcus liquefaciens* and *Bacillus subtilis* are prominent. This curdling may be followed by a digestion of the coagulum under either acid or alkaline conditions and a bitter taste. This change takes place in milk that is kept at a low temperature.

Butyric-acid Fermentation.—Sour cream kept at temperatures above those normally used in storage may support the growth of bacteria which are capable of producing butyric acid. This is accompanied very often by gas formation and results in very undesirable flavors and odors. A spore-bearing organism, *Clostridium butyricum*, is capable of this action. It usually is to be traced to contamination from feces or soil.

Bitter Flavor.—A bitter flavor in milk or cream may be due to a number of causes such as feeds or weeds fed to the cow, or to enzymes produced in the udder of the cow when there is some

FIG. 21.—Ropy milk. Certain types of bacteria produce this ropy condition in milk, and when the milk is poured from a container it forms long, gummy threads which are sometimes several feet long.

local disturbance there or at a time when the cow is in an advanced stage of lactation, or by the action of microorganisms, such as *Streptococcus liquefaciens* and *Torula amara*. It may be coincident with sweet curdling or decomposition of fat, sugar, or protein, and often occurs in milk held for some time at a low temperature.

Alcoholic Fermentation.—A perceptible amount of alcohol may be produced in milk or cream by the action of lactose-fermenting yeasts, which change the lactose into alcohol and other by-products. This often is observed in old cream, especially in the summer.

Production of Colors.—Bacteria may bring about remarkable pigmentation of milk. Such colors as blue, red, yellow, and green are occasionally observed. They are due to soluble pigments produced by bacteria and may be accompanied by other changes in the milk. Among these bacteria are *Pseudomonas syncyanea*, *Flavobacterium synxanthum*, and *Serratia marcescens*.

Miscellaneous Fermentation.—Microorganisms may also produce other changes in milk such as the flavor of turnips, carrots, potatoes, soap, grass, etc., caramel or burnt flavor; and odors resembling a stable or musty room. Most of them are rare, and it is beyond the scope of this text to cover them in detail. There are still other types which seem to exert no perceptible influence upon milk. They may be present in considerable numbers but utilize such small quantities of the constituents of milk that they are hardly noticed. Many of the molds are able to produce complex changes in milk but seldom have the opportunity to exhibit their action because they grow slowly. Milk and cream are used before they can make evident their presence.

THE TRANSMISSION OF DISEASE THROUGH MILK AND DAIRY PRODUCTS

It is understood quite generally that milk and dairy products may transmit disease-producing microorganisms to the consumers of these products. Among the diseases which are most commonly carried through milk and its products are tuberculosis, typhoid fever, diphtheria, scarlet fever, septic sore throat, undulant fever, and various intestinal disturbances especially among children.

Tuberculosis is a disease which affects both man and animal. A cow suffering from tuberculosis may discharge the bacteria

through the mouth, the fecal or urinary discharges, or directly into the milk. This bovine tuberculosis may be transmitted to man and there manifests itself largely as the glandular, or intestinal type of tuberculosis or a tuberculosis of the bones or skin. Occasionally, it is possible for a person infected with the human type of tuberculosis to transmit the organisms through milk. While the organisms of tuberculosis do not appear to grow in milk they nevertheless are capable of setting up an infection in persons consuming infected milk.

Typhoid fever is chiefly a disease of man. The bacteria causing it may find their way into milk directly from a person suffering from the disease, or from a so-called "carrier" who is a person who harbors the organisms after recovery or even without ever showing any signs of the disease. Infected water may be a source of contamination, especially when used to rinse utensils. In farm homes where a case of typhoid fever exists, milk utensils are often washed in the same dishwater as the dishes from the patient. In this way, milk could be infected eventually from the utensils.

Scarlet fever and diphtheria are also diseases which are most common among human beings. The milk becomes infected from the people who handle the milk or utensils when they are suffering from the disease or while they are acting as "carriers." Infected utensils may also be a source of contamination.

Septic sore throat may result from infection of the milk in the udder of a cow suffering from garget caused by bacteria capable of causing septic sore throat in man, or by direct contamination from a person suffering from the disease.

Undulant fever may be transmitted through milk because of infection of milk in the udder of the cow or goat. The infection from goat's milk is usually termed "malta fever." The infection in cow's milk is traced back to animals infected with the bacteria which cause contagious abortion in cattle and which sometimes pass directly into the milk in the udder.

The intestinal disturbances in children, sometimes termed "summer complaint" or "infantile diarrhoea" may be traced to infection from people handling the milk or to contamination of milk with bacteria from the intestines of the cow, which means, in most cases, careless production and excessive filth. There are other diseases which may be carried in milk or dairy products but they occur very rarely.

Determining the Wholesomeness of Milk.—How can one tell whether milk contains pathogenic (disease-producing) bacteria or if a given milk is pure and safe? It is possible to determine the presence of specific disease-producing bacteria in milk but it is usually impractical to do so. The organisms may be there in such small numbers that they escape detection. Further, such an analysis requires a great expenditure of time and money. Inoculations must be made into various laboratory animals, such as the guinea pig or rabbit, and the results awaited. This may take several weeks or several months.

If the purity of milk is doubted, it is much more satisfactory to have the cow or cows tested for tuberculosis or contagious abortion, and examined by a competent veterinarian for signs of garget and other diseases. If the tests for the diseases are positive, the milk from such animals should not be used for food. If it is a question of intestinal infections, the methods of producing milk, the cleanliness of the cow, and other matters should be ascertained. These defects can be corrected without especial difficulty. If it is a question of man-borne diseases, an examination by competent physicians or health officers should clear up that situation. Much more can be learned from the examination of the cows and of the people handling the milk and from a survey of conditions of producing and handling it than from a laboratory analysis of the milk. The cost is also actually less.

Often it is difficult to trace sources of infection and, consequently, wherever there is any question as to the safety of a given supply of milk, the best precaution to take is either to discard the suspected milk or to pasteurize it properly. Pasteurization is one of the most valuable safeguards which the dairy industry uses for preventing the transmission of disease through milk or dairy products.

CHAPTER VII

THE BABCOCK METHOD FOR DETERMINING FAT IN MILK AND CREAM

Until comparatively recent years, milk and cream were bought and sold only to a limited extent. Seventy-five years ago, nearly every family was supplied with milk from its own cows and the dairy products most common on the market, such as butter and cheese, were farm made. Under these conditions, no special need was felt for a means of measuring the exact amount of butter fat in milk. When a farmer wished to demonstrate the superiority of a favorite cow, her milk was kept separate and the cream churned alone. Her butter yield for a day or a week was often determined in this manner.

The great increase in city population, beginning in the United States near the middle of the nineteenth century, resulted in the development of a constantly increasing traffic in fluid milk. This was extended further by the movement begun by the establishment of the first cheese factory in 1854, and the first butter factory in 1872. Soon it was found necessary to use some means for detecting the too common adulteration of milk by either skimming or watering. The lactometer, described elsewhere, was among the first devices used for the purpose of detecting these adulterations. The first creamery or butter factory was operated on the plan of bringing the whole milk to the factory. It was apparent that injustice was done by paying the same price for all milk regardless of richness. This plan, however, of paying for all milk by weight regardless of richness was followed for many years and, in fact, among some cheese factories until within very recent years.

The creamery system was soon changed to that of bringing to the factory only the cream which was separated by the gravity method on the farm. With this plan came still greater difficulties, as the variation in the richness of the cream was much more than the variation of the milk. As a result, various plans for testing the cream were devised. The one used most exten-

sively was known as the "oil-test churn" and consisted in churning a small sample of each farmer's cream separately and measuring the percentage of fat which was melted in the glass churning tube. This system was not applicable to milk and, between 1880 and 1890, the introduction of the power centrifugal separator resulted in a great expansion, in butter factories, based upon the delivery of the whole milk. Several chemists worked upon the problem of devising a practical milk test and several methods were suggested which were quicker in operation than the standard method of extraction employed in the chemical laboratory. Among these were Short and Patrick. A satisfactory method for factory use was not forthcoming until Dr. S. M. Babcock, of the Wisconsin Experiment Station, in 1890, announced the method, since that time, generally known as the Babcock test. Few inventions relating to agriculture have been of greater significance or have come into general use so quickly. The Babcock method now is used universally in the United States and Canada. A remarkable fact is that after nearly 40 years of use no change or improvement has been made in the method. At the present time, milk and cream to the value of over \$3,000,000,000 are marketed yearly in the United States, mostly on the basis of the butter-fat content which is determined by the Babcock method. Another factor responsible for the widespread use of the Babcock test was the refusal of the inventor to patent the method for his own financial benefit.

In addition to the use of the test for evaluating milk for sale, a constantly growing use is in connection with the keeping of records of individual cows to determine their production. In time, probably, the fitness of practically all cows to remain in their owners' herds will be judged, in part, by means of this test.

General Procedure.—Previous to the work of Dr. Babcock, others had discovered that strong acid would digest the proteins of milk and free the fat globules so that they might run together. Dr. Babcock's special contribution was the application of centrifugal force to the samples after the fat has been freed by the action of sulfuric acid. By this means, it is possible to gather the fat at the surface of the fat-and-acid mixture and to measure it on a suitable graduated scale.

In brief, the procedure in making a Babcock test of milk is as follows: By the use of a pipette, the milk sample (17.5 milliliters)

is measured into the milk-test bottle, after which commercial sulfuric acid (17.5 milliliters) is added and the two thoroughly mixed. The bottle containing the mixture is then centrifuged for 5 minutes to bring the fat to the surface. Sufficient water then is added to bring the contents to the base of the bottle neck. The bottle is again centrifuged for 2 minutes and sufficient water then added to bring the fat into the graduated part of the bottle neck. The bottle is centrifuged again for 1 minute to gather the fat into a coherent column. The reading of the fat percentage is made from the graduated scale on the neck of the bottle.

Principles Underlying the Test.—The Babcock method for determining the fat percentage in milk and other dairy products is based upon two principles. The first is that concentrated sulfuric acid, when mixed with milk in correct proportion, will digest (hydrolize) the proteins of the milk, breaking them down into simpler constituents in which form they no longer are capable of maintaining the fat droplets in the emulsified state of dispersion. Thus freed, the fat globules may rise to the surface of the liquid and join together (fuse) into a single mass of fat. The heat generated by the reaction between the sulfuric acid and the milk melts the fat globules and permits them to run together. The heating of the liquid also lowers the viscosity of the acid mixture which makes the conditions more favorable for the movement of the fat droplets to the surface.

The second principle involved concerns the manner of separating and collecting the fat. The contents of the test bottle are a mixture of fat and an acid solution of the other milk constituents. The fat, at the temperature reached during testing, has a specific gravity of 0.9 compared to approximately 1.43 for the acid mixture. In the centrifuge, the greatest force will be exerted on that portion of the mixture having the highest specific gravity, which, in this case, is the acid solution. The centrifuge, used in making the test, is constructed in such a manner that the test bottles assume a horizontal position during the whirling. The fat is forced towards the center; that is, toward the neck of the bottle.

When milk is sold, except in the case of the retail trade, weight rather than volume is the unit used. It is desirable, therefore, that the fat percentage be likewise on a weight basis. For instance, in calculating the pounds of fat in a given quantity

of milk, it is necessary to multiply the percentage figure by the pounds of milk rather than by the gallons. For this reason, the basis of the test is weight, 18 grams of milk being the amount used. As a matter of convenience, the amount to be used is measured rather than weighed. For this purpose a pipette calibrated to 17.6 milliliters is used. It has been found that $\frac{1}{10}$ milliliter adheres to the pipette and, as 1 milliliter of milk weighs 1.032 grams, 17.5 milliliters of milk are equal to 18 grams.

FIG. 22.—Babcock milk-test bottle, pipette, and acid measure.

Testing Whole Milk.—The apparatus required includes (a) the test bottles, (b) a pipette graduated to 17.6 milliliters, (c) an acid measure graduated to 17.5 milliliters, and (d) a centrifuge; in addition, (e) sample bottles, (f) a mixing jar and thermometer, and (g) dividers should be available. A supply of commercial sulfuric acid is necessary. This should have a specific gravity of 1.82 to 1.84 and be free from dirt and sediment.

The first precaution is to be certain that the milk at hand is a fair sample of the entire amount which the completed test is to represent. More errors are made in this connection than in conducting the details of the test. The next step is to take the temperature of the milk, and if it is not between 60 and 70°F.

(15.5 to 21.0°C.) it is brought within these limits, because extreme temperatures affect the accuracy of the measurement of the milk. Another reason for controlling the temperature is to insure proper action of the acid upon the milk. Beyond the temperature figures given above, the action of the acid may be influenced to such an extent as to give an unsatisfactory result.

Measuring the Sample.—The sample is thoroughly mixed by pouring it back and forth several times from the sample bottle and the mixing glass. The pipette then is filled by suction to a point somewhat above the graduation. The dry forefinger is slipped quickly over the top and the milk allowed to escape slowly until the surface is at the mark on the pipette. The measured sample is transferred next to the test bottle. It is well to hold the test bottle at an angle and allow the tip of the pipette to touch the lower side of the neck of the bottle. Some prefer to use a pipette with the lower part small enough to be inserted into the neck of the bottle. There is no objection to this procedure, provided the

FIG. 23.—Putting the milk into the test bottle. The lower end of the pipette should be small enough to go inside the neck of the test bottle.

outside of the pipette has been wiped dry, otherwise, too much milk will be delivered to the bottle. Furthermore, if too much milk is adhering to the outside of the pipette point, it will interfere with the outcoming air which is being displaced by the milk, and the consequent loss of milk in the bubbles that escape will necessitate starting the test over again.

In any case where accurate results are desired, it is the best practice to make two tests of the same sample so that any mistake made in testing or reading the one bottle will be detected on the second one.

Adding the Acid.—Fill the acid measure to the graduation indicating 17.5 milliliters with sulfuric acid (commercial, specific gravity 1.83). The acid should be within the same limits

of temperature, 60 to 70°F. (15.5 to 21.0°C.), as given for the milk. It is especially important to avoid higher temperatures. When adding the acid, hold the test bottle at an angle of a little less than 90 degrees and pour the acid slowly and carefully into the neck, taking care not to fill the neck to such an extent as to stop the free escape of the air, otherwise, the inflow of the acid may be stopped suddenly and a portion overflow on to the fingers of the operator. It is best to add about two-thirds of the measured amount at first. Then rotate the bottle with the hand, gently at first, taking care not to fill the bottom of the neck with the contents, and then rotate more vigorously as the curd is dissolved. Then add the remainder of the acid and shake

FIG. 24.—Centrifuges used in testing milk by the Babcock method. Centrifuges are made to operate by steam, electricity, or hand power.

rather vigorously, always using a rotary motion to prevent spilling the contents. Vigorous shaking should be continued for 1 full minute after the uniform dark color is noticed.

Centrifuging.—The bottles should be placed at once in the centrifuge and whirled for 5 minutes at the proper speed. Most Babcock centrifuges now on the market either are geared so that proper speed is obtained when motor driven, or, as in the case of the hand-operated centrifuges, the correct speed usually is indicated on the crank of the machine. A more complete discussion of proper centrifuge speed will be found in the paragraph on centrifuges. The bottles must be placed in the machine in such a manner as to balance one another. To do this properly requires an even number of bottles. Sometimes, in case of an odd number, a bottle filled with water is used to balance but this only partially serves the purpose on account of the marked difference in specific gravity between the water and the acid mixture.

Occasionally, one wishes to centrifuge only two bottles. These must be placed on opposite sides of the centrifuge wheel, and if the cups supporting the bottles are in pairs, each bottle should be placed in the outside cup of the pair. Bottles whirled in the inside cup with the outside cup empty are likely to break. Some operators prefer to fill two bottles with water and place them in the two inside cups next to the tests, but with most centrifuges this practice is unnecessary.

The centrifuge should be started and stopped with care in order not to injure the centrifuge or break the test bottles. At the end of 5 minutes stop the centrifuge and by means of the

FIG. 25.—Water bath. The test bottles are placed for 5 minutes in the water bath at a temperature of 135°F. before the readings are made.

pipette or other suitable device add water to the test bottles until the contents are close to the base of the neck. The water should be at a temperature of not less than 140°F. (60°C.). In adding the water, allow it to flow down the side of the neck while the bottle is held at an angle in order not to disturb the fat layer. If hard water is used, it is advisable to add a few drops of sulfuric acid to it before using. The centrifuge then is run for 2 minutes at the same speed as before, after which water is added to bring the fat column well within the limits of the graduated scale on the bottle neck. Care must be exercised lest too much water be added and the top of the fat column

raised above the top of the scale. The centrifuge is operated again, this time for 1 minute. The test bottles are next placed for 5 minutes in a water bath at a temperature of 135°F. (57.2°C.) and deep enough so that the hot water is level with the top of the fat column. The tests then are ready for reading.

Reading the Test.—Each test should be read quickly after the bottle is taken from the bath. The space filled by the fat

FIG. 26.—Reading the fat column in a Babcock milk-test bottle. The reading is taken from the straight line which marks the top of the meniscus at the surface of the fat, to the extreme bottom of the fat column. Dividers are used as a matter of convenience.

column is noted and read from the straight line on the surface, the top of the meniscus, to the extreme lower line of the fat in the lower meniscus. As a matter of convenience, a pair of dividers generally is used. The prongs of these dividers should open and close easily and yet show sufficient resistance, so as to prevent spreading once they have been set. One point is placed at the proper level at the bottom of the fat column and the dividers adjusted to bring the other point to the top of the fat column. Without changing the spread, the lower point of the dividers is now placed at zero on the graduated scale, the upper point then

showing the reading in percentage.

Defective Tests.—Difficulties often are encountered in conducting the Babcock test of various milk products. Frequently, the fat column is dark colored and contains black particles, especially at the base. Sometimes the fat column is light in color, often cloudy, and a mass of white material may be found at the base. Again, the fat may be clear, and the base of the column clearly defined, yet bubbles are found at the surface which obliterate the upper meniscus. These difficulties usually may be avoided by one who understands the chemistry involved. One of the most common defects found in the completed tests is the appearance of dark specks in the fat column and at its base. There are several possible causes for this difficulty; namely,

1. Too violent action of acid due to either (*a*) acid or product tested being too warm, or (*b*) too much or too strong acid.

2. Insufficient mixing of acid and sample.

3. Improper addition of water, or addition of water before action of acid is complete.

If the acid or the product to be tested is too warm, the action of the acid is too rapid. The result is that some of the milk solids are charred by the acid, thus forming on the particles a layer which is impervious to the action of the acid. They rise to the surface with the fat because they contain no acid but do contain some fat. The remedy is to adjust the temperature, of both the acid and milk to be tested to not over 70°F. (21°C.) before beginning the test. If the action of the acid still is too violent, further reduce the temperature of the acid and milk or reduce the amount of acid used by about one-tenth. About the same appearance of the fat column results when the operator fails to agitate the contents of the bottle sufficiently before centrifuging. It is not sufficient merely to shake the bottles until the brown color appears; they should be shaken vigorously for at least a minute after that.

In certain practical plants the operators add water to the tests before they are centrifuged. If this is done too quickly, it counteracts the action of the acid before all the curd has been dissolved and the above-mentioned defect results. Occasionally, at the last filling of the bottles the water is allowed to plunge directly into the fat collected at the base of the neck. This carries the fat downward into the acid mixture and some of the dark particles there may be carried upward with the fat, especially if the contents of the bottle have cooled somewhat.

Occasionally, a light-colored, cloudy fat column is observed. The most common cause of this is insufficient action of the acid which may be brought about because (*a*) the acid or the product being tested is too cold, or (*b*) the acid is too weak, or (*c*) too little acid is used. A second cause is the addition of water before the action of the acid is complete.

TESTING CREAM

Variations from Milk-test Procedure.—The Babcock method has been applied to cream, not by Babcock, but by others. In this application certain modifications of the method as used for milk have been necessary. These differences are:

1. The use of a test bottle having a neck of greater capacity than the neck of the milk-test bottle.
2. The proper amount of cream determined by weight rather than by volume.
3. The use of a mineral oil, dyed red, and sometimes known as "red reader," to remove the meniscus from the surface of the fat column before reading.

FIG. 27.—
Bottle for test-
ing cream by
the Babcock
method. Nine
grams of cream
are used with
this bottle.

4. The use, in some cases, of a 9-gram sample instead of an 18-gram sample as in the case of milk.

5. When a 9-gram sample is used it is necessary either to use only 9 milliliters of sulfuric acid, or to add 9 milliliters of cold water to the cream before 17.5 milliliters of acid are added.

6. It is not necessary to control the temperature of the cream before measuring the sample into the bottle, as in the case of milk.

The need for a test bottle having a greater capacity in its neck than that in the neck of the whole-milk test bottle is due to the much greater percentages of fat contained in cream than in milk. It is obvious that the fat column rising over a sample of cream will occupy considerably more space than is required for the fat from an equal quantity of milk.

Why Cream Samples Are Weighed.—The milk test is based upon an 18-gram sample obtained by volumetric measurement in a pipette. Cream must be weighed rather than measured because it is impossible to obtain a definite weight by taking a particular volume. There are three factors concerned: First, the specific gravity varies considerably with the fat content. Cream containing 20 per cent of fat does not have the same volume per unit of weight as does, for example, 40-per cent cream. A certain amount of air also is incorporated in cream, the amount varying with conditions to which the cream has been subjected. The third factor is the viscosity, which varies widely with different lots of cream. As a result, the amount adhering to the pipette is far from constant.

Elimination of the Meniscus.—A small amount of the red reader is allowed to flow down the side of the neck onto the surface of the fat column of a cream test just before the reading is made. This reader makes a distinct line at the level of the top of the

fat column, thus eliminating the meniscus. The elimination of the meniscus has been found necessary in order to make the Babcock cream tests yield accurate results. The reading taken in this manner is found to agree most closely with determinations made by the official Roese-Gottlieb method.

FIG. 28.—Scales for weighing cream samples for testing. The cream sample must be weighed, not measured, as is the case with milk. The bottle containing cream is an approved type for composite samples.

Size of Sample Taken.—Another difference between the methods for cream and milk testing is in the size of the sample tested. For the whole-milk test an 18-gram sample is always used. Eighteen-gram samples are sometimes used for cream testing also, but in many localities 9-gram samples are used. The use of 9-gram samples necessitates still further variations from the method used for milk, for it is necessary in this case either to use only 8 to 9 milliliters of sulfuric acid, or to add 9 milliliters of cold water to the 9 grams of cream before adding 17.5 milliliters of acid. If 17.5 milliliters of sulfuric acid were added to 9 grams of cream, the excessive action of the acid would result in a charring of the fat, yielding a fat column which could not be read accurately, and which might show materials other than fat, or fail to show all of the fat. The addition of 9 milliliters of water

to the cream amounts, in effect, to the use of an 18-gram sample of cream, so far as the amount of acid required is concerned.

It is necessary to control the temperature of milk within rather narrow limits, because expansion or contraction due to wide temperature differences prevents the measurement by volume of exactly 18 grams. Cream is measured directly by weight, however, making control of its temperature unnecessary.

Procedure.—As in testing milk, the first precaution is to make sure that an accurate, representative sample has been obtained. It is more difficult to obtain such a sample of cream than of milk, because of the higher fat content. The sample is mixed thoroughly by pouring from the sample bottle to the mixing glass and back again several times.

Nine or eighteen grams of cream are next weighed into each of two cream-test bottles of a capacity and construction corresponding to the amount of sample to be used. The bottles are placed one on each pan of a cream balance and the scale brought into balance by means of an adjusting device with which the scale is fitted. A 9- or 18-gram weight is placed on one pan and cream measured into the bottle on the opposite pan until the scale again comes into balance. The weight is then removed and cream measured into the bottle on the pan from which the weight was removed until a balance is again reached. Each bottle then contains cream in a quantity equal to the 9- or 18-gram weight used.

The next step is to add sulfuric acid. If 18-gram samples of cream have been weighed into the bottles, then about 17.5 milliliters of acid are added. If 9-gram samples have been used, then a choice of two different procedures is offered, depending upon the type of test bottle in use. Two types of these bottles are available, both having necks of a capacity such that the percentage may be read directly for 9 grams of sample, but with bodies of different capacity, one being about 25 milliliters, the other 50 milliliters. If the smaller bodied bottle is used, 8 to 9 milliliters of sulfuric acid are added. If the larger one is used, 9 milliliters of cold water are added to the cream and then 17.5 milliliters of sulfuric acid.

Regardless of which of the above procedures is followed, it is necessary to mix the acid and the sample immediately after the addition of the acid. This is done exactly as described for milk, by a gentle rotary motion until a uniformly dark color

appears and then by vigorous shaking for at least 1 minute.

The bottles next are centrifuged for 5 minutes. Hot water (140°F. (60°C.) or higher) is added to float the fat to the base of the neck of the bottles. A few drops of sulfuric acid should be added to hard water before it is used. The bottles are next centrifuged for 2 minutes.

Hot water is added to float the fat well up into the neck of the bottle, and the bottles again centrifuged for 1 minute. The

FIG. 29.—Reading the cream test. Mineral oil is placed on the surface to remove the meniscus, the reading is then made from the upper to the lower extremes of the fat column.

bottles next are removed from the centrifuge and placed in a hot-water bath at a temperature of 135°F. (57.2°C.) with the level of the water above that of the fat. After 5 minutes in the water bath, a few drops of red reader are allowed to run gently down the inside of the neck and the length of the fat column from the extreme bottom to the junction of fat and red reader is measured with dividers. The percentage of fat is read from the scale on the neck of the bottle, as in the case of milk.

Approximate Method for Cream Testing.—It is sometimes desirable to know the approximate fat content of cream when only milk-testing equipment is available. A reasonably close estima-

tion of the fat content of cream can be made by the use of milk-testing equipment. By the use of the pipette, 17.6 milliliters of cream are measured into a container. Two pipettesful of water are added, the water being used to rinse all the cream from the pipette. The mixture is tested like whole milk. The water may be used to rinse the cream from the pipette so that an approximately accurate measurement is effected. The reading is multiplied by 3 to account for the dilution with water. This test is likely to yield results which are too low, since 17.6 milliliters of cream are slightly less than 18 grams because the specific gravity of cream is lower than milk.

DETAILS OF TEST BOTTLES AND BALANCES USED

The Whole-milk Test Bottle.—There are several types of test bottles, each type being suited to the testing of a single product or similar group of products. The whole-milk bottle shown in Fig. 22 is commonly of the type spoken of as the "8-per cent bottle." It is composed of a body, with about 50 milliliters capacity, to which is attached a slender neck carrying graduations ranging from 0 to 8 per cent. The capacity of the neck of the bottle between the lower and upper graduations should be exactly 1.6 milliliters. The reason for this is readily seen when we consider that this space must contain 8 per cent of the original sample. The amount of the sample used is 17.5 milliliters which weighs 18 grams, as milk has an average specific gravity of 1.032. Eight per cent of 18 grams is 1.44 grams. But as fat has a specific gravity of 0.9, 1.44 grams of fat will have a volume of 1.6 milliliters.

When the Babcock milk test first was put into general use, a 10-per cent milk bottle was used, rather than the 8-per cent bottle now more common. A few of these bottles are still to be found. They may be read less accurately than the 8-per cent bottle because the scale on the neck of the bottle has only five small divisions between each whole percentage mark, each division having the value of 0.2 per cent, whereas the 8-per cent bottle carries ten divisions, making possible a reading to tenths of a per cent. The neck of the 10-per cent bottle between the zero and ten marks has a capacity of 2 milliliters. The reason for this should be clear from the explanation of the graduation of the 8-per cent bottle.

The Cream Test Bottle.—For the testing of cream, a bottle with greater neck capacity is required than for milk because even the thinnest cream has more fat than can be read on the scale of a whole-milk bottle. To meet this demand, the cream bottle is made with a larger neck. When the diameter of the neck is increased the accuracy of reading necessarily is reduced, because slight errors in the measurement of the height of the fat column cause relatively large errors in the reading. On the other hand, if the bore of the neck is made smaller in order to facilitate accurate reading then the length of the tube must be increased unduly to insure sufficient capacity for the fat from the rich cream, and the bottle becomes top heavy and is broken easily. In attempts to manufacture a bottle that would overcome these faults, many styles have been made and tried. One type of bottle was made with a neck having a small bore tube with a bulb blown at a point midway between its attachment to the body and the tip. This bottle proved unsatisfactory because the glass in the bulb portion was so thin that it was easily broken. Furthermore, some difficulty was encountered, in practice, in bringing the level of the contents of the bottle to a point where the bulb was filled completely with fat, a necessary condition for reading a test in such a bottle.

The cream-test bottles most commonly used at the present time are of three distinct styles known as (1) the 6-inch, 18-gram, 50-per cent bottle; (2) the 6-inch, 9-gram, 50-per cent bottle; and (3), the 9-inch, 18-gram, 50-per cent bottle.

The first of these bottles is not to be recommended. Inasmuch as this bottle is but 6 inches in height, and the neck must accommodate the fat from 18 grams of cream, the bore of the neck is necessarily large, and accurate reading practically impossible.

The second type of bottle is made to use a 9-, rather than an 18-gram charge, in order that the diameter of the neck may be cut down to facilitate more accurate reading. It must be borne in mind, however, that, as the size of the sample to be tested is decreased, the errors in measuring the smaller sample are increased correspondingly so that the increased accuracy assured in reading the sample is counterbalanced by the decreased accuracy in measuring the sample. The neck of this type of bottle should have a capacity of 5 milliliters between the 0 and 50-per cent graduations.

The 9-inch, 18-gram, 50-per cent bottle finds favor with some because it offers the accuracy on weighing the cream that the larger sample affords, and, at the same time, permits quite accurate reading because of the elongated, narrow bore neck. It may be criticized, however, as being less easily handled and more easily broken than the shorter bottle.

The neck of this bottle should have a capacity of 10 milliliters between the 0 and 50-per cent graduations.

Cream Balance.—For the measurement of cream into the test bottles, a small scale known as a “cream balance,” or “cream scale,” is necessary. The cream balance is much less sensitive than an analytical balance. Its weighing pans usually are constructed with a light frame to prevent the bottle from tipping or sliding off, and each pan may hold one, two, four, or six bottles, depending upon the type purchased. The scale is supplied with one of several types of adjusters so that the point of balance may be shifted at will.

The proper sensitivity often is specified by state regulations. This specification usually is one space for each 0.1 gram. This means that if the scale is brought into perfect balance and a 0.1-gram weight is placed on either pan, the pointer then should show a balance at one space from the center of true balance in the direction of the pan on which the weight was placed.

TESTING SKIM MILK, BUTTERMILK, AND WHEY

In applying the Babcock test for skim milk and buttermilk, the only important difference as compared to the test for whole milk is in the type of bottle used. On account of the very small amount of fat present, a reading in the regular milk bottle is not practical. To meet this situation, a double-necked bottle is used, one tube of which is large enough to be used in adding the materials. The second is a small tube for reading the fat and is graduated to hundredths of a per cent.

Usually, it is advisable to add more than 17.5 milliliters of acid for skim milk and buttermilk because there is more protein to be decomposed. The amount of acid needed is determined by the color of the mixture after the acid has been mixed thoroughly with the milk. The color should be a dark brown similar to that resulting when the acid is added to whole milk when making a standard Babcock test. Practice and familiarity with the pro-

cedure help considerably in securing good results with the skim-milk test.

The bottles should be placed in the centrifuge with the filling tubes toward the center of the wheel. When so placed, the fat tube will be at the top when the bottles are carried into a horizontal position by the centrifugal force and no fat will be lodged behind the delivery tube when the bottles again attain their perpendicular position at the end of the centrifuging period. Aside from the differences noted above, the skim-milk test is carried through the same steps as is the whole-milk test.

Whey resulting from cheese manufacture contains 0.20 to 0.50 per cent of fat. It is best, therefore, to use skim-milk test bottles graduated to read as high as 0.50 per cent for testing this product. The Babcock test of whey is conducted in exactly the same way as that of skim milk except that less acid is required to free the fat. This difference results because whey contains very little protein material and less sugar than skim milk. The acid is added in small quantities with considerable shaking after each addition until a brown color appears.

The Skim-milk Test Bottle.—The skim-milk test bottle, though designed for the testing of skim milk, is also suitable for testing buttermilk and whey. These products ordinarily are low in fat content. The neck of the skim-milk bottle is made with an exceedingly small bore. On account of the obvious impracticability of introducing the skim milk or buttermilk and acid through a tube of such small size, a second and larger neck is provided for the purpose of filling. This tube extends through the top of the body of the bottle and delivers the materials near the bottom of the bottle so that when the fat rises, it will enter the smaller tube which is attached at the upper part of the bottle.

A new type of skim-milk test bottle has recently been placed on the market. Inside the large neck is a removable false neck carrying graduations from 0 to 1 per cent. The skim

FIG. 30.—Bottle for testing skim milk and buttermilk. The same procedure is used as for whole milk. The scale allows readings to $\frac{1}{100}$ of 1 per cent.

milk, buttermilk or whey, and acid are poured into the bottle with the false neck removed. Before water is added to float the fat into the upper part of the bottle, this neck is placed in the bottle to receive it. The graduated neck of a skim-milk bottle should have a volume of 0.05 milliliter between 0 and 0.25 per cent, double this amount if graduated to 0.50, and four times this amount if graduated to 1 per cent.

Centrifuges.—The centrifuge consists of a horizontal wheel supported on a vertical drive shaft. The periphery of the wheel carries bottle holders, usually in pairs, so hung that they may swing outward into a horizontal position due to centrifugal force as the wheel gains speed. This entire mechanism usually is enclosed in a suitable steel or iron protector which serves both to prevent quick cooling of the contents of the bottles during centrifuging, and to avoid injury to the operator when breakage of bottles accidentally occurs during operation.

Many different types of centrifuges are on the market. Some are operated by hand, and others by power, either steam or electric. Centrifuges designed for use with the Babcock method may be bought in sizes holding from 2 to 32 bottles. Some of the electrically operated machines are supplied with heating devices for the purpose of keeping hot the contents of the bottle during centrifuging. This feature is desirable, but in purchasing a machine one should make certain that this heater and its wiring are protected properly against the action of the acid which is certain to be spilled in the machine at various times due to accidental breakage of the bottles; otherwise, a short circuit may result and the heater may be ruined.

The steam-driven machine has an obvious advantage in heating the samples because it permits live steam to escape into the centrifuging chamber during operation and thus keeps the contents hot. Some people object to this type of machine because of the water and rust which attend its operation.

Centrifuge Speed Required.—Babcock's original tests were centrifuged at 800 r.p.m. on a wheel 18 inches in diameter. It was found by him that incomplete separation of the fat resulted at lower speeds, while higher speeds gave no better results than those obtained at 800 r.p.m. It is obvious that wheels of a diameter less than 18 inches must travel at a speed faster than 800 r.p.m. in order to generate the same amount of centrifugal force, and machines of a diameter greater than 18 inches need

not travel so fast as 800 r.p.m. When the weight of the objects being centrifuged is always approximately the same, as is true of Babcock test bottles and contents, the square of the r.p.m. of the wheel must vary in inverse proportion to the radius. Thus, at two different radii the velocities must vary according to the formula

$$\frac{r_0}{r_1} = \frac{v_1^2}{v_0^2} \quad \text{or} \quad r_0 v_0^2 = r_1 v_1^2.$$

Using Babcock's original figures we may calculate the speed required at any other diameter by substitution in the above formula:

thus,

$$rv^2 = 9 \times 800^2$$

or,

$$v = \sqrt{\frac{9 \times 800^2}{r}}$$

where r is the radius for which we wish to calculate the reel speed, and v is the velocity in r.p.m. required for the radius r .

The following table shows the wheel speeds required of different diameter machines, calculated by means of the above formula.

Diameter, inches	R.p.m. of wheel	Diameter, inches	R.p.m. of wheel
12	980	18	800
14	907	20	759
16	849	22	724

In order to determine the speed at which a centrifuge should be operated, measure the distance from the center of the wheel to the bottom of one of the bottle cups held in the horizontal position it assumes while the wheel is in motion. This measures the radius of the wheel and may be used in the formula shown above to determine the speed at which it should travel, or the diameter may be obtained if the radius is doubled and the required speed read from the foregoing tabulation.

CHAPTER VIII

COMMON DAIRY PROCESSES

CREAM SEPARATION

When the milk fat is concentrated into a fraction of the original milk, that portion is known as "cream." Cream is not a definite, specific substance. The use of the words "separating cream" often leads to an erroneous conception regarding the nature of cream. It should be understood that the portion of the cream not fat is essentially the same as the skim milk represented by the part remaining as skim milk when the cream was removed. There is no exact limit which may be set regarding the fat content necessary to justify the use of the term cream. In a commercial sense, the term seldom would be applied to a product having less than 16 per cent milk fat. Cream, as sold for household use, contains, as a rule, from 20 to 25 per cent fat. Higher fat percentages also often are available under specific terms, such as "whipping cream." Cream as received at butter factories usually contains from 25 to 40 per cent fat. Cream is separated for one of two purposes. The most important is to obtain a product from which butter may be churned more economically than from whole milk. The second is to provide an article more desirable than milk for table use or for certain manufacturing purposes, more especially for ice-cream making.

Historical.—The extensive use of cream for either of these purposes is relatively modern. Ancient peoples are known to have used milk freely and it is probable that they at times used cream that rose to the top of the milk which had been held some time in containers although there is little in ancient literature to suggest such use as common. It is well established that in early times butter was produced by churning milk. Thus, in one of the oldest parts of the Bible occurs the statement, "surely the churning of milk bringeth forth butter." Probably one reason for the limited use made of cream in early civilizations was the fact that these peoples lived in warm climates and without suitable means of cooling and preserving milk, without which the use of cream

is certain to be rather unsatisfactory. For this reason, the use of cream as a part of the process of butter making, developed chiefly in the northern latitudes where civilization was established later. It is not clear when the use of cream for butter making became common. The extensive use of cream for household purposes is a development of very recent years, and was made possible by the development of suitable means for securing the cream in a fresh condition and maintaining the condition by cooling until consumed.

It is probable that the practice of gravity creaming was followed, to some extent, by most milk producers for at least a century previous to the invention of the centrifugal separator. Milk was sometimes set in shallow pans, sometimes in deep cans, and sometimes diluted with water for creaming. The advent of the centrifugal cream separator, in 1879, marked the beginning of sweeping changes in the dairy industry. Many of these changes were made possible by this machine, and others were indirectly the result of its use.

Basic Principle of Separation.—Separation of cream from milk is possible because of a difference in specific gravity between the fat and the liquid portion or serum. Whether separation is accomplished by gravity or centrifugal methods, the result is dependent upon this difference. The serum or skim-milk portion possesses an average specific gravity of 1.036, while that of butter fat is about 0.930. When milk is allowed to stand, the force of gravity affects both serum and fat, exerting a downward pull on each which is proportional to its specific gravity. As the serum is the heavier, it assumes a position below the fat, just as water will form a layer below oil when a mixture of the two is allowed to stand. The analogy is not complete, however, for, when oil rises on water, it forms a continuous film at the surface, but, when the butter fat, in the form of globules, rises to the surface of milk, the globules maintain their identity at the temperatures below their melting points, preventing the formation of a layer of butter fat; instead, a considerable amount of serum remains with the fat. This combination of the fat of milk, existing in the form of globules dispersed in a portion of the serum of the milk, composes the product commonly recognized as cream.

When milk is revolved swiftly in such a device as a separator bowl, where the generated centrifugal force is about one-thousand

times greater than that of gravity, the milk is thrown to the outside of the arc through which it is traveling. Of two liquids whirling through the same arc, the greater force is exerted by the one of greater specific gravity. The serum, therefore, is forced to the outside of the fat in the bowl, causing the formation of two layers, one of serum, and, inside of that, one of closely crowded fat globules interspersed with some serum. Separation is completed by leading these two layers from the bowl through different outlets.

Gravity Creaming.—Early dairying was entirely a farm enterprise, and no one knows when gravity creaming was first practiced. The rising of cream on milk is so certain to occur whenever milk is allowed to stand that it must have been known for a long time. Early writers agree that the so-called “shallow-setting method” was the first of several gravity methods practiced. This method gave way to the deep-setting method, which, in several of its variations, was in general use until the centrifugal separator was developed. Gravity creaming by the use of both the shallow pan and the deep-setting systems still is practiced where small quantities of milk are produced or the conditions of butter making still are quite primitive.

The Shallow-pan System.—The practice of placing milk in shallow, rather than deep, dishes when cream was desired undoubtedly was based upon experience. During the years when this system came into use, few homes were equipped to furnish cooling facilities. If warm milk is placed in a deep container, cream will rise, to be sure, but the separation is less complete than is the case when milk layer is not over 2 inches deep. The type of vessel used in America for this system of creaming is a tinned metal pan about 4 inches deep. The shallow-pan system is still used to a limited extent where small quantities of milk are produced or where agriculture is conducted in a primitive way. The milk is poured into the pans immediately after milking without cooling and the pans are placed preferably in a moderate temperature, for example in a cellar or basement. The skimming is done at the end of 24 to 36 hours, at which time the milk below the cream usually is coagulated. The cream is removed with a tin “skimmer,” an appliance in the form of a shallow flat dish.

The shallow pan served a useful purpose at a time when quality of product was less important than now and losses of

butter fat were of little significance. As the milk usually is soured to the point of coagulation before skimming takes place, it is evident that the cream secured will not be sweet. For this reason, it is unsuited for table use. Butter made from such cream may be, at times, of fair quality but often is quite the reverse. The manufacture of high-class butter requires some control of the fermentations of the cream by the butter maker. With cream from shallow pans, no control was possible.

Another serious objection to the shallow-pan system was the condition of the skim milk. For pig feeding, the sour condition was not especially objectionable, but for calf raising this condition was a rather serious matter. One strong argument for the introduction of the farm separator was the better quality of the skim milk for feeding purposes.

Another serious objection is the inefficiency of the shallow pan in recovering the fat in the cream. Skim milk from the shallow-pan system contains from 0.5 to 1.5 per cent of fat. If the milk contained 4 per cent fat, a skim-milk test of 0.80 fat is equal to a loss of 20 per cent of the total fat. The fat produced by one cow out of each five is lost in the skim milk. A system with such a low efficiency will not long remain in use when the prices of butter fat reach the levels of recent years and much more efficient methods of getting the cream are available.

The Deep-setting Method.—This method seems to have originated in Orange County, New York, probably earlier than 1850. In the Orange County system the milk was set in cans about 20 inches deep and 8 to 15 inches in diameter, and placed in running spring water which was usually at a temperature of 48 to 50°F. (8.9 to 10°C.). In the later improved forms, glass strips were inserted in the wall of the can, one near the bottom and the other near the top. Through these the cream could be observed. The skimming of the cream at first was done by the use of a small conical dipper with a long handle. By means of this dipper, the cream was skimmed from the top of the milk. In the improved form, a faucet was placed near the bottom of the can and the skim milk drawn off until the lower edge of the cream layer could be observed through the glass strip

FIG. 31.—Can used in the deep-setting process of creaming. This can would be set in cold water 12 or 24 hours before skimming. The cream line may be seen through the glass-covered slot.

to be approaching the faucet. The cream was then drawn into the cream can. The success of such a method was doubted by many users of the shallow-setting method because of the old belief that fat could not rise more than 2 or 3 inches through milk, but demonstrations soon convinced those interested that the deep-setting method was an improvement on that of shallow setting. The low temperatures at which creaming took place not only insured a more efficient removal of fat from the skim milk, but also greatly retarded microbial action, resulting in the production of a better quality of product than could be obtained by shallow setting.

The deep-setting method was soon adopted in northern Europe where ice water was generally used when cold spring water was not available. After this change the system gained favor rapidly, and, to a large extent, superseded the shallow-setting system.

Efficiency of the Deep-setting System.—Fewer criticisms may be made of the deep than of the shallow-setting system, although not all the objectionable features were removed. One objection was the low fat content of the cream. It was not practical to obtain more than 20 or 22 per cent of fat, which resulted in larger losses in the buttermilk than is the case when richer cream is churned. The deep-setting method has the added disadvantage of requiring ice or very cold water, neither of which is available everywhere. The fat loss in the skim milk from deep setting is considerably less than from the shallow pan, amounting to between 0.2 and 0.4 per cent under optimum conditions. This comparatively low loss is obtained only by the use of low temperatures. Babcock, in an early experiment at Wisconsin, demonstrated that the fat content of the skim milk was 0.287 when creaming occurred at 48°F. (8.9°C.), but at 54 to 56°F. (12.2 to 13.3°C.) the fat content was increased to 0.746. It is doubtful if many farmers were sufficiently careful to maintain temperatures as low as 48°F. (8.9°C.) during creaming, and it is probable that when this system was common the fat losses were higher under average conditions than they were believed to be. A loss of 0.4 per cent, which is probably a fair figure for general conditions, means 10 per cent of the total fat produced is lost in the skim milk, or the fat produced by one cow out of ten goes into the skim milk.

The quality of the cream from the deep setting, except in regard to the low fat content, is decidedly better than that from the

shallow pan and may be nearly equal to cream from the centrifugal separator. The skim milk is also much better for feeding purposes. The deep-setting system cannot compete with the cream separator, however, and is now used only in a limited way. Numerous patented devices for creaming milk by the deep-setting plan were placed on the market between 1865 and 1890. These did not concern the system itself but consisted of more convenient arrangements for handling milk by this process. Some were in the form of mechanical arrangements for lifting the milk cans from the water, others, special devices for drawing the cream, or fancy cabinet creamers which contained the milk in one compartment with storage facilities for perishable food in another compartment. The best-known among these were the Cooley and the Stoddard creamers.

The Water-dilution Method.—The so-called “dilution method” was founded on the supposition that the addition of water to milk would lower the viscosity so that the cream could rise more readily. A special tank fitted at the bottom with a drain faucet, above which was a strip of glass giving a view of the contents of the tank, was commonly used. Milk to be separated was placed in such a tank and a quantity of water about equal to that of the milk was added. After about 12 hours, the skim-milk-water mixture was drained through the faucet until the cream was seen nearly to reach the drain. The cream then was caught in a separate container.

This method failed to accomplish the desired results. The separation of fat was not so complete as in the preceding methods. The skim-milk-water mixture contained 0.4 per cent fat, or more, making the fat content 0.8 to 1.0 per cent on the basis of skim milk to which no water was added. Skim milk watered in this manner was neither so palatable, nor so valuable for food as ordinary skim milk. The well water often introduced organisms that caused undesirable changes in the milk and the cream. Added to these disadvantages was the excessive amount of liquid that required handling. As the cream was drawn within 12 hours or less, however, it was in better condition than that from the shallow pan. Various types of apparatus for using the dilution method were advertised extensively under the name “Dilution Cream Separators” during the early period of the farm separator, from 1890 to 1905. By taking advantage of the publicity the centrifugal separator had received,

a large number of these inefficient devices were sold during this period.

CENTRIFUGAL CREAMING

Early Development of Centrifugal Separation.—The first application of centrifugal force in removing fat from milk seems to have been made in 1859, when Fuchs, of Germany, whirled milk in test tubes. He, however, was interested in this method as a means of determining the fat content of milk, not as a means of creaming. His work was followed, in 1860, with a similar study by Fesca of Berlin. The first attempt to substitute centrifugal force for gravity in the creaming of milk was made by Prandtl, of Munich, Germany, in 1864. Prandtl's machine consisted simply of a vertical axis capable of being rotated, on which was mounted a crossbar carrying a bucket at each end. The milk was placed in these buckets and subjected to vigorous rotation, after which the machine was stopped and the cream skimmed off. In 1870, Bond, of Massachusetts, attached two glass jars on a spindle which could be revolved at 200 r.p.m. By this means, he secured cream from milk within a few minutes. In 1873, Jensen, of Denmark, had a somewhat similar device revolving two buckets at 400 r.p.m.

An advance toward the development of the modern machine was contributed by Moser, of Austria, in 1872, who exhibited his machine at a Dairy Exposition in that year. Instead of whirling the milk in buckets, Moser used hollow cylinders which were revolved on their own vertical axes. This device was improved and enlarged in 1874 by Lefeldt, of Germany, with a view to adapting it for use in creameries. He used a large drum revolving 800 r.p.m. To operate this machine 220 pounds of milk were placed in the drum and full speed attained in 5 to 10 minutes. It required 20 or 30 minutes to effect complete separation after full speed was gained, and 25 or 30 minutes more for the drum to stop rotating. When the milk had resumed its horizontal position, the cream floated in a heavy layer on top. The skim milk was removed with a siphon and the cream through a valve at the bottom.

Lefeldt seems to have provided the next advance in 1877 when he devised a tube which removed the cream while the machine was in motion. This was accomplished by introducing the tube in such a position that it would remove the cream as it crowded

toward the center of the drum. The skim milk, however, could not be removed while the machine was in motion.

The first continuous separator is said to have been invented by Prandtl in 1875, but this device was not adopted for practical use. Fleischmann, noted dairy scientist of Germany, states that continuous separators of practical importance appeared almost simultaneously in Sweden, Denmark, and Germany in 1879. In an earlier edition of his book, however, he indicates that continuous separators were brought out in Denmark in 1878, by both Winstруп and Nielsen. These machines were doubtless the forerunners of the Danish-Weston separator, which was long in use in Denmark. Other literature states that De Laval's machine, referred to by Fleischmann as the one appearing in Sweden, was placed on the market in 1878. It is doubtful if any one person may be credited with being the first to invent a continuously operating separator. It is certain that the experiments of Prandtl, Moser, and Lefeldt were important contributions to the invention, and while due credit should be accorded the inventors of the successful machines, it must be recognized that their machines were the result of combining the earlier ideas of pioneers in the same field, and adding certain features necessary to make the machines practical.

The early separators were hollow-bowl machines. The next material advance in construction was made by the De Laval company, and consisted of adding inside fixtures, or discs, to the bowls. These were known as the Alpha discs, and the first De Laval machines equipped with these discs were known as the "Alfa Laval." This improvement, coming in 1890 or 1891, increased the efficiency of separation, and, at the same time, permitted reduction in the size of the bowl without interfering with the capacity of the machines. Since that time, various minor improvements have been made, but the present-day machines are built to operate on the principles recognized by the early workers already mentioned. Indeed, modern separators almost universally embody the principle in the design of the De Laval machine of 1891.

Introduction in United States.—The first centrifugal separators were of the large-capacity, power type, many of which were in use in the United States within a few years after their invention. Their use supplanted a system of gathering gravity-raised cream. Under the centrifugal system all the farmers delivered their milk

to either the creamery or a skimming station and waited in turn for their skim milk which was taken home to be used for feeding livestock. About 1892, the hand separator was placed on the market by the De Laval and several other organizations, and there followed a period during which these machines were tested by various experiment stations with the result that they were recommended over gravity systems and gradually their use was extended. Their adoption by the majority of farmers developed slowly, however, and it was not until after 1900 that they found favor with farmers and not until 1910 that they became very widely used. One of the factors in this development was the encouragement of certain centralizer creamery organizations, who even went so far as to buy the hand separators in carload lots to sell to cream producers in their territory.

The adoption of the hand separator caused a return to the gathered-cream system. Again the skim milk was kept on the farm, and the cream sold as had been done when the gravity-creaming system was employed. This had the advantage of keeping the skim milk at home and avoiding mixing it with the neighbors' skim milk at the skimming station. In this manner, the spread of animal diseases through skim milk was avoided in territories where the skim milk had not been pasteurized before it was returned.

At the present time, a slow change toward the factory skimming of milk can be observed. Many new plants in the West and Middle West, being equipped for the shipment of sweet cream to the eastern markets, are planning to receive milk and do the skimming at the plant, because a better quality of cream usually can be obtained in this way. It is possible that local creameries also may return to the factory-skimming system, as economic conditions make it increasingly necessary to market all of the constituents of milk in place of only the fat which is the common practice now.

How Centrifugal Separation Is Accomplished.—A knowledge of how centrifugal separation takes place may best be gained by following the course of the milk through a separator bowl which is operating normally. As milk enters a rapidly revolving bowl it is acted upon both by gravity and by the centrifugal force generated by rotation. The centrifugal force is so much greater than that of gravity that the effect of the latter becomes negligible. In consequence, milk entering the bowl is thrown to the outer

wall of the bowl rather than to the bottom. This means that the bowl fills from the outside toward the center, rather than from the bottom toward the top as it would if gravity were the only force to which the milk is subjected.

The milk entering the rapidly revolving bowl is subjected at once to a very powerful centrifugal force. The milk serum has a higher specific gravity than the fat and, for this reason, is brought to the outer part of the bowl while the cream is forced towards the center of the bowl. The contrast with gravity creaming should be noted. In one case, the force of gravity causes a slow separation of the fat globules from the heavier skim milk, in the other, centrifugal force developed many times greater than gravity results in a rapid and more complete separation of the fat globules.

Construction of the Centrifugal Separator.—The modern cream separator consists of a bowl which can be rotated at high speed by means of suitable gears, and arrangements for supplying milk to the bowl and removing the cream and skim milk. A typical construction is shown in Fig. 32. The chief parts of the bowl are the shell, the inside fixtures, and the spindle which supports the weight and, by means of which, the rotation is accomplished. The first separators were hollow bowls, but later greatly increased efficiency was found to be possible through the introduction of various devices inside the bowl of which the most widely used is the disc shown in Fig. 33. The remainder of the machine is essentially a set of gears so arranged as to make possible the turning of the spindle on which the bowl is carried at a high rate of speed. The gears are commonly housed in a tight case in which they dip in the oil while operating. When the bowl is supported from the bottom as is most common, two bearings are necessary, one to support the weight, and the second to maintain the upright position. These bearings must be designed and constructed with great care. The upper bearing is generally fitted inside a spring in order that the bearing may adjust itself and maintain the bowl in an upright condition even though the frame of the machine is not exactly level. In a few models the bowl is suspended which makes necessary the use of only one bearing and insures the freedom of the bowl at all times to operate in a perpendicular position.

If the separator has been in operation for some time, a thin layer of a sticky substance, possibly showing some evidence of

FIG. 32.—Cross section showing detailed construction of a modern cream separator. 1. Supply can. 2. Faucet. 3. Regulating chamber. 4. Cream screw. 5. Cream spout. 6. Bowl shell. 7. Milk distributor. 8. Upper bearing. 9. Lower bearing. 10. Sight glass in oil reservoir. (Courtesy, De Laval Separator Company.)

solid impurities, will be found adhering to the wall of the bowl. This is the separator slime. Next in order comes a layer of

FIG. 33.—Sectional view of a cream separator bowl. 1. Inflow of milk into feed shaft. 2. Delivery of incoming milk near bottom and beyond the cream wall. 3. Upward passage of cream from inner ends of discs to the cream outlet. 4. Upward passage of skim milk from the outer ends of the discs to the skim-milk outlets. (Courtesy, De Laval Separator Company.)

skim milk, while at the inner edge of the upright wall of fluid the fat globules are packed closely together forming cream. This

gathering of the cream near the center of the bowl is the first and most important step in centrifugal separation. All that remains is to lead the two layers out of the bowl without remixing. The separate removal of these two layers is accomplished by establishing two outlets at proper distances from the axis of the bowl, one of which connects with the cream layer in the bowl, the other with the outer edge of the bowl where the skim milk with the lowest fat content is found. The connection between the skim-milk layer and the skim-milk outlet is made possible by a device called the "dividing disc." The diagram, Fig. 34, illustrates how this disc functions. The skim milk from near the

FIG. 34.—Diagrammatic cross-section of one-quarter of a cream separator bowl illustrating the filling of the bowl. The filling occurs from the outside towards the center, not from the bottom upwards. The center illustration shows a bowl partly full. The cream wall is already forming. When the bowl is full, as shown on the right, the cream and skim milk discharge through separate outlets.

outer edge of the bowl cavity moves between the dividing disc and the inside shell of the bowl. At the top of the disc the space between it and the shell of the bowl connects with a slot in the neck of the bowl. This slot is the skim-milk outlet. The skim milk which comes from the outlet with some force is gathered in the so-called "skim-milk pan" from which it flows through the spout provided for that purpose. A second outlet, located on the neck of the bowl above the skim-milk outlet, connects with the inner side of the dividing disc and serves to conduct the cream from the bowl into the cream pan. The skim-milk outlet has a capacity much in excess of that of the cream outlet. The two are so located, however, that when the separator is receiving a normal, or nearly normal, inflow of milk a portion will discharge from each outlet. The cream outlet opens from a point slightly nearer the axis of the bowl

than does the skim-milk opening and the cream, therefore, is subjected to less centrifugal force at the point of removal than is the skim milk. As a result of its location and capacity the skim-milk outlet removes from 75 to 90 per cent of the total inflow, the remainder coming from the cream outlet.

Inside Fixtures.—As mentioned the earlier separator bowls were hollow. Later, it was found that the capacity and efficiency could be greatly increased by the use of devices to go inside the bowl. In the hollow bowl the incoming milk did not acquire, immediately, the speed of the rotating bowl on account of the relatively small surface with which it came into contact, this surface being limited to the wall of the bowl. Present-day inside devices are so arranged that the milk is given the full velocity of the bowl as it enters. Another condition tending to low efficiency of separation in the hollow type of bowl is the remixing of the incoming milk with the partially separated milk. The devices now in use are arranged to obviate this difficulty by conducting the milk into the bowl at a point where the remixing with the partially separated milk is reduced to the minimum. A common plan is to bring the milk through a tubular shaft in the center of the bowl to the bottom where openings allow the milk to escape. The cream outlet is at the opposite end of the bowl where the incoming milk does not cause remixing of the cream and skim milk.

Control of Richness of the Cream.—Every cream separator is equipped with a device for regulating the fat content of the cream. This consists of a means for moving either the cream or the skim-milk outlet toward or farther from the axis of the bowl, or for closing off a part of the opening at the same time that it is moved nearer the center. This device, when attached to the cream opening is known as a "cream screw," and when attached to the skim-milk opening, is known as a "skim-milk screw." When the cream screw is moved nearer to the center of the bowl, the centrifugal force operating at this outlet is decreased, due to a reduction in the circle through which it whirls. At the same time, the opening is moved nearer to the inside of the wall of liquid being centrifuged. It is clear that such a change will cause a reduction in the amount of liquid flowing through the cream outlet, and an increase in volume of the liquid flowing through the skim-milk outlet. In effect, the moving of a cream screw toward the center of the bowl

causes a part of the serum, which would otherwise have gone with the fat as cream, to be diverted to the skim-milk outlet and a higher testing cream results. The skim-milk screw also produces changes in the percentage of fat of the cream by changing the ratio of cream to skim milk, but, in this case, a lower testing cream results when it is moved nearer to the center because by so doing, the amount of skim milk delivered through

FIG. 35.—Graphic illustration of the effect of changing the cream screw. The graph represents 100 pounds of whole milk containing 4 per cent fat. When set for thin cream, the same amount of fat is in the cream as when set for thick cream but the volume of the cream is greater because more of the milk serum (skim milk) is taken with the fat. The efficiency of separation is not materially affected by the adjustment of the cream screw.

the skim-milk outlet is reduced, and the amount of cream increased by the added skim milk diverted to the cream outlet. In this way, the fat percentage of the cream may be varied within quite wide limits without any effect upon the efficiency of fat recovery. To illustrate, let it be assumed 100 pounds of 4 per cent milk is separated, resulting in 85 pounds of skim milk and 15 pounds of cream. Ignoring the small loss of fat in the skim milk, the cream will have a fat percentage of 26.66. If the cream screw is now moved nearer the center and another 100 pounds of the same milk separated, the portion recovered as skim milk may be 88 pounds, as cream, 12 pounds. In this

case, the cream contains 33.33 per cent fat. Both lots of cream contain, however, the same quantity of fat.

Factors Governing the Fat Percentage.—It is commonly known that the fat percentage of machine-skimmed cream can be varied by changing the position of the cream screw. The fact that there are at least six other factors which cause variations in fat content of cream is not so commonly known. The separator user too often has assumed that any variation in his cream test as made by the cream buyer is evidence of careless or dishonest practices. Disputes of this nature are only too common between the buyer and the seller. The facts are that cream tests must be expected to vary more or less, and if the same test is reported a number of times in succession, the seller has more reason for suspicion concerning the accuracy of the testing than would be the case if reasonable variations occur, because it is impossible to maintain uniformly all conditions which influence the test. On account of the unreasonable attitude assumed by some cream sellers, based upon a lack of understanding regarding tests, the buyer may be tempted to report the same test regularly which is likely to result in loss to the producer, as the higher tests may be scaled down to avoid disputes because later tests may be lower. The cause of variations in cream tests, other than those due to adjustments of the cream screw are as follows: (1) speed of machine, (2) temperature of milk when separated, (3) richness of milk, (4) rate of inflow, (5) amount of water or skim milk used for flushing, and (6) amount of separator slime in the bowl.

Speed of Machine.—Other conditions remaining the same, the higher the speed the richer the cream. Table IX gives results obtained by the authors with five separators concerning this factor. It is clear from the table that as the speed increases the fat percentage in the cream increases. It should be noted that the effect of speed is more pronounced when the cream screw is adjusted to deliver cream high in fat percentage. This relation of speed to richness of the cream necessarily must be the result of a change in the proportion of cream to skim milk as the speed changes. It should be kept in mind that the milk intake remains essentially the same under all conditions of operation.

As the speed of the bowl is increased, the centrifugal force applied to both the cream and skim milk within the bowl is necessarily increased. Centrifugal force varies not with the

TABLE IX.—THE EFFECT OF BOWL SPEED ON THE PERCENTAGE OF FAT IN CREAM

Separator number	Percentage of fat in cream from operation at different speeds		
	Full speed	Three-fourths speed	Half speed
1	20.00	20.40	17.50
1	51.20	42.40	32.20
2	21.70	21.50	18.20
2	42.35	35.10	22.65
3	21.75	19.95	16.85
3	41.60	29.70	24.00
4	31.30	30.15	28.95
4	39.70	35.50	29.90
5	44.50	22.50	
5	20.00	18.00	

velocity, however, but as the square of the velocity. The skim milk, being farther from the center of the bowl, revolves through a greater arc or at a greater velocity than does the cream. The increase in speed, therefore, has a more pronounced effect upon the skim milk than upon the cream, and the outflowing skim milk moves at a greater velocity through the opening. This increased speed results in a greater total quantity passing out of the skim-milk opening. This inevitably decreases the amount of cream which means a higher fat percentage.

The Temperature of the Milk.—When all other factors are kept constant, an increase in the temperature of the milk to be separated causes a decrease in the fat percentage in the cream. Conversely, a decrease in the temperature of the milk causes an increase of the percentage of fat in the cream. This fact is illustrated by Table X.

Occasionally, with certain machines, the separation of milk at extremely low temperatures results in a decrease of fat percentage in the cream rather than the increase that might be expected normally. This is due to the clogging of the bowl with the cold cream which adheres to the inside fixtures of the bowl. This effect usually is featured by a high loss of fat in the skim milk.

The increase in test of the cream when the temperature of the milk decreases is caused by a choking of the cream outlet by the

TABLE X.—EFFECT OF TEMPERATURE OF MILK SEPARATED ON FAT PERCENTAGE IN CREAM

Separation trial	Temperature, degrees Fahrenheit	Fat content, percentage
1	120	24.5
	90	30.0
	75	43.0
2	120	43.5
	75	50.7
	90	21.5
3	80	22.0
	70	25.4

colder, thicker cream. Cold cream does not flow so readily as warm cream, and, therefore, less liquid is permitted to pass through the cream opening when cold. As most of the fat is still delivered through the cream opening the reduction in flow is represented by a corresponding increase in the skim milk diverted to the skim-milk outlet. As the temperature of the milk increases, the fluidity of the cream increases so that a greater flow again may occur through the cream outlet. Inasmuch as this increased flow must be nearly all skim milk, the fat percentage of the cream decreases proportionately.

Richness of Milk.—In the case of most separators the richness of the milk exercises a direct influence upon the fat percentage of cream skimmed from it. The effect is more pronounced with some separators than with others, due to the difference in bowl construction. This relation is illustrated in Table XI, which presents figures from experiments by the authors.

The effect of the fat percentage of the milk upon the richness of the cream is explained by the fact that the separator bowl is so constructed as to deliver from the cream outlet a rather definite proportion of the inflow regardless of the richness of the milk. If the same quantity of cream is secured from two lots of milk having the same weight but different fat contents, it is clear that the cream from the richer milk will contain the more fat. For example, let it be assumed that from 100 pounds of milk containing 3 per cent fat, 15 pounds of cream were separated. If no fat were lost in the skim milk, this cream would have a fat content of 20 per cent. If the milk had contained 4.5 per cent

TABLE XI.—EFFECT OF RICHNESS OF MILK ON FAT PERCENTAGE IN CREAM

Separator	Fat percentage	
	Milk	Cream
1	5.0	20.15
	4.1	16.85
2	4.8	40.40
	3.0	24.60
3	5.2	48.00
	4.2	41.75
4	4.8	40.00
	3.2	27.00
5	5.4	29.00
	4.2	25.00

fat, however, the yield of cream would have been essentially the same, that is 15 pounds, but the fat content in this case would be 30 per cent. Some separators do not behave exactly as

FIG. 36.—Graphic illustration of an experiment to study the relation of the fat percentage of the milk separated to the amount of cream and the cream test. Practically the same amount of cream is obtained from milk containing 4.8 per cent fat and from that containing 3 per cent. The cream from the 4.8 per cent milk therefore has a much higher fat percentage.

indicated in this calculation, however, and produce a somewhat larger proportion of cream from rich milk than from milk containing low percentages of fat. For this reason, the increase in the cream test may not be exactly in proportion to the increase in the test of the milk separated.

Rate of Inflow.—If the rate of inflow of milk into a separator bowl is markedly altered, a change in the fat content of the resulting cream is to be expected. When other conditions remain

constant, a reduction of inflow causes an increase in the percentage of fat in the resulting cream. In a trial by one of the authors, milk was fed into a separator as fast as possible by removing the regulating float and maintaining the receiving cup full of milk. The cream had a fat content of 16.3 per cent. The intake then was reduced by regulating the flow of milk to a point which maintained but a small amount in the receiving cup. The cream in the second case contained 20.5 per cent fat. It is clear that the increased fat percentage in the second trial was the result of a smaller total intake of milk. The rate of inflow is not subject to much variation with small-sized separators, because the inflow is regulated by a float in the receiving cup. The rate of inflow will be influenced somewhat by the height of the milk in the supply can. Through the variation in pressure exerted by this means the depth of milk in the supply cup is affected. When it contains a deep layer of milk somewhat more is forced into the bowl than when a small amount is in the container. Two trials by one of the authors gave the following results:

	Milk in supply tank	Fat content of cream, percentage
1	{ Low High	25 23
2	{ Low High	32.5 30.0

Separators of large capacity generally are fed from faucets attached directly to large supply tanks. With this arrangement, variations in the fat content of the cream are frequent and more pronounced than in the case of some machines where a float is used to regulate the intake.

The effect of rate of inflow on the percentage of fat in the cream is explained by a change in the ratio of flow through the cream and the skim-milk openings. A reduction in inflow results in the passage of a greater proportion of the intake through the skim-milk outlet and a smaller proportion through the cream outlet. The reduced proportion of cream is represented by skim milk diverted to the skim-milk outlet, which means that

the fat is contained in less cream which is necessarily of a higher test than at the greater inflow. A trial conducted by one of the authors shows the effect of this factor under rather extreme conditions. The inflow of milk was greatly reduced and all other factors kept uniform. The results were as follows:

Rate of flow, pounds per hour	Cream in percent- age of total intake	Fat in cream, percentage
956 (normal)	11.39	36
505	9.68	55

Amount of Flushing.—It is customary to flush the separator bowl just after the milk has all passed through the machine by allowing water or skim milk to flow into the milk intake. This is done to remove cream lodged within the various parts of the bowl and the cream spout. It is readily understood that the addition of water or skim milk to the cream, which will result during flushing, will lower the percentage of fat in the product. The degree to which the test of the cream will be affected depends upon the amount of cream separated and the amount of water or skim milk, or both, used for flushing. The test of a large amount of cream will not be lowered so much by the addition of a given amount of liquid as will a smaller amount. Also, a given amount of cream will be lowered in test proportionately as more flushing liquid is used.

Formation of Separator Slime.—With farm separators slime is rarely a factor in altering the fat content of cream, especially when these machines are washed properly after each separation. A slight reduction in the fat percentage of cream may result if large amounts of milk are separated and the machine is cleaned only after each second operation. The effect is more often noticed with power separators than with hand machines, because power machines often are operated continuously for 4 or 5 hours so that a very thick layer of slime forms on the inside of the bowl shell. When this takes place, the space where the skim milk passes between the dividing disc and shell of the bowl is reduced so that more and more skim milk is diverted to the cream outlet. One of the first indications of this condition is an increase in the size of the stream flowing from the cream spout. The increased flow is, therefore, a signal to stop and clean the bowl.

Variations under Practical Conditions.—Cream usually is bought and sold on the basis of the butter fat contained. The cream producer often is much concerned over the variation in the fat percentage from time to time. Sometimes he is inclined to question the accuracy with which the testing is done. He has not changed the cream screw; the same cows and the same feed are in use; and the separator is operated by the same man. With such conditions uniform why should the test vary from 2 to 5 per cent or even more from one delivery to another? The cream test, however, does vary even when the conditions mentioned are uniform. The cause or causes are to be found among those already described. It is impossible, in most cases, for the man who makes the test to explain the cause of the variation because he does not have the necessary facts at hand. On account of a lack of understanding of the subject, often some cause is suggested which only makes the situation more involved. With a proper understanding of the subject, certain facts may be connected with the variations experienced. For example, it is well known that the milk of fresh cows has a lower fat content than that of cows near the end of the milking period. If a certain herd has a large proportion of fresh cows, the test is likely to be lower. In the spring and early summer the milk is, as a rule, lower in fat, due to the seasonal variation described elsewhere, and this may be sufficient to reduce the test materially. At the same time, the warmer weather is responsible for the milk being separated at a higher temperature. Two factors may thus combine to reduce the fat percentage. The idea sometimes advanced that the feed of the cow is responsible for the changes in test is absurd in view of the fact that it is firmly established that the feed has no material effect upon the richness of milk. A sudden variation may be the result of using more water than usual for flushing the bowl. The temperature at which the milk was separated may have varied widely from the usual or the speed of the machine may have been abnormal. When sudden changes of any magnitude occur, the chances are that several factors combined to give the results noted. One of the authors made a test to determine the effect of combining the possible factors. A machine which had been skimming a cream testing 25 per cent fat was used. For one separation, all the conditions except adjustment of the cream screw were controlled to cause an increase in the fat content of the cream; in another

separation, conditions for a reduced test were combined. The conditions and results are shown by the following:

Separation	R.p.m.	Skim milk for flushing	Fat percentage in milk	Temperature milk	Rate of inflow	Fat percentage in cream
1	70	1.5 quarts	5.45	80°F.	Low	39.5
2	52	1.5 gallons	3.80	90°F.	High	14.0

The results are striking and show how an extreme effect upon the cream test may be produced without changing the cream screw. Here were established combinations of conditions, all of which exist at times in connection with milk separation. As a result, a separator set to deliver cream with 25 per cent of fat under usual conditions, in one case gave cream testing 39.5 in the other 14.0 per cent fat. It is improbable to be sure, that under practical conditions all of these factors will combine to cause such an extreme variation. It is certain, however, that often a combination of two or more is the explanation of a puzzling variation of considerable magnitude in the test. The authors do not infer that all variations in cream tests as made at the creamery or milk station are to be attributed to the conditions of separation. Accurate sampling and testing of cream are by no means easy tasks, and carelessness more often than dishonesty is responsible for a share of the unexplained changes in fat percentage, as experienced by the cream seller.

Efficiency of the Cream Separator.—The efficiency of any separator in removing the fat from the skim-milk portion of milk can be measured by the fat content of the skim-milk. A good separator, properly operated, leaves practically no fat in the skim milk. Many machines now in use consistently produce skim milk containing not over 0.01 per cent fat as determined by the Babcock method. Centrifugal separators are now so well constructed that a fat content of more than 0.03 per cent as measured by the Babcock test means that the machine either is mechanically imperfect or is incorrectly operated.

The cream separator is an exceedingly efficient machine. Even under ordinary conditions of operation, fully 99 per cent of the total fat in milk is recovered in the cream. This is in striking contrast to the shallow-pan system with an efficiency as measured by fat recovery of about 80 per cent and the deep-

setting system with an efficiency of 90 per cent. These figures will hardly convey to the reader the tremendous economic value of the cream separator to the world. A few applications make possible the full significance of the cream separator in modern dairy practice.

The average cow in the cow-test associations of the United States produces 289 pounds of fat in a year. If the milk of one of the average cows from this group was separated during the year by means of a centrifugal separator, the fat remaining in the skim milk at 50 cents per pound would be worth 43 cents. If the deep-setting system were used, the fat lost would have a value of \$14.45, and if the inefficient shallow-pan system was selected, the fat loss would amount to the sum of \$28.90. In 1926, the total butter production of the United States was a little over 2,000,000,000 pounds. Practically all of this was made from cream separated by means of a centrifugal machine. Had the shallow-pan system been used the total would have been reduced fully 400,000,000 pounds; if the deep-setting system had been employed the total would have been about 200,000,000 pounds below the amount actually manufactured. It is a safe statement that the cream separator in the United States saves butter each year that would otherwise be lost to a value of between \$150,000,000 and \$200,000,000.

Factors Governing the Efficiency of Separation.—A number of factors are known to affect the efficiency of separation. The most common causes of inefficiency of separation are, (1) mechanical conditions of machine, (2) low temperature of milk, (3) low speed of bowl, (4) high rate of inflow, (5) clogging of bowl, (6) production of excessively rich cream, and (7) separation of high acid milk.

Mechanical Conditions of Machine.—Occasionally, the spindle supports the bowl at such a level that the stream of cream from the cream outlet is split between the cream and the skim-milk pans, thus remixing some of the cream with the skim milk from which it was just separated. This difficulty is corrected by readjusting the height of the spindle, which usually can be done by means of an adjustment at the lower end of the spindle.

Cases have come to the attention of the authors where trouble resulted from an incorrect assembly of parts such as placing the discs wrong side up in the bowl, or, as is possible in at least one machine, operating the machine minus its dividing disc. This

difficulty now occurs less frequently than in the earlier days of the cream separator because the modern machines either are made so that they can be assembled in only one way, or the correct position of each part is clearly indicated by its construction. Such errors result in a high loss of fat in the skim milk. Occasionally, the discs become so badly worn that incomplete removal of the skim milk results. This fault may be remedied, in many cases, by adding an extra disc to the bowl. It is important that the separator be set level; otherwise, a vibration of the bowl occurs. This results in incomplete separation. The frame should be fixed firmly to a solid foundation to prevent even the slightest movement of the frame while the bowl is in operation. In setting up the separator the leveling should be done at the particular parts of the frame specified by the manufacturers.

Temperature of the Milk.—The temperature of the milk is a factor in the efficiency of separation. Some of the separators as constructed several years ago either clogged completely when the milk was too cold or showed a decided reduction in efficiency. The more modern machines are less subject to the effects of temperature but, as a rule, show a somewhat higher loss of fat in the skim milk, if the temperature of the milk separated is lowered materially. The decreased efficiency at the lower temperature results from the slower movement of the fat through the serum as a result of the increased viscosity of the cold milk. The clogging of a separator which sometimes occurs as the result of cold milk is due to the cream adhering to the bowl parts and moving slowly through the cream outlet.

In order to insure the greatest efficiency in the removal of fat during separation, care should be taken to bring the milk to the machine at a temperature as near 90°F. (32.2°C.) as possible. In dairy plants where large separators are in use some advantages are realized by separating at temperatures as high as 145°F. (62.8°C.). This temperature is often convenient because of previous pasteurization of the milk so that the hot milk may be separated before it is cooled. There is little, if any, lower loss of fat in such skim milk than from separation at 90°F. (32.2°C.). The chief advantage of separation at such high temperatures lies in preventing the extensive growth of microorganisms which occurs when milk is held long at 90°F. (32.2°C.).

Low Speed of Bowl.—If the separator bowl is operated at a speed lower than that prescribed by the manufacturer, a loss of fat

in skim milk is certain to result unless the milk inflow is reduced correspondingly. It is not difficult to understand why this is true. The speed of the bowl determines the amount of centrifugal force generated, and when the amount of centrifugal force is reduced appreciably, the fat cannot be removed as completely from the skim milk during the time it is traveling through the bowl as when greater force is used. If the rate of inflow of the milk is reduced with the speed, however, the milk traveling through the bowl more slowly is subjected to centrifugal force for a longer time; so that fairly efficient removal of fat from the skim milk is assured until the speed is reduced so noticeably that it would be apparent and corrected by the operator. One separator draws milk into its bowl by suction which is dependent on the speed of the bowl. It, therefore, functions automatically to reduce inflow with speed and, thus to a certain extent, avoids fat losses due to subnormal speed of the bowl. In the majority of separators, however, there is no device for automatic control of the rate of inflow by the speed of the bowl, and care should be exercised to insure correct bowl speed at all times.

The effect of bowl speed on the efficiency of separation is shown by Table XII. These data were taken under conditions where the rate of inflow was not varied appreciably. It is well to bear

TABLE XII.—THE EFFECT OF SPEED OF BOWL ON EFFICIENCY OF SEPARATION

Trial number	Fat lost in skim milk at different speeds, percentage		
	Normal speed	Three-fourths speed	Half speed
1	0.02	0.06	0.31
2	0.03	0.05	0.22
3	0.03	0.10	0.90
4	0.03	0.11	0.70
5	0.02	0.05	0.26
6	0.03	0.14	0.62

in mind, however, that the ordinary hand separator automatically increases its inflow slightly at higher speeds because of an increased centrifugal force which increases the output of cream and skim milk at their respective outlets and creates a slightly faster rate of travel through the bowl. This change is not

very significant, however, and at the lower speeds the reduction in rate of inflow thus caused is not sufficient to prevent an increased loss of fat in the skim milk.

High Rate of Inflow.—If milk travels through a separator bowl too rapidly it is subjected to centrifugal force for so short a time that complete removal of fat from the skim milk is impossible. The average farm separator includes an inflow-regulating device so arranged that the correct rate of inflow is insured within fairly narrow limits.

This device consists of a feed cup with an opening of a diameter which causes milk to enter the bowl at a constant rate when the level of the milk in the cup is kept the same. The level of the milk in the cup is kept nearly constant by the use of a float which rises against the faucet of the supply tank as the feed cup fills and retards flow into the cup. This arrangement does not insure entirely uniform inflow rate, however, because a greater pressure is exerted on the opening and the float when the supply tank is full than when it is nearly empty. Experiments have demonstrated that the fluctuations of inflow rate in hand separators are not sufficient, ordinarily, to affect the efficiency of separation.

Factory-size separators do not have so accurate a means for regulating the inflow and require careful supervision in this respect; otherwise, overfeeding of the bowl may take place with some unnecessary loss of fat in the skim milk.

Clogging of Bowl.—During centrifugal separation of milk a gray, sticky mass of material, known as separator slime, gathers on the wall of the bowl. This slime is composed of mucilaginous, nitrogenous material, a normal constituent of milk into which are gathered dirt and bacteria thrown so forcibly against it as to adhere to the walls. As separation continues this wall thickens, and it is possible in time to form a layer of slime thick enough to clog the separator bowl. The first indication of clogging is an increase in the flow of cream.

The efficiency of the separator may be affected to some extent before sufficient slime accumulates actually to clog the machine. The farm separator seldom is operated long enough for clogging to occur from an accumulation of slime. Where large quantities of milk are separated, as in whole-milk creameries, the condition may occur frequently unless the separator is stopped at intervals and the slime removed.

Acidity of Milk.—As pointed out elsewhere, unless milk is thoroughly cooled immediately after milking, the bacteria bring about decomposition at once. The most common change is the formation of acid. As soon as an appreciable amount of lactic acid has been formed, the condition of the casein begins to change. Before the milk is sour to the taste small particles of casein are visible under a lens, later a complete precipitation of casein occurs causing the common curdling of sour milk. After the milk has reached the point of curdling, it is clearly impossible to separate the cream. Milk, however, is often separated after a measurable amount of acid has formed. The formation of the acid does not interfere with the separation of the cream so far as the passage of the fat through the skim milk is concerned. If the fermentation of the milk has reached a point where particles of casein are present, however, this constituent will accumulate rapidly in the separator slime, resulting in frequent clogging of the bowl, and some reduction in the efficiency of separation.

The Factory Separator.—As was previously stated the factory separator preceded the hand machine or farm separator. The present day farm separator can be purchased with capacities ranging from 75 to 750 pounds of milk per hour. The factory separator is designed to handle from 2,000 to 12,000 pounds of milk per hour. Outstanding improvements in the design or construction of the separator are more frequently found in the machines designed for factory use. In recent years a decided improvement has been introduced in connection with the factory separator. These machines are now built so that no air is permitted to enter the bowl or to come in contact with the milk during separation. The milk is fed to the bowl from the bottom of the machine through a hollow spindle. The milk line leading to the hollow spindle is air tight as are the separator bowl and all fittings conducting the skim milk and cream from the machine. The cream forms in a column at the exact center of the bowl. To remove the cream from the bowl the machine is operated under pressure; thus milk is pumped into the machine and exerts a pressure on the cream column, forcing it from the machine. The per cent of fat in the cream is regulated by adjusting the pressure on the cream outlet. With these machines it is possible to separate cream to contain nearly 80 per cent of milk fat. Since no air enters with the milk as it reaches the separator bowl, there is no foaming of skim milk or cream.

EFFECT OF SEPARATION UPON THE MICROÖRGANISMS IN MILK

When milk is set in shallow or deep pans (as described previously) in order that the cream may rise to the surface, it will be found that a considerable percentage of the microörganisms in the milk pass upward into the cream layer with the fat globules.

This tendency for the microörganisms to gather with the fat near the surface is not the result of a specific gravity below that of the milk serum, but is due to a mechanical action. The microörganisms adhere to the surface of the fat globules and are in this manner carried to the upper layers with the cream.

Centrifugal Separation.—In the centrifugal separation of milk the bowl revolves at such a high rate of speed that considerable centrifugal force is exerted on the milk which may contain many microörganisms. Some of these microörganisms are thrown into the separator slime at the walls of the bowl but there does not seem to be any particular selectivity in this action. That is to say, there is no general tendency for certain types of microörganisms to be removed more effectively than others, although there is some evidence that the heavier mold spores, yeasts and larger bacteria, may be quite prominent in the separator slime but not to the exclusion of many other types, even the smallest of the bacteria. The difference in specific gravity between the various microörganisms is scarcely great enough to be a factor. On the other hand, many microörganisms become trapped in the more viscous cream and so attached to the fat globules and appear in considerable numbers in the cream. In practice, it is often found, as a result of this, that cream may have a somewhat higher bacterial count than the skim milk but the difference seldom is striking if the separator itself is not a source of contamination. Actually, large numbers of microörganisms are found in the separator slime in which are present many other substances such as proteins of milk (particles of precipitated casein in the case of abnormal or sour milk), traces of other milk constituents, fibrin, red or white corpuscles from the blood, body cells (complete or in fragments), and foreign material of many sorts.

Why the Bacterial Count May Be Increased.—The fact that cream often shows a higher bacterial "count" than the skim milk, or the whole milk from which it was separated, or that the total bacterial count of skim milk and cream exceeds that of the whole

milk, demands a word of explanation. If the separator itself is not a source of contamination, the bacterial "content" of the cream and skim milk together cannot be greater than the bacterial "content" of the original whole milk because it is known definitely that the separator slime contains large numbers of bacteria which have been removed during separation.

This distinction between "count" and "content" which is made in the case of separation (and later in clarification) is the difference between an apparent and a real situation. The plate "count" is merely a record of the number of individuals, pairs, chains, or clumps of bacteria or other forms, any one of which may produce a single colony on an agar plate. For example, there might have been 100 individual bacterial cells in a given portion of the milk before separation, 100 pairs, and 100 clumps, which would mean 300 colonies on a plate. Under the action of centrifugal force, half of the individuals might have been thrown to the wall of the bowl, all of the pairs broken up so that half of them (or 100 individuals) were caught in the slime of the bowl, and the hundred clumps, each of which might have contained 10 individuals, were disrupted so that half of the cells remained in the slime. The resulting total plate counts of the cream and the skim milk after separation under these conditions might have shown 650 colonies as compared with 300 before separation.

Disease Bacteria and the Separator.—The question sometimes arises as to whether or not disease-producing bacteria are removed from milk by the process of separation. In the case of gravity creaming, it has been found that certain types of pathogenic bacteria actually concentrate in the cream layer. In centrifugal separation some of these disease bacteria but not all of them are cast off in the slime accumulating in the bowl. A considerable proportion of them is distributed in both cream and skim milk, especially the former. Consequently, separation is not a process for increasing the safety of milk from the standpoint of disease-producing types of bacteria.

STRAINING, FILTRATION, AND CLARIFICATION OF MILK

Noticeable quantities of foreign material such as particles of dust, dirt, cinders, feeds, bedding, manure, dandruff, hairs, flies and many other undesirable substances may find their way into milk because of careless handling of milk at the dairy farm. This occurs principally at the time of milking. Other substances

may be present in various quantities and not represent contamination from filthy surroundings. Some of the worn-out cells making up the delicate lining of the udder, its ducts, alveoli, etc., may be cast off into the milk. Where inflammation of the udder occurs, much of the cell debris from the affected parts is accompanied by corpuscles, fibrin, and serum from the blood, much of which may escape detection. Many of these foreign substances, which have been mentioned above, usually carry large numbers of bacteria, some of them yeasts and mold spores. The particles that are soluble disappear but leave their burden of microorganisms in the liquid milk. The larger, insoluble portions release many of their bacteria and other forms when they are bathed in the fluid milk.

FIG. 37.—Strainer commonly used on dairy farms. A cotton filtering disc is held between two metal screens. The assembled strainer is placed over a can and the milk allowed to flow through the cotton disc by gravity. The strainer has a capacity of about 10 quarts. (*Courtesy, Creamery Package Company.*)

Straining.—The practice of straining milk was introduced to provide a means for removing some of the larger particles of foreign material so that the visible sediment in the milk might be reduced. This straining, in the ordinary sense, is accomplished on the dairy farm by means of miscellaneous pieces of cloth, cotton batting, wire gauze, or specially prepared strainer pads. These materials are able to remove principally the large particles, such as straw, hairs, insects, gross dirt, etc. Much of the filth and cell debris passes through the meshes of the strainer. The microorganisms, body cells, and leucocytes are so small that most of them pass through the strainers without restraint. Particles of dirt deposited on the strainers are washed subsequently by succeeding portions of milk so that their contribution of bacteria, etc., is added to the liquid which passes

through. Consequently, the ordinary straining of milk should not be depended upon to remove any considerable number of microorganisms. In fact, strainer cloths that are poorly washed and left unsterilized actually may add bacteria to the milk. The fact remains that ordinary straining does not reduce the bacterial content of milk perceptibly but merely removes some of the gross dirt which might appear as visible sediment in a bottle of milk.

Filtration.—In order to carry the cleansing of milk a step farther, various devices have been suggested for filtering milk through filters possessing pores much smaller than the ordinary strainer, cloth, or metal. The success attained in filtering water supplies and other liquids has served as a basis for such methods being applied to milk. For instance, the use of sponges, sand, and charcoal has been suggested, and these materials have been tried in an experimental way with various degrees of success. Sponges and sand prove impracticable as they lack capacity, are difficult to clean, and soon become clogged with dirt and milk constituents. Where sand is used, losses in butter fat are almost certain to occur. Charcoal has proven undesirable because it decolorizes the milk. In recent years, milk filtering devices which are provided with closely woven cotton cloths or cellulose pads have been used. The mesh of these filters is very fine and provides a much more efficient filtering capacity. They

FIG. 38.—Cross-sectional view of a horizontal milk filter for use in market-milk plants. The milk is pumped into the filter at the bottom, and passes into the chamber on the inside of the cylindrical filter. It is then forced through the filter cloth by the pressure and is discharged at the top of the filter. (Courtesy, Cherry-Burrell Corporation.)

are quite widely used in many sections of the country at the present time. In most cases, it is intended that these filter pads should be used but once and then discarded, since their efficiency is impaired or destroyed by washing. They are found to be effective in removing visible sediment from milk but do not filter

FIG. 39.—A centrifugal clarifier. This is a new type, air-tight, foamless clarifier which is very efficient in removing sediment from milk. (Courtesy, De Laval Separator Company.)

out the leucocytes, epithelial cells, cell fragments, or micro-organisms unless they are trapped on the large particles which make up the visible sediment.

Clarification.—The accumulation of dirt and slime in the bowl of the centrifugal separator undoubtedly suggested to early users of this machine that it could be used as a means of removing foreign materials from milk. In practice, some difficulties were experienced; the cream and the skim milk did not always mix

uniformly; a portion of the milk did not pass close to the periphery of the bowl, which reduced the efficiency; and the space in the bowl for the accumulation of slime was inadequate. As a result, a modified centrifugal separator known as the "centrifugal clarifier" was introduced.

FIG. 40.—Cross-sectional view of De Laval Clarifier. The milk is fed into the bowl from the bottom through the hollow spindle, under pressure from a pump. The sediment is thrown to the wall of the bowl in the space provided beyond the discs. The milk is discharged from the center of the bowl at the top. (Courtesy, De Laval Separator Company.)

In the centrifugal clarifier, the speed of the bowl is reduced so that little separation of the cream occurs. This is prevented further by a construction of the discs in certain types of centrifugal clarifiers, which compels all of the milk to be subjected to the same degree of centrifugal force by passing near the periphery of the bowl. Furthermore, a greater space outside the discs is permitted for the gathering of the heavier material on the walls

of the bowl. Instead of two outlets as in the separator, only one for the unseparated whole milk is provided in the clarifier.

Efficiency in Removing Sediment.—In general, it may be said that the clarifier is the most effective, practical device which is available for improving the quality of milk by removing extraneous foreign material which, unfortunately, may have gained access to the milk during its production and subsequent handling. Due to the fact that most of the dirt, filth, and cell debris present in milk is of higher specific gravity than the milk itself, it is to be expected that a major portion of this foreign material will be thrown out by the clarifier and be collected on the walls of the bowl. The efficiency in removing insoluble dirt is very high, in fact, it is possible to pass through the clarifier milk that has been filtered in the ordinary way and recover in the clarifier slime noticeable quantities of insoluble dirt which has not been removed by filtration. Many of these particles of sediment would be too small to be held back by a filter or to be visible to the naked eye. Milk properly clarified shows no indication of a sediment after standing in a glass bottle.

An examination of the material which is removed by the centrifugal clarifier will reveal a "slime" quite similar to separator slime. It will be found to contain large amounts of actual milk constituents, especially protein substances or particles of precipitated casein, insoluble dirt, and foreign material of all sorts, fibrin, leucocytes, and red blood corpuscles, various cell fragments, and large numbers of microorganisms; in fact anything that readily responds to centrifugal force.

Effect upon Bacterial Count.—If a bacteriological analysis is made of clarified milk it may be found that the milk has either a higher or a lower bacterial count as determined by the plate method than it did before clarification. Whether the bacterial count will be higher or lower after clarification will depend upon a number of different conditions but when the clarifier itself is cleaned and well sterilized before use, the *actual numbers* of microorganisms in clarified milk will be considerably lower than in the milk before clarification because it has been demonstrated that large numbers of organisms are thrown out into the clarifier slime. When the plate count is higher after clarification, it is only an apparent increase or the clarifier has been improperly cleaned. The explanation for these differences between bacterial "counts" and the bacterial "content" or actual numbers has been

given under separation and the same reasons hold for the results obtained during clarification.

The clarifier is not able to remove specific types of bacteria from milk in such a way that it could be depended upon to make milk safer. Some of the disease-producing bacteria may be thrown out into the slime but the majority will be discharged with the milk. Consequently, clarification is not a health measure in the sense that it removes pathogenic bacteria from milk.

Effect upon Keeping Qualities of Milk.—Does clarification improve the keeping quality of milk? The answer is, probably not. While results are not always the same, there is a tendency for clarified milk to show slightly poorer keeping quality probably because of the more uniform distribution of the bacteria in the milk. In any case, however, this difference in keeping quality is not sufficiently great to be worth much consideration. The advantage reached by improving the cleanliness of the milk is far more important than the differences in keeping quality.

Effect upon Cream Line.—Market milkmen are interested in the effect which clarification may have upon the creaming ability of milk since the housewife is so interested in the cream line. Clarification carried out at temperatures below 90°F. (32.2°C.) has little or no effect on the creaming ability of milk. It would be almost too slight to detect in an ordinary milk bottle. When the temperatures of clarification are higher the cream line may be affected noticeably.

PASTEURIZATION

The preservation of foodstuffs by the application of heat undoubtedly has been practiced as long as fire has been known. Pasteurization derives its name from the eminent French scientist, Louis Pasteur, who during his studies in the years 1860 to 1870 found that heating certain liquids, especially wines, to a high temperature, such as 140°F. (60°C.), improved their keeping qualities. This process is widely employed in all branches of the dairy industry. In general terms, it is the heating of milk or other dairy products to a temperature which destroys nearly all of the microorganisms present in that product without seriously affecting the composition or properties of the product. It should be followed by immediate cooling of the product to a temperature sufficiently low to check the growth of the microorganisms which are resistant to the temperature used. Pas-

teurization came into use on a commercial scale in dairy establishments shortly after 1880 in Germany and Denmark. At the present time, it is considered an essential feature in the manufacture of butter and ice cream and in the market-milk industry. It is also spreading rapidly to the cheese industry. Many states have established regulations regarding the pasteurization of milk and cream designed for direct consumption. For example, one state requires that milk or cream to be labeled, "Pasteurized," must have been heated to a temperature of at least 145°F. (62.8°C.) and held at or above that temperature for a period of at least 30 minutes.

The practice has become common to attach a recording thermometer to pasteurizing equipment in order that a record may be available of the temperature to which the product has been subjected. In certain cities a record of this kind is required for the inspection of the control officials.

Relation of Pasteurization to Microorganisms.—Fundamentally, pasteurization is a health measure but actually it is also a commercial expedient. It has been found that a temperature of 142°F. (61.11°C.) maintained for 30 minutes is sufficient to destroy the common disease-producing types of bacteria, such as those of tuberculosis, typhoid fever, scarlet fever, diphtheria, undulant fever, etc., which sometimes are present in milk. Besides, under these conditions approximately 99 per cent of all bacteria are destroyed, as well as most of the yeasts and molds. By the process of pasteurization, milk is rendered safe and commercially attains a better keeping quality. It also provides a substratum in which desirable fermentations can be carried on with greater assurance of success. After the product has been pasteurized, however, all precautions must be taken to prevent recontamination. Furthermore, it must be kept under conditions which will prevent the development of those organisms which have survived. Pasteurization is not a cure-all nor is it foolproof. As much judgment must be exercised in the handling of the pasteurized product as in the case of the raw material.

Methods of Pasteurization.—Two general methods of pasteurization are in use. One is known as the "holding" system and the other as the "flash."

The Holding System.—The holding system consists in bringing the milk or cream to a suitable temperature, usually 142–143°F.

(61.11–61.67°C.) and holding it at that point for at least 30 minutes followed by rapid cooling. A higher temperature may be used in which case, the time of holding may be shortened, for example, 155°F. (68.3°C.) for 20 minutes or 165°F. (73.9°C.) for 15 minutes. A careful control of both temperature and time of heating is important.

The consumer of retail milk expects a deep layer of cream to appear in the upper part of the milk bottle with a sharp line of division between the milk and the cream. The use of a temperature much above 143°F. (61.67°C.) causes physical changes in the condition of the milk as a result of which the so-called "cream line" of the milk is reduced and the milk is judged by the consumer to be low in cream content. The special advantage of the holding system is its high efficiency in reducing the bacterial content without affecting the cream line seriously. For this reason this system is used extensively when milk or cream designed for the retail trade is subjected to pasteurization.

The Flash System.—The machines used are so constructed as to make possible a continuous operation and for this reason sometimes are called "continuous flow" or "short-time, high-temperature" pasteurizers. The system depends upon raising the temperature of the milk or cream quickly to at least 160 to 180°F. (71.1 to 82.2°C.) and often higher, for a few seconds as it passes through the machine. Quick cooling follows.

The flash system is especially applicable to the pasteurization of cream for buttermaking. Its chief advantage in creamery operation is the rapidity with which the process is conducted and the smaller expenditure required for equipment necessary to handle a given amount of cream. It is more commonly used in large creameries where one million or more pounds of butter are made annually.

The flash system has not been used so extensively for the treatment of milk or cream designed for direct consumption. One reason is that some health authorities are not convinced that this type of pasteurization can be relied upon to destroy the disease-producing organisms. Another objection raised is that the high temperature employed may exert an appreciable effect on the taste of the milk, giving it a slightly cooked flavor. The cream line, so important in the sale of milk at retail, also was thought to be seriously affected by this type of pasteurization. These latter objections, however, have been overcome in

recently designed types of short-time, high-temperature pasteurizers especially built for pasteurizing market milk and cream. They operate usually at 160°F. (71.11°C.) for about 20 seconds.

(a)

(b)

FIG. 41.—A horizontal-coil pasteurizer, motor-driven. This type of pasteurizer is used very commonly in creameries and milk plants. The coils (A) illustrated in the sectional view (b) are driven by gears (C) directly attached to an electric motor and carry the heating or cooling medium, while agitating the milk or cream. The vat is insulated (B) thoroughly. (Courtesy, Creamery Package Manufacturing Company.)

Those in use at the present time employ hot water or electricity as the heating medium, and may be either the electric or the so-called "plate" or "internal tubular" type of equipment.

Construction of the Holding Pasteurizers.—There are several different types of holding pasteurizers on the market. These

machines differ from one another primarily in their shape, general construction, and the method employed in agitating the milk or cream during the heating and cooling processes.

Coil Vats.—The most common type of holding pasteurizer is the coil vat. This machine consists of a rectangular or square tank constructed of tinned copper, nickel, glass-lined steel, or chromium steel. The sides and the bottom are insulated with cork or other insulating material which is encased in a wooden or a steel covering. A lid of the same construction is provided to cover the entire tank. A coil is suspended lengthwise in the rectangular vat. The coil is constructed of the same material as the tank and consists of hollow tubing, 2 to 4 inches in diameter and encircles spirally a central shaft. The shaft is set on a line representing the center of the tank from end to end. The coiled tubing is placed at a fixed distance from the shaft in such a manner as to carry the coil to a point within 2 or 3 inches of the sides of the tank. The coil is connected directly with the shaft at both ends so that water may enter from the outside of the vat through the shaft, into the coil, and out of the vat through the shaft at the opposite end. By revolving the shaft by means of the power-driven gearing at the end of the pasteurizer, the milk or cream can be agitated and by passing hot or cold water through the coil, the milk or cream may be heated or cooled. A relatively small tank is provided, generally at the end of the vat (it may be a part of the main vat or a separate tank), to hold the water used in heating and cooling. The square type of pasteurizer is constructed in much the same manner as the rectangular vat except that the coil is suspended vertically in the tank.

Glass-lined Tanks.—Another type of holding pasteurizer is a kettle-shaped tank constructed of steel, which is enameled with glass on the inside. Surrounding the glass-lined tank is a second tank of steel with an air space between the two. The entire vat is often covered with an insulating material. Milk is agitated in the vat by means of a propeller set at one side and near the bottom of the tank. Milk or cream is heated by passing hot water or live steam into the space between the two tanks. At the same time, the propeller is kept in motion to stir the milk. Cooling is very slow in such tanks and for this reason a surface or tubular cooler generally is used in connection with this type of a pasteurizer.

Stainless-steel Tanks.—With the development of chromium-nickel-steel alloys, holding tanks have been placed on the market in a great variety of designs. The resistance of these alloys to corrosion or attack by dairy products has made them extremely

FIG. 42.—A glass-lined pasteurizer. This equipment is used for pasteurizing milk or cream. It represents the "holder" type of pasteurizer. (Courtesy, The Pfaunder Company.)

popular in the milk industry in other equipment as well as holders used in the pasteurization process.

Spray Vats.—Still another type of holding pasteurizer is known as the "spray pasteurizer." This type of holder consists of a long, deep, double-walled tank, the general construction of which, in some instances, is somewhat similar to that of the coil vats. The milk or cream in this type of pasteurizer is agitated very gently by slowly moving paddles which are suspended vertically in the tank containing the milk. Heating or cooling is accom-

plished in this type of pasteurizer by circulating hot or cold water through spraying devices against the side walls of the inner vat by means of a pump.

Construction of Flash Pasteurizers.—There are several types of flash or continuous pasteurizers on the market. These machines are constructed of heavy copper, nickel, or chromium steel. If copper is used, that part coming in contact with the milk should be heavily tinned. The common types in use are the

FIG. 43.—A spray-type of pasteurizer. The spray pasteurizer is provided with slowly moving paddles which keep the milk or cream agitated, while hot or cold water is sprayed in a continuous stream along the side walls of the vat. (Courtesy, Cherry-Burrell Corporation.)

Danish-style heater, the film heater, and the internal-tubular heater.

The Danish Heater.—The Danish heater consists of a double-walled cylinder placed on end with a height about double the diameter. The milk or cream passes continuously through the inner compartment while the heating medium, live steam or hot water, is allowed to enter the compartment between the two walls. A rapidly revolving paddle keeps the milk in a thin layer against the heated wall of the inner compartment. The time required for a particular portion of milk to pass through the machine varies from a fraction of a minute to not more than 2 minutes.

Drum or Film Heater.—This type of flash pasteurizer consists of two drums, one within the other, which are heated by means of steam or hot water. Milk to be heated passes in a thin film

between the heated surfaces and thus is raised very quickly to the desired temperature.

Internal-tubular Heater.—This consists of a series of two tubes, one within the other. Milk flows through the inner tube while steam or hot water is introduced into the outer tube which surrounds the inner tube. In this manner milk or cream flowing through the inner tube is heated to a desired temperature.

Plate-type Pasteurizer.—For a number of years the plate type of heat exchanger has been used for heating or cooling liquids.

FIG. 44.—A continuous or flash pasteurizer. The continuous pasteurizer on the right is connected directly to a tubular cooler which may be simply a surface cooler or a regenerator. This type of set-up is more common in creameries. (Courtesy, Cherry-Burrell Corporation.)

Recently this system has been employed in connection with the pasteurization of milk and cream. European dairies employed these types of flash pasteurizers some time before they were accepted in America.

The plate pasteurizer consists of a compact group of relatively thin metal plates that are held tightly together in a press. The plates are so designed as to permit the flow in opposite directions of milk and water in a thin film between two plates. Milk is brought to the pasteurization temperature in a few seconds. Additional plates permit the cooling of milk very quickly. By

adding still more plates a regenerative system is included, which employs hot milk to heat incoming cold milk and cold milk to cool outgoing hot milk, thus making very efficient use of the heat employed in the process. The principle employed in this type of pasteurizer is used when passing milk and hot or cold water through relatively small tubes, which results in heating and cooling in even shorter time. By almost instant heating and cooling, the creaming ability and original flavor of milk are retained.

Cooling Milk or Cream.—After milk or cream has been subjected to the temperature desired in connection with the flash system of pasteurization, the product generally is cooled by passing it over a surface tubular cooler. Such a cooler consists of a series of hollow tubes constructed of tinned copper, nickel, monel metal, chromium steel, or German silver through which cold water or cold brine may pass and over which the hot milk or cream is allowed to flow in a thin layer. Frequently, the cooler consists of two sections, one set above the other. Cold water is permitted to flow through the upper section and cold brine from a tank of brine, cooled by mechanical refrigeration is connected with the lower section. By means of such an arrangement milk or cream is cooled very quickly to much lower temperatures than can be accomplished with the water available. Ammonia may be allowed to expand directly into the lower section and thus do away with the use of brine. Internal-tubular coolers, similar to the internal-tubular heaters, also are used commonly.

In some cases, the same type of cooler is used to cool milk or cream following the heating process in a holding vat. This procedure shortens the time required to complete the pasteurizing process by reducing the period used in cooling. Flash pasteurizers of the type described are also sometimes employed as coolers by using cold water or brine in the same way that steam is used when heating.

In-the-bottle Pasteurization.—The “in-the-bottle” system of pasteurization is used to a limited extent in the pasteurization of milk and cream for market milk trade. The system consists of placing bottled milk and cream in a tightly closed chest, some types of which have been constructed of wood, some of steel, and others of concrete. By heating the chest, and by carefully controlling the steam permitted to enter the chest, the milk is

heated to the pasteurizing temperature used in the holding method. Cooling is accomplished very slowly by spraying water, first hot and then cold against the bottles, slowly lowering the temperature so as not to chill the glass bottles too quickly.

Electrical Pasteurization of Milk.—During a number of years attempts have been made to devise a practical and satisfactory method of pasteurizing milk by an electric current. So far these attempts have met with little commercial acceptance. The most modern form consists of a regenerative preheater, where the milk is brought to about 120°F. (48.89°C.), and the pasteurizer proper, consisting of a rectangular, vertical chamber 2 feet high and 3 by 4 inches in cross section, with two sides made up of carbon electrodes about 3 inches apart. The milk flows between these electrodes, and the temperature of the milk is raised to 161–163°F. (71.67–72.78°C.) by the resistance offered by the milk to the passage of a 220 volt alternating current. The milk is exposed at this temperature for 10 to 15 seconds, after which it is cooled.

HOMOGENIZATION

The process of rendering milk, cream, certain types of cheese, and condensed milk homogeneous is termed “homogenization.” The machines used to accomplish this purpose are known as “homogenizers.” The first machine was invented by August Gaulin, of Paris, France, in 1902. It was introduced into the United States in 1904. Since the invention, however, of the Gaulin machine others have been introduced, such as the “Progress homogenizer” and the “viscolizer.”

Construction of the Homogenizer.—Although there are several different homogenizers on the market the principle of these machines is similar. They consist of a single-acting triplex pump with each cylinder having a suction and a discharge valve. The discharge valve of each pump empties into a common discharge pipe in which is placed a special valve. The valve in the discharge pipe is similar to a safety or a release valve so constructed that the operator of the machine may vary the pressure required to force a liquid through it. A more recent type of homogenizer is equipped with two valves on the discharge line so that it can be operated at two different pressures. The advantage of this type of machine is discussed in a later paragraph.

Action of the Homogenizer.—When milk or cream is passed through the homogenizer there is a decided reduction in the size of the fat globules. Further, there is an increase in the viscosity of milk or cream which increases the resistance which the smaller fat globules must overcome if they are to move upward. The increase in viscosity is attributed to the larger proportion of the proteins of milk adsorbed on the surfaces of the increased number of fat globules. Although experimental evidence is lacking

FIG. 45.—Homogenizer. Milk or cream intended for market milk or cream may be passed through the homogenizer when it is desired that the butter fat remain in a more permanent emulsion. When the mixture used in making ice cream is passed through the homogenizer, the finished ice cream has a smoother and more velvety texture. (*Courtesy, Manton-Gaulin Manufacturing Company, Inc.*)

there is some indication that homogenization influences the physical structure of casein in milk or cream.

Use of the Homogenizer.—Milk for the market-milk trade is seldom homogenized, as the process destroys the creaming ability of milk. The practical application of the process in connection with milk is found in the manufacture of dry milk when it is desired that the creaming properties of the reconstructed milk be destroyed.

When cream is homogenized the fat globules will not rise readily, and it takes on a smooth, more uniform and viscous body, and appears richer in butter fat than untreated cream. The process is, therefore, used to some extent in preparing cream for

retail trade. It is especially useful in preparing cream of the grade known as "coffee cream." The homogenization of cream retards its whipping properties. Market cream is homogenized at relatively low pressures.

In the manufacture of ice cream the entire mix is passed through the homogenizer immediately after pasteurization. The result is a smoother texture in the finished ice cream than can be obtained otherwise. In addition, the ice-cream mix can be frozen

FIG. 46.—The influence of the homogenizer on the fat globules. Fat globules shown in (a) represent the appearance of the fat globules in cream. The sample is diluted in order to show more clearly their appearance. (b) Illustrates the fat globules from some of the same cream after being homogenized at a 2,000-pound pressure. Note the clumping of numerous globules which is the characteristic appearance of the fat globules after homogenizing. Magnified 735 times.

without danger of the fat globules churning in the freezer, as cream which is homogenized at high pressures cannot be churned under normal conditions. The two-stage valve homogenizer frequently is used by ice-cream manufacturers. A relatively high pressure (2,500 to 3,500 pounds per square inch) is maintained on the first valve and a relatively low (1,500 to 2,000 pounds per square inch) pressure is used on the second valve. The result of this procedure is a reduction in the viscosity that may occur normally when the ice-cream mixture is homogenized at relatively high pressures.

Evaporated whole milks are homogenized after leaving the vacuum pan to prevent the churning of fat or the creaming of the

evaporated milk after it is placed in cans or barrels. Likewise, cream to be used in making cream cheese is homogenized to insure the retention of the fat of the cream in the finished cheese.

Reconstituted Milk and Cream.—Reconstituted milk or cream can be prepared by use of the homogenizer by mixing butter oil or butter with skim milk. Skim milk may be freshly separated or prepared from dried skim milk and water. Such a practice may be followed by various dairy manufacturing plants during a season of shortage or in sections where the production of milk fails to meet the local demand for dairy products.

EMULSIFICATION

In addition to the machines known as homogenizers there are a number of machines used in dairy plants and designed to accomplish somewhat the same purpose. These are known as “emulsors,” “emulsers,” “creamers,” and “emulsifiers.” These machines act on the fat globule but do not reduce its size as markedly as do the homogenizers. Neither do these machines influence the viscosity or affect the proteins of milk as noticeably as the homogenizers. In general, there are two types of machines used for the emulsification of milk and cream. One works on a principle similar to that of a steam injector, drawing the milk or cream into a tube from which it is discharged with considerable force against a cone of fine wire mesh. The other type has the outward appearance of a cream separator. By subjecting milk or cream to centrifugal force and releasing it through tightly fitting steel discs or through small openings a reduction in size of the fat globules results. The machines are used, primarily, in small milk plants where it is desired to produce “coffee cream” on which the fat will not readily rise.

CHAPTER IX

MARKET MILK

The term "market milk" is understood to mean milk in the fluid state, sold to the consumer for direct consumption. In this way, it is differentiated from milk which is destined for use in the manufacture of dairy products, such as cheese, butter, ice cream, condensed or dry milk. Market milk, in a general way, also includes the cream sold directly to the consumer for household purposes.

The market-milk industry is one of tremendous size considered either from the amount of product concerned, the number of people who work in the industry, or the capital represented. First of all, nearly all of the city and the village population, numbering over 60,000,000 in the United States, are milk consumers. On the average, each person in this country consumes about 40 gallons of milk yearly, or slightly less than one pint a day. Approximately 1,000,000 persons are engaged in caring for the cows that produce the milk and in getting the product to the market. New York City alone uses over 1,000,000,000 quarts of milk and over 50,000,000 quarts of cream a year. Placed in tank cars, each holding 50,000 pounds, this would require over 100 cars to haul a supply for one day. The milk producers receive for the milk, sold at wholesale for market milk purposes, the sum of nearly \$1,000,000,000 annually, while the cost to the consumers is practically double this figure.

Stages of Development.—The market-milk industry has developed coincidentally with the growth of the large urban centers of population. The industry has its foundation in the milk supply furnished almost in the dooryard by the family cow. In many instances this situation still exists. With the development of communities, certain families buy their milk from neighbors who keep enough cows to supply local demands. Under these conditions the consumer is in a position to know the methods practiced in producing and handling the milk and

the product reaches him promptly, usually within a few hours after milking.

The small city, ordinarily, is supplied with milk produced on specialized dairy farms within a few miles of the city and often delivered by the dairyman directly to the consumer. Under these conditions the consumer usually knows the source of his milk supply and can readily obtain some information concerning

FIG. 47.—A modern dairy barn. It will be noted that the buildings and premises are well cared for and that everything appears clean and orderly. The convenient milkhouse is evident at the left of the barn. Plenty of light and ventilation are provided.

the conditions under which the business is conducted. As the city becomes larger, a supply of this type becomes inadequate, and the conditions are such that it is no longer profitable to operate dairies near the city.

The next stage is shipment by train or by truck. Farmers some distance from the city, learning of the good market for milk afforded by the city, arrange with the railroads for special transportation in the form of milk trains scheduled at suitable hours. This makes possible the production of milk where the land is relatively cheap, and where the feed for the animals is produced, for the cities many miles away. The individual producer no longer can deliver milk to the consumer. An intermediary organization, therefore, takes over the distributing function, buying milk from the producer, processing it in suitable plants, and distributing it to the customers.

Complexity of the Problem.—In every state, the practices described may be observed; namely, the family cow, the local dairyman selling directly to the consumer, and about every large city, the complicated organizations necessary to supply the great center of population. The complexity of the problem is evident. New York, for example, receives milk from 65,000 farms representing at least seven states and two provinces of Canada. Regular daily shipments are made for a distance of nearly 500 miles. Sweet cream is shipped by carloads from Minnesota, Wisconsin, and other midwest states, to supply the cities of the eastern seaboard. Milk is shipped in tank cars from Wisconsin to Florida.

The time that necessarily must elapse from the time the milk is produced until it reaches the consumer requires the use of the best methods and equipment modern science and engineering have been able to devise. Furthermore, it is evident that business enterprises with large financial resources and competent management must shoulder the responsibility of organizing the collection of the milk in the country, the transportation to the city, the processing in the city, and, finally, the sale and distribution to millions of consumers.

The Necessity for Public Supervision.—It is clear that when the source of supply is removed to a point many miles distant, the milk cannot reach the consumer so promptly as when it is purchased from a neighbor. Milk is a very perishable food product, outstanding in importance as a food, but dangerous if not in proper condition. During shipment, or when the milk reaches the city distributing plant, it is placed in large containers each of which represents the product of many, possibly even hundreds of farms. As a result of these conditions, which are necessary in supplying a large city with milk, the city consumer seldom, if ever, sees the farms where the milk which he uses, is produced. In fact, the typical consumer in the large city never even visits the city distributing plant from which his milk is purchased, and has no information whatever as to the source of the product he uses. The consumer no longer has any means of judging the conditions under which his milk has been produced. He is not qualified to judge concerning the freedom of the product from adulterations. Clearly some governmental agency must take over this function.

PRODUCTION OF MARKET MILK

The starting point in the market-milk industry is the farm. The farmer who undertakes the production of market milk is confronted with many serious problems. First of all, he must be able to obtain a fair return for the use of his capital and labor. The successful accomplishment of this end involves the difficult problems of maintaining a healthy herd, breeding and raising, or purchasing, cows with sufficient milk-producing capacity to make possible economical milk production. The entire farm must be properly organized to make possible a satisfactory income without too great an expense for labor. The farmer must understand the feeding and the care of dairy cows and how to supervise labor. Feed must be grown so far as is practical and economical, and the remainder purchased to the best advantage. Finally, his product must be marketed to the best advantage. These requirements concern the economics of production. The milk producer is confronted with still other exceedingly important questions; such as that of maintaining conditions on the farm which will make possible a safe, clean product acceptable to the city consumer and the control official. A consideration of the economic factors is beyond the scope of this discussion. Attention will, however, be directed towards those problems of health, cleanliness, and keeping quality of the product, which must be taken into account to insure a wholesome and a safe milk supply.

Clean, Healthy Cows.—Inasmuch as certain diseases may be transmitted through the milk from a cow, it is absolutely essential that all cows that are producing milk for the market trade should be free from any infectious or contagious disease. A healthy cow is a prime requisite for safe milk. All milk-producing cows should be free from diseases such as tuberculosis, contagious abortion, mastitis or garget, actinomycosis or lumpy jaw, etc. Regular tuberculin tests should be made and all infected animals removed from the herd. Blood tests for contagious abortion will make it possible to eliminate cows suffering from this disease. Whenever the udder of a cow is inflamed or swollen, as it is when the animal is affected with garget or mastitis, and the milk is abnormal and made up largely of stringy, watery substances, such milk should be discarded, the animal isolated from the rest

of the herd, and a veterinarian consulted. Conditions such as actinomycosis (lumpy jaw), running sores, etc. are sufficient reasons for rejecting the milk for human consumption. In other words, whenever a cow is suffering from some disease or infection there is a possibility that disease-producing bacteria may find their way into milk and be responsible for serious infections in children or adults who consume such milk.

FIG. 48.—Interior view of a modern dairy barn at milking time. The cows, floors, and stalls are clean. The milkers are wearing clean, white suits and using small-top pails.

Much of the dirt which gains access to milk comes from the body of the cow, particularly from the flanks and udder. When the cow is kept clean, the purity of the milk is enhanced as well as its keeping quality. At the time of milking the cows should be especially clean. It is a very good practice to keep the udder and rear quarters clipped and to wipe them off with a damp cloth just before milking. The habitat of the cow is such that she naturally picks up considerable dirt on her shaggy coat and it becomes absolutely necessary to pay some attention to the

cleanliness of her posterior regions if clean, wholesome milk is to be produced.

Proper Construction of Barns.—The cleanliness of stables, particularly of stalls, floors, and gutters, is of vital importance from the standpoint of the cleanliness of the cow. The construction of the barn has a great deal to do with this. Stalls should be of proper length so that the droppings of the cow fall into gutters provided to catch them. Floors and gutters should be made of impervious material such as concrete and be sloped sufficiently well so that all liquid material may drain away promptly. Walls and ceilings should be tight so that they may be kept clean and not be resting places for dust and dirt. If the floor of the stable is kept clean, and fresh, clean bedding is provided, the animals are not so apt to become dirty as where there are accumulations of manure and filth to soil continuously the flanks and udder. Clean, healthy cows are an absolute requirement.

Small-topped Pail.—One of the most satisfactory methods for keeping down the bacterial and dirt content of milk is the so-called small-topped or hooded pail. By means of this type of milk pail a considerable part of bacteria-laden dirt is excluded from the milk. It has been found sufficiently satisfactory to justify special emphasis. Of course, if a milking machine is employed, that serves the same purpose unless it is carelessly handled in moving from cow to cow. Even in this case the small-topped pail should be used for strippings. By means of the hood over the pail, a good share of the dirt which might fall into the milk pail from the body of the cow is diverted. In this way the quality of the milk is certain to be enhanced.

Clean, Healthy People.—Any one intimately connected with the production or handling of milk should be in good health and be clean in his habits. Certain of the serious epidemic diseases are carried through milk which has been infected by persons in contact with the milk at some point at the dairy farm or before it reaches the consumer. The personal factor is of tremendous importance in the production of a clean milk. If the milker is slovenly in his habits, it will usually follow that he is careless in his methods about the dairy, neglecting the cleaning of cows or the stable, the washing and sterilizing of utensils, and other necessary procedures. On the other hand, where the dairyman is careful about his personal habits, dress, etc., he usually will be attentive to all details of sanitation. The personnel employed

on dairy farms and elsewhere in the milk business should be free from contagious or infectious diseases and be neat in person and in their care of the animals and details of dairy hygiene.

Clean and Sterilized Utensils.—Under ordinary farm conditions the utensils are to be considered as the greatest single source of bacteria and often contribute large numbers of organisms to an otherwise high-quality milk. Clean, sterilized, and *dry* utensils are absolute necessities in the production of milk with a low bacterial content and high keeping quality. Milk is brought into contact with a great variety of utensils from the time it leaves the cow until it is placed before the consumer. As was previously pointed out, utensils often are serious sources of contamination, and have a great influence upon the keeping quality of the milk. The utensils not only must appear clean but be clean bacteriologically. This means that they must be rinsed, washed, and sterilized as soon as possible after they have been used. Metal utensils such as pails, cans, separator parts, etc., should be rinsed with cold or lukewarm water after each milking; that is, morning and night. This removes much of the milk. After this is done they should be washed and scrubbed with a brush, using plenty of clean, warm water to which some detergent or washing powder has been added. This is necessary in order to rid the utensils of the film of fat. Then they should be rinsed with plenty of warm or hot water before being sterilized. They may be sterilized by means of hot water, steam, or chemicals such as the chlorine solutions of one kind or another. The hot water or steam is to be preferred if there is an ample supply of either. The point to bear in mind, however, is that the water must be hot enough and used in sufficient quantities so that it may sterilize and make the metal so hot that it is uncomfortable to touch with the bare hands. If steam is used it must be applied sufficiently long to do likewise. When this is done the utensils will dry quickly and, as pointed out elsewhere, this is a very important part of the effectiveness of sterilization and prevention of further growth of microorganisms. Where hot water and steam are not available one may resort to the use of some of the hypochlorite or chloramine solutions. These are quite effective if used when they have the proper amount of available chlorine (not less than 50 parts per million) and when the utensils are cleaned thoroughly.

Strainer cloths should be washed, boiled, and dried after each milking period or replaced by a new cloth twice a day.

The Milking Machine and Separator.—The milking machine has found its way into dairying more extensively each year. It is a labor saver and the majority of milking machines on the market are reasonably satisfactory mechanically. From the standpoint of clean milk production, there is no reason why a high quality of milk cannot be produced where milking machines are used, provided the parts of the milker in contact with milk are kept scrupulously clean. Where milking machines are employed especial care must be exercised to maintain them in a good sanitary condition. They should be rinsed, washed, and sterilized twice a day. The latter may be accomplished by means of hot water over 180°F. (82.2°C.) or by chlorine or other chemical solutions.

The separator is a piece of equipment which is often neglected. The parts of the separator that come into contact with the milk, cream, or skim milk should be washed, sterilized, and dried each time after they are used; otherwise, there is an accumulation of remnants of milk and slime in the bowl which contribute tremendous numbers of microorganisms to milk passing through such a neglected separator.

Prompt, Efficient Cooling.—Inasmuch as milk produced even under the very best conditions contains some bacteria, it must be cooled as soon as possible in order to check the growth of the organisms present and maintain the keeping quality of the milk. As soon as the milking is completed the milk should be cooled thoroughly. This may be accomplished in a number of different ways. The milk may be passed over a special cooler after milking each cow or as a whole when the herd is all milked. Cans may be placed in a tank of cold water and each pail of milk emptied into the can immediately. Otherwise, the filled cans may be set in a tank of cold, or iced, water and cooled. Cooling is facilitated and accelerated by frequent stirring of the milk. The best cooling medium is water or brine. These may be utilized through the agency of the coolers mentioned previously or in a concrete tank. The thing to bear in mind is that the milk should be cooled just as quickly as possible, while the means will depend upon the facilities available or the preference of the dairyman. Cold air is a very poor medium for cooling. Even when the temperature is below zero, milk will be cooled much more slowly

in such air than in water at 50°F. (10°C.), as is illustrated in Table XIII. All milk should be cooled as quickly as possible after the milking and the temperature reduced to below 50°F. (10°C.) if good keeping quality is to be assured.

TABLE XIII.—COMPARISON OF VARIOUS METHODS FOR COOLING MILK

Cooling medium	Stirring	Temperature of cooling medium, degrees Fahrenheit	Temperature of milk			Loss of temperature	
			Original, degrees Fahrenheit	After 1 hour, degrees Fahrenheit	After 2 hours, degrees Fahrenheit	1 hour, degrees Fahrenheit	2 hours, degrees Fahrenheit
Air.....	No	+8 to -4	90	80.0	69.0	10.0	21.0
Air.....	No	36 to 38	89	82.0	75.0	7.0	14.0
Air.....	Yes	36 to 38	90	82.2	76.0	7.8	14.0
Water....	No	45 to 49	90	58.0	50.0	32.0	40.0
Water....	Yes	45 to 49	88	52.0	46.0	36.0	42.0
Ice water	No	40 to 45	88	56.0	46.0	32.0	42.0

Prompt Delivery.—Milk which is intended for market-milk purposes should not be allowed to accumulate, even if kept cool. It should be delivered to the consumers or distributing plants daily. Fluid milk should be fresh as well as clean, cool, and safe when delivered to the ultimate consumer.

Certified Milk.—There are many refinements which can be made in the methods and the equipment employed in the production of milk for the market trade. For example, there has grown up a grade of milk known as “certified” which is produced under exceptionally careful conditions, with special equipment, additional precautions, and control of every conceivable factor influencing the quality of milk.

About 40 years ago, some physicians in New Jersey became interested in the production of a superior quality of milk. They made a study of sanitary methods of milk production and selected a dairyman who agreed to comply with the regulations set down by this group of doctors. This medical group established what is now known as a “Medical Milk Commission” to supervise the production of the milk on this farm. The first “certified milk” was produced under its jurisdiction in 1894 in Essex County, New Jersey. The term “certified milk” has been

registered in the U. S. Patent Office and is protected from misuse under that arrangement. Since that time medical milk commissions have been set up all over the country. They have adopted uniform standards for the production and distribution of certified milk. The regulations are very much in detail and very strict. The supervision of the certified dairies, in recent years, sometimes has been delegated to state departments of health. The certification of equipment and methods has continued to be strict, and certified milk stands out as milk which is produced under the most exacting conditions. It represents the highest quality of raw milk that is obtainable. The originators of the idea are

Fig. 49.—A stainless-steel-tank truck used in transporting milk. (Courtesy of Allegheny Steel Company.)

to be commended for their careful study and diligent efforts. They established a precedent and a standard for sanitary milk production which have influenced, for the better, all market milk. The conditions under which certified milk is produced are nearly ideal and serve as a goal toward which all conscientious dairymen should be guided.

Provisions are now made for pasteurized certified milk. This adds one more factor of safety to an otherwise ideally safeguarded milk supply.

The dairy industry cannot be too careful in the production of milk which is to be used by such a large number of people who are so far away from the source of supply.

Transportation of Milk.—The channels of transportation through which milk passes from the time it is produced on the farm until it reaches the door of the consumer are dependent upon the local situation. Where the producer delivers directly to the consumer, the transportation merely involves a delivery by

wagon or truck from the farm to the town. When the producer sells to a distributor some distance away there may be involved hauling by truck or shipment by rail (electric or steam).

The farmer may, himself, haul the milk to the milk-receiving station or to the city distributor's plant, if close at hand. Often arrangements are made for trucks operated by the purchasing agency to pick up the milk at the individual farms and transport it to the shipping station or distributing plant. In this case, a charge for hauling is usually made and based upon the distance. The greater part of the milk going to the great urban centers is collected first at country receiving stations located at frequent

FIG. 50.—A modern streamline milk tank car used for the transportation of milk over long distances to the larger cities. There are two, 12,000-quart, cork-insulated glass-lined tanks set in either end of the car. The outside shell is steel with a protective coating of aluminum metal fused to the steel surface. (Courtesy of Borden's Farm Products Company.)

points along the railroad. In these country receiving stations the milk may be pasteurized, or merely thoroughly cooled before shipment. Until recent years, shipment was made in ordinary 8- or 10-gallon cans. Usually, blocks of ice were placed on top of the cans to help maintain a low temperature. Recent improvements involve the use of glass-lined, aluminum, or stainless steel tanks mounted on gondola cars or enclosed by the superstructure of an ordinary freight car. These tanks are usually insulated in such a way that it is possible to ship milk long distances with practically no rise in temperature. By the use of this modern system, milk is shipped successfully from Wisconsin to Florida. Special milk trains are operated by many railroads where the city demand is such that large volumes of milk must be trans-

ported long distances. For example, milk trains are operated daily a distance of nearly 500 miles bringing milk to New York City.

Large motor trucks or trailers carrying glass-enameled, aluminum, or stainless steel tanks are widely used at present for transporting milk from rural districts to the large urban centers often hundreds of miles distant. With the milk properly cooled before shipment, with adequate insulation of the tank, and with the usual speed of truck transport, the milk reaches the city plants in excellent condition.

Delivery of Milk.—One of the major items in the price which consumers must pay for milk is delivery cost. Distances between customers, cost of delivery outfits, cost of maintenance and operation of them, salaries of salesmen, and collection costs are among the factors which influence the expense of delivery. Most milk is delivered in the bottle directly to the consumer by means of one- or two-horse rigs. In many instances electric or gasoline trucks replace the horse-drawn vehicle. Some milk is sold to stores for delivery to customers. Restaurants, hotels, etc. purchase some milk by the can and so reduce the handling costs. Many milk companies also handle such products as buttermilk or other fermented milk beverages, cottage cheese, butter, etc. This tends to increase the burden of delivery but makes it possible for the dealer to utilize his surplus products to good advantage. With all the details of overhead and operating expense involved in the delivery, it is not surprising that it constitutes a considerable part of the cost of a quart of milk.

Purchase of Milk.—Milk may be purchased by a distributor in a variety of ways, such as:

1. By measure—that is, by quart, gallon, or can.
2. By total weight, estimated or actual.
3. By either (1) or (2), with minimum standards of butter fat and a premium for additional butter fat and premium for high quality or deductions for poor quality of milk.
4. By weight and test, paying upon the basis of butter fat delivered.
5. By weight and test, with a basic price per 100 pounds of skim milk plus a straight price per pound of butter fat.

The majority of milk, at present, is purchased upon the basis of weight with a minimum standard for butter fat, and a premium for additional butter fat above the standard, and in many sec-

tions with deductions made for a poor quality of milk. The method varies in different localities but there is a tendency toward purchase by weight and butter-fat standards in most dairy sections because of the competition with creameries and cheese factories.

In some cases, cooperative organizations collect the milk produced by the members and sell it at wholesale to distributors. Again, cooperative organizations may undertake the distribution of milk. The fact that a cooperative organization is concerned does not affect the methods involved in supplying a city with

FIG. 51.—A modern market-milk plant. This plant handles sufficient milk to require about 150 wagons for retail delivery. (*Courtesy of Franklin Cooperative Creamery Association.*)

milk. It does affect, however, the nature of the business organization concerned.

The Milk Plant.—It is beyond the scope of this text to discuss in detail the construction, equipment, arrangement, and operation of milk plants. They vary so much in different sections and the methods are changing so rapidly that only a meager picture of them can be drawn.

The modern milk plant is housed in a permanent, well-constructed building that is durable and constructed to facilitate the sanitary and prompt handling of milk. It may be of modest proportions or represent large investments. A typical plant of the latter type is represented in the accompanying figure.

Usually, the plants are provided with a room where the milk is received and weighed. Here the cans may be washed and

prepared for return to the farmer. The milk ordinarily will be conducted or pumped into storage tanks from which it will pass through filters or clarifiers before it is pasteurized.

A separate room usually is provided for pasteurization. The heating of the milk may be accomplished in a variety of ways, by means of surface, drum, tubular, or plate heaters with hot water or steam as a heating medium, in special electrical devices

FIG. 52.—Pasteurizing, cooling, and bottling room in a milk plant. The milk is pasteurized in the spray-type vats, each provided with a recording thermometer. The pasteurized milk is pumped over the surface, tubular, cooler shown in right background. The cooled milk flows directly into the filler tank. The automatic rotary bottle filler and capper is shown in the foreground. Note the handy sanitary pipe and fitting rack in left background. (*Courtesy of Cherry-Burrell Corporation and Winona Milk Company.*)

or directly in large vats or pasteurizing tanks. After heating, the milk is held for the required period of time and then cooled promptly, either over surface coolers or through internal-tubular coolers. From the coolers the milk will pass directly or indirectly to bottle fillers. Here the milk will be delivered into bottles which are capped by machinery. From the bottler the milk passes to a refrigerator where it is stored until delivered.

In most plants there will be provided a special room for washing bottles returned from the consumer. A place must be provided

for offices, machinery, storage of supplies, etc. All machinery must be arranged carefully if economies of operation are to be possible. Each milk plant will have a different arrangement of rooms and equipment. There will be differences between plants in the size of the installations and their type. In general, they will have equipment for weighing and receiving milk, washing cans,

FIG. 53.—Bottling room in a milk plant. The clean and sterilized milk bottles are discharged on a conveyor directly from the bottle washer located beyond partition shown in the background. The bottles pass directly to the automatic rotary bottle filler and capper. The filler operates under a vacuum. The filled bottles are inspected by the attendant and placed in cases which in turn are conveyed into the refrigerator. (Courtesy of Mojonnier Brothers, and Sanitary Farm Dairies, Inc.)

pumps and piping for transferring milk from one part of the plant to another, storage tanks, filters or clarifiers, heaters, pasteurizers and coolers, bottle fillers and cappers, bottle-washing equipment, and provisions for refrigeration. They will all require heating plants, storage rooms, and some sort of office. Additional equipment, such as horses, wagons, trucks, and barns or garages, must be provided.

Some plants are very modest in their investments while others represent the expenditure of thousands or even millions of dollars. Interior views of representative plants will give an idea as to the

type and variety of equipment which is necessary for the modern milk plant.

Problems of the Milk Distributor.—The operators of milk plants are confronted with many perplexing problems. They must be able to obtain a high-grade raw product, handle it expeditiously and economically. When pasteurization is practiced, due care must be exercised in the process so that the normal characteristics of milk may not be altered appreciably.

FIG. 54.—Containers in which market milk is delivered to the consumer. The package at the left is a recently introduced paraffined paper cone, called a "seal-cone." This is used but once and then destroyed. The center figure represents a typical quart bottle of milk with the ordinary cap. The bottle of milk on the right has the lip additionally protected by the hood cap. This is the characteristic "certified-milk" package.

This applies particularly to the matter of flavor and of creaming ability. As long as the housewife measures the quality of milk by the depth of the cream layer at the top of the milk bottle, it will be necessary for the plant operator to take all precautions to preserve the cream line as much as possible. The operation of all equipment, together with the selection of the most satisfactory installation, will have a great deal to do with the success which a milk dealer may attain in supplying the consumer with the type of milk most desired.

HEALTH CONTROL OF MILK SUPPLIES

The milk supply often is rated as second only to the water supply, as a factor concerned with the health of a city. As

pointed out, previously, it is impossible for the city milk consumer to have any knowledge concerning the conditions under which his milk supply is produced. It is also evident that under any conditions few would be able to determine for themselves the wholesomeness of the milk. With the growth of the cities and the increased knowledge concerning the importance of the milk supply as a health factor, have come well-organized departments in city governments having as their duty the careful supervision of the milk supply.

FIG. 55.—Laboratory in a modern milk plant. Equipment is provided for making the necessary chemical and bacteriological tests, and for carrying cultures for various milk beverages. A laboratory is the heart of a successful milk plant. (Courtesy of Sanitary Farm Dairies, Inc.)

The first attempts towards supervision of the milk supply date back about 50 years in the United States. The first efforts were directed towards the elimination of such frauds as watering milk or selling as whole milk that from which a portion of the cream had been removed. Such adulterations were common in those times. A little later, the use of chemical preservatives became common as means of improving the keeping qualities of milk. This practice was also under the ban of law, and food-control officials were given the responsibility of eliminating the practice. The practice of skimming and watering milk for sale and the use of preservatives have been eliminated almost entirely as the result of these efforts. The elimination of these practices is now accepted as a matter of course and the attention of public officials is directed more towards the cleanliness, wholesomeness,

and safety of milk. There are many methods in use for exercising control of the milk supply but all have the same objective—that of protecting the public and ensuring for it a safe and satisfactory milk supply.

Federal laws regarding foods apply only to interstate shipments and are, therefore, not depended upon to regulate local milk supplies. State laws, as a rule, set forth requirements which must be met in producing, handling, and distributing milk as well as other food products. As a rule, both federal and state laws consist mainly of definitions and regulations regarding the fat and the total solids content of milk, prohibiting the use of preservatives, and, in general terms, requiring production and distribution under good sanitary conditions. Adequate supervision of the milk supply is usually the result of city ordinances which add details to regulations and laws of state and federal origin and provide for the personnel necessary to carry them into effect.

Control Measures.—The usual plan is to require every milk distributor to have a permit or license to sell his products. To obtain this permit the product sold and the conditions under which it is produced and handled must conform to the requirements of the regulations. In some cities emphasis is placed upon the sanitary conditions of the premises used in producing and handling milk. In others the actual condition of the milk as offered for sale receives the greater attention. As a rule, the control is more or less of a combination of the two.

Supervision in the Small City.—In a small city having a typical ordinance, evidence that all cows contributing to the milk supply had passed the tuberculin test would be required at intervals. The dairy barns and the premises would be inspected at intervals by an inspector working under supervision of the Department of Health. In making this inspection use would be made of a dairy-farm score card. A copy of the score card as filled out is left with the farm owner. This score card covers important items of construction, equipment, and methods in the dairy barn and serves to make possible a permanent record of the conditions existing, also to point out definitely to the farm manager the places where improvement should be made. If the milk supply for the city goes through a milk plant, these premises and the methods practiced also are subject to inspection at regular intervals.

In addition to the sanitary inspection of premises, samples of the milk would be taken at frequent intervals from delivery wagons. The fat and total solids content of these samples will be determined and, in addition, many health departments also make bacterial counts of the milk. The sediment test may also be employed. If conditions are found which do not conform to the regulations, the license of the milk seller may be cancelled. There is little tendency for arbitrary action on the part of control officials, and producers or distributors whose product is below standard are usually given plenty of opportunity to make the necessary improvements.

Supervision in the Larger Cities.—In the large cities, the health control is conducted along similar lines but requires some modification. It is evident that, with 65,000 farms supplying New York City, it would be impossible to exercise a close supervision over the sanitary conditions under which the milk is produced. The quality of the milk must be determined largely from an examination of the product itself as offered for sale, and by a supervision of the conditions under which the milk is handled. Occasional inspection is generally made of the farms, more frequent examinations are made of the sanitary conditions and practices in the country receiving stations, and a rather close supervision exercised over the quality of the milk, as sold in the city, including the practices and methods followed in the city pasteurizing plants. A health examination is sometimes made of the employees of the city plants.

Pasteurization as a Health-control Measure.—There are certain cities in the United States which require that all market milk be pasteurized. The majority of cities however, permit the sale either of raw or of pasteurized milk. In most of the larger cities (that is, those with populations over 100,000) it will be found that 90 per cent or more of the market milk is pasteurized. Because of the difficulty of inspecting and regulating large numbers of widely scattered dairies supplying a large city with milk, it necessarily follows that most of the milk under these conditions must be pasteurized. Pasteurization has the advantage of reducing the transmission of disease-producing bacteria, diminishing infant mortality, and improving the keeping quality of the milk. Large volumes of milk may be brought to central plants for pasteurization and handling where rigid inspection and control are possible. In this way, the public is protected

more adequately. Pasteurization is not intended to cover up faulty methods of production or handling. Rather, it is primarily a health measure to make good milk safer for human consumption and makes possible a wholesome milk supply, especially for large cities.

Most cities sanction the sale of raw milk. Certain of these restrict this to certified milk. Others permit other grades of raw milk to be sold but the tendency is to limit the sale of raw milk to those dairies that are well equipped, rigidly inspected, and to require the tuberculin testing of cows and medical examination of handlers, besides setting up exacting standards for the bacterial content of the milk.

Reasons for Pasteurization.—It must be granted that it is desirable to have the milk supply made up of milk as nearly unaltered in its natural characteristics as it is possible to obtain. This would mean fresh, raw milk as it is drawn from healthy cows, by healthy people and under the very best sanitary conditions, and delivered promptly to the consumer without contamination or alteration due to chemical or microbiological agencies. This situation requires constant attention, careful supervision, and inspection. Conditions so nearly ideal are difficult to attain, and where large cities require such vast quantities of milk that they must go long distances and to many dairies for their milk supply, pasteurization is a practical necessity in order to safeguard the health and well-being of the average consumer. Economic factors also play a part in this situation to such an extent that it is not at all difficult to understand why pasteurization has such an important place in the modern market-milk industry.

Grades of Milk.—Market milk often is designated by grades or classes. These vary widely, depending upon the local requirements or demands of the trade.

In a general way, there are two classes of market milk, raw and pasteurized. The raw milk is that which is delivered in its natural state after it leaves the cow and without any treatment other than cooling. Pasteurized milk is milk that has been subjected to temperatures sufficient to destroy all disease-producing types of bacteria that may be present in the raw milk. (Pasteurization is discussed elsewhere in this text.)

Under raw milk would be found the milk known as "certified milk" as well as ordinary raw milk. This latter may be designated

in grades such as "Grade A Raw" or "Grade B Raw," or "Inspected Milk," etc. The pasteurized milk ordinarily comes in the one grade, but in certain cities is subdivided into such as "Pasteurized Certified," "Grade A Pasteurized," "Grade B Pasteurized," etc.

The grades are based upon the conditions under which the milk has been produced and handled, as well as upon the quality of the milk from the standpoint of purity, bacterial count, cleanliness, etc. Such grades usually are set up by local regulations.

More recently special classes or types of milk have been introduced on the market. For instance, high fat, special Jersey or Guernsey, vitamin D, soft curd, concentrated, and homogenized milks have all found a place in the modern milk market. They present special problems for the industry and the control officials.

In the hands of competent and energetic public officials the milk supply of a community may be safeguarded satisfactorily. Where officials are lax or ignorant, the public is not assured that its milk supply is above suspicion. The problem in controlling the milk supply of large cities is exceedingly great, because the centers of production are widely scattered and adequate inspection is costly and difficult to accomplish.

CHAPTER X

THE MANUFACTURE OF DAIRY PRODUCTS

BUTTER

The use of butter appears to be as old as recorded history. Hindoo writings, dating back at least 2000 B.C., indicate that butter was used extensively, at that time, both as a food and in connection with religious ceremonies. The oldest parts of the Bible contain frequent references to milk, butter, and cheese. There is, however, some question regarding the use of the term, "butter," in the translation from the original. It is probable that the product, to which reference was made, would hardly pass as butter, according to present-day standards. Butter was used by both the Greeks and the Romans, but apparently more extensively as an ointment for medicinal purposes than as a food. The extensive use of butter as a part of the human diet developed in northern Europe where climatic conditions were more favorable for the preparation of this product. By the twelfth century butter was an important export from the Scandinavian countries.

Early History in the United States.—During the colonial period, and in fact until past the middle of the nineteenth century, the making of butter in the United States was exclusively a farm industry. It was in the hands of the women of the household and the methods and utensils were crude. During the winter season scarcely any butter was on the market, while in the summer the supply was so abundant that the price was exceedingly low. The factory manufacture of cheese had begun in 1851 and, following this lead, in 1861, Slaughter built a factory in Orange County, New York, to use the milk of 365 cows. From this he made both cheese and butter, the cheese largely from skimmed milk. The credit for the first exclusive butter factory or creamery, as such establishments are now termed, is usually given to Stewart who, in 1871, built such a factory at Manchester, Iowa. In these first factories the whole milk was received at the creamery and placed in large shallow vats to allow the cream

to rise. It was, in fact, the shallow-pan system of separation on a large scale. Later, the deep-setting plan was followed, the whole milk still being delivered to the creamery. About 1875, the plan known as the "gathered-cream system" came into use. The only change from the first was that the skimming was done on the farm and the cream taken to the creamery, or commonly gathered by special haulers who operated regular routes.

The Effect of the Cream Separator.—Beginning in 1879, the centrifugal separator was introduced and this resulted in a rapid

FIG. 56.—A modern cooperative creamery representative of the type found in Minnesota. Such a creamery is equipped to manufacture 400,000 to 600,000 pounds of butter yearly. Many creameries in America are much larger and equipped to manufacture several million pounds of butter yearly.

change in the plan of creamery operation. The early cream separators were all power sizes and, as a result, the creameries soon were equipped to separate milk by these more efficient methods. The practice of gathering hand-skimmed cream from farms was within a few years replaced by that of bringing the whole milk to the creamery, the farmer usually receiving his share of the skimmed milk to be taken home for feeding purposes. Not only was the loss of butter fat greatly reduced, but a decided improvement in the quality of butter was possible.

In 1890, hand-power farm-size cream separators came on the market. Another change in the plan of creamery operation resulted. By means of the farm separator, the cream producer

could secure the same efficiency of separation as at the factory and, at the same time, secure the skim milk in much better condition for feeding purposes. The hauling expense likewise was reduced because of the smaller quantities to be handled and the less frequent deliveries. Although a few creameries continued the plan of receiving whole milk and operating a power separator, it may be said, fairly, that the butter-making industry in the United States, after about 1910, was based upon farm-separated

FIG. 57.—Inside view of a creamery. The installation of creamery equipment is shown. Note the series of pasteurizers in the background. Cream, after pasteurization, holding, and cooling, is pumped into the churns in the foreground. Each churn is motor-driven while the pasteurizers are belt-driven. (*Courtesy of Cherry-Burrell Corporation.*)

cream. The creamery operator, however, found more difficulties in maintaining the standard of his product. On the whole, the farm-separator system undoubtedly resulted in a lower standard of butter quality, especially in the earlier years of its use. More recently, the quality of butter made under this system has been improved decidedly in certain regions.

There are indications, however, that the future will see the creameries of America turning again to whole milk. In these plants, many of which have been in operation a number of years, it is possible for the management to receive whole milk, separate the surplus, sell sweet cream, churn all surplus cream, and manufacture from the skim milk and buttermilk concentrated products

such as condensed or dry skim milk, cheese, or casein, all of which are readily marketed. It will be noted, therefore, that the creamery industry has passed through three distinct stages, apparently is now in the fourth, and entering upon the fifth stage of its development. These stages are: (1) the whole-milk creamery using gravity-creaming methods; (2) the creamery gathering cream, separated by gravity on the farm; (3) a return to the whole-milk creamery on the introduction of the factory separator; (4) a return to the cream-gathering plan with the introduction of the farm separator; and (5) a gradual turn back to the whole-milk creamery equipped to manufacture all types of dairy products and especially to make use of the by-products.

FIG. 58.—An upright dasher churn. Churns of this type have been used on farms since colonial days but have largely disappeared in recent years. This churn was used on a Minnesota farm about 1850. (*Courtesy of Minnesota Historical Society.*)

Status of Farm Butter.—As indicated previously, the manufacture of butter was exclusively an industry of the farm until past the middle of the nineteenth century. The introduction of the factory system of manufacturing butter, beginning in 1871, brought about a gradual evolution from farm-made to factory-made butter. That this shift in the industry was slow is indicated by the fact that, in 1900, about 66 per cent of the butter made in America was still a farm product. There was a steady development of the factory system, however, and, by 1920, the butter made on the farm was reduced to about 43 per cent of the total butter made in America; by 1926, this figure had been reduced to below 30 per cent. The butter industry, therefore, followed the line of progress of many

other industries which were introduced on the farm because of necessity.

The manufacture of cloth was at one time a task performed in the home. The art of weaving cloth at home is practically lost to the present generation of America. The same statement could be made concerning many other articles, such as tools, wagons,

implements, shoes, etc., which once were made of necessity on the farm. Milk products were not the only food products formerly prepared and marketed from the farm and which now are prepared primarily under the factory system. The packing industry has greatly reduced the extent of butchering on the farm, and, likewise, breadmaking for home consumption has been greatly reduced during the past 25 to 50 years owing to the development of the modern bakery.

Composition of Butter.—Butter consists primarily of butter fat. In addition to the fat, it contains water, salt (if salted butter), and a small amount of the milk solids-not-fat grouped under the term "curd." In 1912, the U. S. Department of Agriculture reported the composition of 695 samples of creamery butter gathered from 14 states as follows: 82.41 per cent fat, 13.90 per cent water, 2.51 per cent salt, and 1.18 per cent curd. An analysis of 1,000 samples of Minnesota butter, reported by the Minnesota Experiment Station in 1925, shows an average composition of 81.31 per cent fat, 15.35 per cent water, 2.31 per cent salt, and 1.03 per cent curd. According to federal food regulations, butter containing less than 80 per cent fat is considered illegal and is subject to a fine.

Processes Involved in the Manufacture of Butter.—Since butter is made primarily under the factory system, it is intended briefly to discuss the processes involved in the manufacture of this product in the typical modern creamery or butter factory. The processes involved in the manufacture of butter in such an establishment may include the following: (1) separation of milk, (2) selection of cream, (3) neutralization of cream, (4) pasteurization of cream, (5) cream ripening, (6) churning, (7) packing and printing, and (8) marketing.

Separation of Milk for Butter Making.—The ancient practice of churning milk for the production of butter still is followed in limited sections of the United States and abroad. Cream rather than milk is commonly churned for reasons of economy and efficiency. The typical farmer in the surplus butter-producing area of the United States has a relatively small herd. He does not feel that the amount of milk produced justifies daily delivery to the creamery, and the present plan of separating the milk on the farm will under these conditions probably continue until greater specialization results in a larger dairy herd. In those localities where the production of milk is on a larger scale, the milk now in

some cases is delivered at the creamery where a power separator is used and the skim milk sold back to the farmer for feeding or made into such products as condensed or dry skim milk and buttermilk, cottage cheese, or casein. There are indications that this type of operation gradually will be introduced into those localities having a liberal milk supply. The advantages are, the opportunity afforded to use the milk for whatever product may be marketed to the best advantage, the better quality of butter possible, and, especially, the complete utilization of the by-products. With a small dairy herd on the typical general farm, the skim milk can be utilized to good advantage for feeding calves, pigs, and poultry, but with a larger amount available it becomes impractical to keep sufficient animals to use the by-products. It then becomes a matter of economy to use the by-products for other purposes.

Types of Cream Used for Butter Making.—Cream for butter making may be either sweet or sour. By far the largest percentage of butter in the United States is made from sour cream. A comparatively small amount is made from sweet cream. In either case a clean-flavored product is most desirable although not uniformly obtained.

The flavor of cream used for butter making is an important factor influencing the quality of the resulting butter. Many undesirable flavors may develop in cream. A cream may be sweet, yet possess an off-flavor which would yield, on churning, a butter of inferior quality. On the other hand, a cream may be acid, but possess a clean fresh flavor and on churning, produce a butter of high quality. These facts make it necessary to study the cause of off-flavors in cream so that it may be possible to make recommendations as to their prevention. Furthermore, it is desirable that cream intended for butter making should be divided systematically into grades.

Off-flavors in Cream.—The general causes for the common off-flavors and odors that occur in cream may be classified as follows:

1. Off-flavors absorbed.
2. Off-flavors due to bacterial fermentation or chemical action.
3. Off-flavors due to feed.

Absorbed Off-flavors.—It is common knowledge that milk or cream will absorb volatile odors very readily. The average housewife is aware of this fact from practical experience. The

producer of milk and cream also understands this possibility, yet many such flavors reach milk and cream by absorption from the air. One of the most common flavors found in milk or cream due to absorption is the characteristic "cowy" or "barny" flavor which is taken up by the milk from the air of the barn. Cream readily acquires odors from such sources as new lumber, smoked meats, decayed vegetables, cooking foods, and many others. These facts suggest the importance of keeping cream away from foreign odors of all sorts and, further, the need of keeping cream in a tightly covered container.

Off-flavors Due to Bacterial Fermentation or Chemical Action.—The greatest percentage of the off-flavors occurring in cream are due to the growth of bacteria. The number and types of the bacteria, yeasts, molds, etc. present will be dependent largely upon the organisms that were in the milk from which the cream was obtained. Some additional organisms may be picked up from dirty separators, cream cans, and other utensils, but the bulk of them will be those originally present in the milk. The predominance of any particular type after a given period of time will depend very largely upon the temperature at which the cream has been stored. Thus, if cream is kept at temperatures near 70°F. (21.1°C.), the souring types will prevail, while at higher temperatures, putrefactive types may gain the ascendancy.

Dairymen who are selling cream for manufacture into butter should be very attentive to measures of sanitation and refrigeration of their raw product. The eventual return for the cream will depend in a large measure upon the quality of the manufactured product and no manufactured article of high quality can be made from inferior raw products. The dairyman should exercise care in preventing contamination of the milk from the various sources of microorganisms previously mentioned. This is especially true of utensils, such as pails, milking machines, strainers, separators, cans, etc. Further than this, he must cool the cream, promptly and sufficiently, immediately after separating so that the growth of microorganisms may be checked as much as possible.

It is true, also, that, in many instances, contamination takes place in the creamery, and may be responsible for certain off-flavors developing in the finished butter. The most common flavor of cream due to bacterial growth is the sour or high acid flavor. As previously stated, however, acidity does not cause a serious off-flavor if the cream possesses a clean flavor otherwise.

When sweet cream is desired for use as table cream or for sweet-cream butter manufacture, sour cream is considered undesirable. Along with the souring may come undesirable fermentations which produce distinctly objectionable flavors and odors such as putrid, bitter, cheesy, yeasty, musty, barny, and unclean. These flavors are chiefly the result of the action of the enzymes produced by various microorganisms. Many of them are to be attributed to a breaking down of protein in which case decidedly objectionable odors and flavors are to be expected.

No creamery operator can restore the quality of cream which has gone beyond the point of souring, and no dairyman can afford to continue practices which result in highly fermented or putrefied products. The microorganisms must be kept out of the cream as much as possible. Thereafter the raw product must be kept sufficiently cool to inhibit the development of those organisms which may be there inadvertently, and it must be delivered frequently to the factory, if the best returns are to be realized. Besides the flavors produced, because of the growth of bacteria and the subsequent action of their enzymes, there are certain defects of cream which are due entirely to chemical action. Among these may be cited the metallic flavor which may be caused by the action of lactic acid upon exposed metal, such as the iron in rusty cans.

Off-flavors Due to Feed.—As a general rule, a healthy cow will produce milk free from off-flavors or odors. There are certain feeds, however, which, if consumed by the cow, will influence the flavor of her milk. Feeds, such as onions, garlic, ragweed, French weed, or fan weed, which give off volatile substances which find their way into the blood stream, will cause off-flavors in the milk. An excess of certain feeds, such as rye pasture, and some varieties of roots, may cause an off-flavor in the milk of an animal. In general, however, it can be said that feeds are responsible for very few of the off-flavors which occur in cream and that more sanitary methods on the farm will result in a decided improvement in the quality of the average cream.

Cream Grades.—The general classification of causes for off-flavors in cream should be taken into consideration in attempting to formulate a system of cream grading. The question for the creamery operator to decide is: How serious are those flavors which are absorbed from the air, those due to bacterial and chemical action, and those due to feed? In general, it may be

stated that off-flavors which are absorbed from the air are volatile and will pass off during heating and aërating. Furthermore, they do not increase in intensity. The most difficult flavors with which to deal are those due to bacterial development, chemical action, and feeds. The development of flavors due to bacterial action may be checked by pasteurization, but the objectionable products already formed are not removed. For this reason, flavors due to bacterial growth may be exceedingly difficult to overcome. This is particularly true of those off-flavors which are due to the decomposition of proteins of milk. Flavors due to feeds are likewise difficult to eliminate, especially when pronounced.

Cream Grading.—Unfortunately, in the grading of cream there is no method by which the flavors of cream can be measured. The acidity can be determined easily by titrating with alkali solutions, using phenolphthalein as an indicator, but, in determining the presence and severity of flavors, many of which are far more objectionable than acidity, it is necessary to rely on the senses of smell and taste of an individual.

Cream grading is compulsory in a few states in America. The state of Minnesota was the first of the major butter-producing states to adopt a compulsory cream-grading law. In certain countries in Europe it is unlawful to sell anything but sweet cream. Australia has a law that prohibits the mixing of various grades. For a number of years a very effective compulsory cream-grading law has been in effect in Manitoba, Canada. In most of the states in America the grading of cream is left to the individual buyer of cream. In these sections it is not uncommon for creameries to receive two grades of cream, a first and a second. Usually, about the only qualification for the first grade cream is that it have a fairly clean flavor. Cream possessing an off-flavor is graded "second." Whether the cream is sweet or sour makes no difference in price, the result being that it is generally sour.

The acidity test often is used in the grading of cream. In some localities, a common practice is to place all cream in second grade when the acidity is higher than a definite percentage, the standard varying according to the ideas of those in charge of the business. In some localities, an acidity above 0.5 per cent places cream into a second grade. In other sections, the limit of acidity is still lower.

The law in Minnesota requires that all cream purchased for butter making be graded and paid for according to grades. The following grades are defined in the law:

Sweet Cream Grade—shall consist of fresh, clean, fine flavored cream, the acidity of which calculated as lactic acid shall at no time have exceeded 0.20 per cent in cream.

Grade One shall consist of cream that is clean, free from undesirable odors and flavors, the acidity of which calculated as lactic acid shall at no time have exceeded 0.60 per cent at the time and place of purchase.

Grade Two shall consist of cream that is too acid to grade as *Grade One* and/or contains undesirable odors and flavors in a moderate degree.

Unlawful Cream shall consist of cream that contains dirt, filth, or other foreign matter that makes it unfit for human consumption.

In addition to the above grades, the Minnesota law requires that a minimum of one sediment test per month must be made of the cream of each producer patron of a creamery or of any cream buyer.

The grading of cream is carried on in the so-called "receiving room" of the modern plant. Cream is weighed either in the cans in which it is delivered to the creamery or by dumping into a tank placed on a scale. Separate receiving vats or pasteurizers are provided for each grade of cream. It is for this reason that smaller creameries find it difficult to provide the necessary equipment required in grading cream.

Neutralization.—The term "neutralization" is applied to the practice of adjusting the acidity of sour cream. The process consists of adding to cream a sufficient amount of a solution of an alkali, such as calcium oxide, calcium hydroxide, calcium carbonate, sodium bicarbonate, or magnesium oxide, to neutralize partially the lactic acid present. The object of neutralization is to permit the pasteurization of cream without danger of a loss of fat due to the coagulation of casein which takes place on heating cream of relatively high acidity. It further prevents the occurrence of curd particles in butter made from sour cream and doubtless improves the keeping qualities of butter made from such cream. It is obvious that neutralization has no place in the manufacture of butter made from sweet cream and should be

considered as an expedient only in the manufacture of butter made from sour cream.

Pasteurization of Cream for Butter Making.—Butter made from cream which has been pasteurized possesses much better keeping qualities than butter made from unpasteurized or raw cream. The significance of the keeping quality is evident in view of the fact that butter seldom reaches the ultimate consumer in the large cities before it is 2 weeks old and that much of it is from 2 to 6 weeks old before being consumed.

Three systems of pasteurization of cream for butter making are in general use; namely, the "vat system," the "flash system," and combination flash-and-vat system. The vat system consists of placing the cream in a vat, commonly termed "pasteurizer" and "cream ripener," in which the cream is heated to a temperature of 145°F. (62.8°C.) and held 30 minutes, after which it is immediately cooled. The period of holding may be shortened by increasing the temperature. For example, a temperature of 160°F. (71.1°C.) may be used for 15 minutes and 170°F. (76.7°C.) for 5 minutes. Temperatures lower than 145°F. (62.8°C.) are not sufficient to destroy the majority of bacteria.

In the vat pasteurizer the cream is heated by a revolving coil through which hot water flows. This revolving coil also serves to keep the vat contents agitated during the heating process in order to prevent the cooking of the cream on the heating coils. The cream is cooled by passing cold water followed by ice water or cold brine through the coil. Sometimes the plan is followed of passing the cream over a surface cooler which consists of metal pipes through which water and brine may pass.

The flash system of pasteurization consists of bringing the cream rapidly, in fact almost instantly, to a temperature of from 180 to 185°F. (82.2–85.0°C.) and cooling immediately. The apparatus used for this type of pasteurization makes possible a continuous operation and a large capacity. The simplest design is a hollow drum with a double wall. A rapidly revolving agitator by centrifugal force keeps the cream in a thin layer against the outer wall of the drum as it passes through the machine. The heating medium is high-pressure steam between the two walls of the drum.

The combined system of pasteurization consists of heating the cream to the desired temperature by means of a flash-type

pasteurizer, after which it is passed into a vat where it is held for the desired period. It may then be cooled either in the vat or passed over a surface cooler.

The system of pasteurization which is used in a given creamery depends largely upon the volume of cream handled. Where a large volume is handled, the flash system has proved to be the more practical and more economical. When the flash system is used, however, the high temperature to which the cream is subjected results in a cooked taste of the butter. Although this cooked flavor will be hardly noticeable after the butter becomes a few days old, there are operators who prefer to use the combined flash-and-vat system of pasteurization. In those creameries handling a small volume of cream it is necessary that the plant operations be delayed until sufficient cream is delivered and, in such creameries, the vat system of pasteurization has proved the more practical.

Starters.—The creamery industry understands that the term “starter” means a culture of desirable microorganisms in some nutrient material which is usually milk. Starters have found an important place in certain branches of the dairy industry, especially for butter making, cheese making, and the preparation of fermented-milk beverages. The starters which are used in these various fields are somewhat different in character, according to the type of product to which they are to be added. Each of these will be discussed under the separate dairy products.

The culture employed in butter making usually is purchased by the creamery from some laboratory equipped to obtain and to propagate the proper types of bacteria necessary for desirable results. The bacteria in a butter culture are of two types, one of which has the function of fermenting the lactose of milk to produce lactic acid which, in turn, curdles and coagulates the milk, the other, working in association with it to attack principally the citric acid of milk to produce volatile acids and products such as diacetyl which yield the desirable flavor and aroma of a good starter. Both of these types must be present, if the best results are to be obtained. This combination of pure cultures is usually sent to the creameries in the form of milk cultures. The creameryman then inoculates a quantity (usually a quart) of milk (pasteurized at 180°F. (82.2°C.) or higher, for at least 30 minutes), with this culture, and sets it away at a temperature around 68 to 72°F. (20 to 22.2°C.) for several hours (ranging from

8 to 16 hours) until the bacteria have performed their duty so that the milk is coagulated and the desirable flavor and aroma produced. This starter is then said to have "ripened." It is cooled and set away until ready to use. This quart of starter is usually called a "mother starter" and, customarily, is carried in a glass flask or bottle through which the fermentation may be watched. This procedure of inoculating and ripening the "mother culture" is carried on day by day so long as the culture produces favorable results. When the operator desires a quantity of starter to add to cream to which he wishes to impart a delicate, desirable flavor and aroma, he adds a sufficient quantity of this "mother culture" to a batch of milk (which has been pasteurized above 180°F. (82.2°C.) for 30 minutes and cooled to 70°F. (21.1°C.)), and allows it to ripen at 68 to 72°F. (20 to 22.2°C.) for 8 to 16 hours until it is coagulated, after which it is cooled and added to the cream.

It is not possible to describe in words the flavor and aroma which a good starter should possess. This can be determined only by experience and keen observation. The main requirements are proper cultures of the bacteria, thorough pasteurization of milk, control of ripening temperatures and periods, and extreme cleanliness. Starter making is applied bacteriology in its finest sense.

Cream Ripening.—The term, "cream ripening," refers to the fermentation of cream intended for butter manufacture. The process often is called souring but is more than this term would indicate. Following pasteurization the cream is cooled to 68 to 72°F. (20 to 22.2°C.). At this point, there is added to the cream a quantity of starter such as that previously described. The amount of starter used depends upon several factors but usually ranges between 5 and 10 per cent of the total weight of cream.

By this procedure there is planted in the cream a large number of desirable bacteria. By holding the cream at about 70°F. (21.1°C.) for several hours, a fermentation takes place in which there is a development of acidity. A characteristic flavor and aroma will be imparted to the cream to be carried into the resulting butter. A number of years ago it was not uncommon to allow a development of from 0.5 to 0.7 per cent of acid in cream intended for butter making. The tendency, at present, is to limit the acidity to between 0.3 and 0.4 per cent, as it has been found that too high an acidity is detrimental to the keeping

qualities of butter. When the desired acidity is reached, further development is checked by cooling. It must be borne in mind that the principal purpose of a starter in cream is to impart a desirable flavor and aroma, rather than develop a high acidity, and ripening may not be necessary where the starter itself has enough of the desirable flavor and aroma to be taken up by the cream immediately.

When butter was made under farm conditions, all cream was fermented more or less spontaneously before churning, and the public became accustomed to the taste of such butter. When creameries were established, better means for controlling the fermentation were devised, as indicated above. No starter is used in the manufacture of much of the butter made from sweet cream. Such butter is gradually being recognized on the market as "sweet cream" butter. Some of the finest butter made is that churned from sweet cream to which a small amount 1 to 3 per cent, of good starter is added to the cream following pasteurization and cooling.

Butter Color.—The natural color of butter varies under different conditions from a yellowish white to a deep yellow. The yellow color, carotene, is entirely a plant product. Carotene is found abundantly in all green-plant tissue, but largely disappears as the plant becomes mature, and, to a less degree, when forage is dried in the process of haymaking. It is not present in appreciable amounts in grains. These facts are given to explain the close relationship which the feed of the cow bears to butter color. Some breeds of cows, for unknown physiological reasons, transfer more of the carotene from the feed into the fat. Under typical conditions of feeding, if no artificial butter color is used, the butter will be almost white in midwinter, very yellow during the weeks of fresh, luxuriant pastures, and, between these extremes, there will occur a gradual change from one to the other. This extreme change in color under natural conditions is decidedly objectionable to the consumer, who after being familiar with the yellow butter of the summer will refuse to use the light colored butter of winter. As a result of this range in natural butter color, the practice started years ago of using artificial color to make possible a nearly uniform shade of color throughout the year. This practice continues, and butter made while the cows are on dry feed is practically all colored artificially. This is not looked upon as objectionable as the purpose is to regulate the

color to a uniform point and is not in any way misleading. The coloring materials used must conform to the pure food laws, insuring that no harmful substance is used. The shade of color in butter to which people are accustomed determines the market requirements in that region. The eastern cities of the United States prefer butter with a light straw shade; in the southern states, a deeper yellow color is common; while on the western coast, an intermediate shade is most popular.

Carotene is used to a limited extent as a butter color abroad but is not used to any degree in the United States. Because of the fact that it has been shown that carotene is the mother substance from which vitamin A is formed, it is likely to become more popular as a coloring material for butter in the future.

The butter color most commonly used is either vegetable or one of the series of coal-tar dyes. The vegetable color used is a pigment from the seeds of the Annato (*Bixa orellana*) which does not supply carotene but a related pigment. Certain coal-tar dyes approved by the pure-food officials may be used. Both vegetable and coal-tar colors are prepared in a neutral oil which unites with the butter fat and for this reason the buttermilk does not show the presence of color.

CHURNING

Nature of Churning.—When milk or cream is held at a favorable temperature and subjected to continuous agitation, the fat globules coalesce progressively, forming small granules of butter. A small quantity of other milk solids and of water is caught and held with the fat during the process, but the bulk of these constituents is separated from the fat and constitutes the product known as “buttermilk.”

History does not record when man first discovered that fat could be churned from milk. All details of how the process takes place are none too well understood at the present day. Two theories have been advanced, one by Fischer and Hooker, and the other by Rahn. Fischer and Hooker maintain that, during the churning process, there is a reversal of the fat-in-water emulsion which exists in cream to that of a water-in-fat emulsion. Rahn holds to the view that the formation of butter is simply a packing of the globules into a compact mass and that water and air are enmeshed during agitation.

Normally, when cream is churned, it is observed that more or less foaming and whipping take place due to the incorporation of air, the cream increases in viscosity, and small grains of fat become visible to the eye. As churning proceeds, the cream undergoes a decided change in physical makeup: the cream appears granular; small granules of butter become more clearly defined; the cream adheres to the walls of the churn, and drops more like a semisolid mass; suddenly the "breaking" point is reached; butter "comes"; the granules of butter are distinct; there is a definite separation of the fat and serum of the cream. With continued agitation the granules become larger, and make the distinction between the buttermilk and the butter granules even more definite.

Exceedingly thin cream, or exceedingly high testing cream, cannot be said to behave just in the manner above described. Apparently, in the case of thin cream there are retarding factors involved; such cream fails to whip, the increase in viscosity is not so apparent, the "breaking" may be a gradual process, and the butter granules formed may be round and shot-like and fail to fuse after continued agitation. Thick cream of a high percentage of fat churns with very little foaming or whipping, and the period at which the cream breaks from the churn in a mass may be prolonged.

The Churn.—What constituted the first churn no one knows. It is known, however, that, the process of churning milk was known to primitive people. Records are available which show that milk was churned in bags made from animal skins. The Arabs tied such bags of milk to their saddles and dragged them over the ground or tied the bags to trees and swung them back and forth until butter was made. Later, earthenware containers served as churns. From these primitive churns developed the dash churn, the swing churn, the box churn, and the barrel churn, in common use until recent years. After churning in one of these last mentioned types of churns, the butter was placed on a working table where it received the amount of working necessary to incorporate the salt and bring the butter to the proper texture. The introduction of the factory system of butter making stimulated the development of machinery for handling milk and making butter. The period of most rapid change was between 1890 and 1900, due to the introduction of the Babcock test and the cream separator. The same period saw the first use of the

combined churn and butter worker which, since that time, has been in almost universal use in factories. With this equipment,

FIG. 59.—Sectional view of a single-roll, combined churn and butter worker.
(Courtesy of Cherry-Burrell Corporation.)

FIG. 60.—Sectional view of a double-roll, combined churn and butter worker.
(Courtesy of Creamery Package Manufacturing Company.)

the cream is placed in the churn, where the churning process is first completed, then the salting and working of the butter are carried out before the product is removed.

Construction of the Combined Churn and Worker.—In general, the combined churn and worker consists of the following main parts: the drum (or as often termed, the “barrel”), the workers, often termed the “rollers,” the driving gears, and the stands on which the barrel is suspended. The workers are constructed of large rectangular wooden beams, the corners of which are rounded and the four sides concaved. These are set in the churn lengthwise at the center, or at a point between the center, and the inner wall of the drum. There may be one, two, or four rollers in the combined churn and butter worker, depending upon the make of churn. Along the inner wall of the drum and lengthwise of the churn, at carefully determined points, are set two or more shelves. These serve to lift and guide the butter during the working process to a point at which it will be pulled between the revolving worker and a fixed shelf in the single-roll churn or between the workers in the case of a two- or four-roll churn. If the principle applied in the common clothes wringer, where two revolving closely fitted rollers are revolving towards one another, can be imagined, a clearer conception of the principle involved in the case of the workers of the combined churn and butter worker, in use in the modern creamery, will be gained. These churns are constructed to churn and work from 50 to 1,000 pounds of butter. The smaller type is adaptable for large farm dairies.

More recently combined churns and butter workers have been constructed in which no rolls exist. Inserted at both ends of the churn and in the form of wedges running from the head along the barrel, with the wide end against the head, are curved shelves. With each revolution of the churn the butter is lifted on the shelves and dropped toward the center of the churn. The process is repeated until working is completed. A box-shaped metal churn recently introduced employs the same principles.

Churning Procedures.—In order that butter shall not adhere to the wood with which it comes in contact, the pores of the wood must be filled with water. When a churn is used daily, or every other day, no difficulty is experienced regarding this point. All that is necessary is to rinse and cool the churn thoroughly by filling it partially with cold water and revolving for a few minutes, after which the water is withdrawn. If the churn is new, or is used at infrequent intervals, it should be soaked thoroughly by filling it with hot water at least 24 hours before the time for using, and rinsing it with cold water just prior to adding the cream.

The churn is filled from one-third to one-half full of cream. The cream, usually, is allowed to run through a strainer or filter as it enters the churn to assist in breaking any lumps of cream and to remove any particles of curd that might appear otherwise as white spots in the butter. The churn then is operated for a few revolutions and then is stopped to relieve the air pressure, by removing the small stopper provided for the purpose. This pressure may be due, in part, to the escape of gases in the cream but is due mainly to the expansion of the air in the churn caused by the absorption of moisture. The churn then is operated until the butter granules become the size of a pea or a kernel of

FIG. 61.—Butter granules after churning. The appearance of the butter granules after the churning process, ready for washing, salting, and working.

corn. The buttermilk then is allowed to drain thoroughly from the churn. When this is complete, a small quantity of water at the same temperature as the buttermilk may be poured over the butter granules until it is observed to be almost clear as it flows from the gate of the churn. The gate then is closed and the churn filled with wash water to a point approximately the same as that originally reached by the cream. The water should be approximately at the same temperature as the buttermilk, unless the butter is softer than desirable. In this case, the water may be cooled to a temperature below that of the buttermilk in order to harden the butter somewhat during the working. After a few revolutions of the churn the water is drained off and the butter then is ready for salting.

Summary of procedure in churning and working butter under factory conditions:

1. Prepare churn. Wash with hot water and follow with cold water.
2. Place cream in churn.
3. Add butter color, if required, according to shade desired.
4. Start churning and continue until butter granules reach size of peas or popcorn.
5. Drain buttermilk from churn.
6. Rinse buttermilk from walls and ends of churn and from butter by sprinkling with water approximately of the same temperature as buttermilk.
7. Wash butter by adding to churn approximately the same amount of water as there was cream in the churn at the beginning. Water should be near the temperature of the buttermilk, slightly colder if it is desired to firm the butter, or slightly warmer if butter granules appear too firm.
8. Drain wash water from the churn.
9. Sprinkle butter granules with salt if required.
10. Work butter sufficiently to bring the butter into a compact mass.
11. Stop the working process, take a representative sample of the butter from the churn, and make the moisture analysis.
12. Continue working process, permit water from butter to escape from churn if moisture analysis indicates high moisture. If moisture analysis indicates low moisture (below 15.8 per cent), sufficient water should be added to bring moisture in butter to desired amount. Work butter until it has a firm, waxy body.
13. Remove butter from churn.
14. Wash churn.

Factors Influencing Churning.—It is desirable that the churning operation consume the least amount of time compatible with a minimum fat loss in the buttermilk. Further, it is desirable that butter have a firm, waxy body and not appear as a slushy, salvy mass. As a general rule, any condition which tends to make churning easier or which results in the formation of butter granules in a comparatively short period results in a relatively high fat loss in the buttermilk and a slushy, salvy butter at the churn. Likewise, it may be stated generally that any condition which results in the prolongation of the churning period results in comparatively lower fat losses in the buttermilk and a butter of a more firm and waxy appearance. It appears, therefore, that the ease with which cream churns, the time required to

churn, and the condition of the butter are closely associated. The factors involved are discussed in later paragraphs.

Temperature of Cream.—Temperature is the most important factor concerned with churning. In milk, butter fat occurs in the form of globules which are in a liquid condition, as the milk comes from the cow at a temperature of close to 100°F. (37.8°C.). When the temperature is reduced during the interval before churning, the fat globules become firmer. For churning to take place, the temperature of the cream must be such as to allow the fat globules to coalesce. The colder the cream, the longer the period required to complete the churning process. If too cold, the fat globules are hard and may not adhere, making churning almost if not quite, impossible. If too warm, the churning may take place quickly, but the butter obtained will be soft in texture and will contain too much of the milk serum. When all other factors remain constant, sweet cream should be churned at a temperature which will require from 50 to 60 minutes for completion. For sour cream, a period of 30 to 40 minutes gives equally good results, for reasons explained elsewhere. The competent butter maker regulates the churning temperature mainly according to the time required. If the time required for churning considerably exceeds the limits for several days in succession, the competent operator analyzes the situation the best he can and, if there appears to be some explanation, for example, a change in feed due to the approach of winter, he modifies his churning temperature accordingly. As summer approaches and the cows go on pasture, the reverse condition occurs with the difference that the change is more sudden. Typical churning temperatures under factory conditions are 48°F. (8.9°C.) in summer, increasing to 54 to 56°F. (12.2 to 13.3°C.) in winter.

Experience teaches that cream should be held at or below the churning temperature for a period of at least 2 hours before the churning process begins. If cream is cooled rapidly to the churning temperature from a point considerably above, the churning takes place quickly and is accompanied by a soft condition of the butter and an excessive loss of fat in the buttermilk. Evidently, time is a factor in relation to the effect of temperature upon the physical condition of the fat.

When normal churning is completed the temperature of the butter and the buttermilk is from 4 to 8°F. (2.2 to 4.5°C.) higher than that of the cream at the beginning. The rise in temperature

is the result of at least three factors. Some heat is absorbed from the churn itself due to the fact that the churning is carried on in a room considerably warmer than the cream. A second factor is the friction within the churn, and a third, the release of latent heat by the solidification of those fat globules still in the liquid condition. This last factor is most important when the cream has been cooled rapidly from a high temperature and when the period of holding before churning has been short. The temperature of the cream at time of churning and the period and temperature of holding previous to churning are factors which are closely related to the time of churning. There is also an interrelationship best understood by the results of an experiment.

a. Under certain conditions it was found that cream could be churned efficiently (minimum loss of fat) at 48°F. (8.9°C.) in from 40 to 50 minutes. This cream had been held 12 hours at the churning temperature.

b. A portion of the same cream churned in 30 minutes with a decidedly higher loss of fat after it had been held at the same temperature 48°F. (8.9°C.) 2 hours.

c. A third portion cooled to 38°F. (3.3°C.) for 2 hours then slowly warmed to 48°F. (8.9°C.) churned in practically the same time as (a) and with the same efficiency. It is clear in (c) that the lower cooling temperature served the same purpose as the longer period of holding in (a). Had the churning of (c) been begun at a temperature of 38°F. (3.3°C.) the point at which it was held, the time required for churning would have been greatly prolonged. In fact the churning probably would not have taken place until the temperature increased by friction to the same point as that at which the process was complete in (a).

In practical creamery operations these facts are used constantly. If cream must be churned quickly after reaching the factory to make room for more, the operator lowers the temperature previous to churning in proportion to the interval before churning must begin. If the cream is to be held 12 hours or longer it is cooled only to the churning temperature. The churning temperature also may be varied to suit the time of holding. If, for example, 48°F. (8.9°C.) is the usual churning temperature and for some reason the churning must begin after holding the cream only 1 hour, the correct procedure is to cool the cream as quickly as possible to a point 15°F. (8.3°C.) or more below the

usual churning point and to begin churning with a temperature of at least 5°F. (2.8°C.) below the usual point.

Composition of Butter Fat.—It has been pointed out, previously, that the melting point of the butter fat is a factor influencing the ease with which cream will churn. In the fall and winter months butter fat contains, as a result of the character of the feed received by the cows, a larger proportion of the harder fats and is more difficult to churn unless the temperature of churning is raised. Likewise, in the spring months butter may appear as a slushy mass in the churn unless a lower churning temperature is used. This soft condition is due to the presence of a larger proportion of fats with low melting points as a result of the change in the diet of the cows to pasture grass. Other individual feeds, especially cottonseed meal, exert a specific effect upon the hardness of the fat and, for this reason, the churning temperature may vary from one locality to another, depending upon the prevalence of certain feeds. It is apparent from what has been given that these conditions may be met by adjusting the churning temperature.

Influence of Size of Fat Globules.—The size of fat globules is not a factor of any practical importance to the creamery. It is to be considered, however, in comparing the ease with which cream churns in different localities, and at various seasons of the year in the same locality. Other conditions being equal, large fat globules gather into butter granules more easily and more quickly than small ones, and the time required for the process of churning is somewhat less for this reason. The effect of this factor may be observed in some localities where certain breeds predominate, or may be tested, experimentally where the milk of different breeds is available. The small fat globules characteristic of milk produced near the end of the lactation period are one factor in causing the difficult churning so often experienced under farm conditions. Where butter is made under farm conditions, the cream may be from a few cows only and these advanced in lactation. In the creamery, the cream represents the product of so many cows that conditions in the milk of some that might cause difficult churning are counteracted by others.

Acidity as a Factor.—When the acidity of cream develops to the point of precipitating the casein, it churns more readily than the same cream does at a lower acidity. In order to secure the same efficiency in churning, a somewhat lower temperature must be

used for sweet cream, while a longer churning period also must be expected. In factory practice, it sometimes happens that a suitable temperature has been determined by experience for churning sour cream under the existing condition, but when sweet cream is churned at the same temperature, considerable loss of fat in the buttermilk results. The important fact to consider in churning sweet cream is to use a lower temperature and a churning period somewhat longer than for ripened cream from the same source. The easier churning of sour cream is due to the changed physical condition of the cream as a result of the presence of acid. Although sour cream may appear more viscous than sweet, the facts are that the souring lowers the viscosity of the serum due to the coagulation of the casein. The precipitated casein gathered into masses of various sizes offers less resistance to the contact of the fat globules than when the casein is in the normal colloidal solution.

Viscosity of Cream.—The viscosity of the cream is a factor concerned with churning, especially in relation to the time required to complete the process. Extreme viscosity may result in sufficient cream adhering to the churn, especially the barrel type, to reduce the agitation and thus prolong the churning. A viscid cream also incorporates great volumes of air and, when this condition occurs, the fat globules are not brought together readily and churning is delayed.

The viscosity of cream increases with age, also with the development of acidity up to the point where precipitation of the casein begins after which it is again reduced. The composition of the milk serum is perhaps the most important factor. Changes in this portion of the milk accompany advanced lactation and, to some extent, changes in the feed of the cow.

Richness of Cream.—A cream with a high fat content will churn more quickly than one with a low fat percentage. A low fat content, for example 20 per cent, results in a longer churning period and a higher loss of fat in the buttermilk. Nothing is gained by going to the other extreme. When the fat content is 40 per cent, or above, a fat loss often occurs because of unchurned cream adhering to the walls and end of the churn. In a small churn, for example the barrel type, as used on the farm, cream with a high fat percentage may adhere to the churn to the extent of making churning almost impossible. From 30 to 35 per cent fat in the cream gives the best results both from the standpoint of

time required for churning and that of efficiency in recovering the butter fat from the buttermilk. The more difficult churning of thin cream is caused by the larger proportion of milk serum, which acts as a cushion, keeping the fat globules from coming together.

Fullness of Churn.—The amount of agitation, to which the cream is subjected, will influence the time required for the butter granules to form. A typical creamery churn gives sufficient agitation when it is filled from one-third to one-half full. If filled more than half full, the period of time required for churning will be increased. It can be expected, that when a given churning temperature results in butter forming in from 40 to 50 minutes with the churn one-half full, that the same cream, at the same temperature, will require from 4 to 6 hours to churn when the churn is two-thirds to three-fourths full.

Speed of Churn.—The amount of agitation is also influenced by the speed of the churn. It is essential that the cream be given the maximum amount of agitation as the churn revolves. Should the churn be turned too fast, the force of gravity is overcome by centrifugal force and the cream follows the motion of the churn, receiving little or no agitation and, thus, churning is prolonged. The hand-barrel or power churn should be turned at a speed slightly under that at which the centrifugal force might overcome the force of gravity. This will depend to some extent on the diameter of the churn used.

Fat Losses in Buttermilk.—It is important that the churning operation be conducted with the minimum loss of fat in the buttermilk. As pointed out previously, the factors influencing churning are closely associated with these losses. It would appear that cream must be subjected to sufficient agitation to insure the gathering of most of the fat in granular form. Other factors being the same, when the conditions of churning are such that the butter churns in a relatively short period, it is the general rule that the percentage of fat in the buttermilk will be high. When churning conditions are such that a prolonged churning is required, the fat losses appear to be relatively low. Thus, it happens that, when a relatively high churning temperature is used, the cream churns more quickly with higher fat loss in the buttermilk than when cream is churned at a low temperature. The temperature at which cream is churned, however, is not the only factor involved. Cream must be

held at a temperature sufficiently low to ensure the solidification of the fat globules and, since the solidification of fat is a gradual process, it is essential that the cream be held at a low temperature for the period preceding churning. It was previously stated that cream should be held at the churning temperature, or below this temperature, for 2 hours or more, to permit the fat to chill thoroughly. It is possible to churn cream so efficiently that only a trace of fat can be detected in the Babcock test bottle, following the Babcock procedure. High losses of fat, amounting to buttermilk tests of from 1.0 to 5.0 per cent, or above, may readily occur when too high a churning temperature is used, or when a chilling period preceding churning is too short.

Each of the other factors affecting churning may be responsible for wide variations in the percentage of fat in buttermilk, but all are not so pronounced as the effect of temperature. For example, there is a slight increase in the fat loss in buttermilk when the churn is too full, in which case, a prolonged churning period also results. This is an exception to the general rule, because the result of an over-filled churn is a prolonged churning period and the fat loss is slightly increased.

There is a smaller loss of fat in buttermilk when sour cream is churned than is experienced in churning sweet cream under similar conditions. When the churning temperature is lowered and the churning process is prolonged, however, sweet cream can be churned as efficiently as sour cream. It is apparent from the above statements that it is impossible to churn all the butter fat from cream.

Difficult Churning.—The creamery operator seldom experiences any difficulty in getting the cream to churn. The explanation is that the cream comes from a large number of sources, and, furthermore, under factory conditions it is possible to control all conditions carefully. On the farm, however, churning difficulties are common, especially during the winter season. Sometimes butter is secured only after several hours churning, occasionally not at all. The cream may foam until the churn is full. These especially severe cases of difficult churning often are associated with an abnormal taste which develops in both the milk and the cream after standing 12 to 30 hours. This taste is described as rancid, bitter, or stale and has been found, by scientific study, to be due to the action of the enzyme, lipase, in

the milk. The action of the enzyme on the fat is partly responsible for the trouble in churning.

The troubles which confront the farm butter maker are the result of a combination of some of the factors already described. With one restricted source of supply it is not unusual for all cows to be advanced in lactation. This results in small fat globules, a large proportion of hard fat, and, furthermore, the milk serum from cows near the end of lactation is high in protein, causing a higher viscosity in the cream. These unfavorable conditions often are intensified by failure, on the part of the butter maker, to handle the cream so as to develop the proper acidity. Often little attention is given to the temperature of the cream at the time of churning. The remedy is, first of all, to induce the proper development of acid in the cream and then to obtain a suitable temperature at churning. These measures may be ineffective in some cases. The addition of cream from a fresh cow usually brings the desired result. Another procedure having some merit, during periods when difficult churning occurs, is to mix the cream, fresh from the separator, with sufficient warm water to bring the mixture to a volume approximately that of the original milk, and reseparate. This dilutes the milk serum and reduces the viscosity.

Overrun in Butter Making.—The Babcock test shows the amount of butter fat in cream. When butter is churned from the cream some moisture and curd are incorporated. Later, salt is generally added. As a result, the yield of butter exceeds the amount of the fat. This excess over the fat is called the "overrun." For example, from a batch of cream containing 80 pounds of fat a yield of 100 pounds of butter may be obtained. The 20 pounds of butter in excess of the fat is the overrun. The overrun generally is expressed in terms of percentage. In this case 20 (the overrun in pounds) is easily found to be 25 per cent of 80 (the original amount of fat), and the creamery operator, therefore, records his overrun as 25 per cent. The amount of overrun varies with the composition of the butter and the skill of the operator. On account of the possibility of incorporating an undue amount of constituents other than fat, legal standards have been fixed by national and state laws. At present, federal regulations have established a minimum of 80 per cent of fat. Some states also fix a maximum moisture content, usually 16 per cent. The salt content is controlled by the market demand.

It is exceedingly important that the creamery operator have the skill required to secure the maximum overrun and still keep within legal limits for the composition of the butter. An overrun of about 23.5 per cent based upon the cream test is as high as can be expected. A low overrun results from losing an undue amount of fat in the buttermilk as the result of improper control of the conditions of churning or failure to incorporate sufficient moisture.

Salting Butter.—Salt is added to butter to prolong its keeping quality and to impart a pleasing flavor. The salt used in butter must be of a high degree of purity, of fine grain, and readily soluble. The amount of salt added to butter depends upon the market requirements. The salt content of typical butter, as found on American markets, ranges from 2.0 to 3.5 per cent. The market requirements vary from a demand for butter with no salt, to one containing as high as 5 per cent of salt. This variation is associated, partly, with the grade of the product and, partly, with the locality. The creamery operator adds to butter as much salt as the market which he supplies will tolerate. Salt is cheaper than butter fat and every ounce of salt incorporated into butter replaces an equal amount of butter fat. Market requirements for salt may, therefore, better be termed "salt tolerances."

The modern combined churn and butter worker permits the salting of the butter granules, while they are in the churn, immediately after the churning process is completed, and after the buttermilk has been allowed to drain thoroughly from the churn. The amount of salt for a given churning is calculated on the basis of the pounds of fat in the churn. To secure a salt percentage of 2.5 per cent, the operator should add approximately 3.75 pounds of salt per 100 pounds of fat in the churn, as calculated from the test and weight of the cream. A higher salt content in the finished butter calls for a corresponding increase in the amount added. According to the preference of the operator, dry or wet salt is sprinkled evenly over the butter granules or in a trench formed in the butter by means of a butter ladle after working the butter for a few revolutions with the churn in low gear. The next step is the working of the butter.

Working the Butter.—The object of working butter is to bring the granules into a compact mass, distribute the salt evenly, and expel the surplus buttermilk. This important part of the butter-making process must be regulated so that the

finished butter will have the proper composition and the desirable texture or body. The skillful creamery operator determines, by suitable methods, the amount of water and fat in the butter at one or more intervals during the working process. With this information at hand he removes the surplus water by additional working or increases it by adding the water necessary to give the uniform desirable composition. When the working is completed, no free moisture should be visible. Some butter makers judge solely by the appearance of the butter when the working should be stopped. When the combined churn and worker is used a common practice is to operate the machine for the number of revolutions which experience has shown to be necessary. The results are checked by an examination of the butter. The body of the butter should be close, firm, and waxy. The salt should be distributed uniformly and the water droplets evenly dispersed. Uneven distribution of salt resulting from underworking is associated with an uneven color in the butter known as "mottles." This condition results from relatively large droplets of water in such butter being drawn towards points of high salt concentration, which causes a deeper yellow color in these portions. Overworking of butter, in the normal condition of hardness, results in a dull color and a salvy body. When butter in a soft condition is overworked an objectionable condition known as "greasy butter" results.

Marketing of Butter.—Butter is not a product of thickly populated urban districts but of those regions removed some distance from such centers. Fully 75 per cent of the butter produced in the United States is manufactured in the Middle Western states. This means that the greater part of the butter supply goes through central markets. Furthermore, the production of butter varies widely at different seasons, while the consumption is quite constant. This makes it necessary to provide for the holding of the surplus in cold storage until the immediate supply falls below the demand. Butter dealers or brokers have established themselves at the market centers. To these dealers many creameries ship their product, in accordance with a contract, or, in some cases, to be sold upon a commission basis. The wholesale dealers maintain warehouses, cold-storage facilities, office personnel, and the equipment necessary to conduct a business of this character. The product is sold to the retailer or to other smaller jobbers who distribute

it to the retailer. The wholesale dealer buys his butter mainly in tubs and often sells it to the retailer in the form of prints.

Butter may be held in cold storage by any one who is so inclined and who has the necessary capital. In addition to private cold-storage plants, there are abundant facilities available in every large market where, by the payment of the standard charges, any desired amount of butter may be stored. Some

FIG. 62.—Printing, wrapping, and cartoning butter. The battery of two machines cuts, prints, wraps, and places the butter in cartons automatically. Quarter-, half- or full-pound prints may be handled. The attendants simply regulate and check the operation of the machines. (Courtesy of Land O'Lakes Creameries, Inc.)

wholesale dealers also store butter at times, but many who take part in this speculation have no other relation to the butter industry. Butter goes into storage chiefly during the months of May, June, and July, and is removed whenever the market price reaches a point where the butter can be taken out and sold at a profit. Most of the butter stored is not held longer than 8 or 9 months. Some deterioration in quality often occurs, the extent depending upon the quality of the cream used and the methods of manufacture followed. Butter kept in storage has not been injured in the least for human food, and the plan of storing the surplus for times of scarcity is of decided advantage to both the producer and the consumer.

Within the last decade a few creameries have developed efficient marketing systems within their own organizations. These creameries not only sell the butter manufactured in their own plant or plants but may contract to sell butter made in other plants. By maintaining warehouses and a marketing organization in the large market centers, these concerns are able to market to advantage all the butter which they manufacture and permit smaller plants, with a less efficient organization, to realize higher returns.

Market Terms.—The following are some of the terms applied to butter found on the market:

Sweet-cream Butter.—Butter made from sweet cream, to which no starter has been added. The cream is generally pasteurized.

Ripened-cream Butter.—Butter made from ripened cream. A starter has been added to the cream.

Creamery Butter.—Butter made in a factory from cream produced on a number of farms.

Sweet Butter.—Often refers to butter which contains no salt.

Unsalted Sweet-cream Butter.—Butter made from sweet cream and to which no salt is added.

Unsalted Butter.—Butter to which no salt is added.

Salted Butter.—Butter to which salt is added.

Whey Butter.—Butter made from cream separated from whey which results in the manufacture of cheese made from whole milk.

Farm or Dairy Butter.—Butter made on the farm from a single herd, generally from unpasteurized cream.

Renovated or Process Butter.—Butter which is melted, refined, and reworked. A government tax is levied on this type of butter and all plants manufacturing it are subject to government inspection.

Packing Stock.—Butter which is unsuitable for market purposes, ordinarily used for making renovated butter.

Market Grades of Butter.—Creamery butter is graded on the markets according to its flavor, body, color, salt content, and package. The butter score card used on the market is as follows:

Flavor.....	45 points
Body.....	25 points
Color.....	15 points
Salt.....	10 points
Package.....	5 points

100 points

Although, according to the score card, butter may score 100 points, in practice it is assumed that no butter is perfect and the perfect score is never given. Butter seldom is scored more than 93 or 94 points on the market. This means that butter in

FIG. 63.—The grading of butter by federal inspectors. The inspector uses a butter trier with which he removes a long plug of butter from the tub. He then examines the plug for aroma, taste, body and texture, and color.

which no specific defect may be found is given a score of 38 or 39 points on flavor. The generally accepted grades used on the market, with the scores necessary for such classifications, are as follows:

Specials.—Butter scoring 93 points or above. Must be clean, sweet, creamy, and possess no off-flavor.

Extras.—Butter scoring 92 points. Clean, sweet, lacking somewhat in rich, creamy flavor.

Firsts.—Butter scoring 88 to 91½ points. Butter with a slightly objectionable flavor.

Seconds.—Butter scoring 83 to 87½ points. Possesses off-flavors, fishy, stale, unclean, rancid, cheesy, etc.

Thirds.—Butter scoring 80 to 82 points. Seldom used for human consumption.

Butter Defects. *Flavor.*—The average consumer is not concerned with all the defects that the critical judge of butter may look for in butter. Flavor receives the special attention of the consumer and, for this reason, flavor is given the largest number of points on the score card. Butter showing irregular color, a

condition described by the butter man as "mottled," also is very objectionable to the consumer.

While expert judges will agree rather closely in judging the flavor of butter, it is difficult to describe either the desirable or undesirable flavors. Flavor can not be measured chemically and can be described only by comparison with some well-known flavor possessed by other substances. Certain flavor defects sufficiently characteristic to allow of some unanimity in describing them are fishy, rancid, cheesy, metallic, yeasty, lardy, bitter, or cooked. The causes of these flavors are fairly well understood as the result of extensive investigations in America and abroad.

Many lots of butter show defects in flavor equally objectionable but which cannot be classified so definitely. Judges follow the custom of using various descriptive words that may or may not have any relation to the cause which the term may suggest. Often the same flavor might be described in different terms by each of several judges. Among the terms of this class are, "unclean," "fruity," "stale,"

"barny." When a low score is given, and such terms are used, there is little question regarding the quality of the butter, but neither the score nor the descriptive terms are of much assistance to the butter maker in finding the cause of the poor quality.

Body Defects.—By the term, "body," is understood the general character of the physical makeup of the butter. The word texture was formerly in common use with the same meaning. Butter should be reasonably firm, close textured, and of a waxy appearance. A weak-bodied butter is a butter which does not stand up readily at ordinary temperatures; a greasy texture indicates a butter with the appearance of grease; a salvy texture is

FIG. 64.—Mold on butter. Mold sometimes develops on butter as shown in this illustration of butter as it appeared when removed from the tub. If the mold is not growing through the butter but only on the surface, it may be removed by scraping and the unaffected butter sold. If the mold has penetrated the butter, the product is classed as packing stock and sold at a low price.

a butter which has been worked until the grain is destroyed entirely. Butter from which water readily leaks is said to have a "leaky body." Other body defects are crumbly, sticky, and mealy.

Color and Salt Defects.—Either too much or too little color is objectionable. The market, in general, requires a butter of a light straw color. When the color of butter is distributed unevenly or when light streaks show between darker streaks of yellow, butter is said to be "mottled." This defect is due to an uneven distribution of water through the butter, associated with an uneven

FIG. 65.—Farm butter-making equipment. The illustration pictures a hand churn and a lever-type butter worker together with other equipment found in a well-equipped farm dairy.

distribution of salt to which water may be attracted. Distinctly colored areas may appear on the surface due to the action of bacteria, yeasts, or molds. Salt defects in butter may be designated as too high or too low salt content. Butter in which the salt content is so high that undissolved salt occurs throughout the mass is often spoken of as being "gritty."

Farm Butter Making.—The same principles given for butter making under factory conditions apply equally to making butter under farm conditions. Due to the small quantities involved and the limited amount of equipment available, however, the practices differ in many respects. On the farm, due to the small amount of cream, it may not be practical to churn oftener than

twice a week. To keep cream longer than this without pasteurization will nearly always result in inferior butter that will deteriorate rapidly. The proper procedure is to cool the cream immediately after separation and keep it cool until the day previous to churning when it may be warmed to room temperature for souring and again cooled to the churning temperature for at least 2 hours before churning begins. The warming of the cream to encourage souring may be omitted if too great difficulty in churning is not encountered by such a procedure. The use of a starter is seldom practiced under farm conditions.

A floating dairy thermometer always should be available to use in regulating the temperature. No one can guess the temperature with sufficient accuracy. Prolonged churning often results from failure to observe the important precaution of having the cream at the proper temperature when churning begins. It is impossible to give any one temperature as correct for churning under these conditions. Experience has shown that the best rule to follow is to regulate the temperature to a point at which the churning may be completed within 30 to 40 minutes for sour cream, or 50 to 60 minutes for sweet cream. In the summer the temperature probably will be between 45 and 55°F. (7.2 to 12.8°C.) and in winter from 55 to 70°F. (12.8 to 21.1°C.).

The churning should be continued until the butter granules are the size of peas. The buttermilk then is drawn from the churn. The use of a fine strainer is almost necessary; otherwise, some particles of butter will be lost in the buttermilk. A small quantity of cold water then is poured over the butter granules and when the water comes from the churn nearly clear, the buttermilk opening is closed. Next, cold water to an amount approximately equal to the amount of cream churned is poured into the churn, the top put on, and the churn revolved a few times. If the butter appears soft, the water which is used may be considerably colder than the churning temperature. The butter should be firm and waxy when worked and, to obtain this condition, it may be desirable to allow the butter to remain for some time in the cold water.

Many types of churns are used on farms, but the most common, and the most satisfactory, is the ordinary barrel churn.

Various forms of workers are used. In earlier years, the common practice was to use a wooden bowl into which the butter was placed. The working was done with a wooden

ladle. Later, different types of small workers came into use, especially where considerable butter was made. The lever-type hand worker is as satisfactory as any. Any wooden utensil with which butter comes in contact, including churns, ladles, printers, or workers, should be washed thoroughly with hot water and followed by rinsing with an abundance of cold water. This procedure prevents the butter from adhering to the wood. When not in use, wooden utensils should be stored where they will not dry out excessively; otherwise, a period of soaking for

FIG. 66.—Hand butter printer. Butter may be printed in the form of neat prints by means of a hand printer. The print is wrapped in parchment paper and is often placed in an attractive carton.

some hours will be necessary to fill the pores of the wood thoroughly before using. The amount of salt to be used is estimated from the weight of churned butter. The usual amount is from $\frac{3}{4}$ to 1 ounce per pound of butter. The salt is sprinkled over the butter spread on the worker. By means of the lever or ladle, the working is continued until the butter is in a compact mass and the salt distributed uniformly. The proper stage to stop working is judged best by pulling the butter apart by means of a ladle. The individual grains or granules still should be visible but will show a tendency to string out. If uneven color appears after the butter stands a few days, the working was insufficient.

Hand-printing devices are desirable to put the butter into packages for the market. Parchment paper should be used for

wrapping the prints. Another common plan is to pack the butter in stone jars ranging in capacity from 1 to 5 pounds. Farm-made butter is used on the farm where it is made or it may be sold locally. Except when a special outlet is known it is not advisable to undertake to ship butter of this class to the large markets.

CHAPTER XI

THE MANUFACTURE OF DAIRY PRODUCTS (*Continued*)

CHEESE

It is not known who manufactured the first cheese. That it is one of the oldest products made from milk is indicated by the fact that cheese is mentioned in the earliest parts of the Bible (Job X: 10 and I. Samuel XVII: 18). According to Anderegg, the people of Greece used cheese from 1000 to 450 B. C., and the Romans from 775 to 750 B. C. Cheese was a common food in what is now Germany by 800 A. D. For several centuries, during the Dark Ages, the monks of the monasteries were the leaders in the art of cheese making and in teaching others its manufacture. By the year 1000 A. D., cheese had become an important article of trade in the cities of Europe.

The types of cheese made in the European countries differed in the various sections and, as time progressed, certain sections became more or less known for the production of special varieties of cheese. Thus, today, the common cheeses, for which France is known, are Camembert and Roquefort; Switzerland, Emmental, usually known as Swiss cheese; England, Cheddar and Stilton; Belgium, Limburger; Holland, Edam and Gouda; the Scandinavian countries, Primost and Gammelost; and Italy, Gorgonzola and Parmesan. A number of factors, such as climatic conditions, geographic location, etc., were responsible for the development of the various types of cheeses in different localities.

Development of Cheese Making in the United States.—Originally, cheese was made on the farm. This was true of the European countries and America alike. The cheese made in America, in the colonial days, was of the same varieties with which the colonists were familiar in Europe. Certain sections of America became more or less well known for special varieties of cheese because of the settlement of these sections by Europeans from a given locality. Thus, Cheddar cheese became a well-known product in Herkimer County, New York, and Swiss cheese in Green County, Wisconsin. Because of the nationality of the

early settlers in these states cheese early became an important product.

It was in the period between 1860 and 1870 that the greatest change took place in the cheese industry in America, as it was during this period that a large number of cheese factories were established. Jesse Williams, of Oneida County, New York, established a cheese factory in 1851 which is credited with being the first plant actually operated under the factory system. The introduction of this system soon resulted in a reduction in the amount of cheese made on farms. It has been estimated that,

FIG. 67.—A cheese factory. It is essential that fresh milk be secured in the manufacture of cheese. Small factories are placed in rural sections at points convenient to the milk producer. (*Courtesy of Twin City Milk Producers' Association.*)

by 1869, two-thirds of the cheese made in America was made in factories. Today, the amount of cheese manufactured on the farm is practically restricted to that for home consumption, in a few scattered sections.

New York was the leading cheese-manufacturing state for a long period. Between 1899 and 1909, the demand for market milk in New York, and the increased manufacture of cheese in Wisconsin, resulted in New York's dropping to second place in the industry. Wisconsin is the chief cheese-manufacturing state at the present, while the industry, in recent years, has been developing quite rapidly in Kansas, Missouri, Oklahoma, Oregon, and Tennessee.

Influence of Scientific Investigation.—Comparatively little attention was given to the application of science to the manufacture of cheese before the establishment of the state experiment stations. Science found cheese a most interesting field, and science has done much to standardize the methods of manufacture of many different types of cheese. The process of manufacturing cheese under present-day conditions has turned, therefore, from rule-of-thumb methods, for which there were no explanations, to practices based upon the application of fundamental facts involving a knowledge of the chemistry and the bacteriology of milk. No manufactured dairy product requires quite the skill and close application to scientific methods as does the manufacture of cheese. The field is still open, and science will doubtless contribute much, in the future, to the practices at present followed in the cheese factory.

Nature of Cheese.—Cheese consists of a concentration of the constituents of milk, principally fat, casein, and insoluble salts, together with water in which small amounts of soluble salts, lactose, and albumin are found. To retain these constituents in concentrated form, milk is coagulated either by means of lactic acid produced by bacteria or by the addition of rennet. A portion of water is removed by cooking, stirring, or draining the curd or by mechanical application of pressure. The cheese may or may not be ripened, but if ripened, the nature of the process depends upon the particular variety of cheese. The cheeses of particular interest to American markets are the American Cheddar, Cottage, Neufchatel, Roquefort, Swiss, Limburger, Camembert, Brick, and Process cheese. Of this group Cottage, Cheddar, and Process or Loaf cheeses are the most common on the market.

Classification of Cheese.—There are probably about eighteen distinct varieties of cheese. More than 400 names are applied to these varieties, however, owing to the fact that many cheeses, essentially of the same variety, were named in different localities. In addition, private concerns have found it profitable to mix cheeses of different varieties and sell the product in various types of packages under certain trade names. It is possible, however, to classify the cheeses according to two general types, namely, hard and soft.

Among the hard cheeses may be included those which are only semi-hard and ripened by certain molds. Roquefort and Gorgon-

zola are representatives of this group. In addition, there are several semi-hard cheeses, such as Brick, which are ripened by bacteria. Of the hard cheeses, there are a number that may be classed as very hard, with and without gas holes. Those without gas holes are such cheeses as American Cheddar and Edam, while the Swiss or Emmental cheese is representative of the very

FIG. 68.—Some common varieties of cheese found on the American market. Cheddar cheese is the most common cheese found on the market in the United States. Swiss, Roquefort, Limburger, and Brick are common in the larger retail stores. Münster is a soft rennet cheese made in the western part of Germany.

hard cheese possessing gas holes. Soft cheeses consist of the unripened, acid curd, such as the ordinary Cottage cheese; Camembert, ripened by mold; and Limburger, ripened by bacteria.

CLASSIFICATION OF CHEESE

Cheese.....	{ Hard	{ Very hard	{ Without gas holes, <i>Cheddar</i>
			{ With gas holes, <i>Swiss</i>
	{ Soft	{ Semi-hard	{ Ripened by molds, <i>Roquefort</i>
			{ Ripened by bacteria, <i>Brick</i>
		{	{ Ripened by bacteria, <i>Limburger</i>
		{	{ Ripened by mold, <i>Camembert</i>
		{	{ Unripened cheese, <i>Cottage</i>

With the exception of Cottage cheese, all the varieties of cheese common in the United States are made by the use of rennet to coagulate the milk. In Europe, large quantities of ripened soft cheeses and a few varieties that would be classed as hard, are

made from curd formed by the action of the acid produced by the milk-souring organisms.

The yield of cheese of the hard types varies from 8 to 14 pounds from 100 pounds of milk, depending upon such factors as the percentage of fat and casein in the milk; the percentage of milk constituents, principally fat and casein lost in the manufacturing process; and the amount of moisture incorporated in the cheese. The yield of soft cheese is generally greater than that of hard cheese, primarily because of the larger amount of water incorporated. For these the yield may range from 12 to 16 pounds per 100 pounds of milk. Hard cheeses are seldom made from skim milk though, as will be pointed out, skim milk may be used. Some varieties of soft cheese, such as the common Cottage cheese, may be made entirely from skim milk. Fat often is added to such cheese in the form of cream. A common soft cheese known as "Cream," sometimes referred to as "Philadelphia Cream," is made from cream with varying percentages of fat, depending upon the amount of fat desired in the finished cheese.

The hard cheeses in the United States, generally, are made from fresh raw milk. In countries such as New Zealand most of the cheese is made from pasteurized milk. There are distinct advantages to be gained from the pasteurization of milk for cheese making and a superior quality of cheese is usually obtained. With newer methods of pasteurization being introduced, and with larger factory units, its use may become more widespread in this country. There are some difficulties encountered with the coagulation of pasteurized milk, with the control of moisture content, and ripening, but these can be readily overcome. Milk is quite often pasteurized before making it into some of the soft types of cheese, such as Cottage.

Composition of Cheese.—The composition of cheese depends upon the variety. All cheese contains the same constituents of milk, but in varying proportions. The most variable constituents are fat and water. The table shown at the top of page 243 gives the approximate composition of some of the most common cheeses.

A number of factors influence the composition of a given cheese. The analyses submitted are averages reported by various workers and, doubtless, can be depended upon to represent typical cheese of the varieties included.

Milk for Cheese Making.—Cow's milk is used most frequently for the manufacture of cheese; however, several varieties are made

COMPOSITION OF CHEESE¹

Variety of cheese	Fat, per cent	Protein, per cent	Lactose and ash, per cent	Water, per cent
Cottage.....	0.40 to 1.90	12.70 to 21.00	0.20 to 1.10*	71.40 to 79.90
Neufchatel.....	23.00 to 28.00	18.00 to 21.00	0.50 to 1.25	50.00 to 55.00
Swiss (American)...	30.00 to 34.00	26.00 to 30.00	3.00 to 5.00	30.00 to 34.00
Cheddar (green)...	30.00 to 36.79	20.80 to 26.11	3.12 to 7.02	32.69 to 43.89
Roquefort.....	31.50 to 33.53	19.14 to 23.06	5.18 to 6.81	37.49 to 40.10
Brick.....	28.34 to 33.77	20.03 to 23.29	1.68 to 4.20	39.61 to 45.26

* Salt-free.

¹ "Fundamentals of Dairy Science," 2d ed., Reinhold Publishing Corp., New York. Table by Wright, Research Laboratory, Bureau of Dairy Industry, Washington, D. C. Copyrighted.

from goat's, sheep's, or mare's milk. The quality of milk used for cheese making on a commercial scale is of prime importance. It must be of the very best if desired results are to be obtained. Since most cheese made must pass through a ripening period, the type of bacteria which predominate in the milk may play an important part in the development of the flavor of a given cheese. To ensure satisfactory results, milk to be used for cheese making must be fresh, clean, of low bacterial content, and possess a clean, desirable flavor. Any abnormalities in flavor or in odor are to be avoided. A dirty milk or a milk containing large numbers of bacteria which are found associated with unsanitary methods in the dairy cannot be used in the manufacture of a high-quality cheese. Milk having undergone extensive fermentation is practically useless. Furthermore, no treatment of milk can be depended upon to improve a low-quality milk for the manufacture of cheese.

As it will be noted, all of the cheeses mentioned depend in a large measure upon microorganisms for the development of their characteristic flavor, aroma, or appearance. The organisms may be the principal factors, but in nearly every case there is evidence that various enzymes may also take part in the curing process. In every instance, there must be an accurate control of conditions of curing so that particular types of organisms may be favored; otherwise, untoward results will appear.

Cheese making is a splendid example of applied microbiology. The activities of manufacture and curing are directed toward control of fermentations by the selection and the cultivation of specific microorganisms under the most favorable circumstances.

Curd Formation.—A characteristic of all cheese making is the formation of a curd or the coagulation of the milk. Coagulation is brought about by means of the action of lactic acid produced by fermentation, by the action of rennet or pepsin, or by a combination of lactic acid and rennet. In either case, it is the casein of milk which is congealed to form the curd. Casein is coagulated readily by acids and by enzymes, such as rennet and pepsin. The chemical changes involved in the case of acid coagulation and enzyme coagulation are distinctly different. When milk is coagulated by lactic acid, the calcium of calcium caseinate probably unites with the lactic acid to form calcium lactate. The casein is set free and forms a firm “gel” or curd. This same change in milk is brought about by other acids. A simple laboratory experiment will illustrate the action of acids such as hydrochloric, sulfuric, or acetic acid. The change taking place in milk when coagulated by rennet is set forth by Van Slyke and Price as being due to the formation of calcium paracaseinate, as a result of the action of rennet on calcium caseinate.

The rate of rennet coagulation is influenced by several factors, such as the temperature and the acidity of the milk. In the case of the hard variety of cheese, sufficient rennet is added to the milk to bring about a complete coagulation in 15 to 20 minutes. After adding and mixing rennet to milk, the first signs of coagulation may be observed in 8 to 10 minutes. It will be observed that there is slight thickening of the milk, flocculent curd particles will become visible to the eye, and, finally, the casein will form a firm gel. When the coagulation is dependent upon the action of lactic acid produced by the bacterial fermentation of lactose, from 8 to 16 hours may be required before sufficient acid is produced to bring about coagulation.

THE MANUFACTURE OF HARD CHEESE

The common cheese on the American market is correctly known as the American Cheddar. The processes involved in the making of this cheese are given in some detail on account of the importance of this variety, and, further, because of the fact that the procedure followed in the manufacture of other hard cheeses is much the same.

American Cheddar Cheese.—This typical cheese in the hands of the retailer may be sold under a variety of names such as “cream,” “New York,” or “Wisconsin.” Regardless of the

name, the assumption is reasonably correct that the process followed in manufacture is essentially that known among cheese makers as the "Cheddar process." The variety of cheese known as the "Cheddar" originated many years ago and secured its name from the village of that name in Somersetshire, England.

The manufacture of this cheese consists of a number of processes, each of which is intended to assist in concentrating the

FIG. 69.—Cheese curd knives. Knives such as these are used to cut the curd in the manufacture of Cheddar and other varieties of cheese. (Courtesy of Damrow Bros.)

constituents of the milk and eliminating the water. At the same time, conditions are maintained which are favorable for the development of a desirable flavor and a characteristic body and texture in the finished cheese. The terms used and the processes will be outlined briefly.

Equipment Required.—A vat is used to hold the milk and this vat sets inside a second designed to hold water. By controlling the temperature of the water in the outer vat, the temperature of the milk is adjusted to the proper point. The vat should be rectangular in shape, flat bottomed, sloping, however, towards the center and the outlet end where the whey is drawn off.

Curd Knives.—A set of two curd knives is required with which to cut the curd. The knives consist of a series of blades or wires set in a frame. The blades or wires are set at equal distances apart, and, in one knife, the blades or wires are set vertically in the frame and in the other horizontally.

Curd Rake.—A rake constructed of wood is necessary for the stirring of the curd.

The Curd Mill.—The curd mill consists of a piece of apparatus equipped to cut slabs of milk curd into strips about $\frac{1}{2}$ to 1 inch wide and 2 to 3 inches long. One type consists of a hollow cylindrical drum suspended on an axle which can be revolved by either hand or motor power. At regular intervals on the cylinder is a raised section leading towards the inside of the drum and in which are inserted a number of thin blades. A tin tray serves to aid in guiding the curd towards the blades.

Cheese Hoops.—Cheese hoops built of heavily tinned steel are used for holding the curd in preparation for pressing the curd and shaping the finished cheese.

Cheese Bandages and Circles.—The cheese hoops are lined with a cheese bandage which is made of thin woven cotton known as cheesecloth. Into the bottom of the hoop is placed a heavy cloth circle on top of which is placed a thin starched cheesecloth circle. After the curd is placed in the hoop, still another thin starched cheesecloth circle is placed on top of the curd followed by a heavy cloth.

Cheese Press.—A cheese press by means of which the cheese may be pressed after being placed in the cheese hoops is also required.

Paraffin Tank.—A galvanized tank is required for paraffin. The tank must be equipped with a steam coil in the outer jacket in order that the paraffin may be heated. The cheese is dipped into the hot paraffin at the proper time.

Miscellaneous Equipment.—In addition to the above equipment, the cheese factory will need considerable equipment such as a Babcock tester, milk-testing glassware, and apparatus for acidity testing. More modern factories find equipment for the complete analysis of milk and cheese desirable.

Other Supplies.—Among the supplies needed, may be listed cheese rennet, cheese color, salt, paraffin, equipment for making the acidity test, sulfuric acid, etc.

Process of Manufacturing Cheddar Cheese.—The milk intended for cheese making is placed in the cheese vat, as received

at the factory. In recent years, the practice is growing of standardizing the milk to a definite fat percentage in order to ensure cheese of a uniform composition. A fat percentage of 3.25 per cent quite frequently is used. After standardizing the acidity test is made to determine the percentage of acid in the milk. The common practice is to measure the acidity by titrating with tenth-normal sodium hydroxide, using phenolphthalein as an indicator.

FIG. 70.—Inside view of a cheese factory. Here is illustrated much of the equipment used in the making of Cheddar cheese. In the foreground is shown the cheese press, back of which is the cheese vat on which is placed a curd mill. Above the cheese vat is shown a tank into which the whey is pumped after the curd is cooked. From this tank the whey flows through a whey separator, after which it is frequently discarded as practically all butter fat is removed. Milk sugar and albumin are, however, secured from the separated whey when a sufficient quantity is available. (Courtesy of Damrow Bros.)

Ripening the Milk.—A culture of lactic-acid bacteria known as a “starter,” and similar to butter starters, then is added to the milk. Usually, sufficient starter is added to raise the acidity of the milk to 0.17 to 0.20 per cent which is the acidity desired at the time of adding the rennet. By allowing the milk to stand sufficiently long, the additional acid will form, due to the growth of the bacteria carried in the starter.

Addition of Cheese Color.—While the milk is being brought to the setting temperature, cheese color may be added, the amount depending upon the shade desired. If a light-straw

color is desired, about $\frac{1}{3}$ ounce of cheese color may be added to each 1,000 pounds of milk. For a deep yellow, 2 ounces per 1,000 pounds of milk may be added. The milk is stirred thoroughly to ensure an even distribution of color.

Setting the Curd.—The milk is brought to a temperature of 84 to 88°F. (28.9 to 31.1°C.) by heating the water in the outer vat. Casein, it will be recalled, is coagulated by rennet. After adding rennet extract, 2.5 to 4 ounces per 1,000 pounds of milk, the casein of the milk forms a firm curd. Sufficient rennet is added to bring about a firm coagulation within about 20 minutes. The amount needed is regulated by the results obtained from day to day. The rennet extract is diluted with water to about 20 times its volume and added slowly to the milk. Meanwhile, the milk is stirred thoroughly to ensure uniform distribution.

Cutting the Curd.—After a firm curd is formed, it is cut with the cheese knives. The curd should be cut into small cubes about $\frac{1}{2}$ inch square. This is accomplished by cutting the curd lengthwise of the vat with the horizontal curd knife and both lengthwise and crosswise of the vat with the perpendicular curd knife.

Heating the Curd.—After cutting, the curd is heated. This is accomplished by heating the water surrounding the vat with live steam. The temperature of the whey surrounding the curd is raised slowly to that of 98 to 104°F. (36.7 to 40.0°C.). The heating temperature should be reached in 30 to 40 minutes. The curd particles are kept from matting, and the whey agitated from time to time by stirring with the curd rake. During the heating process, the curd particles contract to about one-half their original size, eliminating considerable water or whey. The cheese maker determines the point at which to stop heating by the feel and appearance of the curd particles and the increased acidity of the whey.

Removing the Whey.—After the cooking is completed, the whey is removed from the curd by placing a screen strainer in front of the outlet of the vat to draw it off at this point. The curd remaining in the vat is then piled on each side of the vat to permit it to drain and mat.

Cheddaring the Curd.—After removing the whey and piling, the curd is cheddared. It is this process which distinguishes Cheddar cheese from many others. In the cheddaring process the curd is piled at both sides of the vat and permitted to mat.

The small curd particles soon adhere to one another forming a completely solid mass. By means of a large knife the matted curd is cut into strips which may be about 6 to 10 inches wide by 8 to 14 inches long and 2 to 4 inches thick. The curd strips are turned at intervals of about 15 minutes and piled two to six slabs deep. When the cheddaring process is completed, the small particles lose their identity completely, fusing together into a practically solid mass of curd. Considerable water or whey is eliminated during the process.

Milling the Curd.—After cheddaring, the curd is passed through the curd mill which cuts the slabs of curd into strips about $\frac{1}{2}$ to 1 inch wide and 2 to 3 inches long. Moisture or whey is eliminated during this process also.

Salting the Curd.—The strips of curd are stirred to prevent matting after milling and salt is sprinkled on at the rate of 1 to 2 $\frac{1}{2}$ pounds per 1,000 pounds of milk used.

Hooping the Curd.—After salting, the curd is ready for the cheese hoop. The hoop is lined with a cheese bandage. In the bottom of the hoop is placed a starched cheesecloth circle and, after the curd is placed into the hoop, a similar circle is placed on top of the curd. A cover of a circular block of wood is then placed over the top of the curd.

Pressing the Curd.—The hooped curd then is placed in a cheese press, where pressure is increased gradually as the whey or water comes from the cheese. The pressure should be applied gently at the beginning and increased considerably as the curd packs. The cheese is left in the press about 24 hours, after which it is removed in order to smooth out all wrinkles that may be formed on the bandage and to adjust the bandage along the rim at the top and the bottom of the cheese. It then is placed again in the press for another 24 to 48 hours.

Paraffining the Cheese.—Cheddar cheese is removed from the press and placed in a cool, dry place for several days to permit the surface to dry. After a dry surface is secured, the cheese is dipped into a vat of paraffin which has previously been heated to 212–240°F. (100–115.56°C.). This procedure covers the cheese with a thin layer of paraffin, closes all pores, kills any mold that may have been deposited upon the surface, and checks evaporation of the water from the cheese during curing.

Curing Cheddar Cheese.—The curing of Cheddar cheese is brought about through a series of changes in the protein. The

cheese is placed upon shelves in a well-ventilated room maintained at a temperature ranging from 40 to 65°F. (4.4 to 18.3°C.). The lower the curing temperature, the slower is the curing process and the better the quality of the finished cheese. The finished cheese contains sufficient moisture for bacterial growth. While the exact details of the ripening of Cheddar cheese from the bacteriological viewpoint are not completely understood, it appears that the *Streptococcus lactis* type of bacteria predominates in the fresh cheese and provides an acid medium which restricts the growth of most bacteria. These bacteria soon decrease in numbers, however, and are replaced by certain other types, such as the *Lactobacillus casei*, which have persisted in the milk and which increase tremendously, and attack the protein to produce a part of the characteristic flavor of Cheddar cheese. Thus it is, in part at least, a bacteriological process, although certain enzymes present in the milk and rennet, or produced by microorganisms, apparently play important roles. Whenever organisms other than those mentioned above gain an ascendancy, defects such as those termed "gassy," "burnt," "bitter," "putrid," "yeasty," or "fruity," may appear; the surface of the cheese may be marred by discolored areas, or mold may grow extensively, especially upon the surface.

Forms of Cheddar Cheese.—Cheddar cheese appears on the market in a number of forms and sizes. The various shapes are secured by using hoops of different types. The typical cheese weighs about 40 to 50 pounds, is 13½ to 15 inches in diameter, and 10 to 12 inches high. Thom and Fisk present the following table showing the various sizes and shapes of Cheddar cheeses:

SIZE OF CHEDDAR-CHEESE HOOPS, WEIGHT, AND TERMS APPLIED TO CHEESE

Diameter of hoop, inches	Height of cheese, inches	Weight of cheese, pounds	Terms applied to cheese
6 to 7	7 to 8	9 to 11	Young America
Tapers, 5 to 7	10 to 14	10 to 16	Longhorn
12 to 14	3½ to 4½	18 to 24	Daisy or picnic
14 to 15½	4 to 6	30 to 40	Twin (two in same box)
14 to 16	4 to 7	35 to 40	Flat
13½ to 15	10 to 12	40 to 50	Cheddar
14 to 16	12 to 15	75 to 90	Export

The most common of these cheeses in the retail store is the Twin. The Cheddar is used primarily in the making of Process

or Loaf cheese. In addition to the above, rectangular cheeses of the same type are on the market.

Whole Milk or Skim-milk Cheddar.—Cheddar cheese may be made from whole milk, skim milk, or from milk from which part of the cream has been removed. A Cheddar cheese is never made from cream. The term “cream cheese” applied to Cheddar cheese in some localities refers to typical Cheddar cheese made of whole milk. The use of this term dates back to the time when most of the cheese was made from skim milk.

FIG. 71.—A group of cheese hoops. Cheese of the Cheddar type is shaped into various forms by placing the curd into differently shaped hoops such as illustrated. Here is shown a Loaf cheese mold in the background at the reader's left. In the left foreground is shown a form commonly used in making a cheese known as the Gouda; following, there are shown the hoops used in molding the Longhorn, Young America, Export Cheddar, and Twin Cheddar cheeses. (Courtesy of Creamery Package Manufacturing Company.)

The typical cream cheese is a Neufchatel cheese to which cream is added. Cottage cheese made of skim milk is often referred to as “creamed Cottage.”

Cheddar cheese made from skim milk must be labeled “skimmed Cheddar” in most states, and as half skim and half whole milk is sometimes used, these same states require that such cheese be labeled “half skim.” If three-quarters of the milk going into a Cheddar cheese is skim milk, the cheese must be labeled “three quarters skim.”

Market Grades of Cheddar Cheese.—There are no sharp and definite grades of Cheddar cheese. Cheese is sold on the market according to the style, such as Daisies, Twins or Cheddars, and

according to its age. The terms applied on the market are fresh, fresh cured, and cured or held cheese. A typical market report on cheese issued by the U. S. Department of Agriculture is reproduced below:¹

WHOLESALE PRICES—No. 1 AMERICAN CHEESE

Styles	Boston	New York		Phila- delphia	Chicago
	Fresh	Fresh	Held	Fresh	Fresh
Flats.....					
Twins.....	16 to 17				15¼ to 15½
S. Daisies.....	17 to 17¼	16½ to 17	18 to 19	16½ to 17	15½ to 15¾
Y. Americas.....	17 to 17½	17 to 17¼			
Longhorns.....				16¾ to 17	15¾ to 16

The channels through which cheese is sold are similar to those for butter. Dealers in cheese maintain large warehouses in which cheese is stored and from which it is distributed to smaller wholesale and retail dealers. If Cheddar cheese is to be held for a long period, it is generally kept in cold storage at a temperature near that of 40 to 59°F. (4.4 to 10.0°C.).

The marketing of other types of cheese is much the same as Cheddar with the exception of the soft cheeses such as Cottage and Neufchatel. These are sold more often by the manufacturer directly to the retail distributor or the consumer.

Defects in Cheddar Cheese.—The defects in common cheese are those of flavor, body and texture, color, and outside appearances. The score card used in connection with the scoring of cheese is as follows:

Flavor.....	45
Body and texture.....	30
Color.....	15
Finish.....	10

It must be remembered that the score card is not so commonly used in the grading of cheese as in the grading of butter.

Flavor Defects.—The judge of cheese is accustomed to the use of certain terms in describing the flavor defects in cheese which are more or less understood by all acquainted with the industry.

¹ (Figures are cents per pound.)

Such terms as "high acid," "sour," "bitter," and "unclean" are in use and the particular defects to which they are applied are recognized. The flavor of cheese generally is judged, by the expert, not by the taste but by the smell. A small plug of the cheese is removed and kneaded in the hand and the odor of the warm cheese noted. A desirable cheese flavor is exceedingly difficult to describe in words. It may be described best as a clean, pleasant, rich, nutty flavor.

Body and Texture Defects.—Cheddar cheese should have a firm, waxy, smooth, compact body and texture. One of the most common defects is termed "gassy," in which case, small gas holes appear throughout the cheese. Such a condition is not desirable, but it occurs so frequently that the average consumer may be led to believe this condition characteristic of Cheddar cheese. Gas holes actually indicate unsatisfactory conditions in the handling and care of the milk or the improper use of starter in the manufacture of the cheese. Such cheeses often have a decidedly unpleasant flavor. In addition to gas holes, the body may be too pasty, or too firm or too rubbery. If the curd particles have failed to fuse during pressing, the cheese body may be loose. A cheese high in water may be pasty, while one very low in water may be hard and dry.

Color Defects.—Color in Cheddar cheese may be too high or too light, streaked or uneven, white specks may be visible, or it may be marbled or mottled. It sometimes occurs that the fat is squeezed from cheese during pressing, so that a thin layer is formed between each individual curd particle. Thus, the color is darker around the curd particle. The cheese judge uses the term "seamy" in this case. Certain bacteria, yeasts, or molds may also produce distinct discolorations. A desirable color is one that is uniform throughout.

Defects in Finish.—The appearance of cheese is of considerable importance. The bandages must be smooth and the cheese well shaped. Wrinkles in the bandage, uneven edges, and unclean surfaces are objectionable.

Emmental or Swiss Cheese.—Emmental or Swiss cheese originated in Canton Bern, Valley of Emmental, Switzerland. It is a cheese of the hard type, has a mild, somewhat sweetish taste, and is particularly characterized by the holes or eyes which develop in the cheese. These should be about $1\frac{1}{2}$ to $5\frac{1}{8}$ inch in diameter and from 1 to 3 inches apart.

The cheese is made by cooking milk in huge copper kettles. The modern procedure, in American factories, is to inoculate the milk with a pure culture of *Lactobacillus bulgaricus*, which produces lactic acid, assists in checking the development of undesirable fermentations, and aids in controlling the ripening of the cheese; and with pure cultures of *Lactobacillus casei* and *Propionibacterium shermanii*, the latter to aid in the development of the eyes or holes and the sweetish flavor. The milk is coagulated with rennet and the curd cut in a manner somewhat similar to the process used in the case of Cheddar cheese. In the case of Swiss cheese, however, the curd is cut a second time before heating or cooking proceeds by giving the curd a circular motion in the vat and by using a specially constructed instrument called the "harp" and a fixture within the kettle known as the "breaker." The curd thus is broken into pieces about the size of wheat kernels. The curd is cooked until sufficiently firm. The curd then is brought into a cone-shaped pile in the kettle by giving it a rotary motion while in the whey. The mass of curd then is removed from the whey by means of a cloth resembling burlap. The curd then is placed in hoops which are about 4 to 6 inches deep and of varying diameters. After pressing for about 24 hours, the cheeses are covered with a layer of salt and turned occasionally. After about 2 days, the cheeses are placed in a tank of salt brine where they remain for from 1 to 4 days. The cheese is then cured from 3 to 6 months. The bacterial fermentations which take place are very delicately adjusted to one another and they demand careful attention on the part of the cheese maker to see that conditions are favorable for the proper sequence of these fermentations.

If this is not done, defects may appear. The cheese may be "blind," due to the fact that the propionic acid bacteria have not grown properly. Other defects may appear because of the activity of other bacteria which have not been held in check. Bacteria may be responsible for (1) the "stinker" Swiss cheese, (2) "blowing" where the cheese is puffed out abnormally due to gas, and (3) the "Niszler" defects due to gas-producing spore-bearing bacteria.

Roquefort Cheese.—The manufacture of Roquefort cheese has been carried on in the southern part of France for at least two centuries. The village of Roquefort, France, from which the cheese derives its name, has been famous for Roquefort

cheese for many generations. The cheese is characterized by its striking marbled or mottled appearance, due to the growth through out the cheese of the bluish-green mold, *Penicillium roqueforti*. In France, the cheese is made primarily from sheep's milk. American manufacturers have been rather successful in making a Roquefort from cows' milk but it lacks some of the characteristic strong flavor of the cheese made from sheep's or goats' milk.

The milk for American Roquefort cheese should be clean and fresh and should contain from 3.8 to 4 per cent of milk fat. Starter is added to the extent of 3 to 4 per cent. The milk is allowed to develop from 0.20 to 0.23 per cent of acidity. It is then set at 85 to 86°F. (29.44 to 30.00°C.). Coagulation is brought about by the addition of rennet, using from 3 to 4 ounces per 1,000 pounds of milk. After allowing the milk to stand from 1 to 1½ hours, the curd is cut with curd knives into cubes from ¾ to 1 inch square. A few minutes after cutting, the curd is removed from the whey to a draining rack where it is permitted to drain for 15 to 20 minutes. The curd is then placed in forms that are 6 inches high and 7⅜ inches in diameter. The forms are perforated with small holes ⅜ inch in diameter and ⅜ inch from center to center. As the curd is placed in the forms it is sprinkled with spores of *Penicillium roqueforti* previously grown on bread and dried. After placing the curd in the forms it is permitted to drain for 24 hours in a room held at 68 to 72°F. (20.00 to 22.22°C.) and at a relative humidity of 85 to 90 per cent. The forms are turned at frequent intervals during the first day. At the end of 24 hours the cheese is removed from the forms, placed on draining boards, and turned twice daily. At the end of 3 to 5 days the cheese is placed in a room at 48 to 50°F. (8.89 to 10.00°C.) and salted.

Salting is accomplished by rubbing salt on the cheese at the rate of 7.5 pounds to each 100 pounds of green cheese. At least three applications of salt are required. After salting, the cheese is pierced with needles. This permits free access of air to the interior of the cheese.

The cheese is held in a room at 48 to 50°F. (8.89 to 10.00°C.) and at a relative humidity of 95 per cent for about 3 months. At the University of Minnesota Experiment Station, large sand-stone caves are used for holding cheese during this period. At the end of this period the cheese is wrapped in tinfoil and placed

at 40 to 45°F. (4.44 to 7.22°C.) until the characteristic flavor develops, which requires 3 to 6 months. The ripened cheese is mottled with a blue-green mold which is especially luxuriant along the lines of the punctures made in the cheese. The flavor and aroma of the cheese are due principally to caproic, capric, and caprylic acids, or compounds formed from them, and which are liberated from the milk fat in the cheese by the action of mold enzymes.

Brick Cheese.—Brick cheese was originated in America. It probably got its name from its shape or because bricks are commonly used for weighting down the press during the process of pressing. The cheese resembles Swiss cheese in that it has a slight sweetish taste; however, the flavor is strong as compared with Swiss, resembling, to a certain degree, the flavor of Limburger cheese. The body of the cheese is rather elastic and often contains numerous small round holes or eyes.

The cheese is made from whole milk to which 0.10 to 0.25 per cent of starter is added. The milk is set at about 90°F. and rennet added at the rate of 2½ to 3½ ounces per 1000 pounds of milk. The curd is cut with cheese knives, as in the making of Cheddar cheese. It is then slowly cooked to 106 to 115°F. (41.11 to 46.11°C.) depending upon the acidity of the original milk. After cooking, the curd is placed in a rectangular box without a bottom and along the insides of which are perpendicular grooves which permit drainage. The cheese is pressed by covering with a wooden follower and placing bricks on the cheese for pressure. After remaining in the molds for about 24 hours, the cheese is removed and the surface rubbed with salt. Salt is applied in this manner for about 3 days in succession, the cheese being piled about three deep during this period. The cheeses are then ripened at a temperature of 60 to 65°F. (15.6 to 18.3°C.) for about 60 days.

The curing room should be maintained at a relative humidity of nearly 90 per cent. The ripening is brought about largely by the action of bacteria upon the constituents of the cheese.

SOFT CHEESE

Limburger Cheese.—Limburger cheese originated in Belgium, and was first marketed in the town of Limburg. A cheese of the same type is made in Germany and is known there under the name of "Backstein." Large quantities now are made in the states of

New York and Wisconsin. The cheese possesses a characteristic strong odor and taste, weighs about 2 pounds, and is marketed in packages about 6 by 6 by 3 inches.

The best Limburger cheese is made from whole milk; however, some manufactures make the cheese from skimmed milk or milk from which a part of the butter fat has been removed. The curd is set with sufficient rennet to bring about coagulation in about 40 minutes. A temperature of nearly 96°F. (35.6°C.) is used and no further heat is applied. After cutting, the curd is dipped into rectangular forms 28 inches long, 5.5 inches broad, and

FIG. 72.—A type of cheese, resembling Roquefort, is ripened in sandstone caves that occur along the banks of the Mississippi River at St. Paul, Minnesota. by the Dairy Division of the University of Minnesota. This variety of cheese is being made to a limited extent in Minnesota, Wisconsin, Iowa, and California.

8 inches deep. After being allowed to drain, the cheese is removed from the forms and salt rubbed daily over the surface until the cheese becomes slippery. The cheese is then placed in curing rooms held at a temperature of about 60°F. (15.6°C.). It requires about 2 months for the cheese to ripen.

The Limburger cheese is made from the highest quality of fresh milk. No starters are used. The ripening of this cheese takes place due to the activity of a number of proteolytic types of bacteria and enzymes naturally present in the milk and which work together under the conditions of storage and salting employed in its manufacture.

Camembert Cheese.—Camembert cheese originated in the northern part of France. The cheese is about 4½ inches in

diameter and about 1 inch thick. It is wrapped in tinfoil and placed in a small wooden box the same shape as the cheese. The cheese generally is covered with a rind consisting of dried cheese and mold. Its interior is soft, yellowish in color, creamy or almost fluid, depending upon the degree to which it is ripened. The flavor is somewhat similar to Limburger but not so strong.

Milk for Camembert cheese is set at 78 to 87°F. (25.6 to 30.6°C.) and sufficient rennet added to bring about a firm coagulation in from 2 to 5 hours. The curd is then placed in perforated tin forms or hoops which are set on rush mats where the cheese is allowed to drain. After about 18 hours the cheese is turned frequently for about 2 days. The cheese is then removed from the form and salted on the outside. The curing of Camembert cheese is very difficult. The curing rooms must be maintained at a temperature between 53 and 59°F. (11.7 to 15.0°C.) and at relatively high humidity.

In this country a regular *Streptococcus lactis* culture is used to provide the acidity to control fermentation. To obtain the characteristics of Camembert, a mold culture is added, sometimes to the milk, and sometimes sprinkled on the curd or with the salt. In this case, however, the mold is the *Penicillium camemberti* which differs somewhat from the Roquefort mold. The cheese is placed in the curing rooms which are kept at the proper temperature and with a high humidity. The curd gradually dries and the growth of the Camembert mold, and another mold, *Oospora lactis*, is held in check as it is not desirable to obtain a too rapid, vigorous, or luxuriant growth of these molds or of the various bacteria also developing within the cheese. A slime made up of the molds and some bacteria develops on the surface of the cheese. The mycelium from this mass of molds penetrates into the cheese. Enzymes from the mycelium attack the curd and break it down, starting from the outside and proceeding toward the center. Eventually, the characteristic appearance and flavor of Camembert are developed. From 15 to 20 days are required to bring about the desired changes in the casein. The cheese then is cured at a lower temperature and humidity for about 6 weeks when it is ready for the market.

Cottage Cheese.—The principal unripened soft cheese made in America is the common Cottage cheese. This type of cheese is generally made of skim milk. The milk for best results should be pasteurized. It is set at a temperature of 68 to 72°F. (20 to

22.2°C.) and approximately 5 per cent of good starter is added. After 8 to 12 hours the milk will coagulate and form a firm curd. The curd may be cut with curd knives as in the case of Cheddar cheese, after which it is cooked slowly to 98 to 110°F. (36.7 to 43.3°C.). The whey then is removed and the curd allowed to drain. In some factories the curd and whey are drawn into cheesecloth bags which are hung in a cool room where the whey is permitted to drain. If a starter flavor is not desired, the curd may be washed with cold water. The curd then is stirred and salted to taste. The quality of such cheese is greatly improved by the addition of cream in sufficient quantity to raise the fat content of the finished cheese to about 5 to 10 per cent. A yield of from 12 to 16 pounds per 100 pounds of milk can be secured in making Cottage cheese, depending on the amount of moisture the cheese contains. This cheese possesses rather poor keeping quality because of its high moisture content and the possibility that the undesirable types of microorganisms may gain an ascendancy and cause the rapid decomposition of the product with the accompanying disagreeable flavor and aroma. The keeping quality of the cheese is improved, however, by pasteurizing the milk previous to setting.

Cream Cheese.—A cheese common on American markets is known as "Cream cheese" and sometimes referred to as "Philadelphia Cream" cheese. This cheese has a mild, rich flavor and is used primarily as a spread for bread.

Cream cheese, as the name implies, is made from cream of varying percentages of fat. The cream is pasteurized and homogenized. The cream is thickened by the addition of rennet, placed in cloth, and allowed to drain. About 4 days are required for the cheese to drain. It is then salted, worked into a paste by mixing machines, and placed into packages of the desired size and shape.

Process Cheese—Cheese Spreads.—Process, pasteurized or Loaf cheese is reworked cheese made from one or more varieties, or cheese of the same variety but of varying stages of ripeness. For example, a very common loaf cheese on the market consists of a mixture of old and green Cheddar cheese. The cheeses are cut into small pieces, placed in vats, pasteurized, and homogenized. The liquid cheese which results is forced into forms of the shape desired and allowed to cool. The process also may consist simply of grinding Cheddar cheese of varying

degrees of ripeness into a paste with butter or other cheeses such as Neufchatel, Roquefort, Swiss, etc., depending on the flavor desired. Such cheese is often referred to as "Club cheese." So many combinations may be had, however, by mixing various cheeses, with or without the addition of cream, and by including many different materials for seasoning that the possible number of different cheeses becomes almost unlimited. In a general classification, however, it is best simply to refer to the group as Processed, Reworked or, as often termed on the market, Loaf Cheese, or Cheese Spreads.

CHAPTER XII

THE MANUFACTURE OF DAIRY PRODUCTS (*Continued*)

ICE CREAM

When ice cream was first made is not known. No reference is made to it in the literature of the ancients or in the Bible. According to several writers, water ices were introduced to Europe from Italy. From water ices probably developed recipes for frozen desserts which contained milk or cream. Men-

FIG. 73.—A modern ice-cream plant. Commercial ice cream is manufactured in such a plant and distributed to small retailers over a town or city. A plant of this size may manufacture from 300,000 to 500,000 gallons of ice cream yearly. (*Courtesy of Ives Ice Cream Company.*)

tion is made in French and English cookbooks, published between 1769 and 1776, of "butter ices or cream ices." The term, "ice cream," is found in an advertisement which appeared in the *New York Gazette* of May 19, 1777, by Philip Lenzi, who termed himself a "Confectioner from London," which reads as follows: "May be had almost every day, ice cream; likewise, ice for refreshing wines, etc."

The manufacture of butter and cheese developed in the home but ice cream and ices apparently were products of the exclusive

cafe and caterer. The method of making was long a guarded secret. The idea of manufacturing ice cream commercially and selling it wholesale was introduced by an American, Fussell, of Baltimore in 1851. Fussell later established factories in Washington D. C., Boston, and New York. Commercial ice cream is now manufactured in all the principal cities of America and in many of the cities abroad.

Though ice cream is made in the home, the amount so made has always been very small as compared with the quantities sold from the factory. Therefore, attention will be directed in the discussion to follow, primarily, to the manufacture of commercial ice cream.

Ice Cream Defined.—Ice cream is a variable product. That is to say, it may contain a variety of ingredients in addition to milk, cream, and sugar. Further, there was a time in the history of commercial ice cream when the manufacturer gave little attention to the composition of the finished product. Particularly was this true of the butter-fat content. Because ice cream varies so much in its composition, public officials found it advisable to set forth certain regulations pertaining to its composition. In 1906, the U. S. Department of Agriculture defined it as follows.

Ice cream is a frozen product made from cream and sugar with or without a natural flavoring and containing not less than 14 per cent of milk fat. Fruit and nut ice cream must contain not less than 12 per cent milk fat.

Following the lead of the U. S. Department of Agriculture most of the states passed laws governing the butter-fat content of ice cream. The ice-cream manufacturers were not in favor of a 14 per cent fat standard for ice cream but favored 8 per cent. As a result, the state laws in America governing the butter-fat content of ice cream vary the requirement from 8 to 14 per cent. Certain states have passed laws which govern, in addition to the butter-fat content, the milk solids-not-fat content of ice cream.

Classification of Ice Cream.—There is no definite classification of ice cream generally recognized. In formulating the state laws regarding this product the general conception of the classes is as follows:

A. Commercial Ice Cream

(1) Plain ice cream, containing a standard percentage of fat (milk solids-not-fat and gelatin are mentioned in some states) and flavored

with vanilla, coffee, mint, caramel, or maple (chocolate is included in some states).

(2) Fruit ice cream, containing from 1 to 2 per cent less butter fat than plain ice cream with a variable amount (3 to 8 per cent) of fresh or preserved fruits such as strawberries, raspberries, peaches, pineapples, apricots, raisins, etc.

(3) Nut ice cream, containing from 1 to 2 per cent less fat than plain ice cream, and varying amounts (1 to 5 per cent) of nuts and other added flavors. (Chocolate ice cream is classed as nut ice cream in some states.)

B. Special Ice Creams

In addition to the above may be grouped the following:

(1) Bisque. Usually a plain ice cream of a high percentage (16 to 20 per cent) of butter fat with added bread products or confections such as dried macaroons, sponge cake, and marshmallows. Additional flavoring may or may not be added.

(2) Parfait. An ice cream rich in fat (16 to 20 per cent) containing eggs with or without fruits or nuts and other flavors.

(3) Pudding. An ice cream of high fat content with eggs, nuts, and assorted fruits.

(4) Aufait. A brick ice cream of one or more layers with frozen fruit between.

In addition to the above may be classed ices which are frozen products made of water, sugar, and fruit juices and sherbets which are similar to ices but contain milk, skim milk, or a small quantity of plain ice-cream mix with added water.

Ingredients Used in Commercial Ice Cream.—It is impossible to state definitely the composition of commercial ice cream, as it depends upon the ingredients used by the manufacturer. The materials used and the formulæ adopted vary with the individual responsible, and as a result there is no standard composition. In all cases, however, commercial ice cream must contain butter fat, or the fat of milk, the minimum amount being specified by law in most states of the United States. A high-grade commercial ice cream will contain about 14 per cent butter fat. This means that milk and cream, or milk products, constitute the principal ingredients.

Commercial ice cream, being made principally from milk and cream, will contain in addition to butter fat, milk solids-not-fat, or serum solids. When it is intended to include all the solids contained in ice cream, the term "total solids" is used, which

includes the fat, the milk solids-not-fat, and all other solids added to the ice-cream mix from other sources. Sugar is included when the total composition of ice cream is discussed, because it makes up a large portion of the mixture.

In commercial ice cream a so-called "binder" or "stabilizer" is added in the form of gelatin. This tends to prevent the formation of water crystals. Flavoring extracts, chocolate, fruits, nuts, candies, and bakery products are added to ice cream for their flavoring effect. Summing up, therefore, the composition of ice cream is as follows: butter fat, milk solids-not-fat, or serum solids, sugar, binding and flavoring materials. The term "mix" is commonly used to designate the complete mixture of ingredients which when frozen is known as ice cream.

The Ingredients Used in the Manufacture of Ice Cream.—

Milk and milk products are the principal ingredients used in manufacturing ice cream. They are the source of milk fat and milk solids-not-fat and furnish approximately 60 per cent of the total solids of the ice-cream mix. The milk products commonly used in ice cream are cream, skim milk, butter, condensed and dried milks. Cream is used primarily because it is the best source from which to secure the milk fat in concentration for use in ice cream. When cream is not available, the butter fat may be secured from butter or butter oil, but, as a rule, the use of butter or butter oil in ice cream can be detected, and where an ice cream of the best quality is being manufactured, a high-grade cream is preferred.

Whole milk may be used in combination with cream, when used it generally is added to supply a portion of the fat and furnish the ice-cream mix with milk solids-not-fat or serum solids. The lower the percentage of fat in the cream used in the ice-cream mix, however, the less milk is required. For this reason, the manufacturer often purchases cream of a low fat content for use in ice cream. Since cream is usually purchased on the basis of its fat content, the practice of buying low-testing cream permits the ice-cream manufacturer to secure milk solids-not-fat at a relatively low cost. When cream must be shipped to the ice-cream plant over long distances, however, cream of a high test (40 per cent) is preferred. The increased cost of transportation to the ice-cream manufacturer of low-testing cream more than offsets the cost of milk solids-not-fat so gained. Furthermore, high-testing cream has the advantage of possessing better keeping

qualities than low-testing cream and requiring less space in storage.

Condensed and dried milks are used in ice cream to supply the mixture with milk solids-not-fat. Due to the fact that commercial ice cream is generally high in milk solids-not-fat, these constituents must be added to the mix in concentrated form. If the condensed or dried milk is made from whole milk, the butter-fat content of both must be taken into consideration in calculating the ice-cream mix.

Quality of Dairy Products for Ice Cream.—All dairy products used in the manufacture of ice cream should possess a clean, sweet flavor indicative of sanitary methods of production and handling. A high-grade ice cream cannot be made from poor quality raw products. A sour milk or cream never should be used in ice cream. Most off-flavors occurring in milk or milk products are intensified after freezing. In some instances they may be masked slightly by making a chocolate or caramel ice cream. Such a practice, however, should not be encouraged.

Sweeteners for Ice Cream.—The most common sweeteners used in commercial ice cream are cane and beet sugar. The amount of sugar used varies with the judgment of different manufacturers. It is generally recognized, however, that ice cream should contain at least 12 per cent sugar. The sugar content also affects the smoothness of the resulting ice cream and for this reason many manufacturers add as high as 17 or 18 per cent of cane sugar to the ice-cream mix. A very good ice cream results when 14 to 16 per cent of sugar is used.

Corn sugar, corn syrup, or maltose syrup and honey can be used to sweeten ice cream or as substitutes for a portion of the common sugar required. The practice of using these sweeteners is not considered practical or economical when cane or beet sugar can be purchased at normal prices.

Ice-cream Stabilizers.—By experience, the manufacturer of commercial ice cream has found it advantageous to add to ice cream some material which will tend to hold ice cream in shape after it has been served. Such products are known as "stabilizers" or "binders." Many products have been used, but gelatin has been found to be the most practical. Gelatin is known to the chemist as a colloidal substance. It has the property of absorbing large quantities of water in proportion to its own weight. Such a mixture of water and gelatin will form a jelly

when allowed to set. This property of gelatin is advantageous in the manufacture of ice cream as it will retard the formation of ice crystals during the freezing and hardening process. This results in an ice cream with a smoother body that will stand up better while it is being served.

Gelatin is not a cheap product and in no way cheapens the ice-cream mix. Public opinion was turned against the use of gelatin a number of years ago before the manufacturers of the product had given much consideration to its purity. Today, the gelatin used by the ice-cream manufacturer is identical with that used by the housewife and is a clean, wholesome product. It is a protein food which is readily digested.

Flavoring Materials.—The common flavoring extracts used in the manufacture of ice cream are vanilla, strawberry, lemon, and raspberry. A high-grade extract used in ice cream should result in a pleasing flavor. Some of the flavoring extracts on the market, however, result in undesirable and disagreeable flavors.

Other materials such as chocolate or cocoa, coffee, bakery and candy products, fruits, and nuts, are used in ice cream in quantities pleasing to the taste. Eggs are seldom used in commercial ice cream, but may be utilized in the manufacture of fancy ice creams and custards.

Preparation of the Ice-cream Mix.—The preparation of the ice-cream mix is a very important process in the modern ice-cream factory. At one time, the ice-cream mix was prepared by using a fixed formula. The common measure was the quart and gallon can. Cream and milk were used regardless of their fat content. No attention was given to the milk solids-not-fat which were placed in the mix when milk and cream were used. The result was an ice cream of irregular quality from day to day. Under such conditions it is impossible to apply business principles in a factory as the cost of the mix varies.

The modern ice-cream manufacturer is keen to make use of every fact developed by science. In the typical factory at present a technically trained dairy-products expert is usually employed. It is his duty to make a complete analysis of every product used, and to be responsible for maintaining a uniform composition from day to day. The important technical details are so generally known and understood that the procedure in the preparation of the commercial ice-cream mix can be set forth as typical for most ice-cream factories. These steps include the

following: (1) calculation of the proportion of each ingredient that is to go into the mix; (2) pasteurization of the mix; (3) homogenization of the mix; (4) aging of the mix. After the mix has passed through these steps, it is ready for the ice-cream freezer from which it passes to the hardening room.

Calculation of the Mix.—After the composition of the mix to be used has been decided upon, the next step is to calculate the

FIG. 74.—An ice-cream laboratory. The large ice-cream manufacturer makes a complete analysis of the milk products which enter into the ice-cream mix. The composition of the mix is carefully controlled. (Courtesy of Ives Ice Cream Company.)

amount of each ingredient which is to be used. This part of the work must be done with great care for two very important reasons. First, a satisfactory quality in the finished product is possible only when the proper proportion of constituents is used in the mix. In order to retain the favor of consumers, the ice cream should always taste the same and have the same physical properties; that is, it must have a uniform quality from day to day. The consumer selects other kinds of ice cream for variety but expects a certain type of product, for example, vanilla ice cream, always to have the same characteristics.

The second important reason for giving so much attention to the calculation and preparation of the mix pertains to the cost. If a standard fat content of 12 per cent is required it is highly

important to the manufacturer that the percentage of this expensive ingredient does not vary appreciably from the required standard. If through lack of proper control a fat percentage of 14 per cent were used, the additional cost might practically absorb all of the manufacturer's profits. If the fat percentage were inadvertently lower than the standard, not only would the quality of the product be lowered, but the manufacturer might be violating a city or state statute. The importance of this close control is more easily visualized by calculating the loss that 2 per cent extra fat in the mix would mean to a factory using 2,000,000 pounds of ice-cream mix yearly.

Technical Skill Necessary.—The difficulties encountered in standardizing the mix properly are such that most of the larger ice-cream manufacturers find it profitable to employ for the purpose a man who has had technical training in science and dairy technology. The difficulties to be overcome in preparing a mix of definite composition will be better realized when it is pointed out that the products to be used may include cream, whole milk, concentrated whole milk, skim milk, sugar, gelatin, and flavoring. Furthermore, the first three may vary in composition from day to day. With these ingredients at hand, the problem is to calculate a mixture that will contain a uniform percentage of fat, total solids, and sugar.

Procedure in Calculating a Mix.—It is clear that, first of all, an analysis of the products to be used must be made. For example; butter fat might be supplied from three sources: cream, milk, and concentrated whole milk; the milk solids-not-fat of the mix may be supplied by these same constituents and skim milk; sugar and gelatin also may be used. Almost any group of dairy products may be used as sources of fat and milk solids-not-fat. If the fat of the mix is secured from but one source, for example, cream, the problem is simplified. It is essential, however, in most instances that the milk solids-not-fat be secured from two or more sources.

A Problem in Preparing a Mix.—To illustrate briefly to the reader an ice-cream problem, let it be assumed that it is desired to make 100 pounds of mix to contain 14 per cent fat, 38 per cent total solids, 15 per cent sugar, and 0.5 per cent gelatin. It is necessary, first, to calculate the percentage of solids in the proposed mix which will be in the form of milk solids-not-fat. This figure is obtained by subtracting the total of the fat, sugar, and

gelatin (29.5 per cent) from the total solids (38 per cent), which gives 8.5 as the percentage of milk solids other than fat.

It will be assumed that analyses already made show that there is available to go into the mix: cream, containing 40 per cent fat and 45.5 per cent total solids; plain condensed whole milk, containing 11 per cent fat and 35 per cent total solids; and skim milk, containing 8.5 per cent total solids. There are several methods by which this problem may be calculated. The use of algebraic equations, however, gives the exact amount, while other methods are more of an approximation.

As the unit selected is 100 pounds of mix, it is clear that the amount of sugar and gelatin needed is the same as the desired percentage of these ingredients, that is, 15 pounds of sugar and 0.5 pound of gelatin.

To find the pounds of the other ingredients needed, algebraic equations are formed:

Let x = pounds of cream required in the mix.

y = pounds plain condensed whole milk.

z = pounds of skim milk required.

15 = pounds of sugar.

0.5 = pounds of gelatin.

It is clear the sum of these is 100. Other equations may be formed, one representing the fat, another the total solids. By this means three simultaneous equations are formed which involve the same unknowns, for example,

$$x + y + z + 15 + 0.5 = 100 \quad (1)$$

$$0.40x + 0.11y = 14 \quad (2)$$

$$0.455x + 0.35y + 0.085z + 15 + 0.5 = 38 \quad (3)$$

Of these, equation (1) represents the total mix. It is clear that the pounds of cream, concentrated whole milk, and skim milk required, together with the 15 pounds of sugar, and 0.5 of gelatin should total 100 pounds.

Equation (2) is the fat equation. Fat is supplied by the cream with a fat content of 40 per cent and the concentrated whole milk containing 11 per cent of fat. The mix is to contain 14 per cent.

The third equation represents the total solids. Solids are supplied by all ingredients. A fixed amount is to be supplied by the gelatin and sugar and the amount present in the other ingredients to be used is known. The cream contains 45.5 per

cent solids, the plain condensed milk 35 per cent, and the skim milk 8.5 per cent. The equation will be:

$$0.455x \text{ (total solids to be supplied in cream)} + 0.35y \text{ (total solids from concentrated milk)} + 0.085z \text{ (total solids from skim milk)} + 15 \text{ (pounds of sugar)} + 0.5 \text{ pound of gelatin} = 38.$$

By solving these three equations, it is found that,

$$x = 31.01, y, 14.51 \text{ and } z, 38.98.$$

These figures are the pounds of the cream, the concentrated milk, and skim milk required, together with the sugar and gelatin to make 100 pounds of the mix with the composition as specified. The proof of the problem is given in the following statement:

Ingredients	Pounds used	Pounds, fat	Pounds, total solids	Pounds, sugar	Pounds, gelatin
Cream.....	31.01	12.40	14.11	0	0
Plain condensed milk...	14.51	1.60	5.08	0	0
Skim milk.....	38.98	0	3.31	0	0
Sugar.....	15.00	0	15.00	15	0
Gelatin.....	0.50	0	0.50	0	0.5
Total.....	100	14	38	15	0.5

In commercial practice, the calculation of the mix is often simplified by using milk products of uniform composition. Flavoring is added to the mix at the freezer and generally is not included in the calculation.

Pasteurization of the Mix.—The ingredients which are to make up the mix are placed in a mixing vat in preparation for pasteurization. As a general rule, the viscous fluids are placed in the vat first, followed by the less viscous fluids. Sugar and gelatin are added last. After all ingredients going into the mix are in the vat, the entire mixture is heated to a temperature of 145 to 155°F. (62.8–68.3°C.), and held from 25 to 30 minutes. The mix then is rendered homogeneous by passing through a machine such as the homogenizer or viscolizer.

Homogenizing the Mix.—The homogenizer consists of a series of pumps which draw the mix into small chambers from which it is forced out, under considerable pressure, through a small needle valve. The pressure ranges from 2,000 to 4,000 pounds per square inch. The action of these machines is primarily on

the fat of the mix. The globules are reduced many times in size. In fact, cream or ice-cream mix is very difficult to churn after homogenizing. Ice cream made from a homogenized mix appears slightly richer in fat, and is much smoother and more velvety than if unhomogenized. Immediately after homogenizing, the mix is cooled to a temperature of 40°F. (4.44°C.) or lower.

Aging the Mix.—The mix, after being homogenized and cooled, is aged for a period of 4 to 24 hours. During the summer

FIG. 75.—View of the freezing room in an ice-cream factory. The operator is in the act of drawing ice cream from a batch freezer. To the right of the operator are shown two continuous freezers. (Courtesy of Crescent Creamery Company, St. Paul.)

months the shorter period is used because of the higher acidity which generally is, naturally, present in milk and cream and due to need of rushing the mix to the final state of ice cream to meet the demand. Aging results in a mix taking on an increased viscosity and a glossy, smooth appearance. It further assists in improving the smoothness of the finished product. A certain amount of viscosity is essential, also, in securing an overrun in the manufacture of ice cream. A mix should not have too much viscosity, however, as under such circumstances difficulty is

experienced in securing the swell or overrun. The viscosity of the mix is increased by homogenizing and by aging. It is impossible, however, to accomplish the same results with the homogenizer that are obtained by aging, as the one is a mechanical action, and the other a chemical or colloidal action.

Freezing the Mix.—There are two general types of ice-cream freezers available on the market for use in freezing ice cream, namely, the “batch” and the “continuous” freezers. The batch freezer is the more commonly used, while the continuous type is adaptable for use in factories producing a relatively large volume of ice cream. The batch freezers are made in capacities ranging from 20 to 160 quarts, while the continuous freezer—made as the name implies to freeze continuously—ranges in capacities from 75 to several hundreds of gallons of ice cream per hour. The batch freezer consists of a double-walled cylinder which is fixed firmly on a base. Inside the cylinder are dashers which scrape the frozen material from the walls and keep the cream thoroughly mixed. They also serve to beat air into the freezing mixture. Flavoring extracts, as fruits or nuts, if used, are generally added during the process of freezing.

Freezing of the ice-cream mixture is accomplished by circulating cold brine or by allowing ammonia to expand directly around the walls of the cylinder surrounding the mix. As the mixture freezes, it thickens. When the ice cream in the freezer thickens to a consistency of a semisolid, the brine or ammonia is shut off and allowed to by-pass through a pipe line along the side of the freezer. By allowing the dashers to keep in motion, air is whipped into the semifrozen mixture, causing it to swell in volume. When the desired swell, or overrun, as the ice-cream manufacturer terms the increase in volume, is secured, the ice cream is allowed to flow from the freezer into containers in which the ice cream is sold, or into containers from which it can be quickly removed before placing in a final package. It is then placed in a cold room, commonly referred to as the “hardening room,” which is maintained at a temperature of 0°F. (−17.8°C.), or lower.

The continuous freezer is more complicated than the batch freezer. It is designed to freeze a small stream of the ice-cream mix as it flows through the machine. The freezing is continuous. Swell or overrun is regulated by incorporating air into the mix by means of an air pump. Fruits, etc., are added to the frozen mix

as it flows from the machine. The mix is frozen to the desired state in a few seconds after entering the machine.

Freezing is completed in the hardening room, as indicated above. The rate at which the ice cream is frozen in the freezer and in the hardening room has a direct bearing on the fineness of

FIG. 76.—Sectional view of a commercial ice-cream freezer. The view shows the cylinder surrounded with insulation material, the wall between the outer cylinder, and the inner cylinder through which a cold brine passes, the dasher which keeps the mix agitated and whips air into the partially frozen mixture. After freezing to a semisolid mass the mix is allowed to flow out of the gate at the right end. (Courtesy of the Creamery Package Manufacturing Company.)

the texture of the finished ice cream. The faster the freezing the smaller the ice crystals formed and the smoother the texture of ice cream. In recent years there has been a tendency toward quick freezing. This is accomplished in the hardening room by circulation of the air at a high velocity. Not only does such a practice result in quick freezing, but it is a more economical procedure.

Bulk Ice Cream.—As indicated above, the ice cream, usually, is allowed to flow from the freezer into the package in which it is sold. This procedure is used primarily in the case of bulk ice cream or of ice cream placed in cans containing 5 or 10 gallons. The retail distributor is accustomed to purchasing ice cream in such containers. In addition to the 5- and 10-gallon containers, the factory prepares a fairly large amount of bulk ice cream in containers which hold as little as 1 quart.

Brick Ice Cream.—Brick ice cream is commonly prepared by drawing the semifrozen ice cream from the freezer into tin trays which hold from 1 to 8 quarts each. After the ice cream has been allowed to complete the freezing in the hardening room, it is removed from the tin trays. Individual quarts are then wrapped in parchment paper and generally placed in heavy waxed paper cartons. The ice cream removed from trays holding more than 1 quart is cut by hand or machine into 1- or 2-quart sizes which are then placed in cartons.

Preparation of Brick Ice Cream.—Brick ice cream of two or more layers is prepared by filling the trays at the freezer with varying flavors of different colors. If but one freezer is operated in the factory, it is necessary to freeze one flavor, fill the trays to the point desired, and place in the hardening room. When the freezer is emptied of the first flavor and the second is ready to be removed, the filling of the trays is then completed. If three layers are desired, a third freezing must be made. Larger factories are able to complete this operation very quickly, as they generally operate several freezers at one time. The trays are filled to a given point from one freezer of one flavor and to another point from another freezer of another flavor, until the tray is filled with two or more layers of ice cream.

Individual Forms and Packages.—Ice cream is often made into shapes to represent various objects, such as flowers, fruits, melons, lodge insignia, etc. To prepare these individual forms, hollow molds are used. An individual mold consists of sufficient ice cream for one serving. Bulk ice cream is softened and the mold filled. It is then placed in a cold brine for a few minutes to reharden the softened ice cream. The mold is then dipped into cool water and the ice cream removed. The individual mold of ice cream is then placed in the hardening room and allowed to become thoroughly frozen for a second time. Ice cream of one solid color may be used, but if varying shades are desired on the

finished object, this is done after the individual mold has been rehardened. In addition to the individual forms, ice cream is

FIG. 77.—A birthday cake of ice cream. The cake consists of two or more layers of ice cream, and sponge cake or meringue covered with sweetened whipped cream worked in fancy decorations.

FIG. 78.—Individual forms of ice cream. Individual forms of all shapes may be made of ice cream. A plate of fruit forms is shown in the illustration.

also placed in small cups which hold sufficient for one serving and in which it can be sold at public places.

Following the plan mentioned in connection with the individual forms, ice cream can be prepared in any shape to suit a given

occasion. Not only individual forms are prepared in this manner, but forms of sufficient size to serve a number of people.

Quality of Ice Cream.—Ice cream is not graded on the market as it is sold by the manufacturer directly to the retailer or consumer. The qualities that constitute a good ice cream are left more or less to the judgment of the individual manufacturer and his ability to judge the preference of the public. In general, it is conceded that a high-quality ice cream should have a rich, creamy, sweet taste, be smooth of body, and close-textured. The richness of ice cream is influenced primarily by the fat content. If ice cream contains below 10 per cent of fat, it lacks richness. If too much butter fat is used, it will be too rich. An individual cannot eat a very large serving of ice cream when it contains much more than 14 per cent of butter fat. Because of this fact, commercial ice cream seldom contains more than 14 per cent of fat, and if the laws within the state in which it is sold will permit, a slightly lower fat content is to be preferred. As previously indicated, ice cream containing about 14 per cent of butter fat results in an excellent commercial product. Some fancy ice cream may contain as high as 18 to 20 per cent of fat.

The sugar, gelatin, and milk solids-not-fat in ice cream contribute to its quality and palatability. The sugar content should not be below 12 per cent. The general public prefers an ice cream containing 16 to 18 per cent of sugar. For several reasons, it is not practical for the commercial ice cream to contain as much as 16 to 18 per cent of sugar. A good quality of commercial ice cream contains from 14 to 15 per cent. The milk solids-not-fat will range from 9 to 11 per cent in a high-quality ice cream, the gelatin approximately 0.5 per cent, and the total solids content may range from 36 to 38 per cent. Eggs are sometimes used commercially, and contribute a certain richness and smoothness to the finished ice cream.

In addition to the influence of the constituents on the quality of an ice cream, the quality of the ingredients used in the mix, and the method of caring for the mix through the various processes have a direct bearing on the quality of the finished product.

Ice-cream Defects.—The defects in ice cream commonly referred to are those of flavor, body and texture, and color. The flavor of ice cream is largely due to the flavor imparted by the ingredients used. Milk and milk products must be free from off-flavors. Off-flavors in milk or cream may become intensified in

ice cream. Particularly is this true when ice cream of delicate flavors such as vanilla, peach, pineapple, etc., is made. Such off-flavors as metallic, old cream, rancid, cooked, and bitter may be experienced in ice cream, due to the use of milk or milk products in which these flavors occur.

Other flavor defects are those due to using too much or too little of a given flavor. If ice cream contains too much vanilla, for example, the flavor imparted may be objectionable. If too little vanilla is used, there may be a lack of flavor. Flavor defects also may be due to the use of too large or too small an amount of the ingredients that go into the mix. Butter fat and sugar are examples of ingredients that may influence the flavor, one affecting the richness and the other the sweetness of the finished product.

Body and Texture Defects.—The body and the texture of ice cream are commonly referred to as a single quality. Body refers to the whole structure and is largely influenced by the composition of the mix, while texture has to do with the makeup of the individual particles that form the entire body. To illustrate, two pieces of cloth may be made of the same material and be alike in every way so far as composition or the material of which they are made is concerned. They may differ, however, in that one is more closely woven than the other, or in the fineness of the threads used in their construction. The common defects of body and texture in ice cream are not only due to the material but to the processes used in its manufacture. Although it is difficult to describe accurately the ideal body and texture desired in ice cream, there are a number of defects which are generally recognized and detected. Such defects may be listed as follows: soggy, gummy or sticky, weak, coarse, fluffy, watery, crumbly, and icy. In addition, ice cream may become sandy, a defect which is due to the crystallization of the milk sugar of the mix and which when eaten, grits on the teeth like sand. Buttery body and texture is a term used when it is desired to convey the idea that there are particles of butter in the finished ice cream.

Color Defects.—Ice cream should possess a pleasing color. If its color is too high or if it lacks color, it is objectionable. When ice cream is colored to represent the shades of various fruits, the color should be "natural." In addition, the color should be evenly distributed.

Distribution of Ice Cream.—To ship ice cream, it must be packed in ice and salt or shipped in insulated containers which retard the melting of the frozen product. Solid carbon dioxide is used as a substitute for ice in a few localities in America. It is not practical for a manufacturer of ice cream to distribute his product over a large territory. Milk, cream, butter, cheese, condensed and dried milk can be shipped over long distances to the market. Ice cream must be held at very low temperatures in transit. Further, ice cream, together with the package in which it must be packed, is too bulky to ship or transport over long distances. It is, therefore, more economical to ship the products of which ice cream is made to a point from which the finished ice cream can be easily distributed. For this reason, centers of large population are sought by manufacturers of ice cream in contrast to the location of other dairy manufacturing enterprises in the milk-producing territory.

Ice-cream Making in the Home.—Ice cream is easily made in the home. Recipes for small quantities of finished ice cream may be found in most reliable cookbooks. The home recipes differ materially, from the formulæ used commercially, particularly in the use of starch, so called "Ice-cream powders," and arrowroot flour. Eggs are generally included in the home recipe, but are not so common in commercial ice cream. Dry egg yolk is the more common form in which eggs reach commercial ice cream. More modern cookbooks recommend the making of ice cream which is more like modern commercial ice cream. Such recipes include dried or condensed milk and gelatin in the ice-cream mix, together with milk, cream, and sugar.

Too frequently, in the home it is the practice to prepare the ice-cream mix and freeze immediately. Such a procedure results in a coarse, grainy ice cream. To overcome this defect of home-made ice cream, the mix should be aged for 24 to 48 hours at a low temperature. This procedure is not always possible in the home, nor is it convenient. It is therefore advisable in making ice cream in the home to use a recipe which includes eggs, and to prepare a custard. The custard is heated in a double boiler to a point at which the mixture starts to thicken, after which it is cooled. The mixture is agitated during the heating and cooling.

To freeze ice cream in the home, the small hand freezer is used. The can in which the cream is frozen is filled about half-full with the ice-cream mix. This permits the incorporation of

air or the swelling of the mix during the freezing process. A mixture of cracked ice and coarse salt, consisting of about 1 part of salt to 5 or 6 of ice, should then be placed around the can. Cool water should then be poured over the ice and salt and allowed to come to a point well above the point at which the ice-cream mix comes in the freezer can.

The freezing process should be slow in the beginning and until the mixture starts to thicken. This will require 6 to 8 minutes. The freezer should then be turned rapidly until the freezing is completed. The slow freezing is intended to cool the ice-cream mixture to a point near its freezing point, while the rapid freezing completes the cooling process and whips air into the mixture. If possible, the freezing should stop when the frozen cream can be readily removed from the dasher with a knife or spoon. The ice cream is then packed in ice and salt and allowed to complete freezing before being consumed. This should require about 1 hour.

Microbiology of Ice Cream.—The microorganisms that may be present in ice cream and related frozen delicacies are of importance mainly from the standpoint of health or as criteria of the quality of the ingredients and methods of handling within the factory. Inasmuch as these frozen products are stored at temperatures much too low to permit the development of microorganisms, their deterioration is not due to microbiological agencies.

The numbers of bacteria which are present in ice cream will depend very largely upon the numbers in the raw materials, especially milk, cream, condensed or dried milk, and the extent of contamination from various pieces of equipment with which the product comes in contact. At times, a poor grade of gelatin or unsalted butter may contribute significant numbers of organisms. Water, sugar, flavoring extracts, fruits, nuts, chocolate, etc., seldom add any appreciable numbers.

Number of Bacteria in Ice Cream.—The pasteurization of the complete mixture of the principal ingredients of ice cream, including the milk products used, sugar, and gelatin, will reduce decidedly the numbers of microorganisms. If high-grade flavoring, fruits, etc., are added, and if the equipment through which the product passes is thoroughly sterilized, it is possible to obtain an ice cream with a reasonably low count. In fact, it is not at all difficult to manufacture ice cream under commercial conditions with a count below 100,000 bacteria per milliliter.

The homogenizing process tends to cause an apparent increase in count due to the breaking up of clumps of bacteria, even when the apparatus is sterile. This is much the same sort of phenomenon as described under the process of clarification. A similar increase in count may occur in the freezer. It must be borne in mind, however, that these increases are apparent rather than real, providing the appliances are not contributing bacteria. The change in count must not be confused with changes in actual numbers.

When the ice-cream mix is aged at temperatures below 40°F. (4.4°C.) before freezing, no appreciable increase in numbers is noted unless it is allowed to remain too long at temperatures above 32°F. (0°C.) After the product is frozen, transferred to the hardening room, and maintained at temperatures below 0°F. (-17.8°C.), no growth of bacteria is to be expected. If the ice cream is allowed to melt and remain at temperatures above the freezing point, growth may be resumed; but this seldom occurs under practical conditions.

Importance of Bacteria in Ice Cream.—Ice cream should be made from high-grade raw materials and be handled as carefully as any dairy product, even though low temperatures protect it against deterioration in storage.

The principal concern which the ice-cream industry has in microorganisms is from the standpoint of health. It is possible that the ingredients or the finished product may be infected with disease-producing bacteria which may not be affected adversely by the low temperatures, but remain capable of producing disease among the consumers of ice cream. Pasteurization of the ice-cream mix, sterilization of equipment, and supervision of the health of employees will eliminate the dangers to a great extent.

CHAPTER XIII

THE MANUFACTURE OF DAIRY PRODUCTS (*Continued*)

CONDENSED MILK, DRY MILK, MILK BY-PRODUCTS

CONDENSED MILK

The manufacture of condensed milk, or milk from which a portion of the water is removed, is of comparatively recent origin. This method of preserving milk was introduced on a commercially successful scale by Gail Borden, who was granted a patent on the process in 1856, in the United States and England.

FIG. 79.—A modern condensing and milk-drying plant. This organization is equipped to receive whole milk. The milk is separated and the cream shipped to an eastern market. The skim milk is condensed in which form it may be sold or dried by either the spray or drum process. (*Courtesy of Cameron Creamery Company.*)

The original patent included the concentration of milk by evaporation under vacuum without the addition of sugar or other foreign material. It appears, however, that the first milk manufactured by Borden for sale contained added sugar. Shortly afterwards (1858) Borden offered for sale in New York City and Brooklyn condensed milk at 25 cents per quart.

The first condensed-milk plant was established by Borden in 1856 at Wolcottville, Conn. This factory was in operation

only for a short time. In 1857, Borden, and those with whom he had become associated, established a factory at Burrville, Conn., about 5 miles distance from the first factory. This second venture failed, but in February, 1858, Borden became associated with Jeremiah Milbank, in a third venture at Wassaic, N. Y. This company was known as the New York Condensed Milk Company and later was succeeded by Borden's Condensed Milk Company.

Shortly after the establishment of the New York Condensed Milk Company, a factory was established at Cham, Lake Zug, Switzerland, under the direction of George H. Page. This company prospered in Europe and later established factories in New York, Illinois, and Wisconsin. By the end of the nineteenth century, the industry had spread to various other sections of Europe and America.

During the early days of the industry, condensed milk was sold to the consumer in much the same manner as market milk. When condensed milk was placed in hermetically sealed cans, sugar was added to insure its preservation. In 1884, John B. Meyenberg was granted a patent for the preservation of condensed milk which was based on the sterilization of milk by heat. This invention made possible the placing of unsweetened condensed milk in hermetically sealed cans which became known as "evaporated milk." The first factory manufacturing evaporated milk was known as the Helvetia Milk Condensing Company, located at Highland, Ill.

Classification of Condensed Milk.—Condensed milks as found on the market may be divided into two divisions: sweetened condensed, and unsweetened condensed milk. Either may be made from whole milk or skim milk. When made from skim milk, the words "skim milk" are added to the label—for example, "sweetened condensed skim milk." Sweetened condensed milk appears on the shelf of the grocer in hermetically sealed cans of various sizes. For commercial use it is placed in gallon cans, or sometimes in larger units. The canned milk packed in boxes is known among dealers and manufacturers as "case goods." The term "bulk sweetened condensed milk" is applied to sweetened condensed milk sold in barrels weighing from 300 to 700 pounds, gross.

Unsweetened condensed milk, as the term implies, contains no added sugar. It is sold under several names, according to the

treatment received. Unsweetened condensed milk sold in hermetically sealed cans is called "evaporated milk," to differentiate it from sweetened condensed milk. If unsweetened condensed milk is sold in bulk, it is called "plain condensed" or "unsweetened condensed in bulk." The term, "concentrated milk," is used to designate this type of milk in some instances. Plain condensed is not sold in barrels, but generally in 10-gallon cans. Smaller sized milk cans may be used in some instances. "Superheated" is a term applied to unsweetened condensed milk which has been heated to a high temperature (185 to 195°F. (85 to 90.6°C.)) after condensing. Superheated condensed milk is sold only in bulk. The following outline is intended to assist the reader in clarifying the above statements.

CONDENSED MILKS

A. Sweetened Condensed Milk:

- (a) Sold in cans hermetically sealed, various sizes up to 1 gallon
Trade name, *Condensed milk (sweetened)*
- (b) Sold in bulk, in 5-, 8-, and 10-gallon cans and in barrels
Trade name, *Sweetened condensed (whole or skim) milk*

B. Unsweetened Condensed Milk:

- (a) Sold in hermetically sealed cans, various sizes up to 1 gallon
Trade name, *Evaporated (whole or skim) milk*
- (b) Sold in bulk in 5-, 8-, or 10-gallon cans
Trade names, *Plain condensed (whole or skim) milk; Superheated*
(See descriptive paragraph.)

Composition of Condensed Milk.—In recent years, manufacturers of dairy products have practiced rather careful control of the products placed on the market. This is especially true of the condensed-milk industry. The composition of practically every lot sold is known and taken into account in a wholesale transaction. The composition of condensed milk is expressed in terms of (1) fat percentage, (2) total milk solids, (3) total solids, and (4) sugar (if added during the condensing process). The composition of the unsweetened is expressed in the first three terms; for the sweetened, the sugar percentage is also given.

Bulk sweetened condensed skim milk is sold on the market with a guaranteed minimum of 24 per cent total milk solids. Bulk sweetened, condensed whole milk is generally sold to contain a minimum of 28 per cent total milk solids and 8.0 per cent butter fat. The sugar content of these milks usually ranges from

40 to 45 per cent. Plain condensed and superheated condensed skim milk and whole milk are generally sold to contain the same amount of milk solids as sweetened condensed milks.

The percentage of butter fat and total milk solids in condensed milks is fixed by federal and state laws. According to the federal law, evaporated whole milk must contain not less than 7.8 per cent of milk fat and not less than 25.5 total milk solids, provided that the sum of the percentage of milk fat and total milk solids be not less than 33.7 per cent. Sweetened condensed whole milk must contain not less than 8 per cent milk fat and not less than 28 per cent total milk solids. The federal law requires evaporated and sweetened condensed skim milk to contain not less than 20 and 24 per cent total milk solids respectively. As a general rule, the manufacturers of these condensed milks adhere very closely to requirements as set forth by the federal laws.

The composition of evaporated and sweetened condensed milks is presented in more detail in the following statement:¹

	Water, per cent	Pro- tein, per cent	Butter fat, per cent	Lac- tose, per cent	Ash, per cent	Su- crose, per cent
Evaporated whole milk.	73.40	6.54	8.24	9.93	1.54	
Evaporated skim milk..	71.05	11.16	0.45	14.94	2.40	
Sweetened condensed whole milk.....	26.75	7.85	8.99	12.94	1.77	40.59
Sweetened condensed skim milk.....	28.74	9.14	1.01	18.18	2.05	40.88

Properties of Condensed Milks.—The chief difference between the properties of condensed milk and those of the milk from which it is made is found in the physical properties. This is observed, primarily, in the increased viscosity of the condensed milks. The sugar added to sweetened condensed milk increases the consistency of this type to a thick syrup-like mass. The concentration of the milk solids and the influence of the heat used in condensing in the presence of a slightly increased acid, due

¹ "Fundamentals of Dairy Science," 2d edition, Reinhold Publishing Corp., New York. Table by Wright, Research Laboratories, Bureau of Dairy Industry, Washington, D. C.

to concentration, is responsible for the increase in viscosity in unsweetened condensed milk.

Superheated condensed milk is extremely viscous due to the partial coagulation or jelling of the casein of milk, as a result of having been subjected to relatively high temperatures after condensing. In the manufacture of evaporated milk, sterilization is accomplished by subjecting the condensed milk to high temperatures under pressure. The increase in the viscosity in evaporated milk not only is attributed to the increase in the concentration of the milk constituents but to the hydrophilic condition of the casein which is even more pronounced than in the other unsweetened condensed milks. Evaporated milk is, therefore, subjected to vigorous shaking after sterilization in order to break the curd into a smooth, uniform mass. There may be a slight alteration in the sterilized evaporated milk that may be observed by the slight brownish discoloration and by taste. Due to the fact that evaporated milk is passed through an homogenizer before being placed in cans, the butter-fat globules are many times smaller than those present in normal milk and no cream appears on standing.

Method of Condensing Milk.—Milk boils at a temperature slightly above 212°F. (100°C.) at ordinary atmospheric pressure. Milk, to be condensed, must be boiled, but to use a temperature of 212°F. (100°C.) would be injurious to the finished product. Condensing of milk, therefore, is conducted in a partial vacuum. By placing the milk under conditions of reduced pressure it boils at lower temperatures, according to the well-known principles of physics. On a mountain 10,000 feet high, water boils at a temperature of 193°F. (89.4°C.), which explains the difficulty experienced in cooking meats or in boiling an egg so that it becomes hard at high altitudes. By placing milk under 25 inches of vacuum, as is done in condensing, its boiling point is reduced from a point slightly above 212°F. (100°C.) to about 130° to 145°F. (54.4 to 62.78°C.). The milk then can be boiled vigorously and by providing means for causing the milk to spray in a fine mist and for carrying off the vapors rapidly, a large percentage of the water of milk can be removed quickly. The process is known as “condensing,” and is carried on in various types of condensers and evaporators. The principal machine used for the purpose is known as the “vacuum pan.”

The Vacuum Pan.—The vacuum pan is constructed of copper, steel, or enameled steel. It consists of a cylindrical retort from 3 to 7 feet in diameter, which is placed in a perpendicular position. The bottom of the retort is double walled, slightly concave, and known as the "jacket." Live steam enters this point of the jacket and contributes a portion of the heat required to raise

FIG. 80.—Inside view of a milk-condensing plant. The illustration pictures the installation of the vacuum pan. Note the size of the three pans shown. They are six feet in diameter. (*Courtesy of C. E. Rogers Co.*)

the temperature of the milk to the point at which it boils in the pan. On the inside of the pan, above the jacket, are placed several coils through which live steam passes during the condensing process. Above the coils is the main body of the pan in which the boiling milk rises and sprays before dropping back toward the jacket to repeat the process. A glass peephole is set in the pan at this point to permit the operator to observe the milk during condensing. A manhole also is set at this point to permit a man to enter the pan to clean it.

At the top of the pan is located the dome in which is placed the condenser. The condenser is constructed so that the vapors of the boiling milk are drawn into a trough into which cold water is allowed to spray, thus causing the vapors to condense. From the condenser, the water passes out of the pan to the sewer. A vacuum pump connected with the pan maintains a vacuum of about 25 inches when the milk is at a temperature of about 135 to 140°F. (57.2 to 60°C.).

The Process of Condensing in a Vacuum Pan.—Milk intended for condensing is placed in a tank, commonly termed the “hot well,” where it is heated to a temperature of 145°F. (62.78°C.) to 230°F. (110°C.); (varying temperatures are used at the hot well in making the various types of condensed milk, with 167 to 185°F. (75 to 85°C.) best). The pan, generally, is heated by permitting steam to enter the pan through a pipe line provided for the purpose. About 25 inches of vacuum are drawn on the pan and the water started through the condenser. Milk enters the side of the pan through a pipe line leading from the hot well to the pan. By means of the vacuum, the milk is sucked into the pan. When the jacket is covered with milk, the steam is turned into this section. The steam is turned into the coils as they are covered with milk. The heat currents entering the milk from the bottom and sides cause it to boil vigorously, and to acquire a definite course upward and towards the center and then downward. The vigorous boiling, together with the cross-currents of heat met within the pan, causes the milk to be thrown in a spray as it goes upward, thus increasing materially the rate at which the water evaporates from the milk.

A valve connection on a pipe line entering the bottom of the pan permits the drawing off of the finished condensed milk. The condensed milk is not removed from the pan, however, until the proper concentration is reached. This is determined from the specific gravity of the product. In practice, an instrument known as the Baumé hydrometer is used. By making frequent chemical analyses of condensed milk and observations of the Baumé reading at definite temperatures, it is possible to determine the exact point at which to withdraw the condensed milk from the vacuum pan to secure a finished product of a definite composition.

Standardization of Condensed Milk.—The condensed-milk manufacturer is particularly careful that the finished product

have a definite composition. Not only is close attention given to the butter-fat content, but the milk solids-not-fat are checked closely by chemical analysis. The same may be said of the

FIG. 81.—Milk condensing equipment. A diagrammatic view is shown of a condensing or vacuum pan. Note how the milk is drawn from the hot well into the pan, and the manner in which the milk boils after reaching the pan. The water vaporizes from the milk and moves toward the top where it meets a spray of water, which condenses the vapor, after which it is drawn out through the vacuum pump and into the sewer. The finished condensed milk is drawn from the bottom of the pan into the drop tank. (Courtesy of Mojonnier Brothers.)

sugar content of sweetened condensed milk. It is not unusual for a condensary to handle 100,000 pounds of milk daily. It is highly important, therefore, that the composition of the product be closely checked.

Milk for condensing is analyzed for butter fat and total solids. The ratio of fat to solids-not-fat is calculated. A definite amount of fat and milk solids-not-fat is desired in the finished condensed milk. If the normal milk is too high in butter fat or too high in milk solids-not-fat, the ratio of these two constituents to one another can be adjusted either by the addition of butter fat or by the addition of milk solids-not-fat. Sweet cream or sweet-cream butter is used to raise the fat in proper ratio and skim milk or dried skim milk to adjust the milk solids-not-fat. There are times when the removal of cream is essential in the manufacture of condensed milk of the proper composition. Particularly is this true when large quantities of milk of the Channel Islands breeds is received at the condensary.

After the condensing process is completed, the condensed milk is analyzed and, if found to deviate from the standard desired by the factory, the composition is adjusted by the addition of the necessary ingredients. In the making of sweetened condensed milks, extreme care must be taken to standardize the normal milk at the hot well, as it is not possible to restandardize this type of milk after condensing because of the methods necessarily employed in handling the finished product.

Cooling Condensed Milks.—After condensing reaches the proper point, the product is cooled. The system used varies materially in the case of sweetened and unsweetened condensed milk. Unsweetened condensed milk may be cooled in coil vats, or over surface coolers. Sweetened condensed milk must be cooled quickly and with some agitation. If agitation is used it must be slow, and conducted in such a manner as to prevent the incorporation of air in the finished condensed milk. Due to the high lactose content of sweetened condensed milk and the danger of the sugar crystallizing from the condensing, extreme care must be taken.

After condensing and cooling, the condensed milk is placed in the packages in which it is marketed. Evaporated milk is homogenized, cooled, placed in cans and sterilized. After sterilization, the canned milk is placed in shaking machines to break the coagulated casein. The finished evaporated milk is generally held for a period at the factory to permit any defects to develop which may be due to bacterial fermentation or faulty methods of handling the product.

Other Types of Vacuum Pans.—In addition to the type of vacuum pan previously described, there are on the market others which may be grouped under the term “rapid circulating vacuum pans.” These pans have neither jacket nor steam-heating coils, but the lower section of the pan consists of a steam chest in which are placed a number of straight tubes. Milk enters the tubes under vacuum and, in boiling, there is thrown from the tubes into the body of the pan a spray of hot milk. The vapors are removed by means of a condenser somewhat similar to that used in the other type of vacuum pan. The milk returns to the tubes in a steam chest by means of another route and the process continues until the milk is concentrated to the proper point.

Uses of Condensed Milks.—Unsweetened condensed milk can be used in the home in cooking for any purpose for which ordinary milk is used. This product is sold under the name of evaporated milk or unsweetened sterilized milk, and marketed in cans of various sizes. Sweetened condensed milk is used in cooking in the home in cases when the added sugar contained in the condensed milk does not interfere. A large number of recipes have been prepared for home cooking, using both evaporated and sweetened condensed milk. Condensed milk, especially condensed skim milk, is used in large quantities by bakers, and candy and ice-cream manufacturers. The quantity used for these purposes far exceeds that used in the home.

Defects in Condensed Milks.—The manufacturer of condensed milks must continually guard against a number of defects which may occur in the finished product. Though there are some defects common to both unsweetened and sweetened condensed milk, there are many other defects which are characteristic of but one or the other.

The most serious defects of unsweetened condensed milk are those which occur in the canned or evaporated milk. These defects are largely due to improper sterilization or leaky cans. Bacterial fermentations are responsible for such defects as sour or curdled evaporated milk, the formation of gas, and a rancid or fishy flavor in evaporated milk. Still another defect which may occur in evaporated milk is the churning or separation of the butter fat.

The most common defect in sweetened condensed milk, common both to bulk and canned condensed, is the crystallization

of sugar which causes the sandy or gritty product. This condition is due to the crystallization of lactose. There are a few defects which occur in sweetened condensed milk due to the growth of microorganisms. Such defects as a gassy and cheesy condition in sweetened condensed milk have been shown to be due to specific yeasts and bacteria. Certain molds have been shown to cause the formation of small buttons on the surface of sweetened condensed milk.

Marketing of Condensed Milk.—Condensed milks are marketed in several different ways. Canned milk or case goods are sold directly to wholesale grocery jobbers, who supply the retail stores. Larger retail stores are able to buy canned condensed milk, in the quantities required, directly from the condensary.

Bulk condensed milks are sold, more frequently, direct from the condensary to the baker, the candy maker, or the ice-cream manufacturer. Relatively small quantities of bulk condensed milk are shipped to some of the larger cities, where brokers sell it on the open markets.

DRY MILK

The preservation of milk in the dry form is by no means new. In a new translation of the travels of Marco Polo, referring to various customs of the Tartars in 1298, Marco Polo says:

When the Service, that is, the Military Service, is distant, they carry but little with them. They make a provision of milk thickened and dried to a state of paste, which is prepared in the following manner. They boil the milk and skim off the rich or creamy part as it rises to the top, put it into a separate vessel as butter, for so long as that remains in, the milk will not become hard. The latter is then exposed to the sun until it dries. On going into the service, they carry with them about 10 pounds for each man and of this one-half pound is put every morning in a leathern bottle with as much water as is thought necessary. By their motion in riding, the contents are violently shaken and a thin porridge is produced, on which they make their dinner.

Dry milk was first manufactured commercially by Grimwade of England in 1855. It was not until 1883 that an attempt was made to manufacture dry milk in America and this was in the form of malted milk, a combination of whole-milk powder and the extract of malt. In 1872, Percy of New York City applied for a patent which embraced the idea of atomizing fluids into heated air. An improvement in the process was covered later by

a patent secured by Stauf, of Germany, in 1901. The Stauf patent was purchased by the Merrill-Soule Company of Syracuse, New York. This patent expired in 1918 and since that date other companies have made use of the principles involved.

Types of Dry Milk.—The terms applied on the market to the various types of dried milk are intended to indicate the fat content of the dry milk, the nature of the milk from which the product was made, and the drying process used in the manufacture. Whole milk, cream, skim milk, buttermilk, and whey are dried commercially. The drying may be accomplished by what is termed the “spray” process or the “hot roller” or “drum” process.

Dry Whole Milk.—Dry whole milk or whole-milk powder is made largely by the spray process. The term implies that the powder was made from whole milk which contained a normal percentage of butter fat.

Dry Cream.—“Dry cream” or “cream powder” infers that the moisture of cream has been removed almost entirely by the drying process. The spray process of drying is used in its manufacture.

Dry Skim Milk.—The spray and hot-roller or drum processes are used in drying skim milk. Since there is a difference, particularly in the properties of the milks prepared by the two processes, it is the common practice on the market to indicate the process used when referring to dry skim milk. The terms “spray-process skim-milk powder,” or “dry skim milk, spray process,” are used to designate dry skim milk made by the spray process. The terms “hot-roller” or “drum-process skim-milk powder” or “dry skim milk, hot-roller or drum process” are used to designate dry skim milk made by the hot-roller or drum process.

Dry Buttermilk.—Dry buttermilk is more frequently made by the hot-roller or drum process. The term “dry buttermilk” or “buttermilk powder” is commonly understood to mean buttermilk dried by the hot-roller or drum process. More recently, buttermilk churned from sweet cream has been dried by the spray process. This is designated by the term “spray-process sweet-cream buttermilk powder.”

Dry Whey.—Dry whey is being prepared by the spray process to a very limited extent. It generally is referred to by the term “dry whey” or “whey powder.” The product is not common on the market, generally being prepared on special request.

Composition of Dry Milk.—According to a ruling set forth by the U. S. Department of Agriculture, dried milk made from whole milk must contain not less than 26 per cent of butter fat, and the moisture content must not exceed 5 per cent. In addition, the Department has ruled that dry skim milk shall not contain more than 5 per cent of moisture. The dry-milk manufacturer, therefore, takes every precaution to insure a product which will conform with the United States standards.

The composition of dry milk varies according to the composition of the milk from which it is made. Due to elimination of most of the water in the process of drying, the other milk constituents are increased in about the same proportion. Some difficulty is experienced in making the determination of moisture in dry milks, owing to their colloidal nature. Other constituents are quite readily determined by the standard methods. It is not possible to set forth an entirely satisfactory statement concerning the composition of the various dry milks, because comparatively few analyses have been published. The authors of the book "Fundamentals of Dairy Science" present a number of analyses made by several workers. This material is presented in Table XIV.

TABLE XIV.—COMPOSITION OF DRY MILK AND MILK PRODUCTS¹

Dry product	Water, percent-age	Protein, percent-age	Fat, percent-age	Lactose, percent-age	Ash, percent-age	Total milk solids, percent-age
Whole milk...	4.00	27.20	26.00	36.80	6.00	96.00
Cream.....	0.66	13.42	65.15	17.86	2.91	99.34
Skim milk....	4.00	37.40	1.00	49.20	8.40	96.00
Sour butter-milk.....	1.93	38.74	5.87	39.91	7.68	98.07

¹ "Fundamentals of Dairy Science," 2d ed., Reinhold Publishing Corp., New York. Table by Wright, Research Laboratories, Bureau of Dairy Industry, Washington, D. C.

Properties of Dry Milk.—The properties of dry milk are due largely to the constituents of the milk from which it is made. These properties have an important influence on the uses to which dried milks may be put in the dairy and other industries. If it is to be remixed with water to make a reconstructed milk, it is important that the user be aware of the extent to which

the various types of dry milk may be used for this purpose. If dried milk products are to be of value in the various food industries, they must possess good keeping qualities. The relation of certain properties to the keeping quality is, therefore, important. The influence of heat on the constituents of milk was previously discussed. It is to be expected that dry milk will possess certain properties which can be linked directly with the influence of heat on such constituents of milk as casein, albumin, calcium salts, and lactose.

Solubility.—It is frequently desired to prepare a reconstructed milk from dry milk and water or to remix water with the dry milk. The degree to which the dry milk will disperse in water is commonly referred to as its "solubility." Spray and vacuum-drum process products readily disperse in water and acquire many of the properties of the original milk from which they were prepared. If reconstructed milk prepared from such dry milk be examined, it will be observed that practically no sediment is formed after setting or centrifuging. In addition, the reconstructed milk will pass through a filter paper as will normal milk.

Dried milk made by the atmospheric-drum process, however, disperses in water more slowly and less completely. When reconstructed with water and allowed to stand, a relatively large amount of sediment settles to the bottom and on filtering the mixture a large proportion, relatively, remains on the filter paper. In general, it is conceded that dry milk made by the spray process is about 99 per cent soluble, that made by the vacuum-drum process soluble nearly to this extent, while that made by the atmospheric drum is from 60 to 70 per cent soluble.

Color.—The color of dry milk is influenced by the carotene content of the original milk. If the milk from which the dry milk is made is rich in carotene, the resulting product will possess a darker yellow color than that made from milk lacking carotene. Dried milks, subjected to high heat, such as used in the atmospheric-drum process of drying, possess a darker color than those made under conditions where the milk is not subjected to such high temperatures, as in the case of those made by the spray or the vacuum-drum processes. When milk of a relatively high acidity is dried, the resulting material appears dark in color. Dry, sour-cream buttermilk, which is dried almost entirely by the atmospheric-drum process, is very dark in color.

Hygroscopic Properties.—All dried milk possesses the property of taking up moisture from the air unless sealed in air-tight, moisture-proof containers. The keeping quality of dry milk is endangered by this property if proper precautions are not observed. In addition, certain physical changes take place which cause the dry milk to form very hard lumps if it is permitted to take up moisture from the air.

Taste.—Dry whole milk has a pleasant taste, somewhat sweetish and with a slight suggestion of heated milk. Dry skim milk has a similar although less pronounced taste. Dry buttermilk varies greatly in taste, that made from sweet-cream buttermilk having a rather more agreeable taste than dry skim milk, while that made from sour buttermilk has an acid taste and, usually, as a result of the method of manufacture, a decidedly “cooked” taste.

The taste of heated milk is presumably due to the effect of the heat upon the protein and sugar of the milk. When any of these dry products are reconstituted, the taste of heated milk persists and is a factor limiting the use of dry-milk products in ice-cream manufacture.

Action of Rennet.—The action of rennet on reconstituted milk varies with the conditions of manufacture. In drying milk by the drum process, the heat used is relatively high, and the properties of the milk are so affected that rennet has slight effect upon the reconstructed product. Dry milk from the spray process when reconstituted may be coagulable by rennet although the action is not the same as with normal milk. The curd is very soft and the coagulation uneven.

Methods of Manufacturing Dry Milk.—One of the first methods employed in the drying of milk commercially was that known as the “Dough Process.” This process consists of condensing the milk in a vacuum pan to a low concentration, after which the condensed milk is placed in trays in a drying chamber. After the product is dried, it is ground to a fine powder. The process is still used in a few isolated cases. The modern methods of drying milk, however, as has been previously indicated, are known in a general way as the spray and the drum processes of drying.

The Spray Process.—There are several methods now employed in the powdering of milk by the spray process. Although the processes differ in some respects from one another, each makes use

of the same general principles. Each method requires a large drying chamber, into which hot air is blown at a high velocity. A part of the water of the milk generally is removed previously by means of a vacuum pan. The condensed milk is then sprayed or atomized into the hot chamber where the finely divided milk particles are dried as they fall to the bottom. A portion of the very fine particles may drift with the outgoing air and for this

FIG. 82.—Diagrammatic sketch of a spray-process milk-drying plant. The milk is atomized into a large chamber where the falling mist of milk meets an upward current of hot air. The dried milk falls to the floor of this compartment. The finished product is removed through a hopper and after passing through a bolter is placed in the container, usually a barrel, for shipment. (Courtesy of C. E. Rogers Company.)

reason various means have been provided to catch this portion of the dried milk which might otherwise be lost. The air may be filtered through fine meshed screens or cloth, or it may be washed free of powder with incoming milk, according to the process used.

After the dried milk has fallen to the floor of the drying chamber, it is removed either automatically by means of mechanical devices or by suction. If no means are provided for removing the powder, as it is formed in the drying chamber, the operator removes the powder by means of a scoop shovel at the completion

of the day's operations. After being removed from the drying chamber, the dried milk is placed in various types of containers in which it is sold on the market.

The Drum Process.—The essential feature of this process is a slowly revolving drum heated to a high temperature from the inside with steam under pressure. The product to be dried either is allowed to flow onto the roller in a thin layer or is sprayed on the roller. There are two general types of drum driers on the market, generally termed "atmospheric-drum driers" and "vacuum-drum driers." The dried milk prepared by the drum process is commonly referred to on the market as "hot-roller process" dried milk. The quality of dry milk produced by the two drum processes depends largely upon the type of milk used, and the temperature to which the milk is subjected during drying. The greatest heat is used in connection with the atmospheric-drum process.

The atmospheric-drum process is used almost entirely in the preparation of dried sour-cream buttermilk and dried skim milk. In sections of the United States where sweet cream is churned in butter making, the practice of drying sweet-cream buttermilk by the atmospheric-drum process is used in many creameries where sufficient amounts of the product are available. The general opinion prevails in many quarters that dry milk made by the atmospheric-drum process is of an inferior grade. This opinion is due, mainly, to the fact that so much low-grade material is prepared by this method from sour buttermilk, and surplus skim milk. The process is also used for preparing dry skim milk and dry sweet-cream buttermilk used for human consumption and when proper care is taken an excellent grade of product results. The solubility of these is about 60 to 70 per cent of that made by the spray process, but in other respects the products compare favorably with those from the spray process.

The vacuum-drum driers are used for the same products, but as this process results in a dry milk which is more soluble than that made by the atmospheric drums, because a lower temperature is required on the drums, the process is also used to a limited extent for drying whole milk.

Atmospheric-drum Process.—The atmospheric-drum process of drying skim milk and buttermilk generally consists of two large, steam-heated, horizontal, steel, rotating drums or cylinders placed side by side. Since the milk during the drying process is

continually under atmospheric conditions, the term "atmospheric" drum has been applied generally to driers of this type. Skim milk or buttermilk for drying is allowed to flow on or between the drums from a milk-supply tank suspended above the drier or else sprayed upon the drums by special devices. The milk forms in a thin layer over the surface of the drier and quickly dries, the vapors being removed from the immediate

FIG. 83.—An atmospheric-drum milk drier. Machines of this type are frequently used to dry sour-cream buttermilk used for stock feeding, and sweet-cream buttermilk and skim milk used for human consumption. The machine illustrated is a two-roll type. In addition to the rollers, a conveyer is shown at the side of the roll, and at the right is shown the flaker or mill where the dried milk is ground. (*Courtesy of Buffalo Foundry Company.*)

vicinity by means of a large vapor stack which leads to the outdoors. The dried milk is removed from the surface of the drums as they revolve by means of sharp, close-fitting blades which extend along the sides of the drum. The dried milk comes from the roller in a thin sheet which is easily broken into flakes as it falls into a trough along the side of each drum. From the trough the dried flakes are worked mechanically towards the end of the drier, where they are sacked. In this condition the dried milk is sold as milk flakes. More often, however, the flakes are ground as they reach the end of the drier into a powder which is finely milled and placed either in sacks of 100 pounds each, or barrels of 200 pounds each. Generally, dried milk intended for

animal feed is ground and placed in sacks while that intended for human consumption is finely ground, milled, and placed in barrels. The milling process is frequently carried on at some central point, as a matter of economy.

Vacuum-drum Process.—Milk dried under atmospheric pressure requires an exceedingly high temperature in the drum if thorough drying is to be accomplished. The vacuum drum consists of a machine somewhat similar to the atmospheric drier. It differs, however, in that the drums are encased and revolve in an atmosphere of reduced pressure due to a partial vacuum which is maintained. The milk is applied to the drum in several different ways. The drum may dip into the milk, or the milk may be sprayed on to the drum at certain points, generally at the bottom. In all types of driers using this process, the milk is subjected to a lower drying temperature than is used in the case of the atmospheric drums. It is the reduced heat used in such machines which probably accounts for better solubility of the dried milk that results, as compared with the dried milk prepared on the atmospheric drums.

Grinding and Milling.—Theoretically, spray-process powders are ready for the final package immediately after the drying process. As an extra precaution, especially against lumps of caked milk occurring in the finished product, the spray powder is often passed through a bolting machine before being placed in the containers in which it is marketed. Milling of the powder, however, is not essential. In the case of dried milk made by the drum process, the product is passed through grinding and bolting machines and milled before being placed in the final container. Frequently, drum-process milk is not ground or bolted but the flakes of dried milk are placed in sacks and sold as "dried flakes."

Grading and Standardizing.—To meet the market demand, it is essential that dealers in dried milk assemble large quantities of various grades for distribution. Accordingly, much of the dry milk produced is assembled in central warehouses and graded according to its color, presence of foreign matter, and composition. All first-grade products are then mixed in milling machines, care being taken to produce a finished article of a uniform composition, particularly a uniform fat content.

Use of Dry Milk.—Dry milk was first produced as infant food. Its use has spread into every industry manufacturing

food products in which normal milk is used. It is used in the baking industry, in candy and ice-cream manufacture, and prepared pancake and biscuit flours. The meat industry makes use of dried skim milk and sweet-cream buttermilk in the preparation of certain types of sausage. Dried sour-buttermilk is used chiefly for feeding animals. Some of the off-grades of other dried milk are used for this purpose also. Such dried milk makes excellent feed for young calves, pigs, and chickens.

Malted Milk.—Malted milk is prepared by the drying of a mixture consisting essentially of whole milk combined with the fluid separated from a mash of ground barley malt and wheat flour. It must contain not less than 7.5 per cent fat and not more than 3.5 per cent moisture. It is used widely as a delicious food especially when mixed with fluid milk or ice cream.

Defects in Dry Milk.—The defects in dry milk of most importance are those which occur in that intended for human consumption. The most serious defects are those affecting the flavor of the dried milk, its physical makeup, cleanliness, and color.

The most common flavor defect in dry milk made from whole milk is the development of tallowiness. This flavor is doubtless due to the oxidation of milk fat. Dry skim milk may develop a tallowy flavor but not to the extent of dry whole-milk. Still another flavor, common only in dried milk containing milk fat, is rancidity. This defect appears to be due to the hydrolysis of milk fat, resulting in the liberation of butyric and other fatty acids.

Other defects in flavor may occur in dry milk in general. The most easily detected is a stale, or old and musty flavor which develops after it is held in storage for a period, particularly when any increase in the moisture content takes place.

If improper methods are employed in the drying process and the finished product is permitted to retain a relatively high percentage of moisture (above 5 per cent), it will develop a lumpy condition. In extreme conditions, the physical appearance will become altered and the lumps be exceedingly large and very hard. So hard will they often become, that they can be broken up into pieces only with a hammer. The cleanliness of dry milk is exceedingly important, if it is to be used for human consumption. Foreign material of any nature will render it unfit for use other than for animal feeding.

The color of dry milk is influenced by many factors, many of which are unsolved. That which is made from whole milk should be clear and uniform and no dark specks should be visible. The same thing applies to others intended for human consumption. One of the common color defects of dry milk made by the hot-roller or drum process is the appearance of dark brown specks of burnt milk. Such a condition often indicates unclean conditions in the plant.

Marketing of Dried Milk.—Dried milk is marketed in several types of containers. That which is intended for use in the home is placed in tightly sealed cans of sizes containing from a few ounces to 1 pound.

Others types of containers, such as wooden barrels lined with paper, steel drums, and fiber drums, are used in marketing both spray-process and drum-process dried whole- and skim milk. These containers as sold to the trade contain from 10 to 200 pounds. All second-grade dry milk, from either the spray or drum process, and particularly the latter, is sold in sacks which contain 100 pounds.

MICROBIOLOGY OF CONDENSED AND DRY MILK

The types of microorganisms which will be present in condensed or dry milk will depend upon the flora of the original milk, the extent and kind of contamination in processing, and the relative resistance of the various types present to the processes of condensing or drying.

In the condensing of milk by the vacuum-pan method, the milk is subjected for a short period of time to temperatures ranging from 167 to 212°F. (75 to 100°C.) in the forewarming process. This results in a marked reduction in the total number of microorganisms. During the evaporation in the vacuum pan, the milk is exposed for some time at 130 to 145°F. (54.44 to 62.78°C.). This ordinarily leads to a further destruction of the thermolabile types of organisms. However, there is some evidence to indicate that certain bacteria actually may develop during the condensing process. When superheating is employed at 180°F. (82.22°C.) or higher, a further decrease in numbers of bacteria will ordinarily follow. There will appear in the concentrated product a variable number of organisms, at times a considerable number. Steps must then be taken to hold these organisms in check if the product is to possess a good keeping

quality. Further recontamination of the condensed milks must be prevented as far as possible after the heat treatment.

Effect of Low Water Content, and Concentration of Solids.—

In the case of the regular sweetened condensed milk, the water content is usually somewhere in the neighborhood of 25 per cent which, with the concentration of the milk solids, does not provide a very satisfactory substratum for bacterial development, but which, nevertheless, will not prohibit the growth of many types. To overcome this situation, cane sugar is added so that the final product contains about 40 per cent of cane sugar. This, together with about 30 to 35 per cent of milk solids, competes for the small amount of water. Thus a thick syrup is formed which tends to draw water from the cells of the microorganisms by osmotic pressure with the result that the metabolism of the cell is disturbed to such an extent that it cannot grow and develop normally. For this reason, there is seldom any growth of microorganisms in sweetened condensed milk, and when it is sealed in a tight can its keeping quality is good.

In the case of the unsweetened type of condensed milk, which is usually called evaporated, the moisture is somewhat higher, perhaps up to 75 per cent. This product would be very susceptible to the growth of microorganisms. For this reason, it is necessary to subject it to a heating process, usually at 240 to 245°F. (115.7 to 118.3°C.) for 15 minutes or more, in order that all the microorganisms may be destroyed. Evaporated milk owes its keeping quality to the freedom from living microorganisms.

Microorganisms in Dry Milk.—In the case of dried milk, the process of desiccation is carried to the point where only a trace of water remains in the final product, usually less than 5 per cent. The numbers of microorganisms which will remain in the dry milk will depend upon the method of drying. Where the spray process is used, the temperature of the atomized particles of milk is never very high. Consequently, a sample of fresh powder produced by the spray process may contain thousands or even millions of bacteria per gram, as well as other types of organisms. With the drum process, the film of milk upon the revolving cylinder will reach a high temperature. As a result of this, the majority of organisms will be destroyed and only the most resistant forms will remain. Thus, the bacterial content of drum-dried milk will usually be a few thousand or much less per

gram. Either type of dried milk may pick up contamination during drying, packing, or subsequent handling.

When the dried product is kept for a period of time, there is a tendency for some of the organisms to die, as it is a general rule in biology that if a cell is not growing, it is dying. With the small quantity of water left in the dried milk, there can be no growth, and, consequently, no deterioration of the product can occur because of the activity of microorganisms. Instead, the decrease in numbers continues throughout the life of the dry milk.

Defects Due to Microorganisms.—There are certain defects which may appear in sweetened condensed milk as the result of the growth of certain bacteria and yeast-like organisms which are able to grow in such a concentrated material. Swelling of the package, due to the gas formation, abnormal thickening, and coagulation followed by protein decomposition may take place. Hard, brownish lumps called “buttons” may develop because of the growth of certain molds, such as *Aspergillus repens*.

The evaporated milk, if improperly sterilized or carelessly sealed in the cans, may develop bitter or fishy flavors due to the growth of bacteria. Gas production may also take place sufficient to cause the bulging of the can.

No specific defects of dried milk can be attributed to microorganisms until the product is reconstituted to resemble normal milk by the addition of water. The chances that condensed or dried milks may transmit disease-producing bacteria are rather remote. Pasteurization of the milk before concentration will reduce this possibility to a minimum.

MILK BY-PRODUCTS

Market milk and market cream utilize about 45 to 48 per cent of the milk produced in the United States. The remainder is used in the manufacture of such dairy products as butter, cheese, condensed milk, dry milk, and ice cream. A relatively small quantity is used in the feeding of farm animals, principally the dairy calves. In the separation of milk for market cream and in the manufacture of butter and cheese, there become available large quantities of skim milk, buttermilk, and whey. These three products are the by-products of the dairy industry. The larger part of the dairy by-products available in the United States is, at present, used for animal feeding. There are indications that

this practice will not continue indefinitely. In the future, the use of dairy by-products for human food is certain to increase. They, also, offer a vast reservoir of material for industrial uses.

Skim Milk as a By-product.—On the average, 85 pounds of skim milk are available from each 100 pounds of milk separated. The question of the utilization of this skim milk arises whenever milk is separated to obtain cream for market purposes or butter making. Some skim milk is usually available in city milk-distributing plants, but a place is found for the relatively small amounts by using it for Cottage cheese and other purposes. The real problem of using skim milk to advantage arises in those localities where the extensive manufacture of butter results in enormous quantities of skim milk. The essential difference between skim milk and whole milk is the fat content. One of the authors found the average fat content of 93 samples of skim milk from farm separators to be 0.07 per cent as determined by the modified Roesse-Gottlieb (Mojonnier) method. The same samples averaged 0.02 per cent fat by the Babcock method, using the skim milk bottle. The lower reading from the Babcock method is in accordance with the experience of others. This method when applied to skim milk gives results which are too low. In protein, skim milk varies between 3.4 and 3.8 per cent; the sugar is less variable, averaging between 4.9 and 5.0 per cent; the mineral content is approximately 0.8 per cent.

Skim Milk as an Animal Feed.—On farms marketing cream or butter, a portion of the skim milk, as a rule, is used for raising the calves necessary to maintain the dairy herd. The remainder is largely used for feeding pigs and poultry. The remarkable efficiency of skim milk as a supplement to corn and cereals for growing pigs is well known. Poultry, also, make excellent use of skim milk. The special value of dairy by-products for these purposes is due largely to the quality of the proteins. Cereal proteins are not very efficient, while milk proteins supply what is lacking in the grain proteins. Under present conditions of cheap human food it is conceded that skim milk, buttermilk, and whey can in many localities be used with advantage as animal feed. There is a limit, however, to the amount that can be used with economy in this way. Economic reasons, for example the lack of sufficient grain, often stand in the way of the farmer's increasing the number of pigs to a point where the skim milk available can be fed with advantage. In the state of Minnesota, for example,

after allowing for all the skim milk the calves, pigs, and poultry in the state can use to advantage, at least 1,500,000,000 pounds of skim milk are available for industrial purposes.

Skim Milk for Human Food.—The value of skim milk as a human food is not generally recognized in America. Meat is the chief source of animal protein in the American diet. In the by-products of the dairy industry there are approximately 1,192,466,000 pounds of protein, or 43 per cent as much as is in all the beef, pork, and mutton consumed in the United States. Milk protein can largely replace meat protein in the human diet, as is seen by the small per capita consumption of meat and the high consumption of milk solids in the form of milk and cheese in Europe. When skim milk is fed to the pig, only about 13 to 16 per cent of the protein content is returned in the form of human food. The 84 per cent of the protein so wasted could have been used for human food. Whether skim milk shall serve as animal food primarily or as a human food is largely a problem of economics. In Denmark, at present, about one-half of the skim milk produced is utilized in the diet of the human, the other half being fed to the pig. In Germany, however, very little skim milk is fed to livestock, practically all produced serving as source of animal protein in the human diet.

Other Uses of Skim Milk.—As pointed out, the largest use of skim milk at present is as an animal food. This is likely to decrease rather than increase as other and more economical means of using larger portions of the product are coming into use. It is probable from European experience that the future will see more skim milk, in the form of cheeses of various types, used as human food. A hundred pounds of skim milk yields 15 pounds of Cottage cheese equal in value as human food to an equal weight of round steak. It is clear that, if food prices become higher in proportion to the income, the consumption of such products as Cottage cheese is certain to increase. At present, the chief products produced from skim milk are: condensed skim milk, dry skim milk, and casein.

The condensed product finds extensive use in the baking industry and in the manufacture of confectionery. Limited amounts are also used as a means of increasing the solids in ice-cream mixes. The dry product is also used by the baking industry in bread making, pie fillings, cookies, doughnuts, and similar bakery products. It is further used in the preparation of ready-mixed

pancake, cake, and doughnut flours. Certain infant foods are prepared which consist of modified dry skim milk. It is used by certain firms in the preparation of sausage to which it contributes added food value and adhesive properties. So extensive are the possibilities of the use of dry skim milk in the prepared-food industries that it is inconceivable to what extent the product may be used in the future. In the manufacture of candies, such as chocolates, dry skim milk is extensively used. It is used, also, as is the condensed products, in increasing the milk solids-not-fat, content of ice cream.

Skim milk is the most desirable product from which to manufacture casein. Attention has been previously brought to the uses of casein in the manufacture of casein plastics, its use in the textile and leather industry, as a glue, and in the manufacture of paints, etc.

Buttermilk.—The cream churned for butter averages about 30 per cent butter fat. For each 100 pounds of butter made, there are available, as a by-product, approximately 166 pounds of buttermilk. The composition and food value of buttermilk are essentially the same as those of skim milk. The fat content is somewhat higher, however, and in the case of buttermilk from sour cream, the sugar content is lower. In sour-cream buttermilk from 10 to 15 per cent of the original sugar has been changed into lactic acid through the activity of bacteria. The acid content expressed as lactic acid usually does not exceed 0.8 per cent but may reach 1.0 per cent if certain types of bacteria have taken part in the fermentation. Recent analyses by the authors of a large number of buttermilk samples from typical creameries showed a range in fat content from 0.1 to 0.6 per cent. The buttermilk from over 2,000 churnings made in a creamery operated under especially well-controlled conditions contained on the average slightly less than 0.20 per cent of fat, as shown by the regular Babcock test. In addition to the fat, typical buttermilk will contain about 90 per cent of water, 3.5 per cent protein, 4.4 per cent sugar, 0.6 per cent lactic acid, and 0.7 per cent ash.

At present, large quantities of buttermilk are practically wasted or at best are not used economically. A common practice in connection with the smaller creameries is to sell the buttermilk to some one who uses it for feeding swine. The price received is often not over 1 cent a gallon. As a matter of fact, when animals receive large quantities of buttermilk, the feeding value

is not much more than the price paid. Fed in reasonable quantities as a supplement to cereals and corn, the same buttermilk would have a much higher value.

Commercial Products from Buttermilk.—Due to its economical advantages, the practice of drying buttermilk is rapidly coming into use. The dry product proves to be especially valuable as a constituent in the ration for young chicks. It is also used with advantage in calf raising as a substitute for skim milk, where the whole milk is marketed. A small amount of buttermilk is used for the manufacture of casein. The quality of the casein, however, is not satisfactory and, for this reason, the use of buttermilk for this purpose is limited. A fairly large amount of buttermilk is condensed and, in this form, sold for animal feeding purposes under various trade names. Recently, there has appeared on the market a good deal of dried buttermilk which is derived from the churning of sweet cream. This product has some especially desirable qualities and is used almost exclusively in connection with the preparation of human foods.

Whey.—Whey is the by-product of cheese making. In using the ordinary Cheddar process, the yield of cheese is about 10 pounds per 100 pounds of milk, leaving close to 90 pounds of whey to each 100 pounds of milk used. In this whey is found most of the milk sugar and albumin of the original milk, together with a portion of the mineral matter and somewhat more fat than in skim milk. The composition of typical whey is: water, 93.4 per cent; fat, 0.35 per cent; protein, 0.85 per cent; milk sugar, 4.80 per cent; and ash, 0.6 per cent. Whey is used chiefly as a feed for farm animals, more particularly swine. It serves as an excellent supplement to cereals and corn. It is used to a limited extent as a calf feed, but is not so well adapted to this use as is skim milk. The common practice is, for the farmers delivering milk to a cheese factory, to take back to the farm whey in proportion to the milk delivered. Whey contains very valuable food materials, but the large water content makes condensation or drying expensive. Whey is the principal source of commercial milk sugar. A relatively small amount of whey is condensed and mixed with cheese in the preparation of certain processed brands. In Scandinavian countries a product known as "Primost" is prepared by removing the water from whey by heat. "Primost" has a sweetish taste combined with that of cooked milk, and is a valuable food product.

Manufacture of Casein.—The first step in the manufacture of commercial casein is the coagulation of the casein of skim milk either by natural lactic-acid fermentation, the addition of other acids, or by rennet. Casein prepared by rennet coagulation cannot be used for all purposes. It is darker in color, and often higher in fat, and generally does not bring the price on the market that can be obtained for casein prepared by either artificial acidification or natural fermentation. Rennet casein is largely used by the manufacturer of casein plastics, while acid casein is preferred by casein-glue manufacturers.

When natural souring is practiced, the skim milk is placed in an ordinary cheese vat and brought to a temperature around 70° F. (21.1°C.). Starter is added and the milk allowed to set until a firm curd is formed. The curd is cut or broken up much as in the making of a Cottage cheese, then heated until it is toughened as a result of the cooking process. The whey is then drawn from the vat and the curd piled at each side and allowed to drain. The curd is then washed several times with cool water. It is then ready for the drying process.

Drying of Casein.—The usual method followed in the drying of casein is to place it in trays set in a long tunnel through which a blast of hot air is blown. The tunnel may be constructed of wood or galvanized iron. Doors open along the side of the tunnel, permitting the entrance of trucks containing several shelves. On each shelf of the truck are placed the shallow trays containing the casein. After the casein is dried thoroughly, or to a point where it does not contain much above 2 to 3 per cent moisture, the curd is removed from the tunnel. The curd then is removed from the trays, passed through a grinding machine, and sacked for the market. A yield of from 2.5 to 3.5 pounds of casein per 100 pounds of skim milk is secured.

Milk Sugar.—A crude milk sugar is said to have been prepared from whey as early as 1628. Up until about 1880 milk sugar was made commercially only in Switzerland. Following this date factories were established in other sections of Europe and the United States.

The method of manufacture consists first of separating the fat from the whey by means of a high-speed centrifugal separator. Albumin, which coagulates by heat, is then removed by boiling the whey after the addition of acetic acid. The whey is then placed in a vacuum pan and concentrated until it contains about

60 per cent solids. The concentrated whey is placed in tanks around which cold water is circulated. The milk sugar crystallizes and is removed by centrifuging. Refining is accomplished by dissolving the milk sugar in water with bone black and acetic acid. The liquid is boiled to get rid of still more albumin and the phosphates of milk. These are filtered from the liquid which is then recondensed in the vacuum pans. The concentrated sugar is then dried and ground.

Dry Whey.—Whey is dried by means of the spray process as described in the discussion on dry milk. Before drying, the whey is passed through a centrifugal separator to remove the fat. Only a limited amount of this product is prepared, but there is evidence that more uses will be found for it in the future.

FERMENTED MILK BEVERAGES

Whenever man has led a nomadic life, accompanied by herds of domestic animals, he has made extensive use of milk, or its products, for food. The earliest historical records speak of the use of fermented milk beverages as important items in the simple diet of these wandering tribesmen. The Bible contains a number of references as to the use and virtue of curdled milk. It is easy to conceive of the primitive conditions of sanitation and lack of refrigeration. The milk from the cow, sheep, goat, or mare was undoubtedly highly contaminated with many different microorganisms. The leather bags which served as the common carriers for the milk, naturally, were not easy to clean and sterilization was difficult; in fact, unknown. The prevailing temperatures were for the most part high enough to promote the growth of microorganisms. Fermentation obviously took place in the milk. Thus the fermented milk beverages, which we know today, were purely products of circumstances.

Most of these beverages originated among the tribes in southern and eastern Europe, especially in Russia, the Balkan States, and along the Mediterranean. Some were known in the Scandinavian provinces. Asia, Africa, and South America certainly contributed some characteristic fermented milks.

Many of these beverages are, of course, still prepared in Europe. Some of them have come into use in this country, where control of the fermentation by selection of cultures of yeasts and bacteria has been more exacting.

These fermented-milk beverages form a very interesting link between primitive and modern dairying. The fermentations which microorganisms could produce were known long before the organisms themselves were known. Further than this, these milk beverages have meant an increased consumption of milk through the ages and today we see, serving as adjuncts to the diet, beverages which have actual regulating and medicinal value in the control of intestinal fermentation.

Koumiss.—These beverages have been known under many exotic names. There is one known as Kumyss (Koumiss) which originated with a Russian tribe living along the river Kuma. Milk-souring types of bacteria and yeasts are predominant and bring about a rapid production of lactic acid and alcohol, with the evolution of gas which causes strong effervescence. In some sections of Asia, a brandy-like beverage is distilled from this type of fermented milk.

Kefir.—Another product of southeastern Russia is known as Kefir (Kephir). Here, also yeasts and lactic-acid bacteria produce quantities of acid, alcohol, and carbon dioxide. An interesting feature of this drink is the starter which is used. This consists of the so-called "Kefir grains," the origin of which is not known. They resemble small cauliflowers and carry the yeasts and bacteria necessary for the fermentation.

Leben.—In Egypt, Syria, Algeria, Sardinia, Sicily, Montenegro, and Carpathia a beverage known variously as Leben, Leben raib, Gioddu, etc., is likewise prepared by the action of yeasts and bacteria which produce acid and alcohol, principally.

Yoghurt.—One of the most famous fermented-milk preparations is known as Yoghurt or Matzoön. The renowned Metchnikoff called especial attention to this in his book on the prolongation of life among the Bulgarian tribes. He attributed this longevity to the use of this beverage, especially the presence of certain types of bacteria, one of which is now known as *Lactobacillus bulgaricus*. Some of his observations were inaccurate, but the publicity which was given to milk beverages as agents to promote health and insure long life still carries its impetus into our present-day dairy advertising. This Yoghurt is known under other names in many countries, such as Turkey, India, and the Balkan States. Several types of bacteria and yeasts have been described as being present. The principal characteristic is a high acidity produced largely by the *Lactobacillus bulgaricus*

type. The present-day Bulgarian buttermilk has its origin in Yoghurt. It is prepared from pure cultures of the above-mentioned organism or with combinations of *Streptococcus lactis* starters.

Scandinavian Products.—In Scandinavia, Kaeldermaelk, Taette, Püma, Fiili, Lange-milch, Lange-wei, etc., have been used for some time. Most of these are rather ropy as well as sour, and are produced largely by the action of the lactic-acid type of streptococcus.

Cultured Buttermilk.—One of the favorite milk drinks in this country is the so-called "cultured buttermilk." This is prepared principally from sweet, fresh milk by the addition of ordinary butter starters which contain *Streptococcus lactis* and *Streptococcus citrovorus* or *Streptococcus paracitrovorus*. The acidity is not over 1 per cent, and the flavor is mild and pleasing.

Therapeutic Value of Fermented Milk.—In recent years, attention has been called to the marked therapeutic value of milk cultures of an organism which is a regular inhabitant of the intestines of man and animals, namely, *Lactobacillus acidophilus*. When this organism grows in milk, it produces lactic acid, which curdles the milk. A characteristic but pleasant flavor is also produced. When such milk is consumed regularly, the *Lactobacillus acidophilus* gains predominance among the bacteria in the intestinal tract and in so doing lessens the putrefaction taking place there because of the presence of other types of bacteria. Thus acidophilus milk has a beneficial effect and is often prescribed by physicians for persons suffering from intestinal disturbances.

CHAPTER XIV

DAIRY ARITHMETIC

Certain problems involving mathematics are met in the handling and sale of dairy products. The solution of these problems presents difficulties for many dairymen.

On the farm, the producer wishes to calculate the average daily and yearly milk production of his cows and the fat percentages; he may be confronted with the choice of selling cream with a certain fat percentage at a stated price per gallon of milk, or at a certain price per hundredweight.

In the milk plant, milk is gathered from many sources. The management is concerned with the mathematics involved in standardizing the product so that it may be of uniform composition from day to day. The cheese-maker is interested in the same questions. The ice-cream maker has his problems in preparing and calculating the composition of the ice-cream mix. The butter manufacturer is confronted with the calculation of the overrun and often of the neutralization of cream.

The proportion of the various constituents of milk is commonly expressed in terms of percentage. The use of decimals is, therefore, essential in the handling of the calculations concerning milk and milk products. In the presentation of the material to follow, it is assumed that percentage and the use of decimals are well understood.

CALCULATIONS OF INTEREST TO THE PRODUCER

Problem 1. Determining the Pounds of Fat in Milk.—To determine the pounds of fat in a given quantity of milk when the percentage of fat contained in the milk and the pounds of milk are known, multiply the pounds of milk by the percentage of fat.

For example, assume that a cow produces 25 pounds of milk testing 3.8 per cent fat at one milking.

First reduce per cent to a decimal by moving the decimal point two places to the left, for example 3.8 per cent = 0.038.

Then

$$25 \times 0.038 = 0.95 \text{ (pound of fat produced).}$$

Problem 2. The Average Fat Percentage.—It may be desirable to calculate the average fat test under a variety of conditions. The milk yield and fat percentage for a particular cow may be available by either milkings, days, or months, and it is desired to calculate the fat percentage for all the periods represented. In other cases, the milk yield and fat percentage for each cow in the herd are known and the average for the entire herd is wanted. In milk- or cream-receiving plants the total milk or cream delivered from each farm is known, the test may be available, and the operator wishes to know the true average fat percentage of the mixed product. In calculating averages under any of these conditions, the error is very often made of taking a direct average, that is in adding the fat percentages together and dividing by the number of samples included in the total. This method will give correct results only in case each lot of milk or cream represented is of the same weight. If the amounts vary, an average derived in this way may be far from accurate, as illustrated by the following:

Milk, pounds	Test, per cent	Fat, pounds
200	5.0	10
600	3.0	18
100	4.0	4
—	—	—
Total 900		32

A direct average of the three tests would be 4 per cent ($5 + 3 + 4 = 12$; $12 \div 3 = 4$). The total fat in 900 pounds of milk if it contained 4 per cent fat, would be 36 pounds ($900 \times 0.04 = 36$). If the fat in each lot is calculated separately, however, and the total added, it will be found that the actual amount is 32 pounds. Clearly, the first method is incorrect. The *true average test* would be 3.5 per cent ($(32 \div 900) \times 100 = 3.5$).

Finding the True Average Test.—The correct way to calculate the average test is to determine the amount of fat in each unit separately, take a total of these to give the total fat involved, then divide this fat total by the milk total, and multiply the result by 100. The figure obtained is the true average test. The procedure is illustrated by the table shown on page 314 which represents, by months, the production of a certain cow for a year. The problem is to find the true average fat percentage for the year.

Then:

$$\frac{509.3}{10,346} \times 100 = 4.92 \text{ per cent.}$$

So the true average fat percentage for the year is 4.92 per cent.

The direct average obtained by adding the fat percentages for each month and dividing by twelve would equal 5.22 per cent. In that case, 10,346 pounds of milk would contain 540 pounds ($10,346 \times 0.052 = 537.99$) of fat, which is clearly incorrect, as

Milk, pounds	Fat, per cent	Fat, pounds
1,319	4.30	56.7
1,351	4.30	58.1
1,241	4.40	54.6
1,156	4.20	48.5
1,119	4.40	49.2
956	5.40	51.6
872	5.40	47.1
789	5.50	43.4
709	6.10	43.2
472	7.60	35.9
362	5.80	21.0
Total 10,346		509.3

the sum of the pounds of fat produced during the year is actually 509.3 pounds. An error of the type illustrated is often made in keeping yearly records of cows. Sometimes the milk seller calculates an erroneous average of this kind for his herd from the report of the cow tester and is led, thereby, to question the accuracy of the test he receives from the milk buyer.

Problem 3. The Price of Milk.—Milk is sold, as a rule, by weight and according to the fat content. A basic price is generally set per 100 pounds of milk of a given fat percentage. A certain sum per 100 pounds is generally added to the price for milk testing above the standard set and a proportionate amount deducted for milk testing below the standard. To illustrate, milk may be paid for in a given locality at the rate of \$2 per 100 pounds of 3.5 per cent milk. For all milk testing above 3.5 per cent butter fat, 4 cents per point (each, 0.1 per cent), are added to the basic price, and for all milk testing below 3.5 per cent fat a like amount per point is deducted.

If a producer under the above conditions delivers milk testing 3.8 per cent fat to a milk plant, the value per 100 pounds becomes \$2.12

$$(2.00 + (3 \times 0.04) = 2.12),$$

since the test is 3 points or 0.3 per cent higher than the standard set. If the test had been 3.2 per cent fat, or 3 points lower, the milk would have been paid for at the rate of \$1.88 ($2.00 - (3 \times 0.04) = 1.88$) per 100 pounds of milk. Other methods of paying for milk, based upon the combined market

value of the butter fat and the milk solids-not-fat, are used in a few localities; particularly, in those where milk is bought for cheese making, drying, or condensed-milk manufacture.

To Determine the Value of Cream Sold by the Gallon.—Frequently, the producer of cream sells this product by the gallon. The question arises under such circumstances as to the price received for butter fat. To illustrate such a problem, assume that cream containing 20 per cent of butter fat is being sold at 70 cents per gallon. The price per pound received for fat in this instance is calculated as follows:

Problem 4. To Determine the Pounds of Cream in One Gallon, Testing 20 Per Cent Butter Fat.—One gallon of water weighs 8.34 pounds. The specific gravity of 20 per cent cream is 1.011 (see Appendix). The weight of 1 gallon of this cream is 8.4 pounds ($8.34 \times 1.011 = 8.43174$). A gallon of cream weighing 8.4 pounds and containing 20 per cent butter fat, therefore, contains 1.68 pounds of butter fat ($8.4 \times 0.20 = 1.68$). From this result it is shown that, when cream sells for 70 cents per gallon, the price received per pound of fat is $41\frac{2}{3}$ cents ($70 \div 1.68 = 41.66$).

Problem 5. To Determine the Price per Gallon of Cream.—It is often desired to sell cream by the gallon, and the question arises as to the charge that should be made per gallon for cream of varying fat content when the price desired for the fat so sold is known. Let it be assumed that it is desired to secure 40 cents per pound for butter fat. The cream to be sold is to contain 30 per cent of butter fat. The specific gravity of 30 per cent cream is 1.002. One gallon of water weighs 8.34 pounds; therefore, 1 gallon of 30 per cent cream weighs 8.35 pounds ($8.34 \times 1.002 = 8.35$). Therefore 8.35 pounds of cream containing 30 per cent of butter fat will contain 2.51 pounds of butter fat ($8.35 \times 0.30 = 2.505$). It is desired to secure 40 cents per pound of butter fat. Since 1 gallon of 30 per cent cream contains 2.51 pounds of butter fat, the value of this cream is \$1.00 per gallon

$$(2.51 \times 0.40 = 1.004).$$

If it is desired to maintain the same price per pound of butter fat, sold as indicated in the above problem, for cream of varying tests, it is only necessary to form a problem in simple proportion. For example, if cream containing 30 per cent of butter fat must sell for \$1.00 per gallon in order to net 40 cents per pound for butter fat, for how much per gallon should one sell cream containing 35 per cent butter fat?

$$\begin{aligned} 0.30:0.35::\$1.00:x \\ 0.30x &= 0.35 \\ x &= \$1.166 \end{aligned}$$

Therefore, the price per gallon of 35 per cent cream should be \$1.17.

Farm Separation Problems.—In the separating of milk on the farm a number of questions arise which can be answered by the application of simple mathematics. It is commonly asked,

how much cream of a given percentage of butter fat can be secured from a given amount of milk, and how much skim milk will result on the separation of milk when cream of a given percentage of butter fat is separated?

Problem 6. To Determine the Amount of Cream.—To determine the amount of cream containing a given percentage of butter fat that can be expected from a given quantity of milk containing a definite percentage of butter fat, determine the pounds of butter fat in the milk and divide by the percentage of fat expected in the cream. To illustrate, assume that 800 pounds of milk containing 4 per cent of butter fat is to be separated and it is desired to know about how much cream containing 30 per cent of fat can be expected. The milk in this case will contain 32 pounds of butter fat ($800 \times 0.04 = 32$). If a cream containing 30 per cent of butter fat is desired approximately 106 pounds of this cream can be expected ($32 \div 0.30 = 106$). The loss of fat in the skim milk, in this case, is not considered of practical importance, assuming that milk consists of cream and skim milk. The approximate amount of skim milk that may be expected in the foregoing problem may be calculated by subtracting from the pounds of milk the pounds of cream expected. Thus it will be found that approximately 694 pounds of skim milk ($800 - 106 = 694$) may result. It may be stated that on the farm, 80 to 85 pounds of skim milk may be expected, as a rule, in the separation of each 100 pounds of milk.

Problem 7. To Determine the Most Profitable Market.—Frequently, the producer of milk and cream is confronted with the problem of deciding the most profitable market where several possibilities are available. It may be a question of selling milk by the hundred-weight, cream by the gallon, or cream to the creamery, where a definite price is paid for butter fat. Assume, for example, that the producer has the choice of selling milk at \$1.80 per 100 pounds of 3.5 per cent fat milk, with 4 cents added for each additional point or 0.1 per cent; or to sell cream, to an ice-cream plant, to contain 30 per cent of butter fat at \$1.20 per gallon; or to sell to a creamery manufacturing butter at 40 cents per pound of fat. Which of these will be the most profitable, or will yield the greatest returns? To solve the problem it is essential that the price received in each case be placed on a comparable basis. The most logical procedure is to compare the price received for butter fat under each plan. Since this figure is furnished for the fat sold at one creamery, it remains to determine the price offered under the two other plans.

It is essential that the average fat content of the milk produced be known, if an accurate analysis is to be made. Let it be assumed that the average fat content of the milk is 3.2 per cent. It is further essential that cream be properly standardized, if sold to the ice-cream factory, or that an agreement be reached on the price per gallon paid for cream testing more than 30 per cent fat. This should be on the basis of the value of a 30 per cent cream at \$1.20 per gallon.

The price receivable for butter fat, should the producer accept the plan of selling whole milk, should first be determined. A price of \$1.80 is paid for 3.5 per cent milk with 5 cents a point added or subtracted for milk testing above or below the basic test. In this instance the value of 100 pounds of the milk produced would be lower than the basic price of \$1.80, since the milk test is three points below the basic test ($3.5 - 3.2 = 0.3$). This would mean that the milk would be valued at 12 cents ($3 \times 0.04 = 0.12$) below the basic price or \$1.68 per 100 pounds ($1.80 - 0.12 = 1.68$). To determine the price received per pound of butter fat when \$1.68 is received for 100 pounds of milk containing 3.2 per cent of butter fat, calculate the pounds of fat present in 100 pounds of such milk. The result is found to be 3.2 pounds ($100 \times 0.032 = 3.2$). The price received for butter fat is found to be \$0.525 ($1.68 \div 3.2 = 0.525$).

To determine the value of butter fat sold when \$1.20 per gallon is received for cream testing 30 per cent of butter fat, it is first essential, as in the problem presented above, to know the weight of 1 gallon of 30 per cent cream. This was found in the calculation above to be 8.35 pounds. It was shown that 8.35 pounds of 30 per cent cream contained 2.51 pounds of butter fat. If the producer receives \$1.20 per gallon for such cream, he will receive \$0.478 per pound for butter fat ($1.20 \div 2.51 = 0.478$). It appears, therefore, in this instance, that the producer may select between receiving $52\frac{1}{2}$ cents per pound fat at the milk plant, 48 cents at the ice-cream plant, or 40 cents at the creamery. It may be expected he would elect to sell at the highest price.

Selling Milk or Cream.—When whole milk is sold from the farm, the problem of feeding calves, and perhaps other young stock, becomes acute. Such a case as presented in the preceding problem may involve the value the producer places on skim milk for feeding purposes. He may hesitate to sell the whole milk from the farm if the skim milk can be utilized to a good advantage as a feed for young stock on the farm. Let it be assumed, however, that the producer has use for but half of the skim milk which he produces and that he values this portion at being worth 30 cents per 100 pounds when fed to livestock. Assume the values in the above problem.

Since the price of milk is based on the unit of 100 pounds, calculate the skim milk available from 100 pounds of milk testing 3.2 per cent fat when the cream produced is to contain 30 per

cent of butter fat when sold to the ice-cream plant in the above problem. It is essential to determine the amount of cream containing 30 per cent of butter fat that can be secured from 100 pounds of milk containing 3.2 pounds butter fat. This is found to be 10.7 pounds ($3.2 \div 0.30 = 10.67$). It is apparent, therefore, that there will be 89.3 pounds ($100 - 10.7 = 89.3$) of skim milk available. If one-half of this amount, or 44.7 pounds ($89.3 \times 0.5 = 44.65$), is valued at 30 cents per 100 pounds, it is apparent that the value of this amount of skim milk is \$0.134 ($44.7 \times 0.003 = 0.1341$).

If the farmer, therefore, values the skim milk in 100 pounds of milk at \$0.134, it is necessary to deduct this amount from the price received for whole milk, if he chooses this plan of selling his product. In the above case, therefore, the actual price the farmer may assume would be received for milk containing 3.2 per cent of fat valued at \$1.68 would be \$1.55 ($1.68 - 0.134 = 1.546$). At the price of \$1.55 for milk containing 3.2 pounds of fat, the value per pound of the fat would be \$0.484 ($1.55 \div 3.2 = 0.484$). This price would still be greater than could be received for fat in cream for either the ice-cream plant or creamery.

The above calculation assumes, however, that the producer does not purchase feed for young stock deprived of milk when whole milk is sold on the farm. A possible procedure in such a case would be for the producer to purchase skim-milk powder to supplement the skim milk sold in the whole milk. It is calculated, above, that with each 100 pounds of milk sold the produce-required 44.7 pounds of skim milk as feed for young stock. If whole milk is sold, this skim milk is not available, and the farmer is forced to purchase dry skim milk or a milk substitute.

If the producer purchases a like amount of dry matter in the form of dry skim milk as is contained in 44.7 pounds of skim milk the composition of these products must be known, or assumed, in making the calculation. For practical purposes, assume the skim milk to contain 9 per cent of total solids and the dry skim milk 95 per cent total solids. In 44.7 pounds of skim milk, therefore, there are 4.02 pounds ($44.7 \times 0.09 = 4.023$) of total solids or dry matter. It will, therefore, require 4.2 pounds ($4.02 \div 0.95 = 4.23$) of dry skim milk containing 95 per cent total solids to supply the same amount of dry matter or total solids as is contained in 44.7 pounds of skim milk. At 7 cents a pound, 4.2 pounds of dry skim milk is valued at \$0.294 ($4.2 \times 0.07 = 0.294$).

It appears, therefore, that it is necessary that the producer in the above instance deduct this amount from the sale price of the milk in order to secure the net returns when whole milk is sold. The net return would, therefore, be \$1.39 ($1.68 - 0.294 = 1.39$) per 100 pounds of milk. If the net return on the basis of butter fat is then calculated, it is found that when 3.2 pounds of fat sell for \$1.39, the value per pound of fat is \$0.43 ($1.39 \div 3.2 = 0.434$). It appears, therefore, that the net return on selling whole milk, in this case, is larger than can be received when cream is sold to the creamery at \$0.40 per pound.

STANDARDIZING MILK AND CREAM

One of the most typical calculations in the handling of milk and cream is that of adjusting the percentage of fat to a definite amount, commonly termed "standardization." Occasion for the standardization of milk and cream is more common in the market-milk plant, but it is also used in connection with the manufacture of such products as condensed milk, dry milk, cheese and ice cream. In connection with all these products it is highly desirable that a uniform butter-fat content be present in the finished product.

To Decrease the Fat Content of Milk or Cream.—Obviously, this may be accomplished either by taking out some of the fat or by diluting the original lot by mixing with it a quantity of the same class of material having a lower fat content. In the case of milk the common procedure would be to separate a portion and add skim milk to the remainder. If skim milk from another source were available, the proper amount of this would be used, making the operation of the separator unnecessary. The real problem is to determine how much fat should be taken out in the form of cream or how much skim milk should be added.

Problem 8. Reducing the Fat Content by the Use of the Separator.

Let it be assumed that 500 pounds of milk containing 5 per cent fat are at hand and 400 pounds testing 4 per cent are desired. The fat contained in the 500-pound lot is 25 pounds ($500 \times 0.05 = 25$) and in the desired 400-pound lot, 16 pounds ($400 \times 0.04 = 16$). It is clear that 9 pounds of fat are to be removed by separation ($25 - 16 = 9$).

The problem is to determine how many pounds of milk containing 5 per cent butter fat will contain 9 pounds of butter fat. This is found to be 180 pounds ($9 \div 0.05 = 180$). It is, therefore, necessary to remove 180 pounds from the 500 pounds of milk containing 5 per cent butter fat. There will remain 320 pounds ($500 - 180 = 320$) of milk testing 5 per cent

to which must be added 80 pounds of the skim milk that results on separation ($320 + 80 = 400$). The fat content of the milk so prepared is 16 pounds, or 4 per cent as desired ($400 \times 0.04 = 16$), $((16 \div 400) \times 100 = 4)$.

Problem 9. Addition of Skim Milk.—It may not be necessary to separate a portion of the milk in the above calculation if skim milk from other sources is available. Assume, for example, that an unlimited amount of skim milk is available and it is desired to reduce the fat content of 500 pounds of milk from 5 to 4 per cent of butter fat. It is, again, necessary to calculate the pounds of fat contained in 500 pounds of milk containing 5 per cent butter fat which was found above to amount to 25 pounds ($500 \times 0.05 = 25$). The problem, therefore, is to determine how many pounds of milk containing 4 per cent of butter fat can be made, using 25 pounds of butter fat. By dividing the pounds of fat available by the test of milk desired, it is found that 625 pounds ($25 \div 0.04 = 625$) of milk testing 4 per cent and containing 25 pounds of butter fat might be prepared from 500 pounds of milk containing 5 per cent of butter fat and skim milk. By subtracting the pounds of milk available (500) from the pounds of milk it is intended to make (625), which are to contain 4 per cent of butter fat, it is found that 125 pounds of skim milk should be added to prepare 625 pounds of milk testing 4 per cent.

It is assumed that the fat content of skim milk is low enough to be of no practical significance. This is the common procedure in milk-plant work, but if extremely large quantities of milk are handled daily in condensed-milk factories, it may be advisable to take into consideration the fat content of skim milk. This would necessitate a chemical analysis of the skim milk in standardizing in order to insure accurate work.

Problem 10. Addition of Milk or Cream of Lower Fat Content.—It is possible to reduce the fat content of milk or cream by the addition of milk or cream of a lower fat content. This involves a more complex problem, however, than has been previously reviewed as fat is present both in the milk it is intended to reduce and in the milk used for standardizing. The common practice is to use the so-called "square" method in connection with such problems, in order to simplify them. The following will serve to illustrate a problem of this type and the application of the "square" method of calculation. Assume it is desired to reduce the fat content of a cream testing 40 per cent of butter fat in the making of 500 pounds of 20 per cent cream and that milk containing 3 per cent of butter fat is available for standardizing.

Draw a square and connect the four corners with lines passing diagonally from one corner of the square to the other. In the center of the square, at the point where the two diagonal lines cross, place the figure representing the percentage of fat desired in the restandardized cream. At the left-hand corner, place the figures representing the percentage of fat in the cream to be standardized and in the milk to be used for standardizing. The square now appears as below:

Following along the diagonal lines, to the opposite corners at the right of the square, place the difference between the figures at the left-hand corner of the square and the center as follows:

The result of this calculation is to give the proportion of 40 per cent cream and 3 per cent milk (in this problem), which will result in a cream testing 20 per cent. The figure at the right-hand side of the square just opposite the figure on the left-hand side of the square refers to the same product: that is to say, in the above instance the figure at the upper right-hand corner refers to the proportion of cream testing 40 per cent required, and the figure in the lower right-hand corner refers to the milk testing 3 per cent required. The result of this calculation, as followed above, is that by mixing 17 parts of 40 per cent cream with 20 parts of 3 per cent milk, a total of 37 parts of 20 per cent cream will result ($20 + 17 = 37$).

It is desired to prepare 500 pounds of 20 per cent cream:

$$\begin{aligned} 20:37::x:500 \\ 37x &= 10,000 \\ x &= 270.2 \end{aligned}$$

Therefore, 270.2 pounds of 3 per cent milk will be required.
Then,

$$\begin{aligned} 17:37::x:500 \\ 37x &= 8,500 \\ x &= 229.7 \end{aligned}$$

Therefore, 229.7 pounds of 40 per cent cream will be required.

From these calculations, it is found that 270.2 pounds of milk containing 3 per cent of butter fat should be mixed with 229.7 pounds of cream containing 40 per cent of butter fat, to prepare 499.9 (500 pounds desired) pounds of cream testing 20 per cent.

To check this problem, calculate the pounds of fat required in 500 pounds of cream testing 20 per cent which is found to be 100 pounds ($500 \times 0.20 = 100$). Calculate the pounds of fat present in 270.2 pounds of milk testing 3 per cent, which is found to be 8.1 pounds ($270.2 \times 0.03 = 8.1$). Also, the pounds of fat contained in 229.7 pounds of cream testing 40 per cent is found to be 91.88 pounds ($229.7 \times 0.40 = 91.88$). The total of the fat supplied in the milk and cream is found to be 99.98 pounds

$$(91.88 + 8.10 = 99.98), \text{ (100 pounds desired.)}$$

Problem 11. Standardizing a Given Quantity of Milk or Cream.—In the above problem a definite quantity of a given cream was prepared from milk and cream of a given fat content. Frequently, it occurs that a given quantity of milk or cream is to be reduced in fat content, but the quantity of milk or cream which will result is unknown. Assume, for example, that it is desired to reduce 500 pounds of cream testing 30 per cent of butter fat to

25 per cent and that an unlimited quantity of 3 per cent milk is available for standardizing. By use of the square, the calculation is as follows:

The proportion is as follows:

$$\begin{aligned} 22:5::500:x \\ 22x &= 2500 \\ x &= 113.63 \end{aligned}$$

Therefore, 113.63 pounds of milk testing 3 per cent are required.

By mixing 500 pounds of cream containing 30 per cent of fat, and 113.63 pounds of milk containing 3 per cent of fat, a total of 613.63 pounds of cream containing 25 per cent of fat will be obtained.

To prove or check the problem, the fat desired in 613.63 pounds of cream testing 25 per cent is found to be 153.4 pounds ($613.63 \times 0.25 = 153.4075$). The fat contained in 500 pounds of cream testing 30 per cent of fat is found to be 150 pounds ($500 \times 0.30 = 150$), and that in 113.63 pounds of 3 per cent milk, 3.4 pounds ($113.63 \times 0.03 = 3.4089$). The total of the fat contained in the cream and in milk is found to be 153.4 pounds

$$(150 + 3.4 = 153.4),$$

the amount of fat required.

The reduction of the fat in milk or cream is frequently accomplished with skim milk. The square method can be used but, when the fat content is considered as zero, as is often the case in practical work, the square is not so essential in simplifying the calculation. If the skim milk is analyzed and its fat content considered in the calculation, the square simplifies the calculation, as in the above illustrations.

To Increase the Fat Content of Milk and Cream.—The above calculations have dealt with problems which required the reduction of the fat content in milk or cream. It is frequently desired to raise the fat content of milk or cream, in which case it is necessary either to remove skim milk, to add cream, or to add milk or cream of a higher test; or to separate and remix the skim milk and cream. The procedures involve the same principles as those reviewed in reducing the fat content of milk or cream.

CALCULATIONS PERTAINING TO BUTTER

In the manufacture of butter, either on the farm or in the factory, certain calculations are essential to assist in the making of a uniform butter and in keeping the operator informed as to the results secured in churning. The common calculations

include the determination of the overrun secured in churning cream, the estimated yield of butter from cream on churning, and the determination of the amount of salt or color to add.

Problem 12. Calculation of Overrun in Butter Making.—When cream containing a definite amount of butter fat is churned, the amount of butter which results exceeds the butter fat. The reason for this is explained by the fact that butter contains in addition to butter fat, added salt, if salted butter is made, a small amount of curd, and water. The water content may amount to as much as 15.9 per cent of the total weight of the butter as previously referred to under the subject of butter making. The “overrun” is the term applied to the weight of butter which results in excess of the weight of butter fat churned. Overrun may be expressed in terms of pounds, or, as is usually the case, in terms of percentage. To calculate the percentage of overrun which results in churning cream, the pounds of butter in excess of the pounds of fat are first determined. By dividing the pounds of overrun by the pounds of fat churned, and by multiplying by 100, the percentage of overrun is secured.

For example, let it be assumed that 2,000 pounds of cream containing 30 per cent of fat or 600 pounds of fat yield 732 pounds of butter. To determine the pounds of overrun, the pounds of fat churned are subtracted from the pounds of butter which resulted. This subtraction reveals the fact that there are 132 pounds of overrun ($732 - 600 = 132$). By dividing the pounds of overrun (132), by the pounds of fat churned (600), and multiplying by 100, it is found that the overrun amounts to 22 per cent, ($132 \div 600 \times 100 = 22$).

Problem 13. To Determine the Overrun from the Composition of Butter. It is frequently desired to estimate the amount of overrun secured in the manufacturing of butter when only the fat content of the butter is known from an analysis made. The calculation assumes no loss of fat in churning. Assume, for example, that a sample of butter contains exactly 80 per cent of fat—the minimum fat content that butter may contain, according to the federal laws. This means that in 100 pounds of this butter there are 80 pounds of fat. Therefore, if 80 pounds of fat resulted in the making of 100 pounds of butter, the difference between 80 and 100, or 20, equals the pounds of overrun. The percentage of overrun is 25 ($(20 \div 80) \times 100 = 25$). It should be clearly understood, therefore, that the maximum overrun that can be secured in the making of legal butter is 25 per cent.

Problem 14. Estimating the Yield of Butter.—To estimate the yield of butter from the churn, it is essential, first, to estimate the overrun that is expected. The overrun expected is influenced by the composition of the butter and the loss of fat and butter in churning. Without going into a detailed discussion of these points, however, let it be assumed that an overrun of 22 per cent is expected on churning. If 200 pounds of fat are contained in the churn and 22 per cent overrun is expected, this will mean that 22 per cent of 200, or 44 pounds ($200 \times 0.22 = 44$) of overrun will be secured. By adding the pounds of overrun (44) to the pounds of fat in the churn (200) it is found that 244 pounds of butter are expected from the churn ($200 + 44 = 244$).

Problem 15. To Calculate the Amount of Salt to Add to Butter.—This is done in many different ways in the creamery and on the farm, as referred to under the subject of butter making. The amount of salt required, however, is first dependent upon the amount desired in the finished butter. If a butter containing 2.5 per cent of salt is desired, a slight excess of salt must be added to this amount, to maintain the percentage, as some of the salt is lost in the churn. The amount lost may amount to as much as 0.5 per cent in the large factory churns. This would mean that about 3 per cent of salt should be added, if the finished butter is to contain 2.5 per cent of salt. After determining the percentage of salt desired in the finished butter, calculate the amount of butter expected from the churn, as previously explained. If 400 pounds of butter are expected, it must contain 2.5 per cent of salt, or 10 pounds ($400 \times 0.025 = 10$). In addition, 0.5 per cent is to be added in excess, which means that 3 per cent, or 12 pounds of salt ($400 \times 0.03 = 12$) should be added.

After the above calculations and frequent analyses have been made, it is generally the practice in the creamery to reduce the salt calculation to a common figure, such as salt required per pound of butter expected, pounds of salt per pound of fat in churn, or the pounds of salt per can of cream in the churn. Reference was made to the common methods of determining the amount of salt required in making butter on the farm, under the subject of butter making.

Calculation of the Color Required.—Color is added to butter at the rate of a given amount to each pound of finished butter expected or, as in the case of the addition of salt, according to the fat or amount of cream present, the more accurate method being the first mentioned. One ounce, or a certain number of milliliters, or a fraction of an ounce, of color is added per 100 pounds of finished butter expected. The calculation required in this case is simple.

Problem 16. Neutralization of Milk or Cream.—The principle involved in the neutralization of milk or cream is based upon the chemical reaction which takes place when an alkali and an acid are brought together to form a salt. When an alkali such as lime hydrate ($\text{Ca}(\text{OH})_2$) is used as a neutralizer in milk or cream, the chemical reaction which takes place between the alkali and the lactic acid of milk is as follows:

The molecular weights of lactic acid and lime hydrate are 90 and 74, respectively. Since two molecules of lactic acid are required to neutralize one molecule of lime hydrate, it is apparent from the above equation that 180 grams ($90 \times 2 = 180$) of lactic acid are neutralized by 74 grams of lime hydrate.

If it is desired, therefore, to calculate the amount of lime hydrate required to neutralize 1 pound of lactic acid, a problem in proportion may be set up and calculated as follows:

$$\begin{aligned}
 180:74::1:x \\
 180x &= 74 \\
 -x &= 0.4111
 \end{aligned}$$

One pound of lactic acid is, therefore, completely neutralized by 0.4111 pound of lime hydrate.

The above calculation is correct when lactic acid is neutralized in water solutions and when the lime hydrate is chemically pure. For coarse work, such as is practiced in the creamery, it is assumed that the neutralizer used is 100 per cent chemically pure. It has been shown by Hunziker, however, that when lime is added to milk or cream, a portion of it attaches itself to the casein and about 20 per cent more lime than the theoretical calculation indicates is required to accomplish the desired results in practice.

Therefore, if in water solutions, 1 pound of lactic acid is neutralized by 0.4111 pound of lime hydrate, in milk or cream there would be required 20 per cent more lime, or an excess of 0.08222 pound

$$(0.4111 \times 0.20 = 0.08222);$$

or a total of 0.4933 pound of lime hydrate ($0.4111 + 0.0822 = 0.4933$).

Problem 17. When the above facts are available, the calculations in the creamery are simplified. Let it be assumed that it is desired to reduce the acidity of 2,000 pounds of cream with an acidity of 0.50 per cent to an acidity of 0.20 per cent. It appears, therefore, that the acidity is to be reduced by 0.30 per cent ($0.50 - 0.20 = 0.30$). If 0.30 per cent of lactic acid is to be reduced in 2,000 pounds of cream it is apparent that 6 pounds of lactic acid are to be neutralized ($2,000 \times 0.003 = 6$). From the above calculations it was shown that 0.4933 pound of lime hydrate will neutralize 1 pound of lactic acid in milk or cream. If this is true, it is evident that 2.9598 pounds ($6 \times 0.4933 = 2.9598$) of lime hydrate will be required to neutralize 6 pounds of lactic acid.

Neutralizers are not added to milk or cream in the dry form, but are diluted in water. A 20 per cent solution of the neutralizer is frequently used. In the above calculation, therefore, it would be essential to make a 20 per cent solution of the 2.9598 pounds of lime hydrate before it is added to the cream. This would mean that the lime hydrate should be made up to 14.799 pounds ($2.9598 \div 0.20 = 14.799$), with water, in the above calculation.

To calculate similar problems, as described above, using different neutralizers, it is only essential to follow the same procedure, taking into account their molecular weights in determining the amount of each required to neutralize 1 pound of lactic acid.

ICE CREAM

The calculations required in the manufacture of ice cream are more complex than are those discussed heretofore. Reference is made to the calculation of the ice-cream mix under the subject of ice-cream manufacture. It is possible, however, to calculate the composition of an ice-cream mix if the ingredients used

are known. Frequently, in small ice-cream factories where a given formula is used, it is desirable to make such a calculation. No facilities may be available for chemical analysis, but the milk ingredients purchased are bought according to a guaranteed composition.

Problem 18. To Determine the Composition of an Ice-cream Mix.—For convenience in calculating the composition of an ice-cream mix, construct a chart and list along the left-hand side the ingredients used in the mix, indicating their composition and the amount of each used. For example, let it be assumed that an ice-cream manufacturer is using a mix consisting of 211.42 pounds of 40 per cent cream; 231.2 pounds of plain condensed whole milk containing 11 per cent fat and 35 per cent total solids; skim milk which contains about 9.2 per cent total solids; sugar; and gelatin. Gelatin is calculated as containing 100 per cent total solids. The fat and total solids of each ingredient are calculated and classified as indicated below. The total of the mixture is then secured and the total fat, total solids, sugar, and gelatin determined. By dividing each of these by the total pounds in the mix and multiplying by 100, the percentage of each is calculated.

Ingredient	Pounds	Pounds, fat	Pounds, total solids	Pounds, sugar	Pounds, gelatin
Cream, 40 per cent fat, 45 per cent total solids.....	211.42	84.57	96.24		
Plain condensed whole milk, 11 per cent fat and 35 per cent total solids	231.20	25.43	80.92		
Skim milk, 9.2 per cent total solids.....	412.38		37.88		
Sugar, 100 per cent.....	140.00		140.00	140.00	
Gelatin, 100 per cent.....	5.00		5.00		5.00
Total.....	1,000.00	110.00	360.04	140.00	5.00
Per cent.....		11	36	14	5

In the above problem the total solids in the cream are given. If the analysis is not available, subtract the pounds of fat in the cream from the total pounds of cream and calculate pounds of solids-not-fat using the average composition of skim milk as the percentage of serum solids present.

Overrun in Ice Cream.—The overrun in ice cream is based upon the increased volume of ice cream over that of the ice-cream mix.

The ice cream, however, owing to its physical nature, readily takes up air in handling. This makes it difficult to secure an accurately measured sample. It is, therefore, more common to determine the overrun on the basis of the weight of a given volume of ice-cream mix as compared with the weight of a given volume of the finished ice cream. To illustrate, assume that 1 gallon of ice-cream mix weighs 9 pounds, and after freezing, 1 gallon of the finished ice cream weighs 5 pounds. If the difference in weight of 1 gallon of mix and 1 gallon of finished ice cream is divided by the weight of 1 gallon of finished ice cream, and multiplied by 100, it is found that the overrun secured in this case is 80 per cent ($9 - 5 = 4$, $(4 \div 5) \times 100 = 80$).

CHAPTER XV

MISCELLANEOUS TESTS

SAMPLING MILK AND CREAM

Milk and its products are subjected to chemical analysis probably more frequently than any food product. Of the analyses conducted on milk and cream, the butter-fat determination is the most common. The practice of paying for milk or cream upon the basis of the butter-fat content has become common in every section of America. In addition to the butter-fat analysis, however, milk and cream are frequently analyzed by commercial plants such as ice-cream factories, condensaries, and dry-milk plants for total milk solids. Not infrequently, when milk is bought and sold, it is subjected to tests which are designed to determine sanitary methods employed in the production and handling, the addition of preservatives or water, the ability of milk to withstand heat, etc. For each test to which milk is subjected, a small representative sample must be secured. Although the material, here presented, deals, primarily, with the sampling of milk for the butter-fat analysis, the reader should realize that the same precautions which are cited in the sampling of milk or cream for the butter-fat analysis are equally important in sampling milk for other purposes.

Importance of Sampling.—In plants handling market milk or manufacturing the various milk products, a single butter-fat analysis may be the means of determining the butter-fat content of hundreds or thousands of pounds of milk or cream. A single test may involve hundreds of dollars' worth of the product. The importance, therefore, of securing an accurate and representative sample of milk or cream for analysis cannot be over-emphasized. The greatest errors which occur in the testing of milk or cream do not occur in the operation of the Babcock test, but in the failure to secure a representative sample of the milk or cream to be analyzed.

How to Secure a Sample.—Due to the difference in specific gravity between the milk serum and the fat of milk, the fat

globules are continually rising towards the surface of milk or cream, and these products must be thoroughly mixed before a sample is taken for analysis. On the farm, the milk of an individual cow may be poured from one pail to another and a small sample of milk secured immediately. When larger volumes of milk are handled on the farm, the milk or cream should be thoroughly mixed by means of some device, such as a milk- and cream-stirrer, as is done in the receiving room of the manufacturing or milk plant.

It is exceedingly difficult to secure a representative sample of a given milk or cream when large volumes of it have been dumped into vats or pasteurizers. A small sample should then be taken at three or more different places in the vat. A sampling dipper may be used, or else a sampling tube, made for this purpose. For best results, milk and cream should be sampled when they are at a temperature between 60 and 90°F. (15.7 to 32.2°C.). If too cold, cream will be thick and viscous, and will be difficult to sample. Milk is more readily sampled at low temperatures than cream, as it does not become so viscous as the latter.

Sampling Frozen Milk or Cream.—Reference was made previously to the manner in which milk or cream freezes. If frozen milk is sampled for analysis, and only the unfrozen portion secured in the sample, such a portion will contain the solids of milk, including the fat, in a more highly concentrated form than occurs in normal unfrozen milk.

This is also true of thin cream or cream containing less than 30 per cent of milk fat. By warming frozen milk or thin cream, the frozen portion will melt, after which a sample for analysis may be secured. Should such milk or cream be solidly frozen, extreme care must be exercised in thawing. Sudden warming of such cream will encourage "oiling off" of milk fat. Under these conditions it is very difficult to secure an accurate sample.

When cream containing 30 per cent or more of fat is frozen, a sample of the liquid portion offers a representative sample. Thawing of such cream is not necessary to secure an accurate sample. When solidly frozen, such cream may be sampled by scraping the top surface to the solid cream and chipping the frozen cream. The frozen chips should be weighed into the test bottle before melting if an accurate test of the sample is to be secured.

Sampling Churned Milk or Cream.—It is exceedingly difficult to secure a representative sample from milk or cream if the fat has partially churned. As a matter of fact, many commercial plants refuse to pay for milk or cream on the basis of a fat test made from such milk or cream. A reasonably accurate sample may be secured, however, if the product is heated to a temperature of 100 to 110°F. (37.8 to 43.3°C.) or to a point sufficiently high to melt the churned fat granules, and then agitated vigorously and a sample removed immediately. This same procedure may be followed in attempting to sample milk or cream over which a "cream plug" or a layer of partially churned fat appears.

Sampling Sour Milk or Cream.—Sour milk or cream, in which coagulated casein is present, frequently must be sampled. Milk may be stirred thoroughly, agitated, and a sample removed as in sampling sweet milk. If the milk has stood for a period of time, however, and the cream which has formed has had an opportunity to dry over a part of the surface a tough layer which is very difficult to break and to distribute evenly, forms at this point. By warming the milk slightly during agitation, the butter fat may be liquefied and a sample secured.

Sour cream offers much the same difficulty as sour milk, and it frequently happens that some butter fat is interlocked with the coagulated casein. Lumps of curd should be broken down as finely as possible, during the warming of such cream, and a sample secured after thorough agitation. In the creamery receiving sour cream, the practice often followed is to agitate the sample thoroughly, and to use the so-called "McKay sampling" tube for securing the sample.

Preserving the Sample.—Samples of milk for certain analyses may be preserved, until the time for making the determination, by adding such preservatives as corrosive sublimate, formalin, and bichromate of potash. For general analytical work formalin is to be preferred, as bichromate of potash and corrosive sublimate add to the solids of milk and, thus, influence analyses involving the total solids. These preservatives, however, serve when milk or cream is to be preserved for butter-fat analysis. The preservatives will be referred to more fully, elsewhere.

COMPOSITE MILK SAMPLE

A composite milk sample is one which, when properly prepared, represents two or more lots of milk. When it is desired to make one analysis which will be representative of all milk sampled,

the sample is prepared by mixing small samples of milk from different lots of milk, in one container. For extremely accurate results, the amount of milk constituting each sample going into the composite must be in proportion to the amount of milk involved. The purpose of such a sample is obviously to reduce the number of analyses. It may be used in preparing milk samples for all types of chemical analysis where it is desired to secure one figure to represent all lots examined. It is used extensively, by milk producers, in connection with the records of the production of individual cows. A common plan is to prepare a composite sample covering 3 days each month.

Even wider use of the composite test is made in connection with the purchase of milk at creameries, cheese factories, condensaries, and milk-receiving stations. To make certain of the quality of the milk received, the operator must make a daily butter-fat test of the milk delivered by each patron, or prepare a sample to which each delivery will contribute, and test this at intervals. As a rule, the period covered, when milk is purchased by the test, is either 1 or 2 weeks. The labor saved, by the composite sampling system used in this manner, is clearly considerable. A man with suitable equipment can test about 150 samples in a day. Where milk is received from 150 producers daily, practically the full time of one man would be required to perform the tests.

The equipment required for preparing composite samples, methods of taking the sample, preservatives used, and the application of the method of sampling cream are discussed in the following paragraphs.

Equipment Required.—The equipment required for preparing a composite sample is an air-tight jar, a sampling tube or dipper, and a suitable preservative. Any type of container may be used provided it is air tight. As milk contains a high percentage of water, evaporation of moisture will occur readily if exposed to the air. If moisture escapes, the milk will become more concentrated and the fat reading obtained, consequently, will be too high.

FIG. 84.—The composite sample bottle. A wide-mouthed bottle with a rubber stopper has been shown to be the most reliable and practical container for holding the composite milk or cream sample.

The Sample Container.—In making preparations to take composite samples either at the creamery or at the dairy farm, it is necessary to provide at least one sample container for each milk patron or each cow in the herd. These containers should be labeled permanently. This can be done by using a metal tag on which is stamped a number and which can be attached to the container by means of a wire. A gummed label may be used by coating the label with white shellac, after it is pasted on the bottle, so as to prevent its soaking off during washing.

In the factory, a rack should be provided for holding the composite samples. The containers should be arranged in a definite order in the rack so that time may be saved by the worker in placing the sample in the container. This rack should be placed in a convenient location and care should be taken that it is not exposed to direct sunlight.

Taking the Sample.—The sample of milk to be used as part of the composite is taken either with a sampling tube or with a small dipper. The object of using a sampling tube is to regulate the quantity of milk taken in proportion to the amount of milk sampled. The reason for this will be readily understood. If the same amount of milk were sampled each time, a dipper which holds a definite quantity would be satisfactory. For example, suppose three lots of milk of 100 pounds each were sampled:

Pounds, milk	Percentage, fat	Pounds, fat
100	3	3
100	5	5
100	6	6

The fat percentage in the composite sample would be 4.66, which is clearly correct. Suppose, however, in place of the three lots of milk each weighing 100 pounds there were considerable variations in the weights of the milk sampled:

Pounds, milk	Percentage, fat	Pounds, fat
500	3	15
200	5	10
50	6	3

In this case, a composite sample, made by taking the same quantity from each lot, would give the same result, a direct average of the fat percentage in the three lots, namely 4.66. If this figure is used, however, apparently 36.35 pounds of fat were delivered. As a matter of fact, the actual amount would be 28 pounds. Had, however, the sample been made up by using a sampling tube, the amount taken from each delivery would be in proportion to the amount delivered, and the average test would not have been 4.66, but the correct figure, 3.86.

The Dipper Method.—As indicated, a small dipper with a capacity of 1 ounce is sometimes used. As this plan results in taking the same quantity regardless of the amount of milk sampled, it should not be used when there is much variation in the amount of milk sample—or when wide variations occur in the fat percentages from one lot to another. The practical question often arises regarding the seriousness of the errors resulting from the use of this convenient method in sampling daily deliveries of milk delivered by milk patrons to the milk plant, creamery, cheese factory, or condensary. It should be recalled that, although there is some variation in the percentage of fat of individual cows, there is very little variation in the percentage of fat in the mixed milk from a herd from day to day. Practical experience as well as experimental evidence teaches that for all practical purposes the sampling dipper may be used with all the assurance of accuracy desired when it is used on mixed herd milk, when the milk is properly stirred before taking the sample, and when equivalent amounts are involved each day.

The Sampling Tube.—There are on the market several different types of milk-sampling tubes, all of which, when properly used, will result in the securing of an accurate sample. There are two distinct advantages of the sampling tube over the dipper method of securing the sample for the composite: (1) The sampling tube results in the securing of the sample in aliquot portions, as the amount taken always represents the same fraction of the quantity of milk sampled. (The container holding the milk should have straight sides and be of equal diameter throughout.) (2) The sampling tube provides a fairly representative sample regardless of how long the milk may have stood before sampling, since by this method a column of milk which represents the milk from top to bottom is removed from the container.

Preservatives for the Composite Sample.—If the composite milk sample is to be successful, the milk must be kept sweet during the period while the sample is being assembled. This is accomplished by the use of a preservative. It is a good plan to place the preservative in the empty bottle before milk is added. Several preservatives are used:

FIG. 85.—Milk- and cream-sampling equipment. At the left is shown a common milk- or cream-stirring rod with which the sample may be stirred and a sample removed. The small dippers are commonly used for removing milk samples in plants receiving milk. The McKay sampler at the right is shown in separate parts, and as it appears when ready for use.

Corrosive Sublimate.—Mercuric chloride or corrosive sublimate is one of the strongest preservatives used for this purpose. A comparatively small amount will keep milk from souring and decomposing for such time as is necessary in using the composite-test system. As this chemical is highly poisonous, the common practice is to add a dye, usually bright red, in order to prevent some one from using the preserved milk by mistake for food. This preservative is prepared in tablets containing a definite amount, together with coloring material. The presence of the corrosive sublimate does not interfere with the Babcock method.

Formalin.—Formalin (40 per cent solution of formaldehyde) is a very effective antiseptic and preservative. Since formalin comes in a liquid form, it is very convenient to handle. Approximately 1 milliliter or 28 drops will serve as a preservative for 1 quart of milk for a week or more. One objection often raised against the use of formalin is that it causes a hardening of the casein of milk, thus making it more difficult to test. This same objection may be offered against corrosive sublimate if it is used in excessive amounts. If, however, during the operation of the Babcock test, a little more time is given for the action of the acid on the casein, very little trouble will be experienced from the use of either of these preservatives. Formalin, like corrosive sublimate, is inexpensive.

Bichromate of Potash.—Potassium bichromate or bichromate of potash comes in powder or tablet form. Although not so effective as corrosive sublimate or formalin, this preservative has certain advantages. It colors the milk a deep yellow without the addition of extra coloring material. Further, it is not so violent a poison and, therefore, not so dangerous to handle. It has several decided disadvantages, however, compared with formalin and corrosive sublimate, and is seldom used.

Composite Cream Sample.—It is conceded that composite samples should not be made from thick sour cream. Cream which has soured and become extremely viscous is too difficult to sample and cannot be readily measured with the ordinary equipment available or in use. It has been shown, however, at the Minnesota Experiment Station that with sweet cream the composite-sample system is equally as accurate as daily testing. As a matter of fact, the work at that station hints that inaccuracy is more apt to occur where a daily cream sample is tested than when a composite is tested, because of the possible error in reading the cream test several times during a given period, compared with one reading, as is the practice when the composite sample is used.

Care of the Composite Sample.—The most important precaution is to use containers that are completely air tight. Glass-stoppered bottles, often assumed to be the best, have been found unsuitable, as the stoppers do not fit tightly enough to prevent evaporation. Cork stoppers absorb fat from the sample and are, therefore, undesirable. The best stoppers to use are those of rubber. The samples should be kept in a cool place, away from

direct sunlight. There is little danger of evaporation during the fall and spring months, but during the winter months, it is advisable to guard against keeping the samples in warm, dry rooms or close to the radiators, etc., used in heating the rooms. In some localities, the temperature of the room may become excessively high in the summer, making it advisable to place the samples in a cooler place. The sample should be agitated, on the addition of a new sample, to prevent the drying of milk on the sides of the container.

Testing the Composite Sample.—Care should be taken in testing the composite sample to make sure that fat is thoroughly and evenly distributed throughout the sample. Care should also be taken to avoid the formation of masses of cream which must be melted. The sample bottle should be placed in a water bath at 90 to 100°F. (32.2 to 37.8°C.) for a few minutes, in order to make possible a thorough distribution of the fat on agitation.

MODIFIED BABCOCK TESTS

Testing Butter by the Babcock Method.—A modification of the Babcock method sometimes is applied to butter. For this purpose, butter-test bottles capable of reading up to 90 per cent are used. In conducting this test, 6 grams of butter ordinarily are used, although some bottles are made for testing a 9-gram sample. The butter sample is prepared for analysis by warming it slowly and at the same time stirring it gently with a glass rod until the butter reaches a pasty consistency. Six or more grams of the prepared sample are weighed into a test bottle by means of a cream balance. By inserting a small funnel in the neck of the bottle, this can be accomplished more readily. The butter is slowly melted by holding it close to a free flame, the melted material being allowed to flow from the funnel into the test bottle. Ten to fifteen milliliters of warm water (120°F.) (48.9°C.) are used to wash the clinging fat into the bottle. Sulfuric acid is carefully added with constant shaking, until a light brown color is obtained. This should require less acid than the ordinary cream test. The tests are then centrifuged and handled in the same manner as cream tests.

Testing Cheese by the Babcock Method.—Cheese samples are chopped finely and 9 grams of the cut material are weighed into a 9-gram, 50 per cent, cream-test bottle (18 grams may be used in an 18-gram, 50 per cent bottle). Boiling water to the amount of

9 milliliters is added and the mixture is agitated thoroughly. Next, sulfuric acid is added in small portions, with careful shaking after each addition, until the cheese curd entirely disappears and a dark-brown mixture is obtained. The test is then completed as an ordinary cream test.

Testing Ice Cream.—The most successful modification of the Babcock test for ice cream is that devised by Crowe. Two reagents are employed, designated as *A* and *B*. Reagent *A* consists of 90 milliliters of normal butyl alcohol and 10 milliliters of ammonium hydroxide (chemically pure). Reagent *B* consists of a mixture of equal parts of sulfuric acid, specific gravity 1.82 to 1.83, and ethyl alcohol (95 per cent, Formula number 30). This mixture is prepared by carefully pouring the acid down the side of a beaker containing the alcohol. The beaker must be one that will withstand high temperatures. Both reagents must be kept in tightly stoppered bottles.

The ice-cream sample is melted and 9 grams weighed into a 10 per cent Babcock milk-test bottle. Five milliliters of reagent *A* are added to the bottle and mixed thoroughly. Following the addition of reagent *A*, 30 milliliters of reagent *B* are added and the contents of the bottle again mixed.

The bottle is then placed in a water bath at 175 to 180°F. (79.44 to 82.22°C.) for 15 minutes, shaking at intervals. It is then centrifuged in the Babcock tester for 5, 3, and 1 minute, adding water after the 5- and 3-minute periods at 180°F. (82.22°C.). The reading is multiplied by 2, since a 9-gram sample was used in an 18-gram bottle.

A modification of the Babcock test intended for use in the determination of butter fat in ice cream was introduced by Garrett and Overman. The test, as suggested by them, is conducted as follows: Weigh into a Babcock milk-test bottle 9 grams of the ice cream to be tested. To this add, from a graduated pipette, exactly 0.8 milliliter of normal butyl alcohol.

Nine milliliters of a salt solution consisting of 200 grams of trisodium phosphate, 200 grams of sodium salicylate made up to 1 liter with a mixture of 3 volumes of ammonium hydroxide, and 7 volumes of water, prepared and warmed before using, are then added and thoroughly mixed with the sample. All small lumps of curd should be entirely dissolved. The Babcock bottle containing the sample is then placed in a water bath at 160 to 190°F. (71.1 to 87.8°C.) for 15 or 20 minutes, shaking the

bottle well two or three times while heating. A clear layer of fat will appear on the surface of the solution in the test bottle. The sample is then centrifuged at a high speed (1,000 to 1,200 r.p.m. in a 22-inch Babcock tester) for 5 minutes. Hot water is then added to the bottle to a point at the base of the neck of the Babcock bottle. The sample is whirled again for 5 minutes and sufficient hot water again added to bring the fat column into the graduated neck of the test bottle. The third whirling period is for 3 minutes. Before the test is read, the bottles should be placed in a water bath as is the procedure in conducting the Babcock test.

The Garrett-Overman test is adapted for use in testing ice cream. The test is more easily conducted, however, if the butyl alcohol is added first to the test bottle and then the salts added in sufficient amounts (excess alkali required) in the dry state, followed with the ammonium hydroxide. An elongated funnel such as might be constructed from an ordinary 17.6-milliliter milk pipette may serve to conduct the compounds used into the bottle.

Testing Condensed Milk.—Condensed milks are manufactured to contain from 28 to 34 per cent, or more, of total milk solids. Some condensed milks, known as sweetened condensed milks, contain added sugar, which makes them as difficult to test as ice cream. The Babcock test may be applied to the evaporated or unsweetened condensed milks, although it is apt to give poor results. In general, other methods, or extensive modifications of the Babcock method, must be used to give reliable results.

Testing Dry Milk.—The Babcock method may be used for determining the fat content of dry milk. The procedure is to dissolve 10 grams of dry milk in 90 milliliters of water. This mixture is warmed and mixed until a complete solution is effected. This is tested as milk and the result multiplied by 10.

THE CALIBRATION OF BABCOCK TESTING GLASSWARE

Calibration of Glassware.—In the early years, following the introduction of the Babcock test, inaccurately calibrated glassware was not uncommon. At present, only a small percentage of that put on the market is open to this objection. To help ensure the conditions necessary for accurate results, however, the laws of several states require that Babcock glassware sold within their

boundaries be tested for accuracy of graduation. This often is done by the state experiment station at a small charge. Where this law is in force, companies selling glassware usually keep on hand a quantity of glassware which has been tested and stamped in accordance with the state law. Large individual users of testing apparatus also, at times, calibrate the glassware in use. Several methods are used but in all the first requirement is that the bottle shall be cleaned thoroughly, and shall be not merely apparently clean, but chemically clean.

With new glassware it usually is sufficient to wash with potassium bichromate cleaning solution and then to rinse several times with distilled water. Glassware that already has been used, should be washed in a strong alkaline cleaning solution prepared by adding some common dairy cleaning powder to warm water. A brush should be used for this cleaning, particularly on the necks of the bottles. After rinsing, the glassware should be washed out with potassium dichromate cleaning solution and finally with distilled water.

Use of Plunger.—One of the methods makes use of a small brass plunger. The thoroughly cleaned bottles are filled to the zero mark with a suitable liquid. (Many prefer a colored alcohol or water.) The plunger is made to give the correct volume at 70°F. (21.1°C.). For this reason, both the liquid and the plunger should be subjected to a temperature of 70°F. (21.1°C.) for some time before the work is begun. The procedure is to fill the bottle to a point slightly above the zero per cent mark with the liquid chosen, next carefully drying the inside of the neck by means of strips of blotting paper. By means of the blotter, sufficient liquid to bring the lower part of the meniscus (bottom of curved surface of liquid) exactly to the zero mark, is absorbed. The lower half of the brass plug is inserted in the liquid. The lower part of the meniscus should stand at the half-way mark on the scale; *viz.*, at the 4 per cent for the 8 per cent milk bottle, or at 25 per cent for the 50 per cent cream bottle.

FIG. 86.—Apparatus for calibrating milk-test bottles. By inserting the plunger into a Babcock test bottle previously filled to the zero mark, the accuracy of the graduations is determined.

The upper half of the plunger should be lowered into the bottle. The reading is then taken at the highest mark on the scale. If higher or lower than this mark, the bottle is inaccurate and, if the variation is greater than the amount of one of the smallest divisions on the scale, the bottle is not considered accurate enough to use. The tolerances for Babcock test bottles are recognized as follows:

- 8 per cent milk test bottle, 0.1 per cent.
- 10 per cent milk test bottle, 0.1 per cent.
- 50 per cent cream test bottle, 0.5 per cent.
- Skimmed-milk test bottle, 0.01 per cent.

Calibrating with Water.—A satisfactory method is to add water to the bottles from a small accurately graduated burette. In this case, as in that of the brass plunger method, the bottles are filled to the zero mark and the interior of the necks of the bottles dried with the blotter paper. The amount of liquid which should fill exactly the calibrated portion of the neck is added accurately by means of the burette. The level of the liquid then should coincide with the upper mark on the scale. This method is not satisfactory, as a means of calibrating the skim-milk bottle, because it is impossible to measure accurately the small amount of water needed; also, it is mechanically impossible to introduce the water directly into the small graduated neck.

Use of Mercury.—Mercury may be used for measuring the volume of the graduation of test bottles and for this purpose generally is considered more satisfactory than water. The bottles to be tested must be perfectly clean and entirely dry. The amount of mercury needed is weighed out on an analytical balance. Mercury has a specific gravity of 13.5471 at 68°F. (20°C.) and this figure is used in determining the weight necessary to yield the correct volume for the graduations of the scale on the particular type of bottle to be tested. The correct amount of mercury is weighed out and poured into the bottle to be tested. A tightly fitting stopper is pressed in with one end at the upper point in the graduated scale. The bottle is then inverted and the accuracy of the graduated scale determined by noting if the mercury fills the volume from the lowest to the highest points. If care is used, the same mercury may be used for a great many determinations with only occasional reweighing

to insure correctness. The mercury method is faster than the others when many bottles are to be tested. In addition, it has the advantage of being the most accurate.

The method of calibrating the skim-milk test bottle differs from that described for other types in that no stopper is used. The carefully weighed mercury is allowed to flow into the small tube and is kept there by placing the finger at the top of the tube, much as one handles a pipette.

ROESE-GOTTLIEB FAT ANALYSIS

In milk condensaries, dry-milk, and ice-cream plants where large volumes of milk are handled, it is frequently necessary to determine the butter-fat content with extreme care. The equipment used frequently in these plants is known as the "Mojonnier tester" which is used in connection with a modification and a simplification of the Roese-Gottlieb method.

This method consists (see Appendix) of extracting the fat from the dairy product with ether. To the sample is first added, however, strong ammonium hydroxide which dissolves the casein, neutralizes the acid present, and reduces the viscosity. Following the ammonia, a quantity of 95 per cent alcohol is added to the sample to prevent the formation of a gelatinous mixture which occurs when ether is shaken with milk. To the sample is then added ether in which butter fat is soluble. Other milk solids-not-fat present in the ether solution are eliminated by the addition of petroleum ether to the sample. The solution of ether and fat is then poured off into an evaporating dish, the ether driven off by heat, and the ether extract weighed and reported as butter fat.

THE DETERMINATION OF SPECIFIC GRAVITY

Specific gravity is the relation between the weight of a given volume of any substance and an equal volume of water at the same temperature. One milliliter of water at 39.2°F. (4°C.) weighs 1 gram; therefore, when a liquid is at a temperature of 39.2°F. (4°C.), its specific gravity is the weight in grams of 1 milliliter. It has been determined that the specific gravity of milk averages 1.032, so it is clear that 1 milliliter of milk weighs 1.032 grams.

Since the weight of a given volume of water at a given temperature is known, it is possible to calculate, from the weight, the volume of milk or cream, or from the volume, the weight upon

the basis of the specific gravity of the substance, as illustrated in the following example:

One gallon of water at 39.2°F. (4°C.) weighs 8.3 pounds and since the average specific gravity of milk is 1.032, 1 gallon of average milk will weigh 8.3×1.032 , or 8.56 pounds. The approximate specific gravity and weight per gallon of a number of milk products are as follows:

SPECIFIC GRAVITY AND WEIGHT PER GALLON OF CERTAIN MILK PRODUCTS

Product	Approximate specific gravity	Weight per gallon, pounds
Milk.....	1.032	8.56
Butter fat.....	0.93	7.72
Skim milk.....	1.036	8.60
Buttermilk.....	1.035	8.59
Cream:		
20 per cent fat.....	1.006	8.48
30 per cent fat.....	0.996	8.43
40 per cent fat.....	0.977	8.38
50 per cent fat.....	0.962	7.98

Value of Specific-gravity Determinations.—It is distinctly advantageous in many instances to determine the specific gravity of milk. The percentage of total solids and solids-not-fat in a given milk can be estimated with reasonable accuracy if the specific gravity and fat percentage are known. This fact is widely used in the condensed and dried milk industries, where the yield of products is estimated from the total solids content of the milk. In condensing milk, the progress of concentration is observed by making specific-gravity readings of the milk.

The specific gravity may be used also as an indication of adulteration of milk with water, but not as definite proof of such irregularity. Some years ago, low specific gravity of milk was accepted as definite proof that water had been added. Now, however, it is recognized that milk is not necessarily adulterated, even though its specific gravity is low. When milk with low specific gravity is encountered, it should be considered suspicious, and should be tested for watering, by a more accurate method.

The Lactometer.—According to definition, the determination of the specific gravity of milk requires that we determine the weight relationship of equal volumes of milk and water at the

same temperature. In a practical way, this could be done by weighing water in a can filled level full and then refilling the can with milk at the same temperature as the water and reweighing. If the water weighed 62 pounds, and the milk 64 pounds, the relationship would be $64 \div 62 = 1.032$.

As a matter of convenience, the specific gravity of milk usually is determined with a lactometer. The lactometer is a hydrometer with a scale adapted to the limits of the specific gravity of milk. Any hydrometer works on the principle that a body floating in a liquid sinks to such a level that it displaces a volume of liquid equal in weight to the floating body. In liquids of low specific gravity, the hydrometer sinks farther before displacing a great enough volume of the liquid to equal its own weight than in a liquid of higher specific gravity. Thus a scale may be placed on the stem of the hydrometer so as to read the specific gravity directly at the point level with the liquid floating the hydrometer. The lactometer is weighted to float in milk and its scale is especially adapted to the range of specific gravities of milk.

To determine specific gravity by means of the lactometer, bring a sample of the milk to be tested to a temperature between 50 and 70°F. (10 to 21.1°C.). Place the milk in a tall cylinder and lower the clean lactometer gently into the milk. Allow the lactometer to float until it reaches equilibrium and then read the scale at the point level with the surface of the milk. Inasmuch as a correction must be made for temperatures above or below 60°F. (15.6°C.), it is necessary to determine the temperature at the time of reading the lactometer. Both determinations should be recorded.

Types of Lactometers.—Several types of scales are used on lactometers. The Quevenne, New York Board of Health, and

FIG. 87.—The lactometer. The lactometer may be used in connection with the Babcock test for estimating the total solids of milk. It is often used as an aid in detecting the adulteration of milk by water.

Baumé lactometers all carry different scales the reading of each of which may be converted into specific gravity by a simple calculation. The Quevenne lactometer has been the most widely used of the three because its reading is most readily converted into specific gravity. For this reason, the reading of the Quevenne lactometer is described here.

Correction for Temperature.—The scale of the Quevenne lactometer is graduated from 15 to 40. Readings on this scale are known as “lactometer degrees” and designated by *L*. To determine the specific gravity it is first necessary to correct the lactometer reading for a temperature of 60°F. (15.6°C.). For each degree Fahrenheit above 60° (15.6°C.), 0.1 must be added to the lactometer reading, while for each degree below 60°F. (15.6°C.), 0.1 must be subtracted. This correction cannot be made accurately if the temperature is lower than 50°F. (10°C.), or higher than 70°F. (21.1°C.). The reading, corrected for temperature, is usually designated as corrected lactometer reading (*Corr. L*) and is used for calculating either specific gravity or total solids.

Calculation of Specific Gravity.—The specific gravity of a milk is calculated from its corrected lactometer reading by dividing by 1,000 and adding 1. Thus, if the corrected reading were 32.5, calculate as follows:

$$\text{Corr. } L = 32.5.$$

$$\text{Specific gravity} = \frac{32.5}{1,000} + 1 = 1.0325.$$

It is seen that the corrected lactometer reading really constitutes the last figures of the specific gravity and that no calculation is necessary if 1.0 is placed before the corrected reading.

Calculation of Total Solids.—The total solids content of milk may be estimated also from the corrected lactometer reading. In skim milk, the percentage of total solids is approximately one-fourth of the corrected lactometer reading. However, in whole milk the fat causes a decrease in the lactometer reading but an increase in the total solids. Furthermore, the percentage of solids-not-fat increases about 0.2 for each 1 per cent fat. Therefore, the following formula has been found to yield approximately correct results for determining the percentage of total solids:

$$T.S. = \frac{\text{corr. } L}{4} + (1.2 \times \text{per cent fat}).$$

Example.—Assume a corrected reading of 32 and a percentage fat content of 4.

Then,

$$T.S. = 3\frac{1}{4} + (1.2 \times 4) = 12.8 \text{ per cent.}$$

The percentage of solids-not-fat quite obviously is equal to the percentage of total solids minus the percentage of fat. Therefore, the following formula may be used to calculate the percentage of solids-not-fat:

$$S.N.F. = \frac{\text{corr. } L}{4} + (0.2 \times \text{per cent fat}).$$

Using previous example,

$$S.N.F. = 3\frac{1}{4} + (0.2 \times 4) = 8.8.$$

THE DETERMINATION OF ACIDITY IN MILK AND ITS PRODUCTS

The production of acid in milk is commonly termed "souring," and the sour taste of such milk is due to the presence of lactic acid. As has been pointed out elsewhere in this text, the souring of milk is caused by the action of bacteria which break down lactose to form lactic acid. The percentage of acid present in dairy products at any time is, therefore, a rough indication of the age and manner in which the milk has been handled previously.

When the acidity of milk is determined by titration against an alkali, however, a part of the substances that neutralize the alkali are compounds other than lactic acid. If a regular acidity test is made of perfectly fresh milk, in which no lactic acid has been formed, an appreciable amount of acid-reacting substances will be detected. This reaction is due, partly, to certain acid salts of milk and, partly, to the alkali-binding capacity of the milk proteins. The amount of these substances in milk is equivalent in acid properties to from 0.10 to 0.18 per cent lactic acid. The titratable acidity of fresh milk usually is called natural acidity, and a milk showing less than 0.18 per cent titratable acidity, calculated as lactic acid, is looked upon as fresh and unfermented.

Use of the Acidity Test.—The acidity test is of great value in grading milk and cream. Many of the microorganisms common

to milk produce lactic acid from lactose, if held at favorable temperatures, and the determination of the lactic-acid percentage in cream is, therefore, a quick and practical means of differentiating between the products that have been well cared for, and those in which microbial action has been permitted. Many cream and milk buyers use the acidity test as one of the indices of quality in the products they purchase. It must be understood, however, that the acidity test is not the only index of quality in milk and cream. Disgusting odors and flavors are not detected by the acidity test, but are readily noted by the senses of taste and smell.

Use of Acidity Test in Dairy Manufactures.—The acidity test finds many uses in controlling the manufacture of dairy products. One of its common applications is in the making of Cheddar cheese, in which the proper time to begin each successive step in the process of manufacture is indicated principally by the percentage of lactic acid developed. The butter industry finds a good use for this test in the handling of sour cream in preparation for churning. Before such cream can be pasteurized successfully the lactic acid must be neutralized and, in order to determine the correct amount of neutralizer to use in a given batch of sour cream, it is necessary to know the percentage of acid present. With the aid of the acidity test it is possible to neutralize sour cream to any desired point very accurately. Still further use of the acidity test is found in the technical control of ice cream and condensed milk. Also, some organizations make a specialty of selling fermented milk drinks. The success in manufacturing these beverages is dependent on controlling the fermentation, and, in many cases, the acidity serves as an indication of the degree of development so that the procedure in making the drinks also can be controlled accurately.

Basis of the Acidity Test.—The determination of the acidity of milk by titration with a tenth-normal solution of an alkali, such as sodium hydroxide, is based upon the fact that a given volume of a tenth-normal solution of an alkali will exactly neutralize an equal volume of a tenth-normal solution of an acid. In other words, each milliliter of a tenth-normal solution of sodium hydroxide (which contains 4.001 grams in 1 liter of water) will neutralize 1 milliliter of a tenth-normal solution of lactic acid (which contains 9.006 grams in 1 liter of water). As it is desired to calculate the percentage of lactic acid in a given

amount of milk, and since 1 milliliter of a tenth-normal lactic acid contains 0.009 gram of lactic acid, the number of milliliters of a tenth-normal alkali necessary to neutralize the lactic acid in the sample, multiplied by 0.009, will give the number of grams of lactic acid in the sample. When this result is divided by the total number of grams of milk in the sample and multiplied by 100, the percentage of lactic acid in the sample will be obtained. This calculation may be illustrated more clearly by the following formula:

$$\% \text{ of lactic acid} = \frac{\text{milliliters } N/10 \text{ alkali} \times 0.009}{\text{grams of sample}} \times 100.$$

As can be seen readily, this formula permits the calculation of the percentage of lactic acid in samples of various sizes. When the test was first developed, samples as large as 25 and 50 grams were used. In more recent practice, however, the amount has been reduced to 9 or 18 grams.

The Details of the Acidity Test.—The materials needed for conducting acidity tests are a white enameled or porcelain cup, stirring rod, 9- and 17.6-milliliter pipettes, burette, 1 per cent alcoholic solution of phenolphthalein and *N/10* sodium hydroxide (4.001 grams made up to 1,000 milliliters with distilled water).

To make the test, the burette is filled with *N/10* NaOH, care being taken that no air bubbles are entrapped in the lower part. The cup used should be clean. If milk, skim milk, or buttermilk is to be tested, by means of the 17.6-milliliter pipette, place 18 grams in the cup. If cream is to be tested, the 9-milliliter pipette is commonly used, for cream weighs about 1 gram per

FIG. 88.—The acid test. The equipment required in making the acid test of milk consists of a burette, a cup with a white lining, and a stirring rod. Titration is made using *N/10* sodium hydroxide and phenolphthalein as an indicator. (Courtesy of Land O'Lakes Creameries, Inc.)

milliliter. By rinsing the cream into the cup with water, the entire 9 milliliters can be placed there regardless of the viscosity of the cream. If ice cream or condensed milk is to be tested, it is well to weigh either 9 or 18 grams into the cup. After the sample has been measured into the cup, three to five drops of indicator are added. The alkali is added next. The reading of the alkali in the burette at the lowest point of the meniscus is noted and the alkali allowed to flow slowly into the cup containing the sample: at the same time, the contents of the cup are stirred constantly. When a faint but definite and persistent pink color appears, the end point has been reached. The reading of the burette is taken again at the lowest point of the meniscus and the amount of alkali required to neutralize the acid in the sample is found by subtracting the first reading from the one made after titrating. The number of milliliters of alkali thus found is used in the formula previously shown to determine the percentage of lactic acid in the sample.

THE SEDIMENT TEST

Visible foreign matter in milk is objectionable for several reasons. The presence of dirt is an objection in itself, but it is, furthermore, an indication of carelessness in handling which usually means a lack of sanitation. Another chapter takes up this matter in greater detail and points out that conditions which cause visible dirt to find its way into milk are such that many microorganisms which decompose milk are usually added with the dirt. Furthermore, the presence of particles of visible dirt usually means that a considerable amount of other foreign matter has entered the milk but cannot be seen because it is in solution.

The retailer as well as the milk consumer is interested in clean milk. For this reason, the conditions on each farm where milk is produced are often rated by the use of a score card. The condition of the milk as delivered by the producer is also closely scrutinized. A differential in price may be made, depending upon the results of such examinations. One of the very objectionable conditions is the presence of visible dirt. The value of a method for determining the relative amount of insoluble sediment in milk is obvious. A crude method consists in looking for dirt at the bottom of milk bottles that have stood undisturbed for some time. A more reliable method is known as the "sediment test."

How to Conduct the Test.—The sediment test is made by filtering a definite quantity of milk through a white cotton disc. The amount of visible dirt is estimated from the degree to which this disc is discolored. This test has been standardized by the American Public Health Association and the Association of Official Agricultural Chemists. The directions call for a pint sample to be filtered through a cotton disc, 1 inch in diameter. These discs may then be compared with standard discs, prepared from pints of milk to which have been added weighed amounts of sediment and representing all degrees of cleanliness from "clean" to "very dirty." Definite scores may be established for each standard and the results of the test recorded accordingly. In ordinary practice, a close estimation of the amount of dirt present may be made by noting the degree to which the discs become discolored. Some laboratories responsible for milk quality keep a file of sediment discs from the milk of each producer. This amounts to keeping a record of the care with which each producer handles his milk. Other milk plants paste the disc on a card and send it to the producer of the milk from which it was taken.

ANALYSIS OF BUTTER AT CREAMERY

For all practical purposes butter consists of butter fat, moisture, salt, and curd. Butter also contains a small amount of milk ash and milk sugar, but in a creamery analysis, these ingredients are not determined separately, but are included with the protein under the designation of "curd." The butter maker is concerned primarily at present with the moisture and fat analyses, yet it is recognized that a complete analysis is essential when attempting to manufacture butter of a uniform composition.

Sampling Butter.—Care should be taken to secure a representative sample when testing butter at the churn. It is good practice to take the sample from several points along the butter roll.

FIG. 89.—The butter trier. The trier is used to secure a sample of butter from a given package for examination by a butter judge, or as a sample for analysis. If the entire plug is not required, a sample for analysis may be cut from the plug at various points and the remainder inserted back into the hole from which the plug was removed.

The surface of the roll should be scraped with a butter ladle, at the points where the samples are to be taken, and a small portion of butter removed by means of a metal blade or spoon. This sample should be placed in a clean, dry, glass jar or tumbler. In securing a sample from a tub or box of butter, a trier should be used and the sample taken diagonally through the bulk. Free moisture adhering to the trier should be wiped off before placing the butter in the sample jar.

Preparation of Sample.—When the butter to be analyzed has just been removed from the churn, it is sufficiently soft to allow working with a steel blade until thoroughly mixed. If the sample is leaky or too firm for proper mixing, as may be the case after butter has been held in the cold room, it should be melted slowly and rehardened by setting the jar in a cold-water bath and stirring it slowly.

Moisture Test.—*Equipment Required:*

Steel blade or spoon.

Butter trier.

Alcohol lamp or other means of heating sample.

Aluminum cups (2) (Tall aluminum measuring cups will serve.)

Accurate moisture balance.

Iron tripod, height 5 inches, diameter 4 inches.

Asbestos-center wire gauze square, 5 inches square.

Operation of the Test.—Ten grams of butter are weighed into an aluminum cup. The butter is then heated over a low flame until it ceases foaming and a light-brown color appears. It is advisable, when heating the sample, to place the aluminum cup on an asbestos-center wire gauze placed on a tripod. This tends to distribute the heat evenly to all points on the bottom of the cup. After the moisture is driven from the butter, the sample is allowed to cool and is reweighed. The loss in weight divided by the original weight of the sample multiplied by 100 gives the percentage of moisture contained. Some scales on the market read directly the percentage of moisture.

Salt Analysis (Cornell Method).

Equipment Required:

500-milliliter bottle marked at the upper surface of the liquid when the bottle contains 300 milliliters of water.

Cream or butter-test balance.

17.6-milliliter milk pipette.

White cup.

Glass stirring rod.

25-milliliter burette graduated in tenths of a milliliter.

Glass funnel.

Petcock.

Aluminum measuring cup.

100-milliliter graduated cylinder.

Reagents Required:

Small bottle (50 to 100 milliliters) potassium chromate solution prepared by placing 10 grams of potassium chromate in a graduated cylinder and adding water to bring contents to 100-milliliter mark.

A 1-liter bottle of standard tenth-normal silver nitrate, prepared by dissolving 17.5 grams of chemically pure silver nitrate in water and making up to a volume of 1,000 milliliters.

Method of Conducting Test.—Ten grams of butter are weighed into an aluminum cup. The butter is melted and poured into

FIG. 90.—Butter-moisture scale. A moisture scale is provided with a scale from which the percentage of moisture contained in the sample may be read. The illustration shows also the aluminum cup in which the butter sample is weighed, a 10-gram weight in place on the scale, and tongs with which the cup may be handled.

a bottle through a glass funnel. Hot distilled water (or rain water) is placed in the aluminum cup and the rinsings are poured into the bottle. This procedure is repeated until all the butter in the cup is transferred. Hot water is added to the bottle sufficient to bring the liquid to the 300-milliliter mark. Place

the stopper in the bottle and shake it vigorously for about $\frac{1}{2}$ minute. Allow this to stand for 5 minutes to permit the butter fat to rise, and by means of a milk pipette, 17.6 milliliters of the clear portion are pipetted from the bottle. This is accomplished by holding the index finger over the end of the pipette when inserting it to the bottom of the bottle where the sample is taken. The pipetted portion is placed in a white cup and a few drops of potassium chromate solution added. Standard tenth-normal silver nitrate solution is run from a burette into the sample in the cup, stirring constantly, until a permanent brownish-red color appears. Each milliliter of standard silver nitrate solution required represents 1 per cent of salt in the original sample of butter.

Butter Analysis by the Kohman Method.—A practical method for the complete analysis of butter has been introduced by Kohman, by which butter may be analyzed for fat, salt, moisture, and curd in a comparatively short time. In conducting the test the following equipment and materials are essential:

Equipment:

- Butter-test scale.
- 2 half-pint aluminum measuring cups (handles removed).
- 1 ten-gram weight.
- 1 steel blade or spoon.
- 1 alcohol lamp.
- 1-liter bottle.
- 1 indicator bottle, glass stopper.
- 1 pair tongs.
- 200-milliliter graduated cylinder.

Chemicals:

- Distilled or filtered rain water (rain water free of sediment).
- Filtered gasoline.
- Wood alcohol for alcohol lamp.
- Chromate indicator (10 grams potassium chromate made up to 100 milliliters by the addition of distilled water).
- Silver nitrate solution (29.062 grams silver nitrate with distilled water added to make 1,000 milliliters).

Operation of the Kohman Method.—Place the aluminum cup on the right-hand pan of the scale and balance it with the weight on the 10 per cent beam placed at the 10 per cent mark. (Placing the 10 per cent weight as indicated makes possible, later, the weighing of the salt and curd.) Weigh into the cup 10 grams of butter.

The moisture contained in the butter is now driven off by heating the sample slowly over an alcohol flame until it becomes a light-brown color and ceases sputtering. (The cup is held by the tongs during the heating.) After allowing the cup to cool, it is placed on the scale and the moisture loss measured by pushing the weight on the 20 per cent beam from zero to such a point as will balance the scale. The reading represents the percentage of moisture contained in the butter.

The liquid fat is then treated with 100 milliliters of gasoline to dissolve the butter fat. This is accomplished by stirring vigorously and allowing it to stand for 4 minutes. The gasoline containing the dissolved fat is then carefully poured off and the procedure repeated. With the second extraction, the sample is allowed to stand but 2 minutes. The residue consists of the salt and curd contained in the butter sample.

Next, the sample is heated to dryness and after it cools it is again placed on the balance. The weight on the 20 per cent beam is returned to zero and the 10-gram weight is removed, the scale being brought to a balance by pushing the weight on the 10 per cent beam toward the zero mark. This reading subtracted from 10 indicates the percentage of salt and curd contained in the sample. The difference between the total moisture, salt, and curd and 100 represents the percentage of fat.

The dry residue is then dissolved in 176 milliliters of warm distilled water (or clean rain water), and stirred thoroughly. Pipette 17.6 milliliters of the solution into a white cup and add a few (3 to 5) drops of the potassium chromate solution. Titrate with silver nitrate solution (29.062 grams made up to 1,000 milliliters with distilled water) until a permanent brownish color appears. The milliliters of silver nitrate solution used indicates the percentage of salt in the butter. By subtracting the percentage of salt from the percentage of salt and curd, the percentage of curd is determined.

EXAMPLE OF METHOD OF CALCULATION

Moisture, per cent.....	15 8
Salt and curd, per cent.....	3 2
<hr/>	
Total per cent—moisture, salt, and curd.....	19 0

To determine the percentage of fat, subtract 19 (total moisture, salt, and curd) from 100, which equals 81, the percentage of fat in the sample.

The dry residue may be washed from the dish with hot water and the salt test completed by the Cornell method. The main difference between the method outlined above and the Cornell salt test is the strength of the silver nitrate solution.

Curd Determination.—The amount taken for the salt determination, 17.6 milliliters, represents one-tenth of the original sample or 1 gram of butter. When titrated with the silver nitrate solution, made up as directed, each milliliter of silver nitrate used represents 1 per cent of salt. If, for example, the salt-and-curd percentage is found to be 3.2 and the salt 2.6, the percentage of curd is the difference between these two figures, or 0.6.

DETECTION OF ADDED WATER IN MILK BY FREEZING POINT DETERMINATION

FIG. 91.—Hortvet cryoscope. This apparatus is designed for the determination of the freezing point of milk. It is used primarily in control laboratories when it is desired to determine whether milk has been adulterated with water.

per cent, by the accurate determination of the freezing point of milk. The determination is made by supercooling milk to a point slightly below the normal freezing point and starting the freezing action by inserting a small crystal of ice into the milk. An accurate thermometer inserted in the milk during the cooling and freezing indicates the temperature at which the milk freezes. The cryoscopic method as embodied in the apparatus designed by Hortvet is the one most frequently used in conducting the test.

The test is used to a limited extent by purchasers of large quantities of milk and in milk-inspection laboratories. The

limited use of the test is chiefly due to the skill required in conducting it.

TOTAL SOLIDS DETERMINATION

It is a common procedure in many manufacturing plants using dairy products, such as ice-cream factories, condensaries,

FIG. 92.—The Mojonnier tester. The Mojonnier tester is a compact apparatus containing all the equipment and reagents necessary for the total solids analysis and a modified method of conducting the Roesse-Gottlieb test. The apparatus is used in large market-milk plants, ice-cream factories, and milk-condensing plants where a single analysis may represent a large volume of product, and it is important that the analysis be accurate. (*Courtesy of Mojonnier Brothers.*)

and dry-milk plants, to analyze milk and the finished products for dry matter or "total solids." The "Mojonnier tester" is used frequently for this purpose in these factories and it is also used in making the fat determination by the modified Roesse-Gottlieb method. The Mojonnier method of determining the total solids of milk is virtually the same as the official method of the Association of Official Agricultural Chemists. The chief

difference lies in the special provisions which are made available in the Mojonnier tester for rapid heating and subsequent cooling of the sample. The procedure consists of weighing a few grams of the product to be analyzed into a flat-bottom dish, and subjecting the sample to heat until all moisture has been driven off. The moisture, or the total dry residue which remains, may be calculated in this way.

THE MARSCHALL RENNET TEST

The Marshall rennet test is used frequently in the cheese factory when it is desired to set milk with rennet under uniform conditions from day to day. The test consists of the addition of 1 milliliter of rennet to a definite quantity of milk and observing the rate of coagulation. Rennet coagulation of milk is influenced principally by the temperature of the milk, the strength of the rennet extract, and the acidity of the milk. The first two mentioned factors can be controlled, but the acidity of milk may vary from day to day. The rennet test, therefore, serves as an indirect measure of the acidity of milk, since the more acid present in milk, the more quickly the rennet will coagulate the milk.

The Marshall rennet test makes use of a 1-milliliter pipette to measure the rennet extract, a small bottle in which the diluted rennet is placed, a spatula with which to mix the milk, and a special cup to hold the milk. The cup generally is made of granite ware and about 1 quart in capacity. On the inside of the cup is a scale graduated from 0 at the top to 10 at the bottom. A small hole in the bottom of the cup permits the milk to flow out.

The test is operated as follows: 1 milliliter of rennet extract is placed in the small bottle and made up to 20 milliliters with cold water. The cup is filled with milk at from 84 to 86°F. (28.9 to 30°C.) to above the zero mark. The milk is permitted to flow through the small opening in the bottom of the cup. When the surface of the milk reaches the zero mark, the diluted rennet is added, and the milk stirred thoroughly with the spatula until the milk has passed half of one space on the scale.

The flow of the milk eventually is stopped, due to the coagulating action of the rennet. Observation is then made on the scale at the point reached by the surface of the milk. If good results are being secured in the manufacture of cheese with a rennet test of four and the rennet test indicates six, the cheese maker knows

that more acid must be permitted to develop before the rennet extract is added to the vat of milk. If the rennet test indicates three spaces, the cheese maker knows that too much acid is present and acts accordingly in conducting the manufacturing process.

THE METHYLENE BLUE REDUCTION TEST FOR QUALITY OF MILK

This test is variously known by other names, such as the "reductase," "methylene blue," and "methylene blue reduction test." It is a test that shows the comparative activity of the bacteria in milk and, for this reason, it is a rough indication of the number of bacteria per milliliter. It is based on the observation that the color imparted to milk by a small amount of methylene blue disappears in a time, the length of which is dependent largely upon the number of microorganisms present if other factors are constant. The change brought about is a chemical reduction of the methylene blue due to the action of the bacteria, apparently by the utilization of the oxygen dissolved in the milk as some believe or due to an enzyme, reductase, produced by organisms. In conducting the test, definite quantities of methylene blue are added to 10 milliliters of milk and the samples held at a uniform temperature (98.6°F. (37°C.)) until the blue color has disappeared. The milk which remains blue the longest is considered to be of the best quality, and a scale of grading different milk samples, on the basis of the time required to reduce a definite quantity of methylene blue, has been worked out.

The same test may be applied to sweet cream by using a more concentrated solution of methylene blue.

Use of the Test.—This test finds wide application in certain of the dairy industries. It is particularly adapted to guide the cheese maker in grading the milk delivered to his factory, and compact outfits for use in making the test are on the market. Buyers of milk for condensing also find the test a good one for grading the milk from the individual producers. The reductase test is used to some extent by the buyers of milk for the market-milk trade, and by creameries for grading sweet cream.

THE ALCOHOL TEST

When milk contains more than 0.21 per cent acid, or when calcium and magnesium compounds are present in greater than normal amounts, it will coagulate on the addition of alcohol.

This fact is the basis of the alcohol test which furnishes a means of judging the quality of milk. Coagulation of milk by alcohol also may be due to several causes other than those mentioned above, among which should be mentioned diseases of the udder, presence of colostrum, and rennin formed by microorganisms.

The widest use of the alcohol test is found in the condensed-milk industry. Difficulties with coagulation of milk during the process of condensing are rather common. Research work has indicated that this trouble may be caused by an excess of calcium and magnesium salts in the milk. The alcohol test, used on fresh milk, along with the acidity test, will usually indicate the milk which is likely to coagulate during processing. If the acidity of the milk is lower than 0.21 per cent, coagulation by alcohol is taken to indicate a salt balance in the milk, which is unfavorable to processing. If such milk cannot be returned, the buyer at least knows that certain precautions in processing are necessary.

Details of the Test.—The only reagent needed is a 75 per cent alcohol solution. This is usually prepared from 95 per cent alcohol by mixing with distilled water in the proportion of 79 parts of 95 per cent alcohol to 21 parts of distilled water. Ordinary 6-inch test tubes serve as containers for the tests. Means for supporting these tubes in an upright position should be available, such as test-tube racks, wire baskets, or blocks of wood with holes bored to fit the test tubes. Equal parts of 75 per cent alcohol and milk are placed in a tube, the tube inverted several times with the thumb held tightly over the open end, and then the tube is examined to note any coagulation that may have occurred. If coagulation has occurred, fine particles of curd will be visible on the inside surface of the tube, or the tube will show a very milky layer which would not be visible if no coagulation had occurred. Some experience in interpreting the results of these tests is desirable.

THE FERMENTATION TEST

One test of the quality of milk consists in setting samples of the milk, to be examined at room temperature, in tubes that previously have been boiled in water to render them practically sterile. This is a good means for differentiating between very bad milk and good milk. If the milk does not curdle for a long time, it is usually of good quality and contains few bacteria. If it curdles relatively soon, but forms a smooth curd free from

gas pockets and little whey, the milk is of fair quality. If it curdles quickly, forms numerous gas pockets, and clear whey appears, the milk is of very poor quality.

It must be remembered that such a test is very crude, and results of one day may not compare favorably with those of another day because of the varying temperature conditions. A number of milks tested at one time, however, under identical conditions may be compared directly. If milk shows gas fermentation continually, that milk is being produced under filthy conditions, for the most common gas-producing and putrefactive organisms are found in fecal matter and other filth.

TESTS FOR HEATED MILK

Several tests have been devised for detecting heated milk. When milk is sold as pasteurized it frequently is desired to learn if the milk has been heated sufficiently. The tests used are based on the presence in milk of certain enzymes, as previously discussed, which in the presence of peroxides, set free oxygen. Oxidizable compounds such as guaiac and paraphenylenediamine are used as indicators in this test. The tests most frequently used are the Storch and the Arnold tests.

Storch Test.—A drop of hydrogen peroxide is added to 5 milliliters of milk to be examined. Two drops of paraphenylenediamine are then added. The milk is then shaken. If the milk has not been heated above 172°F. (77.8°C.), a blue color appears. If a bluish-gray color appears, after a minute, the milk was heated to 175°F. (79.4°C.) or higher.

Arnold or Guaiac Test.—To 5 milliliters of milk add a few drops of saturated alcoholic or acetone solution of guaiac and follow this with a few drops of a 0.2 per cent solution of hydrogen peroxide. A blue color indicates that the milk was not heated at all or not above 176°F. (80°C.). If the milk has been heated to 176°F. (80°C.) or above, no coloration appears.

TO DISTINGUISH BETWEEN BUTTER AND OLEOMARGARINE

The question as how to distinguish between oleomargarine and true butter frequently arises in the minds of those purchasing butter. It should be clearly understood that it is not possible in all cases to differentiate between the two by simple tests and that carefully conducted chemical analysis of the fat may be necessary, if a positive result is required. This can be done only by a

competent chemist experienced in the technique of analyzing dairy products and interpreting the results. A simple test which can be used to a limited extent, however, is known as the "household foam test." It consists of heating the suspected sample in a spoon over a slow flame. Oleomargarine boils with a marked noise and considerable sputtering, but produces little or no foam. Butter generally boils with less noise and foams vigorously. Renovated butter acts in the same way as oleomargarine.

NOTE.—Detailed directions for making many of the common tests will be found in "Standard Methods of Milk Analysis" published by the American Public Health Association and the Association of Official Agricultural Chemists.

APPENDIX

OUTLINE OF METHODS FOR BACTERIOLOGICAL ANALYSIS OF MILK¹

1. Collection of Samples.—Milk should be thoroughly mixed, and sampled with a sterile tube long enough to reach to the bottom of the can or bottle. Each sample should be at least 10 milliliters and should be kept in a tightly stoppered bottle or vial (closure with cotton plugs is not permitted). Samples should be iced, and if plates are not made within 4 hours of the time when the samples were taken, the time elapsing should be reported.

2. Macroscopic Colony Count (Petri Plate Method).

COMPOSITION OF MEDIUM

	Per Cent
Agar (market, not oven dried).....	1.5
Beef extract (Bacto).....	0.3
Peptone (Bacto).....	0.5
Distilled water.....	97.7

The preferred reaction of the medium is pH 6.6, but it need not be adjusted if it is between pH 6.4 and pH 7.0. If necessary to adjust the reaction, special attention should be given to the H-ion concentration, making use of the indicator brom thymol blue.

At least two dilutions are usually made in plating: 1 to 100, 1 to 1,000, or 1 to 10,000—unless the quality of the milk is such that the highest or lowest of these is known to be superfluous. In no case are less than two plates made from each sample. Each sample bottle and dilution bottle should be shaken 25 times with an up-and-down motion of about 1 foot, in not more than 7 seconds. After dilution of the milk, the agar should be poured into the plates within 15 minutes.

Incubation is at 37°C. for 48 hours.

The plates used for counting should have, if possible, between 30 and 300 colonies each. If there are no plates within these limits, the one having nearest to 300 should be counted. Counting should be done with a lens magnifying 2½ diameters. The exact counts from each plate should be recorded, but not more than two significant left-hand digits should be used in making the final report.

Results should be expressed, not as so many "bacteria per milliliter" of milk; but as "colonies per milliliter," or better as "standard plate count" so much per milliliter. The practice of publishing counts from individual samples of milk showing the quality of a given milk supply is not sanctioned,

¹ See "Standard Methods of Milk Analysis" published by the American Public Health Association, New York, for complete description of methods.

and a series of samples should be examined before rendering judgment in regard to any milk supply.

3. Microscopic Count of Bacteria (Breed Method).—Milk is taken in a capillary pipette discharging 0.01 milliliter and dried over an area of 1 cm.² on a microscopic slide. It should be stained in methylene blue after washing out the fat in xylol and fixing in alcohol; or stained by the use of the so-called Newman stain. The number of bacteria per milliliter should be estimated by counting those within a given area in a microscopic field, this area having been carefully measured and its ratio to a square centimeter determined. At least 1/10,000 part of a milliliter of milk is to be examined, and if the milk is of high grade, this must be done under favorable conditions for accurate counting. The ratio used in comparing the "standard plate count" with the count of bacteria per milliliter as shown under the microscope is placed at 1 to 4. Preparations should be preserved a reasonable time after the reports have been sent to the person or persons interested.

Where counts are made to determine the probable agar plate count, the count should be of clumps of bacteria rather than individual bacteria, each isolated bacterium or compact group being counted as one.

ROESE-GOTTLIEB METHOD OF FAT DETERMINATION¹

(Official Method of Association of Official Agricultural Chemists)

Transfer 10 grams of the sample to a Röhrig tube or a similar apparatus, add 1.25 cubic centimeters of strong ammonium hydroxide (2 cubic centimeters if the sample is sour), and mix thoroughly. Add 10 cubic centimeters of 95 per cent alcohol and mix well. Add 25 cubic centimeters of ether. shake vigorously for 30 seconds, add 25 cubic centimeters of petroleum ether (redistilled slowly at a temperature below 60°C.), and shake again for 30 seconds. Let stand 20 minutes, or until the upper liquid is practically clear. Draw off as much as possible of the ether-fat solution (usually 0.5 to 0.8 cubic centimeter will be left) into a weighed flask through a small, quick-acting filter. The flask should be weighed with a similar one as a counterpoise. Again extract the liquid remaining in the tube, this time with 15 cubic centimeters of each ether; shake vigorously 30 seconds after each addition; and allow to settle. Draw off the clear solution through the small filter into the same flask as before and wash the tip of the spigot, the funnel, and the filter with a few cubic centimeters of a mixture of the two ethers, in equal parts, free from suspended water. To insure complete removal of the fat, a third extraction is necessary. This third extraction yields less than 1 milligram of fat if the previous ether-fat solutions have been drawn off closely. Add a glass bead and evaporate the ethers slowly on a steam bath; then dry the fat in a boiling-water oven to constant weight. Weigh the flask with a similar flask as a counterpoise. Do not wipe the flask immediately before weighing.

Remove the fat completely with petroleum ether. Deduct the weight of the dried flask with residue and bead to obtain the weight of fat. Finally, correct this weight by a blank determination on the reagents used.

¹ From "Standard Methods of Milk Analysis," American Public Health Association, New York.

BABCOCK METHOD OF FAT DETERMINATION¹

(Official Method of Association of Official Agricultural Chemists)

A. REAGENT

Sulfuric acid.—Specific gravity 1.82 to 1.83 at 20°C.

B. APPARATUS

(a) *Standard Babcock Test Bottle for Milk.*—8 per cent 18-gram, 6-inch milk test bottle, total height 150–165 millimeters (5.9 to 6.5 inches).

The bottom of the bottle shall be flat, and the axis of the neck shall be vertical when the bottle stands on a level surface. The charge of milk for the bottle shall be 18 grams.

Bulb.—The capacity of the bulb to the junction with the neck shall be not less than 45 cubic centimeters. The shape of the bulb shall be either, cylindrical or conical. If cylindrical, the outside diameter shall be between 34 and 36 millimeters; if conical the outside diameter of the base shall be between 31 and 33 millimeters, and the maximum diameter between 35 and 37 millimeters.

Neck.—The neck shall be cylindrical and of uniform diameter from at least 5 millimeters below the lowest graduation mark to at least 5 millimeters above the highest. The top of the neck shall be flared to a diameter of not less than 10 millimeters. The graduated portion of the neck shall have a length of not less than 63.5 millimeters. The total per cent graduation shall be 8. The graduations shall represent whole per cent, 0.5 per cent, and 0.1 per cent, respectively, from 0.0 to 8.0 per cent. The tenths per cent graduations shall not be less than 3 millimeters in length; the 0.5 per cent graduations shall not be less than 4 millimeters in length and shall project 1 millimeter to the left; and the whole per cent graduations shall extend at least halfway around the neck to the right and shall project at least 2 millimeters to the left of the tenths per cent graduations. Each whole per cent graduation shall be numbered, the number being placed to the left of the scale. The capacity of the neck for each whole per cent on the scale shall be 0.20 cubic centimeter. The maximum error of the total graduation or any part thereof shall not exceed the volume of the smallest unit of the graduation.

Each bottle shall be so constructed as to withstand the stress to which it will be subjected in the centrifuge.

(a) *Testing.*—The mercury-and-cork, alcohol-and-burette, and alcohol-and-brass-plunger methods may be employed for the rapid testing of the bottles, but the accuracy of any questionable bottle shall be determined by calibration with mercury (13.5471 grams of clean dry mercury at 20° to be equal to 5 per cent on the scale of an 18-gram bottle and 10 per cent on the scale of a 9-gram bottle), the bottle being previously filled to zero with mercury.

¹ From "Standard Methods of Milk Analysis," American Public Health Association, New York.

(b) *Pipette*.—The standard milk pipette shall conform to the following specifications:

Total length, not more than 330 millimeters.

Outside diameter of suction tube, 6–8 millimeters.

Length of suction tube, 130 millimeters.

Outside diameter of delivery tube, 4.5–5.5 millimeters.

Length of delivery tube, 100–120 millimeters.

Distance of graduation mark above bulb, 15–45 millimeters.

Nozzle, straight.

Graduation, to contain 17.6 cubic centimeters of H_2O at 20° when the bottom of the meniscus coincides with the mark on the suction tube.

Delivery in 5–8 seconds.

The maximum error in the graduation shall not exceed 0.05 cubic centimeter.

The pipette is to be marked “Holds 17.6 c.c.”

(b₁) *Testing*.—The pipette shall be tested by measuring from a burette the volume of H_2O (at 20°) that it holds up to the graduation mark.

(c) *Acid Measure*.—The device employed to measure H_2SO_4 , whether a graduated cylinder or a pipette attached to a Swedish acid bottle, shall be graduated to deliver 17.5 cubic centimeters.

(d) *Centrifuge or “Tester.”*—The standard centrifuge, however driven, shall be constructed throughout and so mounted as to be capable, when filled to capacity, of rotating at the necessary speed with a minimum of vibration and without liability of causing injury or accident. It shall be heated, electrically or otherwise, to a temperature of at least 55° during the process of centrifugalizing. It shall be provided with a speed indicator, permanently attached, if possible. The proper rate of rotation may be ascertained by reference to the table below. By “diameter of wheel” is meant the distance between the inside bottoms of opposite cups measured through the center of rotation of the centrifuge wheel while the cups are horizontally extended.

Diameter of wheel, in inches.....	10	12	14	16	18	20	22	24
Number revolutions per minute.....	1,074	980	909	848	800	759	724	693

(e) *Dividers or Calipers*.—For measuring the fat column.

(f) *Water Bath for Test Bottles*.—Provided with a thermometer and a device for maintaining a temperature of 55 to 60° .

(Reserve Side of Score Card)

Equipment	Score		Methods	Score	
	Per- fect	Al- lowed		Per- fect	Al- lowed
COWS			COWS		
Health.....	6		Clean.....	8	
Apparently in good health.....	1		(Free from visible dirt, 6.)		
If tested with tuberculin within			STABLES		
a year and no tuberculosis is				6	
found, or if tested within six			Cleanliness of stables.....		
months and all reacting ani-			Floor.....	2	
mals removed.....	5		Walls.....	1	
(If tested within a year and reacting			Ceilings and ledges.....	1	
animals are found and removed, 3.)			Mangers and partitions.....	1	
Food (clean and wholesome).....	1		Windows.....	1	
Water (clean and fresh).....	1		Stable air at milking time.....	5	
STABLES			Freedom from dust.....	3	
Location of stable.....	2		Freedom from odors.....	2	
Well drained.....	1		Cleanliness of bedding.....	1	
Free from contaminating sur-			Barnyard.....	2	
roundings.....	1		Clean.....	1	
Construction of stable.....	4		Well drained.....	1	
Tight, sound floor, and proper gut-			Removal of manure daily to 50 feet	2	
ter.....	2		from stable.....		
Smooth, tight walls and ceiling... 1			MILK ROOM OR MILK HOUSE		
Proper stall, tie, and manger..... 1			Cleanliness of milk room.....	3	
Provision for light: Four sq. ft. of glass			UTENSILS AND MILKING		
per cow.....	4		Care and cleanliness of utensils.....	8	
(Three sq. ft., 3; 2 sq. ft., 2; 1 sq. ft.,			Thoroughly washed.....	2	
1. Deduct for uneven distribution.)			Sterilized in steam for 15 minutes 3		
Bedding.....	1		(Placed over steam jet, or scalded		
Ventilation.....	7		with boiling water, 2.)		
Provision for fresh air, controllable			Protected from contamination... 3		
flue system.....	3		Cleanliness of milking.....	9	
(Windows hinged at bottom, 1.5;			Clean, dry hands.....	3	
sliding windows, 1; other open-			Udders washed and wiped..... 6		
ings, 0.5.)			(Udders cleaned with moist cloth, 4;		
Cubic feet of space per cow, 500 ft. 3			cleaned with dry cloth or brush at least		
(Less than 500 ft., 2; less than 400			15 minutes before milking, 1.)		
ft., 1; less than 300 ft., 0.)			HANDLING THE MILK		
Provision for controlling tempera-			Cleanliness of attendants in milk room	2	
ture.....	1		Milk removed immediately from stable		
UTENSILS			without pouring from pail.....	2	
Construction and condition of utensils	1		Cooled immediately after milking each		
Water for cleaning.....	1		cow.....	2	
(Clean, convenient, and abundant.)			Cooled below 50°F.....	5	
Small-top milking pail.....	5		(51° to 55°, 4; 56° to 60°, 2.)		
Milk cooler.....	1		Stored below 50°F.....	3	
Clean milking suits.....	1		(51° to 55°, 2; 56° to 60°, 1.)		
MILK ROOM OR MILK HOUSE			Transportation below 50°F.....	2	
Location: Free from contaminating sur-	1		(51° to 55°, 1.5; 56° to 60°, 1.)		
roundings.....	2		(If delivered twice a day, allow per-		
Construction of milk room.....			fect score for storage and transporta-		
Floor, walls, and ceilings.....	1		tion.)		
Light, ventilation, screens.....	1		Total.....		
Separate rooms for washing utensils and	1			60	
handling milk.....	1				
Facilities for steam.....					
(Hot water, 0.5.)					
Total.....					
	40				

Equipment.....+ Methods.....=.....Final Score

NOTE 1.—If any exceptionally filthy condition is found, particularly dirty utensils, the total score may be further limited.

NOTE 2.—If the water is exposed to dangerous contamination, or there is evidence of the presence of a dangerous disease in animals or attendants, the score shall be 0.

SPECIFIC GRAVITY AND WEIGHT PER GALLON OF MILK AND CREAM¹

Percentage of fat (by weight)	Specific gravity, 20°/4°C.	Specific gravity, 10°/4°C.	Pounds per gallon at 20°C. (68°F.)	Pounds per gallon at 10°C. (50°F.)
0.025	1.035	1.037	8.63	8.65
1	1.034	1.036	8.62	8.64
2	1.033	1.035	8.61	8.63
3	1.032	1.034	8.60	8.62
4	1.031	1.033	8.59	8.61
5	1.029	1.032	8.58	8.60
6	1.028	1.031	8.57	8.59
7	1.027	1.030	8.56	8.59
8	1.026	1.029	8.55	8.58
9	1.024	1.028	8.54	8.57
10	1.023	1.027	8.53	8.56
11	1.022	1.026	8.52	8.55
12	1.020	1.025	8.50	8.54
13	1.019	1.024	8.49	8.54
14	1.017	1.023	8.48	8.53
15	1.016	1.022	8.47	8.52
16	1.015	1.021	8.46	8.51
17	1.014	1.020	8.45	8.50
18	1.013	1.019	8.44	8.49
19	1.012	1.018	8.44	8.49
20	1.011	1.017	8.43	8.48
21	1.010	1.017	8.42	8.48
22	1.009	1.016	8.41	8.47
23	1.008	1.015	8.40	8.46
24	1.007	1.014	8.40	8.46
25	1.007	1.014	8.39	8.45
26	1.006	1.013	8.39	8.45
27	1.005	1.012	8.38	8.44
28	1.004	1.012	8.37	8.44
29	1.003	1.011	8.36	8.43
30	1.002	1.011	8.36	8.43
31	1.001	1.010	8.34	8.42
32	1.000	1.010	8.34	8.42
33	0.999	1.009	8.33	8.41
34	0.998	1.008	8.32	8.40
35	0.998	1.008	8.31	8.40
36	0.997	1.007	8.31	8.40
37	0.996	1.007	8.30	8.39
38	0.995	1.006	8.30	8.39
39	0.994	1.005	8.29	8.38
40	0.993	1.005	8.28	8.38

¹ Reproduced from page 42, Circular 19, U. S. Bureau of Standards, 1924.

AUTHORS' NOTE.—The specific gravities here presented were based on work with mixed herd milk and should not be translated as referring to milk of individual cows.

Specific gravity 20°/4°C. means the specific gravity at 20°C. (68°F.) in terms of water at its maximum density as unity, and specific gravity 10°/4°C. means the specific gravity at 10°C. (50°F.) in terms of the same unit. These specific-gravity values are numerically the same as density at 20 and 10°C., respectively, in grams per milliliter.

NOTE.—The specific gravity at 20°/20°C. (68°/68°F.) corresponding to any percentage of fat can be obtained by dividing the specific gravity at 20°/4°C. by the density of water at 20°C. (0.9982343).

STANDARD UNITS OF MEASURE AND WEIGHT

UNIT OF LENGTH

A meter (m.) is taken from the international prototype meter at the International Bureau of Weights and Measures; at 32°F. (0°C.) = 39.37 inches = 3.280833 feet = 100 centimeters.

A foot (ft.) = 0.3048006 meter = 30.48006 centimeters = 12 inches.

UNIT OF CAPACITY

A liter (l.) is the volume occupied by the mass of 1 kilogram of pure water at 4°C. under barometric pressure of 760 millimeters = 0.264178 U. S. gallon = 61.025 cubic inches = 1,000 cubic centimeters = 1,000 milliliters.

A gallon U. S. (gal.) = 231 cubic inches = 3.785332 liters = 8.32823 pounds pure water in air at 60°F. = 3.777623 kilograms pure water in air at 60°F. (15.56°C.) = 0.8327 imperial gallon = 4 quarts.

An imperial gallon (English) = 277.274 cubic inches = 4.54346 liters = 1.20032 U. S. gallons = 9.996 pounds pure water at 60°F. (15.56°C.).

UNIT OF WEIGHT OR MASS

A kilogram (kg.) is taken from the international prototype kilogram at the International Bureau of Weights and Measures = 2.204622341 pounds Avoirdupois = 2.6792285 pounds Troy = 15,432.356 grains = 1,000 grams.

A pound (Avoirdupois) (lb.) = 0.4535924277 kilogram = 453.5924277 grams = 1.2152778 pounds, Troy = 16 ounces, Avoirdupois = 7,000 grains

CONVERSION TABLE OF WEIGHTS AND MEASURES

Ordinary weights and measures	Equivalents in metric system	Metric weights and measures	Equivalents in ordinary system
1 inch.....	2.54 centimeters	1 millimeter	0.03937 inch
1 foot.....	0.3048 meter	1 centimeter	0.3937 inch
1 square inch.....	6.452 square centimeters	1 meter	3.2808 feet
1 square foot.....	929.030 square centimeters	1 square millimeter	0.00155 square inch
1 cubic inch.....	16.387 cubic centimeters	1 square centimeter	0.155 square inch
1 cubic foot.....	0.0283 cubic meter	1 square meter	10.764 square feet
1 fluid ounce.....	29.57 milliliters	1 milliliter	0.061 cubic inch
1 quart.....	946.4 milliliters	1 milliliter	0.0338 fluid ounce
1 gallon.....	3.7854 liters	1 liter	1.057 quarts
1 grain.....	64.8 milligrams	1 gram	15.432 grains
1 ounce (Avoirdupois)	28.35 grams	1 gram	0.0353 ounce (Avoirdupois)
1 pound (Avoirdupois)	453.59 grams	1 kilogram	2.2046 pounds (Avoirdupois)

TABLE FOR CALCULATING TOTAL SOLIDS IN MILK FROM SPECIFIC GRAVITY
AND FAT PERCENTAGE
Per Cent Total Solids

Lactometer reading at 60°F. (15.6°C.) (Quevenne degrees)											
Percent- age of fat	26	27	28	29	30	31	32	33	34	35	36
3.00	10.10	10.35	10.60	10.85	11.10	11.36	11.61	11.86	12.11	12.36	12.61
3.05	10.16	10.41	10.66	10.91	11.17	11.42	11.67	11.92	12.17	12.42	12.68
3.10	10.22	10.47	10.72	10.97	11.23	11.48	11.73	11.98	12.23	12.48	12.74
3.15	10.28	10.53	10.78	11.03	11.29	11.54	11.79	12.04	12.29	12.55	12.80
3.20	10.34	10.59	10.84	11.09	11.35	11.60	11.85	12.10	12.35	12.61	12.86
3.25	10.40	10.65	10.90	11.16	11.41	11.66	11.91	12.16	12.42	12.67	12.92
3.30	10.46	10.71	10.96	11.22	11.47	11.72	11.97	12.22	12.48	12.73	12.98
3.35	10.52	10.77	11.03	11.29	11.53	11.78	12.03	12.28	12.54	12.79	13.04
3.40	10.58	10.83	11.09	11.34	11.59	11.84	12.09	12.34	12.60	12.85	13.10
3.45	10.64	10.89	11.15	11.40	11.65	11.90	12.15	12.40	12.66	12.91	13.16
3.50	10.70	10.95	11.21	11.46	11.71	11.96	12.21	12.46	12.72	12.97	13.22
3.55	10.76	11.02	11.27	11.52	11.77	12.02	12.27	12.52	12.78	13.03	13.28
3.60	10.82	11.08	11.33	11.58	11.83	12.08	12.33	12.58	12.84	13.09	13.34
3.65	10.88	11.14	11.39	11.64	11.89	12.14	12.39	12.64	12.90	13.15	13.40
3.70	10.94	11.20	11.45	11.70	11.95	12.20	12.45	12.70	12.96	13.21	13.46
3.75	11.00	11.26	11.51	11.76	12.01	12.26	12.51	12.76	13.02	13.27	13.52
3.80	11.06	11.32	11.57	11.82	12.07	12.32	12.57	12.82	13.08	13.33	13.58
3.85	11.12	11.38	11.63	11.88	12.13	12.38	12.63	12.88	13.14	13.39	13.64
3.90	11.18	11.44	11.69	11.94	12.19	12.44	12.69	12.94	13.20	13.45	13.70
3.95	11.24	11.50	11.75	12.00	12.25	12.50	12.75	13.00	13.26	13.51	13.77
4.00	11.30	11.56	11.81	12.06	12.31	12.56	12.81	13.06	13.32	13.57	13.83
4.05	11.36	11.62	11.87	12.12	12.37	12.62	12.87	13.12	13.38	13.63	13.89
4.10	11.42	11.68	11.93	12.18	12.43	12.68	12.93	13.18	13.44	13.69	13.95
4.15	11.48	11.74	11.99	12.24	12.49	12.74	12.99	13.25	13.50	13.76	14.01
4.20	11.54	11.80	12.05	12.30	12.55	12.80	13.05	13.31	13.56	13.82	14.07
4.25	11.60	11.86	12.11	12.36	12.61	12.86	13.12	13.37	13.62	13.88	14.13
4.30	11.66	11.92	12.17	12.42	12.67	12.92	13.18	13.43	13.68	13.94	14.19
4.35	11.72	11.98	12.23	12.48	12.73	12.98	13.24	13.49	13.74	14.00	14.25
4.40	11.78	12.04	12.29	12.54	12.79	13.04	13.30	13.55	13.80	14.06	14.31
4.45	11.84	12.10	12.35	12.60	12.85	13.10	13.36	13.61	13.86	14.12	14.37
4.50	11.90	12.16	12.41	12.66	12.91	13.16	13.42	13.67	13.92	14.18	14.43
4.55	11.97	12.22	12.47	12.72	12.97	13.22	13.48	13.73	13.98	14.24	14.49
4.60	12.03	12.28	12.53	12.78	13.03	13.28	13.54	13.79	14.04	14.30	14.55
4.65	12.09	12.34	12.59	12.84	13.09	13.34	13.60	13.85	14.10	14.36	14.61
4.70	12.15	12.40	12.65	12.90	13.15	13.40	13.66	13.91	14.16	14.42	14.67
4.75	12.21	12.46	12.71	12.96	13.21	13.46	13.72	13.97	14.22	14.48	14.73
4.80	12.27	12.52	12.77	13.02	13.27	13.52	13.78	14.03	14.28	14.54	14.79
4.85	12.33	12.58	12.83	13.08	13.33	13.58	13.84	14.09	14.34	14.60	14.85
4.90	12.39	12.64	12.89	13.14	13.39	13.64	13.90	14.15	14.40	14.66	14.91
4.95	12.45	12.70	12.95	13.20	13.45	13.70	13.96	14.21	14.46	14.72	14.97
5.00	12.51	12.76	13.01	13.26	13.51	13.76	14.02	14.27	14.52	14.78	15.03

TEMPERATURE CONVERSION TABLE
Fahrenheit to Centigrade
(Values in body of table give in degrees Centigrade the temperature indicated
in degrees Fahrenheit at top and side)

Temperatures below 0° F.										
Temperature degrees Fahrenheit	0	1	2	3	4	5	6	7	8	9
0	-17.78	-18.33	-18.89	-19.44	-20.00	-20.56	-21.11	-21.67	-22.22	-22.78
-10	-23.33	-23.89	-24.44	-25.00	-25.56	-26.11	-26.67	-27.22	-27.78	-28.33
-20	-28.89	-29.44	-30.00	-30.56	-31.11	-31.67	-32.22	-32.78	-33.33	-33.89
-30	-34.44	-35.00	-35.56	-36.11	-36.67	-37.22	-37.78	-38.33	-38.89	-39.44
Temperatures above 0° F.										
	0	1	2	3	4	5	6	7	8	9
0	-17.78	-17.22	-16.67	-16.11	-15.56	-15.00	-14.44	-13.89	-13.33	-12.78
+10	-12.22	-11.67	-11.11	-10.56	-10.00	-9.44	-8.89	-8.33	-7.78	-7.22
20	-6.67	-6.11	-5.56	-5.00	-4.44	-3.89	-3.33	-2.78	-2.22	-1.67
30	-1.11	-0.56	0.00	+ 0.56	+ 1.11	+ 1.67	+ 2.22	+ 2.78	+ 3.33	+ 3.89
40	+ 4.44	5.00	5.56	6.11	6.67	7.22	7.78	8.33	8.89	9.44
50	10.00	10.56	11.11	11.67	12.22	12.78	13.33	13.89	14.44	15.00
60	15.56	16.11	16.67	17.22	17.78	18.33	18.89	19.44	20.00	20.56
70	21.11	21.67	22.22	22.78	23.33	23.89	24.44	25.00	25.56	26.11
80	26.67	27.22	27.78	28.33	28.89	29.44	30.00	30.56	31.11	31.67
90	32.22	32.78	33.33	33.89	34.44	35.00	35.56	36.11	36.67	37.22

100	37.78	38.33	38.89	39.44	40.00	40.56	41.11	41.67	42.22	42.78
110	43.33	43.89	44.44	45.00	45.56	46.11	46.67	47.22	47.78	48.33
120	48.89	49.44	50.00	50.56	51.11	51.67	52.22	52.78	53.33	53.89
130	54.44	55.00	55.56	56.11	56.67	57.22	57.78	58.33	58.89	59.44
140	60.00	60.56	61.11	61.67	62.22	62.78	63.33	63.89	64.44	65.00
150	65.56	66.11	66.67	67.22	67.78	68.33	68.89	69.44	70.00	70.56
160	71.11	71.67	72.22	72.78	73.33	73.89	74.44	75.00	75.56	76.11
170	76.67	77.22	77.78	78.33	78.89	79.44	80.00	80.56	81.11	81.67
180	82.22	82.78	83.33	83.89	84.44	85.00	85.56	86.11	86.67	87.22
190	87.78	88.33	88.89	89.44	90.00	90.56	91.11	91.67	92.22	92.78
200	93.33	93.89	94.44	95.00	95.56	96.11	96.67	97.22	97.78	98.33
210	98.89	99.44	100.00	100.56	101.11	101.67	102.22	102.78	103.33	103.89
220	104.44	105.00	105.56	106.11	106.67	107.22	107.78	108.33	108.89	109.44
230	110.00	110.56	111.11	111.67	112.22	112.78	113.33	113.89	114.44	115.00
240	115.56	116.11	116.67	117.22	117.78	118.33	118.89	119.44	120.00	120.56
250	121.11	121.67	122.22	122.78	123.33	123.89	124.44	125.00	125.56	126.11

For $^{\circ}\text{F} \dots 0.1$ 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
interpolation $^{\circ}\text{C} \dots 0.06$ 0.11 0.17 0.22 0.28 0.33 0.39 0.44 0.50 0.56

MOLECULAR WEIGHTS OF ACIDS, BASES AND SALTS AND QUANTITIES
NECESSARY FOR TENTH-NORMAL SOLUTIONS

Substance	Formula	Molecular weight	Number of grams per liter for N/10 solution
Calcium hydroxide.....	Ca(OH)_2	74.08	3.704
Calcium oxide.....	CaO	56.07	2.804
Hydrochloric acid.....	HCl	36.47	3.647
Lactic acid.....	$\text{C}_3\text{H}_6\text{O}_3$	90.06	9.006
Magnesium oxide.....	MgO	40.32	2.016
Potassium hydroxide.....	KOH	56.11	5.611
Silver nitrate.....	AgNO_3	169.89	16.989
Sodium bicarbonate.....	NaHCO_3	84.01	8.401
Sodium carbonate.....	Na_2CO_3	106.01	5.301
Sodium chloride.....	NaCl	58.46	5.846
Sodium hydroxide.....	NaOH	40.01	4.001

INDEX

A

- Acidity, of milk, 15, 57, 58
 - test, 345-348
 - in cream grading, 209, 210
 - titration of, 58
- Acidophilus milk, 311
- Acids, amino (*see* Proteins)
 - effect on milk, 68
 - fatty (*see* Fatty acids)
- Adenine, 37
- Adulteration of milk, 61
- Aerobacter aerogenes*, 107, 108
- Albumin, 28, 30, 31, 44, 45, 57, 64, 68
 - in butter, 31
 - coagulation of, 31, 64
 - commercial uses, 31
 - composition, 31
 - influence, of acids on, 68
 - of heat on, 31
 - of rennet on, 31
 - properties of, 30, 31
 - in whey, 31
- Alcohol test, 357, 358
- Alkaligenes viscosus*, 109
- Amino acids (*see* Proteins)
- Annato, 215
- Antiseptics, action on microörganisms, 92
- Arachidic acid, 22
- Arnold test, 359
- Ash, in colostrum, 44, 45
 - composition, 33, 34
 - influence of feed on, 54
 - of milk, 33, 34, 42, 44, 45, 57, 58, 61, 64, 65
 - relation to freezing point, 61
 - specific gravity, 58
 - uses, 34
- Aspergillus repens*, 303

B

- Babcock test, 7, 8, 113-131, 336-338, 363-364
 - for buttermilk, 128-130
 - calibration of glassware for, 338-341
 - centrifuges, 103, 131, 364
 - for cream, 121-128
 - apparatus for, 127, 128
 - approximate determination, 125, 126
 - balance for, 128
 - procedure, 122-125
 - red reader for, 125
 - glassware, description, 126-130, 363, 364
 - specifications, 363, 364
 - historical, 7, 8, 113, 114
 - for milk, 114-121
 - apparatus required, 116, 117
 - defects, 120, 121
 - procedure, 114-120
 - modified, 336-338
 - for butter, 336
 - for cheese, 336, 337
 - for condensed milk, 338
 - for dried milk, 338
 - for ice cream, 337
 - principles underlying, 115, 116
 - for skim milk, 128-130
 - for whey, 128-130
- Bacillus subtilis*, 109
- Bacteria, capsules, 85
 - cell structure, 85
 - definition, 84
 - distribution, 84
 - effect of pasteurization on, 168
 - motility, 86
 - numbers in milk, 85
 - reproduction, 86, 87

- Bacteria, size, 84, 85
(See also Microorganisms)
- Bacterial analysis, counts, 98, 99
effect of clarification on, 166, 167
of separation on, 160, 161
official methods for, 361, 362
- Bacteriology, in dairying, 6, 8, 84
- Bacterium lactis*, 106
- Bacterium lactis acidii*, 106
- Beef fat, composition, 20
- Benzoic acid, 92
- Bichloride of mercury, 92
- Bichromate of potash (see Potassium bichromate)
- Bitter milk, 45-47
- Bixa orellana* (see Annato)
- Borax, 92
- Boric acid, 92
- Breed, influence on color of milk, 43, 44
on composition of milk, 41, 44
on quality of dairy products, 44
on size of fat globules, 19, 26
- Breeds, dairy, 41, 44
- Butter, 201-237
albumin in, 31
analysis, for fat, 352-354
Kohman, 352, 353
modified Babcock, 336
for moisture, 350, 352
for salt, 350, 353, 354
by-products of, 11
calculation of, color for, 324
overrun, 323
salt for, 228, 324
yield, 323
calories in, 82
carotene in, 214, 215
churning of, 215-227
color, 214, 215
artificial, 214
defects, 234
market requirement for, 214, 215
variation in, 59, 60
composition, 205
consumption of, 3
- Butter, cream for, 206-212
ripened for, 213, 214
curd in, 205
defects, 232-234
farm-made, 204, 205, 234-237
fat in, 17
(See also Milk fat)
average per cent, in milk and milk products, 17, 205
fishy flavor in, 35, 233
flavor of, 22, 206-214, 231, 232
food value of, 82
hardness of, 23
historical statements concerning, 5, 7, 113, 114, 132, 201-205
lecithin in, 35
manufacture of, 205-229
by-products from, statistics, 11
processes involved in, 205-229
(See also Buttermaking)
market grades of, 231, 232
marketing of, 229-232
melting point, 23, 24
molds in, 233, 234
mottles in, 232, 233
neutralization of cream for, 210, 211
oil, fat in, 17
pasteurization of cream for, 211, 212
rancidity of, 22, 23, 36, 226, 233
salt in, 205, 228, 234
sampling, 349, 350
score card for, 231
separation of milk for, 205, 206
specific heat of, 62, 63
standards, 205, 227, 228
starters for, 212, 213
statistics, 10, 11
sweet cream, 214, 231
tests for, 349-354
vitamins in, 82
working of, 228, 229
- Butter making, cream for, 206-210
neutralized for, 210, 211
ripened for, 213, 214
factory system of, 7
farm, 204, 205, 234-237
history of, 201-204

- Buttermaking, overrun in, 227, 228
 process of, 205-229
 salting in, 228
 starters in, 212, 213
 working, 228, 229
 (*See also* Butter, Churn, and Churning)
- Buttermilk, 11, 225, 226, 306, 307
 acidity of, 83
 from churning, 306
 commercial uses, 11, 307
 composition, 306
 cultured, 311
 dried, 292, 293, 295, 300
 fat losses in, 220, 224-226
 food value of, 83
 lecithin in, 35
 testing of, 128-130
 viscosity of, 66, 67
- Butyric acid, 20, 28, 109
- Butyrin, 22-25, 27
- By-products (*see* Milk by-products)

C

- Calcium, in cheese, 82
 in milk, 72, 73
- Calcium caseinate, 27
 action of acids on, 239
 formation of, 239
 influence on color of milk, 57
- Calcium paracaseinate, 244
- Calcium phosphate, physical state
 in milk, 57
 precipitation of salts of, 65
- Calories defined, 70
 in various foods, 70, 79
- Capric acid, 20-22, 24, 256
- Caprin, 22
- Caproic acid, 20-22, 24, 256
- Caprylic acid in milk fat, 20-22, 24, 256
- Carbohydrates in milk, 70, 71
- Carbon dioxide in milk, 37
- Carotene, in butter, 214-215
 influence of feed on, 36, 59, 60, 214
 in milk, 35, 36, 60
 relation of breed to, 39, 59, 60, 214
 source of, 35, 36, 60
- Carotenoids (*see* Carotene)
- Casein, in cheese, 28, 29
 coagulation, 64, 65, 244, 308
 in colostrum, 44, 45
 commercial uses, 29, 30, 308
 composition, 308
 drying, 308
 effect of acid on, 29, 68, 308
 of alcohol on, 27, 29
 glue from, 29, 67
 influence of freezing on, 61
 of heat on, 29, 64, 65
 of rennet on, 29, 244
 manufacture of, 29, 308
 in milk, 28, 29
 paints from, 29, 30
 physical state in milk, 27, 57
 plastics from, 29, 30, 308
 properties, 28, 29
 specific gravity, 58
 viscosity of milk influenced by, 66
- Catalase in milk, 36, 37
- Centrifuges for Babcock test, 130, 131, 364
 speed requirements, 130, 131
- Certified milk, 188, 189
- Cheese, 238-260
 American Cheddar, 238, 239, 244-253
 cream, 251
 curing, 249, 250
 defects in, 252, 253
 forms of, 250, 251
 grades, market, 251, 252
 manufacturing procedure, 244-252
 score card for, 252
 American type of Roquefort, 254-256
 Babcock test for, modified, 336, 337
 Brick, 256
 calcium in, 82
 Camembert, 257-258
 casein in, 28
 classification of, 240-242
 Club, 260
 composition, 242, 243
 consumption of, 3

- Cheese, Cottage, 258, 259
 Cream, 259
 Emmental (*see* Cheese, Swiss)
 enzymes, relation to ripening, 36
 fat in, 17
 food value of, 82
 hard, 244-256
 history of, 1, 6, 11, 12, 113, 238, 239
 iron in, 82
 Limburger, 256, 257
 milk used for, 11, 242, 243
 nature of, 240
 phosphorus in, 82
 process, 259, 260
 reworked, 260
 Roquefort, 41, 254-256
 Roquefort type, 254-256
 soft, 256-260
 spreads, 259, 260
 statistics on, 11, 12
 sulphur in, 82
 Swiss, 253, 254
 types on market, 12
 varieties of, 12, 238-242
 yield, 307
Cheese making, curd formation, 244
 factory system of, 7
 fat losses in, 19, 20
 milk for, 11-17, 242, 243
 rennet for, 244, 248
 (*See also* Cheese, American Cheddar, etc.)
Chemistry in dairying, 7
Chlorine solutions, 92, 186
Cholesterol in milk, 35
Churn (*see* Churning)
 combined churn and butter worker, 216-218
 history, 215, 216
Churning (*See also* Butter and Butter making)
 difficult, 19, 226, 227
 factors influencing, 220-225
 acidity of cream, 223, 224
 composition of butterfat, 223
 fullness of churn, 225
 richness of cream, 224, 225
 size of fat globules, 19, 223
 Churning, factors influencing, speed of churn, 225
 temperature of cream, 221, 222
 viscosity of cream, 224
 fat losses in, 225, 226
 nature of, 215, 216
 overrun in, 227, 228
 procedure, 218-229
 temperature, influence of fatty acids on, 23
 theories concerning, 215, 216
Clarification of milk, 164-167
 effect on bacterial count, 166, 167
 on cream line, 167
 on keeping quality, 167
Clarifier, centrifugal, 164-167
 action of, 164-167
 slime from, 166
Clostridium butyricum, 109
Colloidal phosphate, in milk, 59
Color, of milk, influence of breed on, 14, 15, 36, 43, 44, 59, 60
 carotene on, 35, 36, 60
 calcium caseinate on, 59
 colloidal phosphate on, 59
 fat on, 14, 15, 54, 59
 feed on, 15, 54, 55, 59, 60
 heat on, 15
 lactochrome on, 38, 60
 milk solids on, 14
Colostrum, composition and properties, 44, 45
Composite sample, 330-336
Composition of milk (*see* Milk; Milk products; Cheese; etc.)
Concentrated milks, food value, 82
Condensed milk, 281-291
 Babcock test, modified for, 338
 classification, 282, 283
 composition, 17, 283, 284
 defects, 290, 291, 303
 food value, 82
 history, 7, 12, 281, 282
 manufacture of, 178, 179, 285-289
 marketing, 291
 microorganisms in, 290, 291, 301-303
 milk, amount used for, 12
 properties, 284, 285

- Condensed milk, standardization of, 287-289
uses, 290
vacuum pans, construction and operation, 286-290
- Cooling milk, 175
- Copper in milk, 34
- Corrosive sublimate, 92, 334
- Cottonseed meal, effect on fat, 23
- Cream, acidity test for, 345-348
albumin in, 31
approximate fat test for, 125, 126
Babcock fat test for, 121-128
bacteria for ripening, 108, 213, 214
for butter making, 206-210
churnability, factors affecting, 220-226
composite sample of, 335
cooling of, 175
defined, 132
dried, 292
freezing, manner of, 61
grades of, 208-210
homogenization, influence on, 176-178
lecithin in, 35
line, effect of clarification on, 167
of freezing on, 61
of heat on, 65, 66
neutralization of, 210, 211, 324, 325
off-flavors in, 206-208
pasteurization of, 211, 212
plastic, 17
plug, 330
reconstruction of, 179
ripening of, 213, 214
sampling, 328-330
separation of, 132-161
specific gravity of, 367
specific heat of, 62, 63
standardization of, 319-322
viscosity of, 66, 224, 227
weights per gallon of, 367
whipping, 66, 132
(*See also* Separation; Butter)
- Creanery system, historical, 113, 114, 201-204
- Creatine, 37
- Creatinine, 37
- Cryoscope, 354
- Cultured buttermilk, 311
- Curd determination in butter, 354
(*See also* Cheese making; Cheese, Cheddar; Butter)
- D
- Dairy arithmetic, calculations, butter, color, 324
overrun, 323
salt, 324
yield, 323
cream, amount separated, 315-317
neutralization of, 324, 325
standardization of, 319-322
value per gallon, 315
fat, average percentage, 313, 314
ice cream, composition, 325, 326
overrun, 326, 327
markets, most profitable, 316, 317
milk, fat in, 312-319
neutralization, 324, 325
standardization of, 319-322
- Dairy cows, number of, 8, 9
- Dairy-farm inspection, score card for, 365, 366
- Dairy industry, development of, 3-9
extent of, 9-13
permanency of, 4, 5
- Dairy products, consumption of, 3
in the diet, 3, 81-83
early uses, 1, 3
influence of breed on, 44
(*See also* Milk; Milk products)
- Dairying, history, 1-9
relation of, to agriculture, 4-7
- Density of milk (*see* Specific gravity)
- Diastase, 37
- Diphtheria, 104, 111, 168
- Diseases transmitted through milk and milk products, 110, 111, 168
- Disinfectants, 92
- Dried milk, 291-301
action of rennet on, 295

Dried milk, Babcock test, modified
 for, 338
 color, 294, 301
 composition, 293
 defects, 300, 301
 fat in, 17
 food value of, 82
 grading of, 299
 history of, 7, 12, 13, 291, 292
 hygroscopic properties of, 295
 manufacture of, 295-299
 marketing of, 301
 microbiology of, 301, 302
 properties of, 293-295
 solubility of, 294
 standardizing of, 299
 types of, 292
 uses, 299, 300
 Drugs, effect on composition of milk,
 55

E

Emmental cheese (*see* Cheese, Swiss)
 Emulsification of milk, 179
 Enzymes, action of, 96, 97
 cheese ripening, relation to, 36,
 250, 257, 258
 in cream, 207, 226, 227
 effect on milk, 67, 68
 fat splitting, 36
 in milk, 36, 37, 359
 nature of, 96
 relation to off-flavors, in cream,
 207, 226, 227
 in milk, 36, 37, 68
 types of, 36, 37, 97
 (*See also* Catalase; Diastase;
 Galactase; Lactase; Lipase;
 Peroxidase; Reductase)
Escherichia coli, 106
 Evaporated milk (*see* Condensed
 milk).

F

Factory system of dairy manufac-
 turing, 7

Fat, beef, 20, 23
 globules, 17, 20
 of milk, 69, 70, 71
 (*See also* Milk fat)
 Fatty acids, chemical structure, 20,
 23
 composition, 21, 22
 glycerides of, 20, 28
 in milk fat, 20, 28
 influence of breed on, 25, 26
 influence of, on characters of milk
 fat, 25, 26
 on churning, 23
 of feed on, 22, 23, 25, 27
 on flavor of butter, 22
 of lactation period on, 22, 26
 of plane of nutrition on, 27, 28
 insoluble, 22, 23
 non-volatile, 22, 23
 properties of, 23
 relation to melting point of fat, 23
 to rancidity, 23
 soluble, 22, 23
 volatile, 22, 23
 Feed influence, on off-flavors in
 cream, 206, 208
 relation of, to composition of milk
 fat, 26, 27
 Fermentation test for milk, 358, 359
 Fermented milk, 83, 309-311
 Fibrin in milk, 31
 Fili, 311
 Filters for milk, 163, 164
 Filtration of milk, 161, 163, 164
 Fishy flavor, 35
 Flavor of milk, 15, 46, 47, 54, 108-
 110
 effect of heat on, 65
 Food accessories, carbohydrates in,
 71
 cleanliness of, 76
 dairy products for, 81, 83
 digestibility of, 76, 77
 economy of, 77
 energy equivalents of, 77, 78
 fat in, 70, 71
 palatability of, 76
 requirements of, 76, 77

Food accessories, supplying energy,
71
minerals, 73
protein, 71, 72
vitamins in, 74, 76
water content, 70
(*See also* Vitamins)

Formalin, 92, 335

Freezer, ice-cream, 272, 273

Freezing point of milk, 60, 61
determination, 61, 354, 355

G

Galactase in milk, 36

Garget, 100

Garrett-Overman test for ice cream,
337

Gases in milk, 37

Gelatin, 265, 266

Germicides, 92

Globulin in milk, 57

Glycerides, 20, 21, 28

Glycerol, 20, 21

Gravity creaming (*see* Separation)

Guaiac, 359

Guanine, 37

H

Heated milk, test for, 351, 352

History of dairy industry, 1, 4, 5

Homogenization, 176-179, 270, 271

Household foam test for oleomargarine, 359, 360

Human milk, 40

Hydrogen-ion concentration of milk,
57

Hydrogen peroxide, 92, 359

I

Ice cream, 261-280

Babcock test, modified for, 337
brick, 274

bulk, 274

calculation of composition, 325,
326

of overrun, 326, 327

Ice cream, classification, 262, 263

composition of, 262-264, 276

consumption of, 12

defects, 276, 277

defined, 262

distribution of, 278

fat in, 17

flavoring materials for, 264, 266

food value of, 82

forms, individual, 274-276

freezer, 272, 273

Garrett-Overman test for, 337

gelatin for, 265, 266

history of, 12, 261, 262

ingredients used in, 12, 263-266,
276, 277

manufacture in the home, 278, 279

microbiology of, 279, 280

milk for, 276, 277

mix, aging of, 271, 272

calculation of, 267-270

freezing of, 272, 273

homogenization of, 178, 270,
271

pasteurization of, 270

preparation of, 266-272

viscosity of, 67, 271, 272

overrun, 272

proteins in, 28

quality of, 276

of ingredients, 265

stabilizers for, 265, 266

statistics of, 12

sweeteners for, 265

Intestinal disturbances, 102, 111

Iodine in milk, 54

Iron, in cheese, 82

in milk, 73, 74

K

Kaeldermaek, 311

Kefir, 310

Kohman test, for butter, 352-354

Koumiss (Kumyss), 40, 310

L

Laetalbumin, 28, 30, 31

(*See also* Albumin)

- Lactase, 37
 Lactation, stage of, influence on composition of milk, 44, 47
 Lactic acid in fermented milks, 83
Lactobacillus acidophilus, 107, 311
Lactobacillus bulgaricus, 107, 254, 310
 in Swiss cheese, 254
 in Yoghurt, 310
Lactobacillus casei, 107, 250, 254
 in Cheddar cheese, 250
 in Swiss cheese, 254
 Lactochrome in milk, 36, 60
 Lactoflavin (*see* Lactochrome)
 Lactoglobulin, 31, 34
 Lactometer, 342-344
 Lactose, action of bacteria on, 32, 33, 46, 105, 106-108, 110, 310, 311
 in colostrum, 44, 45
 composition of, 32
 manufacture of, 308, 309
 properties of, 32, 52, 58
 relation to freezing point of milk, 61
 to milk products, 33
 in whey, 307, 308
 Lange-milch, 311
 Lange-wei, 311
 Lard, 20
 Lauric acid in milk fat, 20, 21, 22, 24
 Leben, 310
 Lecithin, associated with fat globule, 18
 in dairy products, 35
 trimethylamine from, 35
 Leucocytes in colostrum, 45
 Linoleic acid, 22
 Lipase, in milk, 36, 46, 47, 226, 227
 relation to bitter milk, 36, 46, 47, 109
 to rancidity, 36, 47
 Livestock improvement, 8, 9
- M
- Malta fever, 111
 Malted milk, 300
 Market milk, 180-201
 control of, 182, 195-197
 delivery of, 191
 development, 10, 180, 181, 189-191
 distribution problems, 195
 grades of, 199, 200
 health control, 182, 195-197
 pasteurization of, 198, 199
 plants, 192-195
 problem, complexity of, 182
 production of, 183, 188
 purchasing, methods of, 191, 192
 standardization of, 319-322
 statistics, 10
 supervision, public, 182, 195-198
 transportation of, 189-191
 Marketing, of butter, 229-232
 of cheese, 252
 of condensed milk, 291
 of dry milk, 301
 of ice cream, 278
 Marschall rennet test, 356, 357
 Mastitis, 100, 183
 Meniscus, 120, 122
 Methylene blue test (*see* Reductase, test)
 Microorganisms, in Brick cheese, 256
 in Camembert cheese, 258
 in Cheddar cheese, 247, 249, 250
 in condensed milk, 290, 291, 301-303
 in Cottage cheese, 259
 counting, methods of, 98, 99
 decomposition products from, 89, 97
 in dried milk, 301-303
 effect, of clarification on, 166, 167
 of electricity on, 92, 93
 of filtration on, 164
 of pasteurization on, 168
 of separation on, 160, 161
 of straining on, 162, 163
 of temperature on, 93, 96
 of thunderstorms on, 93
 enzymes from, 96, 97
 in fermented milk, 309-311
 growth, 89-98
 factors influencing, 89-96

- Microorganisms, growth, products of,
89, 96-98
in ice cream, 279, 280
importance in dairying, 84
in Limburger cheese, 257
in milk for cheese making, 243
miscellaneous changes due to, 98
nature of, 84-87
nomenclature of, 88, 89
pigments from, 97
relation to cream ripening, 108,
212-214
to fermentation of milk, 104,
110
in Roquefort cheese, 92, 255, 256
sources in milk, 99-104
in starters, 108, 212, 213
in Swiss cheese, 254
toxins from, 98
(*See also* Bacteria; Molds;
Yeasts)
- Milk, acidity of, 15, 58, 68
test for, 345-348
adhesiveness of, 67
for adults, 81
albumin in, 30, 31
alcohol test for, 357, 358
alcoholic, 110
alkali production in, 108
analysis, for bacterial content,
361, 362
aroma of, 15, 46, 47, 59, 65, 100
ash content of, 16, 33, 34
Babcock test for (*see* Babcock
test)
beverages (*see* Fermented milk)
bitter, 44, 47, 109, 110
boiling point of, 63, 285
for butter making, 10, 11, 201
by-products, 303-309
calcium salts in, 65
carbon dioxide in, 37
carotene in, 35, 36
carotenoids, 35
casein in, 28, 29
catalase in, 36, 37
certified (*see* Certified milk)
characteristics, general, 14, 15
for cheese making, 11, 12, 242, 243
Milk, chemical nature of, 15
for child, 80, 81
cholesterol in, 35
churning of, in shipping, 19, 20
clarification of, 164-167
coagulation, 15
colloidal nature of, 57
color of, 15, 35, 36, 43, 44, 59, 60,
108
colostrum, 44, 45
composition, 15, 16, 38-43
factors influencing, 40-56
condensed (*see* Condensed milk)
for condensed and dried milk, 12
constituents of, 14-37
consumption of, 3, 16
cooling of, 175, 187, 188
copper in, 34
creatine in, 37
creatinine in, 37
defined, 14
delivery of, 188, 191
diastase in, 37
digestibility of, 76, 77
diseases transmitted through, 110,
112
dried (*see* Dried milk)
dry matter in, 16
effect of acids on, 15, 68
of heat on, 15, 64, 66
emulsification of, 179
energy, supplied by, 70, 71, 77
enzymes in, 36, 37
(*See also* Eyzymes)
fat, absorption of odors by, 25
action of centrifugal separator
on, 16, 17, 19
amount in milk, 16
Babcock, official test for, 363,
364
carotene, distribution in, 60
composition, 20, 22, 26, 223
factors influencing, 25, 28,
40-42
defined, 20
digestibility, affected by size of
globules, 20
fatty acids in, 20, 22

- Milk, fat, globules, 15, 18, 20, 223
adsorbed materials on, 17, 18
effect of freezing on, 61
of heat on, 65
of size on churning, 19, 20, 223
of size on separation, 19
factors influencing size of, 19
influence of shipping on, 20
size, importance of, 18, 19, 20
hardness of, 23, 25, 27, 223
in butter, 205
in colostrum, 44, 45
in milk, factors influencing, 40, 49
in milk products, 17, 44
influence of age of cow on, 47
of breed on, 17, 25, 26, 41, 43
of feed on, 23, 26, 27
of plane of nutrition on, 27, 28
of stage of lactation on, 26, 44, 47
loss in cheese making, 242
melting point, 23-27
factors influencing, 23-27
membrane around, 18
nature and structure of, 17, 18
odors absorbed by, 25
physical state in milk, 17, 57
properties of, 23, 25
relation to churning, 25, 223
to flavor of milk, 16
Roese-Gottlieb official test for, 362
softness of, 23
solidifying point of, 24
solubility of, 24, 25
specific gravity of, 24, 58, 126, 133
heat of, 62, 63
structure of, 17, 18
in whey, 129
fermentation of, 15, 104-110
test of, 358, 359
fermented, 309-311
filtration of, 163, 164
flavor, 65, 106-110
as a food, 4, 14, 69-83
food value, 69-83
- Milk, freezing, 60, 61
point of, 60, 354
galactase in, 36
gases in, 37
"germicide" period of, 104, 105
guanine in, 37
history of industry, 4, 7
homogenization of, 176-179
(*See also* Homogenization)
human, composition of, 40
hydrogen-ion concentration of, 15, 57
for ice cream, 12, 276, 277
iodine in, 34
iron in, 34
lactase in, 37
lactochrome in, 36, 60
lactoglobulin in, 31, 34
lactose in, 15, 30, 31, 34, 39, 42, 57
lecithin in, 18, 35
lipase in, 36
losses in handling, 13
malted, 300
market (*see* Market milk)
mineral balance, effect of heat on, 64, 65
minerals in, 33, 34, 39, 42, 57, 58, 61, 64, 65, 69, 72, 73, 79
minor constituents, 34-37
nature of, 14, 15
neutralization, calculation of, 324-325
non-protein, nitrogenous substance in, 37
odor of, 15, 46, 47, 59, 65
palatability of, 76
pasteurization of, 167-176, 198, 199
(*See also* Pasteurization)
peroxidase in, 37
phospholipids in, 35
physical state of, 57
pigments in, 35, 36, 44
plants, 192-195
powder (*see* Dried milk)
preservatives for samples, 330, 334, 335
properties of, 16, 57, 68
protein in, 16, 28, 31, 39, 77, 78

- Milk, proteolysis of, 108
 rancidity of, 47
 reaction of, 15, 57, 58
 reconstituted, 179
 reductase test for, 357
 relation of richness to food value,
 79, 80
 ripening for Cheddar cheese, 247
 ropiness in, 108, 109
 sampling, 328-330
 composite, 330-336
 tube, 330
 sanitary production of, 183-188
 sediment test for, 348, 349
 separation (*see* Separation)
 serum solids of, 16
 solids-not-fat of, 16, 51, 205
 souring of, 91, 105-107
 specific gravity of, 58, 62, 341-
 345
 heat of, 62, 63
 standardization of, 319-322
 statistics, 9-13
 straining of, 161-163
 sugar (*see* Lactose)
 sweet curdling of, 109
 taste of, 15, 46, 47, 57
 total solids, 42
 determination of, 344, 345, 355,
 356
 transportation, 7, 189-191
 urea in, 37
 uric acid in, 37
 uses of, 9-13
 viscosity of, 66, 67
 vitamins in, 74-76
 water in, 16, 57
 wholesomeness of, 112
 yield, influence of age of cow on,
 47
- Milk products, ash in, 34
 food value of, 3, 34, 81, 83
 specific gravity, 341-345
 total solids, determination of, 355,
 356
- Milking machine, 101, 185, 187
- Mineral matter (*see* Ash)
- Mojonnier tester, 355, 356
- Molds, 88
 in butter, 233, 244
 in condensed milk, 303
- Myristic acid in milk fat, 20, 21, 22,
 24
- Myristin, 23, 24
- N
- Neutralization, calculation of, 324,
 325
 of cream, for butter making, 210,
 211
- Non-protein, nitrogenous substance,
 37
- Nutrition, part in development of
 dairying, 4, 8
- O
- Odor of milk, 15, 46, 47
- Off-flavors in milk and cream, 97,
 105-110, 206-208
- Oil test churn, 114
- Oleic acid in milk, 20, 21, 22, 24
- Olein, 24, 25, 26, 27
- Oleomargarine test for, 359, 360
- Oospora lactis*, 258
- Osmotic pressure, 93
- Overrun, in butter, 227, 228, 323
 defined, 227
 in ice cream, 272, 326, 327
 (*See also* Butter; Ice cream)
- P
- Palmitic acid in milk fat, 20, 21, 22,
 24
- Palmitin, 23, 24, 25
- Paraphenylenediamine, 359
- Pasteurization, effect on micro-
 organisms, 92, 95, 168
 of cream for butter making, 211-
 212
 electrical, 92, 176
 flash, 169, 170, 173-175
 as health measure, 198, 199
 history of, 167, 168
 holding, 168-173, 175, 176

Pasteurization, of ice-cream mix, 270
 in-the-bottle, 175, 176
 of milk for starter making, 213
 cheese making, 242
 reasons for, 199
Penicillium camemberti, 258
Penicillium roqueforti, 255
 Peroxidase, 37
 Phenolphthalein, 15, 347
 Phospholipids, 35
 (See also Lecithin)
 Pigments, in milk, 35, 36, 44, 60, 66,
 67
 Plastic cream, 17
 Potassium, bichromate, 335
 chromate, 351, 352
 Preservatives, 92, 334, 335
 Primost, 307
 Process cheese, 259, 260
Propionibacterium shermanii, 254
 Proteins, composition of, 28, 71, 72
 in foods, 71, 72
 in milk, 20, 31, 46, 71, 72
Pseudomonas syncyanea, 110
 Püma, 311

R

Rancidity, of butter, 22, 23, 26, 226
 due to enzymes, 36
 of ice cream, 277
 of milk, 47
 Reagents, table of *N/10* solutions,
 373
 Reductase, in milk, 36, 37
 test, 357
 Refrigeration, artificial, 8
 Rennet, action on milk, 68, 244, 356
 addition to milk for Cheddar
 cheese making, 248
 for cheese making, 244
 Marshall test for, 356, 357
 Roese-Gottlieb fat analysis, 341, 355

S

Salicylic acid, 92
 Salt, in butter, 228
 in cheese, 249, 254, 255, 257, 258,
 259

Salt (see Ash)
 Sampling (see Milk; Cream)
 Scandinavian fermented milks, 311
 Scarlet fever, 104, 110, 111, 168
 Score card, for butter, 231
 for cheese, 252
 for dairy farm, 365, 366
 Sediment test, 348, 349
 Separation, calculations on, 315-317
 centrifugal, 138-161
 control of richness of cream by,
 145-147
 cream, basic principle, 133, 134
 historical, 132, 133
 early development, 138-140
 effect, on fat globules, 19
 on microorganisms in milk,
 160, 161
 factors influencing, fat percentage
 of cream, 145-154
 variations under practical con-
 ditions, 153, 154
 gravity, 134
 deep setting, 135, 136
 shallow pan, 134, 135
 water dilution, 137, 138
 Separator, bowl, disk, 139, 141, 143-
 145
 hollow, 139, 141
 centrifugal action, 140, 141
 cleaning of, 187
 construction of, 141-145
 course of milk through, 140, 141
 cream screw, effect on richness of
 cream, 145, 146
 efficiency of, 154-159
 factors governing efficiency of,
 155-159
 factory type, 139, 140, 159
 hand type, 140
 history of, 8, 138-140
 influence of, on butter industry,
 202-204
 on dairying, 7, 8
 principle of, 133, 134
 Septic sore throat, 100, 104, 110, 111
Serratia marcescens, 108, 110
 Serum solids of milk, 16
 Shallow pan (see Separation, gravity)

- Silver nitrate, 351-353
 Skim milk, for animal feeding, 304, 305
 Babcock test for, 128-130
 as a by-product, 10, 304
 Cheddar cheese from, 251
 composition of, 304
 Cottage cheese from, 258
 dried, 292
 as human food, 305
 specific heat of, 62, 63
 uses, 11, 304-306
 vitamin content of, 83
 Sodium hydroxide, 346, 347, 373
 Soft curd milk, 200
 Solids-not-fat of milk, 16
 influence of seasonal variations on, 49-51
 Solutions, tenth normal, 373
 Souring of milk, influence of thunder storms, 93
 Specific gravity, 58, 341-345
 of cream, 367
 of milk, 58, 341
 products, 342
 Specific heat of milk and dairy products, 62, 63
 Standard units of measure and weights, 368
 Standardization of milk and cream, 319-322
 Starters, for cheese making, 247, 254, 257-259
 for cream ripening, 212-214
 microorganisms in, 108, 212-214
 nature and properties, 212-214
 preparation and propagation of, 212, 213
 Stearic acid in milk fat, 20, 21, 22, 24
 Stearin, 24, 25
 Sterilization, 96, 186, 187
 Storch test, 359
 Straining of milk, 161-163, 187
Streptococcus citrovorus, 108, 311
Streptococcus lacticus, 106
Streptococcus lactis, 89, 106-108, 250, 258, 311
 in Camembert cheese, 258
 in Cheddar cheese, 250
Streptococcus lactis, in cultured buttermilk, 311
 in Yoghurt, 311
Streptococcus liquefaciens, 108, 109, 110
Streptococcus paracitrovorus, 108, 311
 Sulfuric acid for Babcock test, 116, 363
 Summer complaint, 102
 Sweet cream butter, 214, 231
- T
- Tables, conversion, for temperature, 370, 371
 for weights and measures, 368
 Taette, 311
 Tallow, composition, 20
 Taste and odor of milk, factors influencing, 15, 46, 47, 54, 59
 Tests, acidity, 345-348
 alcohol, 357
 Arnold or guaiac, 359
 Babcock, modified for milk products, 336, 337
 butter, 349-354, 359, 360
 Cornell salt, 350, 351
 Crowe, 337
 cryoscopic, 354
 curd, 354
 fermentation, 358-359
 for frozen cream, 329
 Garrett-Overmann, 337, 338
 for heated milk, 359
 Kohman, 352-354
 Marshall rennet, 356
 methylene blue, 357
 modified Babcock, 336, 337
 Mojonnier, 355, 356
 for oleomargarine, 359, 360
 reductase, 357
 Roese-Gottlieb, 341, 355
 sediment, 348, 349
 specific gravity, 341-345
 Storch, 359
 total solids, 344, 345, 356
 (See also Babcock test)
Torula amara, 110
 Total solids, 42
 determination of, 344, 345, 356, 369

Transportation of milk, 7, 189-191

Trimethylamine, 35

Tuberculosis, 100-102, 110, 111, 168

Typhoid fever, 103, 104, 110, 111,
168

U

Ultra-violet rays, 92

Undulant fever, 110, 111, 168

Urea, 37

Uric acid, 37

Utensils, care of, 186, 187

V

Vacuum pan, 281, 296, 301, 308

Ventilation, 102

Viscosity, of buttermilk, 66, 67

of condensed milk, 67, 284, 285

of cream, 66, 224, 227

of ice-cream mix, 67, 271, 272

measurement of, 67

of milk, 66

influence of various factors on,
65, 66

products, importance, 66, 67

Vitamins, in butter, 82, 215

in milk, 37, 74-76

in skim milk, 83

W

Water, adulteration of milk with, 61

in foods, 70

in milk, 70

physical state in milk, 57

Weights and measures, per gallon
of cream, 367

tables for conversion, 368

Whey, from Cheddar cheese, 248

composition of, 307

dried, 292, 309

fat in, 129

lactose from, 307-308

Primost from, 307

specific heat, 62, 63

testing of, 128-130

use of, 307

(See also Cheddar cheese)

X

Xanthophyll, in corn, 36

Y

Yoghurt, 310, 311

Yeasts, 87, 88

in butter, 234

in fermented milk, 310

SF 239 E194 1936
ECKLES CLARENCE HENRY
1875-1933
MILK AND MILK PRODUCTS
40805013 SCI

000031387079

A37753