3 1761 05478940 9

S&M

A

450

A. Ryerson

Chrysothrix

Digitized by the Internet Archive
in 2007 with funding from
Microsoft Corporation

WORKS OF
CLARENCE W. HUDSON

PUBLISHED BY

JOHN WILEY & SONS

Notes on Plate-Girder Design.

8vo, vii + 75 pages, figures throughout the text
and 2 folding plates. Cloth, \$1.50 net.

Deflections and Statically Indeterminate Stresses.

Small 4to, xiii + 258 pages, profusely illustrated
with figures in the text, and full page plates
Cloth, \$3.50 net.

NOTES

ON

PLATE-GIRDER DESIGN

BY

CLARENCE W. HUDSON, C.E.

MEM. AM. SOC. C.E.

*Professor of Civil Engineering, Polytechnic Institute of Brooklyn, N. Y.
Consulting Engineer*

FIRST EDITION

FIRST THOUSAND

NEW YORK

JOHN WILEY & SONS

LONDON: CHAPMAN & HALL, LIMITED

1911

Copyright, 1911,

BY

CLARENCE W. HUDSON

THE SCIENTIFIC PRESS
ROBERT DRUMMOND AND COMPANY
BROOKLYN, N. Y.

PREFACE

THE following Notes on Plate-Girder Design have been used by the author to give his civil engineering students the theoretical and practical information necessary to enable them to make a design and general detailed drawing for a through plate-girder railway bridge. The theory of the plate girder has been developed so that it may be applied to such structures for any duty. The notes may easily be given to the average class in one recitation per week for one semester of the college year. They have greatly facilitated the computation and drawing-room work with my own classes.

It is with the hope that they may be useful to other teachers, and engineers, that they are published.

C. W. HUDSON.

POLYTECHNIC INSTITUTE, BROOKLYN, N. Y.,
January, 12, 1911.

CONTENTS

ARTICLE 1. STRESS DISTRIBUTION AND GENERAL.....	1
<p>Theory of stress distribution. Limits of the use of the plate girder. Design and detail drawing for a single-track deck plate-girder bridge. Design and detail drawing for a single-track through plate-girder bridge. The weight of a plate girder. Problems.</p>	
ARTICLE 2. REQUIRED AREA OF CROSS-SECTION FOR THE FLANGES,....	2
<p>Figures showing make up of cross-section for plate girders. Formula for obtaining the required area of the tension flange. Problems.</p>	
ARTICLE 3. THE DESIGN OF THE CROSS-SECTION OF THE FLANGES,.....	5
<p>Composition of the flanges. Minimum pitch of rivets in tension flanges. Formula for a safe unit stress for the compression flange. Thickness of material in compression flanges. Problems.</p>	
ARTICLE 4. LENGTHS OF COVER PLATES.....	14
<p>Formulas for the length of cover plates for girders carrying uniform and concentrated loads by analytic methods. Graphic determination of lengths of cover plates. Examples of the application of the formulas for finding lengths of cover plates. Problems.</p>	
ARTICLE 5. RIVET SPACING IN GIRDER FLANGES.....	20
<p>Rivet spacing a function of the shear. Formulas for spacing rivets connecting flanges to the web. Formulas for spacing the rivets connecting the component parts of the flanges. Formula for rivet spacing at the ends of cover plates. Problems.</p>	

	PAGE
ARTICLE 6. WEB PLATES.....	28
<p>Stresses on the faces of an element of the web. Stresses of maximum intensity and the planes on which they act. Computation of the stress intensity at various points in the web for a definite case. Problems.</p>	
ARTICLE 7. AREA OF WEB PLATES.....	37
<p>Discussion of stress distribution throughout the web plate. Relation of shearing and compression unit stresses. Unit stresses for shear and compression in web plates. Problems.</p>	
ARTICLE 8. STIFFENERS FOR WEB PLATES.....	42
<p>Functions of stiffeners. Intermediate stiffeners. Concentrated load stiffeners. Formulas for size of stiffeners. Spacing of stiffeners. Problems.</p>	
ARTICLE 9. SPLICES FOR WEB PLATES.....	46
<p>Arrangement of splices. Duty of a web splice. Thickness of web splice plates. Number and arrangement of rivets in the splice. Maximum stresses on the rivets of a web splice. Problems.</p>	
ARTICLE 10. SPLICES FOR THE COMPONENT PARTS OF THE FLANGES....	51
<p>Location of splices in flange material. Disposition of flange splicing material. Rivets for splicing the component parts of the flanges. Problem.</p>	
ARTICLE 11. CONNECTING ONE GIRDER TO ANOTHER.....	55
<p>Size and arrangement of the material for the connection. Rivets for the various parts of the connection.</p>	
ARTICLE 12. END BEARINGS.....	59
<p>The duty of end bearings. Area of bearing on masonry. Proper length and width of bearings. Thickness of bearing plates. Different forms of end bearings. Problem.</p>	

CONTENTS

vii

	PAGE
ARTICLE 13. POSITIONS OF LOADING FOR MAXIMUM SHEAR AND MOMENT.....	64
<p>Maximum end shear. Maximum shear at any point. Maximum moment at any definite point. Absolute maximum moment and the point at which it occurs. Problems.</p>	
ARTICLE 14. PREPARATION OF A TABLE OF BENDING MOMENTS, SHEARS, AND CONCENTRATED LOADS FOR COOPER'S E_{40} LOADING.....	69
<p>Advantages of tables of moments and shears. Equations for maximum moments. Preparation of a table of moments. Table of, and sketches showing positions of loads for maximum moments. Problems.</p>	
ARTICLE 15. TABLE OF MOMENTS, SHEARS, AND CONCENTRATED LOADS FOR COOPER'S E_{60}	74

NOTES ON PLATE-GIRDER DESIGN

ART. 1. STRESS DISTRIBUTION AND GENERAL

The theory of stress distribution for plate girders is the same as that for solid beams of uniform material, it being generally assumed that the common theory of flexure applies with sufficient accuracy to the built-up girder. This assumption is certainly not strictly true. The rivets connecting the various parts together cause a local and small irregularity of stress distribution; splices of the various parts, and non-prismatic form, produce quite marked irregularity of this distribution. The "Theory of Flexure" properly applied to plate-girder design, however, leads to a thoroughly good engineering structure, as an immense tonnage of such work constructed during the past forty years and doing excellent duty witnesses.

This wide use of the plate girder for service under greatly varying conditions has increased the knowledge of its capacity and given valuable practical information as to the design of certain of its features.

The requirements for its fabrication, shipment and erection have also affected its design. These requirements are not fixed in their nature, although in certain respects,

such as minimum thickness of material in web plates, and minimum edge distances for punching, they fix a limit to the size of certain parts.

The correct design of plate girders therefore requires theoretical knowledge and either practical experience or formulated rules, based on practical experience, and so carefully and closely drawn as to prevent a poor design.

Plate girders are used for bridges anywhere from 18" deep and 15' long to 126" deep and 130' long, and even beyond these limits; they are also used in buildings and other important engineering work to a great extent. In general, the lower limit of their use is the I beam, which will furnish the proper strength at a less cost per pound of material; their upper limit is the truss, whose total cost is less than the heavier but cheaper per pound girder.

In order to design properly any structure it is necessary to understand the composition and relation of each to each of the various parts. The following drawings are meant to illustrate some of the most essential features of plate-girder construction. They are therefore not meant to be casually inspected, but thoroughly studied, and the function of the various parts in carrying a load to the supports, the makeup of the parts and their connection, each to each clearly understood.

Fig. 1a shows a single-track deck plate-girder bridge.

Fig. 1b shows a single-track through plate-girder bridge.

The computation of the stresses in any structure is the preliminary step in the design. The stresses themselves are a function of the weight of the structure, and hence an early estimate of the weight of each portion of the

Hending, Live.....	3,340,900
Dead.....	658,100
	<u>3,999,000 ÷ 8.5 = 470,500</u>
	at 10.000 = 47.05 sq. in.
End shear, Live.....	196,000
Dead.....	34,000
	<u>230,000</u>

STANDARD NO. 17

80'-0" OVER ALL, DECK PLATE GIRDER, S.T.
THE NATIONAL LINES OF MEXICO
Scale $\frac{1}{4}" = 1'-0"$. April, 1907

BOLLER & HODGE,
Consulting Engineers, New York

Section of the
 building
 showing the
 interior of the
 building
 showing the
 interior of the
 building

SECTION OF THE

SECTION OF THE
 building
 showing the
 interior of the
 building
 showing the
 interior of the
 building

Architectural drawing showing structural details and dimensions.

Architectural drawing showing structural details and dimensions.

Architectural drawing showing structural details and dimensions.

Architectural drawing showing structural details and dimensions.

structure is necessary. Many valuable compilations of weights of structures are to be had, but they are not usually accompanied by full data. Every engineer must be sure of the quantities which go into his structure, and they therefore should be estimated as the computations are carried along and all computations based on wrong assumed dead loads corrected.

The design of a structure should always begin with the part receiving the load and follow with each successive part in the path of the load as it travels to the support.

For example, in an ordinary through plate-girder railroad bridge, the design of the various parts should be made in the following order: Rails, ties, stringers, floor-beams, lateral bracing, and main girders.

In making a first estimate of the weight of any girder, compute the live-load stress at the center of the bottom flange and increase this for impact if any is to be added, add to this sum 15% for the stress due to the weight of the girder, then determine the net area of this member in square inches. This net area in square inches multiplied by 14 will give a weight per foot of girder which may be used as a first estimate.

This estimate is based on equal gross areas 15% greater than the net area of the bottom flange, for top flange, bottom flange, and web, and their sum increased 15% for details. An error of 1% in the total stress due to a wrong first assumed dead load should require a corrected dead load to be used.

It is very difficult to give a good general rule for estimating the weight of girders, as the weight obviously is a

function of the depth, loading, unit stresses, and many other things.

PROBLEMS

1a. Sketch the cross-section of a plate girder with and without cover plates, and write the name of each part on the sketches.

1b. Sketch the plan of single-track railroad deck plate-girder bridge and write the names of the various parts on the sketch.

1c. Sketch the plan of single-track railroad through plate-girder bridge, and write the names of the various parts in the sketch.

ART. 2. REQUIRED AREA OF CROSS-SECTION FOR THE FLANGES

The plate girder is a built-up structure, and may be made with a variety of cross-sections depending on the requirements of the case. The forms of cross-section most frequently used are those of *a*, *b* and *c* of Fig. 2.

FIG. 2.

The object of these forms being to take advantage of the known law of stress distribution in flexure.

The relation between the moment of the outer forces and inner stresses for homogeneous bodies subject to flexure is given from the formula

$$M = \frac{SI}{c},$$

in which M is the moment of the outer forces;

S is the unit stress in the extreme fiber of the cross-section under consideration;

I is the moment of inertia of the cross-section;

c is the distance from the neutral axis to the extreme fiber of the cross-section.

Any existing straight prismatic girder may be examined for intensity of flexural stress in a plane normal to the axis by means of this formula. The plate girder of prac-

FIG. 2d.

tice is, however, far from the ideal prismatic bar of the Theory of Flexure. The application of the preceding formula to the design of girders is very tedious, and while it could be greatly facilitated by the use of tables of $\frac{I}{c}$ for a great variety of cases, the labor of its application to problems of design is not warranted.

The almost universal method of plate-girder flange design will now be developed, with the aid of the following nomenclature and Fig. 2d.

Let A be the net area of each flange;

h be the distance c. to c. of gravity of flanges;

S be the allowable unit stress for tension or compression produced by flexure;

h_1 be the depth of the web plate;

t be the thickness of the web plate;

h_2 be the depth out to out of flanges;

I_f be moment of inertia of each flange about its own horizontal axis.

Then the flexure formula becomes

$$M = \frac{SI}{c} = \frac{S}{\frac{h_2}{2}} \left[2 \times A \times \left(\frac{h}{2} \right)^2 + \frac{th_1^3}{12} + 2I_f \right],$$

$$M = S \left[A \cdot h \cdot \frac{h}{h_2} + \frac{th_1}{6} \cdot h_1 \cdot \frac{h_1}{h_2} + \frac{4I_f}{h_2} \right].$$

The right half of this equation represents the moment of the internal stresses; of the three terms which make up this half it may be said:

The term $\frac{4I_f}{h_2}$ is small in most cases, but for shallow girders it is relatively quite large, its omission from the expression requires the other terms to be larger.

The value of $\frac{h}{h_2}$ is always less than unity, and in shallow girders considerably less, frequently as much as 10%.

The value of $\frac{h_1}{h_2}$ is usually less than unity, for very shallow girders without cover plates it is often equal to unity, and for girders with two or more cover plates it may be as much as 10% less than unity.

If h , h_1 , and h_2 be taken equal, and the term $\frac{4I_1}{h_2}$ be dropped the formula may be written:

$$M = S \left(A \cdot h + \frac{th_1}{6} \cdot h \right) = Sh \left(A + \frac{th_1}{6} \right).$$

That is, the approximate moment of the internal stresses equals the unit stress times the depth times the net area of one flange plus $\frac{1}{6}$ of the area of the web plate. Many engineers drop the $\frac{th_1}{6}$ from the expression, as its value is small and it is on the side of safety to do so. Others include it with the idea that as the web takes a part of the horizontal stresses these horizontal stresses should be considered in designing the flanges and web splices. Where stiffeners or splices are used on the web it is impossible to maintain the full web section, and the web available as flange is usually taken as $\frac{th_1}{8}$, which corresponds to a vertical rivet pitch of about 4". The preceding formula should be written for the purpose of design:

$$A = \frac{M}{hs} \frac{th_1}{6}, \quad . \quad . \quad (1) \quad \text{or} \quad A = \frac{M}{hs} \frac{th_1}{8}. \quad . \quad . \quad (1')$$

In this formula $\frac{M}{h}$ is known as the flange stress, just as in the case of trusses the moment divided by the depth is the chord stress.

PROBLEMS

2a. Compute the net area required in the flanges of a plate girder 30' long and 48" deep out to out of flange angles, when carrying two loads, of 160,000 lbs. each, spaced 5' from the center of the girder and a uniform load of 300 lbs. per linear foot. Assume a web plate of $48 \times \frac{1}{2}$ ".

2b. Make up a section for the bottom flange of the girder of Prob. 2a, using only two angles.

2c. Make up a section for the bottom flange of the girder of Prob. 2a, using two cover plates and two angles.

ART. 3. THE DESIGN OF THE CROSS-SECTION OF THE FLANGES

Flanges of plate girders are generally composed of angles in pairs or angles in pairs and plates, as is shown in Fig. 2a, 2b, and 2c. The several parts are connected by rivets. The holes for the rivets are generally punched to a diameter $\frac{1}{16}$ " greater than that of the rivet, or to a diameter of $\frac{3}{16}$ " less and subsequently reamed to $\frac{1}{16}$ " greater, or, as in the best class of railway work, drilled to a diameter $\frac{1}{16}$ " greater than that of the rivet. It is customary in designing tension members to allow for a hole $\frac{1}{8}$ " greater in diameter than that of the rivet, that is, for a $\frac{3}{8}$ " rivet a hole 1" in diameter should be deducted. The number of holes to be deducted from any tension flange depends on the number of rows of rivets and the spacing of the rivets in the rows. Much might be written on this point, but here only little will be given.

For the flange shown in *a* in section, the views of *c* and *d* are longitudinal developments of one of the angles showing common methods of grouping the rivets.

It is clear that a symmetrical arrangement of rivets such as shown in *c* is better than that of *d*, for the center of gravity of the net area through *x-x* and *y-y* of *c* lies in the root of the angle, while for the corresponding sec-

FIG. 3.

tions of *d* it is first to the right of the root and then to the left, as indicated. The arrangement at *d* is sometimes chosen because it permits a little more freedom in driving one of the inner lines of rivets. Care must be taken in locating the sections *x* and *y* so that $2D + H \geq V$; for the case selected the longitudinal pitch *p* cannot be less than $\sqrt{3.25^2 - 2.25^2} = \sqrt{\frac{88}{16}} = \frac{1}{4}\sqrt{88} = 2.35''$. In fact the stresses

passing through the space marked D are considerably bent and thereby increased, and therefore the distance p for a good stagger for this case should be 3". It should be noted that most girders have an excess of strength except at the point of maximum bending moment and at the ends of cover plates, and hence care in staggering the rivets need only be exercised at these points.

The entire flange stress is developed in small increments by the web and transmitted to the flange by the rows of rivets connecting the vertical legs of the angles to the web. It is clear that these angles then should comprise a considerable part of the total flange area—some engineers require 50%, others permit as little as 33½%. The girder which has a flange stress developed in a short distance requires heavier angles than one in which the stress is developed in a great distance. The foregoing provision for maintaining net section applies particularly to the tension flange. The compression flange is usually made equal in gross area to the tension flange.

The compression flange is in somewhat the condition of a column as far as liability to failure in a sidewise direction is concerned. For girders with a constant top flange section the maximum unit stress occurs only at the point of maximum moment, for a flange with cover plates; that is, for a flange which varies closely as the flange stress, the unit stress is nearly constant throughout. The web stiffeners, if any are used, give considerable lateral stiffness to the top flange, reaching and connecting, as they do for half their length to material in tension. The sketch of Fig. 3e will help make this point clear. The tension flange

is held in line by virtue of its stress; any tendency to side-wise deflection of the compression flange is resisted by the tension flange if stiffeners are used.

If the unit stress for static loads in tension is 16,000 lbs. per square inch, then $16,000 - 70 \frac{l}{r}$ is a corresponding unit stress for a compression member, in which the quantities need no definition. If it be assumed that a girder flange

FIG. 3e.

is similar to a column in its action and that its section is a rectangle whose width = b , then

$$\left(16,000 - 70 \cdot \frac{l}{r}\right) = \left(16,000 - 70 \cdot \frac{l}{b} \sqrt{\frac{1}{12}}\right) = 16,000 - 242 \frac{l}{b},$$

or

$$16,000 - 240 \frac{l}{b}, \quad . \quad . \quad . \quad . \quad . \quad (2)$$

gives a compressive unit stress for a girder flange corresponding to 16,000 lbs. per square inch in tension. As the stress in a girder flange is only a maximum for a

small part of its length a formula for the safe compressive and unit stress

$$P = 16,000 - 200 \frac{l}{b}, \quad (2')$$

may be used.

Experience has shown that no material should be used which is less in thickness than $\frac{1}{16}$ of the distance between the rivets in the direction of the action of the stress, $\frac{1}{8}$ of the distance from the center of a rivet to the edge of the piece at right angles to the line of stress, or that any angle leg when used alone in a girder flange shall be longer than 12 times its thickness, otherwise the girder flange may fail in detail rather than as a whole.

For simplicity and ease of construction the compression flange should not be made of greater section than the tension flange, therefore the compression flange must be supported in a sidewise direction at frequent intervals, which, from the preceding formula, will be about every ten times the flange width. It is customary to consider that the rivets completely fill the rivet holes in the compression flange and that the full gross section of the flange may be assumed to act to resist compression. This assumption with regard to the rivets always filling the holes is open to serious question, and if they do fill the holes they do not offer the same resistance to lateral deformation which takes place under compression as the unpunched material. However, it is fair to assume that they partially make up the punched-out material. The formula for the unit stress for the compression flange is believed to be severe enough to allow it to be applied to the gross area

of the flange. The depth h (called the effective depth) of formula (1) is obtained by taking the gross area of both flanges in computing the location of the center of gravity of the flanges.

It should be borne in mind that if there is no lateral deflection of the top flange that its maximum unit stress depends entirely on $\frac{I}{c}$, the section modulus, as it is sometimes called. While rivet holes affect the position of the neutral axis for the sections in which they occur, probably two-thirds or one-half of the length of a girder will be undiminished by holes, hence in applying the formula $M = \frac{SI}{c}$ to check the results of formula (1) it will be best to determine the position of the neutral axis from the gross section, and find the moment of inertia of the net section of the entire girder section for I in the formula.

PROBLEMS

3a. Compute the probable maximum unit stress in the tension flange of the girder of Prob. 2b, by means of the formula $M = \frac{SI}{c}$.

3b. Compute the probable maximum unit stress in the tension flange of the girder of Prob. 2c, by means of the formula $M = \frac{SI}{c}$.

3c. Compute the probable maximum unit stress in the compression flanges of Probs. 3a and 3b, by means of the formula $M = \frac{SI}{c}$.

ART. 4. LENGTHS OF COVER PLATES

The plate girder, being a composite structure, may easily be constructed so that its cross-section may vary approximately as the moments and shears require. The full flange section being required only where the moment is a maximum, a method of determining where the parts may be omitted when no longer required is necessary to economically design the girder. In general the cover plates are the only parts of the flange which do not extend the full length. Two methods will be developed for finding where cover plates (or any other part of the flange) may be omitted.

The first: For girders which carry a uniform load, or a load which may be closely represented by a uniform load. Deck plate girders for railway bridges may be included in this classification.

In Art. 2 the approximate moment of the internal stresses at any section $= Sh \times \left(A + \frac{th_1}{6} \right)$ in which $\left(A + \frac{th_1}{6} \right)$ is the net flange area, designating this area by a for simplicity, the moment of the internal stresses becomes Sha .

Let w = the uniform load per foot of girder, or for locomotive loading the uniform load which would produce the same end shear, then the bending moment at any point distant x from the end $= \frac{wx}{2} - \frac{wx^2}{2}$, and this must equal the moment of the internal stresses.

$$\therefore \frac{wx}{2} - \frac{wx^2}{2} = Sha,$$

if it is desired to find the location of the point n , where the first cover plate must begin, substitute for S , h , and a their value for the portion of the girder between the end and n and solve for x . It is more convenient in practice to have the formula in such form as to give the length of cover plate direct. For this purpose

Let c = the theoretical length of any cover plate $= l - 2x$;

C = the practical length of any cover plate $= c + y$
 (y = from 2 to 5 feet) the additional length y being required for locating a few rivets, so that the plate may be capable of taking stress where it is theoretically required.

FIG. 4a.

From the foregoing relation between the moments of the outer and inner forces may be written

$$x^2 - lx + \frac{l^2}{4} = \frac{l^2}{4} - \frac{2Sha}{w} \quad \text{and from this} \quad x = \frac{l}{2} - \sqrt{\frac{l^2}{4} - \frac{2Sha}{w}}.$$

$$\therefore C = y + c = y + l - 2x$$

$$= y + l - 2\left(\frac{l}{2} - \sqrt{\frac{l^2}{4} - \frac{2Sha}{w}}\right) = y + 2\sqrt{\frac{l^2}{4} - \frac{2Sha}{w}}. \quad (3)$$

To use the formula to find the length of the second plate, take a and h for the portion of the girder between n and o .

Another simple formula by the author for finding the lengths of cover plates for this class of loading is given in Eng. News, XXXII, page 278, the issue of Oct. 4, 1894.

The second: For girders carrying loadings which may not be represented by a uniform load. Girders of this class receive their loads through other girders or columns at definite points. The main girders of through plate girder spans with floorbeams are common examples of this class.

As before the resisting moment $=Sha$, where

a = area of flange at end of any cover;

h = depth c. to c. of gravity of flanges at end of any cover;

S = unit stress.

The bending moment M at any point along the length of the beam and distant x from the left end, where P_1 , P_2 , P_3 , etc., of Fig. 4b are the concentrated loads, w the

FIG. 4b.

uniform load per foot of length, and R_1 the left hand reaction, is given from

$$M = R_1x - wx \cdot \frac{x}{2} - P_1(x - 0) - P_2(x - b) - \text{etc.}$$

Since the moment of the external forces = moment of internal stresses

$$R_1x - \frac{wx^2}{2} - P_1(x-0) - P_2(x-b) + \text{etc.} = Sha, \quad (4)$$

in which every quantity is known except x .

To apply this to any point n between the first concentrated and the end the above becomes

$$R_1x - \frac{wx^2}{2} = Sha, \quad (4')$$

in which R_1 and Sha are known, and the solution of which is a very simple matter. It should be noted that the proper position for the live load is that which makes R_1 a maximum.

To apply it to any point q between two loading points the formula becomes,

$$R_1o + (R_1 - P_1)(x-o) - \frac{wx^2}{2} = Sha. \quad (4'')$$

The position of the live load must be taken, first, so as to make the bending moment at P_1 a maximum; second, so as to make the bending moment at P_2 a maximum.

This gives two equations of the form of (4'') each of which must be solved for x .

The value of x , which is least, i.e., the one requiring the longest cover, is to be taken.

The lengths of cover plates are readily found by a graphic method which needs no explanation beyond the following sketch: 4c. The full line is drawn to represent

the resisting moment of the various portions, and the dotted line the moments of the outer forces.

The application of formulas (3) and (4) will now be made to finding the lengths of cover plates; for this purpose assume a girder 43' long c. to c. end bearings, $60\frac{1}{2}$ "

FIG. 4c.

deep out to out of flange angles and of the following composition:

$$\begin{aligned}
 1 \text{ web plate } 60 \times \frac{3}{8} &= 22.50 \text{ sq.in.} \times \frac{1}{2} &= 2.81 \text{ sq.ins.} \\
 2 \text{ top angles } 6 \times 6 \times 19.6 &= 11.52 + 2.81 &= 14.33 \text{ sq.ins.} \\
 1 \text{ top plate } 14 \times \frac{1}{2} &= 7.00 + 14.33 = &= 21.33 \text{ sq.ins.} \\
 1 \text{ top plate } 14 \times \frac{1}{2} &= 7.00 + 21.33 = &= 28.33 \text{ sq.ins.} \\
 2 \text{ bottom angles } 6 \times 6 \times 19.6 &= 11.52 - 2.00 = 9.52 + 2.81 &= 12.33 \text{ sq.ins.} \\
 1 \text{ bottom plate } 14 \times \frac{1}{2} &= 7.00 - 1.00 = 6.00 + 9.52 = &= 15.52 \text{ sq.ins.} \\
 & &= 18.33 \text{ sq.ins.} \\
 1 \text{ bottom plate } 14 \times \frac{1}{2} &= 7.00 - 1.00 = 6.00 + 15.52 = &= 22.52 \text{ sq.ins.} \\
 & &= 24.33 \text{ sq.ins.}
 \end{aligned}$$

The girder will first be assumed to act as in a single-track deck railway bridge, using formula (3),

Maximum bending moment = 1,938,410 ft.lbs.

$$\text{Maximum end shear} = 193,500 \text{ lbs.} \left(w = \frac{193,500}{21.5} = 9000 \right).$$

$$a = 12.33, 18.33, \text{ and } 24.33 \text{ sq.in.}$$

$$h = 4.77, 4.85, \text{ and } 4.93 \text{ ft.}$$

$$\begin{aligned}
 \text{For first cover } C_1 &= y + 2\sqrt{\frac{(43)^2}{4} - \frac{2 \times 12.33 \times 4.77 \times 16,000}{9000}} \\
 &= y + 2\sqrt{462.2 - 209.1} = y + 2\sqrt{253.1} \\
 &= 2 + 2 \times 16 = 34' \text{ long.}
 \end{aligned}$$

$$\begin{aligned}
 \text{For second cover } C_2 &= y + 2\sqrt{462.2 - 2 \times \frac{1833}{9000} \times 4.85 \times 16,000} \\
 &= y + 2\sqrt{462.2 - 316.1} = y + 2\sqrt{146.1} \\
 &= 2 + 24 = 26'.
 \end{aligned}$$

The girder will now be assumed to have floorbeams attached to it as indicated in Fig. 4d. The reaction R_1 , when the moment at P_1 is a maximum, is 136,500 lbs. and the own weight of the girder 300 lbs. per linear foot.

FIG. 4d.

Then for the first cover

$$136,500x - 300\frac{x^2}{2} = 12.33 \times 4.77 \times 16,000 = 941,000.$$

$$\begin{aligned}
 910x - x^2 &= 6273 \quad \text{or} \quad x^2 - 910x + 207025 = -628 + 207025 \\
 x &= 45.5 - 38 = 7.5.
 \end{aligned}$$

The length of the first cover $C_1 = 2 + (43 - 15) = 30'$.

For the second cover

$$136,500x - 150x^2 = 18.33 \times 4.85 \times 16,000 = 1,422,400.$$

$$x^2 - 910x = 9483;$$

$$x = 455 - 445 = 10.$$

The length of the second cover $C_2 = 2 + (43 - 20) = 25'$.

PROBLEMS

4a. Let each of the flanges of the girder of this Art. consist of

2 angles $6 \times 6 \times 17.2$ lbs. = 10.12 sq.ins.

1 cover plate $14 \times \frac{3}{8}$ " = 5.25 "

1 cover plate $14 \times \frac{3}{8}$ " = 5.25 "

1 cover plate $14 \times \frac{3}{8}$ " = 5.25 "

and $\frac{1}{8}$ of the web plate $60 \times \frac{3}{8}$.

Find the lengths of the cover plates when it acts as a part of a deck railway bridge.

4b. Find the lengths of the cover plates when the girder of Prob. 4a acts as a part of a through bridge. The concentrated load $P_1 = 105,000$ lbs. The loads being spaced as shown in Fig. 4d.

ART. 5. RIVET SPACING IN GIRDER FLANGES

The connection between the web and flanges of girders, as in other composite structures, is made by means of rivets. These rivets are spaced with reference to the horizontal component of the stress in the flange, for at the extreme fiber the direction of the stress is horizontal and the maximum shearing unit stresses in the flanges are very small, and hence the horizontal component is the only stress of importance.

The one important exception to the foregoing is where the girder load is applied to one of the flanges, here the rivets have to transmit the loading which the girder carries together with the horizontal stress increments between the flanges and web. The exceptional case will receive special consideration.

The moment of the external forces at any point in a girder equals the moment of the internal stresses, there-

fore between any two points it is essential that there be enough rivets to properly develop the stresses produced by the maximum increase in moment between the points. The increment in the moment is constantly varying throughout the girder length. The general equation for moment for a simple girder as given in Art. 4 is

$$M = R_1x - \frac{wx^2}{2} - P_1(x-0) - P_2(x-b) - \text{etc.},$$

The derivative of M with respect to x is,

$$\frac{dM}{dx} = R_1 - wx - P_1 - P_2 - \text{etc.}, \text{ and is the shear.}$$

It is therefore seen that the greatest increase in the bending moment occurs when the shear has the greatest possible value.

The increase in bending moment between two points so close together that the load between them may be neglected, is the shear multiplied by the distance between the points; the increase in flange stress is this increase in moment divided by the depth.

Let V = the maximum shear at any point on the girder;

h = the effective depth, i.e., the depth c. to c. of gravity of flange, in inches;

R = the least value of the rivet to resist either crushing or shear, and

p = the space between two adjacent rivets in inches.

Then $\frac{V \times 1}{h}$ = the maximum increase in flange stress in a space of 1 inch (a)

$\frac{R}{p}$ = stress per inch of girder length carried by the rivets (b)

For the proper degree of strength (a) should equal (b).

$$\therefore \quad \frac{V}{h} = \frac{R}{p} \quad \text{or} \quad p = \frac{Rh}{V} \quad . \quad . \quad . \quad (5)$$

In order to show the application of (5) to determining rivet pitch: Let Fig. 5a represent a portion of the girder

FIG. 5a.

used to illustrate the method of finding lengths of cover plates in Art. 4.

The shear at $a = 193,500$, at $b = 153,000$, and at $c = 118,000$.

The value of a rivet in bearing = 24,000, and in shear 12,000 lbs. per sq.in.

The pitch for $\frac{7}{8}$ " rivets, at (a) =

$$p = \frac{4.77 \times 12 \times 7876}{193,500} = 2.34"$$

provided the flange angles are designed to carry the entire flange stress at this point. If, however, as was assumed in finding the length of the cover plates, the portion of the web used as flange area is 2.81 sq.in., then the pitch = $\frac{2.34 \times 12.33}{(12.33 - 2.81)} = \frac{2.34 \times 12.33}{9.52} = 3.03"$. The pitch of 2.34" would require that two lines of rivets be used, as good construction requires that the rivets be not closer

than 3". It is also customary to use two rows of rivets to connect a 6" angle leg to the web.

If the load is applied directly to the girder flange then the previous computation needs modification for the rivet pitch in the vertical legs of the angles of the loaded flange. Let Fig. 5*b* represent a part of the top flange of the girder of Fig. 5*a* and assume that it carries one-half a railway track on the top flange. One engine wheel weighing 50,000 lbs., including impact, will then be carried in a space of about

FIG. 5.

42", it being the custom to assume that three ties carry one axle load. Let H_r and V_r of Fig. 5*c* represent the resultant horizontal and vertical forces on the rivet as applied to the rivet by the girder web; the resultant of these two forces R should not exceed the ability of the rivet to safely resist either shear or crushing. To determine the pitch for this case,

Let W = the wheel load including impact (or other concentrated load);

a = total flange area

a_1 = total flange area with the part of web used for flange deducted;

s = three times the distance c. to c. of ties in inches,

h = effective depth of the girder in inches;

h_r = horizontal increment of stress in a length of one inch carried by a_1 ;

v_r = vertical load per inch of length of flange affected by the concentrated load,

$$r_r = \text{resultant of } h_r \text{ and } v_r, = \sqrt{h_r^2 + v_r^2} \\ = \sqrt{\left(\frac{V}{h} \cdot \frac{a_1}{a}\right)^2 + \left(\frac{W}{s}\right)^2}.$$

Then if R = the value of the rivet, as before,

$$p = \frac{R}{r_r} = \frac{R}{\sqrt{\left(\frac{V \cdot a_1}{h \cdot a}\right)^2 + \left(\frac{W}{s}\right)^2}}.$$

Let this be applied to finding the pitch for connecting the top flange angles to the web for the end of the girder of Fig. 5a.

$$\frac{Va_1}{ha} = \frac{193,500 \times 9.52}{57.24 \times 12.33} = \frac{193,500 \times 9.52}{705.77} = 2610;$$

$$\frac{W}{s} = \frac{50,000}{42} = 1190;$$

$$p = \frac{7876}{\sqrt{2610^2 + 1190^2}} = \frac{7876}{2710} = 2.91''.$$

For the heavier concentrated loads, such as columns bring when carried on the flanges of the girders, the flange angles will often not contain enough rivets for security, and stiffeners must be used, as will be explained later. The foregoing gives a simple method for finding the maximum permissible pitch of the rivets connecting the vertical legs of the flange angles to the web.

The determination of the pitch of the rivets for con-

necting the cover plates to the horizontal legs of the flange angles is not a simple matter if theoretical accuracy is desired.

At *b*, Fig. 5*a*, the point where the first cover plate begins the flange angles have in them all the stress they can carry. It is clear, therefore, that from *b* to *c* with the rivets connecting the first cover to the flange angles spaced to take only the flange stress increment, the flange angles simply transmit the increments of stress to the first cover plate. At *c* the first cover plate and angles have all the stress they can carry, and with rivets spaced as before the increments of flange stress from *c* to the point of maximum flange stress are simply transferred through the angles and first cover to the second cover. Rivets connecting a cover plate to a flange are generally spaced to take the increments of flange stress which occur from the end to the point of maximum stress in the cover. If *n* be the number of lines of rivets connecting the cover to the flange then

$$p = \frac{nRh}{V}, \quad \dots \dots \dots (5')$$

Assuming two lines of rivets in the cover plates the pitch at *b* for connecting the first cover to the flange angles

$$= \frac{2 \times 7216 \times 57.24}{153,000} = 5.41''. \quad \text{This is the maximum that may}$$

be used; the actual pitch would be made considerably less and usually a multiple of $\frac{1}{2}$, $\frac{3}{4}$, or 1" and at the same time such a pitch as would stagger well with the rivets in the vertical legs of the flange angles. If the maximum

pitch permissible were used the stress per square inch in the first cover plate would be zero at b and increase to 16,000 at c . This is highly undesirable, as there would exist in the girder in juxtaposition the angles with a unit stress of 16,000 and a cover with an average of 8000 lbs. The girder flange material cannot act in any such way without undue bending stresses on the rivets.

For this important reason cover plates should be made longer than a mere consideration of their relation to the moment polygon would require. The additional length, designated by y in formula (3) required, is a function of the number of rivets necessary to equalize the flange unit stress in all the flange material, and may be determined as follows:

Let n = number of rows of rivets in the cover plates;

a = area of flange without the cover plate under consideration, with unit stress s ;

a_1 = area of flange, including the cover plate under consideration, with unit stress s_1 ;

p = pitch in inches of the cover plate rivets in each line;

R = value of one rivet connecting the cover to the flange;

y_1 = additional length of cover plate required at each end in ft. $= \frac{y}{2}$. $y_1 = \frac{(a_1 - a)s_1}{12Rn} \cdot p$.

$$y = \frac{(a_1 - a)s_1}{6R \cdot n} \cdot p = \frac{S \cdot a \cdot p}{6a_1 \cdot R \cdot n} (a_1 - a). \quad . \quad . \quad . \quad (6)$$

The value of y for the first cover of the first example used to illustrate the method of finding the lengths is:

$$y = \frac{16,000 \times 12.33 \times 6}{6 \times 18.33 \times 7216} \cdot \frac{p}{n} = \frac{3}{2} \cdot \frac{p}{n}$$

If the rivets be placed 3" apart in two rows $y = 2.25$.

If enough rivets are used at the end of a cover plate as at b of Fig. 5a to transmit to it its full proportion of the flange stress, the rivet pitch required to connect the cover plates to the flange at any point will be the following:

$$p = \frac{A_1}{A} \cdot \frac{n \cdot Rh}{V} \cdot \dots \dots \dots (5'')$$

In which A_1 is the total flange area, and A the area of all the cover plates, at the point under consideration. The number of rivets as determined by (5') and (5'') should be increased by 20% to allow for the bending stresses. To still further limit these bending stresses no rivet passing through angles and covers should have a grip more than five times the diameter of the rivet.

PROBLEMS

5a. Using unit stresses of 10,000 and 20,000 lbs. for rivets in shear and crushing, compute the required rivet pitch for connecting the bottom flange angles to the web at c of Fig. 5a.

5b. For the data of Prob. 5a compute the rivet pitch for connecting the top flange angle to the web at a point vertically over c , including the effect of a locomotive wheel load.

5c. Using the unit stresses of 5a compute the value of y for the second cover plate.

5d. Compute the pitch of the rivets in the cover plate of 5c just adjacent to the portion y .

ART. 6. WEB PLATES

The maximum stresses that the web of a beam or girder must resist are of varying intensity and direction throughout its area.

For any elementary parallelopiped cut from the body of a beam in equilibrium subject to flexure, the forces on the faces of the element perpendicular to the plane of the drawing may be represented for the most general case

FIG. 6a.

as shown. The weight of the elementary particle may be neglected, as it is an infinitesimal of the third order as compared with the amount of stress on the faces, which are infinitesimals of the second order.

As the length of the sides of the particle approach zero as a limit, the intensities of the oppositely directed forces p_y are equal, and also the forces p_x . If the oppositely directed normal forces are of equal intensity the tangential or shearing forces q are also of equal intensity. The intensity of the shearing stresses at any point in a homogeneous prismatic body subject to flexure is given

from $q = \frac{VQ}{bI}$, a well-known formula of Mechanics of Materials, in which

q = the unit shearing stress;

V = the total shear;

b = the width of the body at the point under consideration;

Q = statical moment of the portion of the body above the point under consideration with reference to the neutral axis of the body, and

I = moment of inertia of the body with reference to the neutral axis.

The intensity of stress p_x at any point is given from the flexure formula $p_x = \frac{My}{I}$, in which the quantities are too well known to need definition.

FIG. 6b.

FIG. 6c.

The intensity of stress p_y may be found as follows: Let Fig. 6b represent any beam subject to flexure and a any point in the beam. Assume two planes distant $1''$ apart on either side of a as shown by the dotted lines.

The vertical forces on the portion of the beam above a and between the parallel lines are as indicated on the larger scale sketch, Fig. 6c, in which V_R is the sum of

the shearing resistances of the right surface above a , V_L is the sum of the shearing resistances of the left surface above a .

$W = (P_1 + w + W_1)$ = the total load between the two assumed planes above the point a , and A = the area in square inches of the horizontal surface through a . Then

$$V_L - V_R - W + p_y A = 0,$$

or

$$p_y = \frac{V_R + W - V_L}{A}. \quad . \quad . \quad . \quad . \quad (7)$$

Care must be taken in giving the proper signs to V_R and V_L .

Having a method for finding p_x , p_y and q for any point in a beam, there remains to be found the plane in which their combined action has the greatest intensity.

The stresses per square inch p_x , p_y and q may be produced in any manner, even in an arbitrary manner or p_x and q , and p_y and q may be the rectangular components into which the actual stresses on any elementary parallelopiped have been resolved, as far as the following argument is concerned.

Let Fig. 6d be a redrawing of 6a. Let the plane OP be passed through the elementary particle perpendicular to the face and making the angle θ with AA' , consider the elementary figure to have a dimension of unity perpendicular to the plane of the drawing.

Let it be required to find θ so that the stresses on OP will be normal and therefore either the maximum or minimum stresses in the body.

Let p represent the intensity of stress on OP , then

$$\overline{OP} \times p \times \frac{AP}{OP} = p_x \times AP + q \times AO, \quad \text{or} \quad p - p_x = q \cot \theta. \quad (a)$$

and

$$\overline{OP} \times p \times \frac{AO}{OP} = p_y \times AO + q \times AP, \quad \text{or} \quad p - p_y = q \tan \theta. \quad (b)$$

FIG. 6d.

Subtracting the second form of (b) from (a),

$$p_y - p_x = q(\cot \theta - \tan \theta) = q \cdot \frac{1 - \tan^2 \theta}{\tan \theta} = q \cdot \frac{2}{\tan 2\theta} \quad (8)$$

or $\tan 2\theta = \frac{2q}{p_y - p_x}$. The solution of this gives two values of θ , one of which corresponds to OP and the other to OP' .

Further, multiplying (a) by (b),

$$(p - p_x)(p - p_y) = q^2 \tan \theta \cot \theta = q^2$$

$$p^2 - p(p_x + p_y) = q^2 - p_x p_y$$

$$p^2 - p(p_x + p_y) + \left(\frac{p_x + p_y}{2}\right)^2 = \left(\frac{p_x + p_y}{2}\right)^2 + q^2 - p_x p_y$$

$$p \frac{p_x + p_y}{2} = \pm \frac{1}{2} \sqrt{(p_x + p_y)^2 + 4(q^2 - p_x p_y)}$$

$$p = \frac{1}{2}[p_x + p_y \pm \sqrt{(p_x + p_y)^2 + 4(q^2 - p_x p_y)}] \\ = \frac{1}{2}[p_x + p_y \pm \sqrt{(p_x - p_y)^2 + 4q^2}]. \quad (9)$$

The two values of p given from (9) correspond to the maximum and minimum values and occur on either OP or OP' .

For an extended treatment of the subject of combined stresses see Wood's Analytical Mechanics, Chapter V.

If either or all of the quantities p_x , p_y or q have a direction opposite to that shown in Fig. 6d they should be entered in the formulas with a minus sign.

The planes of maximum shear make angles of 45° with the lines of maximum direct stress.

The amount of p_y is small, except for large concentrated loads, with reference to p_x and q . If p_y be neglected, at the end of the beam where $p_x=0$ the angle $\theta=45^\circ$ and $p=q$, that is the direct stresses are equal to the shears in intensity and make an angle of 45° with them.

If p_y be neglected, at all points on the neutral axis where p_x is zero, $p=q$ and makes an angle of 45° with the axis.

In determining the location of the plane on which p , the principal stress intensity, is a maximum note, the values of the component stresses and inspection will show about the direction the resultant must have. If difficulty occurs in applying formula (9) it will be better to derive a special formula for the case at hand.

PROBLEM

6a. A plate girder of 14' effective length carries a total load of 10,000 lbs. per linear foot of length, the load being applied to the top flange. Consider the structure to be solid and of a cross section composed of 4 angles $4'' \times 4'' \times \frac{1}{2}''$ and 1 plate $24 \times \frac{1}{2}''$, as shown in the sketch, determine the maximum stress intensity and the direction of

its action at each numbered point as is indicated for points Nos. 3, 7, 9, 11, and 15 of Fig. 6e.

FIG. 6e.

This problem is so important for a proper understanding of the stress distribution on web plates that it is completely solved for points Nos. 3, 7, 9, 11 and 15, and much of the computation made for the remaining points, in what follows in this article. In Fig. 6e arrows acting toward a point indicate compression and away from the point tension.

The computations for p_x , p_y and q should be made about as follows:

$$\begin{aligned}
 I_x &= 1\frac{1}{2} \times \frac{1}{2} \times (24)^3 &= 576.00 \\
 5.56 \times 4 &= 22.24 \\
 4 \times 3.75 \times 10.82^2 &= 1756.08 \\
 \hline
 &= 2354.32 \\
 M_A &= 0 \\
 M_B &= 2,205,000 \text{ in.-lbs.} \\
 M_C &= 2,940,000 \text{ in.-lbs.}
 \end{aligned}$$

At points Nos. 1, 2, 3, 4 and 5, $p_x = 0$

FIG. 6f.

$$\text{At points Nos. 7 and 9,} \quad p_x = \frac{2,205,000 \times 4}{2354.32} = 3,740$$

$$\text{At points Nos. 11 and 15,} \quad p_x = \frac{2,940,000 \times 8}{2354.32} = 10,000$$

$$Q_{11} = 2 \times 3.75 \times 10.82 = 81.15$$

$$+ 2.00 \times 10.00 = 20.00$$

$$\hline 101.15$$

$$Q_7 = 2 \times 3.75 \times 10.82 = 81.15$$

$$2.00 \times 10 = 20.00$$

$$2.00 \times 6 = 12$$

$$\hline 113.15$$

$$Q_3 = 113.15 + 2 \times 2 = 117.15$$

$$q = V \cdot \frac{Q}{bI} = \text{for}$$

$$\text{No. 3} = V \cdot \frac{117.15}{.5 \times 2354.32} = 70,000 \times .0993 = 6960$$

$$\text{No. 7} = V \cdot \frac{113.15}{.5 \times 2354.32} = 35,000 \times .0960 = 3360$$

$$\text{No. 11} = V \cdot \frac{101.15}{.5 \times 2354.32} = 0000 \times .0853 = 0000$$

From formula (7) there is found

$$\text{at No. 3, } p_y = \frac{833\frac{1}{2} - 833\frac{1}{2} \times .5}{.5} = 830$$

$$\text{at No. 7, } p_y = \frac{833\frac{1}{2} - (833\frac{1}{2}) \cdot 304}{.5} = 1240$$

$$\text{at No. 11, } p_y = \frac{833\frac{1}{2} - (416\frac{2}{3} + 416\frac{2}{3}) \cdot 121}{.5} = \frac{733}{.5} = 1470$$

Values of Q , $\frac{Q}{bI}$, and $\frac{VQ}{bI}$ should be tabulated as follows:

FIG. 69.

Let A_1 = the area above division No. 11 = $4.25 + .75 = 5.00$ sq.ins.

A_2 = the area above division No. 10 = $5.00 + 1.50 = 6.50$ sq. ins., etc.

Values of $q \times$ areas:

$$q \times A_1 = V \times .017$$

$$A_2 = V \times .046$$

$$A_3 = V \times .081$$

$$A_4 = V \times .121$$

$$A_5 = V \times .165$$

$$A_6 = V \times .210$$

$$A_7 = V \times .257$$

$$A_8 = V \times .304$$

$$A_9 = V \times .352$$

$$A_{10} = V \times .401$$

$$A_{11} = V \times .450$$

$$A_{12} = V \times .500$$

$$q \times A_{13} = V \times .550$$

$$A_{14} = V \times .599$$

$$A_{15} = V \times .648$$

$$A_{16} = V \times .696$$

$$A_{17} = V \times .743$$

$$A_{18} = V \times .790$$

$$A_{19} = V \times .835$$

$$A_{20} = V \times .879$$

$$A_{21} = V \times .919$$

$$A_{22} = V \times .954$$

$$A_{23} = V \times .983$$

$$A_{24} = V \times 1.000$$

At No. 3:

$$\tan 2\theta = \frac{2 \times 6960}{830 - 0} = \frac{13,920}{830} = 16.771$$

$$2\theta = 86^\circ - 36''$$

$$\theta = 43^\circ - 18''$$

$$p = \frac{1}{2}[0 + 830 \pm \sqrt{(830)^2 + 4(6960)^2}]$$

$$= \frac{1}{2}[830 \pm 13,940]$$

$$= +7380 - 6550$$

At No. 7:

$$\tan 2\theta = \frac{2 \times 3360}{1240 - 3740} = \frac{6720}{2500} = 2.683$$

$$2\theta = 68^\circ - 10'$$

$$\theta = 34^\circ - 05'$$

$$p = \frac{1}{2}[3740 + 1240 \pm \sqrt{(2500)^2 + 4(3360)^2}]$$

$$= \frac{1}{2}[4980 \pm 7170]$$

$$= +6080, -1100.$$

At No. 9:

$$p_x = -3740$$

$$p_y = \frac{833\frac{1}{2} - 833\frac{1}{2} \times .696}{.5} = 510$$

$$q = 3360$$

$$\tan 2\theta = \frac{2 \times 3360}{510 + 3740} = \frac{6720}{4260} = 1.59$$

$$2\theta = 57^\circ - 50'$$

$$\theta = 28^\circ - 55'$$

$$p = \frac{1}{2}[-3740 + 510 \pm \sqrt{(4250)^2 + 4 \times 3360^2}]$$

$$= \frac{1}{2}[-3230 \pm 7950]$$

$$= -5590, +2360.$$

At No. 11:

$$\tan 2\theta = \frac{2 \times 0}{1470 - 10,000} = \text{an infinitesimal}$$

$$\theta = 0$$

$$\begin{aligned} p &= \frac{1}{2}[10,000 + 1470 \pm \sqrt{(8530)^2 + 4 \times 0}] \\ &= \frac{1}{2}[11,470 \pm 8530] \\ &= +10,000, +1470. \end{aligned}$$

At No. 15:

$$p_x = -10,000$$

$$p_y = \frac{833\frac{1}{2} - (416\frac{3}{4} + 416\frac{3}{4})}{.5} \cdot 879 = \frac{100}{.5} = 200$$

$$q = 0$$

$$\begin{aligned} \tan 2\theta &= \frac{2 \times 0}{200 - 10,000} = \text{an infinitesimal} = \frac{1}{2}[-9800 \pm 10,200] \\ &= -10,000, +200 \end{aligned}$$

$$0 = 90 \text{ or } 0$$

$$p = \frac{1}{2}[-10,000 + 200 \pm \sqrt{(10,200)^2 + 4 \times (0)^2}]$$

ART. 7. AREA OF WEB PLATES

The preceding article has shown that the stresses in the web of a plate girder are of greatly varying directions and intensities. The tensile stresses need an adequate amount of material to resist them, the amount of which is a direct function of the stress.

The action of the compressive stresses is augmented to a much greater degree than for tension, by secondary stresses if the material be even very slightly lacking in uniformity. That is, a certain kind of column action is set up.

The maximum tensile and compressive stresses in the

web cross each other at right angles; at the neutral axis they are approximately equal, and make angles of approximately 45° with the axis and equal the shearing stresses in intensity; above the neutral axis the compressive stress intensity is increasing while the tensile is decreasing; below the axis the opposite relation exists.

The shearing stresses are of the greatest intensity at the neutral axis, on horizontal and vertical planes, for any cross-section. At the cross-section where the greatest resultant shear occurs, there, on the neutral axis will be found the maximum shearing unit stresses. For simple spans the shear is a maximum at the ends of the span.

It is the practice to design web plates so that they will resist the shear at the point of maximum shear, and have enough thickness to provide ample bearing for the rivets connecting flange angles to the web; this latter very frequently determines the thickness of the web plate. The design of the web plate is also governed by practical considerations, such as requirements for handling in shop and field and requirements to resist corrosion.

The best practice requires as a minimum for the thickness of girder webs: $\frac{7}{16}$ " for railway, $\frac{3}{8}$ " for highway, and $\frac{5}{16}$ " for building work. It is the practically universal custom to make the web plate, for a girder, of uniform section throughout its length.

The shearing unit stress should be about 20% less than that used for direct tension, that is, where 16,000 is used for tension, 13,000 is a consistent unit for the maximum shearing stress intensity. Where the shearing stress is assumed to be uniformly distributed over the girder

web this unit should be reduced to 10,000 lbs. per square inch and applied to the net section.

The web plate is also designed to resist any tendency to buckling or sidewise failure. The tensile stresses which act on any element of the web tend to pull the element back into its proper position if from any cause the element is displaced laterally. In the portion of the web below the neutral axis the excess of tensile over compressive stress would give a component perpendicular to the web which would tend to take out any buckle that might exist. In the portion above the neutral axis the corresponding component would tend to increase any buckle. This can readily be seen by a study of Fig. 7a.

FIG. 7a.

FIG. 7b.

In order to determine whether a web needs stiffening an investigation which will lead to a safe structure can be made on the following basis:

Formulas (8) and (9), of Art. 6, show that at the neutral axis of the girder the maximum resultant compressive stress intensity approximately equals the maximum shearing stress intensity and that the line of its action makes an angle of about 45° with the neutral axis. A compressive unit stress equal to the maximum shearing

stress intensity is therefore assumed to act along the element of the web having a length of l in Fig. 7b, and this must be less than the permissible unit stress for a column of this length. Assuming that a safe unit stress for a column is given from the formula

$$P = 16,000 - 70 \frac{l}{r},$$

the notation for which needs no definition, the 16,000 should be reduced to 12,000 if the average shearing unit stress is used, as the maximum unit compression. The formula then becomes

$$P = 12,000 - 52.5 \frac{l}{r}.$$

Substituting for l and r their values,

$$l = d\sqrt{2}, \text{ and } r = .29t,$$

where t = the thickness of the web.

The formula then is

$$P = 12,000 - 52.5 \frac{d\sqrt{2}}{.29t} = 12,000 - 257.5 \frac{d}{t} \quad (a)$$

As the tension in the web below the neutral axis will prevent buckling, the value of d should be $\frac{d}{2}$, and as the tension in the upper half of the web helps to prevent buckling the constant may be divided again by 2, the formula then being

$$P = 12,000 - 65 \frac{d}{t} \quad (10)$$

It should be noted that d equals either the clear distance between flange angles or stiffeners.

To show the method of applying this formula to see if web stiffeners are necessary let the girder of Fig. 5a be examined.

The average shearing unit stress $= \frac{193,500}{22.5} = 8580$ lbs. per square inch.

The allowable unit stress $= 12,000 - \frac{65 \times 48.5}{.375} = 12,000 - 8420 = 3580$ lbs. per square inch.

As the actual stress exceeds the allowable, the web must be made thicker or the stiffeners placed closer together or else both combined.

If the web be made $\frac{1}{2}$ " thick

The average shearing unit stress $= \frac{193,500}{30} = 6450$ lbs. per square inch.

The allowable shearing unit stress $= 12,000 - \frac{65 - 48.5}{.5} = 12,000 - 6300 = 5700$ lbs. per square inch, which shows that the web must be further thickened or the stiffeners placed closer together.

If the web be made $\frac{3}{8}$ " thick and stiffeners placed 30" apart in the clear the average shearing unit stress

$= \frac{193,500}{26.25} = 7380$ lbs. per square inch.

The allowable shearing unit stress $= 12,000 - \frac{65 \times 30}{.44} = 12,000 - 4420 = 7580$ lbs. per sq.in.

PROBLEMS

7a. The accompanying sketch shows the cross-section of the girder of Prob. 6a and the curve of unit shear distribution. Construct the

FIG. 7c.

figure to three times the size of the sketch shown and write in the value of the ordinates to the curve at points 1" apart from the top to the bottom of the section.

7b. Are stiffeners required on the web of the girder of Prob. 6a? If not, show it by computation.

7c. What is the minimum thickness permissible for the web of the girder in Prob. 6a?

ART. 8. STIFFENERS FOR WEB PLATES

Stiffeners have several important functions, the chief of which are:

- (a) They keep the web from buckling, due to the compressive stresses in it.
- (b) They help hold the compression flange from lateral failure as a whole and from failure in detail in any direction.
- (c) They are used to relieve the rivets connecting the

loaded flange to the web, by transferring the load directly to the web.

- (d) They are used to reduce to proper amount the vertical stresses, on horizontal planes, in the web brought by local concentrated loads.
- (e) They help hold the web true to shape during manufacture and erection.

According to their principal functions they should be divided into two general classes, *intermediate stiffeners*, which are chiefly used for the purposes of (a), (b) and (e); *concentrated load stiffeners*, for (c) and (d), although each class performs all the functions of course. Intermediate stiffeners act as a beam standing vertically to resist lateral displacement. They are generally made of angles in pairs and riveted to the girder web as shown in Fig. 8a. The

FIG. 8a.

legs of the stiffening angles which are against the fillers are near the neutral axis of the pair and therefore should be only large enough to receive the connecting rivets; a $3\frac{1}{2}$ " leg for $\frac{1}{2}$ " rivet and 3" leg for $\frac{3}{4}$ " are enough.

The width b of the outstanding legs is the principal

element of efficiency for resistance to transverse displacement. A common rule is to make the width of the outstanding leg (O) equal to the depth of the girder (d) in inches divided by 30 plus 2'', or expressed as a formula

$$O = \frac{d}{30} + 2''. \quad (11)$$

60 | The following is a common method of locating intermediate stiffeners.

Intermediate stiffeners should be used at points as required by (10) or wherever the unsupported depth between flange angles is more than 160 times the web thickness. Where intermediate stiffeners are required they should never be further apart in the clear than the clear distance between the flange angles, with a maximum limit of 5'.

Concentrated load stiffeners act to transfer a concentrated load into the web or to transfer the girder load to a support. The sketch of Fig. 8b will illustrate both cases.

FIG. 8b.

The girder here shown being loaded with three concentrated loads of 180,000, and its own weight of 250 lbs. per linear foot. The lines of maximum web stress

for a girder of this character are very different from those of the girder of problem 6a. If such a girder were constructed without stiffeners, and formula (7) were applied to finding the intensity of p_v , this intensity would be found to be very high. The heavy vertical stiffeners are added to transfer the point of application of these loads from the outer edges of the flanges to an average position of the center of the web, and thereby decrease the intensity of vertical stress on horizontal planes just at the inner edge of the flange angles. These stiffeners cannot fully accomplish their object, as they are of elastic material and they are shortened by compression, and, as they are fastened to the web, the web and stiffeners move together except for a variation due to the deformation of the rivets. The stiffeners also serve to relieve the flange rivets from the component due to the vertical load.

Stiffeners supporting concentrated loads may be designed as columns with the formula $P = 16,000 - 70 \frac{l}{r}$, in which l should be taken as one-half the girder depth and r as the radius of gyration about an axis in the longitudinal center line of the girder.

Wherever the combined stress intensity on a web plate exceeds the allowable unit stress the stresses may be reduced by means of side plates, as shown by dotted lines.

Where the concentrated load stiffeners are at the end of a girder they should have their outstanding leg about equal to the horizontal leg of the flange for the sake of good appearance, and where it is desired to face the ends of such girders the stiffening angles must be made thicker

by $\frac{1}{8}$ " than theoretical considerations determine, to allow for material removed by such facing.

PROBLEMS

8a. Determine the size of the end stiffeners for the girder of Fig. 5a, using two pairs of angles, one on the outer and one on the inner edge of the sole plate.

8b. Assuming the wall plate to be 18" long for Fig. 5a, determine the size and spacing of the intermediate stiffeners for the girder.

8c. Determine the sizes of the stiffeners at the points of concentrated loading for the girder of Fig. 8b.

8d. Determine the sizes and spacing of the intermediate stiffeners for the girder of Fig. 8b.

ART. 9. SPLICES FOR WEB PLATES

Webs of plate girders should not be spliced unless necessary, but as wide plates cannot be procured in one piece, in general, for girders over 60 ft. long, splicing for long girders is unavoidable. The manufacturers furnish lists of the maximum dimensions of their plates. The number and location of the web splices should be determined by a combined consideration of the cost and resulting efficiency of the possible arrangements. The splice should be designed with the idea of transferring the stresses in the web across the cut in the most direct manner possible, just as in plate girder design as a whole the effort should be made to have the stresses developed as indicated by the theory of flexure for solid beams. Let it be required to splice the web at the center of the girder which has an effective length of 80', and a composition as shown in Fig. 9a.

The girder has been designed on the assumption that

1/3 the gross area of the web is available as flange area. The maximum bending moment = 6,300,000 ft.-lbs. The center shear simultaneous with this moment = 0. The maximum center shear = 75,000 lbs., and the bending moment simultaneous with this = 3,400,000 ft.-lbs.

FIG. 99.

The flange area is made up of:

$$\frac{1}{8} \text{ web} = 96 \times \frac{7}{16} \times \frac{1}{8} = 5.25 \text{ sq.in.}$$

2 angles $8 \times 8 \times 32.7 = 19.23 - 2.50 = 16.73$

1 cover plate $20 \times \frac{1}{2} = 10 - 1.00 = 9.00$

1 cover plate $20 \times \frac{1}{2} = 10 - 1.00 = 9.00$

a total of 39.98 sq.ins.

The simplest form of web splice consists of two vertical plates terminated at the top and bottom by the vertical legs of the flange angles, but this makes a normal distribution of the web stresses impossible in the vicinity of the splice. The resultant of all the forces on any beam cross-section may be represented by a shear and a couple

as is well known from mechanics, but the proper form of splice should be designed with reference to the distribution of these forces. The portion of the web between

FIG. 9b.

the flange angles is so near the extreme fiber that the stresses may be assumed to be horizontal throughout. The flange unit stress has been taken at 16,000 lbs.; the bearing and shearing values for rivets will be taken to correspond to this at 24,000 and 12,000 lbs. per square inch respectively, or at 50% more and 25% less than for tension. The thickness of the splice plates

should be sufficient to transmit the maximum possible stresses which can occur at the point of maximum stress in the splice.

The total stress on the portion of the web between the flange angles $= (8'' - 1'') \times \frac{7}{16} \times 14,667 = 44,800$ lbs.; the least that can be used for this part of the splice will be $2 - 7 \times \frac{3}{8}$ flats for each flange. The net area of these two plates $= 4.5$ sq.in., while that of the strip of the web $= 3.06$ sq.in. The bearing value of the rivets is less than that for double shear, hence one rivet is worth 9190 lbs. at the edge of the web plate and $9190 \times \frac{43.75}{48} = 8350$, an average for this part of the splice. The number of rivets on each side of the splice for splicing the strip $= \frac{44,800}{8350} = 5.37$ or 6.

For the condition of maximum moment there is no shear at the splice and the web stresses are horizontal.

The number of vertical rows of rivets is evidently a

function of the vertical pitch, the more vertical rows the greater the vertical pitch.

Let w = the pitch of the rivets in a vertical direction;

n = number of vertical rows of rivets;

d = distance from the neutral axis to horizontal row of rivets.

For three vertical rows

$$(w-1)\frac{7}{16} \times 16,000 \times d/48 - 3 \times 9190 \times d/48$$

or

$$w = 34.570/7000 = 4.94'', \text{ say } 4\frac{1}{2}''.$$

For two vertical rows

$$(w-1)\frac{7}{16} \times 16,000 \times d/48 - 2 \times 9190 \times d/48$$

or

$$w = 25,380/7000 = 3.62, \text{ say } 3''.$$

For this splice 3 vertical rows on each side spaced $4\frac{1}{2}$ will be used, as it gives a web plate with less reduction of strength at the splice.

The splice should now be examined for the case of 75,000 shear and simultaneous moment of 3,400,000 ft.-lbs.

From (5) the flange pitch at the center $p = \frac{9190 \times 96}{75,000} = 11.6''$ for no part of the web acting as flange. The flange as designed uses 5.25 sq.ins. of the web for flange area; the pitch of the rivets connecting the flange angles to the web is $\frac{9190 \times 96}{75,000 \times \frac{34.73}{39.98}} = 11.6 \times \frac{39.98}{34.73} = 13.3''$.

The $7 \times \frac{3}{8}$ flats on the vertical legs of the flange angles will therefore be made to take about 6 or 8 rivets on each side of the splice.

For a web splice at some point other than the center of the girder, the number of rivets in the flange plates on the side toward the center will be the number required for splicing the web; on the side toward the end the number will be the sum of those for connecting flange to web plus those for web splice.

The extreme fiber stress on the web for a moment of 6,300,000 ft.-lbs. was 16,000; for a moment of 3,400,000 ft.-lbs. it is 8630. For the strip of web between the flange angles the previous determination is evidently ample. A study of the stress intensity at different points in the web for this condition of loading would show that the stress intensity was nowhere as great as for the case for which the splice was designed.

A safe resultant rivet bearing of 9190 should not be exceeded.

The vertical component on a rivet at either edge of the main splice plates will not exceed $75,000/54 = 1390$ lbs., the horizontal component $= 3.5 \times \frac{7}{16} \times 8630 \times 38/48 \times \frac{1}{3} = 3480$ per rivet. The resultant $= \sqrt{1390^2 + 3480^2} = 3800$.

PROBLEMS

9a. What is the relative efficiency of the unriveted plate of Fig. 9a to that of the section of the plate through the first vertical line of rivets in the splice.

9b. Compute and compare the resisting moment of the rivets in the splice of Fig. 9a with that of the net section of the web plate through the first vertical line of rivets.

9c. Make a sketch of a splice for the girder, using only two vertical rows of rivets on each side of the splice.

ART. 10. SPLICES FOR THE COMPONENT PARTS OF THE FLANGES

Splicing any of the component parts of a girder flange should be avoided, as it is never necessary except to meet some emergency, or reduce the cost slightly. The flange angles and cover plates, for girders of the maximum length now used, may be obtained in one piece. The cost of a few very long pieces, however, may be so high, due to the expense of shipment in less than proper amounts, or the need of the completed structure may be so urgent, as to make it advisable to permit splicing of component parts of the flange.

Flange angle splices should be located when possible as follows:

- a. Where there is an excess of flange section over the required amount;
- b. Between adjacent pairs of stiffeners, where these pairs of stiffeners are far enough apart to permit a splice of proper length to be made;
- c. So that not more than two flange angles shall be spliced in any cross-section of the girder;
- d. So that the flange angles on opposite sides of the girder flange will be spliced on opposite sides of the center of the girder.

The splicing material should be disposed with reference to the shape of the section spliced. The splice for an angle with equal legs should be made by a cover angle with two equal legs. The net area of each leg of the splice

should equal the net area of the leg spliced. In general in splicing or connecting material under stress the splice or connection should be arranged to avoid any redistribution of stress. This requires that angles with unequal legs be spliced by cover angles with unequal legs, and that the net area of each leg of the one be equal to the net area of each leg of the other.

The number of rivets in the splice on each side of the point where the angles are cut should be determined with care. The duty of the rivets in developing the flange stress as well as in connecting the spliced parts should be clearly understood. For the purpose of illustration let it be supposed that for the girder of Fig. 5a the only material available for the flange angles is 4 angles $6 \times 6 \times \frac{1}{2}$ —16' 4 $\frac{1}{2}$ " long and 4 angles $6 \times 6 \times \frac{1}{2}$ —28' 4 $\frac{1}{2}$ " long. This makes it necessary to splice the bottom flange at a point 6' from the center of the girder. Fig. 10 shows the splice in considerable detail. The net area of the two angles = 9.52 sq.ins., and this at 16,000 = 152,320 lbs. as the strength which must be developed by both the rivets and angles of the splice. Two $6 \times 6 \times \frac{9}{16}$ angles with the legs cut to 5 $\frac{1}{2}$ " each and the corner of the angle planed so to fit the fillet of the flange angles will be used for the splicing material.

The shear, at the point of splicing, simultaneous with maximum flange stress, is 50,000 lbs. The pitch of the rivets cannot be less than 6" in each line without reducing the flange section (see Art. 3).

The horizontal flange increment I per rivet from Formula (5) = $\frac{50,000}{59} \times 3 = 2540$ when none of the web is assumed

to act as flange area; for this girder, however, 2.81 sq. in. of the web was assumed to act as flange area. The value of I therefore is $2540 - 2540 \times \frac{2.81}{24.33} = 2540 - 290 = 2250$ lbs.

FIG. 10 (a and b).

Fig. 10 (c) shows the forces on a rivet through the web and vertical legs of the splice and flange angles due to increment I .

FIG. 10 (c, d and e).

Fig. 10 (d) shows the forces on a rivet through the web and vertical legs of the splice and flange angles due to splicing, for the left portion of the splice.

Fig. 10 (e) shows the forces on a rivet through the

web and vertical legs of the splice and flange angles due to splicing, for the right portion of the splice.

The unit stresses on the rivet will be taken at 12,000 lbs. per square inch for shear, and 24,000 lbs. per square inch for bearing.

Consideration of the forces on the rivets and the thickness of flange and splice material shows that the shearing value of the rivets is the determining one along the plane *AA*.

The number required in the vertical legs = $\frac{152,320}{4 \times 7216} = 5.3$ or 6.

FIG. 10 (*f*, *g* and *h*).

Fig. 10 (*f*), (*g*) and (*h*) show the forces on the rivets through the horizontal legs of the flange angles of the top flange splice. It is readily seen that the number of rivets

required = $\frac{152,320}{4 \times 7216} = 5.3$ or 6.

FIG. 10i.

Cover plate splices should be located so that a simple lengthening of an outer cover plate will form the splice. For example if a splice were required in the first cover

plate of the girder of Art. 4, it should be spliced by extending the second cover a distance x , which must be enough to permit the location of a proper number of rivets, shown by the dotted lines in Fig. 10 (i).

PROBLEM

10. Design a splice for the flange angles of the girder of Prob. 4a, which shall be located at the same point in the length of the girder as was the one used to illustrate this article.

ART. 11. CONNECTING ONE GIRDER TO ANOTHER

The problem of framing one girder into another is one so frequently met with that a connection for two adjacent stringers and the floorbeam between them will be designed to illustrate the method of making the computations for such connections.

FIG. 11a.

Fig. 11a is a line drawing of a plan showing the relative position of girders, floorbeams, and stringers. A load on any stringer is carried first to the floorbeams at its ends. The floorbeam carries it to the girders and the girders to the abutments or other end supports.

The stringer is composed of 1 web plate $27 \times \frac{1}{2}$;

4 angles $5 \times 3\frac{1}{2} \times 13.6$ ($\frac{1}{2}$ ").

The floorbeam is composed of 1 web plate $38 \times \frac{1}{2}$;

4 angles $5 \times 3\frac{1}{2} \times 19.8$ ($\frac{3}{4}$ ")

The maximum stringer reaction is 97,800 lbs. ($ll = 48,800$
Imp. = 46,600 and $dl = 2400$).

The maximum reaction for two stringers is 131,700 lbs.
($ll = 66,300$, Imp. = 60,600 and $dl = 4800$).

The requirements of construction will be assumed to demand that the bottom flange of the stringer be $4\frac{1}{2}$ " above the bottom flange of the floorbeam. The connection between the stringer and floorbeam is made by two vertical angles which are riveted onto the stringer in the bridge shop. The rivets through the outstanding legs of the connection angles and the floorbeam web must be field driven. The unit stresses are 12,000 and 24,000 for shear and bearing for shop rivets and 20% less than these values for field-driven rivets; $\frac{7}{8}$ " rivets will be used and the connection angles will be made $\frac{1}{2}$ " thick so that after they are faced on the back of their outstanding legs they will not be less than $\frac{3}{8}$ " thick on these legs.

Fig. 11 (d) shows how the load W is applied to each rivet and carried to the stiffeners. The rivet should be examined for crushing by the web for W and for shear for $\frac{W}{2}$.

The number required for crushing = $\frac{97,800}{10,500} = 9.3$ or 10.

For shear the number = $\frac{97,800}{2 \times 7216} = 6.8$ or 7. The upper and lower rivet in the lines xx and zz of (b) cannot be

counted for this connection, as they have other duty to perform. Therefore, in order that the rivets be not closer than 3", a leg for the connection angles which will contain 2 rows of rivets must be used. As 10 rivets are required, a symmetrical arrangement demands 11. These rivets pass through fillers and a good requirement is to extend the fillers for such cases and put 50% additional rivets through

FIG. 11.

them. Many good designers consider it allowable to assume that fillers connected to web plates by a line of rivets such as *yy* increase the bearing value of rivets in lines *xx* and *zz* by the entire bearing value of the rivets in *yy*.

Consideration of (c) of Fig. 11 shows that it will be possible to get

16 rivets in the two lines *oo* and have them a little over 3" apart, and

18 rivets in the two lines *oo* and have part of them $2\frac{3}{4}$ and part 3" apart.

Fig. 11 (*c*) shows how the forces act on a rivet connecting the outstanding legs of the connection angles to the floorbeam web.

The bearing value of a field rivet in the $\frac{3}{8}$ (net thickness) stiffener leg is 6300.

The shearing value of a field rivet is 5770.

For the maximum stringer load the number of rivets required for shear $= \frac{97,800}{5770} = 16.95$ or 18, which would enable two lines of rivets to be used, if part of the number are $2\frac{3}{4}$ " apart.

The rivets must also be examined for bearing on the floorbeam web when both stringers are bringing their combined maximum loads at this connection. The bearing value of a field rivet in the $\frac{1}{2}$ " floorbeam web = 8400 lbs.

The number of rivets required $= \frac{131,700}{8400} = 15.6$ or 16, which is one less than the number which are required for maximum shear on the rivets for one stringer loaded.

The number of rivets by the second computation is usually, though not in this case, the larger and hence the governing one. The rivets should be located on the lines *oo* in (*c*) of Fig. 11. The two fillers under the connection angles and on the stringer web must be $\frac{1}{2}$ " thick and 3" wider than the angle leg. They should therefore be $9" \times \frac{1}{2}"$ flats.

The requirement of two lines of rivets for the leg of the connection angle against the stringer web demands a

6" leg. One line between each leg of the connection angle and the floorbeam web fixes the width of the out-standing leg at $3\frac{1}{2}$ or 4".

The connection angles cannot be less than $\frac{3}{4}$ " in thickness. Examination of this net section through lines *xx* and *oo* shows them to be ample to resist shear. Sometimes they must be increased in thickness for this.

The connection angles are therefore made $6 \times 4 \times 16.2$ ($\frac{3}{4}$).

PROBLEM

11. Design the connection between two adjacent stringers and their floorbeam. The stringer consisting of

1 web $24 \times \frac{7}{8}$;

4 angles $5 \times 3\frac{1}{2} \times 15.2$ ($\frac{7}{8}$)

The floorbeam consisting of

1 web $34 \times \frac{1}{2}$;

4 angles $5 \times 3\frac{1}{2} \times 13.6$ ($\frac{1}{2}$);

2 covers $11 \times \frac{1}{2}$.

The shears being the same as for the example solved in this article.

ART. 12. END BEARINGS

The end bearings of a girder must receive the load brought to the end of the girder and distribute the same over the masonry or other support. For the single-track girder of Art. 4, which was taken to illustrate the method of finding lengths of cover plates an end reaction of 193,500 lbs. was assumed. For girders less in length than 60' one end of the girder is bolted to the masonry and the other

allowed to slide on a plate. This arrangement makes the determination of the reactions possible.

The area of the bearing on the wall, assuming the bridge seats to be of granite and 600 lbs. per square inch as a unit stress, should be $\frac{193,500}{600} = 323$ sq.in.

It is not advisable to make an end bearing of the simple nature indicated in Fig. 12 too long. The tendency of

FIG. 12.

such a bearing is to overstress the bearing along its inner edge.

The upper plate of the two shown at each end is called the sole plate, and is connected by rivets, countersunk on the bottom, to the girder. The bottom of the sole plate at (b), the expansion end, should be planed.

The lower plate of the two shown at each end is called the wall plate.

The upper surface of the wall plate at (b), the expansion end, should be planed.

The wall plates are held in position by the two anchor bolts at each end.

The bearings at the ends of the girder, when of two simple plates, should not be too wide, as the tendency of the bearing is to overload the masonry along the portion covered by the bottom flange of the girder.

The bearing for this case will be made $18 \times 18''$.

The two plates which project beyond the bottom flange angles must be strong enough in flexure to distribute the load on the bridge seat. Each inch of length of the plates may be considered acted on in a transverse direction by the forces shown in (d).

The bending moment then
 $= 5400(9/2 - 6.18/2) = 5400 \times 1.41 = 7614 \text{ in.-lbs.}$

If the sole and wall plates be made of equal thickness, then the resisting moment of each plate must be 3807 in.-lbs.

The depth (or thickness) of plate required may be obtained from $M = \frac{SI}{c} = \frac{S \cdot bd^2}{6} = 3807$ or $d^2 = \frac{3807}{16,000} \times 6 = 1.43''$ and $d = 1.25''$ about.

These plates should neither of them be less than $\frac{3}{4}''$ thick, even if a less thickness would furnish proper strength.

For small spans generally only two pairs of stiffeners, one over the outer and the other on the inner edge of the bearing plates, are used.

The end stiffeners for this case should be $5 \times 3\frac{1}{2}$ angles and their radius of gyration in a direction transverse to the web is 2.78" approximately. The required area for

FIG. 12.

these stiffeners $= \frac{193,500}{15,250} = 12.7$ sq.in. [$P = 16,000 - 70 \frac{30}{2.78} = 16,000 - 750 = 15250$].

Therefore 4 angles $5 \times 3\frac{1}{2} \times 12 (\frac{7}{16}) = 14.11$ sq.in. will be ample.

The addition of another pair of stiffeners over the center of the bearings would help greatly in distributing the pressure over the wall plates, as their outstanding

FIG. 12.

legs would prevent an upward deflection of the plates and angles between the pairs of stiffeners. The additional stiffeners are shown by dotted lines in Fig. 12 (a) and (b).

A better bearing for the ends of this girder could be made by making it shorter in the direction of length of the girder and using either a cast or built-up pedestal to distribute the load in a transverse direction as is indicated in (f) and (g) of Fig. 12. For a length of 12" the width should be 27". The sizes for either case (f) or (g) should be determined from the laws of flexure, and direct stress.

For longer girders with greater end reactions to secure proper distribution of the load on the masonry and proper application of the reaction to the girder, a bearing should be used which by means of its form and action will insure this result. This is generally accomplished by means of an upper and lower shoe, both of which may freely rotate about a pin. These upper and lower shoes should have

FIG. 12A.

proper bending strength and proper bearing on the pin and masonry. These shoes may be either built up of rolled material or cast in one piece. Their detailed design will not be undertaken here, as no new principles are to be developed.

PROBLEM

12. Design an end bearing for a girder of a single-track railway bridge of 36' effective length, the cross-section of the girder at the

end being 1 web plate $48 \times \frac{7}{16}$ and 4 angles $6 \times 6 \times 19.2(\frac{3}{4})$, the end reaction being 180,000 lbs.

APPENDIX

ART. 13. POSITIONS OF LOADING FOR MAXIMUM SHEAR AND MOMENT

The shears and moments, which are necessary for the design of plate girder bridges, are required for such a great variety of span lengths within the limiting lengths of span for such structures, that special methods of computing and tabulating them are advisable. In the principal Railway Engineers' Bridge Works and Consulting Engineers' offices the major part of the structures designed will be made for some standard loading. The loading known as Cooper E₅₀ is perhaps more widely used than any other for railway bridges. The quantities given in Table No. 1 are for Cooper's E₅₀ and are similar to those which should be determined and kept on record for any standard loading to enable design to be made with proper facility.

SHEARS

In computing shears it should be noted that for deck bridges the maximum end shear is given for the engine located so that either the first or last driving wheel stands at the end of the span.

The maximum shear at an interior point on the left of the center of the span is given when the load extends from the right and up to the point and perhaps a little beyond. Every load that passes from just to the right

of the point to just the left of the point under consideration causes a decrease in shear by the amount of that load. Any further movement of the system to the left increases the shear until another load passes from the right to the left of the point. The maximum shear must therefore be determined by trial and generally will occur for the first or second engine wheel just to the right of the given point.

For through bridges the maximum shear in any panel is given when the well-known criterion $P - \frac{W}{m}$ is satisfied, in which P is the load in the panel, W the total load on the bridge and m the number of equal panels in the span. Sometimes two or even three positions of the load satisfy the criterion, in which case the maximum shear is determined by computing the shear for all positions which satisfy the criterion.

For maximum concentrated load brought to a floor beam or trestle bent by two adjacent stringers or girders: The criterion for position is $P = \frac{nW}{n+m}$, in which n and m are the lengths of the adjacent spans and P the load on the span of length n , and W the load on both spans.

BENDING MOMENTS

The bending moment, due to a certain number of moving loads at any definite point in a girder either deck or through, is a maximum when $P = \frac{nW}{m}$, in which P is the load on the left of the point, W the total load on the structure and n the distance from the point to the left

end and m the span length. This criterion enables any group of loads to be placed to produce a maximum moment. The criterion will sometimes be satisfied by more than one position of the live load, generally that position which has the heaviest load at the point under consideration and in addition the greater load on the structure is the one giving maximum moment. The moment for all positions of load which satisfies the criterion must be computed for a certain determination of the maximum.

For a deck structure the point of maximum bending moment occurs at or near the center, generally a little distance away from the center, the location of this point of maximum moment being different for different systems of loading. To aid in determining the position of the loading for absolute maximum it should be remembered that:

- (a) The maximum moment must occur where the shear passes through zero;
- (b) For a system of concentrated loads the shear must pass through zero at one of the loads;
- (c) The amount of load on either segment, into which the point of maximum moment divides the span, is to the total load on the span as the length of the segment is to the span length.

These requirements for practical cases fix the point of maximum bending moment under one of the two wheels adjacent to the resultant of the system. The criterion for the exact position of the loading to produce maximum bending moment follows:

For any given system of loading, the loads should be so placed that the center of the span is half way between the resultant of the system and one of the two loads which are nearest to the resultant. This criterion may be established as follows:

Let Fig. 13a show any girder carrying the system of moving loads shown.

FIG. 13a.

Let a be the center of the span;

o be the point of maximum moment which occurs under o or n ;

the resultant of the system $= W$;

c be the distance of W from the right end;

the resultant of the loads to the left of o be P ;

b be the distance from o to P ;

x be the distance from o to a ;

Then the bending moment at

$$\begin{aligned}
 o = M - R_1 \left(\frac{l}{2} - x \right) - Pb - \frac{Wc}{l} \left(\frac{l}{2} - x \right) - Pb \\
 - \frac{Wc}{2} - \frac{Wcx}{l} - Pb. \quad (\alpha)
 \end{aligned}$$

Now suppose the loading to advance a small distance to the left of dx , then $b=b$, $x=x+dx$, and $c=c+dx$, and the bending moment

$$M' = R_1 \left(\frac{l}{2} - [x + dx] \right) - Pb \quad \text{as} \quad R_1 = \frac{(Wc + dx)}{l} \quad \text{this} \\ = \frac{W(c + dx)}{l} \left(\frac{l}{2} - [x + dx] \right) - Pb;$$

neglecting terms containing dx^2 ,

$$M' = \frac{Wc}{2} - \frac{Wcx}{l} - \frac{Wcdx}{l} + \frac{Wdx}{2} - \frac{Wxdx}{l} - Pb. \quad (\beta)$$

Subtracting (α) from (β)

$$M - M' = dm = -\frac{Wdx}{2} + \frac{Wxdx}{l} + \frac{Wcdx}{l} \\ \frac{dm}{dx} = -\frac{W}{2} + \frac{Wx}{l} + \frac{Wc}{l},$$

and for a maximum this must equal 0.

$$\therefore -\frac{W}{2} + \frac{Wx}{l} + \frac{Wc}{l} = 0 \\ -\frac{l}{2} + x + c = 0$$

and

$$x = \frac{l}{2} - c,$$

which establishes the criterion as stated.

PROBLEMS

13a. Compute the maximum bending moment for a deck plate girder of 18' effective span length for Cooper's E_{80} . Assume the girder to carry one-half the loading.

13b. Compute the maximum bending moment for a 25' span, same loading as 13a.

13c. Compute the maximum center moment for a 25' span, same loading as 13a.

ART. 14. PREPARATION OF A TABLE OF BENDING MOMENTS, SHEARS, AND CONCENTRATED LOADS FOR COOPER'S E₁ LOADING

The great advantage of a table of moments and shears is that it may be prepared in a few days for all spans for which it is at all likely to be needed. Computations for a system of quantities made at one time show by the law of the increase or decrease of the quantities any error, and the similarity of the computations enables them to be very rapidly made. When a system of many loads moves over spans of varying length it is evident that *one load produces maximum moment* for spans up to a certain length, two loads for a certain other length, and so on.

FIG. 14a.

For one load on a span see Fig. 14a.

$$M = R(l - x) = \frac{50,000x}{l}(l - x) = 50,000x - \frac{50,000x^2}{l}$$

$$\frac{dM}{dx} = 50,000 - \frac{100,000x}{l} = 0$$

or $M = \text{a max.}, \text{ when } x = \frac{l}{2}.$

$$\therefore M = \frac{50,000l}{4}, \text{ which, as is well known, is the general}$$

expression for max. moment for any span with one load.

The general equation for moment for two loads spaced 5' apart is

$$\begin{aligned}
 M &= R(l - 5 - x) = \frac{250,000 + 100,000x}{l}(l - x - 5) \\
 &= 250,000 \times 100,000x - 750,000 \frac{x}{l} - 100,000 \frac{x^2}{l} - \frac{1,250,000}{l}, \\
 \frac{dM}{dx} &= 100,000 - \frac{750,000}{l} - \frac{200,000x}{l} = 0. \quad \therefore x = \frac{l}{2} - 3.75.
 \end{aligned}$$

FIG. 14b.

Substituting for x its value, we have for

$$\begin{aligned}
 M &= \frac{250,000 + 100,000\left(\frac{l}{2} - 3.75\right)}{l} \left[l - \frac{l}{2} + 3.75 - 5\right] \\
 &= 250,000l - 125,000 + \frac{156,250}{l}.
 \end{aligned}$$

By plotting the curves of moments for different lengths of spans we see that somewhere between 8' and 9' one load and two loads produce the same moment.

To find this point exactly we make the equations for moments simultaneous and solve to find the value of l for which the moments are equal.

For this case $\frac{50,000l}{4} = 250,000l - 125,000 + \frac{156,250}{l}$,
whence $l = 8.54'$.

The next step is to get the general equation of moments for three loads. Make it simultaneous with that for two

loads, and solve for l , which gives the upper limit for two loads as 11.125'.

The equation for 4 loads is

$$M = 50,000l - 500,000 + \frac{312,500}{l}.$$

FIG. 14c.

The equation for five loads will now be written

$$\text{dist. of c.g. from right load} = \frac{2,075,000}{225,000} = 9.22'.$$

FIG. 14d.

The point of max. moment will be under the second driver.

$$\text{Reaction at } R_1 = \frac{2,075,000 + 225,000x}{l}$$

Maximum bending moment

$$\begin{aligned}
 &= \frac{2,075,000 + 225,000x}{l} \times (l - x - 23 + 13) - 575,000 \\
 &= \frac{2,075,000 + 225,000x}{l} \times (l - x - 10) - 575,000 \\
 &= 2,075,000 + 225,000x - \frac{2,075,000x + 225,000x}{l} \\
 &\quad - \frac{20,750,000 + 2,250,000x}{l} - 575,000 \\
 \frac{dM}{dx} &= 225,000 - \frac{2,075,000}{l} - \frac{450,000x}{l} - \frac{2,250,000}{l} = 0 \\
 &\quad - \frac{450,000x}{l} = -225,000 + \frac{2,075,000 + 2,250,000}{l} \\
 450,000x &= 225,000l - 4,325,000 \\
 x &= \frac{l}{2} - 9.61.
 \end{aligned}$$

Substituting this value for x in the following simplified expression for the moment

$$\begin{aligned}
 &1,500,000 + 225,000x - \frac{4,325,000x}{l} - \frac{225,000x^2}{l} - \frac{2,075,000}{l} \\
 \text{there is given} \\
 M &= 1,500,000 + 225,000\left(\frac{l}{2} - 9.61\right) - \frac{4,325,000}{l}\left(\frac{l}{2} - 9.61\right) \\
 &\quad - \frac{225,000}{l}\left(\frac{l}{2} - 9.61\right)^2 - \frac{20,750,000}{l} \\
 &= 1,500,000 + 112,500l - 2,162,500 - 2,162,500 + \frac{41,568,056}{l} \\
 &\quad - 56,250l + 2,162,500 - \frac{20,783,925}{l} - \frac{20,750,000}{l} \\
 &= -662,500 + \frac{34,131}{l} + 56,250l = 56,250l - 662,500 + \frac{34,131}{l}.
 \end{aligned}$$

Making the moments for four and five loads equal, we have:

$$50,000l - 500,000 + \frac{312,500}{l} = -662,500 + \frac{34,131}{l} + 56,250l$$

$$-6250l = -162,500 - \frac{278,369}{l}$$

$$6250l^2 - 162,500l = +278,369$$

$$l^2 - 26l = 44.54$$

$$l^2 - 26l + 169 = 44.54 + 169$$

$$l - 13 = \pm 213.54 = \pm 14.61$$

$$l = 13 \pm 14.61 = 27.61'$$

as the limiting length of span for which four loads produce maximum moments.

The tabulation following shows the moments and the positions of the loads that produce them for the spans from 9 to 27' for intervals of 1'.

Span—	Mom.—	Limits:		
9	117,360	8.536' $x = \frac{l}{2} - 3.75'$		
10	140,625	to		
11	164,200	11.124' $R = 50,000 - \frac{125,000}{l}$		
12	200,000			
13	237,500			
14	275,000			
15	312,500	$M = 25,000l - 125,000 + \frac{156,250}{l}$
16	350,000	Limits:		
17	387,500	11.125' $x = \frac{l}{2} - 5'$		
18	425,000	to		
19	466,450	$R = 75,000$		
20	515,625	18.66' $M = 37,500l - 250,000$
21	564,880			
22	614,210	Limits:		
23	663,500	18.67' $x = \frac{l}{2} - 8.75'$		
24	713,020	to		
25	762,500	27.61' $R = 100,000 - \frac{250,000}{l}$		
26	812,020			
27	861,570	$M = 50,000l - 50,000 + \frac{312,500}{l}$
28				
29				
30				
31				
32				
33				
34				
35				
36				
37				
38				

PROBLEMS

14a. Compute the foregoing table up to 38'.

14b. Compute the maximum H end shear for one girder of a 38' effective single-track deck plate-girder bridge. Two girders carry one track. Cooper's E_{80} .

ART. 15. TABLE OF MOMENTS, SHEARS AND CONCENTRATED LOADS FOR COOPER'S E_{80}

The method of writing equations for bending moments of Art. 14 need not be followed for spans over 30' long. For spans over 30' in length the maximum center moment is only a small fraction of one per cent. less than the absolute maximum moment. The following table gives a convenient arrangement of the quantities for spans up to 75' effective length.

For through spans tables of moments at the panel points and shears in all the panels for varying number of panels and panel length are readily prepared and should be made for any loading as much used as Cooper's systems.

PROBLEMS. Loading Cooper's E_{80} .

15a. Compute the live load concentration for a trestle bent which carries adjacent spans of 30' and 60'. Show by a sketch the position of loads.

15b. Compute the maximum center moment for a 60' span. Show by sketch the position of loads.

15c. Compute the maximum shear at the center of a 60' span. Show by sketch the position of loads.

15d. Compute the maximum shear at a point 15' from one end of a 60' span. Show by sketch the position of the loads.

Span in ft	End Sh.	Q. Pt. Sh.	C. Sh.	C. Mom.	Conc. Fl. Mom.	Span in ft	End Sh.	Q. Pt. Sh.	C. Sh.	C. Mom.
10'	75.0	50.0	25.0	140.6	100.0	43'	198.4	122.1	57.3	1856.5
11'	81.9	52.3	27.3	164.3	109.1	44'	201.4	123.8	58.0	1929.0
12'	87.5	54.1	29.1	200.0	116.6	45'	204.3	125.4	58.6	2001.5
13'	92.3	55.8	30.8	237.5	123.1	46'	207.0	126.8	59.3	2074.0
14'	96.4	58.9	32.1	275.0	130.4	47'	209.9	128.5	59.9	2146.5
15'	100.0	62.5	33.4	312.5	136.6	48'	212.6	130.3	60.4	2219.0
16'	106.2	65.6	34.4	350.0	142.3	49'	215.4	132.0	61.3	2297.0
17'	111.8	68.4	35.3	387.5	147.0	50'	218.1	133.6	62.1	2377.3
18'	116.6	70.9	36.1	425.0	151.6	51'	220.9	135.3	63.0	2457.6
19'	121.0	73.0	36.0	466.5	157.3	52'	223.5	136.9	63.8	2538.0
20'	125.0	75.0	35.9	515.6	163.9	53'	226.3	138.4	64.5	2618.4
21'	128.6	78.6	37.0	564.9	169.9	54'	229.0	140.1	65.3	2702.6
22'	131.9	81.9	38.0	614.3	175.4	55'	231.8	142.0	66.0	2791.3
23'	134.8	84.7	38.9	663.6	180.4	56'	234.4	143.8	66.6	2880.1
24'	137.5	87.5	39.8	713.0	184.9	57'	237.1	145.5	67.3	2968.9
25'	142.0	90.0	40.5	762.5	189.1	58'	239.8	147.1	67.9	3057.6
26'	145.3	92.3	41.4	812.0	194.3	59'	242.4	148.8	68.8	3150.5
27'	148.1	94.5	42.1	861.6	200.3	60'	245.0	150.3	69.6	3247.1
28'	151.1	96.4	42.9	913.8	205.8	61'	247.8	151.8	70.5	3343.9
29'	153.9	98.3	43.5	969.9	210.9	62'	250.4	153.3	71.3	3440.5
30'	157.6	100.0	44.1	1026.1	215.6	63'	253.6	154.8	72.0	3537.3
31'	161.1	101.9	45.5	1082.3	Fl. Bm. Conc. 30' and 60' = 298.6 40' and 60' = 328.6 Note: Shears in thousands of lbs. and Moments in thousands of ft.-lbs. Shears and Moments for one track.	64'	256.8	156.3	72.8	3638.8
32'	164.3	103.9	46.9	1138.6		65'	259.5	157.8	73.5	3743.8
33'	167.4	105.9	48.1	1194.9		66'	262.4	159.3	74.3	3848.8
34'	170.3	107.8	49.3	1251.0		67'	266.0	160.8	74.9	3953.8
35'	172.9	109.5	50.4	1307.4		68'	269.5	162.3	75.6	4058.8
36'	176.4	111.1	51.4	1371.7		69'	273.0	163.8	76.2	4163.8
37'	179.6	112.5	52.4	1435.9		70'	276.3	165.3	76.9	4268.8
38'	182.8	113.8	53.3	1500.0		71'	279.5	166.8	77.7	4376.0
39'	185.8	115.0	54.1	1566.6		72'	283.4	168.3	78.5	4481.3
40'	188.5	116.9	55.0	1639.1		73'	287.0	169.9	79.2	4588.1
41'	192.0	118.8	55.8	1711.6		74'	290.6	171.3	80.0	4700.0
42'	195.3	120.5	56.5	1784.1		75'	294.3	172.6	80.7	4813.8

SHORT-TITLE CATALOGUE

OF THE

PUBLICATIONS

OF

JOHN WILEY & SONS

NEW YORK

LONDON: CHAPMAN & HALL, LIMITED

ARRANGED UNDER SUBJECTS

Descriptive circulars sent on application. Books marked with an asterisk (*) are sold at net prices only. All books are bound in cloth unless otherwise stated.

AGRICULTURE—HORTICULTURE—FORESTRY.

Armsby's Principles of Animal Nutrition.....	8vo.	\$4 00
* Bowman's Forest Physiography.....	4vo.	2 00
Budd and Hansen's American Horticultural Manual:		
Part I. Propagation, Culture, and Improvement.....	12mo.	1 25
Part II. Systematic Pomology.....	12mo.	1 25
Elliott's Engineering for Land Drainage.....	12mo.	1 25
Practical Farm Drainage. (Second Edition, Rewritten.).....	12mo.	1 50
Graves's Forest Mensuration.....	8vo.	0 00
* Principles of Handling Woodlands.....	Large 12mo.	1 50
Green's Principles of American Forestry.....	12mo.	1 50
Grotenfelt's Principles of Modern Dairy Practice. (Wells.).....	12mo.	2 00
* Herrick's Denatured or Industrial Alcohol.....	8vo.	4 00
Holm's Milk in Denmark. (In Press.).....		
* Kemp and Waugh's Landscape Gardening. (New Edition, Rewritten.).....	12mo.	1 50
* McKay and Larsen's Principles and Practice of Butter-making.....	8vo.	1 50
Maynard's Landscape Gardening as Applied to Home Decoration.....	12mo.	1 50
Sanderson's Insects Injurious to Staple Crops.....	12mo.	1 50
Insect Pests of Farm, Garden, and Orchard. (In Press.).....		
* Schwarz's Longleaf Pine in Virgin Forest.....	12mo.	1 25
* Solotaroff's Field Book for Street-tree Mapping.....	12mo.	0 75
In lots of one dozen.....		8 00
* Shade Trees in Towns and Cities.....	8vo.	2 00
Stockbridge's Rocks and Soils.....	8vo.	2 50
Winton's Microscopy of Vegetable Foods.....	8vo.	7 50
Wolf's Handbook for Farmers and Dairymen.....	16mo.	1 50

ARCHITECTURE.

Atkinson's Orientation of Buildings or Planning for Sunlight. (In Press.).....		
Baldwin's Steam Heating for Buildings.....	12mo.	2 50
Berg's Buildings and Structures of American Railroads.....	4to.	2 00

Birkmire's Architectural Iron and Steel.....	8vo,	\$3 50
Compound Riveted Girders as Applied in Buildings.....	8vo,	2 00
Planning and Construction of American Theatres.....	8vo,	3 00
Planning and Construction of High Office Buildings.....	8vo,	3 50
Skeleton Construction in Buildings.....	8vo,	3 00
Briggs's Modern American School Buildings.....	8vo,	4 00
Byrne's Inspection of Materials and Workmanship Employed in Construction.....	16mo,	3 00
Carpenter's Heating and Ventilating of Buildings.....	8vo,	4 00
* Corthell's Allowable Pressure on Deep Foundations.....	12mo,	1 25
Eckel's Building Stones and Clays. (In Press.).....		
Freitag's Architectural Engineering.....	8vo,	3 50
Fire Prevention and Fire Protection. (In Press.).....		
Fireproofing of Steel Buildings.....	8vo,	2 50
Gerhard's Guide to Sanitary Inspections. (Fourth Edition, Entirely Revised and Enlarged.).....	12mo,	1 50
* Modern Baths and Bath Houses.....	8vo,	3 00
Sanitation of Public Buildings.....	12mo,	1 50
Theatre Fires and Panics.....	12mo,	1 50
* The Water Supply, Sewerage and Plumbing of Modern City Buildings.....	8vo,	4 00
Johnson's Statics by Algebraic and Graphic Methods.....	8vo,	2 00
Kellaway's How to Lay Out Suburban Home Grounds.....	8vo,	2 00
Kidder's Architects' and Builders' Pocket-book.....	16mo, mor.,	5 00
Merrill's Stones for Building and Decoration.....	8vo,	5 00
Monckton's Stair-building.....	4to,	4 00
Patton's Practical Treatise on Foundations.....	8vo,	5 00
Peabody's Naval Architecture.....	8vo,	7 50
Rice's Concrete-block Manufacture.....	8vo,	2 00
Richey's Handbook for Superintendents of Construction.....	16mo, mor.	4 00
Building Foreman's Pocket Book and Ready Reference.....	16mo, mor.	5 00
* Building Mechanics' Ready Reference Series:		
* Carpenters' and Woodworkers' Edition.....	16mo, mor.	1 50
* Cement Workers' and Plasterers' Edition.....	16mo, mor.	1 50
* Plumbers', Steam-Fitters', and Tinners' Edition.....	16mo, mor.	1 50
* Stone- and Brick-masons' Edition.....	16mo, mor.	1 50
Sabin's House Painting.....	12mo,	1 00
Siebert and Biggin's Modern Stone-cutting and Masonry.....	8vo,	1 50
Snow's Principal Species of Wood.....	8vo,	3 50
Wait's Engineering and Architectural Jurisprudence.....	8vo,	6 00
	Sheep,	6 50
Law of Contracts.....	8vo,	3 00
Law of Operations Preliminary to Construction in Engineering and Architecture.....	8vo,	5 00
	Sheep,	5 50
Wilson's Air Conditioning.....	12mo,	1 50
Worcester and Atkinson's Small Hospitals, Establishment and Maintenance, Suggestions for Hospital Architecture, with Plans for a Small Hospital.....	12mo,	1 25

ARMY AND NAVY.

Bernadou's Smokeless Powder, Nitro-cellulose, and the Theory of the Cellulose Molecule.....	12mo,	2 50
Chase's Art of Pattern Making.....	12mo,	2 50
Screw Propellers and Marine Propulsion.....	8vo,	3 00
* Cloke's Enlisted Specialists' Examiner.....	8vo,	2 00
* Gunner's Examiner.....	8vo,	1 50
Craig's Azimuth.....	4to,	3 50
Crehore and Squier's Polarizing Photo-chronograph.....	8vo,	3 00
* Davis's Elements of Law.....	8vo,	2 50
* Treatise on the Military Law of United States.....	8vo,	7 00
* Dudley's Military Law and the Procedure of Courts-martial.....	Large 12mo,	2 50
Durand's Resistance and Propulsion of Ships.....	8vo,	5 00

• Dyer's Handbook of Light Artillery.....	16mo.	\$2 00
Eisner's Modern High Explosives.....	8vo.	4 00
• Fletcher's Text-book on Field Fortifications.....	Large 12mo.	2 00
Hannibal and Bonaparte's The Queen's Campaign.....	16mo.	1 00
• Hoff's Elementary Naval Tactics.....	8vo.	1 50
Inglis's Handbook of Problems in Direct Fire Intervive Ballistics. (In Press.).....	8vo.	4 00
• Linné's Ordnance and Gunnery.....	8vo.	2 00
• Lyndon's Logarithmic and Trigonometric Tables.....	8vo.	1 00
• Lydon's Treatise on Electromagnetic Phenomena, Vols. I and II.....	8vo.	2 00
• Mahan's Permanent Fortifications. (Murray.).....	8vo. half mor.	7 50
Manual for Coastal Artillery.....	16mo. mor.	1 50
• Mercator's Attack of Fortified Places.....	16mo.	2 00
• Elements of the Art of War.....	8vo.	4 00
Nixon's Artillery Manual.....	16mo.	1 00
Peabody's Naval Architecture.....	8vo.	7 50
• Phelps's Practical Marine Surveying.....	8vo.	2 50
Putnam's Nautical Charts.....	8vo.	2 00
Rust's Ex-meridian Altitude, Azimuth and Star-Finding Tables.....	8vo.	2 00
• Selkirk's Catechism of Manual of Gunnery Data.....	16mo.	50
Sharpe's Art of Subjugating Armies in War.....	16mo. mor.	1 50
• Taylor's Speed and Power of Ships. 2 vols. Text 8vo, plates oblong etc.		7 50
• Trench and Paine's Manual of Bayonet Exercises and Mock-dutty Fencing.....	24mo. leather.	3 00
• Weaver's Military Explosives.....	8vo.	3 00
• Woodhull's Military Hygiene for Officers of the Line.....	Large 12mo.	1 50

ASSAYING.

Bett's Lead Refining by Electrolysis.....	8vo.	4 00
• Butler's Handbook of Blowpipe Analysis.....	16mo.	75
Fletcher's Practical Instructions in Quantitative Assaying with the Blowpipe.....	16mo. mor.	1 50
Forman and Parloe's Manual of Practical Assaying.....	8vo.	5 00
Lodge's Notes on Assaying and Metallurgical Laboratory Experiments.....	8vo.	3 00
Low's Technical Methods of Ore Analysis.....	8vo.	5 00
Miller's Cyanide Process.....	12mo.	1 00
Manual of Assaying.....	12mo.	1 00
Mine's Production of Aluminum and its Industrial Use. (Wells.).....	12mo.	2 50
Ricketts and Miller's Notes on Assaying.....	8vo.	5 00
Robins and Lenglen's Cyanide Industry. (Le Chem.).....	8vo.	4 00
• Seamon's Manual for Assayers and Chemists.....	Large 12mo.	2 50
Ulke's Modern Electrolytic Copper Refining.....	8vo.	3 00
Wilson's Chlorination Process.....	12mo.	1 50
Cyanide Processes.....	12mo.	1 50

ASTRONOMY.

Cornstock's Field Astronomy for Engineers.....	8vo.	2 50
Craig's Azimuth.....	4to.	5 50
Crandall's Text-book on Geodesy and Least Squares.....	8vo.	3 00
Deoditt's Treatise on Practical Astronomy.....	8vo.	4 00
Hayford's Text-book of Geodetic Astronomy.....	8vo.	5 00
Hausner's Azimuth.....	16mo. mor.	1 00
• Text-book on Practical Astronomy.....	8vo.	2 00
Merriman's Elements of Precise Surveying and Geodesy.....	8vo.	2 50
• Michie and Harlow's Practical Astronomy.....	8vo.	3 00
Rust's Ex-meridian Altitude, Azimuth and Star-Finding Tables.....	8vo.	3 00
• White's Elements of Theoretical and Descriptive Astronomy.....	12mo.	2 00

CHEMISTRY.

• Abderhalden's Physiological Chemistry in Thirty Lectures. (Hall and Defren.).....	8vo.	5 00
• Abegg's Theory of Electrolytic Dissociation. (von Ebel.).....	12mo.	1 25
Alexeyeff's General Principles of Organic Synthesis. (Mathews.).....	8vo.	3 00

Allen's Tables for Iron Analysis.....	8vo,	\$3 00
Armby's Principles of Animal Nutrition.....	8vo,	4 00
Arnold's Compendium of Chemistry. (Mandel.).....	Large 12mo,	3 50
Association of State and National Food and Dairy Departments, Hartford Meeting, 1906.....	8vo,	3 00
Jamestown Meeting, 1907.....	8vo,	3 00
Austen's Notes for Chemical Students.....	12mo,	1 50
Baskerville's Chemical Elements. (In Preparation.)		
Bernadou's Smokeless Powder—Nitro-cellulose, and Theory of the Cellulose Molecule.....	12mo,	2 50
* Biltz's Introduction to Inorganic Chemistry. (Hall and Phelan).....	12mo,	1 25
Laboratory Methods of Inorganic Chemistry. (Hall and Blanchard.)	8vo,	3 00
* Bingham and White's Laboratory Manual of Inorganic Chemistry.....	12mo,	1 00
* Blanchard's Synthetic Inorganic Chemistry.....	12mo,	1 00
Bottler's Varnish Making. (Sabin.) (In Press.)		
* Browning's Introduction to the Rarer Elements.....	8vo,	1 50
* Butler's Handbook of Blowpipe Analysis.....	16mo,	75
* Claassen's Beet-sugar Manufacture. (Hall and Rolfe.).....	8vo,	3 00
Classen's Quantitative Chemical Analysis by Electrolysis. (Boltwood.)	8vo,	3 00
Cohn's Indicators and Test-papers.....	12mo,	2 00
Tests and Reagents.....	8vo,	3 00
Cohnheim's Functions of Enzymes and Ferments. (In Press.)		
* Danneel's Electrochemistry. (Merriam.).....	12mo,	1 25
Dannerth's Methods of Textile Chemistry.....	12mo,	2 00
Duhem's Thermodynamics and Chemistry. (Burgess.).....	8vo,	4 00
Effront's Enzymes and their Applications. (Prescott.).....	8vo,	3 00
Eissler's Modern High Explosives.....	8vo,	4 00
* Fischer's Oedema.....	8vo,	2 00
* Physiology of Alimentation.....	Large 12mo,	2 00
Fletcher's Practical Instructions in Quantitative Assaying with the Blowpipe.	16mo, mor.	1 50
Fowler's Sewage Works Analyses.....	12mo,	2 00
Fresenius's Manual of Qualitative Chemical Analysis. (Wells.).....	8vo,	5 00
Manual of Qualitative Chemical Analysis. Part I. Descriptive. (Wells.)	8vo,	3 00
Quantitative Chemical Analysis. (Cohn.) 2 vols.....	8vo,	12 50
When Sold Separately, Vol. I, \$6. Vol. II, \$8.		
Fuertes's Water and Public Health.....	12mo,	1 50
Furman and Pardoe's Manual of Practical Assaying.....	8vo,	3 00
* Getman's Exercises in Physical Chemistry.....	12mo,	2 00
Gill's Gas and Fuel Analysis for Engineers.....	12mo,	1 25
* Gooch and Browning's Outlines of Qualitative Chemical Analysis.	Large 12mo,	1 25
Grotenfelt's Principles of Modern Dairy Practice. (Woll.).....	12mo,	2 00
Groth's Introduction to Chemical Crystallography (Marshall).	12mo,	1 25
* Hammarsten's Text-book of Physiological Chemistry. (Mandel.).....	8vo,	4 00
Hanausek's Microscopy of Technical Products. (Winton.).....	8vo,	5 00
* Haskins and Macleod's Organic Chemistry.....	12mo,	2 00
* Herrick's Denatured or Industrial Alcohol.....	8vo,	4 00
Hinds's Inorganic Chemistry.....	8vo,	3 00
* Laboratory Manual for Students.....	12mo,	1 00
* Holleman's Laboratory Manual of Organic Chemistry for Beginners. (Walker.).....	12mo,	1 00
Text-book of Inorganic Chemistry. (Cooper.).....	8vo,	2 50
Text-book of Organic Chemistry. (Walker and Mott.).....	8vo,	2 50
Holley's Analysis of Paint and Varnish Products. (In Press.)		
* Lead and Zinc Pigments.....	Large 12mo,	3 00
Hopkins's Oil-chemists' Handbook.....	8vo,	3 00
Hopkin's Directions for Laboratory Work in Physiological Chemistry.	8vo,	1 25
Johnson's Rapid Methods for the Chemical Analysis of Special Steels, Steel-making Alloys and Graphite.....	Large 12mo,	3 00
Landauer's Spectrum Analysis. (Tingle.).....	8vo,	3 00
Lassar-Cohn's Application of Some General Reactions to Investigations in Organic Chemistry. (Tingle.).....	12mo,	1 00
Leach's Inspection and Analysis of Food with Special Reference to State Control.....	8vo,	7 50
Löb's Electrochemistry of Organic Compounds. (Lorenz.).....	8vo,	3 00

Lodge's Notes on Assaying and Metallurgical Laboratory Experiments.	80	75
Low's Technical Method of Ore Analysis.	80c	2 00
Low's Patent for Steel Structures.	12mo.	1 00
Lunge's Techno-chemical Analysis. (Cobalt).	12mo.	1 00
* McKay and Larsen's Principles and Practice of Baster-making.	80c	1 50
Maire's Modern Pigments and their Vehicles.	12mo.	2 00
Mandell's Handbook for Bio-chemical Laboratory.	12mo.	1 50
* Martin's Laboratory Guide to Qualitative Analysis with the Microscope.	12mo.	5 00
Mason's Examination of Water. (Chemical and Bacteriological).	12mo.	1 25
Water-supply. (Considered Principally from a Sanitary Standpoint).	80c	4 00
* Matheson's First Principles of Chemical Theory.	80c	1 00
Matthews's Laboratory Manual of Dyeing and Textile Chemistry.	80c	2 50
Textile Fibres. 2d Edition, Rewritten.	80c	6 00
* Meyer's Determination of Radicals in Carbon Compounds. (Thoma).	12mo.	1 25
Third Edition.	12mo.	1 00
Miller's Cyanide Process.	12mo.	1 00
Manual of Assaying.	12mo.	1 00
Minet's Production of Aluminum and its Industrial Use. (Waller).	12mo.	2 50
* Mittlestadt's Technical Calculations for Sugar Works. (Beerhals).	12mo.	1 50
Mixter's Elementary Text-book of Chemistry.	12mo.	1 50
Morgan's Elements of Physical Chemistry.	12mo.	2 00
* Physical Chemistry for Electrical Engineers.	12mo.	1 50
* Moore's Experiments in Organic Chemistry.	12mo.	0 50
* Outline of Organic Chemistry.	12mo.	1 50
Morse's Calculations used in Cane-sugar Factories.	16mo. mar.	1 50
* Muir's History of Chemical Theories and Laws.	80c	4 00
Mulliken's General Method for the Identification of Pure Organic Compounds.	80c	5 00
Vol. I. Compounds of Carbon with Hydrogen and Oxygen. Large 8vo.	8 00	
Vol. II. Nitrogenous Compounds. (In Preparation).		
Vol. III. The Commercial Dyestuffs. Large 8vo.	8 00	
* Nelson's Analysis of Drugs and Medicines.	12mo.	5 00
Ostwald's Conversations on Chemistry. Part One (Ramm).	12mo.	1 50
" " " " Part Two (Turnbull).	12mo.	2 00
* Introduction to Chemistry. (Hall and Williams). Large 12mo.	1 50	
Owen and Standage's Dyeing and Cleaning of Textile Fabrics.	12mo.	2 00
* Palmer's Practical Test Book of Chemistry.	12mo.	1 00
* Panch's Physical Chemistry in the Service of Medicine. (Fischer).	12mo.	1 25
Penfield's Tables of Minerals, Including the Use of Minerals and Statistics of Domestic Production.	80c	1 00
Pictet's Alkaloids and their Chemical Constitution. (Biddle).	80c	5 00
Poole's Calorific Power of Fuels.	80c	3 00
Prescott and Winslow's Elements of Water Bacteriology, with Special Reference to Sanitary Water Analysis.	12mo.	1 50
* Reising's Guide to Piece-Dyeing.	80c	25 00
Richards and Woodman's Air, Water, and Food from a Sanitary Standpoint.	80c	2 00
Ricketts and Miller's Notes on Assaying.	80c	3 00
Rideal's Disinfection and the Preservation of Food.	80c	4 00
Rizzo's Elementary Manual for the Chemical Laboratory.	80c	1 25
Robine and Lenglen's Cyanide Industry. (Le Clercq).	80c	4 00
Ruddiman's Incompatibilities in Prescriptions.	80c	2 00
Why in Pharmacy.	12mo.	1 00
* Ruer's Elements of Metallography. (Mathewson).	80c	3 00
Sabin's Industrial and Artistic Technology of Paint and Varnish.	80c	3 00
Salkowski's Physiological and Pathological Chemistry. (Orndorff).	80c	2 50
* Schimml's Essentials of Volumetric Analysis. Large 12mo.	1 50	
Manual of Volumetric Analysis. (Fifth Edition, Rewritten).	80c	5 00
* Qualitative Chemical Analysis.	80c	1 25
* Seamon's Manual for Assayers and Chemists. Large 12mo.	2 50	
Smith's Lecture Notes on Chemistry for Dental Students.	80c	2 50
Spencer's Handbook for Cane Sugar Manufacturers.	16mo. mar.	3 00
Handbook for Chemists of Beet-sugar Houses.	16mo. mar.	3 00
Stockbridge's Rocks and Soils.	80c	2 50
Stone's Practical Testing of Gas and Gas Meters.	80c	3 50
* Tillman's Descriptive General Chemistry.	80c	3 00

* Tillman's Elementary Lessons in Heat	8vo,	\$1 50
Treadwell's Qualitative Analysis. (Hall.).....	8vo,	3 00
Quantitative Analysis. (Hall.).....	8vo,	4 00
Turneure and Russell's Public Water-supplies.....	8vo,	5 00
Van Deventer's Physical Chemistry for Beginners. (Boltwood.).....	12mo,	1 50
Venable's Methods and Devices for Bacterial Treatment of Sewage.....	8vo,	3 00
Ward and Whipple's Freshwater Biology. (In Press.)		
Ware's Beet-sugar Manufacture and Refining. Vol. I.....	8vo,	4 00
Vol. II.....	8vo,	5 00
Washington's Manual of the Chemical Analysis of Rocks.....	8vo,	2 00
* Weaver's Military Explosives.....	8vo,	3 00
Wells's Laboratory Guide in Qualitative Chemical Analysis.....	8vo,	1 50
Short Course in Inorganic Qualitative Chemical Analysis for Engineering Students.....	12mo,	1 50
Text-book of Chemical Arithmetic.....	12mo,	1 25
Whipple's Microscopy of Drinking-water.....	8vo,	3 50
Wilson's Chlorination Process.....	12mo,	1 50
Cyanide Processes.....	12mo,	1 50
Winton's Microscopy of Vegetable Foods.....	8vo,	7 50
Zsigmondy's Colloids and the Ultramicroscope. (Alexander.)..	Large 12mo,	3 00

CIVIL ENGINEERING.

BRIDGES AND ROOFS. HYDRAULICS. MATERIALS OF ENGINEERING. RAILWAY ENGINEERING.

* American Civil Engineers' Pocket Book. (Mansfield Merriman, Editor-in-chief.).....	16mo, mor.	5 00
Baker's Engineers' Surveying Instruments.....	12mo,	3 00
Bixby's Graphical Computing Table.....	Paper 19½×24½ inches.	25
Breed and Hosmer's Principles and Practice of Surveying. Vol. I. Elementary Surveying.....	8vo,	3 00
Vol. II. Higher Surveying.....	8vo,	2 50
* Burr's Ancient and Modern Engineering and the Isthmian Canal.....	8vo,	3 50
Comstock's Field Astronomy for Engineers.....	8vo,	2 50
* Corthell's Allowable Pressure on Deep Foundations	12mo,	1 25
Crandall's Text-book on Geodesy and Least Squares.....	8vo,	3 00
Davis's Elevation and Stadia Tables.....	8vo,	1 00
Elliott's Engineering for Land Drainage.....	12mo,	1 50
* Fieberger's Treatise on Civil Engineering.....	8vo,	5 00
Flemer's Phototopographic Methods and Instruments.....	8vo,	5 00
Folwell's Sewerage. (Designing and Maintenance.).....	8vo,	3 00
Freitag's Architectural Engineering.....	8vo,	3 50
French and Ives's Stereotomy.....	8vo,	2 50
Gilbert, Wightman, and Saunders's Subways and Tunnels of New York. (In Press.)		
* Hauch and Rice's Tables of Quantities for Preliminary Estimates... 12mo,		1 25
Hayford's Text-book of Geodetic Astronomy.....	8vo,	3 00
Hering's Ready Reference Tables (Conversion Factors.).....	16mo, mor.	2 50
Hosmer's Azimuth.....	16mo, mor.	1 00
* Text-book on Practical Astronomy.....	8vo,	2 00
Howe's Retaining Walls for Earth.....	12mo,	1 25
* Ives's Adjustments of the Engineer's Transit and Level.....	16mo, bds.	25
Ives and Hilt's Problems in Surveying, Railroad Surveying and Geodesy.....	16mo, mor.	1 50
* Johnson (J.B.) and Smith's Theory and Practice of Surveying. Large 12mo,		3 50
Johnson's (L. J.) Statics by Algebraic and Graphic Methods.....	8vo,	2 00
* Kinnicutt, Winslow and Pratt's Sewage Disposal.....	8vo,	3 00
* Mahan's Descriptive Geometry.....	8vo,	1 50
Merriman's Elements of Precise Surveying and Geodesy.....	8vo,	2 50
Merriman and Brooks's Handbook for Surveyors.....	16mo, mor.	2 00
Nugent's Plane Surveying.....	8vo,	3 50
Ogden's Sewer Construction.....	8vo,	3 00
Sewer Design.....	12mo,	2 00
Parsons's Disposal of Municipal Refuse.....	8vo,	2 00
Patton's Treatise on Civil Engineering.....	8vo, half leather,	7 50

Reed's Topographical Drawing and Sketching.....	4mo.	\$5 00
Riemer's (Staff)-sinking under Difficult Conditions (Coring and Peck).....	8vo.	1 00
Riebert and Higgins's Modern Stone-cutting and Masonry.....	8vo.	1 00
Smith's Manual of Topographical Drawing. (McMillan).....	6mo.	2 50
Seiter's Air and Ventilation of Subways.....	12mo.	2 50
* Tracy's Exercises in Surveying.....	12mo. cloth	1 00
Tracy's Plane Surveying.....	16mo. cloth	1 00
Vonaldi's Garbage Cremation in America.....	8vo.	2 00
Methods and Devices for Bacterial Treatment of Sewage.....	8vo.	2 00
Walt's Engineering and Architectural Jurisprudence.....	8vo.	0 00
Law of Contracts.....	Shoep.	0 00
Law of Operations Preliminary to Construction in Engineering and Architecture.....	8vo.	5 00
Warren's Stereotomy—Problems in Stone-cutting.....	8vo.	2 50
* Waterbury's Vest-Pocket Hand-book of Mathematics for Engineers.....	2 1/2 x 3 1/4 inches, cloth	1 00
Enlarged Edition, including Tables.....	cloth	1 50
Webb's Problems in the Use and Adjustment of Engineering Instruments.....	16mo. cloth	1 25
Wilson's Topographic Surveying.....	8vo.	2 50

BRIDGES AND ROOFS.

Boller's Practical Treatise on the Construction of Iron Highway Bridges. 8vo.	2 00
* Thomas River Bridge. Oblong paper.	2 00
Burr and Falk's Design and Construction of Metallic Bridges.	8vo. 3 00
Influence Lines for Bridge and Roof Computations.	8vo. 2 00
De Bock's Mechanics of Engineering. Vol. II. Small 4to.	10 00
Poster's Treatise on Wooden Trestle Bridges.	4to. 2 00
Powder's Ordinary Foundations.	8vo. 2 50
Greene's Arches in Wood, Iron, and Stone.	8vo. 2 50
Bridge Trusses.	8vo. 2 50
Roof Trusses.	8vo. 1 25
Grinn's Secondary Stresses in Bridge Trusses.	8vo. 2 50
Heller's Stresses in Structures and the Accompanying Deformations.	8vo. 2 00
Howe's Design of Simple Roof-trusses in Wood and Steel.	8vo. 2 00
Symmetrical Masonry Arches.	8vo. 2 50
Treatise on Arches.	8vo. 4 00
* Hudson's Deflections and Statically Indeterminate Stresses. Small 4to.	2 50
* Plate Girder Design.	8vo. 1 50
* Jacoby's Structural Details, or Elements of Design in Heavy Framing. 8vo.	2 25
Johnson, Bryan and Turneaure's Theory and Practice in the Designing of Modern Framed Structures. Small 4to.	10 00
* Johnson, Bryan and Turneaure's Theory and Practice in the Designing of Modern Framed Structures. New Edition. Part I. 8vo.	3 00
* Part II. New Edition.	8vo. 4 00
Merriman and Jacoby's Text-book on Roofs and Bridges.	8vo. 2 50
Part I. Stresses in Simple Trusses.	8vo. 2 50
Part II. Graphic Statics.	4mo. 2 50
Part III. Bridge Design.	8vo. 2 50
Part IV. Higher Structures.	8vo. 2 50
Sondericker's Graphic Statics, with Applications to Trusses, Beams, and Arches.	8vo. 2 00
Waddell's De Pontibus, Pocket-book for Bridge Engineers. 16mo. cloth.	2 50
* Specifications for Steel Bridges.	12mo. 50
Waddell and Harrington's Bridges Engineering. (In Preparation.)	

HYDRAULICS.

Barnes's Ice Formation.....	8vo.	3 00
Bazin's Experiments upon the Contraction of the Liquid Jet Issuing from an Orifice. (Trautwine).....	8vo.	2 00
Bovey's Treatise on Hydraulics.....	8vo.	3 00

Church's Diagrams of Mean Velocity of Water in Open Channels.

	Oblong 4to, paper,	\$1 50
Hydraulic Motors.....	8vo,	2 00
Mechanics of Fluids (Being Part IV of Mechanics of Engineering) ..	8vo,	3 00
Coffin's Graphical Solution of Hydraulic Problems.....	16mo, mor.	2 50
Plather's Dynamometers, and the Measurement of Power.....	12mo,	3 00
Folwell's Water-supply Engineering.....	8vo,	4 00
Prizell's Water-power.....	8vo,	5 00
Fuertes's Water and Public Health.....	12mo,	1 50
Water-filtration Works.....	12mo,	2 50
Ganguillet and Kutter's General Formula for the Uniform Flow of Water in Rivers and Other Channels. (Hering and Trautwine.).....	8vo,	4 00
Hazen's Clean Water and How to Get It.....	Large 12mo,	1 50
Filtration of Public Water-supplies.....	8vo,	3 00
Hazelhurst's Towers and Tanks for Water-works.....	8vo,	2 50
Herschel's 115 Experiments on the Carrying Capacity of Large, Riveted, Metal Conduits.....	8vo,	2 00
Hoyt and Grover's River Discharge.....	8vo,	2 00
Hubbard and Kiersted's Water-works Management and Maintenance.	8vo,	4 00
* Lyndon's Development and Electrical Distribution of Water Power.	8vo,	3 00
Mason's Water-supply. (Considered Principally from a Sanitary Stand-point.).....	8vo,	4 00
Merriman's Treatise on Hydraulics.....	8vo,	5 00
* Molitor's Hydraulics of Rivers, Weirs and Sluices.....	8vo,	2 00
* Morrison and Brodie's High Masonry Dam Design.....	8vo,	1 50
* Richards's Laboratory Notes on Industrial Water Analysis.....	8vo,	50
Schuyler's Reservoirs for Irrigation, Water-power, and Domestic Water-supply. Second Edition, Revised and Enlarged.....	Large 8vo,	6 00
* Thomas and Watt's Improvement of Rivers.....	4to,	6 00
Turneure and Russell's Public Water-supplies.....	8vo,	5 00
* Wegmann's Design and Construction of Dams. 6th Ed., enlarged....	4to,	6 00
Water-Supply of the City of New York from 1658 to 1895.....	4to,	10 00
Whipple's Value of Pure Water.....	Large 12mo,	1 00
Williams and Hazen's Hydraulic Tables.....	8vo,	1 50
Wilson's Irrigation Engineering.....	8vo,	4 00
Wood's Turbines.....	8vo,	2 50

MATERIALS OF ENGINEERING.

Baker's Roads and Pavements.....	8vo,	5 00
Treatise on Masonry Construction.....	8vo,	5 00
Black's United States Public Works.....	Oblong 4to,	5 00
Blanchard and Drowne's Highway Engineering. (In Press.)		
Bleinger's Manufacture of Hydraulic Cement. (In Preparation.)		
Botiller's Varnish Making. (Sabin.) (In Press.)		
Burr's Elasticity and Resistance of the Materials of Engineering.....	8vo,	7 50
Byrne's Highway Construction.....	8vo,	5 00
Inspection of the Materials and Workmanship Employed in Construction.	16mo,	3 00
Church's Mechanics of Engineering.....	8vo,	6 00
Mechanics of Solids (Being Parts I, II, III of Mechanics of Engineering).....	8vo,	4 50
Du Bois's Mechanics of Engineering.		
Vol. I. Kinematics, Statics, Kinetics.....	Small 4to,	7 50
Vol. II. The Stresses in Framed Structures, Strength of Materials and Theory of Flexures.....	Small 4to,	10 00
Eckel's Building Stones and Clays. (In Press.)		
* Cements, Limes, and Plasters.....	8vo,	6 00
Powder's Ordinary Foundations.....	8vo,	3 50
* Greene's Structural Mechanics.....	8vo,	2 50
Holley's Analysis of Paint and Varnish Products. (In Press.)		
* Lead and Zinc Pigments.....	Large 12mo,	3 00
* Hubbard's Dust Preventives and Road Binders.....	8vo,	3 00

Johnson's (C. M.) Rapid Methods for the Chemical Analysis of Special Steels, Steel-making Alloys and Castings.....	Large 12mo.	\$2.00
Johnson's (J. H.) Materials of Construction.....	Large 8vo.	4.00
Kemp's Cast Iron.....	8vo.	2.50
Lane's Applied Mechanics.....	8vo.	2.50
Low's Points for Steel Structures.....	12mo.	1.00
Maire's Modern Pavements and their Vehicles.....	12mo.	2.00
Mason's Technical Mechanics.....	8vo.	4.00
Merrill's Studies for Building and Decoration.....	8vo.	2.00
Merriman's Mechanics of Materials.....	8vo.	3.00
• Strength of Materials.....	12mo.	1.00
Merrill's Steel. A Manual for Steel-makers.....	12mo.	2.50
Merriman's Highway Engineering.....	8vo.	2.50
• Mervick's Strength of Materials.....	12mo.	2.00
Patton's Practical Treatise on Foundations.....	8vo.	3.00
Rice's Concrete Block Manufacture.....	8vo.	2.00
Richardson's Modern Asphalt Pavement.....	8vo.	3.00
Richer's Building Foreman's Pocket Book and Ready Reference Book.....	8vo.	2.00
• Current Workers' and Plasterers' Edition (Building Mechanics' Ready Reference Series).....	16mo.	1.50
Handbook for Superintendents of Construction.....	16mo.	4.00
• Stone and Brick Masons' Edition (Building Mechanics' Ready Reference Series).....	16mo.	1.50
• Rie's Clays: Their Occurrence, Properties, and Uses.....	8vo.	3.00
• Rie and Leighton's History of the Clay-working Industry of the United States.....	8vo.	2.50
Sabin's Industrial and Artistic Technology of Paint and Varnish.....	8vo.	2.00
• Smith's Strength of Material.....	12mo.	1.25
Snow's Principal Species of Wood.....	8vo.	2.50
Spaulding's Hydraulic Cement.....	12mo.	2.00
Text-book on Roads and Pavements.....	12mo.	2.00
• Taylor and Thompson's Extracts on Reinforced Concrete Design.....	8vo.	3.00
Treatise on Concrete, Plain and Reinforced.....	8vo.	5.00
Thurston's Materials of Engineering. In Three Parts.....	8vo.	8.00
Part I. Non-metallic Materials of Engineering and Metallurgy.....	8vo.	2.00
Part II. Iron and Steel.....	8vo.	3.50
Part III. A Treatise on Brasses, Bronzes, and Other Alloys and their Constituents.....	8vo.	2.50
Tilghon's Street Pavements and Paving Materials.....	8vo.	4.00
Turneure and Maurer's Principles of Reinforced Concrete Construction. Second Edition, Revised and Enlarged.....	8vo.	3.50
Waterbury's Cement Laboratory Manual.....	12mo.	1.00
Laboratory Manual for Testing Materials of Construction. (In Press.)		
Wood's (De V.) Treatise on the Resistance of Materials, and an Appendix on the Preservation of Timber.....	8vo.	2.00
Wood's (M. P.) Rustless Coatings: Corrosion and Electrolysis of Iron and Steel.....	8vo.	4.00

RAILWAY ENGINEERING.

Andrews's Handbook for Street Railway Engineers.....	3 x 5 inches, mob.	1.25
Berg's Buildings and Structures of American Railroads.....	4to.	5.00
Brooks's Handbook of Street Railroad Location.....	16mo.	1.50
• Burt's Railway Station Service.....	12mo.	2.00
Butts's Civil Engineer's Field-book.....	16mo.	2.50
Crandall's Railway and Other Earthwork Tables.....	8vo.	1.50
Crandall and Barnes's Railroad Surveying.....	16mo.	2.00
• Crockett's Methods for Earthwork Computations.....	8vo.	1.50
Dredge's History of the Pennsylvania Railroad. (1879).....	Paper.	5.00
Fisher's Table of Cubic Yards.....	Cardboard.	25
Godwin's Railroad Engineers' Field-book and Explorer's Guide.....	16mo.	2.50
Hudson's Tables for Calculating the Cubic Contents of Excavations and Embankments.....	8vo.	1.00
Ives and Hilt's Problems in Surveying, Railroad Surveying and Geometry.....	16mo.	1.50
Molitor and Beard's Manual for Resident Engineers.....	16mo.	1.00

ELECTRICITY AND PHYSICS.

• Abegg's Theory of Electrolytic Dissolution. (von Ende.)	12mo.	\$1 25
Andrew's Hand-book for Street Railway Engineers.	8 x 5 inches, cov.	1 25
Anthony and Hall's Lectures on the Theory of Electrical Measure- ments.	12mo.	1 00
Anthony and Bracken's Text-book of Physics. (Magle.) Large	12mo.	2 00
Benjamin's History of Electricity.	8vo.	1 00
Bette's Lead Refining and Electrolysis.	8vo.	1 00
Burgess and Le Châtelier's Measurement of High Temperatures. Third Edition. (In Press.)		
Clawson's Quantitative Chemical Analysis by Electrolysis. (Baltimore.)	8vo.	2 50
• Collins's Manual of Wireless Telegraphy and Telephony.	12mo.	1 50
Crooke and Squier's Polarizing Photo-chromograph.	8vo.	2 00
• Danvers's Electrochemistry. (Marrian.)	12mo.	1 25
Dawson's "Engineering" and Electric Traction Pocket-book.	16mo. cov.	2 50
Dolezalek's Theory of the Lead Accumulator (Storage Battery).	(One Ende.)	
	12mo.	2 50
Duhem's Thermodynamics and Chemistry. (Burgess.)	8vo.	1 00
Flather's Dynamometers, and the Measurement of Power.	12mo.	2 00
• Getman's Introduction to Physical Science.	12mo.	1 50
Gilbert's De Magnete. (Mottelay.)	8vo.	2 00
• Hanchett's Alternating Currents.	12mo.	1 00
Haring's Ready Reference Tables (Conversion Factors).	16mo. cov.	2 50
• Hobart and Ellis's High-speed Dynamo Electric Machinery.	8vo.	6 00
Holman's Precision of Measurements.	8vo.	2 00
Telescope Mirror-scale Method, Adjustments, and Tests. Large	8vo.	72
• Hutchinson's High-Efficiency Electrical Illuminants and Illumination.	Large 12mo.	1 50
Jones's Electric Ignition. (In Press.)		
Karapetoff's Experimental Electrical Engineering—		
• Vol. I.	8vo.	2 50
• Vol. II.	8vo.	2 50
Kinsbrunner's Testing of Continuous-current Machines.	8vo.	2 00
Landauer's Spectrum Analysis. (Tingle.)	8vo.	3 00
Löb's Electrochemistry of Organic Compounds. (Lorenz.)	8vo.	2 00
Lynden's Development and Electrical Distribution of Water Power.	8vo.	3 00
• Lyons's Treatise on Electromagnetic Phenomena. Vols. I. and II. 8vo. each.		6 00
• Michie's Elements of Wave Motion Relating to Sound and Light.	8vo.	4 00
• Morgan's Physical Chemistry for Electrical Engineers.	12mo.	1 50
• Norris's Introduction to the Study of Electrical Engineering.	8vo.	2 50
Norris and Dennison's Course of Problems on the Electrical Characteristics of Circuits and Machines. (In Press.)		
• Parshall and Hobart's Electric Machine Design.	4to. half cov.	12 50
Reagan's Locomotives: Simple, Compound, and Electric. New Edition.	Large 12mo.	2 50
• Rosenberg's Electrical Engineering (Hallam Gee—Kinsbrunner.)	8vo.	2 00
Ryan, Norris, and Hoxie's Electrical Machinery. Vol. I.	8vo.	2 00
Schapper's Laboratory Guide for Students in Physical Chemistry.	12mo.	1 00
• Tillman's Elementary Lessons in Heat.	8vo.	1 25
• Timbie's Elements of Electricity.	Large 12mo.	2 00
Tury and Pitcher's Manual of Laboratory Physics.	Large 12mo.	2 00
Ullie's Modern Electrolytic Copper Refining.	8vo.	2 00
• Waters's Commercial Dynamo Design.	8vo.	2 00

LAW.

• Brennan's Hand-book of Useful Legal Information for Business Men.	16mo. cov.	5 00
• Davis's Elements of Law.	8vo.	2 50
• Treatise on the Military Law of United States.	8vo.	7 00
• DuVley's Military Law and the Procedure of Courts-martial. Large	12mo.	2 50
Manual for Courts-martial.	16mo. cov.	1 50
Wait's Engineering and Architectural Jurisprudence.	8vo.	6 00
	8vo.	6 50
Wait's Law of Contracts.	8vo.	2 00

Wait's Law of Operations Preliminary to Construction in Engineering and Architecture.....	8vo, \$5 00
	Sheep, 5 50

MATHEMATICS.

Baker's Elliptic Functions.....	8vo, 1 50
Briggs's Elements of Plane Analytic Geometry. (Böcher.).....	12mo, 1 00
* Buchanan's Plane and Spherical Trigonometry.....	8vo, 1 00
Byerly's Harmonic Functions.....	8vo, 1 00
Chandler's Elements of the Infinitesimal Calculus.....	12mo, 2 00
* Coffin's Vector Analysis.....	12mo, 2 50
Compton's Manual of Logarithmic Computations.....	12mo, 1 50
* Dickson's College Algebra.....	Large 12mo, 1 50
* Introduction to the Theory of Algebraic Equations.....	Large 12mo, 1 25
Emch's Introduction to Projective Geometry and its Application.....	8vo, 2 50
Fiske's Functions of a Complex Variable.....	8vo, 1 00
Halsted's Elementary Synthetic Geometry.....	8vo, 1 50
Elements of Geometry.....	8vo, 1 75
* Rational Geometry.....	12mo, 1 50
Synthetic Projective Geometry.....	8vo, 1 00
* Hancock's Lectures on the Theory of Elliptic Functions.....	8vo, 5 00
Hyde's Grassmann's Space Analysis.....	8vo, 1 00
* Johnson's (J. B.) Three-place Logarithmic Tables: Vest-pocket size, paper,	15
* 100 copies,	5 00
* Mounted on heavy cardboard, 8 X 10 inches,	25
* 10 copies,	2 00
Johnson's (W. W.) Abridged Editions of Differential and Integral Calculus.	Large 12mo, 1 vol. 2 50
Curve Tracing in Cartesian Co-ordinates.....	12mo, 1 00
Differential Equations.....	8vo, 1 00
Elementary Treatise on Differential Calculus.....	Large 12mo, 1 50
Elementary Treatise on the Integral Calculus.....	Large 12mo, 1 50
* Theoretical Mechanics.....	12mo, 3 00
Theory of Errors and the Method of Least Squares.....	12mo, 1 50
Treatise on Differential Calculus.....	Large 12mo, 3 00
Treatise on the Integral Calculus.....	Large 12mo, 3 00
Treatise on Ordinary and Partial Differential Equations... Large 12mo,	3 50
* Karapetoff's Engineering Applications of Higher Mathematics. Large 12mo,	0 75
Koch's Practical Mathematics. (In Press.)	
Laplace's Philosophical Essay on Probabilities. (Truscott and Emory.) 12mo,	2 00
* Le Messurier's Key to Professor W. W. Johnson's Differential Equations.	
Small 8vo,	1 75
* Ludlow's Logarithmic and Trigonometric Tables.....	8vo, 1 00
* Ludlow and Bass's Elements of Trigonometry and Logarithmic and Other	
Tables.....	8vo, 3 00
* Trigonometry and Tables published separately.....	Each, 2 00
Macfarlane's Vector Analysis and Quaternions.....	8vo, 1 00
McMahon's Hyperbolic Functions.....	8vo, 1 00
Manning's Irrational Numbers and their Representation by Sequences and	
Series.....	12mo, 1 25
Mathematical Monographs. Edited by Mansfield Merriman and Robert	
S. Woodward.....	Octavo, each 1 00
No. 1. History of Modern Mathematics, by David Eugene Smith.	
No. 2. Synthetic Projective Geometry, by George Bruce Halsted.	
No. 3. Determinants, by Laenas Gifford Weld. No. 4. Hyper-	
bolic Functions, by James McMahon. No. 5. Harmonic Func-	
tions, by William E. Byerly. No. 6. Grassmann's Space Analysis,	
by Edward W. Hyde. No. 7. Probability and Theory of Errors	
by Robert S. Woodward. No. 8. Vector Analysis and Quaternions,	
by Alexander Macfarlane. No. 9. Differential Equations, by	
William Woolsey Johnson. No. 10. The Solution of Equations,	
by Mansfield Merriman. No. 11. Functions of a Complex Variable,	
by Thomas S. Fiske.	
Maurer's Technical Mechanics.....	8vo, 4 00
Merriman's Method of Least Squares.....	8vo, 2 00
Solution of Equations.....	8vo, 1 00

MacFarland's Standard Reduction Factors for Gases.	8vo,	\$1 50
Mahan's Industrial Drawing. (Thompson.)	8vo,	3 50
Mehrtens's Gas Engine Theory and Design.	Large 12mo,	2 50
Miller, Berry, and Riley's Problems in Thermodynamics and Heat Engineering.	8vo, paper,	0 75
Oberg's Handbook of Small Tools.	Large 12mo,	2 50
* Parshall and Hobart's Electric Machine Design. Small 4to, half leather.		12 50
* Peelle's Compressed Air Plant. Second Edition, Revised and Enlarged.	8vo,	3 50
Perkins's General Thermodynamics. (In Press.)		
Poole's Calorific Power of Fuels.	8vo,	3 00
* Porter's Engineering Reminiscences, 1855 to 1882.	8vo,	3 00
Randall's Treatise on Heat. (In Press.)		
* Reid's Mechanical Drawing. (Elementary and Advanced.)	8vo,	2 00
Text-book of Mechanical Drawing and Elementary Machine Design	8vo,	3 00
Richards's Compressed Air.	12mo,	1 50
Robinson's Principles of Mechanism.	8vo,	3 00
Schwamb and Merrill's Elements of Mechanism.	8vo,	3 00
Smith (A. W.) and Marx's Machine Design.	8vo,	3 00
Smith's (O.) Press-working of Metals.	8vo,	3 00
Sorel's Carbureting and Combustion in Alcohol Engines. (Woodward and Preston.)	Large 12mo,	3 00
Stone's Practical Testing of Gas and Gas Meters.	8vo,	3 50
Thurston's Animal as a Machine and Prime Motor, and the Laws of Energetics.		
	12mo,	1 00
Treatise on Friction and Lost Work in Machinery and Mill Work.	8vo,	3 00
* Tillson's Complete Automobile Instructor.	16mo,	1 50
* Titsworth's Elements of Mechanical Drawing.	Oblong 8vo,	1 25
Warren's Elements of Machine Construction and Drawing.	8vo,	7 50
* Waterbury's Vest Pocket Hand-book of Mathematics for Engineers.		
	2 $\frac{1}{2}$ × 5 $\frac{1}{2}$ inches, mor.	1 00
* Enlarged Edition, Including Tables.	mor.	1 50
Weisbach's Kinematics and the Power of Transmission. (Herrmann—Klein.)	8vo,	5 00
Machinery of Transmission and Governors. (Hermann—Klein.)	8vo,	5 00
Wood's Turbines.	8vo,	2 50

MATERIALS OF ENGINEERING.

Burr's Elasticity and Resistance of the Materials of Engineering.	8vo,	7 50
Church's Mechanics of Engineering.	8vo,	6 00
Mechanics of Solids (Being Parts I, II, III of Mechanics of Engineering).		
	8vo,	4 50
* Greene's Structural Mechanics.	8vo,	2 50
Holley's Analysis of Paint and Varnish Products. (In Press.)		
* Lead and Zinc Pigments.	Large 12mo,	3 00
Johnson's (C. M.) Rapid Methods for the Chemical Analysis of Special Steels, Steel-Making Alloys and Graphite.	Large 12mo,	3 00
Johnson's (J. B.) Materials of Construction.	8vo,	6 00
Keep's Cast Iron.	8vo,	2 50
* King's Elements of the Mechanics of Materials and of Power of Transmission.	8vo,	2 50
Lanza's Applied Mechanics.	8vo,	7 50
Lowe's Paints for Steel Structures.	12mo,	1 00
Maire's Modern Pigments and their Vehicles.	12mo,	2 00
Maurer's Technical Mechanics.	8vo,	4 00
Merriman's Mechanics of Materials.	8vo,	5 00
* Strength of Materials.	12mo,	1 00
Metcalf's Steel. A Manual for Steel-users.	12mo,	2 00
* Murdock's Strength of Materials.	12mo,	2 00
Sabin's Industrial and Artistic Technology of Paint and Varnish.	8vo,	3 00
Smith's (A. W.) Materials of Machines.	12mo,	1 00
* Smith's (H. E.) Strength of Material.	12mo,	1 25
Thurston's Materials of Engineering.	3 vols.,	8 00
Part I. Non-metallic Materials of Engineering.	8vo,	2 00
Part II. Iron and Steel.	8vo,	3 50
Part III. A Treatise on Brasses, Bronzes, and Other Alloys and their Constituents.	8vo,	2 50

Waterbury's Laboratory Manual for Testing Materials of Construction.

Wood's (Dr V.) Elements of Analytical Mechanics.	(In Press.)	8vo.	\$5.00
Treatise on the Resistance of Materials and an Appendix on the Preservation of Timber.		8vo.	2.00
Wood's (M. P.) Rustless Coatings: Corrosion and Electrolysis of Iron and Steel.		8vo.	4.00

STEAM-ENGINES AND BOILERS.

Berry's Temperature-entropy Diagram. Third Edition, Revised and Enlarged.	12mo.	2.50
Carnot's Reflections on the Motive Power of Heat. (Thomson.)	12mo.	1.50
Chase's Art of Pattern Making.	12mo.	2.50
Crofton's Steam-engine and other Heat Motors.	8vo.	5.00
Hawson's "Engineering" and Electric Traction Pocket-book.	16mo. cloth.	3.00
* Goffhardt's Steam Power Plant Engineering.	8vo.	6.00
Goss's Locomotive Performance.	8vo.	5.00
Hessner's Indicator Practice and Steam-engine Economy.	12mo.	2.00
Hirschfeld and Barnard's Heat Power Engineering. (In Press.)		
Hutton's Heat and Heat-engines.	8vo.	5.00
Mechanical Engineering of Power Plants.	8vo.	2.00
Kant's Steam Boiler Economy.	8vo.	4.00
Kramer's Practice and Theory of the Injector.	8vo.	1.50
MacCord's Slide-valves.	8vo.	2.00
Meyer's Modern Locomotive Construction.	4to.	10.00
Miller, Barry, and Riley's Problems in Thermodynamics.	8vo. paper.	0.11
Moyse's Steam Turbines.	8vo.	4.00
Peabody's Manual of the Steam-engine Indicator.	12mo.	1.50
Tables of the Properties of Steam and Other Vapors and Temperature-Entropy Table.	8vo.	1.00
Thermodynamics of the Steam-engine and Other Heat-engines.	8vo.	2.00
* Thermodynamics of the Steam Turbine.	8vo.	2.00
Valve-gears for Steam-engines.	8vo.	2.50
Peabody and Miller's Steam-boilers.	8vo.	4.00
Puget's Thermodynamics of Reversible Cycles in Gases and Saturated Vapors (Otterberg).	12mo.	1.25
Reagon's Locomotives: Simple, Compound, and Electric. New Edition. Large 12mo.		3.50
Richard's Locomotive Engine Running and Management.	12mo.	2.00
Smart's Handbook of Engineering Laboratory Practice.	12mo.	2.50
Snow's Steam-boiler Practice.	8vo.	2.00
Spangler's Notes on Thermodynamics.	12mo.	1.00
Valve-gears.	8vo.	2.50
Spangler, Greene, and Marshall's Elements of Steam-engineering.	8vo.	3.00
Thomas's Steam-turbines.	8vo.	4.00
Thurston's Handbook of Engine and Boiler Trials, and the Use of the Indicator and the Prony Brake.	8vo.	1.00
Handy Tables.	8vo.	1.50
Manual of Steam-boilers, their Design, Construction, and Operation.	8vo.	3.00
Manual of the Steam-engine.	2 vols. 8vo.	10.00
Part I. History, Structure, and Theory.	8vo.	6.00
Part II. Design, Construction, and Operation.	8vo.	6.00
Wehrenfennig's Analysis and Softening of Boiler Feed-water. (Faltmann.)	8vo.	4.00
Weissbach's Heat, Steam, and Steam-engines. (Du Bois.)	8vo.	2.00
Whitham's Steam-engine Design.	8vo.	5.00
Wiesel's Thermodynamics, Heat Motors, and Refrigerating Machines.	8vo.	4.00

MECHANICS PURE AND APPLIED.

Church's Mechanics of Engineering.	8vo.	5.00
Mechanics of Fluids (Being Part IV of Mechanics of Engineering).	8vo.	3.00
* Mechanics of Internal Work.	8vo.	1.50
Mechanics of Solids (Being Parts I, II, III of Mechanics of Engineering).	8vo.	4.00
Notes and Examples in Mechanics.	8vo.	2.00

Dana's Text-book of Elementary Mechanics for Colleges and Schools .12mo.	\$1 50
Du Bois's Elementary Principles of Mechanics:	
Vol. I. Kinematics.....	.8vo, 3 50
Vol. II. Statics.....	.8vo, 4 00
Mechanics of Engineering. Vol. I.....	Small 4to, 7 50
Vol. II.....	Small 4to, 10 00
* Greene's Structural Mechanics.....	.8vo, 2 50
* Hartmann's Elementary Mechanics for Engineering Students.....	.12mo, 1 25
James's Kinematics of a Point and the Rational Mechanics of a Particle.	
Large 12mo.	2 00
* Johnson's (W. W.) Theoretical Mechanics.....	.12mo, 3 00
* King's Elements of the Mechanics of Materials and of Power of Transmission.....	.8vo, 2 50
Lanza's Applied Mechanics.....	.8vo, 7 50
* Martin's Text Book on Mechanics, Vol. I, Statics.....	.12mo, 1 25
* Vol. II. Kinematics and Kinetics.....	.12mo, 1 50
* Vol. III. Mechanics of Materials.....	.12mo, 1 50
Maurer's Technical Mechanics.....	.8vo, 4 00
* Merriman's Elements of Mechanics.....	.12mo, 1 00
Mechanics of Materials.....	.8vo, 5 00
* Michie's Elements of Analytical Mechanics.....	.8vo, 4 00
Robinson's Principles of Mechanism.....	.8vo, 3 00
Sanborn's Mechanics Problems.....	Large 12mo, 1 50
Schwamb and Merrill's Elements of Mechanism.....	.8vo, 3 00
Wood's Elements of Analytical Mechanics.....	.8vo, 3 00
Principles of Elementary Mechanics.....	.12mo, 1 25

MEDICAL.

* Abderhalden's Physiological Chemistry in Thirty Lectures. (Hall and Defren.).....	.8vo, 5 00
von Behring's Suppression of Tuberculosis. (Bolduan.).....	.12mo, 1 00
* Bolduan's Immune Sera.....	.12mo, 1 50
Bordet's Studies in Immunity. (Gay.).....	.8vo, 6 00
* Chapin's The Sources and Modes of Infection.....	Large 12mo, 3 00
Davenport's Statistical Methods with Special Reference to Biological Variations.....	.16mo, mor. 1 50
Ehrlich's Collected Studies on Immunity. (Bolduan.).....	.8vo, 6 00
* Fischer's Nephritis.....	Large 12mo, 2 50
* Oedema.....	.8vo, 2 00
* Physiology of Alimentation.....	Large 12mo, 2 00
* de Fursac's Manual of Psychiatry. (Rosanoff and Collins.).....	Large 12mo, 2 50
* Hammarsten's Text-book on Physiological Chemistry. (Mandel.).....	.8vo, 4 00
Jackson's Directions for Laboratory Work in Physiological Chemistry.....	.8vo, 1 25
Lassar-Cohn's Praxis of Urinary Analysis. (Lorenz.).....	.12mo, 1 00
Mandel's Hand-book for the Bio-Chemical Laboratory.....	.12mo, 1 50
* Nelson's Analysis of Drugs and Medicines.....	.12mo, 3 00
* Pauli's Physical Chemistry in the Service of Medicine. (Fischer.).....	.12mo, 1 25
* Pozzi-Escot's Toxins and Venoms and their Antibodies. (Cohn.).....	.12mo, 1 00
Rostoski's Serum Diagnosis. (Bolduan.).....	.12mo, 1 00
Ruddiman's Incompatibilities in Prescriptions.....	.8vo, 2 00
Whys in Pharmacy.....	.12mo, 1 00
Salkowski's Physiological and Pathological Chemistry. (Orndorff.).....	.8vo, 2 50
* Satterlee's Outlines of Human Embryology.....	.12mo, 1 25
* Smith's Lecture Notes on Chemistry for Dental Students.....	.8vo, 2 50
* Whipple's Typhoid Fever.....	Large 12mo, 3 00
* Woodhull's Military Hygiene for Officers of the Line.....	Large 12mo, 1 50
* Personal Hygiene.....	.12mo, 1 00
Worcester and Atkinson's Small Hospitals Establishment and Maintenance, and Suggestions for Hospital Architecture, with Plans for a Small Hospital.....	.12mo, 1 25

METALLURGY.

Betts's Lead Refining by Electrolysis.....	.8vo, 4 00
Bolland's Encyclopedia of Founding and Dictionary of Foundry Terms used in the Practice of Moulding.....	.12mo, 3 00

Iron Powder.....	12mo.	\$2 50
Supplements.....	12mo.	2 50
* Borchers's Metallurgy. (Hall and Hayward).....	8vo.	1 00
Burgess and Le Chatelier's Measurement of High Temperatures. Third Edition. (In Press.).....		
Douglas's Untechnical Addresses on Technical Subjects.....	12mo.	1 00
Gossel's Minerals and Metals: A Reference Book.....	16mo. var.	2 00
* Hall's Lead-smelting.....	12mo.	2 50
Johnson's Rapid Methods for the Chemical Analysis of Special Steels, Steel-making Alloys and Graphite.....	Large 12mo.	3 00
Kepp's Cast Iron.....	8vo.	2 50
Merrill's Steel. A Manual for Steel-makers.....	12mo.	2 00
Moser's Production of Aluminium and its Industrial Use. (Walder.).....	12mo.	2 50
Palmer's Foundry Practice. (In Press.).....		
* Price and Meade's Technical Analysis of Brasses.....	12mo.	2 00
* Rose's Elements of Metallurgy. (Mathewson.).....	8vo.	3 00
Smith's Materials of Machinery.....	12mo.	1 00
Tate and Stone's Foundry Practice.....	12mo.	2 00
Thurston's Materials of Engineering. In Three Parts.....	8vo.	8 00
Part I. Non-metallic Materials of Engineering, see Civil Engineering, page 9.		
Part II. Iron and Steel.....	8vo.	2 50
Part III. A Treatise on Brasses, Bronzes, and Other Alloys and their Constituents.....	8vo.	2 50
Ulke's Modern Electrolytic Copper Refining.....	8vo.	3 00
West's American Foundry Practice.....	12mo.	2 50
Moulders' Text Book.....	12mo.	2 50

MINERALOGY.

Baskerville's Chemical Elements. (In Preparation.).....		
* Browning's Introduction to the Rarer Elements.....	8vo.	1 50
Brush's Manual of Determinative Mineralogy. (Penfield.).....	8vo.	4 00
Hyth's Pocket Hand-book of Minerals.....	16mo. var.	2 00
Chester's Catalogue of Minerals.....	8vo. paper.	1 00
	Cloth.	1 25
* Crane's Gold and Silver.....	8vo.	3 00
Dana's First Appendix to Dana's New "System of Mineralogy".....	Large 8vo.	1 00
Dana's Second Appendix to Dana's New "System of Mineralogy".....	Large 8vo.	1 50
Manual of Mineralogy and Petrography.....	12mo.	2 00
Minerals and How to Study Them.....	12mo.	1 50
System of Mineralogy.....	Large 8vo. half leather.	12 50
Text book of Mineralogy.....	8vo.	4 00
Douglas's Untechnical Addresses on Technical Subjects.....	12mo.	1 00
Eakle's Mineral Tables.....	8vo.	1 25
Eckel's Building Stones and Clays. (In Press.).....		
Gossel's Minerals and Metals: A Reference Book.....	16mo. var.	2 00
* Groth's The Optical Properties of Crystals. (Jackson.).....	8vo.	2 50
Groth's Introduction to Chemical Crystallography (Marshall).....	12mo.	1 25
* Hayes's Handbook for Field Geologists.....	16mo. var.	1 50
Iddings's Igneous Rocks.....	8vo.	2 00
Rock Minerals.....	8vo.	2 00
Johannsen's Determination of Rock-forming Minerals in Thin Sections. With Thomsen Index.....	8vo.	5 00
* Martin's Laboratory Guide to Qualitative Analysis with the Microscope.....	12mo.	60
Merrill's Non-metallic Minerals: Their Occurrence and Uses.....	8vo.	4 00
Stones for Building and Decoration.....	8vo.	2 00
* Penfield's Notes on Determinative Mineralogy and Record of Mineral Tests.....	8vo. paper.	50
Tables of Minerals, Including the Use of Minerals and Statistics of Domestic Production.....	8vo.	1 00
* Pirsson's Rocks and Rock Minerals.....	12mo.	2 50
* Richards's Synopsis of Mineral Characters.....	12mo. var.	1 25
* Ries's Clays: Their Occurrence, Properties and Uses.....	8vo.	4 00

* Ries and Leighton's History of the Clay-working Industry of the United States.....	8vo.	\$2 50
* Rowe's Practical Mineralogy Simplified.....	12mo.	1 25
* Tillman's Text-book of Important Minerals and Rocks.....	8vo.	2 00
Washington's Manual of the Chemical Analysis of Rocks.....	8vo.	2 00

Mining.

* Beard's Mine Gases and Explosions.....	Large 12mo.	3 00
* Crane's Gold and Silver.....	8vo.	5 00
* Index of Mining Engineering Literature.....	8vo.	4 00
* Ore Mining Methods.....	8vo.	5 00
* Ore Mining Methods.....	8vo.	3 00
* Dana and Saunders's Rock Drilling.....	8vo.	4 00
Douglas's Untechnical Addresses on Technical Subjects.....	12mo.	1 00
Eisler's Modern High Explosives.....	8vo.	4 00
Goessel's Minerals and Metals: A Reference Book.....	16mo. mor.	3 00
Ihlseng's Manual of Mining.....	8vo.	5 00
* Iles's Lead Smelting.....	12mo.	2 50
* Peele's Compressed Air Plant.....	8vo.	3 50
Riemer's Shaft Sinking Under Difficult Conditions. (Corning and Peele.)	8vo.	3 00
* Weaver's Military Explosives.....	8vo.	3 00
Wilson's Hydraulic and Placer Mining. 2d edition, rewritten.....	12mo.	2 50
Treatise on Practical and Theoretical Mine Ventilation.....	12mo.	1 25

SANITARY SCIENCE.

Association of State and National Food and Dairy Departments, Hartford Meeting, 1906.....	8vo.	3 00
Jamestown Meeting, 1907.....	8vo.	3 00
* Bashore's Outlines of Practical Sanitation.....	12mo.	1 25
Sanitation of a Country House.....	12mo.	1 00
Sanitation of Recreation Camps and Parks.....	12mo.	1 00
* Chapin's The Sources and Modes of Infection.....	Large 12mo.	3 00
Folwell's Sewerage. (Designing, Construction, and Maintenance.).....	8vo.	3 00
Water-supply Engineering.....	8vo.	4 00
Fowler's Sewage Works Analyses.....	12mo.	2 00
Fuertes's Water-filtration Works.....	12mo.	2 50
Water and Public Health.....	12mo.	1 50
Gerhard's Guide to Sanitary Inspections.....	12mo.	1 50
* Modern Baths and Bath Houses.....	8vo.	3 00
Sanitation of Public Buildings.....	12mo.	1 50
* The Water Supply, Sewerage, and Plumbing of Modern City Buildings.....	8vo.	4 00
Hazen's Clean Water and How to Get It.....	Large 12mo.	1 50
Filtration of Public Water-supplies.....	8vo.	3 00
* Kinnicutt, Winslow and Pratt's Sewage Disposal.....	8vo.	3 00
Leach's Inspection and Analysis of Food with Special Reference to State Control.....	8vo.	7 50
Mason's Examination of Water. (Chemical and Bacteriological).....	12mo.	1 25
Water-supply. (Considered principally from a Sanitary Standpoint).....	8vo.	4 00
* Mast's Light and the Behavior of Organisms.....	Large 12mo.	2 50
* Merriman's Elements of Sanitary Engineering.....	8vo.	2 00
Ogden's Sewer Construction.....	8vo.	3 00
Sewer Design.....	12mo.	2 00
Parsons's Disposal of Municipal Refuse.....	8vo.	2 00
Prescott and Winslow's Elements of Water Bacteriology, with Special Reference to Sanitary Water Analysis.....	12mo.	1 50
* Price's Handbook on Sanitation.....	12mo.	1 50
Richards's Conservation by Sanitation.....	8vo.	2 50
Cost of Cleanness.....	12mo.	1 00
Cost of Food. A Study in Diets.....	12mo.	1 00
Cost of Living as Modified by Sanitary Science.....	12mo.	1 00
Cost of Shelter.....	12mo.	1 00
* Richards and Williams's Dietary Computer.....	8vo.	1 50

Richards and Wadman's Air, Water, and Food from a Sanitary Stand- point.....	6cs.	\$2 00
• Richey's Pumps, Sinks, Etc., and Tinsmiths' Edition (Building Mechanics' Ready Reference Series).....	16mo, 8cs.	1 00
Rideal's Disinfection and the Preservation of Food.....	8cs.	4 00
Super's Air and Ventilation of Buildings.....	12mo.	2 00
Townsend and Russell's Public Water Supplies.....	8cs.	2 00
Venable's Garbage Cremation in America.....	8cs.	2 00
Method and Devices for Bacterial Treatment of Sewage.....	8cs.	2 00
Ward and Whipple's Freshwater Biology. (In Press.).....		
Whipple's Microscopy of Drinking-water.....	8cs.	2 50
• Typhoid Fever.....	Large 16mo.	2 00
Value of Pure Water.....	Large 12mo.	1 00
Winslow's Systematic Relationship of the Comensals.....	Large 12mo.	2 50

MISCELLANEOUS.

• Bart's Railway Station Service.....	12mo.	2 00
• Chapin's How to Enamel.....	12mo.	1 00
Enstrom's Geological Guide-book of the Rocky Mountain Region of the International Congress of Geologists.....	Large 8cs.	1 00
Ferrel's Popular Treatise on the Winds.....	8cs.	4 00
Fitzgerald's Boston Machinery.....	16mo.	1 00
• Frita, Autobiography of John.....	8cs.	
Garnett's Statistical Abstracts of the World.....	24mo.	75
Haines's American Railway Management.....	12mo.	2 50
Hannay's The Microscopy of Technical Products. (Winton).....	8cs.	5 00
Jacob's Betterment Briefs. A Collection of Published Papers on Or- ganized Industrial Efficiency.....	8cs.	5 00
Metcalfe's Cost of Manufactures, and the Administration of Workshops.....	8cs.	5 00
Putnam's Nautical Charts.....	8cs.	5 00
Ricketts's History of Renesmee Polytechnic Institute 1824-1894.....	Large 12mo.	5 00
• Reetz and Palmer's Charts of the Atmosphere for Astronauts and Aviators.....	Olds 4to.	2 00
Rotherham's Emphasized New Testament.....	Large 8cs.	2 00
Rust's Ex-Meridian Altitude, Azimuth and Star-finding Tables.....	8cs.	5 00
Standage's Decoration of Wood, Glass, Metal, etc.....	12mo.	2 00
Thorne's Structural and Physiological Botany. (Bennett).....	16mo.	2 25
Westermaier's Compendium of General Botany. (Schneider).....	8cs.	2 00
Winslow's Elements of Applied Microscopy.....	12mo.	1 50

HEBREW AND CHALDEE TEXT-BOOKS.

Gesenius's Hebrew and Chaldee Lexicon to the Old Testament Scriptures (Tregelles).....	Small 4to, half cow.	5 00
Green's Elementary Hebrew Grammar.....	12mo.	1 25

PLEASE DO NOT REMOVE
CARDS OR SLIPS FROM THIS POCKET

UNIVERSITY OF TORONTO LIBRARY

S&M
A
450