THE HARNESS

MAKERS GUIDE

JOHN A. SEAVERNS

THE HARNESS MAKERS' GUIDE

(COPYRIGHT).

PRICE

1/-
NETT.

BOUND IN CLOTH. 1/6.

PUBLISHED AT THE
OFFICE OF
"SADDLERY AND HARNESS,"
WALSALL.

SECOND
EDITION.

JOHN A. SEAVERN

Webster Family Library of Veterinary Medicine
Cummings School of Veterinary Medicine at
Tufts University
200 Westboro Road
North Grafton, MA 01536

THIS PAGE IS FOR

- (1). He who knows not, and knows not he knows not.
- (2). He who knows not, and knows he knows not
- (3). He who knows and knows not he knows.

PRICE:—

*Complete with necessary
Oil Lamps, or Gas Appara-
tus, Bottom Waxed, Thread
Winder, and Accessories.*

(A Table for support-
ing the work is also
supplied when required)

£30

It is not for

He who knows and
knows he knows, for

He has already in-
stalled our

WIDE-WORLD KNOWN

No. 6 Saddlers & Harness Makers' Machine.

☛ Send for our Latest Catalogue FREE on Application. ☛

**THE BRITISH UNITED SHOE MACHINERY CO. LIMITED,
UNION WORKS, LEICESTER.**

THE
HARNESS MAKERS' GUIDE
CONTAINING THE LENGTHS
FOR CUTTING AND MAKING HARNESS,
BRIDLE WORK, STRAPS, &c.,
SHEWING THE COST OF MANUFACTURE

SECOND EDITION.—COPYRIGHT.

WALSALL :
OFFICE OF "SADDLERY AND HARNESS,"

1907.

HARNESS MAKERS,

BROWN SADDLERS,

BRIDLE CUTTERS.

MAKERS OF

PURSES, POCKET BOOKS,
KNEE CAPS, and all kinds of
FANCY LEATHER GOODS.

Harness Furniture,
Bits, Stirrups, Spurs,
The "Holdfast" Patent Hame,

&c., &c.

Patent
"Holdfast" Hames.

WM. OVERTON LD.

MANUFACTURERS,

ARGENT WORKS, WALSALL.

INDEX

	PAGE		PAGE
A Few Hints on Cutting	4	Collar Fore Wales	33
A Good Black, especially for Chamois Skins	69	Collars, Head	37
Wax for Bridle and Brown Leather Work	70	Neck	13
American Buggy Harness	30	Compo, Brown	70
Pair-Horse Harness	30	Harness Blacking	71
A Polish for Belt Edges	70	Coupling Straps	42
Aprons, Knee	37	Covers, Loin	35
A Suitable Cement for Joining the Splices of Machine Belts	69	Cruppers for Riding Saddles	41
Backbands, Breechings, &c., for Gig Harness	24	Cutting, A Few Hints on	4
Bags, Nose	35	Dog Collars, Sizes of Solid Leather ..	39
Bag Straps, Gladstone	40	Donkey Harness	31
Balance Girth, Side Saddle	41	Body Roller	42
Ball Black for Leather Straps	70	Dressing for Belts	71
Belt Edges, A Polish for	70	Dressing, Leather	72
Belting, Machine	43	Dumb Jockey	39
Belts, Dressing for	71	Dyeing Leather	73
Blacking, Harness	71	Embrocation	74
Black Leather Lacquers	70	Engraving and Monogram Cutting ..	62
Varnish for Leather	70	Estimate for Cob Backband	60
Wax, Harness Makers'	71	4in. Leather Body Roller	60
Body Roller, Donkey	42	Making 30 ft. x 6 in. Double Leather Belting ..	61
Brass, Polishing Paste for	74	Making 60 ft. x 3 in. Machine Belting	61
Breeches or Legging Straps	42	New Middle to Backband	60
Breaking Caveson	38	New Pair of Points to Traces	60
Breastplate, Riding	43	Plain Medium-Quality Briass Thill Harness	48
Bride and Brown Leather Work, A Good Wax for	70	Set of Best Thill Harness	45
Bridles, Riding	33	Set of Lined Gig Harness with Sil.-plated Furn. ..	55
Show	35	Set of Lined Gig Harness, with French Backband	59
Steeplechase, etc.	34	Set of Lined Gig Harness, with Kicking Strap	58
Brown Compo	70	Set of Lined Gig Harness, with Long Breeching	58
Cream or Paste for Brown Leather	70	Set of Lined Gig Harness, with Tilbury Backband	59
Edges, For Rubbing up	71	Set of Plain Pony Harness ..	50
Leather, Brown Cream or Paste for	70	Brass-mounted Tradesmen's Harness	52
Buggy Harness, American	30	3in. Tie Wantey	60
Bullock Harness, for Draught	18	Van Backband	60
Bus Harness, Three-horse	28	Extra Throatband for Harness Bridle ..	42
Cab Harness, Hansom	20	Fire Engine Harness	18
Cart Harness—Leader	8	Foal Slips	40
London Style—Thiller	9	Fore Wales, Collar	33
Scotch—Leader	11	For Rubbing up Brown Edges	71
Scotch—Thiller	11	Four-in-Hand Harness	29
Thiller	6	Full-Size Gig Harness	21
Cart Horse Headstall	13	Goat Harness	32
Head-Collars	13	Funeral Carriage Harness	29
Caveson, Breaking	38	Gag Head and Rein	41
Cement for Joining Leather	69	Gig Harness, Backbands, Breechings, &c., for	24
Chamois Skins, A Good Black, especially for	69	Cob-Size	22
Choosing Leather	1		
Clothing, Horse	37		
Cob-Size Gig Harness	22		

	PAGE		PAGE
Gig Harness, Full-Size	21	London Style Cart Harness—Thiller ..	9
" Pony-Size	23	Machine Bands, The Cleansing of ..	72
Girths	40	Belting	43
Gladstone Bag Straps	40	Belts, A Suitable Cement for ..	
Glue, Waterproof	69	Joining the Splices of ..	69
Goat Harness, Full-Size	32	Metal, Polishing Paste for	74
Grease or Soap, Harness	71	" Pltd. Harness	74
Gun Strap (or Sling)	42	Metallic Polishing Powder	74
Hansom Cab Harness	20	Monogram Cutting, Engraving and ..	62
Harness, American Buggy	30	Mowing Machine Harness	16
" American Pair Horse	30	Neck Collars	13
" Blacking	71	Nose Bags	35
" Blacking Compo	71	Nosebands for Riding Bridles ..	34
" Blacking Polish	71	Pair-Horse Harness, American ..	30
" Bullock, for Draught	18	Pair-Horse Harness	26
" Cart—Leader	8	" Van Harness	20
" Cart—Thiller	6	Paste for Patent Leather	69
" Cob-Size, Gig	22	Paste, Permanent	69
" Compo Renovator	71	Patent Leather, Liquid Renovator for ..	72
Harness, Donkey	31	" " Paste for	69
" Fire Engine	18	" " Polish	72
" Four-in-Hand	29	" " To Restore	74
" Full-Size, Gig	21	Permanent Paste	69
" Full-Size, Goat	32	Pit Harness	14
" Funeral Carriage	29	Plated Harness, Metal Polishing ..	
" Gig, Backbands, Breechings, ..		Paste for	74
&c., for	24	Plough Harness	17
" Grease or Soap	71	Polish, Harness	71
" Hansom Cab	20	" Harness Blacking	71
" London Style, Cart—Thiller ..	9	" Patent Leather	72
" Makers' Black Wax	71	Polishing Paste for Brass	74
" Makers' Jet	71	" " for Metal	74
" Mowing Machine	16	" " Metal	74
" Pair-Horse	26	" " for Silver Plate	74
" Pit	14	" Powder, Metallic	74
" Plough	17	Pony-Size Gig Harness	23
" Polish	71	Pony, Tail Case for	41
" Pony-Size, Gig	23	Race Surcingle	42
" Scotch, Cart—Leader	11	Renovator, Harness Compo	71
" Scotch, Cart—Thiller	11	Reins, Rope	40
" Tandem	28	Riding Bridles	33
" Three-horse Bus	28	" Nosebands for	34
" Van, Pair-Horse	20	" Breastplate	43
" Van, Single Horse	19	Riding Saddles, Cruppers for ..	41
Harness Bridle, Extra Throatband for ..	42	Rope Reins	40
Head Collars	37	Rug Straps, Sizes of	39
" " Cart Horse	13	Scotch Cart Harness—Leader ..	11
Headstall, Cart Horse	13	" " —Thiller	11
Hopper Strap	42	Show Bridles	35
Horse Clothing	37	Side Saddle Balance Girth, etc. ..	41
Inflexible Black Japan for Leather ..	72	Silver Plate, Polishing Paste for ..	74
Ink, Stencil	74	Single Horse Van Harness	19
Jet, Harness Makers'	71	Sizes of Solid Leather Dog Collars ..	39
Jockey, Dumb	39	" Rug Straps	39
Joining Leather, Cement for	69	Slips, Foal	40
Knee Aprons	37	Steeplechase Bridles, etc.	34
Leader Cart Harness	8	Stencil Ink	74
" Scotch Cart Harness	11	Stirrup Leathers	40
Leather, Black Varnish for	70	Strap, Hopper	42
" Choosing	1	Straps, Breeches or Legging	42
" Dressing	72	" Coupling	42
" Dyeing	73	Strap (or Sling), Gun	42
" Inflexible Black Japan for ..	72	Surcingle, Race	42
" Lacquers, Black	70	Tail Case for Pony	41
" Straps, Ball Black for	70	Tandem Harness	23
" To Join	69	The Cleansing of Machine Bands ..	72
" To Remove Spots from	74	Thiller Cart Harness	6
Leathers, Stirrup	40	" " —London Style	9
Liquid Renovator for Patent Leather ..	72	" Scotch Cart Harness	11
Loin Covers	35	Three-Horse Bus Harness	28

	PAGE
To Join Leather	69
To Remove Spots from Leather	74
To Restore Patent Leather	74
Van-Harness, Pair-Horse	20
" " Single Horse	19
Waterproof Glue	69

ILLUSTRATIONS.

American Trotting Harness	17
Buggy Harness	8
Four-in-hand Pony Harness—Frontispiece	
Gig Harness	21

	PAGE
Harness Back	5
Hunting Outfit	56
Pair-horse Carriage Harness	25
Patterns for a Complete Suit of Horse Clothing	36
" " London-Style Cart Har- ness—Thiller	10
" " Pit Harness	15
" " Scotch Cart Harness— Thiller	12
Polo Outfit	49
Sling for Sick Horse	40
Tandem Harness	33
Whole Hide	5

This Index tells you which page to turn to when you wish to refer to the useful and valuable information contained in the "Harness Makers' Guide."

THE GOLDEN NAG, on the other hand, tells the World that you are looking at a smart up-to-date Saddler's Shop. Full particulars of this splendid advertisement on receipt of Trade Card to

T. KIRBY & SONS LTD.,

Proprietors and Publishers of "Saddlery and Harness,"

"Harness Makers' Guide," &c.,

WALSALL.

FRANK MILLER'S

Harness Dye and Collar Blacking

Used by every important Harness and Collar Manufacturer in the World. ❧❧

5 GAL. KEGS AND 48 GAL. BARRELS.

FRANK MILLER'S Stitching Wax

IN BARRELS OF 2,500 BALLS.
THE FINEST WAX MADE.

BLACK AND BROWN,
for Machine or Hand Work.

FRANK MILLER'S Harness Dressing

MUCH SUPERIOR TO JET FOR FINISHING.

Makes Second-hand Harness look like New.

SIZES:—PINTS TO BARRELS OF 48 GALLONS.

ALL WHOLESALE HOUSES STOCK OUR GOODS.

If unable to obtain, write

THE FRANK MILLER CO.,

Tower Chambers, Moorgate, LONDON, E.C.

PREFACE.

IN issuing the Second Edition of "THE HARNESS MAKERS' GUIDE," the publishers repeat the warning given in the preface to the First Edition, to the effect that the lengths and sizes given in this work are based on an average between those recognized by different makers. Hence it is necessary that cutters should exercise caution when fitting animals of abnormal proportions.

The information given has been thoroughly revised, and every endeavour has been made to increase the usefulness of the present edition by the inclusion of instructions for the manufacture of a large number of additional articles. The article upon "Choosing Leather" has been re-written, and the information imparted is the result of a life-long study of leather manufacture, and is from the pen of a practical currier of high repute. The scope of "THE HARNESS MAKERS' GUIDE" is increased by the inclusion of an instructive and practical article upon the art of "Engraving and Monogram Cutting." This is added for the benefit of those who have the time and desire to devote to this fascinating work.

In a work of this kind it would be absolutely impossible for no mistakes to occur; the publishers will, therefore, welcome intelligence of such, with a view to correction in future issues.

MAY, 1907.

AN EXPLANATION.

The "Crown" Brand of our Black and Brown Harness Leather is a super selection, and no time nor labour is spared in the preparation; the price is a secondary object is to produce a Harness Leather second to none.

OUR
THREE BRANDS.

"CROWN."

The "Sceptre" Brand in both Black and Brown Harness Leather is the same oak-bark tannage, and warranted unweighted and unadulterated. It is intended to meet the requirements of the large bulk of the Harness Trade who are looking for an honest and reliable Harness Leather. Consistent with a sound, thoroughly well bated oak-bark tannage and pure hand-stuffed, unweighted dressing, it is listed at the lowest possible price.

"SCEPTRE."

The "Orb" Brand is an inferior selection, and is offered to meet the demand for a lower grade article "at a price." It is a reliable quality, and is suitable for export or the intermediate trade. Where competition is a difficulty, it may be recommended with confidence.

"ORB"

S. E. NORRIS & CO.,

St. Paul's Leather Works,

SHADWELL, LONDON, E.

THE HARNESS MAKERS' GUIDE.

CHOOSING LEATHER.

Harness in Great Britain is almost universally made from leather stained black on the grain, and this equally applies to Europe, Canada, and the United States; but in many tropical countries, more especially in South Africa and Australia, brown harness leather, natural colour, or stained a light London colour, or even a rich orange is in use.

It is difficult to account for this, unless it be that in hot, dry countries the dust would be more apparent on black leather—and brown boots are certainly more in demand there for this reason—or whether it is that the native product in a young country is brown for the sake of economy, and the prejudice becomes “rooted.” But in a chapter on “Choosing Leather,” it is of greater importance to decide the relative merits of each.

Now, it is natural that if a man wishes to buy brown leather he selects it of a bright, attractive, even colour throughout, but to produce leather of this description, practically no grease whatever can be used in the dressing, and as grease (the more the better) is the very life and vitality of leather that is exposed to weather and hard usage, it follows that brown leather dressed according to the accepted methods in vogue cannot possess the same durability as black leather, the colour of which is not affected by the amount of grease it is fed upon during the various currying processes. It is, however, only right to add that one London firm of old standing has broken free from the limitations of prejudice and solved the problem of how to produce a brown leather, bright, even, and attractive in colour, and yet with sufficient grease in it to lubricate the fibres and make it sufficiently waterproof to withstand the attacks of damp and weather.

Harness leather may be obtained direct from the currier, or from the saddlers' ironmonger, in the form of backs (*i.e.*, with the bellies cut off) or hides. Both are cut down the backbone after leaving the tannery, as it is in this form a piece of leather is more easily dealt with, and the currier can set out the grain better. It is a question for the harness maker himself to decide whether to buy hides or backs, as it is entirely governed by the class of business which he does. If the bulk of his trade is jobbing work, more especially in country districts, there are many opportunities for profitably using the bellies, and as the price of hides is from 1½d.

to 2d. per lb. less than the equivalent weight in backs, it may be found more economical to buy in this form.

Where to buy is a matter of the first importance, as a harness maker's reputation for supplying a reliable article may easily be ruined, or at least seriously prejudiced, by using inferior and adulterated leather.

If he is in a small way of business and requires single sides at a time, he cannot do better than go to a well-reputed firm of saddlers' ironmongers and obtain his leather at the same house as his metal work and sundries, for they will doubtless give his orders greater personal attention. If, however, he is in a position to buy half-a-dozen pairs at a time (generally known as a bale) he will be well advised to open an account with some firm of harness curriers whose reputation for first-class and reliable quality has stood the test of years. In buying direct you may not only save the middleman's profit, but you have the satisfaction of coming into personal contact with the producer, who can not only offer practical advice in the event of complaint, but he is likely to be more amenable to persuasion and compromise should actual loss result.

It is of the utmost importance to buy well, and the harness maker, having found his market, must next concern himself with the quality of the leather he buys.

We all know the difference that a certain year's crop will make to the value of a vintage, but that difference is as nothing to the differences between the relative value of one tannage and another. It takes a very shrewd judge of leather to assess the quality of tannages, and faith in the ability of your currier's judgment is inevitable. Leather can now be tanned in as many days as it once took months, and it is a regrettable fact that many fine old tanneries that took from twelve to fifteen months to produce leather in the mildest of cold oak bark liquors, have of late years been either closed or been forced to radically alter their methods, in consequence of the inability of the harness maker to appreciate the quality of their old-time leather.

There still remains a wide difference between the astringent foreign extract tannages so largely used and a genuine English oak bark tannage worked on scientific principles. The finished article may appear similar, but the latter will stand the test of time, which the former will not. One will bring credit to the harness maker—who, having convinced himself that he is getting what he pays for, is willing to give a shilling or two more for his back—the other, through ignorance or parsimony, courts complaints and loss of accounts.

The dressing or currying of leather is a subject upon which every harness maker considers he is entitled to speak, and as regards the finished article he does so with considerable justification, for he handles the leather previous to its manufacture into harness, and his contract work gives him the opportunity of watching its wearing qualities. The harness maker, almost to a man, will ask for a "well filled" leather, and will often remark, "I don't like the dubbin spared."

On the other hand, the dealer or saddlers' ironmonger more frequently stocks a light fleshed leather, under the impression that it is not weighted. Now this is a fallacy, for whereas harness leather, weighted on the flesh side by drumming or brushing into it melted sugar or other heavy weighing saccharine matter, possesses a light, bright coloured flesh, while the leather well and thoroughly curried with best cod oil and tallow is not so firm as the dry, harsh, smart-looking weighted leather, but has a well-filled, fat, dark mahogany-coloured flesh. With this latter there may be a little more difficulty in keeping the wax on the thread, but this is of little importance as compared with the more waterproof nature of the leather, its freedom from any tendency to crack, its well lubricated fibre, increasing in a remarkable way the tensile strength of the leather and its consequent durability.

Touching on the subject of cracky leather, it may be mentioned that the most fruitful source of this complaint is the drumming in of melted sugar, glucose, or other crystalline weighting matter which penetrates the grain, and it follows that when this cools it forms minute crystals, fixing the fibre and making the surface brittle. There are, however, two other genuine causes for this trouble. When the raw hide arrives at the tannery, and before it goes to the liquors, it is passed through "limes" of varying strengths to part the hair from the pelt, and this makes the grain brittle and has to be counteracted by subsequent bating and scouring processes. If this is not scientifically and thoroughly done it will never produce a kind mellow grain, and that absence from crack that is so vital to the durability of the leather. If the stitches sink readily and easily into the grain, it may be taken as an indication of a well-bated and thoroughly scoured leather, and care should be exercised in sewing such leather not to pull through too hard. The third cause of leather cracking is too quickly drying (after setting or resetting) in a strong east wind. This requires care in the drying sheds, and the *louvre* or weather boards should be regulated accordingly.

Any unbiassed article on the subject of "Choosing Leather" must necessarily draw attention to the almost universal use of artificial weighting materials in the production of harness leather, with the object of being able to sell at a low price. It may be taken as an axiom that all such weighting materials of a deleterious nature are soluble in water, and it therefore follows that if two pieces of leather, one weighted, the other not, are soaked in water and re-dried, the weighted piece will suffer greater loss in weight than the unweighted piece. For exact data, the pieces to be tested must be cut from the same part of the hide, and must be of the same substance and weight. It also follows that the leather that has lost most will be the least waterproof, for a sound bark tannage and scientifically blended greases are little affected by immersion in water. On the other hand, it is a fatal test for common extract tannages and artificial weighting materials of any kind, as both are soluble in water and soak out during the period of immersion.

Though the adulteration of harness leather is so universal, it is not always practicable for the harness maker to detect it with certainty, and it is a safe plan, when buying from your ironmonger

or currier, to insist upon having only such leather as is stamped and guaranteed "unadulterated." This will ensure freedom from glucose or other artificial weighting material, as prosecution could result if proved to be untrue. Some curriers sell harness leather with specified brands, and it is reasonable to suppose that when sold in this way the currier particularly aims at uniformity in tannage, dressing, and selection. If this can be relied upon it relieves the harness maker of much anxiety, for reliability and uniformity have been the secret of the success of many a good business.

In purchasing leather, see that it is free from warble holes, and is of a close, firm grain, without scratches or other imperfections, and well filled and level throughout. This is not always easy to obtain. Some hides will have a perfect grain, and be full and plump at the back, but fall away at the shoulders, and nothing makes more imperfect reins, backbands, or traces, than these.

A FEW HINTS ON CUTTING.

Harness leather should be of a close, firm, glossy grain, well grown, and of fairly even substance. In choosing it, see that the flanks and other extremities are light and clean, because any excess of weight or waste here, increases the cost of the prime parts.

Having selected a suitable side or back, examine it carefully for any defects. There are two methods of cutting. The first—and that which is more generally adopted—is to straight-edge the leather as shown by the dotted line in Fig. 2, and to cut straight away from this edge. Another plan (which is preferred by some cutters), is to cut 6 inches into the back, as shown by the full line in the same illustration, utilizing this off-cut for gig reins. The leather at this part is found to give greater satisfaction in wear than when the strips are taken close to the back line, where it is always less firm, and consequently not of the same tensile strength.

The part marked A in Fig. 2 will be found stouter than any other portion, and from B to the belly-edge it will be lighter than elsewhere. That marked C is seldom of any use when cut into strips. It is generally flabby, and well scored by the butcher, and proves of more value if cut off in the piece, when it comes in useful for side-piecing collars and such like repairs.

No rule can be laid down here as to the correct order in which the strips should be taken after straight-edging the hide or back. Not only would this necessitate dealing with every style of harness given here, but different qualities would also have to be dealt with, and the various conditions of manufacture. One man may have half-a-dozen pairs of backs to choose from, of different weights and substances, and he is thus able to cut out the various parts with a better regard to efficiency and economy than the man who has a single pair for the purpose.

Practice and careful judgment are the best tutors in gaining knowledge of this work.

Fig. 1.—WHOLE HIDE.

A, Butt. B B, Belly. C, Shoulder. D, Neck. E E, Cheeks. F, Face.

Fig. 2. — HARNESS PACK.
(See Hints on Curing)

CART HARNESS—THILLER, No. 1.

BRIDLE.

Head	1½ by 22in.	Throat	1½ by 22in.
Cheeks, cut	1½ by 30in.	„ point	1½ by 9in.
„ made up	1½ by 13in.	Front, between	1½ by 15in.
Noseband, cut	1½ by 20in.	Winker Stay	1¼ by 13in.
„ made up	1½ by 14in.	„ „ split... ..	8in.
Winkers, cut to pattern	6¾ by 6¼in.		
Bearing Rein, off side	1½ by 60in.		
„ „ near side	1½ by 24in.		
If with chain, off side	1½ by 42in.		
„ „ near side	1½ by 12in.		
If with billets, cut these	1½ by 12in.		
Leading Rein	1 by 60in.		

COLLAR AND HAME STRAPS.

Collar Straps (2)	1½ by 16in.
Top Hame Strap	1 by 28in.
Collar Housing (square)	9 by 22in.
Housing Straps (2)	1 by 12in.

Round Collar Housing cut to pattern.

BREAST COLLAR.

Body, cut	4 by 44in.
Lay, made up	3 by 36in.
Wither strap	2¼ by 38in.
„ „ split	1 by 12in.
„ „ tugs (4)	1 by 6in.
„ „ „ placed from chains	4½in.

Ordinary Breaching Irons are used for the draft chains.

If Contract Irons, make back tugs proportionately shorter.

When required for Plough or Fore Gears, hooks must be used instead of chains.

SADDLE.

Top, cut in two pieces, about	8 by 24in.
Girths, if nailed to tree	1½ by 60in.
Girth Points, if nailed to tree	1½ by 24in.
Girths, if sewn into rings	1½ by 56in.
Girth Points, if sewn into rings	1½ by 22in.
Meter Buckle Pieces (2)	1½ by 9in.

CRUPPER.

If made to buckle to loop on saddle tree.

Body	3½ by 24in.	Hip Straps (2)	1½ by 26in.
Lay	2 by 20in.	Loin Strap	1½ by 48in.
Billet	2 by 26in.	Loin Strap Tugs	1½ by 5in.

Distance between dee and buckle, 10in.

If made to buckle to strap nailed on tree.

Crupper Strap, 2 by 18in. Other particulars as above.

Cart Harness—Thiller, No. 1 (*continued*).**BREECHING.**

Body, cut $3\frac{1}{2}$ by 72in.	Lay, made up ... $2\frac{1}{2}$ by 58in.
„ made up ... $3\frac{1}{2}$ by 60in.	Hip Strap Tugs ... $1\frac{1}{2}$ by 7in.
Lay, cut $2\frac{1}{2}$ by 70in.	If with dees $1\frac{1}{2}$ by 5in

Hip Strap Tugs fixed 14 inches from each end.

No. 2.**BRIDLE.**

Head $1\frac{1}{2}$ by 24in.	Throat, cut ... $1\frac{1}{4}$ by 20in.
Noseband, cut ... $1\frac{1}{2}$ by 20in.	„ made up.. $1\frac{1}{4}$ by 15in.
„ made up $1\frac{1}{2}$ by 14in.	„ point, cut . $1\frac{1}{4}$ by $12\frac{1}{2}$ in.
Winker Stay ... $1\frac{1}{2}$ by 14in.	„ „ made up $1\frac{1}{4}$ by 10in.
„ „ split $8\frac{1}{2}$ in.	Front cut 25in., made 15in. within

Winkers cut to pattern—(winker and cheek combined).

Winker part about $7\frac{1}{2}$ in. square; extended cheek $2\frac{1}{2}$ in. wide.

Total length 15in.

The winker scoloped or cut D pattern before blocked and sewn.
Cheeks and nose cut for turning through rings as indicated on
patterns for Scotch Cart Harness.

Chape to secure cheek buckles. $1\frac{1}{4}$ in. dee attached by link to the
buckles, into which throat and point are sewn.

Small lin. bucklepiece slides on head to receive winker-strap.

Collar Straps $1\frac{1}{2}$ by 17in.

Hame Straps $1\frac{1}{4}$ by 24 to 28in.

SADDLE.

(Made on 13in. Lincoln Tree).

Top cut in two pieces, about $6\frac{1}{2}$ by 21in.

Side leathers cut about 6in. by 10in., and shaped.

The front pattern of top shaped so that the centre is raised when
nailed on the tree.

Sidestrings (or Hangers) $1\frac{3}{8}$ by $16\frac{1}{2}$ in.

Girth (when made up on above) ... $1\frac{3}{4}$ by 50 to 54in.

Girth point „ „ „ $1\frac{3}{4}$ by 24in.

Crupper Strap 2 by 16in.

An illustration of this style of saddle, with full particulars for
making same, appeared in "SADDLERY AND HARNESS"
for April, 1901.

BREECHING AND CRUPPER.

Body, cut $3\frac{1}{2}$ in. wide. | Lay, cut $2\frac{7}{8}$ in. wide.

The full length of hide or back.

Body made up, 60in.

The two strips are reversed—the light or neck ends being turned
beyond where the body is punched for the hip-strap tugs.

Hip-strap tugs, about 12in. from each end.

„ „ cut $1\frac{1}{2}$ by 17in.

Cart Harness—Thiller, No. 2 (*continued*).

Hip-strap tugs strongly sewn together at the back, underneath the shaped safes.

Loin-strap tugs, cut $1\frac{1}{2}$ in. by 10 in.

„ „ joined, etc., at back as hip-strap ditto.

„ cut ... $1\frac{1}{2}$ by $50\frac{1}{2}$ in.; made up 46 in.

Hip-straps (2) ... $1\frac{1}{2}$ by $30\frac{1}{2}$ in.; „ 26 in.

Crupper body $3\frac{1}{2}$ by 24 in.

„ lay $2\frac{1}{2}$ by 26 in.

„ „ reduced in front to $2\frac{1}{2}$ in. for buckle.

Distance between dee and opening for loin-strap about 9 in.

BILLETED WANTEY, or BELLYBAND.

Body, made up 3 by 36 in. Billets (2) 3 by 28 in.

TIE WANTEY.

Body, cut 3 in. by full length of hide.

Lay, cut $2\frac{1}{2}$ in. „ „ „

Tie Piece $2\frac{1}{2}$ in. to make total length 13 feet.

Made up full width the first 3 feet, then gradually reduced to a point

Cart Bellyband with chain-ends, made up 3 in. or $3\frac{1}{2}$ in. by 36 in.

Either stout single leather, or double and sewn 4 rows.

CART HARNESS—LEADER.**BRIDLE.**

Leading Rein, 1 by 102 in. Other particulars same as Thiller.

Collar and Hame Straps as Thiller.

BACKBAND.

Body, cut 4 by 40 in. | Made up 4 by 32 in.

Safes cut to pattern.

Bellyband $1\frac{3}{4}$ by 38 in. | Bellyband Strap ... $1\frac{3}{4}$ by 17 in.

Or with rings and hook-ends, $2\frac{1}{4}$ by 36 in. single, or double,
and sewn 3 rows.

CRUPPER.

If to buckle to Collar Straps.

Body $3\frac{1}{2}$ by 48 or 50 in. | Dock, cut $3\frac{1}{2}$ by 18 in.

Body, split at point 12 in. | Hip Straps, made up $1\frac{1}{2}$ by 26 in.

Body, split at back 12 in. | Hip Strap Tugs „ $1\frac{1}{2}$ by 5 in.

Hip Strap dee sewn on to Crupper body 12 in. from end.

If made without dock, cut body 40 in. long.

Cart Harness—Leader (*continued*).**CRUPPER.**

If to buckle to Collar.

Body	3½ by 46in.	Billet	2 by 24in.
Split at back end only	8in.		

LONDON STYLE CART HARNESS—THILLER.**BRIDLE.**

Head	1¼ by 24in.	Cheeks, cut	1¼ by 28in.
Winkers, cut	6¾ by 6¼in.	Cheeks, made up ...	1¼ by 13in.
Brace Piece (see Fig. 3), Combined Winker and Brace Piece (see Fig. 4.)			
Figs. 1 & 2 Noseband, cut to pattern.		Front, within ...	1¼ by 14in.
1 & 2 Noseband, made up...	15in.	Front, Throat, and Point,	
Check Rein	1 by 78in.	cut in one piece...	1¼ by 48in.
Throat	1¼ by 22in.	Rein, off side ...	1¼ by 60in.
Throat, point ...	1¼ by 9in.	Rein, near side ...	1¼ by 26in.
Rein holders from dees in cheeks ... ¾ by 24in.			

REIN RUNNERS (For supporting Check Rein).

Neck Runner ...	1¼ by 22in.	Wither Runner ...	1½ by 18in.
Rib Runner ...	1½ by 12in.	Billet in each case	¾ by 9in.

COLLAR.

Housing, cut to pattern (see Fig. 5).

Meter Straps	1¼ by 17in.
Hame Strap	1 by 27in.

SADDLE.

Fig. 6 {	Housing for 12in. tree		18 by 24in.
	„ „ 11in. tree		17 by 23in.
	„ „ 10in. tree		16 by 22in.
	Girth		1½ by 60in.
	Girth Strap		1½ by 24in.
	Meter Buckle Pieces		1¼ by 9in.

CRUPPER.

Hanging dee in place of a dock.

Body	3½ by 20in.	Hip Straps	1¼ by 27in.
Lay	2½ by 20in.	Loin Strap	1¼ by 48in.
Billet	2½ by 27in.	Turn back of lay over second dee	
First dee from buckle	10in.	forms "butt" against which hip	
Second dee from buckle	13in.	strap dee rests.	

BREECHING.

Body, made up ...	3 by 72in.	Loin Strap Tugs ...	1¼ by 5in.
Lay	2½ by 70in.	Hip Strap Tugs ...	1¼ by 7in.
Hip Strap Tugs from each end 16in.			
Tug Safes cut to pattern (see Fig. 7).

Figs. 1 & 2.—Swelled Nosepieces for Name-plate.

Fig. 3.—Brace-piece for Cheek.

Fig. 5.—Round Housing for Collar.

Fig. 4.—Combined Winker and Brace-piece, shewing Cheek-line.

Fig. 6.—Square Housing for Saddle.

Fig. 7.—Safe Pattern for Breeching Tugs.

PATTERN FOR LONDON-STYLE CART HARNESS—THILLER.

Leading Rein 1 by 66in
Other particulars as Thiller.

Fig. 1.—Head-piece.

Fig. 8.—Crupper.

Fig. 5.—Front-seam
Lay-piece. Fig. 6.—Back-seam
Lay-piece. Fig. 2.—Cheek and
Winker combined.

Fig. 4.—Saddle-top Cover.

Fig. 7.—Breeching
Tug Safe.

Fig. 3.—Noseband.

PATTERNS FOR SCOTCH CART HARNESS—THILLER.

Scotch Cart Harness—Leader (*continued*).**CRUPPER.**

Hip Straps (2) sewn on to ring	1½	by	24in.
Hip Strap Tugs (2) with safes	1½	by	5in.
Fore Bearers (2) sewn on to ring and going forward to tugs on chain traces at draft	1½	by	42in.
Fore Bearer Tugs (2) with safes	1½	by	5in.

Hip Straps and Fore Bearers are frequently cut 1¾in. wide for Thiller as well as for Leader, in which case the Tugs are also cut 1¾in. wide.

CART HORSE HEADSTALL.

Head, made up	1½	by	48in.
Nose, ,,	1½	by	36in.
Brace pieces	1½	by	13in.
,, ,, between on head			18in.
,, ,, ,, nose			14in.
Throat (sewn on to head) ... 1		by	18in.
,, point (sewn on to head) ... 1		by	9in.

Ends of brace pieces and throat cut mitre shape.

In some districts the strapping is cut 1¾in. or 2in. wide, and some are made without the throatband.

CART HORSE HEAD-COLLARS.

Head, cut	1½	by	28in.
,, made up	1½	by	24in.
Nose, cut	1½	by	23in.
,, made up	1½	by	16½in.
Front (if used), cut	1½	by	25in.
,, ,, made up ... (within)	1½	by	15in.
Throat, cut	1	by	18in.
,, (with lin. buckle), made up	1	by	14in.
,, point, cut	1	by	10in.
,, ,, made up	1	by	8in.
Cheeks, cut	1½	by	20in.
,, made up	1½	by	8½in.
Back Stay, cut	1¼	by	15in.
,, ,, made up	1¼	by	6in.
Braces, cut	1½	by	15½in.
,, made up	1½	by	6in.
Bucklepiece, cut	1½	by	7½in.
,, made up	1½	by	3in.

NECK (sometimes called **Stable** or **Manger**) **COLLARS.**

Made up about 44in. long.

Cut 1¾in., 2in., or 2¼in. wide, as required.

In some localities swivels are used for attaching chain; in others strong dees are regularly used. These are put in about 6in. from the buckle end.

PIT HARNESS.

FULL SIZE.

HOODED BRIDLE.

Fig. 1 showing bridle with skull cap and hood complete; near side of hood the sight hole is closed, on the off side it is shown open.

Fig. 2: Hood Pattern—Lengths, A to B $12\frac{1}{2}$ in., C to D $22\frac{1}{2}$ in., E to F $13\frac{3}{4}$ in., G to H 19in., I to J $16\frac{3}{4}$ in., C to G, and D to H 5in., I to C, and J to D $4\frac{3}{4}$ in., V cut $1\frac{3}{4}$ in. by 1in., C to K $6\frac{3}{4}$ in., L to G $1\frac{3}{4}$ in. In fixing bring C to G and D to H, the wrap over cut off, if not a closed sight.

Fig. 3: Skull Cap Pattern—Lengths, A to B $10\frac{3}{4}$ in., C to D $7\frac{3}{4}$ in., E to F $3\frac{1}{4}$ in., head strap slip cut $2\frac{1}{2}$ in. (lay a piece of leather under this), A to G $7\frac{1}{2}$ in. for pad; let the basil leather lie flat and stuff lightly.

BRIDLE.

Headstrap	...	...	...	$1\frac{1}{2}$	by	20in.
Front, cut	...	...	...	$1\frac{1}{2}$	by	17in.
Front, within	...	...	...			$15\frac{1}{2}$ in.
Nose, cut	...	...	...	$1\frac{1}{2}$	by	17in.
Nose, within	...	...	...			14in.
Throatband, cut	...	...		$1\frac{1}{2}$	by	22in.
„ made up	...	...				18in.
„ strap	...	...		$1\frac{1}{2}$	by	10in.
Chin Strap	...	...		$\frac{3}{4}$	by	10in.
Buckle piece, cut	...	...		$\frac{3}{4}$	by	$11\frac{1}{2}$ in.
„ made up	...	...				10in.
Lead Rein	...	...	...	1	by	12in

COLLAR.

Size	...	...	...			22in.
Fore wale, cut	...	...	...	7	by	56in.

Side pieces to fit.

Cloth or Check, 32in. by 12in.	Throat piece, $5\frac{1}{2}$ in.
Closing Strap, $1\frac{1}{4}$ in. by 12in.	Buckle piece, $1\frac{1}{4}$ in. by 12in.
Hame Chafer, $2\frac{1}{2}$ in. by 7in.	Long Straps, $1\frac{3}{4}$ in. by 21in.

SADDLE.

$8\frac{3}{4}$ in. by 32in., three thicknesses to pattern.

Cross Bars, cut 13in. by $1\frac{3}{4}$ in.

Space under cross bars, $3\frac{1}{2}$ in. for a $2\frac{1}{4}$ in. backband.

Crupper Strap, cut, 2in. by 18in.; made up, doubled.

Linings, check, 15in. by 28in., sewn to $8\frac{1}{2}$ in. from centre.

Chined $2\frac{1}{2}$ in. wide.

Space under cross bars for $2\frac{1}{4}$ in. backband, $3\frac{1}{2}$ in.

Girth, made up ... $1\frac{1}{2}$ by 36in. } with squares and chapes.
Girth Strap, made up $1\frac{1}{2}$ by 20in. }

Fig. 1.—Pit Bridle (complete).

Fig. 3.—Skull Cap.

Fig. 2.—Hood Pattern.
PATTERNS FOR PIT HARNESS.

Pit Harness (*continued*).**BACKBANDS AND BELLYBANDS.**

Cut $2\frac{1}{4}$ in. wide ; length from 18 in. to 22 in., trace ends in addition.

CRUPPER.

Body		$3\frac{1}{2}$	by	19 in.
Lay, made up		$2\frac{1}{4}$	by	15 in.
Hip Straps, made up		$1\frac{3}{4}$	by	26 in.
(Lined throughout).				
Dock Loop		$\frac{3}{4}$	by	10 in.
Pad				17 in.
Lining for pad		$6\frac{1}{2}$	by	20 in.
Basil or white leather bindings to pad.				

BREECHING.

Body, made up		$3\frac{1}{2}$	by	56 in.
Lay		$2\frac{1}{2}$	by	54 in.

Muller rings and short tugs $1\frac{3}{4}$ in., set in, with the filling cut with small half circle extension 12 in. from end for ring chapes.

Loin Strap, cut		$1\frac{1}{2}$	by	48 in.
„ „ tug		$1\frac{1}{2}$	by	5 in.

Rope Reins, 24 ft. Billets for ditto, 1 in. wide

No loops except in Bridle and Loin Strap Tug.

Limmer Tugs, $1\frac{3}{4}$ in., double thickness throughout.

Chains for ditto, swivel with about 6 links and hook.

Very loose narrow loop.

MOWING MACHINE HARNESS.

In addition to ordinary Plough Harness :—

Pole Straps (double leather) 2 by 36 in.

These should be very strong owing to the danger of injury to horses when they break, and the close proximity of the machine knives. If with light breechings, make same style as Pole Harness.

Seat		$1\frac{3}{4}$	by	70 in.
Hipstraps		$1\frac{1}{4}$	by	28 in.
Loin Strap		$1\frac{1}{4}$	by	48 in.
Tugs (4)		$1\frac{1}{4}$	by	5 in.
Breeching Straps		$1\frac{1}{2}$	by	42 in.

PLOUGH HARNESS.

Bridles, etc., as ordinary Cart Harness.

Backband, with pipes	...	...	...	4	by	54in.
„ pipes cut	...	...	...	5	by	18in.
„ with chains	...	...	...	4	by	40in.

Backband Safes to pattern

Other parts as ordinary cart harness

Backband, with pipes, made up	...	...	...	3	by	54in.
„ pipes, cut	...	...	...	5	by	16in.
„ with chains, made up	...	...	...	3	by	40in.
„ (off side), if to buckle, made up...	...	...	...	3	by	48in.
„ (near side), if to buckle, made up	...	...	...	3	by	12in.

Backband safes to pattern.

Cruppers, cut	...	...	...	...	3	by	48in.
„ split front end	...	...	...	...			12in.
„ split back end	...	...	...	...			9in.
„ rein runner on dee	...	...	...	...	$\frac{3}{4}$	by	16in.

Cruppers, no hipstraps and tugs.

LEATHER BACKBAND.

Made up $3\frac{1}{2}$ in. or 4in. by 39in.

Safes or flaps cut about 9in. deep, 6in. wide at bottom for about 4in., the upper part being gradually reduced to width of backband.

These are fitted with hooks at each end. Sometimes the flaps are left plain; in other cases they are lined with leather or check and padded, to keep the chains from chafing the horse.

When webs are used for the centres they are cut from 36in. to 38in., the hooks and flaps being attached by ends or chapes cut about 9in. or 10in. long, and generally made half-circle pattern at the top.

One or two rein dees are placed on at different distances from the ends, according to the districts in which they are used.

ANOTHER STYLE OF PLOUGH BACKBAND.

Leather Backband cut $3\frac{1}{2}$ in. by 60in.

Turn back 6in. from each end and punch holes as for buckles in bend. Secure eye-ends of chains with pin inside the bends.

Safes, 10in. long by $3\frac{1}{2}$ in. at top, and $5\frac{1}{2}$ in. at bottom.

Sew on one dee 12in. from one end, and another 24in.—i.e., on top of backband.

Other kinds are made with narrower hooks, pad for top of backband, and to regulate by one or two buckles.

BULLOCK HARNESS, FOR DRAUGHT.**BRIDLES.**

The various parts made as for Cart Bridles.

Cheeks, made up	...	...	...	...	...	...	1½	by	12½in.
Head, made up	...	...	...	...	...	...	1½	by	24in.
Front, between	...	...	...	...	...	...	1½	by	24in.
Throat, ...	...	...	...	...	...	...	1½	by	15in.
Point	...	...	...	...	...	...	1½	by	10in.
Cut in one piece	...	...	...	...	...	...	1½	by	52in.
Chin Strap, made as hame strap	...	...	...	...	...	...	¾	by	18in.

1½in. rings in Cheeks and Chin Straps.

BACKBANDS.

Made as body rollers	...	...	...	...	...	...	4	by	78in.
Padded centre	...	...	...	...	...	...			18in.
Near side from pad centre	...	...	...	...	...	...			24in.
"	"	"	"	"	"	"	1½	by	18in.
" Pads, with 1¾in. dees sewn on for reins.									
Pads, with 1½in. rings for crupper straps									

CRUPPER.

Body	...	...	...	...	...	...	2	by	24in.
" split	...	...	...	...	...	...			8in.
" lay	...	...	...	...	...	...	1¼	by	15in.
Strap	...	...	...	...	...	...	1¼	by	48in.
Crupper folded dock to buckle.									

REINS.

Made up (each side)	...	...	...	...	...	...	1	by	168in.
Lined parts	...	...	...	...	...	...			20in.
Couplings	...	...	...	...	...	...	1	by	84in.
Pole Straps	...	...	...	...	...	...	1½	by	24in.
Traces (with cock-eye ends)	...	...	...	...	...	...	1½	by	78in.
Hame Tugs	...	...	...	...	...	...	1½	by	9in.
Meter Strap to slide on hame strap, and buckle to front of pad	...	...	...	...	...	...	¾	by	28in.
Hip Straps (double leather)	...	...	...	...	...	...	1¼	by	60in.
" " trace bearers (4) ,made up	...	...	...	...	...	...	1¼	by	7in.

FIRE ENGINE HARNESS.**BRIDLE.**

Heads, cut	...	...	...	...	...	...	1¾	by	23in.
" split	...	...	...	...	...	...	¾	by	7in.
Cheeks, made up	...	...	...	...	...	...	¾	by	8in.
Fronts, within	...	...	...	...	...	...			13in.
Throatbands, cut	...	...	...	...	...	...	¾	by	26in.
" " made up	...	...	...	...	...	...	¾	by	19in.
Nosebands (centres only) made up...	...	...	...	...	...	...	1¼	by	14in.

Fire Engine Harness (*continued*).

Plain Winker Stays		1¼	by	12½in.
" " " split		¾	by	7½in.
Shoulder Tugs		1¾	by	18in.
Traces		1¾	by	74in.
Hame Straps (top only)		¾	by	22in.

REINS.

Drafts		1	by	84in.
Couplings		1	by	80in.
Billets		1	by	13in.
Handparts		1	by	72in.

PARTICULARS.—Heads split, and a ¾ dee sewn in each to receive spring hook in throat. Throatbands made up with a buckle in one end, and a 3in. spring hook in the other end for near side. Nosebands slide on cheek billets, no chin pieces or points. No bearing reins or throat swivels. Driving Reins: Drafts and couplings with billets ordinary style. A 5in. spring hook put on to each billet (loose). Handparts plaited or with stops sewn on. A ¾in. dee sewn in one end of handparts, and a 3in. spring hook in the other end for rapid coupling. Traces made with D-shaped draw eyes with removable screwed stems. The sway-bar hook is sewn to a leather slide piece—same as a Martingale ring for gig harness—which slides on the top hame strap and holds sway-bar and traces ready for use. Collars should be wide enough to go on easily to prevent delay in harnessing the horses. Bits: Liverpool, or any cheeked bits, must take the spring hooks easily.

SINGLE HORSE VAN HARNESS.**BRIDLE.**

Head		1¾	by	24in.
Head, split		¾	by	7in.
Front, cut		1¾	by	22in.
Front, within		13½in.		
Noseband		1¼	by	33in.
" centre		14in.		
" point		¾	by	7in.
Throatband made up		¾	by	21in.
Winker Rounding		1½	by	13in.
" " point		1	by	8in.
Cheeks, made up		1	by	9in.
Cheeks, billets		1	by	12½in.
Winkers		6¼	by	6½in.

SADDLE.

Girth		2½	by	28in.
" lay		1¼	by	11in.
" strap		1¼	by	18in.

Backband		1¾	by	105in.
" middle				48in.
" point				20in.
Shaft Tugs, cut		1¾	by	32in.
" " between holes				16in.
" " linings		1¾	by	15in.

CRUPPER.

Body		2	by	25in.
Body, split				8½in.
Body, lay		1¼	by	16in.
Strap		1¼	by	46in.
Dock		4	by	17½in.

BREECHING.

Seat		2	by	45in.
Tugs		1½	by	6in.
Placed from rings				8in.
Loin strap		2¼	by	52in.
" " split				16in.

Single Horse Van Harness (continued).**TRACES.**

Chain End and sewn
to hame ring ... $1\frac{3}{4}$ by 60in.

REINS.

Drafts ... $1\frac{1}{8}$ by 84in.
Handparts ... $1\frac{1}{8}$ by 78in.
Billets ... $1\frac{1}{8}$ by 14in.

Hame Strap (top)... $\frac{7}{8}$ by 24in.
.. .. (bottom) $\frac{7}{8}$ by 19in.

If with box-top saddle :—

Backband with chain ends.
Middle only ... $1\frac{3}{4}$ by 33in.
Girth ... $1\frac{1}{2}$ by 64in.
.. strap ... $1\frac{1}{2}$ by 27in.

PAIR-HORSE VAN HARNESS (Pole).**BRIDLES.**

Heads ... 1 by 24in.
.. safe ... $2\frac{1}{4}$ by 8in.
Throats (to go over
head) ... $1\frac{1}{8}$ by 42in.
Nosebands ... $1\frac{1}{4}$ by 33in.
.. centre... 14in.
.. point ... 1 by 7in.
Winkers ... $6\frac{5}{8}$ by $6\frac{7}{8}$ in.
Winker rounding $1\frac{1}{8}$ by 13in.
.. strap 1 by 8in.
Fronts, made up... $1\frac{3}{8}$ by 25in.
.. between head slides 15in.
.. throat slides formed at
extreme ends.

COLLARS.

No Meter Straps to Collars.

TRACES, Chain Ends.

Shoulder part ... $1\frac{3}{4}$ by 15in.
Drafts ... $1\frac{3}{4}$ by 50in.

PADS.

Surcingles, off side $2\frac{1}{2}$ by 45in.
.. near side $2\frac{1}{2}$ by 14in.
.. lays ... $1\frac{1}{4}$ by 12in.
.. straps ... $1\frac{1}{8}$ by 20in.

Bellybands ... $1\frac{1}{2}$ by 32in.
.. points ... $1\frac{1}{2}$ by 16in.

CRUPPERS.

Bodies, cut ... 3 by 42in.
.. made up ... 3 by 39in.
.. split, front only 13in.
.. lay ... $2\frac{1}{4}$ by 25in.
.. reach just long enough to
form safe for hip strap dee.

BREECHINGS.

Seats, made up ... $2\frac{1}{4}$ by 70in.
.. lays made up $1\frac{1}{8}$ by 68in.
Loin straps ... $1\frac{1}{4}$ by 44in.
Hip straps points... $1\frac{1}{8}$ by 17in.
Hip straps, brace
pieces ... $1\frac{1}{2}$ by 8in.
Tugs (8) ... $1\frac{1}{4}$ by $5\frac{1}{2}$ in.
First tug from ring 13in.
Between tugs $4\frac{1}{2}$ in.

REINS.

Made up ... $1\frac{1}{8}$ by 168in.
Couplings ... $1\frac{1}{8}$ by 80in.

Hip Straps each made with two points sewn to a ring, which is then connected to Crupper dee by a brace piece. Safes cut and fixed under rings.

HANSOM CAB HARNESS.**BRIDLE.**

Head ... $1\frac{3}{4}$ by 23in.
.. split ... 7in.
Cheeks, cut... $\frac{7}{8}$ by 30in.
.. made up ... 8in.
Front, cut ... $1\frac{1}{4}$ by 21in.
.. within ... 13in.
Throat, cut ... $\frac{7}{8}$ by 26in.

Throat, made up ... 19in.
Nose, cut ... $1\frac{1}{4}$ by 30in.
.. middle ... 12in.
.. point ... $\frac{7}{8}$ by 6in.
.. space for billets $1\frac{1}{8}$ in.
Winker stay ... $1\frac{1}{4}$ by 12in.
.. split $7\frac{1}{2}$ in.
.. point reduced to $\frac{7}{8}$ in.

Hansom Cab Harness (*continued*).**SADDLE.**

Girth		2¼	by 27in.
„ lay		1¼	by 10in.
„ long loop		1	by 9in.
Girth Strap		1¼	by 18in.

BACKBAND.

Backband		1¾	by 100in.
„ middle			41in.
„ point			18in.
Shaft Tugs, cut		1¾	by 27in.
„ between holes			13in.
„ linings			12½in.

CRUPPER.

Crupper, body		1¾	by 25in.
„ split			8in.
„ lay		1¼	by 15in.
„ strap		1¼	by 42in.
„ dock, cut		4	by 17in.

(It is an improvement to cut winker and loin-straps wider, and cut a piece out of centre of split part).

BREECHING.

Loin Strap, cut		1¾	by 52in.
„ „ split			17in.
Breeching Seat		15⁄8	by 42in.
„ tugs		7⁄8	by 5½in.
Shaft Straps		1¼	by 30in.

TRACES.

Chain ends, and			
sewn to hame rings		15⁄8	by 57in.

REINS.

Reins, drafts		1½	by 84in.
„ extra pieces		1½	by 78in.
„ handparts		1½	by 78in.
„ billets		1½	by 13in.

MARTINGALE.

Martingale, body		1¼	by 38in.
„ billet		1	by 10in.

FULL-SIZE GIG HARNESS.**BRIDLE.**

Head, cut		1½	by 23in.
„ split			6¼in.
Cheeks, cut		¾	by 30in.
„ made up			8in.
„ allow for billets			12in.
Noseband, cut		1¼	by 29in.
„ swelled centre			12in.
„ point		¾	by 6in.
„ billet spaces			1in.
Throat, cut		¾	by 27in.
„ made up			19½in.
Chain Front, lining			
cut		1½	by 21in.
„ between			13in.
Winker stay		1¾	by 12½in.
„ split			7½in.
„ rounding		1	by 13½in.
„ „ point		¾	by 6in.

HAMES AND TRACES.

Hame Tugs, cut		1½	by 18in.
„ „ made up			9in.
„ „ safes to pattern			12in.
Hame strap (top)		¾	by 19in.
„ „ (bottom)		¾	by 18in.
Traces, made up		1½	by 72in.

SADDLE.

Girth, cut		2¼	by 27in.
„ short lay		1½	by 11in.
Girth, large loop		1	by 8in.
Girth strap		1½	by 18in.

BACKBAND.

Backband		1½	by 96in.
„ point			18in.
„ middle			39in.
Shaft Tugs, cut		1½	by 24in.
Shaft Tugs, between holes			12in.
Shaft Tugs, linings			12in.

Full-Size Gig Harness (*continued*).**CRUPPER.**

Body		1½ by 23in.
" split		8in.
Lay		1⅞ by 15in.
Strap		1⅞ by 42in.
Dock		3¾ by 18in.

BREECHING.

Seat		1½ by 42in.
Tugs (4)		¾ by 5in.
Tugs placed from ends		6in.
Shaft Straps		1⅞ by 32in.
Hip Strap		1½ by 52in.
" "	split	17in.

KICKING STRAP.

For two wheeler		1¼ by 66in.
For four wheeler		1¼ by 74in.
Tugs		1¼ by 14in.

REINS.

Driving Reins, drafts	1	by 78in.
" handparts	1	by 72in.
" billets	1	by 13in.
Bearing Rein,		
middle		¾ by 78in.
Bearing Rein, round-		
ing cut	... 1	by 23in.
" made up		18in.
Bearing Rein, billets	¾	by 10½in.

SHORT MARTINGALE.

Body, cut		1 by 36in.
" made up		1 by 24in.
Billet		1 by 14in.

LONG MARTINGALE.

Rounding, cut	... 1	by 24in.
" made up		22in.
Body		1 by 39in.
Patchpiece to pattern.		

COB-SIZE GIG HARNESS.**BRIDLE.**

Head, cut		1½ by 21½in.
" split		5¾in.
Cheeks, cut		¾ by 28in.
" made up		7in.
" billets		12in.
Noseband, cut		1⅞ by 27in.
" swelled centre		11in.
" point	... ¾	by 5½in.
" billet spaces		1in.
Chain Front, lining		
cut		1⅞ by 20in.
Chain Front, between		12in.
Winker Stay		1¼ by 11½in.
" "	split	6¾in.
Winker, rounding...	1	by 12in.
" " point	¾	by 5½in.
Throat, cut		¾ by 26in.
" made up		18½in.

HAMES AND TRACES.

Hame Tugs, cut		1¾ by 16in.
" " made up		8in.
" " safes to pattern		11in.
Hame Strap (top)...	¾	by 18in.
" " (bottom)	¾	by 17in.
Traces, made up		1¾ by 66in.

SADDLE.

Girth, cut		2 by 24in.
" short lay		1 by 10in.
Girth, large loop...	⅞	by 6½in.
Girth Strap...	... 1	by 17in.

BACKBAND.

Backband		1¾ by 90in.
" point		17in.
" middle		36in.
Shaft Tugs, cut		1¾ by 23in.
" " between holes		11½in.
" " linings		11¼in.

CRUPPER.

Body		1½ by 21½in.
" split		7in.
Lay		1 by 14in.
Strap		1 by 39in.
Dock		3½ by 17in.

BREECHING.

Seat		1¾ by 39in.
Tugs (4)		¾ by 5in.
" placed upon ends		5½in.
Shaft Straps		1 by 30in.
Hip Strap		1½ by 48in.
" " split		16in.

Cob-Size Gig Harness (*continued*).**KICKING STRAP.**

For two wheeler ... $1\frac{1}{8}$ by 60in.
 For four wheeler... $1\frac{1}{8}$ by 68in.
 Tugs $1\frac{1}{8}$ by 13in.

REINS.

Driving Reins, drafts $\frac{7}{8}$ by 72in.
 „ handparts $\frac{7}{8}$ by 66in.
 „ billets $\frac{7}{8}$ by 12in.
 Bearing Rein, middle $\frac{3}{4}$ by 69in.
 Bearing Rein, round-
 ings, cut ... 1 by $21\frac{1}{2}$ in.
 „ made up ... 17in.
 Bearing Rein, billets $\frac{3}{4}$ by 10in.

SHORT MARTINGALE.

Body, cut $\frac{7}{8}$ by 35in.
 „ made up ... $\frac{7}{8}$ by 21in.
 Billet $\frac{7}{8}$ by 13in.

LONG MARTINGALE.

Rounding cut ... 1 by 22in.
 „ made up ... 20in.
 Body $\frac{7}{8}$ by 36in.
 Patchpiece to pattern.

PONY-SIZE GIG HARNESS.**BRIDLE.**

Head, cut $1\frac{1}{4}$ by 20in.
 „ split $5\frac{1}{4}$ in.
 Cheeks, cut $\frac{5}{8}$ by 25in.
 „ made up ... 6in.
 „ billets 11in.
 Noseband, cut ... 1 by 25in.
 „ swelled centre 10in.
 „ point ... $\frac{5}{8}$ by 5in.
 „ billet spaces $\frac{7}{8}$ in.
 Throat, cut $\frac{5}{8}$ by 25in.
 „ made up ... $17\frac{1}{2}$ in.
 Chain Front, lining
 cut 1 by 19in.
 Chain Front, between 11in.
 Winker Stay $1\frac{1}{8}$ by $10\frac{1}{2}$ in.
 „ „ split $6\frac{1}{4}$ in.
 Winker rounding $\frac{7}{8}$ by $10\frac{1}{2}$ in.
 „ rounding point $\frac{5}{8}$ by 5in.

HAMES AND TRACES.

Hame Tugs, cut ... $1\frac{1}{4}$ by 14in.
 „ „ made up 7in.
 „ „ safes to pattern 10in.
 Hame Strap (top)... $\frac{5}{8}$ by 17in.
 „ „ (bottom) $\frac{5}{8}$ by 16in.
 Traces, made up ... $1\frac{1}{4}$ by 63in.

SADDLE.

Girth, cut $1\frac{7}{8}$ by 22in.
 Girth, short lay ... $\frac{7}{8}$ by 9in.
 „ large loop ... $\frac{3}{4}$ by 6in.
 „ Strap $\frac{7}{8}$ by 16in.

BACKBAND.

Backband $1\frac{1}{4}$ by 84in.
 „ point 16in.
 „ middle ... 34in.
 Shaft Tugs, cut ... $1\frac{1}{4}$ by 22in.
 „ „ between holes 11in.
 „ „ linings $10\frac{1}{2}$ in.

CRUPPER.

Body $1\frac{1}{4}$ by 20in.
 „ split 6in.
 Lay $\frac{7}{8}$ by 13in.
 Strap $\frac{7}{8}$ by 36in.
 Dock... ... $3\frac{1}{4}$ by 16in.

BREECHING.

Seat $1\frac{1}{4}$ by 36in.
 Tugs (4) $\frac{5}{8}$ by $4\frac{1}{2}$ in.
 Tugs placed from ends 5in.
 Shaft Straps $\frac{7}{8}$ by 28in.
 Hip Strap $1\frac{1}{4}$ by 44in.
 „ „ split ... 15in.

Pony-Size Gig Harness (*continued*).**KICKING STRAP.**

For two wheeler ...	1	by 54in.
For four wheeler ...	1	by 62in.
Tugs ...	1	by 12in.

REINS.

Driving Reins, drafts	$\frac{3}{4}$	by 66in.
„ handparts	$\frac{3}{4}$	by 60in.
„ billets	$\frac{3}{4}$	by 11in.
Bearing Rein, middle	$\frac{5}{8}$	by 60in.
Bearing Rein, round-		
ings, cut ...	$\frac{7}{8}$	by 20in.
„ made up ...		16in.
Bearing Rein, billets	$\frac{5}{8}$	by 9 $\frac{1}{2}$ in.

SHORT MARTINGALE.

Body, cut ...	$\frac{3}{4}$	by 30in.
„ made up ...	$\frac{3}{4}$	by 18in.
Billets ...	$\frac{3}{4}$	by 12in.

LONG MARTINGALE.

Rounding, cut ...	$\frac{7}{8}$	by 20in.
„ made up ...		18in.
Body ...	$\frac{3}{4}$	by 34in.
Patchpiece to pattern.		

BACKBANDS, BREECHINGS, &c., FOR GIG HARNESS.**FULL-SIZE.****BACKBANDS** (Various).

French, centre ...	$1\frac{1}{2}$	by 39in.
„ points sewn on tugs ...	$1\frac{1}{2}$	by 24in.
Tilbury, full length ...	$1\frac{1}{2}$	by 105in.
„ with two points ...	$1\frac{1}{2}$	by 90in.
„ each point ...		18in.
„ centre ...		34in.
„ reversed sewing each side of centre		13in.
Bellyband, for either French or Til-		
bury backband ...	$1\frac{1}{2}$	by 28in.
False backband for 2 wheeler, middle	$1\frac{1}{2}$	by 26in.
„ „ „ „ billets (2)	$1\frac{1}{2}$	by 24in.
False bellyband for 2 wheeler, middle	$1\frac{1}{2}$	by 32in.
„ „ „ „ billets ...	$1\frac{1}{2}$	by 24in.

BREECHINGS (Various).

Buckle Seat, cut ...	$1\frac{1}{2}$	by 36in.
„ „ lay ...	$1\frac{1}{8}$	by 36in.
„ „ between buckles ...		32in.
Ring points, made up ...	$1\frac{1}{8}$	by 9in.
Long Breeching ...	$1\frac{3}{8}$	by 126in.
„ „ reduced for turnback to		1in.
Crupper, Martingale style ...	$1\frac{1}{2}$	by 50in.
„ „ reduced for turnback to		1in.

BREAST COLLAR.

Body (folded leather) ...	$2\frac{1}{2}$	by 39in.
lay ...	$1\frac{1}{2}$	by 39in.
„ between buckles ...		33in.
Neck Strap ...	$1\frac{3}{4}$	by 40in.
„ „ reduced at points to ...		1in.

Backbands, Breechings, &c., for Gig Harness (continued.)**COB SIZE.****BACKBANDS (Various).**

French, centre	1 $\frac{3}{8}$	by	36in.
„ points sewn on tugs	1 $\frac{3}{8}$	by	21in.
Tilbury, full length	1 $\frac{3}{8}$	by	99in.
„ with two points	1 $\frac{3}{8}$	by	87in.
„ each point			17in.
„ centre			32in.
„ reversed sewing each side of centre			12in.
Bellyband for either French or Tilbury	1 $\frac{3}{8}$	by	26in.
False backband for two wheeler,			
middle	1 $\frac{3}{8}$	by	23in.
False backband for two wheeler,			
billets	1 $\frac{3}{8}$	by	22in.
False bellyband for two wheeler,			
middle	1 $\frac{3}{8}$	by	29in.
False bellyband for two wheeler,			
billets	1 $\frac{3}{8}$	by	22in.

BREECHINGS (Various).

Buckle Seat, cut	1 $\frac{3}{8}$	by	33in.
„ „ lay	1	by	33in.
„ „ between buckles			29in.
Ring points, made up	1	by	8in.
Long Breeching	1 $\frac{1}{4}$	by	114in.
„ „ reduced for turnback to			1in.
Crupper, Martingale style	1 $\frac{3}{8}$	by	44in.
„ reduced for turnback to... ..			1in.

BREAST COLLAR.

Body (folded leather)	2 $\frac{1}{4}$	by	33in.
Lay	1 $\frac{3}{8}$	by	33in.
„ between buckles			27in.
Neck Strap	1 $\frac{1}{2}$	by	34in.
Reduced at point to			$\frac{7}{8}$ in.

PONY SIZE.**BACKBANDS (Various).**

French, centre	1 $\frac{1}{4}$	by	33in.
„ points sewn on tugs	1 $\frac{1}{4}$	by	18in.
Tilbury, full length	1 $\frac{1}{4}$	by	93in.
„ with two points	1 $\frac{1}{4}$	by	84in.
„ each point			16in.
„ centre			30in.
„ reversed sewing each side of centre			11in.
Bellyband, for either French or Tilbury...	1 $\frac{1}{4}$	by	24in.
False backband for two wheeler, middle...	1 $\frac{1}{4}$	by	20in.
„ „ „ „ billets ...	1 $\frac{1}{4}$	by	20in.
False bellyband for two wheeler, middle	1 $\frac{1}{4}$	by	26in.
„ „ „ „ billets ...	1 $\frac{1}{4}$	by	20in.

Backbands, Breechings, &c., for Gig Harness (*continued.*)**BREECHINGS.**

Buckle Seat, cut	...	...	...	...	1¼	by	30in.
" "	lay	...	...	...	7⁄8	by	30in.
" "	between buckles	...	...	...			26in.
Ring points, made up	...	...	...	...	7⁄8	by	7in
Long Breeching	...	...	...	...	1½	by	102in
" "	reduced for turnback to	...	...	...			7⁄8in.
Crupper, Martingale style	...	...	...	...	1¼	by	38in.
" "	reduced for turnback to	...	...	...			7⁄8in.

BREAST COLLAR.

Body (folded leather)	...	...	...	...	2	by	27in.
Lay	...	...	...	...	1¼	by	27in.
" "	between buckles	...	...	...			21in.
Neck Strap	...	...	...	...	1¼	by	28in.
" "	reduced points to	...	...	...			¾in.

PAIR-HORSE HARNESS.**FULL-SIZE.****BRIDLES as Gig.****HAMES AND TRACES.**

Hame Tugs, made up	...	...	...	1½	by	18in.
Hame Tugs, safes to pattern	...	...	...			21in.
Short Tugs, to hame tug buckles	...	...	...	1½	by	5in.
Hame Straps (top only)	...	...	...	¾	by	22in.
Traces	...	...	...	1½	by	78in.
" hand leather	...	...	...	1½	by	5in.
Pole pieces	...	...	...	1½	by	60in.

PADS.

Tops to pattern.						
Girths, near side	...	...	...	2¼	by	15in.
" off side	...	...	...	2¼	by	42in.
" points...	...	...	...	1½	by	18in.
Pad End Straps	...	...	...	1½	by	9in.

CRUPPERS, same as Gig.

Loin Straps	...	...	...	1	by	50in.
Trace Carriers, cut	...	...	...	1	by	14in.
Patent Leather to pattern.						

BREECHINGS.

Breechings, cut	...	...	...	1¾	by	132in.
Breechings reduced at buckles to	...	...	...	1½in.		

REINS.

Driving Reins, each side	...	...	...	1	by	168in.
" couplings	...	...	...	1	by	80in.
" billets	...	...	...	1	by	14in.
Bearing Rein, full bradoon, middle	...	...	...	¾	by	72in.
" roundings, cut	...	...	...	1	by	31in.
" " made up	...	...	...			24in.

MARTINGALES.

Body, cut	...	...	...	1	by	36in.
" made up	...	...	...	1	by	24in.
Billets	...	...	...	1	by	14in.

COB SIZE.**BRIDLES as Gig.****HAMES AND TRACES.**

Hame Tugs, made up	...	...	...	1¾	by	16in.
Hame Tugs, safes to pattern	...	...	...			19in.
Short Tugs, sewn to hame tug buckles	...	...	...	1	by	4½in.
Hame Straps (top only)	...	...	...	¾	by	21in.
Traces, made up	...	...	...	1¾	by	75in.
" hand leather	...	...	...	1¾	by	5in.
Pole pieces	...	...	...	1¾	by	57in.

Pair-Horse Harness (continued).**Cob Size (continued.)****PADS.**

Tops to pattern.	
Girths, near side ... 2	by 13in.
„ off side ... 2	by 39in.
Girth point ... 1	by 17in.
Pad End Straps ... 1	by 9in

CRUPPERS, same as Gig.

Loin Straps ... 1	by 48in
-------------------	---------

Trace Carriers, cut 1	by 13in.
-----------------------	----------

Patent Leather to pattern.

BREECHINGS.

Breechings, cut ... 1¼	by 120in.
------------------------	-----------

Breechings, reduced at buckles to ...	1in.
--	------

REINS.

Driving Reins, each side	1	by 162in.
„ couplings	1	by 78in.
„ billets	1	by 13in.
Bearing Rein, full bradoon, middle	¾	by 69in.
„ roundings, cut	1	by 28in.
„ „ made up		21in.

MARTINGALES.

Body, cut ...	¾	by 33in.
„ made up ...	¾	by 21in.
Billets ...	¾	by 13in.

PONY SIZE.

BRIDLES, as Gig.

HAMES AND TRACES.

Hame Tugs, made up ...	1¼	by 14in.
„ „ safes to pattern ...		17in.
Short Tugs, sewn to hame tug buckles ...	¾	by 4in.
Hame Straps (top only) ...	5/8	by 20in.
Traces, made up ...	1¼	by 72in
„ hand leather ...	1¼	by 4½in.
Pole pieces ...	1¼	by 54in.

PADS.

Girths, near side	...	...	...	...	1¾	by	11in.
„ off side	...	...	...	...	1¾	by	36in.
Girth points	...	...	...	...	¾	by	16in.
Pad-end Straps	...	...	...	...	¾	by	8in.

CRUPPERS, same as Gig.

Loin Straps ...	¾	by 46in.
-----------------	---	----------

Trace Carriers, cut ...	¾	by 12in.
-------------------------	---	----------

Patent leather to pattern.

BREECHINGS.

Breechings, cut ...	1½	by 108in.
„ reduced at buckles to ...	¾	

REINS.

Driving Reins, each side ...	¾	by 156in.
„ couplings ...	¾	by 75in.
„ billets ...	¾	by 12in.
Bearing Rein, full bradoon, middle ...	5/8	by 66in.
„ „ roundings, cut ...	¾	by 25in.
„ „ „ made up		18in.

MARTINGALES.

Body, cut ...	¾	by 30in.
„ made up ...	¾	by 18in.
„ billets ...	¾	by 12in.

THREE-HORSE BUS HARNESS (for Horses to Run Abreast).

Bridles as ordinary Van Harness.

Breechbands 10ft. long altogether by $1\frac{3}{4}$ in. wide, spliced in the centre, lined in the middle from 3ft. 3in. to 4ft. From each end of Breechband tapered 16in. to $1\frac{1}{2}$ in.

Buckle-pieces for Loin Straps made up, $4\frac{1}{2}$ in. by $1\frac{1}{4}$ in.

Put in body of Breechband 18in. each way from centre of Breechband.

Hip Straps, 4ft. 6in. long by $1\frac{1}{4}$ in.

Cross Straps to go from Hip Strap Pad to Hame Ring at Draft, 4ft. long by $\frac{3}{4}$ in. wide. Billet on Cross Straps, front end, 15in. long. Back end of Cross Strap turned back to form a loop for Hip Strap to run through.

Pad for top of hips (for Loin Strap to run through, and Cross Straps to Hame Ring), 10in. long by $2\frac{1}{4}$ in. wide, made of fair strength of leather; a loop sewn on either end of Hip Strap to run through. Make a pad of $\frac{1}{4}$ in. felt, covered with soft black leather or basil, and sew under the leather pad with loops on. Sew Hip Strap 1 row across in the centre to hold the pad in its place, and it leaves the ends loose to run the loops of the Cross Straps on the Loin Straps.

HAMES AND TRACES.

Ring on the Draft of Hames.

From Ring to Square, double leather 18in. long by 2in. wide.

Square, 2in. wide (inside) by 4in. long (inside). Bar across centre with tong to form a buckle to take the Breechband. Two loops on Hame Tug to take point of Breechband.

Back ends of Traces from Square to Chain, 3ft. 10in. long, made up, by $2\frac{1}{4}$ in. or $2\frac{1}{2}$ in. broad. Single Traces tapered at each end to fit on Square and Chain.

TANDEM HARNESS.

WHEELER.—Same as Gig Harness.

LEADER.

Bridle, Crupper, etc., as Gig Harness.

Traces, full size	...	...	$1\frac{1}{2}$	by 120in.
„ cob size	...	...	$1\frac{3}{8}$	by 114in.
„ pony size	...	...	$1\frac{1}{4}$	by 108in.
Reins, full size	...	...	1	by 288in. each side.
„ cob size	...	...	$\frac{7}{8}$	by 276in. „
„ pony size	...	...	$\frac{3}{4}$	by 264in. „

FOUR-IN-HAND HARNESS.

WHEELER.—Same as Pair-Horse Harness.

LEADER.

Traces $1\frac{1}{2}$ by 66in.

Reins : Drafts, couplings, and billets as Wheeler.

Handparts, extra lengths added to make up to 24in. each side.

FUNERAL CARRIAGE HARNESS.**WHEELER.****BRIDLE.**

Ordinary carriage, with the exception of a safe to the head. This is cut 7 inches long by 5 inches wide. The two corners of one side are well rounded off—this part comes to the back of the head—the straight edge of the safe being placed in a line with the head about half an inch in front. Check Rein : $\frac{5}{8}$ in. wide by 30in. long. Billet each end, $\frac{5}{8}$ in. by 8in.

BREAST COLLAR

Body, 60in. by 5in., lined for safes at each end only, 12in. Layer, 34in. by $1\frac{3}{4}$ in. (if for $1\frac{3}{4}$ in. traces). Polestrap dee placed 3in. from centre of collar. In making the collars see that this dee is placed on the pole side of each, or they will not be a pair of collars. Tugs for wither strap made up $5\frac{1}{2}$ in. by $1\frac{1}{4}$ in. and placed 9in. from the heel of each trace buckle. If box loops are to be used, cut these $6\frac{3}{4}$ in. by $5\frac{1}{4}$ in. Wither strap cut 44in. by $1\frac{1}{4}$ in., wither strap safe 25in. by $2\frac{1}{2}$ in. Polestraps, 60in. by $1\frac{3}{4}$ in. See following sketch for method of letting in rein dees.

PADS (Ordinary Carriage).

With pad leathers 24in. by $6\frac{1}{2}$ in., if with two rows of beading. Short tugs and point straps same as for ordinary carriage harness. Girths, near side, 16in. by $2\frac{1}{4}$ in. ; off side, 44in. by $2\frac{1}{4}$ in. ; strap, 18in. by $1\frac{1}{8}$ in.

BREECHING.

Long Breeching, 120in. by $2\frac{1}{4}$ in. Five feet of the centre part is left the full width, then tapered off towards each end to $1\frac{5}{8}$ in. Breeching Tugs 30in. between at the seat, and 4in. between at the sides. Loin strap and crupper (ordinary).

TRACES (with loop ends).

These are cut $1\frac{3}{4}$ in. by 93in., then when they are turned and the loop is formed should measure 78in. from point to end of loop.

REINS.

Drafts 84in. by 1in., couplings 78in. by 1in., handparts 84in. by 1in., billets 14in. by 1in.

Funeral Carriage Harness (continued).**LEADER.**

Bridles, wither straps, and breast collars same as Wheeler, with the exception that there are no pole-dees inserted in the latter.

Traces with cock eyes, $1\frac{1}{2}$ in. by 70 in.

Loan Strap, 52 in. by $1\frac{1}{4}$ in. Trace bearers, cut 17 in. by $1\frac{1}{4}$ in.

Reins: Drafts, couplings, and billets as above. Extra strips added to make up to 25 ft. each side.

AMERICAN PAIR-HORSE HARNESS.**BRIDLE.**

Crown pieces	... 1 $\frac{3}{8}$	by 23 in.
„ „ split	... $\frac{5}{8}$	by 7 in.
„ „ layers	... $\frac{5}{8}$	by 9 in.
Cheeks, cut	... $\frac{5}{8}$	by 29 in.
„ made up	...	8 in.
Nosebands, cut	... $1\frac{1}{4}$	by 30 in.
„ middle	...	12 $\frac{1}{2}$ in.
„ point	... $\frac{5}{8}$	by $5\frac{1}{2}$ in.
„ buckle piece	... $\frac{5}{8}$	by 9 in.
„ billet spaces	...	$\frac{7}{8}$ in.
Winkers (square)	... $5\frac{1}{2}$	by $6\frac{1}{4}$ in.
Throatbands	... $\frac{5}{8}$	by 26 in.
Checks or bearing-		
rein roundings	... $\frac{3}{4}$	by 22 in.
Centre parts	... $\frac{3}{4}$	by 60 in.
Fronts made up	... $1\frac{1}{4}$	by 13 in.
Winker braces	... $1\frac{1}{8}$	by $13\frac{1}{2}$ in.
„ split	... $\frac{1}{2}$	by 8 in.
„ point	... $\frac{5}{8}$	by $5\frac{1}{2}$ in.

HAMES AND TRACES.

Hame Tugs, made		
up	... $1\frac{1}{4}$	by 17 in.
Hame Tug Safes—		
	$1\frac{3}{4}$ & $2\frac{3}{4}$	by $20\frac{1}{2}$ in.
Hame Strap (top)	... $\frac{3}{4}$	by 26 in.
Traces	... $1\frac{1}{4}$	by 82 in.

PADS.

Pad Tops	... $2\frac{1}{2}$	by 17 in.
Housings	... $5\frac{3}{4}$	by $20\frac{1}{2}$ in.
Pad Sides	... $2\frac{1}{8}$	by 25 in.
Pad Points	... $\frac{7}{8}$	by 10 in.
Market Straps	... 1	by 20 in.
Market Tugs	... 1	by 20 in.

CRUPPERS.

Crupper Points	... $\frac{5}{8}$	by $7\frac{1}{2}$ in.
Docks	... $4\frac{3}{4}$	by 18 in.

BELLYBANDS.

Short layers	... $\frac{7}{8}$	by $23\frac{1}{2}$ in.
Bodies	... $1\frac{1}{2}$	by 17 in.
Long Layers	... $\frac{7}{8}$	by 35 in.
Bodies	... $1\frac{3}{8}$	by 20 in.

MARTINGALES.

Martingales	... $\frac{7}{8}$	by 27 in.
Turnbacks	... $\frac{7}{8}$	by 34 in.
„ bodies	... $1\frac{7}{8}$	by 19 in.

REINS.

Short Reins	... $1\frac{1}{8}$	by 82 in.
Long Reins	... $1\frac{1}{8}$	by 84 in.

AMERICAN BUGGY HARNESS.**BRIDLE.**

Head	... $1\frac{1}{4}$	by 23 in.
„ split	... $\frac{1}{2}$	by 7 in.
Cheeks, cut	... $\frac{1}{2}$	by 28 in.
„ made up	...	$7\frac{3}{4}$ in.
Front between	... $\frac{5}{8}$	by $12\frac{1}{2}$ in.
Throat	... $\frac{1}{2}$	by 20 in.
Winker Stay	... 1	by 12 in.
„ „ split	... $\frac{3}{8}$	by 7 in.

BRIDLE (continued).

Winker Stay, billet	$\frac{1}{2}$	by 5 in.
Overcheck	... 1	by 30 in.
„ split	... $\frac{1}{2}$	by 10 in.
„ point	...	$\frac{1}{2}$ in.
„ nose piece	$\frac{3}{8}$	by 9 in.
„ check rein	$\frac{1}{2}$	by 30 in.
„ billets	... $\frac{1}{2}$	by $6\frac{1}{2}$ in.

American Buggy Harness (continued).**BREAST COLLAR.**

Body	...	2	by	36in.
Neck Strap	...	1¼	by	38in.
"	"	points		5½in.
"	"	tugs cut	5/8	by 7in.
Traces	...	1	by	84in.
"	"	lap on breast collar		12in.

SADDLE.

Tree	...			3in.
Skirts	...	2½	by	3in.
Jockeys	...	2¾	by	4½in.
Flaps	...	2½	by	22in.
Backband	points...	7/8	by	20in.
Tugs, cut	...	7/8	by	20in.
"	"	between holes		9in.
Bellyband (Griffiths)		1¾	by	18in.
"	"	billets		7/8 by 26in.

CRUPPER.

Turn back style	...	1¼	by	44in.
Body	...	1¼	by	20in.
"	"	split	5/8	by 8in.
Turn back reduced				
to	...	5/8		
Dock	...	3½	by	14in.

BREECHING.

Body	...	2	by	38in.
"	"	layers cut	1½	by 14in.
"	"	rounds cut	7/8	by 12in.
"	"	from D to end		6½in.
Shaft Straps	...	¾	by	30in.
Hip Straps	...	¾	by	43in.
"	"	tugs cut	5/8	by 7in.

REINS.

Drafts	...	7/8	by	78in.
Handparts	...	1	by	72in.

DONKEY HARNESS.**BRIDLE.**

Head, cut	...	1¼	by	19in.
Head, split	...	5/8	by	5in.
Cheeks, cut	...	5/8	by	26in.
Cheeks, made up				6in.
Front, cut	...	1	by	18in.
Front, within	...			12in.
Throat Band, cut	5/8	by	18in.	
Throat Band, made up				14in.
Noseband, cut	...	1	by	23in.
"	"	middle		10in.
"	"	point	5/8	by 5in.
Flat Winker Stay,				
cut	...	1	by	11in.
"	"	split	½	by 6½in.
"	"	point	¾	by 4½in.
Rounded Winker				
Stay, cut	...	7/8	by	10in.
"	"	point	5/8	by 5in.

HAMES AND TRACES.

Hame Tugs	...	1½	by	7in.
Hame Strap (top)	5/8	by	18in.	
Hame Strap (bottom)	5/8	by	15in.	
Traces	...	1½	by	51in.

BREAST COLLAR.

Body	...	1¾	by	24in.
Lay	...	1½	by	24in.

BREAST COLLAR (continued).

Between buckles				17in.
Neck Strap	...	1	by	27in.
(Reduced at points to 5/8).				
Tugs	...	5/8	by	4in.

SADDLE.

Girth	...	1¾	by	16in.
"	"	Lay	¾	by 6in.
"	"	Strap	¾	by 15in.
Backband	...	1½	by	72in.
Backband, middle	...			30in.
"	"	point		16in.
Shaft Tugs, cut	...	1½	by	21in.
"	"	between holes		10½in.
"	"	linings		10½in.

CRUPPER.

Crupper Body, cut	1¼	by	18in.	
"	"	Split	5/8	by 6½in.
"	"	Lay	¾	by 11in.
Crupper Strap	...	¾	by	36in.

BREECHING.

Breeching Seat	...	1½	by	28in.
"	"	Tugs	5/8	by 4in.
Loin Straps	...	1¼	by	34in.
"	"	Split		12in.
Shaft Straps	...	¾	by	24in.

Donkey Harness (continued).**KICKING STRAP.**

Kicking Strap for
 two wheeler ... $\frac{7}{8}$ by 52in
 Kicking Strap for
 four wheeler ... $\frac{7}{8}$ by 60in.
 Kicking Strap Tugs $\frac{7}{8}$ by 12in.

REINS.

Drafts ... $\frac{3}{4}$ by 66in.
 Hand-parts ... $\frac{3}{4}$ by 54in
 Billets ... $\frac{3}{4}$ by 11in.

DONKEY CART SADDLE AND BREECHING.

Bellyband, made up ... $1\frac{1}{4}$ by 36in.
 „ Strap, made up ... $1\frac{1}{4}$ by 21in.
 „ and Strap attached by short sidestring to tree.
 Back Girth (nailed on hind corner of tree to go round back part
 of body), 45in. long.
 Strap for same, 17in. long.
 Breeching Body, made up, about ... $1\frac{1}{2}$ by 36in.
 Crupper „ „ „ ... $1\frac{1}{2}$ by 14in.
 Loose loin and hip-straps, made up, about $\frac{7}{8}$ by 26in.
 Tugs for same, made up, about ... $\frac{7}{8}$ by 5in.

FULL-SIZE GOAT HARNESS.**BRIDLE.**

Winkers D pattern, $2\frac{3}{8}$ in. deep, 3in. wide. Head $\frac{5}{8}$ in. wide, 13in. long. Cheeks, made cart bridle style, $\frac{5}{8}$ in. wide, $5\frac{1}{2}$ in. long. Ring or dee at bottom—spaces left 1in. from ring for nosepiece to slide through. Front, throat and point as cart bridle, cut in one piece, $\frac{5}{8}$ in. by 22in. Noseband, to slide through cheeks, $\frac{5}{8}$ in. by 15in.

BREAST COLLAR AND TRACES.

Body, $1\frac{1}{2}$ in. by 20in. ; Lay, 1in. by 18in. ; between buckles, 13in. Neck-strap buckles inserted just behind trace buckles. Neck-strap, $\frac{5}{8}$ in. by 16in. Traces (single leather), 1in. by 36in.

PAD LEATHER AND CRUPPER.

Leather cut 2in. by 22in. Two $1\frac{1}{8}$ in. dees stitched on for reins, and one $\frac{3}{4}$ in. dee for crupper strap. Backband slides under loops holding rein dees. Girth, $1\frac{1}{2}$ in. by 14in. Strap, $\frac{3}{4}$ in. by 10in. Backband, 1in. by 45in. Tugs (single leather) cut, 1in. by 12in., spliced 4in. long, with buckle in centre. Crupper body, 1in. by 10in., split 4in. Strap and lay in one, $\frac{5}{8}$ in. by 28in. Hip Strap, $1\frac{1}{4}$ in. by 24in., split 7in.

BREECHING.

Breeching, 1in. by 18in. Tugs, $\frac{5}{8}$ in. by 3in. Back Tugs placed 3in. from rings. Breeching Straps, $\frac{5}{8}$ in. by 14in.

REINS.

Leading Rein $\frac{5}{8}$ in. by 30in., hand-loop at one end, 6in. billet at the other end. Driving Reins, $\frac{5}{8}$ in. by 13ft., full length. Billets, $\frac{5}{8}$ in. by 7in.

COLLAR FORE WALES.

	ins.	by	ins.	and twice the proposed depth of Collar			
Pony ...	4	by	10½				
Gig ...	4¼	by	11	„	„	„	„
Carriage ...	4½	by	11½	„	„	„	„
Cab ...	4½	by	11½	„	„	„	„
Stage ...	4¾	by	12	„	„	„	„
Van ...	5	by	12	„	„	„	„
Van (heavy) ...	5½	by	13	„	„	„	„
Cart ...	6	by	13	„	„	„	„

When possible to cut cart forewales wider they are decidedly better for sewing on the afterwales.

RIDING BRIDLES.

SNAFFLE.

	Full Size.	Cob Size.	Pony Size.
	Inches.	Inches.	Inches.
Head, cut ...	1¾ by 42	1¼ by 40	1 by 38
„ split, near side	⅞ by ½ by 8	¾ by ½ by 7½	⅝ by ⅜ by 7
„ „ off side	⅞ by ½ by 24	¾ by ½ by 23	⅝ by ⅜ by 22
„ length between points	26	24½	23
Cheeks, to sew on, cut...	⅞ by 15	¾ by 14	⅝ by 13
„ „ „ made up	11	10	9
„ billeted, cut ...	⅞ by 11½	¾ by 10½	⅝ by 9½
„ „ between buckles	9	8	7
„ billets ...	⅞ by 8	¾ by 8	⅝ by 7½
Reins ...	1⅞ by 50	1 by 48	⅞ by 46
„ billets ...	1⅞ by 8	1 by 8	⅞ by 7½
Front, cut ...	⅞ by 19½	¾ by 18½	⅝ by 17
„ made up ...	14	13	12

PELHAM.

	Full Size.	Cob Size.	Pony Size.
	Inches.	Inches.	Inches.
Head, cut ...	1¾ by 42	1¼ by 40	1 by 38
„ split, near side	⅞ by ½ by 8	¾ by ½ by 7½	⅝ by ⅜ by 7
„ „ off side	⅞ by ½ by 24	¾ by ½ by 23	⅝ by ⅜ by 22
„ length between points	26	24½	23
Cheeks, to sew on, cut...	⅞ by 15	¾ by 14	⅝ by 13
„ „ „ made up	11	10	9
„ billeted, cut ...	⅞ by 11½	¾ by 10½	⅝ by 9½
„ „ between buckles	9	8	7
„ billets ...	⅞ by 8	¾ by 8	⅝ by 7½
Reins ...	1 by 52	⅞ by 50	¾ by 48
„ „ „	⅞ by 48	¾ by 46	⅝ by 44
„ billets ...	8	8	7½
Front, cut ...	⅞ by 19½	¾ by 18½	⅝ by 17
„ made up ...	14	13	12

Riding Bridles (continued).**WEYMOUTH.**

	Full Size.	Cob Size.	Pony Size.
	Inches.	Inches.	Inches.
Head, cut	1 $\frac{3}{8}$ by 42	1 $\frac{1}{4}$ by 40	1 by 38
„ split, near side	$\frac{7}{8}$ by $\frac{1}{2}$ by 8	$\frac{3}{4}$ by $\frac{1}{2}$ by 7 $\frac{1}{2}$	$\frac{5}{8}$ by $\frac{3}{8}$ by 7
„ „ off side	$\frac{7}{8}$ by $\frac{1}{2}$ by 24	$\frac{3}{4}$ by $\frac{1}{2}$ by 23	$\frac{5}{8}$ by $\frac{3}{8}$ by 22
„ length between points	26	24 $\frac{1}{2}$	23
Cheeks (3) to sew on, cut	$\frac{7}{8}$ by 15	$\frac{3}{4}$ by 14	$\frac{5}{8}$ by 13
„ „ „ made up	11	10	9
„ billeted, cut ...	$\frac{7}{8}$ by 11 $\frac{1}{2}$	$\frac{3}{4}$ by 10 $\frac{1}{2}$	$\frac{5}{8}$ by 9 $\frac{1}{2}$
„ between buckles ...	9	8	7
„ billets	$\frac{7}{8}$ by 8	$\frac{3}{4}$ by 8	$\frac{5}{8}$ by 7 $\frac{1}{2}$
Sliding head	$\frac{7}{8}$ by 32	$\frac{3}{4}$ by 30	$\frac{5}{8}$ by 28
Reins	1 by 52	$\frac{7}{8}$ by 50	$\frac{3}{4}$ by 48
„ „ „ „	$\frac{7}{8}$ by 48	$\frac{3}{4}$ by 46	$\frac{5}{8}$ by 44
„ billets	8	8	7 $\frac{1}{2}$
Front, cut	$\frac{7}{8}$ by 19 $\frac{1}{2}$	$\frac{3}{4}$ by 18 $\frac{1}{2}$	$\frac{5}{8}$ by 17
„ made up	14	13	12

STEEPLECHASE BRIDLES, Etc.

Head, cut	1 $\frac{3}{8}$ by	42in. ...	1 $\frac{1}{4}$ by	42in.
„ split, near side ...	$\frac{7}{8}$ by	7 $\frac{1}{2}$ in. ...	$\frac{3}{4}$ by	7 $\frac{1}{2}$ in.
„ „ off side ...	$\frac{7}{8}$ by	24in. ...	$\frac{3}{4}$ by	24in.
„ length between points		26in. ...		26in.
Cheeks, to sew on, cut ...	$\frac{7}{8}$ by	13in. ...	$\frac{3}{4}$ by	13in.
„ „ made up	$\frac{7}{8}$ by	9in. ...	$\frac{3}{4}$ by	9in.
Front, cut	$\frac{7}{8}$ by	19 $\frac{1}{2}$ in. ...	$\frac{3}{4}$ by	19 $\frac{1}{2}$ in.
„ made up		14in. ...		14in.
Reins, cut	1 by	58in. ...	$\frac{7}{8}$ by	58in.
„ made up	1 by	54in. ...	$\frac{7}{8}$ by	54in.

The reason for cheeks being shorter than in the case of ordinary snaffle bridles is on account of large ring bits being used; while it is always desirable in making bridles for the above purpose to give a good length of rein, exceeding rather than being under the above measurements.

When ordinary snaffle bridles are being fitted with large ring bits the cheeks should be made proportionately shorter.

NOSEBANDS FOR RIDING BRIDLES.

In addition to the narrow, stitched nosebands (which are passed through the openings left specially for the purpose), others of a different and sometimes broader kind are frequently used, and therefore a few particulars about some of them will help to make this section of the Guide more complete.

Nosebands for Riding Bridles (*continued*).NOSEBAND made on $\frac{7}{8}$ in. Spiked Rings.Front part made up 13in. long, $\frac{7}{8}$ in. in centre, reduced to $\frac{5}{8}$ in. at each end. Raised and sewn.

Buckle part on near-side, made up ...	$\frac{5}{8}$ by	3in.
Strap part on off-side	„ ...	$\frac{5}{8}$ by 10 $\frac{1}{2}$ in.
Head-strap	„ ...	$\frac{5}{8}$ by 32in.
„ buckle side	„ ...	$\frac{5}{8}$ by 9in.

Broad Nosebands 28in. long by any width from 1 $\frac{1}{4}$ in. to 1 $\frac{3}{4}$ in. Left broad for centre of the nose and tapered for point and buckle-end similar to a harness bridle noseband. Some prefer the head-strap and cheek sewn in; others to loop round the noseband so that the latter slides tightly through them. In both cases the head-strap should be made to allow about the same length as in the one mentioned above. In some cases these are left broad at the back, the strap-end only being reduced to receive buckle, which is fixed on by a small chape, the back of noseband thus serving as a guard or safe.

SHOW BRIDLES.

	Cob. Inches.	Gig. Inches.	Carthorse. Inches.
Head, cut	2 $\frac{1}{4}$ by 22	2 $\frac{1}{2}$ by 24	2 $\frac{3}{4}$ by 30
„ split	$\frac{3}{4}$ by 6	$\frac{7}{8}$ by 7	1 by 9
Cheeks, to pattern, cut 2	by 12	2 $\frac{1}{8}$ by 14	2 $\frac{1}{4}$ by 16
„ between buckles...	7	8 $\frac{1}{2}$	10
„ billets	$\frac{3}{4}$ by 8	$\frac{7}{8}$ by 9	1 by 10
Front, between	1 by 12	1 $\frac{1}{8}$ by 13	1 $\frac{1}{4}$ by 14 $\frac{1}{2}$
Throat, made up	$\frac{3}{4}$ by 18	$\frac{7}{8}$ by 19	1 by 21
Nose, cut	1 $\frac{1}{4}$ by 28	1 $\frac{1}{2}$ by 30	1 $\frac{3}{4}$ by 34
„ swelled middle to pattern	11 $\frac{1}{2}$	12 $\frac{1}{2}$	15
„ point	$\frac{3}{4}$ by 6	$\frac{7}{8}$ by 6	1 by 7
Bearing Rein (off side)...	1 by 66	1 $\frac{1}{8}$ by 72	1 $\frac{1}{4}$ by 84
„ „ (near side)	1 by 16	1 $\frac{1}{8}$ by 18	1 $\frac{1}{4}$ by 22
„ „ (billets) ...	1 by 8	1 $\frac{1}{8}$ by 9	1 $\frac{1}{4}$ by 10
Leading rein up to 16ft. long	1	1 $\frac{1}{8}$	1 $\frac{1}{4}$

NOSE BAGS.

Pony.	Cob.	Full Size.	Cart Horse.
16 by 18in. ...	17 by 19in. ...	18 by 20in. ...	19 by 22in.

LOIN COVERS.

	Pony.	Cob.	Thill.	Trace.
	24 by 30in. ...	30 by 36in. ...	36 by 48in. ...	48 by 54in.
Straps	$\frac{3}{4}$ by 22in. ...	$\frac{7}{8}$ by 24in. ...	1 by 24in. ...	1 by 24in.

Hood.

Breast Cloth.

G to G 18 in. I to I 36 in.
H „ H 44 „ I „ H 29 „

Pattern of Ears.

Pad Cloth.
K to K 25 in.
L „ L 13 in.

Pattern of Hood.

Quarter Cloth, with Breast Girth.

A to B 47 in. E to bottom 33 in.
C „ D 41 „ F „ „ 35 „
C „ bottom 35 „ D „ „ 34 „

Body Roller.

PATTERNS FOR A COMPLETE SUIT OF HORSE CLOTHING.

KNEE APRONS.

For one Person. For two Persons (ordinary size). Extra large.
 48 by 50in. ... 48 by 60in. ... 48 by 72in.

STRAPS FOR KNEE APRONS.

Made up $\frac{5}{8}$ in. or $\frac{3}{4}$ in. by 42in.

One each loop back and front, and one loose loop.

HORSE CLOTHING.**ROLLERS.**

	Full Size. Inches.	Cob Size. Inches.	Pony Size. Inches.
Web 	5 by 78	4½ by 72	4 by 66
Pad 	18	16	14
Straps 	1¼ by 18	1⅞ by 16	1 by 14
,, placed from ends	10	9	8
Facings 	2 by 20	1⅞ by 18	1¾ by 16
Cross pieces 	2 by 5	1⅞ by 4½	1¾ by 4
Long loop 	1¼ by 5¼	1⅞ by 4¾	1 by 4¼

KNEE CAPS.

	Full Size. Inches.	Cob Size. Inches.	Pony Size. Inches.
Kersey, to pattern ..	10½ by 9	9½ by 8	8½ by 7
Leather blocks (oval) ..	5 by 6	4¾ by 5¾	4½ by 5¼
Strap & front in one, cut	1¼ by 20	1⅞ by 18	1 by 16
Reduced for strap to ..	⅝ by 9	⅝ by 8	½ by 7
Bottom straps 	½ by 12	½ by 11	⅜ by 10

HEAD COLLARS.**ALBERT.**

	Full Size. Inches.	Cob Size. Inches.	Pony Size. Inches.
Head, cut 	1¼ by 28	1⅞ by 25½	1 by 23
,, made up 	1¼ by 25	1⅞ by 23½	1 by 21
Nose, cut 	1¼ by 21	1⅞ by 20	1 by 19
,, made up 	1¼ by 16	1⅞ by 15	1 by 14
Front, cut 	1 by 21	⅞ by 20	¾ by 19
,, made up 	15	14	13
Throat, cut 	1⅞ by 21½	1 by 20	1 by 19
,, made up 	15½	14	13
,, rounded 	11	10	9
Cheeks (solid) cut ..	1¼ by 14	1⅞ by 12½	1 by 11
,, ,, made up 	8½	7	6
Back Stay, cut 	1¼ by 15	1⅞ by 13	1 by 11
,, ,, made up 	6½	5½	4½
Side pieces (lined) cut... 1¼ by 12	5	1⅞ by 11	1 by 10
,, ,, made up 	5	4½	4
Buckle part, cut 	1¼ by 7½	1⅞ by 7½	1 by 6½
,, ,, made up 	3	3	2½

Head Collars (*continued*).

NEWMARKET.

	Full Size. Inches.	Cob Size. Inches.	Pony Size. Inches.
Head, cut	1¼ by 36	1⅞ by 33	1 by 30
„ made up	33	30	27½
Nose, cut	1¼ by 21	1⅞ by 20	1 by 19
„ made up	16	15	14
Front, cut	1 by 21	¾ by 20	¾ by 19
„ made up	15	14	13
Throat, cut	1⅞ by 21½	1 by 20	1 by 19
„ made up	15½	14	13
Cheek (near side only) cut	1¼ by 14	1⅞ by 12½	1 by 11
„ ditto made up	8½	7	6
Back Stay, cut	1¼ by 15	1⅞ by 13	1 by 11
„ made up	6½	5½	4½
Jowl pieces, cut	1¼ by 12	1¼ by 11	1 by 10
„ „ made up	5	4½	4

When these are required with long chalbands they should be made up about the following lengths, etc.:—

Full Size.	Cob Size.	Pony Size.
¾ by 45in. ...	¾ by 39in. ...	⅝ by 33in.

Head Collar Rein	1¼ by 54in.
„ „ „ billet	1¼ by 11in.
Pillar Rein	¾ by 42in.
„ „ „ billet	¾ by 10in.

BREAKING CAVESON.

Head	1½ by 27in.
„ split	1 by ½ by 8in.
Buckle piece on head	¾ by 6in.
Throat	½ by 19in.
Face Strap, leading from centre of nose to head, cut	1¼ by 28in.
Face Strap, leading from centre of nose to head, made up	23in.
Face Strap, leading from centre, reduced at point to	¾ by 10in.
Front, cut	1 by 21½in.
„ between	12in.
Lay under centre of front to form slide for face strap	1 by 4in.
Cheeks, cut	1 by 13in.
„ made up	1 by 8½in.
Front part of nosepiece (padded)	1⅝ by 18½in.
Noseband (off side strap) made up	¾ by 14in.
„ (near side) made up	¾ by 4½in.
Small straps for fastening padded part to nose iron	½ by 4½in.
Lunging Rein	1¼ by 144in.

DUMB JOCKEY.

Reins	...	...	...	...	...	$\frac{7}{8}$ in.	by	54in.
„ billets	...	...	...	...	...	$\frac{7}{8}$ in.	by	21in.
Crupper, body	...	...	...	...	...	1 $\frac{3}{4}$ in.	by	24in.
„ split each end	...	...	...	...	...			8in.
„ billets (2)	...	...	...	...	...	$\frac{7}{8}$ in.	by	48in.

Dock made to buckle.

SIZES OF SOLID LEATHER DOG COLLARS.**COLLIE DOGS.**

Width.	Length.				Width.	Length.	Rounded.
$\frac{1}{2}$ in.	...	11in.	12in.	13in.		$\frac{3}{4}$ in.	... 16in. ... 9in.
$\frac{5}{8}$ in.	...	13in.	14in.	15in.		$\frac{3}{4}$ in.	... 18in. ... 10in.
$\frac{3}{4}$ in.	...	14in.	15in.	16in.		$\frac{7}{8}$ in.	... 20in. ... 11in.
$\frac{7}{8}$ in.	...	15in.	16in.	18in.		$\frac{7}{8}$ in.	... 22in. ... 12in.
1in.	...	17in.	18in.	19in.		1in.	... 24in. ... 14in.
1 $\frac{1}{8}$ in.	...	19in.	20in.	21in.			
1 $\frac{1}{4}$ in.	...	21in.	22in.	23in.			
1 $\frac{3}{8}$ in.	...	22in.	23in.	24in.			
1 $\frac{1}{2}$ in.	...	23in.	24in.	25in.			
1 $\frac{3}{4}$ in.	...	24in.	26in.	28in.			
2in.	...	26in.	28in.	30in.			

GREYHOUND COLLARS.

Broad part about 2in. by 19in.

Two each narrow buckles and straps sewn on, or as lays throughout.

On cutting 2in. by 19in., leave full width for 12in. taper to 1in. for strap, sew dee on with lay in front of the buckle, passing strap through dee before buckling on the neck.

WHIPPET COLLARS.

Broad part 1 $\frac{1}{2}$ in. or 1 $\frac{5}{8}$ in. by about 13in.

Light loop sewn underneath at one end for opposite end to pass through before buckling by the short strap, which is sewn on; or continuation lay and strap as in the case of Greyhound Collars.

SIZES OF RUG STRAPS.

Width.	Length.			
$\frac{1}{2}$ in.	...	18in.	21in.	24in.
$\frac{5}{8}$ in.	...	30in.	36in.	42in.
$\frac{3}{4}$ in.	...	—	42in.	48in.
$\frac{7}{8}$ in.	...	—	48in.	54in.
1in.	...	—	54in.	60in.

GLADSTONE BAG STRAPS.

Size of Bag... ..	16in.	18in.	20in.	22in.	24in.	26in.
Size of Straps ... lin. by	45in.	48in.	51in.	54in.	57in.	60in.

STIRRUP LEATHERS.

1 $\frac{1}{8}$ in.	48in.
1 $\frac{1}{4}$ in.	54in.
1 $\frac{3}{8}$ in. 54in., 57in., & 60in.	

GIRTHS.

Width of Web	2 $\frac{1}{2}$ in.	2 $\frac{3}{4}$ in.	3in.	3 $\frac{1}{4}$ in.
Made up—Pony	36in.	39in.	—	—
„ —Cob	—	42in.	44in.	—
„ —Full size	—	—	45in.	48in.

ROPE REINS.

Shaft Horse, rope cut	28ft.
Two „ „ „	48ft.
Three „ „ „	68ft.
(Pin horse billets sewn on ring to slide on rope).	
Four-Horse (in double-shafted waggon), rope cut	54ft.
Billets, cut 1in. by about 16 $\frac{1}{2}$ in.	

FOAL SLIPS.**CART HORSE FOALS.**

Head-strap	1 by	40in.
Nose	1 by	27in.
Cheeks	1 by	10in.
Head and nose crossed in ring.		
Cheeks apart on head		15in.
„ „ nose		11in.
Hand-leather sewn on ring about 9in.		

DITTO FOR NAG FOALS.

Head-strap	$\frac{7}{8}$ by	36in.
Nose	$\frac{7}{8}$ by	25in.
Cheeks	$\frac{7}{8}$ by	8in.
To cross as in above slip.		
Cheeks apart on head		12in.
„ „ nose		9in.
Hand-leather sewn on ring about 8in.

SLING FOR SICK HORSE.

CRUPPERS FOR RIDING SADDLES.

	Horse Size.	Cob Size.	Pony Size.
Body, cut	1¼ by 16	1¼ by 14	1¼ by 12in.
„ made up	14½	12½	11in.
„ split	6	5½	5in.
Strap	⅞ by 24	⅞ by 21	¾ by 18in.
Dock (for rounding)... ..	1½ by 15	1½ by 14½	1¾ by 14in.

These are generally made up with one loop sewn in where strap is sewn on to body, an additional loop about 3in. further back, and a slide loop on the strap.

If required specially strong, a lin. strap is put on the horse size, and the body made 1½in. wide.

Occasionally a broad piece of leather is folded for the dock instead of making them round.

TAIL CASE FOR PONY.

Depth	7in.
Width	8in.
Strap when buckled	32in.

GAG HEAD AND REIN (Riding Bridle).

Loose Head-strap	¾ by 27in.
Cheeks, from end of rein	¾ by 12 to 14in.
„ rounded	8in.
Reins, made up	¾ or ⅞ by 54in.

If head made like ordinary bridoon, long-side 36in.

SIDE SADDLE BALANCE GIRTH, Etc.

Loose Girth, made up	1½ by 42in.
Strap on off-side of saddle	1 by 17 or 18in.
Strap screwed on near-side point of tree (in slanting position)	1 by 15in.

If attached to looped stirrup leather on the near-side instead of strap on tree point, the stirrup leather is made about 1in. wide by 2ft. 6in.

Ordinary leather girth sewn on side saddle flap,
about 1½in. by 2ft. 6in.

Strap for same, about 1in. by 18in.

EXTRA THROATBAND FOR HARNESS BRIDLE.

(i.e., when sewn into a small ring or dee fastened in cheek near the bottom of winker).

Off-side, with buckle ... 13in.

Near-side Strap ... 6½in.

Slightly longer if sewn into the cheek without a dee.

HOPPER STRAP.

7ft. long, 1¼in. or 1½in. wide.

DONKEY BODY ROLLER.

Web ... 4ft. 3in. | Strap ... 1ft. 3in.

RACE SURCINGLE.

Web, about ... 2¼ by 57in. | Strap ... 1 by 24in.

BREECHES OR LEGGING STRAPS.

Made up ¼in. or ⅜in. wide by 17in. or 18in. long.

COUPLING STRAPS.

FOR WAGGON OR DRAY HORSES.

Made up 1¼in. wide by 33in. and 27in.

FOR CALVES.

Made up about 1¼in. by 29in. long.

Watering Chain in the centre.

NECK COLLAR (for Tying up Beast).

About 2¼in. wide by 48in. long.

GUN STRAP (OR SLING).

Long-side made with loop sewn on the end opposite to punch holes, the latter being passed through loop when fastened on gun. 1¼in. wide by 30in.

Short-side looped in similar way, but buckle-end passed through loop before buckle and loop are sewn in to receive the long side. Made up 1¼in. by 15in.

RIDING BREASTPLATE.

Neck-strap, cut	...	...	...	$\frac{7}{8}$ by	28 $\frac{1}{2}$ in.
Made up (from bend to bend)	...	...	...		23in.
Crestpiece, cut	...	...	...	1 $\frac{3}{8}$ by	14in.
				(Tapered to $\frac{7}{8}$ in.)	
Made up (from bend to bend)	...	...	...		9in.
Wither-straps, cut	...	...	...	$\frac{5}{8}$ by	26 to 29in.
Made up	...	...	...		24 to 27in.
Bottom (or girth part), cut	1 $\frac{3}{8}$ in. wide	by	46in.	(tapered to 1in.	
Made up (from ring to bend when buckled),	36in.				

MACHINE BELTING.

The usual lengths of joints and number of lines of sewing in each case:—

Width of Belt.	LENGTH OF JOINTS.				LINES OF SEWING.			
	Single.		Double.		Single.		Double.	
1in. ...	3in. ...	—	...	...	2 lines. ...	—		
1 $\frac{1}{4}$ in. ...	3in. ...	—	...	...	2 „ ...	—		
1 $\frac{1}{2}$ in. ...	3 $\frac{1}{2}$ in. ...	—	...	...	2 „ ...	—		
1 $\frac{3}{4}$ in. ...	3 $\frac{3}{4}$ in. ...	—	...	...	2 „ ...	—		
2in. ...	4in. ...	3in. ...	...	...	2 „ ...	2 lines.		
2 $\frac{1}{4}$ in. ...	4 $\frac{1}{4}$ in. ...	3in. ...	...	...	2 „ ...	2 „		
2 $\frac{1}{2}$ in. ...	4 $\frac{1}{4}$ in. ...	3in. ...	...	...	3 „ ...	2 „		
2 $\frac{3}{4}$ in. ...	4 $\frac{1}{4}$ in. ...	3in. ...	...	...	3 „ ...	2 „		
3in. ...	4 $\frac{1}{2}$ in. ...	3 $\frac{1}{4}$ in. ...	...	...	3 „ ...	3 „		
3 $\frac{1}{4}$ in. ...	4 $\frac{1}{2}$ in. ...	3 $\frac{1}{4}$ in. ...	...	...	3 „ ...	3 „		
3 $\frac{1}{2}$ in. ...	4 $\frac{1}{2}$ in. ...	3 $\frac{1}{2}$ in. ...	...	...	3 „ ...	3 „		
4in. ...	4 $\frac{3}{4}$ in. ...	3 $\frac{3}{4}$ in. ...	...	...	4 „ ...	3 „		
4 $\frac{1}{2}$ in. ...	4 $\frac{3}{4}$ in. ...	3 $\frac{3}{4}$ in. ...	...	...	4 „ ...	4 „		
5in. ...	5in. ...	4in. ...	...	...	4 „ ...	4 „		
5 $\frac{1}{2}$ in. ...	5 $\frac{1}{4}$ in. ...	4 $\frac{1}{4}$ in. ...	...	...	4 „ ...	4 „		
6in. ...	5 $\frac{1}{2}$ in. ...	4 $\frac{1}{2}$ in. ...	...	...	4 „ ...	4 „		
6 $\frac{1}{2}$ in. ...	6in. ...	5in. ...	...	...	4 „ ...	4 „		
7in. ...	6 $\frac{1}{2}$ in. ...	5 $\frac{1}{2}$ in. ...	...	...	5 „ ...	5 „		
7 $\frac{1}{2}$ in. ...	7in. ...	6in. ...	...	...	5 „ ...	5 „		
8in. ...	7 $\frac{1}{2}$ in. ...	6 $\frac{1}{2}$ in. ...	...	...	5 „ ...	5 „		
9in. ...	8in. ...	7in. ...	...	...	6 „ ...	6 „		
10in. ...	8 $\frac{1}{2}$ in. ...	7 $\frac{1}{2}$ in. ...	...	...	6 „ ...	6 „		
11in. ...	9in. ...	8in. ...	...	...	6 „ ...	6 „		
12in. ...	10in. ...	8 $\frac{1}{2}$ in. ...	...	...	6 „ ...	6 „		

The length of joints allowed is for stout ends. For shoulder, and light ends of strips the joints must be proportionately longer to produce an even substance throughout the belt.

Machine Belting (*continued.*)

BEST QUALITY MACHINE BELTING : Its average weight per 100 feet, and price per foot :—

Width.	PRICE PER FOOT.		WEIGHT PER 100 FEET.	
	Single.	Double.	Single.	Double.
	s. d.	s. d.		
1in. ...	0 4	... —	... 6½lbs.	.. —
1¼in. ...	0 5½	... —	... 8lbs.	.. —
1½in. ...	0 7	... —	... 11lbs.	... —
1¾in. ...	0 8	... —	... 14lbs.	... —
2in. ...	0 9	... 1 9	... 16lbs.	... 26½lbs.
2¼in. ...	0 10	... 2 0	... 18lbs.	... 30lbs.
2½in. ...	1 0	... 2 2	... 22lbs.	... 36lbs.
2¾in. ...	1 2	... 2 4	... 25lbs.	... 41lbs.
3in. ...	1 3½	... 2 7	... 28lbs.	... 46lbs.
3½in. ...	1 6½	... 3 2	... 33lbs.	... 55lbs.
4in. ...	1 10	... 3 7	... 39lbs.	... 65lbs.
4½in. ...	2 1	... 4 1	... 45lbs.	... 74lbs.
5in. ...	2 5	... 4 6	... 52lbs.	... 86lbs.
5½in. ...	2 7	... 4 10	... 56lbs.	... 93lbs.
6in. ...	2 9	... 5 4	... 60lbs.	... 100lbs.
6½in. ...	3 0	... 6 0	... 64lbs.	... 106lbs.
7in. ...	3 4	... 6 6	... 68lbs.	... 112lbs.
7½in. ...	3 8	... 7 2	... 72lbs.	... 120lbs.
8in. ...	4 0	... 7 10	... 76lbs.	... 127lbs.
9in. ...	4 7	... 8 11	... 94lbs.	... 156lbs.
10in. ...	5 2	... 10 0	... 104lbs.	... 172lbs.
11in. ...	5 9	... 11 6	... 114lbs.	... 190lbs.
12in. ...	6 6	... 12 7	... 124lbs.	... 206lbs.

ESTIMATE SHEET No. 1.**SET OF BEST THILL HARNESS, WITH BRASS FURNITURE.**

Particulars.	BRIDLE.	Ozs.		
1¼ in. × 24 in.	Head	5		
2 in. × 15 in.	Nosepiece (lined)	8		
1¼ in. × 48 in.	Front, Throat and Point	11		
1¼ in. × 54 in.	Off-side Rein	13		
1¼ in. × 26 in.	Near-side Rein	7		
¾ in. × 24 in.	Cheek Straps (2)	6		
1 in. × 78 in.	Check Rein and Billet	12		
¾ in. × 9 in.	Facepiece Strap	3		
1¼ in. × 13 in.	Cheeks and Brace Pieces	10		
6¼ in. × 6¾ in.	Winker Linings	12		
			s.	d.
	Leather @ 2/- per lb.	5lbs. 7ozs.	10	10½
6¼ in. × 6¾ in.	Patent Leather Winkers @ 2/8, 8ozs. ...		1	4
Brass.	One Pair Rosettes		0	5
"	Two S. Hooks		0	4
"	Two Scallopes 2¼ in., fluted		0	6½
"	Four 1¼ in. Buxton Buckles		0	8
"	One 1 in. " "		0	1½
"	Three ¾ in. whole Buxton Buckles		0	4½
"	Four 1¼ in. Rings		0	8
"	Two ⅞ in. Dees for Cheeks		0	2
"	One Flyer		0	7½
"	One Jointed Noseplate		0	6½
"	One Facepiece		0	3½
With swivel.	One Galvanized Check Rein Chain		0	9
Winkers sewn 9 to	Hemp, Wax, etc.		0	6
inch, other parts 8.	Labour, 13 hours @ 6d.		6	6
			£1	4 8½

(Leather 12/2½, Furniture 5/6, Sundries 6d., Labour 6/6.)

	REINS.		
1½ in. × 30 ft.	3¾ lbs. Leather @ 2/-	7	6
	Two 1⅞ in. Brass Buxton Buckles	0	3
	Labour, 1½ hours @ 6d.	0	9
		8	6

	HAMES.		
32 in.	Best Solid Brass (—) Brand	15	3
1¼ in. × 26 in.	Hame Strap, 6ozs. Leather @ 2/-	0	9
	One 1¼ in. Buxton Buckle	0	2
	Making Hame Strap	0	2
		16	4

Estimate Sheet No. 1 (*continued.*)

Particulars.		s.	d.
23½in.	Collar (bought)	10	0
1½in. × 17in.	Collar Straps, 10ozs. Leather @ 2/- ...	1	3
12in. × 22in.	Housing Patent Leather, 11lb. 8ozs. Leather @ 2/8	4	0
1in. × 9in.	Housing Straps (2), 3ozs. Leather @ 2/8	0	6
	Two 1in. Housing Buckles	0	2
	Two Fluted Scallopes 2½in.	0	8½
	Labour, 4 hours @ 6d.	2	0
		18	7½

(Collar 10/-, Leather 5/9, Furniture 10½d., Labour 2/-.)

SADDLE

18in. × 24in.	Patent Leather for Housing, 3lbs. @ 2/8	8	0
	Linings for Housing, 1lb. @ 1/6 ...	1	6
1½in. wide.	Girth and Strap, 1lb 8ozs. @ 2/- ...	3	0
"	Meter Buckle Pieces, 8ozs. @ 2/- ...	1	0
"	Crupper Loop, 4ozs. @ 2/-	0	6
	One 12in. Tree	1	4
	One 12in. Pad (bought)	3	6
	One Pair Galvanized Australian Irons...	0	10
	One Pair 7⁄8in. Beads	1	1
Brass.	One Pair Rings and Clips	1	0
"	Four 2¾in. Fluted Scallopes @ 5/3 ...	1	9
"	One Pair of Ridger Bars... ..	1	0
"	Three 1½in. Buxton Buckles	0	6
	Four Tie Strings for Pad	0	4
	Hemp and Wax	0	4
Top sewn 9 to inch, other parts 8.	Making, 12 hours @ 6d.	6	0
		£1	11 8

(Leather 14/-, Tree 1/4, Pad 3/6, Furniture 6/2, Sundries 8d., Labour 6/-.)

MARTINGALE.

1½in. wide.	Girth, }	lb. Leather @ 2/- ...	2	0
¾in. wide.	Ring Straps, }			
	Linings for Facepieces, ½lb. Leather @ 1/4		0	8
Brass.	Four Facepieces @ 3/6		1	2
"	One 1¾in. Ring		0	2
"	One 1½in. Buxton Buckle		0	2
"	Two ¾in. whole Buxton Buckles ...		0	4
	Labour, 1½ hours @ 6d.... ..		0	9
			5	3

(Leather 2/8, Furniture 1/10, Labour 9d.)

Estimate Sheet No. 1 (*continued*).

Particulars.	BREECHING AND CRUPPER	s.	d.
3in. × 72in.	} Seat and Lay, bs. Leather @ 2/- ...	8	0
2½in. × 70in.			
1¼in. × 50in.	Loin Strap, 10ozs. Leather @ 2/- ...	1	3
1¼in. × 27in.	Hip Straps, 12ozs. Leather @ 2/- ...	1	6
	Tugs (4), 1lb. Leather @ 2/- ...	2	0
3½in. × 20in.	Crupper Body, 12ozs. Leather @ 2/- ...	1	6
2½in. wide.	Lay and Billet, 1lb. 4ozs. Leather @ 2/-	2	6
	One 2½in. Brass Buxton Buckle ...	0	5
	Four 1¼in. „ „ „ „ ...	0	8
	Two 2½in. Brass on Iron Dees... ..	0	8½
	One Pair 3½in. Galvanized Contract		
	Breeching Irons	2	1
Sewing 8 to inch.	Labour, 16 hours @ 6d.	8	0
	Hemp, Wax, etc.... ..	0	8
		<u>£1</u>	<u>9 3½</u>

(Leather 16/9, Furniture 3/10½, Sundries 8d., Labour 8/-.)

WANTEY, WITH TWO BILLETS.

Stout single leather.	Body, 3½in. wide by 36in. long.		
	Billets, 3½in. wide by 30in. long.		
	3½lbs. of Leather @ 2/-... ..	7	0
Brass.	Two 3½in. Buxton Buckles	1	7
	Labour, 1½ hours @ 6d.	0	9
	Hemp and Wax	0	2
		<u>9</u>	<u>6</u>

TOTAL.

Bridle	1	4	8½
Reins	0	8	6
Hames and Strap	0	16	4
Collar, Housing, etc.	0	18	7½
Saddle	1	11	8
Martingale	0	5	3
Breeching and Crupper	1	9	3½
Wantey	0	9	6
	<u>£7</u>	<u>3</u>	<u>10½</u>

This shows the prime cost of harness. Trade profit differs with each locality, so that no attempt will be made to add this in any of the estimates. In taking the cost of leather at 2s. per lb., and labour at 6d. per hour, this has been done for simplicity in working out each item. Where these do not correspond with the prices paid, the difference must be allowed for.

ESTIMATE SHEET No. 2.

PLAIN MEDIUM QUALITY BRASS THILL HARNESS—NO
WANTEY, REINS, CHECK REIN, OR MARTINGALE.

Particulars.		BRIDLE		lbs.	ozs.		
1½in. × 24in.	Head	...	...	...	4½		
1½in. × 48in.	Throat, Front and Point ...	...	...	...	9½		
1½in. × 54in.	Off-side Rein	...	...	...	12		
1½in. × 24in.	Near-side Rein	...	...	...	6½		
1½in. × 15in.	Nosepiece	...	...	...	4		
1½in. × 13in.	Cheeks	...	...	...	9		
6¼in. × 7¼in.	Winkers and Brace Pieces ...	...	...	1	1		
" "	Winker Linings	...	...	...	12		
						s.	d.
		Leather @ 1/8	...	...	4 10½	7	9
Brass.		Four 1½in. Buxton Buckles ...	...	...	...	0	8
		Four 1¾in. Rings	...	...	...	0	8
		Two S. Hooks	...	...	...	0	4
		Labour, 9 hours @ 6d. ...	...	...	...	4	6
Sewing 8 to inch all parts.		Hemp, Wax, etc.	...	...	...	0	5
						14	4

(Leather 7/9, Furniture 1/8, Sundries 5d., Labour 4/6.)

HAMES.

32in.	¾ Brass Cased with Japanned Tackle	11	0
1¼in. × 26in.	Hame Strap, 5ozs. @ 1/9	0	5½
	One 1¼in. Buxton Buckle	0	2
	Making Hame Strap	0	2
		11	9½

COLLAR AND HOUSING.

24in.	Collar (bought)	10	0
1½in. × 16in.	Collar Straps, 9ozs. Leather @ 1/9 ...	1	0
Circular.	Housing, 14ozs. Leather @ 1/9 ...	1	7
	Labour, 3 hours @ 6d.	1	6
	Hemp, Wax, and Thongs	0	4
		14	5

SADDLE.

18in. × 24in.	Housing, 3lbs. Leather @ 1/9	5	3
	" Binding, ½lb. Leather @ 1/9..	0	10½
1½in. wide.	Girth & Strap, 1lb. 6oz., Leather @ 1/9	2	4½
"	Meter Buckle Pieces, 8oz. Leather @ 1/9	0	10½
	Crupper Loop, 4ozs. Leather @ 1/9 ...	0	5½
	One 12in. Tree	1	4
		11	2
Carried forward		11	2

Estimate Sheet No. 2 (*continued.*)

Particulars.			s.	d.
	Brought forward ...	...	11	2
	One 12in. Pad (bought) ...	...	2	9
	One Pair $\frac{7}{8}$ in. Beads ...	...	1	1
	Rings and Screws... ..	...	0	10
	Three $1\frac{1}{2}$ in. Buxton Buckles ...	...	0	6
	Four Tie Strings for Pad ...	...	0	4
	Hemp and Wax ...	...	0	3
All parts sewn 8 to inch.	Labour, 10 hours @ 6d. ...	...	5	0
			<u>£1</u>	<u>1 11</u>

(Leather 9/10, Tree 1/4, Pad 2/9, Furniture 2/5, Sundries 7d., Labour 5/-.)

BREECHING AND CRUPPER.

3½in. × 60in.	{ Seat and Lay, 3¾lbs. of Leather @ 1/9	6	7
2½in. × 58in.			
1½in. × 48in.	Loin Strap, 10ozs. Leather @ 1/9	...	1 1
1½in. × 26in.	Hip Straps, 12ozs. Leather @ 1/9	...	1 4
No safes.	Tugs (4), 12ozs. Leather @ 1/9	...	1 4
3½in. × 24in.	Crupper Body, 10ozs. Leather @ 1/9	...	1 1
2½in. wide.	Lay and Billet, 1lb. 2ozs. Leather @ 1/9	1	11½
	One 2½in. Brass Buxton Buckle	..	0 5
	Four 1½in. „ „	...	0 8
	Two 2½in. Brass Dees ...	...	0 8½
	One Pair 3½in. Japanned Breeching Irons	1	3
Sewing 8 to inch.	Labour, 15 hours @ 6d. ...	...	7 6
	Hemp, Wax, etc. ...	...	0 8
			<hr/>
		£1	4 7

(Leather $13\frac{3}{4}$ ½, Furniture $3\frac{1}{2}$ ½, Sundries 8d., Labour 7/6.)

TOTAL.

Bridle	...	...	...	0	14	4
Hames and Strap	...	...	...	0	11	9½
Collar and Housing	...	...	...	0	14	5
Saddle	...	...	...	1	1	11
Breeching and Crupper	...	...	...	1	4	7
				<u>£4</u>	<u>7</u>	<u>0½</u>

ESTIMATE SHEET No. 3.**SET OF PLAIN PONY HARNESS, BRASS FURNITURE,
NO BEARING REIN.**

Particulars.	BRIDLE.				Ozs.
1¼in. × 20in.	Head	...	...	...	4
1½in. × 25in.	Nosepiece (lined centre only)	...	...	...	5
¾in. × 25in.	Cheeks	...	...	...	5½
¾in. × 16in.	Throat	...	...	...	1½
1in. × 11in.	Winker Stay	...	...	...	1½
	Winker Linings	...	...	...	3
	Leather @ 1/8			1lb. 4½ozs.	2 2
	Patent Leather for Winkers, 4ozs. @ 2/-				0 6
	Fancy Patent Leather Front	...	...		0 10
	Pair Winker Plates	...	...		0 3½
Brass.	Pair Rosettes	...	...		0 4
"	½-doz. ¾in. Wire Buckles	...	...		0 4
	One Common Pony Wilson Bit	...	...		0 4½
	Labour	...	...		3 6
	Hemp, etc.	...	...		0 3
					<hr/> 8 7

(Leather 3/6, Furniture 1/0½, Sundries 6½d., Labour 3/6.)

REINS.					
¾in. × 20ft.	Drafts and Billets, 14ozs. @ 2/-	...	...	...	1 9
¾in. × 54in.	Handparts (brown)	...	...	...	1 3
	Two ¾in. Buckles	...	...	...	0 2
	Making, etc.	...	...	...	0 8
					<hr/> 3 10

COLLAR, HAMES, & TRACES.

18in.	Plain Leather Collar	...	...	...	7 0
	Pair All-over Ring Draft Hames	...	...	...	3 6
	Hame Strap, 6ozs. @ 1/8...	...	...	...	0 7½
	Two ¾in. Buckles	...	...	...	0 1½
1¼in. × 54in.	Traces, 1lb. 10ozs. Leather @ 1/8	...	...	...	2 8½
Polished.	Pair Chain Ends	...	...	...	0 7
Sewn 7 to in., 4 rows.	Making Traces and Hame Strap	...	...	...	4 6
	Hemp and Wax	...	...	...	0 6
					<hr/> 19 6½

SADDLE.

4in.	Plain Flap Saddle, with Screw Skirts	...	...	...	12 6
	Pair Plain Wire Terrets	...	...	...	0 7½
	Plain Knob	...	...	...	0 3
	Girth, Strap & Lay, 10oz. Leather @ 1/8	...	...	...	1 0½
	¾in. Roller Buckle	...	...	...	0 1½
					<hr/> 14 6½
	Carried forward	...	...	...	14 6½

Estimate Sheet No. 3 (*continued.*)

s. d.

Brought forward	14	6½
Making and Sewing on Girth and Strap	0	9
Hemp and Wax	0	1

15 4½
BACKBAND AND TUGS.

Particulars.		lbs.	ozs.	
1¼in. × 8lin.	Backband	1	6	
1¼in. wide.	Tugs		10	
	Leather @ 1/8 per lb.	2	0	3 4
	Two 1¼in. Tug Buckles...			0 7½
	Pair Tug Loops (brass) ...			0 3
	One 1¼in. Roller Buckle			0 2
Sewn 4 rows,	Making Backband			3 6
7 to inch.	Making Tugs			2 3
	Hemp and Wax			0 6
				10 7½

(Leather 3/4, Furniture 1/0½, Sundries 6d., Labour 5/9.)

BREECHING AND CRUPPER.

1¼in. & 5/8in.	Breeching Seat and 4 Tugs...	10 oz.	
7/8in.	Shaft Straps	5	„
1¼in.	Split Hip Strap	7	„
1¼in. & 7/8in.	Crupper Body, Lay and Strap	8	„
	Leather @ 1/8 per lb.	1lb. 14ozs.	3 1½
	Four 5/8in. Buckles		0 3
	Three 7/8in. Buckles		0 3
	Two 1½in. Rings		0 2½
Sewn 9, once round.	Making Breeching Seat and Tugs		2 6
	Plain Hip Strap		0 4
	Crupper		0 7
	Making Breeching Straps		0 6
	Hemp and Wax		0 3
	Paper Dock		0 8
			8 8

(Leather 3/1½, Furniture 8½d., Sundries 11d., Labour 3/11.)

TOTAL.

Bridle	8 7
Reins	3 10
Collar, Hames and Traces ...	19 6½
Saddle	15 4½
Backband and Tugs	10 7½
Breeching and Crupper	8 8

£3 6 7½

ESTIMATE SHEET No. 4.**SET OF PLAIN, BRASS-MOUNTED TRADESMEN'S
HARNESS (Full Size).**

$\frac{3}{4}$ in. Strapping and Bridle. $1\frac{1}{2}$ in. Traces and Backband.

BRIDLE.						s.	d.
2 $\frac{1}{4}$ lbs. of Leather @ $\frac{1}{9}$ per lb.	...	...	...	...	...	3	11 $\frac{1}{2}$
Patent Leather, 6oz. @ $\frac{2}{8}$ per lb.	...	...	...	...	...	1	0
Pair Winker Plates	...	...	...	...	...	0	4
„ Rosettes	...	...	...	...	...	0	6
Chain Front	...	...	...	...	...	0	7 $\frac{1}{2}$
Pair Plain Swivels	...	...	...	...	...	0	4 $\frac{1}{2}$
Twelve $\frac{3}{4}$ in. Buckles	...	...	...	...	...	0	9
Two $\frac{3}{4}$ in. Rings	...	...	...	...	...	0	1
One Flat Ring Wilson Bit	...	...	...	...	...	1	6
Making Bridle: Winkers and front sewn 12, noseband	...	...	...	...	...	6	6
10, other parts 8 to inch	...	...	...	...	...		
						15	7 $\frac{1}{2}$

(Leather $4/11\frac{1}{2}$, Furniture $2/4$, Sundries $1/10$, Labour $6/6$.)

REINS, lin. $\times$ 24ft.

Drafts and Billets, $1\frac{1}{4}$ lbs. @ $\frac{1}{9}$	...	...	...	...	...	2	2 $\frac{1}{2}$
Pair lin. Handparts	...	...	...	...	...	1	10
Pair lin. Buckles	...	...	...	...	...	0	2 $\frac{1}{2}$
Making	...	...	...	...	...	1	0
						5	3

COLLAR.

22in. Plain Stage Collar	...	...	...	...	...	9	6
--------------------------	-----	-----	-----	-----	-----	---	---

HAMES, HAME STRAPS, AND TRACES.

Pair 23in. All-over Brass Ring Draft Hames	...	...	...	...	...	4	3
Traces, $1\frac{1}{2}$ in. $\times$ 5ft., Leather $3\frac{1}{4}$ lbs. @ $\frac{1}{9}$	...	...	...	...	...	5	8 $\frac{1}{2}$
Hame Straps, Leather $\frac{1}{4}$ lb. @ $\frac{1}{9}$	...	...	...	...	...	0	5 $\frac{1}{2}$
Two $\frac{3}{4}$ in. Buckles	...	...	...	...	...	0	1 $\frac{1}{2}$
Pair Galvanised Trace Chains	...	...	...	...	...	0	9
Making Traces, Sewn 4 rows	...	...	...	...	...	6	0
Making Hame Straps	...	...	...	...	...	0	4
						17	7 $\frac{1}{2}$

(Leather $6/2$, Furniture $5/1\frac{1}{2}$, Labour $6/4$.)

Estimate Sheet No. 4 (*continued.*)**SADDLE.**

	s.	d.
6in. Plain Solid Leather Cab Saddle	15	0
Girth, Strap and Lay, 14oz. Leather @ 1/9	1	6½
One 1½in. Roller Buckle	0	2½
One Pair Plain Terrets	1	1
One Plain Knob	0	4
Making Girth, Strap and sewing on to Saddle	1	0
	19	2

BACKBAND, 1½in. × 8ft.

2lbs. 6oz. leather @ 1/9	4	2
Shaft Tugs, 13oz. Leather @ 1/9	1	4
One 1½in. Roller Buckle	0	3½
Pair 1½in. Tug Buckles	0	11
Pair 1½in. Tug Loops	0	4½
Making Backband, sewn 8	3	6
Making Tugs, sewn 8	2	6
	13	1

(Leather 5/6, Furniture 1/7, Labour 6/-.)

CRUPPER.

Body 1½in., Strap and Lay 1½in. wide, 13oz. of Leather @ 1/9	1	4
One 1½in. Buckle	0	1½
Dock (paper)	0	8
Making Crupper	1	4
	3	5½

BREECHING.

Seat 1½in. × 42in., 14oz. Leather @ 1/9	1	7
Four Tugs, 6oz. Leather @ 1/9	0	8
Four ¾in. Buckles	0	3
Two 1¾in. Rings	0	4½
Making Breeching, sewn 9, Tugs 8	3	9
	6	7½

(Leather 2/3, Furniture 7½d., Labour 3/9.)

SHAFT STRAPS.

Shaft Straps 1½ × 30in., 12oz. Leather @ 1/9	1	4
Two 1½in. Buckles	0	4
Making	0	6
	2	2

Estimate Sheet No. 4 (continued.)

HIP STRAP.							s.	d.
Hip Strap 1½in. × 4ft., 10oz. Leather @ 1/9	...	...	...	...	...	...	1	1
Making	...	...	...	...	...	...	0	4
							<hr/>	
							1	5

TOTAL.						s.	d.
Bridle	...	...	...	...	...	15	7½
Reins	...	...	...	...	...	5	3
Collar	...	...	...	...	...	9	6
Hames, Hame Straps, and Traces...	...	...	...	...	...	17	7½
Saddle	...	...	...	...	...	19	2
Backband and Tugs	...	...	...	...	...	13	1
Crupper	...	...	...	...	...	3	5½
Breeching	...	...	...	...	...	6	7½
Shaft Straps	...	...	...	...	...	2	2
Hip Strap	...	...	...	...	...	1	5
Hemp, Wax, etc.	...	...	...	...	...	2	6
						<hr/>	<hr/>
						£4 16	5

ESTIMATE SHEET No. 5.**SET OF LINED GIG HARNESS, WITH SILVER-PLATED FURNITURE.—MEDIUM QUALITY.**

$\frac{3}{4}$ in. Bridle; $1\frac{1}{2}$ in. Traces, Backband and Tugs; $1\frac{3}{8}$ in. Breeching; 1in. Crupper and Shaft Straps. Ordinary Bearing Rein to Bridle.

BRIDLE.						s.	d.
2 $\frac{1}{4}$ lbs. Leather @ 2/4	...	...	...	...	...	5	3
6oz. Patent Leather @ 3/-	...	...	...	...	...	1	1 $\frac{1}{2}$
1 doz. $\frac{3}{4}$ in. Buckles @ 3/-	...	...	...	...	...	3	0
Chain Front	...	...	...	...	...	1	10
Pair Rosettes	...	...	...	...	...	2	0
Pair Ball Swivels	...	...	...	...	...	2	6
Two $\frac{3}{4}$ in. Rings	...	...	...	...	...	0	6
Pair Winker Plates	...	...	...	...	...	0	4
Nickel-silver Liverpool Bit	...	...	...	...	...	4	0

MAKING.							
Winkers, sewn 14 to inch	...	...	...	...	...	2	6
Cheeks sewn 12 to inch	...	...	...	...	...	2	6
Head, with Lay, sewn 13 to inch	...	...	...	...	...	1	0
Face Piece sewn 14 to inch	...	...	...	...	...	1	4
Noseband sewn 13 to inch	...	...	...	...	...	2	8
Front sewn 14 to inch	...	...	...	...	...	1	8
Winker Strap sewn 13 to inch	...	...	...	...	...	1	2
Bearing Rein, with grooved roundings	...	...	...	...	...	2	3

£1 15 7 $\frac{1}{2}$

(Leather 6/4 $\frac{1}{2}$, Furniture 9/10, Bit, etc., 4/4, Labour 15/1.)

COLLAR.

23in. Patent Leather Collar	...	...	...	...	12	6
-----------------------------	-----	-----	-----	-----	----	---

HAMES.

All-over Hames, with Finger Draft and Ball Dees	...	16	0
Shoulder Tugs, 1lb. Leather @ 2/4	...	2	4
Hame Straps, $\frac{1}{4}$ lb. Leather @ 2/4	...	0	7
One Pair $1\frac{1}{2}$ in. Buckles	...	2	3
Two $\frac{3}{4}$ in. Buckles	...	0	6 $\frac{1}{2}$
Making Tugs (no savers) sewn 11 to inch, and rivetting to Hames	...	4	0
Making Hame Straps	...	0	6

£1 6 2 $\frac{1}{2}$

TRACES, $1\frac{1}{2}$ in. $\times$ 5ft. 10in.

3 $\frac{1}{4}$ lbs. Leather @ 2/4	...	8	9
Making, sewn 11 to inch	...	10	3
		<u>19</u>	<u>0</u>

Estimate Sheet No. 5 (*continued.*)

SADDLE.							s.	d.
6in. Patent, Lined Flap	...	...	...	...	...	...	19	0
Pair Ball Terrets	...	...	...	...	...	...	5	0
Hook	...	...	...	...	...	...	1	6
One lin. Roller Buckle	...	...	...	...	...	...	0	6½
Girth, Short Lay and Strap, 1¼lbs. Leather @ 2/4	...	...	...	...	...	...	2	11
Patent Leather Patch Piece...	...	...	...	...	...	...	0	2
Making Girth, sewn 10	...	...	...	...	...	...	1	0
Making Strap, sewn 12 once round	...	...	...	...	...	...	1	0
Sewing on Girth and Strap	...	...	...	...	...	...	0	8
							£1 11	9½

(Leather 3/1, Saddle 19/-, Furniture 7/0½, Labour 2/8.)

BACKBAND, 1½in. × 8ft. 3in								
2¼lbs. Leather @ 2/4	...	...	...	...	...	...	5	3
One 1½in. Roller Buckle	...	...	...	...	...	...	0	9
Making, sewn 11, four rows in centre	...	...	...	...	...	...	6	0
							12	0

SHAFT TUGS.								
1lb. Leather @ 2/4	...	...	...	...	...	...	2	4
One Pair Tug Buckles	...	...	...	...	...	...	2	3
Making, sewn 9 to inch	...	...	...	...	...	...	4	0
							8	7

CRUPPER.								
1lb. Leather @ 2/4	...	...	...	...	...	...	2	4
One lin. Buckle	...	...	...	...	...	...	0	4½
Linseed Dock	...	...	...	...	...	...	1	6
Making Crupper, sewn once round 13 to inch	...	...	...	...	...	...	5	0
							9	2½

BREECHING								
1¼lbs. Leather @ 2/4	...	...	...	...	...	...	2	11
Two 1¾in. Rings	...	...	...	...	...	...	1	10
Two ¾in. Dees	...	...	...	...	...	...	0	7
Four ¾in. Buckles @ 3/3	...	...	...	...	...	...	1	1
Making body, sewn 12 to inch once round, with oval	...	...	...	...	...	...	2	8
Making four tugs sewn 10 to inch	...	...	...	...	...	...	2	2
							11	3

(Leather 2/11, Furniture 3/6, Labour 4/10.)

Estimate Sheet No. 5 (*continued.*)**SHAFT STRAPS.**

	s.	d.
$\frac{3}{4}$ lb. Leather @ 2/4	1	9
Two lin. Buckles @ 4/6	0	9
Making, sewn 12 to inch once round	3	6
	<hr/>	<hr/>
	6	0

HIP STRAP.

	s.	d.
$\frac{3}{4}$ lb. Leather @ 2/4	1	9
Making, sewn once round, 13 to inch	5	0
	<hr/>	<hr/>
	6	9

REINS, lin. $\times$ 25ft.

	s.	d.
Drafts and Billets, $1\frac{1}{2}$ lbs. Leather @ 2/4	3	6
Pair of lin. Handparts	2	2
Making	1	2
	<hr/>	<hr/>
	6	10

TOTAL.

	s.	d.
Bridle	1	15 7 $\frac{1}{2}$
Collar	0	12 6
Hames, Hame Tugs, and Hame Straps	1	6 2 $\frac{1}{2}$
Traces	0	19 0
Saddle	1	11 9 $\frac{1}{2}$
Backband	0	12 0
Shaft Tugs	0	8 7
Crupper	0	9 2 $\frac{1}{2}$
Breeching	0	11 3
Shaft Straps	0	6 0
Hip Strap	0	6 9
Reins	0	6 10
Hemp, Wax, etc.	0	3 6
	<hr/>	<hr/>
	£9	9 3

CHAMBERS' PATENT BOLT CART PAD.

Fitted and
Removed
in 5 minutes.

**H. C.
CHAMBERS**

Cart Pad
Manufacturer,

BEST IN THE MARKET.

BURES, SUFFOLK, R.S.O.

ESTIMATE SHEET No. 6.

THE SAME HARNESS AS No. 5, WITH KICKING STRAP
IN PLACE OF BREECHING. FOR TWO WHEELER.

KICKING STRAP, 1¼in. × 5ft. 3in.						s.	d.
1lb. of Leather @ 2/4	...	...	...	...	...	2	4
TUGS, 1¼in. × 14in.							
½lb. Leather @ 2/4	...	...	...	...	...	1	2
Two 1¼in. K.S. Buckles	...	...	...	...	...	1	8
Making Kicking Strap, sewn once round	13	...	...	...	...	3	4
Making Tugs, sewn 12 to inch	...	...	...	...	...	2	6
Hemp, Wax, etc.	...	...	...	...	...	0	6
						11	6
Cost of Harness No. 5	...	...	...	...	...	9	9 3
DEDUCT:—							
Breeching	...	...	...	...	...	11	3
Shaft Straps	...	...	...	...	...	6	0
Hip Strap	...	...	...	...	...	6	9
Hemp and Wax	...	...	...	...	...	0	9
						1	4 9
						8	4 6
Add Cost of Kicking Strap and Tugs	...	...	...	...	...	11	6
Cost of Kicking Strap Harness	...	...	...	...	...	£8	16 0

ESTIMATE SHEET No. 7.

THE SAME HARNESS AS No. 5, WITH LONG BREECHING
IN PLACE OF SHORT BREECHING. FOR FOUR
WHEELER.

BREECHING, 1½in. points to 1½in. centre, 11ft. 6in. long.							
Leather, 2½lbs. @ 2/4	...	...	...	...	...	5	10
KICKING STRAP, 1¼in. × 6ft. 3in.							
1lb. 2ozs. Leather @ 2/4	...	...	...	...	...	2	7½
Tugs, ½lb. Leather @ 2/4	...	...	...	...	...	1	2
Two 1¼in. Kicking Strap Buckles	...	...	...	...	...	1	8
Two Loops	...	...	...	...	...	2	0
Two 1½in. Breeching End Buckles	...	...	...	...	...	1	0
Making Long Breeching, sewn once round	13 to inch	..	...	...	...	7	1½
„ Kicking Strap, sewn once round, 13 to inch	...	...	...	...	...	3	9
„ „ Tugs, sewn 12 to inch	...	...	...	...	...	2	6
Hemp and Wax	...	...	...	...	...	0	10
Cost of Long Breeching...						£1	8 6
Cost of Harness No. 5	...	...	...	...	...	9	9 3
DEDUCT:—Ordinary Breeching, etc.						1	4 9
						8	4 6
Add Cost of Long Breeching, etc.	...	...	...	...	...	1	8 6
Cost of Harness with Long Breeching	...	...	...	...	...	£9	13 0

Cost of Harness with French Backband	£10 5 3
---	---------

Supplementary Estimates (*continued.*)

MAKING 60ft. × 3in. MACHINE BELTING (Single).

	£	s.	d.
Leather, 31lbs. @ 1/6	2	6	6
Sewing 14 joints, 4 to inch, 3 rows, @ 3d.	3	6	
Hemp and Wax	1	0	
Cutting, Preparing and Finishing Belt, 3½ hours @ 8d.	2	4	
Rivets and Washers	0	4	
	<hr/> £2 13 8 <hr/>		

MAKING 30ft. × 6in. DOUBLE LEATHER BELTING,
SEWN HELVETIA LACES.

32lbs. Leather @ 1/6	2	8	0
5 doz. ¼in. × 3ft. Helvetia Laces @ 1/7	7	11	
Sewing	7	6	
Cutting, Preparing and Finishing, 6 hours @ 8d.	..	4	0
Rivets and Washers	1	0	
	<hr/> £3 8 0 <hr/>		

To accurately gauge the cost of New Harness
or Repairs, use should be made of . . .

“THE ESTIMATE AND COST BOOK,”

published at the office of “Saddlery and Harness,”

Walsall. Price 1/= post free.

ENGRAVING AND MONOGRAM CUTTING.

At the outset of this article it may be stated that skilful penmanship is an absolutely indispensable qualification to anyone who intends acquiring a practical knowledge of the art of engraving. It is useless to start cutting letters in metal before they can be well drawn on paper.

The primary difficulty which faces the beginner, who purposes teaching himself, is the selection of tools. The writer, when starting, had no proper tools, but upon finding this out, the advice of an assistant in a London tool warehouse was solicited, and with the tools afterwards obtained by his advice, and from personal observations of different kinds of engraving, good progress was made. Dog collars, watches, and other articles were engraved in a fairly good though amateurish style, but the best results not being quite satisfactory, arrangements were made to spend a week as improver in a London engraving shop, and it was there that the proper way to do the work was learnt. A correct method and all sorts of "wrinkles" were learnt in that one week, and it was to that contact with the professional engraver that the great improvement made was due.

Metal engraving may be divided into three branches: (1) Copper (and steel) plate engraving for printing purposes, in which the letters and words have all to be cut to read backwards; (2) Ordinary engraving, such as dog collar plates, whips, watches, and other articles; and (3) Brass plate engraving, such as name plates for doors and shop fronts, and "brasses" for cart harness, etc., when not cast in. The plainer sort of work included in No. 2 only is dealt with here. Possessing, in addition to the ability to shape letters above referred to, the virtues of patience and perseverance, without which it is useless to think of success, our beginner may purchase the necessary tools. These may consist of three square and six lozenge gravers in handles, for cutting; one dry point (an ordinary seat awl serves the purpose excellently) for marking; one pair dividers, like small compasses; one lens, like the magnifying glass used by watchmakers; and one oilstone for sharpening gravers, etc. He must also procure or make himself a sand-bag, *i.e.*, a leather case just like a flat Dutch cheese, about 6in. in diameter, stuffed full of sand to lay the work upon, and a "fiddle," *i.e.*, a piece of wood about 12in. by 1in., with a piece of buff leather glued half the length (like a straight crest brush, with buff leather instead of bristles) to polish the metal after the cutting is finished. All

SIDE
VIEW.

SQUARE GRAVER.

the above-mentioned tools will cost from 7s. to 10s., and make a complete outfit for the present. Three of the lozenge gravers

must be converted into flat sculpers, and are much better to use than flat sculpers proper, which, however, may be bought instead

SIDE VIEW.

LOZENGE GRAVER.

if preferred. The conversion of a lozenge graver to a flat sculper is obtained simply by rubbing the under sharp edge down on the

FRONT VIEW.

FLAT SCULPER CONVERTED FROM GRAVER.

oilstone from about 1 in. from the point to the required width.

POINT OF FLAT SCULPER PROPER.

All of the gravers when purchased will probably be found too long and too hard. The graver is pushed by the handle, or haft, resting against the palm of the hand, and the blade held by the thumb and two first fingers of right hand, just like a pen. When in this position the point should not be more than about $\frac{1}{2}$ in. in front of finger tips, or control is weakened. To properly temper the gravers when too hard, they must be held in a gas jet until they get to a straw colour heat, then suddenly withdrawn and dipped in oil, not water. When made the proper length and temper, the gravers must be given a "belly" or the points will be continually breaking off in the metal worked upon, causing much annoyance and delay. This is done by rubbing down on the oilstone each under-side of

AS PURCHASED.

BELLY MADE AT POINT.

the graver at the point. The points and bellies must be rubbed on oilstone until perfectly smooth and bright, with a keen edge, or they will not cut clean, but leave a burr each side of the groove.

Having now all necessary tools properly prepared, let the beginner plant his sand-bag firmly on his counter, with a good light right in front of him. If the light is artificial he had better place a tissue paper shade between it and the pad. Place the article to be engraved—we will say a dog collar—on the pad, and with the dividers, or compasses, mark the spaces for words, and with the dry point, or seat awl, trace the letters required, thus:—

Now put the lens in the left eye, closing the right one. If it

cannot be kept in the eye, get a piece of old clock spring long enough to wind round the head, and attach it. Now take a flat sculper of the width of point required, in the right hand as directed above, and hold the dog collar with the fingers of the left hand, so that the words read away from you as shown below. First cut all the upright lines and parts of lines of letters from bottom to top with a clean cut all the way, or little by little—the writer has found the former method the better for soft metal, and the latter

for hard metal—then turn the collar round so that the words read toward you, and cut the lines already made clean to the bottom. Next turn the dog collar so that it reads upside down, and cut the parallel lines, or parts of lines of letters as shown below. Then turn the collar round so as to read the right way, and cut parallel lines, just made clean, to the end. This leaves only the round parts of the letters to do. These must be done very carefully in very small cuts, widening the outside edge as you go. Each separate cut is indicated below by the cross

The flat sculper is now done with, and it only remains to finish the ends of the letters with the square graver. This is easy to do, but hard to explain. Anyone who has followed the article thus far will discover the way in a minute if he will examine any sample of engraving. The best explanation that can be here given is that the ends are cut straight across with the graver held at an angle of about 45 degrees from the right-hand corner only. The accompanying drawing deals with block, or "sans seraph," letters, whether upright or slanting.

Sans
Seraph.

When it is required to cut Roman letters the fine lines are made with a lozenge graver, and the seraphs, *i.e.*, fan tails, cut from each corner as directed for the ends of block letters. In what is known as round-hand lettering, the thick lines may be made either with the flat sculper or with the square graver, and the fine lines with the lozenge graver, connecting the two with the square graver. In both round-hand and Roman lettering, make the thick lines first, then the thin lines, and then connect with the square graver. Seraphs, if any, should be done last. The cutting should be so clean as not to require any "finishing." To clean off the work, put a little dry "Brillantine" or polishing powder on the "fiddle" and rub across the plate.

With the above few hints an intelligent, observant, and energetic young man should learn how to engrave a dog collar and similar articles fairly well. He will find the work (after the first few weeks of breaking the points off the tools and running the gravers right across the plate into his left hand), very interesting, and if he can design monograms and fancy ornamental lettering and embellishments, it will become quite a fascinating pursuit. But

Roman.

it is necessary, if he means to become at all skilful, to get into touch with a professional engraver, or a good amateur, and of the latter, it may be said, there are very few. In one day he could thus learn more than by a week or a month of book-reading on the subject. The letters engraved on brass cart harness plates, scallops, etc., are done quite differently. This is rougher and more laborious. The plate is fixed to a board or in a vice, the graver is punched with a hammer, and the work done in a manner identical to that of a mason cutting a tombstone.

Albery

Round-hand.

With regard to monograms, they appear both ornamental and as indicating ownership upon well-nigh everything to-day. They are noticed upon horse rugs, carriages, whips, crops, watches, rings, books, notepaper, bicycles, brush backs, walking sticks, umbrellas, leather cases, etc., etc., and the designs for them are in endless variety. How many have been puzzled when they have had a monogram, to pick the initials of a new customer, and explain to anyone which is the first, second, third, or fourth letter. As far back as the writer can trace, the earliest monograms of modern times were the marks of old merchants put upon bales of goods, as the A.F., J.T.B., and F.A.S., as shown. From these has evolved another variety of monogram, in which, as the F.A.S. shows, the letters are, as it were, hung

A B F A S

one upon the other, an arrangement with an old-world method that is to-day very much favoured.

As in most other things, there is fashion in monograms, and not a few amateurs ingeniously exercise their skill in forming novel arrangements for their initials. The N.E.C., which is termed a running cypher, or script, as it is here arranged, is more simple than any monogram, is easier read at a glance, and looks quite as well. The designing of a really artistic monogram, however, particularly when the combination of letters is an awkward one, is possible only to the specialist, simple as the task may appear. Just at the present time the plain block "Egyptian," or Roman, style of monogram, the simplest of its kind, is the most fashionable, the letters M.C. and D.O.L. being devoid of ornamentation. They

M.C.

appear, in fact, as if just carved out of a piece or block of wood. It is really marvellous to notice the different tastes that some people have for monograms, amongst them,

some of high artistic intelligence. One, for instance, will adopt a style as severe as another's is ornate and complicated, and whilst some like huge designs, the monograms of others are of infinitesimal proportions. The handles used for this work are not round, and there is nothing at the bottom of the hand to catch against the article you are engraving.

It is difficult to engrave a medalion or coin. To try and hold it seems absurd, therefore it must be a fixture. Get a small tin box, blocked and very firm; heat the lid till it will melt a piece of engraver's wax (such as is used for brass door plates, etc.),

melt enough on the lid to hold the coin, and drop the latter on the wax when hot; then let it get cool. It will then be ready to operate upon, and will not be easily moved. Silver mounts, etc., are difficult to sketch on with pencil, especially where monograms are wanted, but this can be easily overcome by putting your finger on a piece of Russian tallow or hard fat, and smearing it over the surface, which may then be sketched upon without scratching it.

To try and put the reader into the way of sketching a monogram is a very difficult thing, as no two letters will go together in exactly the same way. Perhaps the plainest monograms, of which this is another variety, are "The Roman." It looks a very easy matter to sketch a monogram of this description, but it requires the most careful handling, as imperfections here show up more distinctly than in many of the more complicated varieties.

Embossed monograms for notepaper and cards which are raised upon the paper are, of course, struck up from dies which descend upon the paper when it is resting upon a bed of gutta-percha.

The time taken over a monogram, naturally enough, depends upon the size and the amount of labour to be put into it. Some monograms would take as long to sketch on the article as another would to engrave. The wholesale prices of engraving monograms, etc., are as follows:—Cypher monograms on mounts,

STEEL MONOGRAM DIE.

etc., 3s. 6d. each; fancy two-letter blocks, on mounts, etc., 4s. 6d.; inscriptions on small plated articles, per dozen letters, 1s.; coats of arms, 7s. 6d. and 10s. 6d. each; double lined two-letter cyphers and monograms, by the dozen, 6s. The sizes of

monograms vary so much that whilst an ornamental cypher could probably be put on to the handle of a spoon in about ten minutes, spread over the back of a watch it might take a couple of hours. Some intricate designs, of course, take days to complete. Just below you have a capital specimen of a three-letter monogram which looks well on anything. Amongst curious monograms, a notable one was seen which consisted of the entire twenty-six letters of the alphabet, a design far too complicated to be reproduced here. Five of its letters were done in gold, six in brown, six in violet, and nine in green.

Where the same monogram is to be engraved upon a number of articles—say spoons—the first one finished is taken and rubbed over with printing ink—that is, ink used for printing newspapers or placards.

Well, after you have applied the ink to the monogram with the end of your finger and rubbed it well in, and then wiped off with a piece of damp paper (ladies' curl paper is the thing), enough ink has remained in the cuts to mark the paper, and this in turn transfers an impression to the next subject.

The monograms A.M. and J.T. are in perfect "gothic" style. It must be understood that monogram work such as is done by the best engravers only—a trade which is most difficult to learn in all its branches—is treated of now.

Here, attention may be called to the fact that—as in the design beneath—letters are sometimes reversed for the sake of appearance, when the reverse letter is not to be read,

this monogram not being C.C.L., but C.L. A few years ago, great numbers of people collected monograms, just as they now do stamps, etc., and displayed them in their albums.

The writer remembers reading an article on engraving, some years ago, which stated that it takes an apprentice three years before he can properly sharpen an ordinary graver.

Besides being cut into articles, monograms cut out of gold or silver, metal-plated or gilded, are often fixed on them, these being termed "piercings," because they are pierced or cut out, and are most often done with a fret-saw (like you may have seen queen's or king's heads cut out of pennies), and afterwards carved up or ornamented by hand. Some of these are very expensive indeed, especially when ornamented with precious stones. Not everyone can correctly read even a three-letter monogram. The next one, here shown, is of course D.B.R., the D.B. being read in the ordinary way from left to right, and you know the R stands for the surname, because it is made the most important letter. Some

monograms upon harness are difficult to read, but whenever you

get a letter hatched or shaded as in the accompanying cut, you may know that it is to be understood as the initial of the surname. Where there are more letters they are grouped according to the skill of the artist, not jumbled up anyhow.

Where one letter of the three is thus made to stand out prominently, and where there is no reading from left to right, a different course is adopted. Another three-letter design is here depicted. The S is now the last letter because you see it is hatched; of the other two the O is the smaller, therefore you are informed that the reading is B.O.S. If you can think of these easy rules you will be able to make out a good many of these devices, and take more interest in any monogram of notable heads that you may meet with.

It is a fact that there are not a few people to whom a monogram, composed of more than two letters, is as unintelligible as a time-table or directory. They may, perhaps, know what the letters in themselves are, but as to the order in which they should read them they are entirely ignorant.

COPPER-PLATE ENGRAVING AND

DIE SINKING.

Inscriptions or Monograms engraved, and all classes of Copper-plate Engraving and Die Sinking undertaken by T. Kirby & Sons Limited, Walsall.

USEFUL RECIPES.

A SUITABLE CEMENT FOR JOINING THE SPLICES OF MACHINE BELTS.—Take 1lb. of best French glue, break it up and soak it in just enough water to cover for 12 hours, then pour off the unabsorbed water, and bring the glue to a liquid state by heat. The two surfaces to be joined must each receive a thin coating; they are then joined, and immediately put under a press.

CEMENT FOR JOINING LEATHER.—Soak for one day, one pound of common glue in enough water to cover, and one pound of isinglass in ale droppings, then mix together and heat gently until boiling; at this point add a little pure tannin, and keep boiling for half-an-hour. If the glue and isinglass, when mixed, be too thick, add water. This cement should be used warm, and the jointed leather pressed tightly together for 12 hours.—“Chemical Recipes.”

PASTE FOR PATENT LEATHER.—The following is a French recipe for preserving the gloss of patent leather:—Melt pure wax over a water bath, place on a moderate coal fire, add first some olive oil, then some lard, and mix intimately by stirring; next add some oil of turpentine, and finally some oil of lavender, fill the resulting paste in boxes, where, on solidifying, the necessary consistency will be acquired. To restore the gloss to the leather, apply a little of the paste, and rub with a linen rag. This will keep the leather soft and prevent cracking.

PERMANENT PASTE is made by adding to each half-pint of flour paste, without alum, 15 grains of corrosive sublimate, previously rubbed to powder in a mortar, the whole to be well mixed; this, if prevented from drying by being kept in a covered pot, remains good any length of time, and is therefore convenient; but unfortunately it is extremely poisonous, though its excessively nauseous taste would prevent it being swallowed accidentally. It possesses the great advantage of not being liable to the attacks of insects.

TO JOIN LEATHER.—By adding a little vinegar to ordinary glue, any two substances, such as leather and iron, may be effectively joined.

WATERPROOF GLUE.—10 parts linoleate of manganese, 20 parts best white glue, 5 parts water, 2 parts yellow oxide of lead. Soak the glue in the water until the latter has become absorbed, then gently heat it to render it fluid; meanwhile heat the linoleate of manganese to about 400 degrees Fah., and stir it in the hot melted glue. When well incorporated, mix in the lead oxide, and, if too thick, thin with more hot linoleate of manganese. As this compound dries very quickly, it is best to use it hot and freshly prepared, as it does not readily melt when heated, owing to the oxidizing action of the lead salt on the constituents of the linoleate, whereby insoluble linoxide is formed.—“Chemical Recipes.”

A GOOD BLACK, ESPECIALLY FOR CHAMOIS SKINS.—Four ounces of ground nut galls, one pound of green nut shell (butter nut pods) are boiled in two quarts of water for one hour, and strained. Then one ounce of iron filings, half an ounce of common salt, and one quart of vinegar are mixed, allowed to stand for an hour, and added.

A GOOD WAX FOR BRIDLE AND BROWN LEATHER WORK.—1lb. of bees wax, $\frac{1}{4}$ lb. clear resin, and $\frac{1}{4}$ lb. white lead. Heat all these together in a vessel over a slow fire, and, when thoroughly melted and well mixed, pour it into a bowl of clean water, and proceed to pull it as in making ordinary wax. The more it is pulled, the more tenacious will it be found in adhering to the threads, and cementing the work together.

A POLISH FOR BELT EDGES.—For polishing the edges of machine belts, add two tablespoonfuls of melted glue to half-a-pint of water; then add a little red ochre to colour it. Apply this to the edges whilst in a hot state, and polish with a coarse cloth.

BALL BLACK FOR LEATHER STRAPS. — $\frac{1}{4}$ oz. isinglass, $\frac{1}{4}$ oz. indigo, 4oz. logwood, 2oz. soft soap, 4oz. glue softened, and 1 pint vinegar. Well mix, warm, strain, and allow it to cool.

BLACK LEATHER LACQUERS FOR CHEAP ARTICLES.—Dissolve 12oz. black pitch in 35 fluid ounces of turpentine.

BLACK VARNISH FOR LEATHER.—Rub 2oz. lamp black in 8 fl. oz. turps, and separately digest 24oz. shellac, 10oz. ven. turps, and 4oz. Sandarac resin in 192 fl. oz. methylated spirits. When these resins have dissolved, mix the turps and lamp black mixtures, and well shake the whole.

BROWN CREAM OR PASTE FOR BROWN LEATHER.—Melt some spermaceti wax in a gallipot or earthenware vessel placed in a saucepan, when fluid, stir in some olive oil and some lard. The relative quantities of these two ingredients will determine whether the compound is to be a cream or paste, more oil being used for the former, and wax if a paste is desired. When these articles are thoroughly incorporated by stirring, add some tinc. of annatto or turmeric, according to colour desired, or a little solid Bismark brown may be used as a colouring matter—a few grains is sufficient to a pound of cream. There is one advantage and one drawback in using this aniline dye, viz: It readily siezes on leather and permanently stains it, and this prevents the leather showing a worn or shabby appearance, but it also deepens to a dark brown by frequent applications. When the colouring matter is well mixed, add some oil of turps, and finally oil of lavender as a perfume. The portions will be determined by the operator. Well stir the whole compound, and keep it simmering from 5 to 10 minutes, then ladle it out into tin boxes to congeal, if for a paste; but, if cream is desired, thin with a larger quantity of turps to the required consistency, and bottle off. To use this compo, smear a little over the leather with a sponge or linen rag, and, when well rubbed in, polish with a piece of flannel or felt.

BROWN COMPO.—20 fl. oz. good malt vinegar, 10 fl. oz. filtered water, 2oz. good glue, 1 dr. soft soap, 1 dr. isinglass, colour with annatto or turmeric. Mix the water and vinegar, and dissolve glue in the fluid by gently heating it, add colouring and the other ingredients, and boil from 10 to 15 minutes; strain the mixture, and bottle. To use this compo, lay it on with a rag or flannel.

DRESSING FOR BELTS (ADHESIVE).—5lb. tallow, 1lb. yellow wax, 2lb. common chalk, 1lb. black lead, and 1lb. resin. Dissolve these together by gentle heat. Put upon the belt when slightly warm. Be sure and keep well stirred in the kettle while applying it to the belt. Use a little at a time and frequently.

FOR RUBBING UP BROWN EDGES, make a solution of oxalic acid and add to good harness compo.

HARNESS BLACKING.—Melt 2lbs. mutton suet, 6lbs. bees' wax, when melted, stir in 6lbs. sugar candy, 2½lbs. lamp black, 2lbs. soft soap, and ½lb. indigo in powder, and when the whole has been thoroughly mixed by heating and stirring for an hour over a slow fire, add ½-gallon oil of turps.

HARNESS BLACKING POLISH.—Heat together, over a slow fire, 16oz. white wax and 24oz. turps. When the wax has dissolved, mix in 8oz. ivory black and 1oz. powdered indigo. Stir the mixture till cold. Take a little of this compound on a cloth or piece of flannel (old is best) not fluffy, and polish with a shoe brush.

HARNESS BLACKING COMPO.—1¼oz. yellow wax, ½oz. powdered indigo, ½oz. powdered extract of logwood, 1oz. powdered drop black, 7oz. spirits of turps. Melt the wax in turps over slow fire, then the other ingredients, and mix together. Keep in a vessel from which the air is excluded, and stir well before using. Apply with a sponge or soft brush, and polish with a hard brush.

HARNESS COMPO RENOVATOR.—Dissolve ½oz. isinglass, or best gelatine, and 8oz. glue in 1 quart vinegar in separate vessels. Extract the goodness from 8oz. logwood by boiling it in 1 quart vinegar, strain and dissolve in it ½oz. indigo. Mix the two compounds. Add 4oz. soft soap, and strain.

HARNESS GREASE OR SOAP.—4oz. ammonia soap, 1oz. palm oil, 3oz. ordinary hard soap (pure), and 1¾oz. of a solution of tannin, made by digesting 9 to 16oz. tannic acid in 4oz. water. Gently heat the oil and soap together until melted, using a water bath, then add the ammonia soap, and lastly the tannin solution. Well mix by constantly stirring, and put into stoneware jars. The ammonia soap is prepared by heating olive oil to the boiling point, and then stirring in sesqui-carbonate of ammonia (in powder) until the smell of ammonia that is given off remains permanent in the compound. Do not lay on more than the leather will absorb.

HARNESS MAKERS' BLACK WAX.—2lb. of Stockholm pitch, 2lb. resin, ¼-pint seal oil. In summer add more resin and less oil. Put the ingredients into an iron vessel, and melt over a slow fire. When thoroughly melted and incorporated, pour into a pail of cold water, and work the wax well until it swims, then cut into balls.

HARNESS MAKERS' JET.—8oz. gelatine, 6oz. gum arabic, 1½ pints water. Dissolve these together in an oven, then add 12oz. treacle and 10oz. ivory black. Stir occasionally, and, when cold, bottle off. Apply with a sponge. This will not resist water.

HARNESS POLISH.—4oz. glue, 1½ pints vinegar, 2oz. gum-arabic, ½-pint black ink, 2 drachms isinglass. Break the glue into small

parts, put in a basin, pour over it about 1 pint vinegar, and let it stand until soft. Put the gum in another vessel with the ink till dissolved. Melt the isinglass in as much water as will cover it. To mix them, pour the remaining vinegar, with softened glue, into a saucepan, stand on a gentle fire, stir till perfectly dissolved—see it does not burn at bottom, and not reach boiling point, about 180 degrees Fahr. Next add the gum, heat again, and add isinglass. Apply with a sponge.

INFLEXIBLE BLACK JAPAN FOR LEATHER.—Dissolve 16oz. shellac in $3\frac{1}{4}$ pints wood naphtha, and add sufficient lamp black to colour.

LEATHER DRESSING.—A fine, brilliant, elastic dressing for leather can be made as follows:—To 3lbs. of boiling water, add, with continual stirring, $\frac{1}{2}$ lb. white wax, 1oz. transparent glue, 2oz. gum senegal, $1\frac{1}{2}$ oz. white soap, and 2oz. brown candy. Finally add $2\frac{1}{2}$ oz. alcohol, and after the whole is cooled, 3oz. fine Frankfort black. The dressing is thinly applied to the leather with a soft brush; and, after it is dried, it is rubbed with a piece of fine pumice, and polished with a stiff brush.

LIQUID RENOVATOR FOR PATENT LEATHER.—Paraffin oil 48 parts, oil of lavender 1 part, essence of citronelle 1 part, spirits of ammonia 2 parts. Method of preparation:—Mix all together, and shake the bottle before using, laying on a coating with a sponge, and polishing with a soft cloth or leather afterwards.

PATENT LEATHER POLISH.—The following recipe is given by a German journal as being a good patent leather polish:—Take 60 parts whale soap and 500 parts water. Let this soak over-night. Also 60 parts glue, 500 parts water. Let this soak over-night. Boil these each separately, adding the first to the second. When thoroughly boiled add 15 parts wax, 10 parts lamp black, and boil again. Apply very sparingly to the leather.

THE CLEANSING OF MACHINE BANDS.—To cleanse a machine band, it should first be scrubbed with a brush and warm water and soap, and then, while it is still wet, a solution of ammonia should be rubbed in, which will saponify the grease in the band. Immediately after this, the band must be well rinsed in tepid water, and then stretched out to dry. Before, however, it is quite dry, smear the inner surface—and slightly also the outer surface—with the following preserving solution, viz.: 1 kilogramme of india-rubber heated to 50 degrees, mixed with the same quantity of rectified oil of turpentine. When this is completely dissolved, 780 grammes of colophonium is added, and after that 750 grammes of yellow wax. When this is well mixed, 3 kilogrammes of train oil, to which $1\frac{1}{4}$ kilogrammes of melted tallow has been added, are poured in, stirring briskly all the while. When the band is in use its inner surface only should be smeared, the outer surface not being done after the first time. By this means, the tannin squeezed out of the band is replaced, slipping is prevented, and the band remains elastic. One kilogramme equals 2lbs. $3\frac{1}{4}$ ozs.; 1oz. equals 28 grammes.

DYEING LEATHER.—The introduction of aniline dyes has brought about a simple and effective means by which articles in small quantities may be dyed without the necessity for providing the extensive plant required when the work is carried out by the old wood dye process. As harness makers frequently require a piece of leather of a particular shade, or have in hand some article which may be brought more to the taste of the purchaser if suitably coloured to his fancy, a few recipes, with instructions for preparing the leather, are given with a view to assisting the novice in bringing about the desired change of colour. The surface of the skin must first be well washed with warm water, the advantage of which is that the dye does not penetrate so quickly, and may thus be spread more evenly over the surface. A mordaunting fluid is next applied; this differs according to the colour of the dye to be used. For all light shades, the mordaunt consists of 1 part phosphate of soda dissolved in 100 parts of water. For various shades of browns, a very small quantity of tartaric acid is added to the above, the proportion being $\frac{1}{2}$ oz. of tartaric acid to 20 gallons of the mordaunt solution. For all blue and green colours, the following mordaunt is recommended:—10 gallons water, 1 lb. phosphate of soda, 1 lb. dextrine, $\frac{1}{2}$ oz. tartaric acid. It is much better to commence with weak dye solutions, when aniline colours are used. See that no cracks, scratches, cuts, musty grain, or other imperfections are on the grain side. The least scratch or blemish is sure to be more conspicuous when finished than when in previous state, and it is impossible to obtain evenness of shade when the grain is musty or bruised, because the damaged places are sure to absorb the dye more readily than where the grain is perfect. A good plan for testing the colour, is to first apply it to a piece of scrap leather, and allow it to dry. All aniline dyes dry a lighter shade than when wet. To increase the depth of colour, give two or three coatings, draining the skin well before each additional coat is given. The method of preparing the dye is simple. It is only necessary to dissolve aniline in hot water at the rate of about 240 grains (half an ounce) to 10 quarts of water. The dyes, after being dissolved, must be strained through a linen cloth. They are applied with a brush, which is dipped in flat, and the dye distributed as evenly as possible. A very nice light tan colour is prepared from Phosphine No. 1., while Phosphine No. 2 gives a somewhat darker shade, and Phosphine No. 3 a dark brown.

WATER.

Bright Straw Colour.—1 Naphthalin Yellow to	400 parts.
Golden Yellow.—1 Methanil Yellow to	... 100 ..
Violet.—1 Methyl Violet to	... 100 ..
Light Green.—1 Victoria Green to	... 200 ..
Dark Green.—1 Extra Brilliant Green to	... 100 ..
Sky Blue.—1 Water Blue D.N. to	... 200 ..
Imperial Blue.—1 Water Blue D.N. to	... 100 ..
Buff { 4 N.	} to 400 ..
1 Ersine	
Reddish Brown.—1 Seal Brown to	... 100 ..

METALLIC POLISHING POWDER.—Well dry on a plate or piece of paper 15oz. carb. magnesia, 15oz. precipitated chalk (carb. lime), and 25oz. ferric oxide (red ox. iron). Then mix all these powders together, and sift several times through fine mesh sieve. Put up in air-tight boxes.

METAL POLISHING PASTE FOR PLATED HARNESS.—2lb. precipitated chalk, 6oz. spirits turps, 3oz. spirits of wine, $1\frac{1}{2}$ oz. spirits camphor, and $\frac{3}{4}$ oz. liq. ammonia. Mix the fluids together, and then gradually stir in the chalk. The metal should be covered with this compo by means of a sponge, and, when dried, polished off with a chamois leather.

POLISHING PASTE FOR BRASS.—Mix 3oz. oxalic acid in 1 quart of hot water, then mix by stirring in 100oz. powdered pumice stone, 2oz. oil of turps, 12oz. soft soap, and 12oz. olive or rape oil.

POLISHING PASTE FOR METAL.—No. 1: 2oz. liq. cocoa-nut oil, and stir into it 2oz. Tripoli powder, 1oz. alum, 1oz. tartaric acid, and 1oz. white lead. No. 2: 4oz. cocoa-nut oil, 2oz. lye of 30 or 40° strength, 5oz. colcothar, 5oz. water, and 1oz. spirits of sal-ammoniac. Make a soap of the oil and lye, by stirring the oil with the lye. Having separately stirred up the col. red ox. of iron in the water, mix with the soap, and add spirits of sal-ammoniac.

POLISHING PASTE FOR SILVER PLATE.—Mix 3oz. turps with 8oz. water, and boil in this mixture, until dissolved, 1lb. of hard, curd soap, and then stir in 6oz. liq. ammonia.

TO REMOVE SPOTS FROM LEATHER.—To take grease out of leather, apply white of egg to the spots, and dry in the sun. Repeat till spots are gone.

TO RESTORE PATENT LEATHER.—One pint raw linseed oil, 4ozs. cider vinegar, 2oz. spirits of wine, 1oz. butter of antimony, $\frac{1}{2}$ oz. spirits of hartshorn, and $\frac{1}{2}$ oz. oil of lavender. Shake them well together and they are ready for use. Apply with soft brush, and polish with cotton pad until dry.

EMBROCATION.—Ingredients: 1 gallon white wine vinegar, $\frac{1}{2}$ gallon oil of turpentine, 20 eggs (new laid), and $\frac{1}{2}$ -pint liquid ammonia. The eggs are first broken into a large jar or dish, and well beaten with a whisk until thoroughly assimilated. Procure the best white wine vinegar, and place in a large vessel over the fire, carefully watching that it does not boil. The turpentine is put into another vessel, and heated to about 180 deg. Fahr. The eggs, having been suitably prepared, pour on to them the hot turpentine—constant stirring taking place—and, afterwards, the heated vinegar. A continued motion must be given to the mixture for at least three hours to ensure proper blending of the ingredients. Getting the right heat to the various ingredients, when the mixing takes place, and keeping up an uninterrupted movement to the admixture, will ensure perfect union of the parts, and give an emulsion free from any kind of sediment or floating liquid when bottled off, and allowed to stand for a time.

STENCIL INK.—A good ink for stencil purposes may be made by mixing the following:—4ozs. whiting, 4ozs. ground gum-arabic, 4oz. ultramarine blue, 2oz. of warm water. The cost is trifling.

JOHN POUND & CO.

Actual Makers

Specialité :—
FITTED DRESSING CASES

Specialité :—
FITTED DRESSING BAGS.

CASES

SUIT
SHIRT
HAT
COLLAR
AND
BRUSH

OVERLAND
CABIN
AND
SARATOGA

TRUNKS

WRITE FOR FULL CATALOGUE.

THE "PREMIER" BRAND OF COMPRESSED FIBRE TRUNKS.

Covered in Best Canvas, Hand-Prepared on Superior Fibre Plates.

At the TOP-OF-THE-TREE

For Appearance, Price, Lightness, and Strength.

MADE IN

DRESS,
CABIN,
OVERLAND

TRUNKS.

SUIT,
BONNET,
&c.,

CASES.

81-84 LEADENHALL ST., LONDON.

Telegrams :
"Pound, London."

Telephone :
4278 Avenue.

DAVID BIRD,

MANUFACTURER OF EVERY DESCRIPTION OF

Harness Furniture, Hames,

Brass, German and Nickel Silver Caster. &c., &c.

PATENTEE AND SOLE MANUFACTURER OF

BIRD'S PATENT "BULLDOG" CLIPS

(No. 25074) FOR RING DRAFT HAMES.

Made to Screw or Rivet. Saves time and leather, as will be seen at once on referring to sketches below.

Central Works, Shaw Street, WALSALL.

THE BEST BITS ON EARTH.

When you purchase a Bit, see that the words

‘Hawkins Never Rust’

are stamped upon it, otherwise you get an inferior article, the Trade being flooded with cheap goods stamped with misleading names, which are only imitations.

ONLY ONE QUALITY—THE BEST.

MOHAWK PATENT BITS.

Humane.

Safe.

Effective.

**Mohawk Driving and
Riding Bits.**

**The most successful Bits of the Century.
Write for Descriptive Circulars
and Prices.**

The Genuine Article requires NO SCOURING, simply wash & wipe it. Always a bright STEEL colour, which will not go yellow or corrode, and will **“NEVER RUST.”**

Supplied by Saddlers only. Specially adapted for Yeomanry Fittings.

Refuse to purchase unless our Trade Mark or Name appears on every Article.

BITS, STIRRUPS & SPURS MADE IN ALL PATTERNS.

INVENTORS AND SOLE WHOLESALE MANUFACTURERS—

HAWKINS LTD., WALSALL.

Our Complete PRICE LIST, with Illustrations of everything a Saddler requires, sent on application.

NAT. TELEPHONE NO. 108.

ESTABLISHED 1880.

London Address—F. TEW,
7a Edmund Place, Jewin Street.

C. C. WALKER & MOLD LTD.

MANUFACTURERS OF ALL KINDS OF

MALLEABLE Buckles, Riding and Driving Bits,
IRONFOUNDERS. Harness Furniture, &c., SUITABLE FOR ALL MARKETS.

DESPATCH FOUNDRY AND BUCKLE WORKS,

STAFFORD STREET, WALSALL.

No Cutting SHOW-CARDS AND
TESTIMONIALS ON
APPLICATION.

IN **Sleigh's** ?

SADDLERS
ONLY
SUPPLIED.

Embrocation

MINIMUM PRICE FIXED ALLOWING A
GOOD PROFIT TO THE RETAILER.

It will PAY YOU to handle Sleigh's Superior Embrocation, as it bears a much larger profit than other similar preparations, and is acknowledged to be the strongest and most efficacious on the market. Sales are largely increasing.

Put in 2/- and 1- Bottles.

SLEIGH & CO., MANUFACTURING
SADDLERS' IRONMONGERS, **WALSALL.**

WEBS! WEBS! WEBS!

J. WALKER & SON (Successors to J. Hill & Co.
and T. R. Cobb & Co.)

17 and 18 North Bar, BANBURY.

Manufacturers & Factors of SADDLERS' WOOLLENS, ROLLER, CIRTH,
SURCINGLE, BRACE, BELT & EVERY KIND
OF WEB, BANDAGE & SADDLE SERGE, KERSEYS, BLANKET RUGS, HORSE CLOTHING,
COLLAR CHECK, &c.

J. W. & S. are the sole makers of "COBB'S" Webs, as used
in the Royal Mews and by the principal West-End Houses,
and which have the world-wide reputation of a century.

ROLLERS, CIRTHS, BRACES,
BELTS, BANDAGES made
up on the Premises.

HANDFORD GREATREX

Telegrams—"BARK, WALSALL."

National Telephone—149.

& CO. LTD.

Oak Bark Tanners,
Curriers, Japanners, &c.

Coach, Saddle, Bridle,
and Harness Leather.

WHITTIMERE STREET,
LICHFIELD STREET,
RUSHALL STREET,

WALSALL.

SHUTT & MARSHALL,

Silver Platers & Brass Founders,

MANUFACTURERS OF **Harness Furniture** FOR HOME & EXPORT
EVERY DESCRIPTION OF

CASTERS TO THE TRADE

Customers' Patterns
kept Strictly Private.

in Brass, Nickel, Gun Metal, &c.

FREDERICK STREET WORKS, WALSALL.

T. P. LEE,

Leather Merchant & Importer

(NOTHING LIKE LEATHER),

BUSH LANE HOUSE,

CANNON ST., LONDON, E.C.

SPECIALITIES: _____

Chamois Leathers, for Stable use, &c.

Tan Sheep, for Saddle Covers, Gaiters, &c.

Strained and Unstrained White Sheep.

Buck, Doe and Fawn Skins, for Saddle
Seats, Breeches, Strappings, &c.

Buff Hides, for Accoutrements, Whip
Keepers, &c.

White and Coloured Mock Buck, Doe,
Antelope, Reindeer, and Norway Doe
Leather, &c., &c.

BUCK TALLOW (guaranteed
pure), for **Curriers' Use.**

*All Leather carefully selected absolutely
suitable for any stated purpose.*

NO CONNECTION WITH ANY OTHER
FIRM OF A SIMILAR NAME.

CUMMINGS & CO.'S

IMPROVED BROWN LEATHER

Edging Dye

*For Finishing Edges of all
kinds of Brown Leather.*

Will keep any length of time without
deteriorating. Best and only thing of
its kind ever discovered.

ONCE USED ALWAYS USED.

Supplied through Wholesale Houses.

IN TINS. **1/-** IN TINS.

Free Sample sent on application
at the Manufactories:

Southgate, & 1, 2, & 3 Bell Lane,

GLOUCESTER.

WHOLESALE ONLY.

H. DUNKLEY'S

Improved Clippers

BUYERS, PLEASE NOTE **ONLY ADDRESS**—

131 Dalston Lane, LONDON, N.E.

No connection with any other Firm trading in same Name.

OVERTON & CO.,

Saddlers' Ironmongers,

27, 28 & 28½ FREER STREET, WALSALL.

Proprietors and Publishers of

The Saddlers' Red Book

Which contains 123 pages of ELABORATE ILLUSTRATIONS.
with full Price Lists.

By far the best and most comprehensive Album of Harness, Saddlery,
Bridle Work and Stable Requisites in the market.

SPECIALITIES:—

“OCO” METAL HARNESS FURNITURE.

The hardest, brightest, and most durable metal yet discovered. Will neither rust nor tarnish. Price only a little above nickel.

REGISTERED DIAMOND PATTERN HARNESS FURNITURE

The handsomest pattern on the market, and as easy to clean as any other.

‘LADAS,’ ‘BLACK BESS,’ ‘ROYAL’ and ‘STANDARD’
CLIPPERS.

Cannot be beaten for quality or price.

JOSEPH DIXON,

Saddlers' Tools Manufacturer,

ABLEWELL WORKS, WALSALL.

THE LARGEST AND BEST TOOL MAKER
IN THE UNITED KINGDOM.

EVERY KIND OF
SADDLERS' TOOLS
ALWAYS IN STOCK.

All Tools Marked
"J. DIXON."

Insist upon having TOOLS of this Brand, which may be obtained from

ALL SADDLERS' IRONMONGERS.

Department of Veterinary Medicine
Tufts University
200 Westboro Road
North Grafton, MA 01536

Established 1624

W. & J. RICHARDSON,
CURRIERS,

Telephone
No. 728Y4

DERBY

Telegraphic Address
"HIDES" DERBY.

Speciality: HAND DRESSED UNWEIGHTED
BACKS, That stand the hard wear of
the Derbyshire Hills.