Webster 1972

NOAA TR ERL 229-POL 7

A UNITED STATES
DEPARTMENT OF
COMMERCE
PUBLICATION

NOAA Technical Report ERL 229-POL 7

U.S. DEPARTMENT OF COMMERCE
National Oceanic and Atmospheric Administration
Environmental Research Laboratories

Current Meter Observations in Massachusetts Bay

DAVID HALPERN

GC
41
.H3
1972

BOULDER, COLO.
FEBRUARY 1972

ENVIRONMENTAL RESEARCH LABORATORIES

The mission of the Environmental Research Laboratories is to study the oceans, inland waters, the lower and upper atmosphere, the space environment, and the earth, in search of the understanding needed to provide more useful services in improving man's prospects for survival as influenced by the physical environment. Laboratories contributing to these studies are:

Earth Sciences Laboratories (ESL): Geomagnetism, seismology, geodesy, and related earth sciences; earthquake processes, internal structure and accurate figure of the Earth, and distribution of the Earth's mass.

Atlantic Oceanographic and Meteorological Laboratories (AOML): Oceanography, with emphasis on the geology and geophysics of ocean basins, oceanic processes, sea-air interactions, hurricane research, and weather modification (Miami, Florida).

Pacific Oceanographic Laboratories (POL): Oceanography; geology and geophysics of the Pacific Basin and margins; oceanic processes and dynamics; tsunami generation, propagation, modification, detection, and monitoring (Seattle, Washington).

Atmospheric Physics and Chemistry Laboratory (APCL): Cloud physics and precipitation; chemical composition and nucleating substances in the lower atmosphere; and laboratory and field experiments toward developing feasible methods of weather modification.

Air Resources Laboratories (ARL): Diffusion, transport, and dissipation of atmospheric contaminants; development of methods for prediction and control of atmospheric pollution (Silver Spring, Maryland).

Geophysical Fluid Dynamics Laboratory (GFDL): Dynamics and physics of geophysical fluid systems; development of a theoretical basis, through mathematical modeling and computer simulation, for the behavior and properties of the atmosphere and the oceans (Princeton, New Jersey).

Research Flight Facility (RFF): Outfits and operates aircraft specially instrumented for research; and meets needs of NOAA and other groups for environmental measurements for aircraft (Miami, Florida).

National Severe Storms Laboratory (NSSL): Tornadoes, squall lines, thunderstorms, and other severe local convective phenomena toward achieving improved methods of forecasting, detecting, and providing advance warnings (Norman, Oklahoma).

Space Environment Laboratory (SEL): Conducts research in solar-terrestrial physics, provides services and technique development in areas of environmental monitoring, forecasting, and data archiving.

Aeronomy Laboratory (AL): Theoretical, laboratory, rocket, and satellite studies of the physical and chemical processes controlling the ionosphere and exosphere of the earth and other planets.

Wave Propagation Laboratory (WPL): Development of new methods for remote sensing of the geophysical environment; special emphasis on propagation of sound waves, and electromagnetic waves at millimeter, infrared, and optical frequencies.

Marine Minerals Technology Center (MMTC): Research into aspects of undersea mining of hard minerals; development of tools and techniques to characterize and monitor the marine mine environment; prediction of the possible effects of marine mining on the environment; development of fundamental mining technology (Tiburon, California).

NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

BOULDER, COLORADO 80302

U.S. DEPARTMENT OF COMMERCE

Peter G. Peterson, Secretary

NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

Robert M. White, Administrator

ENVIRONMENTAL RESEARCH LABORATORIES

Wilmot N. Hess, Director

NOAA TECHNICAL REPORT ERL 229-POL 7

Current Meter Observations in Massachusetts Bay

DAVID HALPERN

BOULDER, COLO.
February 1972

For sale by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402
Price 40 cents

TABLE OF CONTENTS

	PAGE
ABSTRACT	1
1. INTRODUCTION	1
2. DATA REDUCTION	4
3. DATA PRESENTATION	5
3.1 Histogram	5
3.2 Statistics	5
3.3 East and North vs. Time	6
3.4 Progressive Vector Diagram	7
3.5 East and North Periodograms	7
4. CONCLUSION	8
5. ACKNOWLEDGEMENTS	8
6. REFERENCES	9
7. DATA SUMMARIES	
Station T 10.6 meters	10
Station T 25.8 meters	13
Station T 45.6 meters	16
Station E 7.6 meters	19
Station E 15.2 meters	22
Station E 22.8 meters	25
Station A 10.6 meters	28
Station A 25.8 meters	31
Station A 45.6 meters	34

CURRENT METER OBSERVATIONS IN MASSACHUSETTS BAY

David Halpern

Summaries of current meter measurements recorded in Massachusetts Bay during the summer of 1967 are presented in computer-generated output as histograms, basic statistics, periodograms, progressive vector diagrams and east-north component plots.

1. INTRODUCTION

During the summer of 1967 a surface float, with 3 current meters suspended beneath it, was moored at 3 different locations in Massachusetts Bay (Figure 1). The measurement periods, the instrument depths, the water depths and the mooring line scopes at each site are given in Table 1.

The surface float consisted of a toroid and a tripod tower with 2 platforms. Since the total weight of the mooring cable was insufficient to stabilize the buoy, which had a net buoyancy of 2600 kg, nine 22-kg weights were attached to the bottom of the toroid. The surface float was moored with a single 7.93-mm galvanized aircraft cable. Each current meter (Geodyne Model 102 film recording current meter (Richardson et al., 1963)) was free to swivel about the mooring line axis.

Each instrument measured a 50-second average of speed and direction each minute. The time series of the 50-second averaged speed values obtained from the instruments positioned at Station T and all the speed

Figure 1. Location of stations T, E and A in Massachusetts Bay.
Dotted lines are 20-fathom bottom contours.

Table 1. Description of the current meter measurements. The time origins of all the data were destroyed by film exposure. Depths in meters.

Date	Location	Station	Water depth	Scope	Current meter number	meter depth
July	42°16.5'N	T	82	1.05	H879	10.6
13-17	70°24.9'W				H880	25.8
					H881	45.6
July	42°16.2'N	E	29	1.07	H880	7.6
24-28	70°16.6'W				H879	15.2
					H881	22.8
August	42°16.6'N	A	61	1.05	H881	10.6
22-25	70°08.5'W				H880	25.8
					H879	45.6

and direction histograms have been given elsewhere (Halpern, 1969). We have included the histograms in this report for "completeness" of the data summary.

2. DATA REDUCTION

Speed was determined over a 50-second interval by counting the number of switch closures produced by 16 small magnets mounted on the Savonius rotor. The next measurement occurred 10 seconds later. The time series of speed was edited for zero values and for erroneously high values; approximately 1% of the series was replaced by linearly interpolated values.

During the 50-second sampling period the current direction was measured by the simultaneous recording of 20 instrument-vane orientations, which give the direction of the current relative to the instrument, and 20 magnetic compass readings, which give the orientation of the instrument relative to magnetic north. The current direction associated with the 50-second averaged speed was equal to the difference between the vector average of each set of 20 measurements. Current direction is defined as the direction in which the water is flowing.

The basic data consists of two time series, one of 50-second averages of speeds and one of 50-second averages of directions. Directions are referred to true north.

3. DATA PRESENTATION

There is a two-page data summary of the measurements obtained from each current meter. The location and depth of the instrument, the number of observations and the observation period are given on the first page. Some of this information has been repeated on each of the four plots found on the second page to aid the researcher interested in comparing the same type of plot from different instruments.

3.1 Histogram

The basic data was plotted as histograms of speed and of direction. The speeds were sorted into groups of 1.5 cm/sec and the directions were arranged in 6° sets. The speeds seen on the histograms are higher than those occurring in the other plots due to the presence of high-frequency phenomena such as internal waves (Halpern, 1971a) and mooring motion and because the Savonius rotor is an omnidirectional sensor. Direction histograms were plotted on a linear scale to eliminate the distortion inherent in a polar plot. Zero degrees refers to true north.

3.2 Statistics

The basic data consists of N observations of speed and direction, i.e., (S_i, θ_i) , $i = 1, 2, 3, \dots, N$. We define the north (+v) - south (-v) and east (+u) - west (-u) components of horizontal velocity by $u_i = S_i \cdot \sin \theta_i$ and $v_i = S_i \cdot \cos \theta_i$.

The following statistics were computed for S_i , u_i , and v_i . (Here the dummy variable x_i is used.)

$$\text{Mean, } \bar{x} = \frac{1}{N} \sum_{i=1}^N x_i$$

$$\text{Variance, } \sigma^2 = \frac{1}{N} \sum_{i=1}^N (x_i - \bar{x})^2$$

$$\text{Standard deviation, } \sigma = \sqrt{\sigma^2}$$

$$\text{Skewness} = \frac{\frac{1}{N} \sum_{i=1}^N x_i^3 - \frac{3}{N} \bar{x} \sum_{i=1}^N x_i^2 + 2\bar{x}^3}{\sigma^3}$$

$$\text{Kurtosis} = \frac{\frac{1}{N} \sum_{i=1}^N x_i^4 - \frac{4}{N} \bar{x} \sum_{i=1}^N x_i^3 + \frac{6}{N} \bar{x}^2 \sum_{i=1}^N x_i^2 - 3\bar{x}^4}{\sigma^4}$$

3.3 East and North vs. Time

These diagrams, which accentuate inertial and tidal period oscillations, were generated from the u_i and v_i series by computing the arithmetic mean of non-overlapping groups of 60 points, e.g., $U_1 = \frac{1}{60} \sum_{i=1}^{60} u_i$, $U_2 = \frac{1}{60} \sum_{i=61}^{120} u_i$ and similarly for V . The U_m and V_m data sets were the 1-hour vector averaged east and north component series.

3.4 Progressive Vector Diagram

The 1-hour averaged east (X) and north (Y) displacements (in kilometers) were given by $X_m = U_m \cdot 36 \cdot 10^{-3}$ and $Y_m = V_m \cdot 36 \cdot 10^{-3}$. The progressive vector diagram (Sverdrup et al., 1942), which represents the path taken by a water particle if it is assumed that the observed motion is characteristic of a considerably extended water mass, was generated by successive additions of the end points of the position vectors (X_m, Y_m) . The progressive vector diagram, which accentuates very low frequency events (e.g., mean flow), is not the horizontal projection of a water particle trajectory with time. The spatial scale of the diagram corresponds to the displacement which would occur if the motion over the entire area (i.e., the extent of the displacement diagram) were the same as that observed at the location of the current meter.

The plot begins with an asterisk surrounded by a circle. Every twelfth hour is marked on the curve by an asterisk.

3.5 East and North Periodograms

By use of a fast Fourier transform algorithm, raw periodograms (Bingham et al., 1967), defined so that the integral over positive frequencies is equal to twice the total variance, were computed for the 1-hour vector averaged U_m and V_m series. (We note that generally a periodogram ordinate is not a consistent spectral estimate of a random process.) The data length (90 hours) was too short to form spectral estimates.

4. CONCLUSION

It is important to note that (1) the data presentation given in this report is biased towards a description of phenomena associated with periods greater than about 6 hours, (2) during the summer months the circulation in Massachusetts Bay contains both external and internal tidal motions (Halpern, 1971b), and (3) 7-minute period fluctuations having 50-second averaged speeds of about 50 cm/sec have been measured in Massachusetts Bay.

An analysis of this current meter data will be discussed in a later paper.

5. ACKNOWLEDGEMENTS

I thank Norman Brenner (Massachusetts Institute of Technology) for the subroutine to compute the fast Fourier transform and Linda Olund (University of Washington) for preparing the CURRENT PLOT computer program. Assistance by Pat Laird (Pacific Oceanographic Laboratory) and Kurt Schneblee (National Ocean Survey) is gratefully acknowledged.

The current meter measurements were one segment of an experimental program conducted in the Department of Meteorology, Massachusetts Institute of Technology and supported by the Office of Naval Research under contract Nonr 1841 (74). This report was prepared at the Pacific Oceanographic Laboratory.

6. REFERENCES

- Bingham, C., M. D. Godfrey, and J. W. Tukey, Modern Techniques of Power Spectrum Estimation, IEEE Trans. Audio Electroacoustics, AU-15, 56-66.
- Halpern, D., Observations of short-period internal waves in Massachusetts Bay, Ph.D thesis, Department of Meteorology, Massachusetts Institute of Technology, Cambridge, Massachusetts, 1969.
- Halpern, D., Observations on short-period internal waves in Massachusetts Bay, J. Mar. Res., 29, 116-132, 1971a.
- Halpern, D., Semidiurnal internal tides in Massachusetts Bay, J. Geophy. Res., 76, 6573-6584, 1971b.
- Richardson, W. S., P. B. Stimson, and C. H. Wilkins, Current measurements from moored buoys, Deep-Sea Res., 10, 369-388, 1963.
- Sverdrup, H. U., M. W. Johnson, and R. H. Fleming, The Oceans, Prentice-Hall, Englewood Cliffs, N. J., 1942.

Location: Station T

Depth: 10.6 meters

STATISTICS OF CURRENTS LAT. 42 16.6N LONG. 70 24.9W
 DEPTH 10.6 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 13/VII/67 TO 17/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	29.32	62.96	7.94	.228	4.64	71.51	4.63
U	7.54	276.26	16.62	-.437	2.65	46.96	-55.04
V	2.98	580.63	24.10	-.317	1.85	48.64	-71.12

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station T
Depth: 25.8 meters

STATISTICS OF CURRENTS LAT. 42 16.6N LONG. 70 24.9W
 DEPTH 25.8 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 13/VII/67 TO 17/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	15.34	16.66	4.08	2.521	13.87	60.70	6.17
U	1.69	149.88	12.24	-.086	1.76	40.12	-31.49
V	-4.97	74.53	8.63	.139	3.43	28.29	-60.70

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

NORTH-SOUTH COMPONENT OF CURRENT VELOCITY
LAT. 42 16.6N LONG. 70 24.9W DEPTH 25.8 M
HOURLY AVERAGES 13/VII/67 TO 17/VII/67

PROGRESSIVE VECTOR DIAGRAM
HOURLY AVERAGES OF CURRENTS
LAT. 42 16.6N LONG. 70 24.9W DEPTH 25.8 M
OBSERVATION PERIOD 13/VII/67 TO 17/VII/67

EAST-WEST COMPONENT OF CURRENT VELOCITY
LAT. 42 16.6N LONG. 70 24.9W DEPTH 25.8 M
HOURLY AVERAGES 13/VII/67 TO 17/VII/67

PERIODOGRAMS OF HOURLY AVERAGES OF
U AND V COMPONENTS OF CURRENT VELOCITY
LAT. 42 16.6N LONG. 70 24.9W DEPTH 25.8 M
OBSERVATION PERIOD 13/VII/67 TO 17/VII/67

Location: Station T

Depth: 45.6 meters

STATISTICS OF CURRENTS LAT. 42 16.5N LONG. 70 24.9W
 DEPTH 45.6 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 13/VII/67 TO 17/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	13.50	20.48	4.53	1.551	6.47	45.79	1.03
U	1.47	126.80	11.26	-.041	1.99	37.24	-34.47
V	-2.08	69.56	8.34	-.718	3.99	42.74	-31.65

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station E
Depth: 7.6 meters

STATISTICS OF CURRENTS LAT. 42 16.2N LONG. 70 16.6W
 DEPTH 7.6 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 24/VII/67 TO 28/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	42.59	132.74	11.52	-.214	2.96	73.56	7.72
U	12.65	1243.33	35.26	-.362	1.72	70.97	-65.21
V	15.69	297.61	17.25	-.815	3.86	53.84	-47.84

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY, EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY, NORTH = POSITIVE V

Location: Station E
Depth: 15.2 meters

STATISTICS OF CURRENTS LAT. 42 16.2N LONG. 70 16.6W
 DEPTH 15.2 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 24/VII/67 TO 28/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	36.05	178.69	13.37	.050	2.62	84.88	7.20
U	1.61	976.78	31.25	-.087	1.87	72.87	-54.01
V	13.80	308.88	17.58	-.249	3.70	84.25	-48.40

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station E

Depth: 22.8 meters

STATISTICS OF CURRENTS LAT. 42 16.2N LONG. 70 16.6W
 DEPTH 22.8 METERS NUMBER OF OBSERVATIONS = 5500
 OBSERVATION PERIOD 24/VII/67 TO 28/VII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEN	KURT	MAX CM/SEC	MIN CM/SEC
S	36.49	288.63	16.99	-.262	2.30	81.28	2.57
U	-.61	1369.87	37.01	-.187	1.86	78.92	-78.70
V	3.89	234.69	15.32	.319	4.03	60.18	-55.00

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station A
Depth: 10.6 meters

STATISTICS OF CURRENTS LAT. 42 16.5N LONG. 70 08.5W
 DEPTH 10.6 METERS NUMBER OF OBSERVATIONS = 4400
 OBSERVATION PERIOD 22/VIII/67 TO 25/VIII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	29.01	145.63	12.07	.426	2.87	87.45	6.69
U	1.27	578.06	24.04	-.498	2.26	56.87	-72.27
V	4.30	389.33	19.73	-.372	2.51	65.35	-62.91

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station A
Depth: 25.8 meters

STATISTICS OF CURRENTS LAT. 42 16.5N LONG. 70 08.5W
 DEPTH 25.8 METERS NUMBER OF OBSERVATIONS = 4450
 OBSERVATION PERIOD 22/VIII/67 TO 25/VIII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	21.50	73.91	8.60	.361	2.20	47.84	5.66
U	2.53	287.49	16.96	-.034	1.76	44.65	-33.95
V	-8.30	173.35	13.17	.020	2.45	37.67	-40.93

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY. EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY. NORTH = POSITIVE V

Location: Station A
Depth: 45.6 meters

STATISTICS OF CURRENTS LAT. 42 16.5N LONG. 70 08.5W
 DEPTH 45.6 METERS NUMBER OF OBSERVATIONS = 4450
 OBSERVATION PERIOD 22/VIII/67 TO 25/VIII/67

	MEAN CM/SEC	VARIANCE (CM/SEC) ²	ST-DEV CM/SEC	SKEW	KURT	MAX CM/SEC	MIN CM/SEC
S	17.84	83.51	9.14	1.233	7.24	102.37	3.09
U	3.67	329.12	18.14	.209	2.05	73.28	-66.62
V	-2.21	54.24	7.37	.509	15.70	100.49	-42.70

S = SPEED

U = EAST-WEST COMPONENT OF VELOCITY, EAST = POSITIVE U

V = NORTH-SOUTH COMPONENT OF VELOCITY, NORTH = POSITIVE V

achusetts

oratories

RETURNED
SEP 10 1986

DEMCO